MONTANA WIND ENERGY ATLAS

1987 Edition

Prepared by GeoResearch, Inc. Billings, MT

Energy Division
DEPARTMENT OF NATURAL RESOURCES AND CONSERVATION
Capitol Station
Helena, MT 59620
406-444-6697

Abstract

The Montana Wind Energy Atlas, developed by GeoResearch, Inc., under contract with the Montana Department of Natural Resources and Conservation, is a comprehensive analysis of wind energy data, designed for use by individuals and organizations interested in wind energy development in the state. Data collected by a variety of public and private organizations at 158 wind monitoring sites around Montana were reviewed. Data from 56 sites are anlayzed in the Atlas. Information on the sites and the data collection programs is included.

Table of Contents

| I. | INTRODUCTION | 1 |
|------|--|----|
| II. | WIND MONITORING PROGRAMS IN MONTANA | 3 |
| | NWS/FAA/USAF Montana Air Quality Bureau | 16 |
| | U.S. Environmental Protection Agency | |
| | Bureau of Reclamation, U.S. Department of Interior | |
| | Montana Department of Natural Resources and Conservation | |
| | U.S. Department of Energy | |
| | Bonneville Power Administration | |
| | Western Area Power Administration | |
| | Conclusions | |
| III. | WIND ENERGY POTENTIAL | 10 |
| 111. | | |
| | Western Valley Floors | |
| | Eastern Slopes | |
| | East and Northeast Plains | |
| | Exposed Modificani Crests | 20 |
| IV. | SITE-BY-SITE WIND ANALYSES | 25 |
| | Beaverhead County | |
| | Dillon FAA Airport | 30 |
| | Big Horn County | |
| | Decker Coal #8 | 32 |
| | Spring Creek #1 | |
| | Westmoreland Absaloka #2 | 36 |
| | Blaine County | |
| | Hays | 38 |
| | Broadwater County | |
| | Three Forks | 48 |
| | Cascade County | |
| | Great Falls Malmstrom AFB | 50 |
| | Great Falls NWS Airport | 52 |
| | Salem | |
| | Chouteau County | |
| | Highwood Bench | 66 |
| | Custer County | |
| | Miles City FAA Airport | 68 |

| Daniels County 5cobey Border 70 Scobey Hanrahan 72 |
|--|
| Dawson County Glendive Microwave |
| Deer Lodge County Anaconda C-Hill |
| Fergus County Lewistown FAA Airport110 |
| Flathead County Big Prairie |
| Gallatin County Bozeman FAA Airport12 |
| Glacier County 120 Blackfoot 120 Cut Bank 130 Cut Bank FAA Airport 140 |
| Granite County Drummond FAA Airport |
| Hill County Havre NWS Airport |
| Jefferson County Microwave Tower 166 Whitehall FAA Airport 167 |
| Lake County Ronan Ninepipes |
| Lewis and Clark County Helena NWS Airport |
| Liberty County Whitlash |
| Madison County Norris Hill |
| Mineral County Superior NWS Airport19 |
| Missoula County Missoula Hoerner-Waldorf #1 |
| Park County Livingston Candidate Wind Turbine Site |
| Pondera County Heart Butte |

| | Powder River County Broadus Randall Ranch |
|----|---|
| | Rosebud County 238 Colstrip BN 238 Western Energy #12 248 |
| | Silver Bow County Butte FAA Airport |
| | Teton County Choteau |
| | Valley County 256 Fort Peck 256 Glasgow Air Force Base 258 Glasgow NWS Airport 260 |
| | Wheatland County Judith Gap |
| | Yellowstone County 280 Billings NWS Airport 290 Custer FAA Airport 290 Laurel New Farm 292 Shawnee Park 294 |
| V. | POWER LAW ANALYSES |
| | Power Law Analyses in General |
| | APPENDIX A. WIND MEASUREMENT IN GENERAL |
| | Wind Measurement Devices 305 Site Location 305 Instrument Calibration 306 Instrument Maintenance 306 Data Screening 306 Data Interpretation 307 |
| | APPENDIX B. METHODOLOGY |
| | Data Collection 309 Data Analyses 310 Site Selection 312 |
| | APPENDIX C. ADDITIONAL WIND MONITORING SITES |
| | Montana Air Quality Bureau313NWS/FAA/USAF313Department of Natural Resources and Conservation315Old West Regional Commission317U.S. Department of Interior, Bureau of Reclamation317Western Area Power Administration318Electric Power Research Institute325Bonneville Power Administration325U.S. Forest Service326 |
| | APPENDIX D. BIBLIOGRAPHY |

List of Tables

| II - 1 | Wind Monitoring Site Locations | 5 |
|--------|---|-----|
| II - 2 | Monitoring Agency and Duration | 10 |
| IV - 1 | Sites Analyzed for the Montana Wind Energy Atlas | |
| | Annual Average Wind Speed and Wind Power | 25 |
| IV - 2 | Sites Analyzed for the Montana Wind Energy Atlas | |
| | Wind Energy Potential Ranking by Wind Speed | 27 |
| V - 1 | Power Law Exponents, Montana Power Company Salem Site | |
| V - 2 | Power Law Exponents, Montana Power Company Salem Site | |
| V - 3 | Power Law Exponents, Livingston Candidate Wind Turbine Site | |
| V - 4 | Power Law Exponents, Livingston Candidate Wind Turbine Site | 301 |
| V - 5 | Actual vs Calculated Wind Speeds, | |
| | Montana Power Company Salem Site - 30 meters | 302 |
| V - 6 | Actual vs Calculated Wind Speeds, | |
| | Montana Power Company Salem Site - 100 meters | 302 |
| V - 7 | Actual vs Calculated Wind Speeds, | |
| | Livingston Candidate Wind Turbine Site - 30 meters | 303 |
| V - 8 | Actual vs Calculated Wind Speeds, | |
| | Livingston Candidate Wind Turbine Site - 45.7 meters | 303 |
| V - 9 | Accuracy of Power Law Exponents, | |
| | Montana Power Company Salem Site | 304 |
| V - 10 | Accuracy of Power Law Exponents, | |
| | Livingston Candidate Wind Turbine Site | 304 |
| A - 1 | Types of Wind Sensors and Their Operational Principles | |
| B - 1 | Sites Analyzed for the Montana Wind Energy Atlas, | |
| | Average Station Pressure (millibars) | 311 |
| B - 2 | Sites Analyzed for the Montana Wind Energy Atlas, | |
| | Monthly and Annual Average Temperature (degrees Kelvin) | 311 |
| C - 1 | Additional Montana Air Quality Bureau Wind Monitoring Sites | 313 |
| C - 2 | Additional NWS/FAA/USAF Monitoring Periods and Sites | |
| C - 3 | DNRC Wind Energy Survey, Livingston to Springdale | |
| C - 4 | Western Area Power Administration Wind Monitoring Sites | |
| C - 5 | Oregon State University, Wind Prospecting Fly Over | |
| C - 6 | Bonneville Power Administration Wind-Run Monitoring Sites, Average Velocity | |
| C - 7 | U.S. Forest Service, Fire Weather Data Sites | |
| C - 8 | U.S. Forest Service, Fire Weather Data Summaries | 329 |

NOTE: Tables and figures for individual sites are in the relevant site-by-site wind analysis, as listed in Table of Contents.

List of Maps

| II - 1 | Wind Monitoring Site Locations, | |
|---------|---|----|
| | Showing Monitoring Agencies and Durations | 4 |
| III - 1 | Generalized Annual Average Wind Speed Isopleths | |
| | Generalized Annual Average Wind Power Isopleths | 23 |

Acknowledgments

The original report was prepared by the staff of GeoResearch, Inc., Billings, directed by Michael Machler, under contract to the Department of Natural Resources and Conservation as part of the Sustainable Energy Assessment (SEA) Project. Paul Cartwright was project manager, and with Bill Phippen, edited the report. Dan Nelson did the layout; Rose-Ann Montgomery and Margie Peterson handled word processing. The update was prepared by Paul Cartwright, with additional data analysis by GeoResearch, Inc.

Introduction

The Montana Wind Energy Atlas is a comprehensive analysis of wind energy data designed for use by individuals and organizations involved in wind energy development. It contains wind data that are representative of selected geographical areas across the state. This atlas represents the first time that Montana wind energy data held by numerous public and private entities have been collected, evaluated, and made available in a single volume. The Atlas should be a valuable reference for developers and engineers concerned with siting and construction of commercial-scale wind farms, as well as for individuals interested in smaller-scale installations.

The Department of Natural Resources and Conservation contracted with GeoResearch, Inc., of Billings to develop the Atlas. The first phase of its development involved a thorough survey of public and private agencies to determine the amount of Montana wind data available. Through this survey, GeoResearch established an extensive meteorological data base for the state; this base included wind speed, wind direction, and atmospheric stability data in hard copy or machinereadable form. The sets within the data base then were evaluated on the basis of length of record, similarity of data collection methods, adequacy of the data, and area for which the data are representative. With the aid of detailed computer programs, the usable data were subsequently analyzed and reduced to summary form for publication. This Atlas provides a wind energy profile for selected locations representative of the different geographical areas of the state. It does not summarize all historical data from all Montana wind monitoring sites.

The Montana Wind Energy Atlas is organized as follows:

• Chapter I: Introduction

Chapter II: Wind Monitoring Programs in

Montana

• Chapter III: Wind Energy Potential

• Chapter IV: Site-by-Site Wind Analyses

• Chapter V: Power Law Analyses

Chapter II is a discussion of wind energy measurement programs conducted in Montana. The information available from these programs is evaluated in terms of how well it represents a region, its overall quality, and the inter-site comparability of collection methods. A list of the more important monitoring sites is included, along with a map showing site locations, monitoring agencies, and durations of data collection.

Chapter III summarizes wind data analyses from a statewide perspective. Sites are ranked by wind energy potential. Detailed tables and generalized isopleth maps display average annual wind speed and average annual wind power.

Chapter IV presents a detailed site-by-site description and analysis of all sites included in the Atlas. For each site, the data collected are evaluated for the period of data coverage, the method of collection, and the quality of the data. Summaries of monthly and annual average wind speed and wind power density are presented.

For purposes of this Atlas, sites where the average annual wind speed is equal to or greater than 11 miles per hour are considered "high potential" sites. In the description of such sites, these additional data summaries are provided:

- Diurnal wind speed frequency distribution by season;
- Directional frequency and average speed (wind rose);
- Coefficients of the Weibull distribution.

Detailed descriptions of site characteristics also are presented for the high potential sites. These descriptions include information on current use of the site, availability of space for further development, ease of access, and proximity of the site to transmission lines, sensitive communications equipment, and aircraft corridors.

Additional data analyses for two sites — the Livingston Candidate Wind Turbine site and the

Montana Power Company Salem site — where wind speed data gathered at more than one height above ground level were available, are presented in Chapter V. Variations in wind speed with height were analyzed for these sites.

Four appendices are included in this Atlas. Appendix A describes wind measurement procedures in general. Appendix B describes the methods used to gather and analyze the data. Appendix C briefly discusses sites for which data analyses are not

presented. Appendix D is a bibliography listing wind energy resource information for Montana.

The Atlas was updated in 1987. It originally contained data available to DNRC as of the beginning of 1983. The updated version has information on nine additional sites, and larger term data on eleven sites in the first edition of the Atlas. Many of these sites are high potential sites. DNRC hopes to continue to update and expand the Atlas in the future.

WIND MONITORING PROGRAMS IN MONTANA

Most wind monitoring in Montana has been conducted by the following agencies:

- National Weather Service (NWS);
- Federal Aviation Administration (FAA);
- U.S. Air Force (USAF);
- Air Quality Bureau, Montana Department of Health and Environmental Sciences (AQB);
- U.S. Environmental Protection Agency (EPA);
- Bureau of Reclamation, U.S. Department of the Interior (BOR);
- Montana Department of Natural Resources and Conservation (DNRC);
- U.S. Department of Energy (DOE):
- Bonneville Power Administration (BPA)
- Western Area Power Administration (WAPA)
- Private companies.

These monitoring programs were established for various reasons: to provide wind information for aviation, agriculture, and general public use (NWS, USAF, FAA); to study the dispersion of air pollutants (AQB, EPA, private companies); and to investigate potential wind power applications (DNRC, Bureau of Reclamation, DOE, BPA, WAPA, private companies).

Because of the different objectives of these monitoring efforts, the data have been collected by different means and organized into different formats (see Appendix A for a discussion of wind measurement in general). The periods of monitoring, averaging times, and representativeness of the data vary among the different monitoring programs. Information on various Montana wind monitoring site locations, monitoring agencies, and monitoring duration are presented on Map II-1 and Tables II-1 and II-2. The site numbers on the map are referenced in the tables. The 1987 additions may be found at the end of the tables.

Other groups, such as the U.S. Forest Service, also have conducted some monitoring in Montana. Some of these programs are discussed in Appendix C.

NWS/FAA/USAF

The National Weather Service is charged with providing weather-related services to aviation, agriculture, and the general public. To accomplish these tasks, the NWS, among other things, gathers meteorological data at several airports in Montana. The Federal Aviation Administration, to meet its responsibility to aviation, also collects meteorological data at many airports around the state. The United States Air Force has gathered similar data at Malmstrom Air Force Base and Glasgow Air Force Base. Over time, these agencies have assembled a large meteorological data base.

Data are taken hourly at NWS, FAA, and USAF airport stations. The meteorological parameters recorded include sky condition, visibility, barometric pressure, temperature, dewpoint, wind direction, wind speed, peak wind gust, and other significant data. The data are recorded approximately 10 minutes before each hour and are intended to represent a one-minute averaging period. Wind direction is read to the nearest 10 degrees, and wind speed is read to the nearest whole knot.

The advantages of the NWS, FAA, and USAF data are:

- They are available from a number of stations;
- The stations are distributed over a large geographic area;
- The data records typically are of many years' duration;
- The quality assurance program followed by the NWS, FAA, and USAF is good, so data accuracy is high;
- The data are readily available, both in hard copy and in machine-readable form.




Table II-1. Wind Monitoring Site Locations

| Site No. | Site Name | County | Location |
|-------------|--|-------------------------------|--|
| 1 | Dillon FAA Airport Dillon FAA Airport | Beaverhead Beaverhead | 45 15 00N 112 33 00W 45 15 00N 112 33 00W |
| 2 | Decker Coal #8 | Big Horn | 45 03 19N 106 48 17W |
| 3 | Hardin | Big Horn | 45 46 00N 107 49 00W |
| 4 | Hardin MDN | Big Horn | 45 30 00N 107 30 00W |
| 5 | Spring Creek #1 | Big Horn | 45 07 02N 106 52 32W |
| 6 | Westmoreland Absaloka #2 | Big Horn | 45 46 27N 107 04 57W |
| 7 | Yellowtail Dam | Big Horn | 45 19 06N 107 57 45W |
| 8 | Youngs Creek | Big Horn | 45 02 00N 107 01 00W |
| 9 | Hays Forestry Shop | Blaine | 45 55 44N 108 41 42W |
| 10 | Three Forks | Broadwater | 45 59 20N 111 35 32W |
| 11 | Ekalaka | Carter | 45 57 37N 104 25 18W |
| 12 | Great Falls City Sewage Pump | Cascade | 47 30 00N 111 15 00W |
| 13 | Great Falls Kiwanis Park | Cascade | 47 30 35N 111 16 32W |
| 14 | Great Falls Malmstrom Air Force Base Great Falls Malmstrom Air Force Base Great Falls Malmstrom Air Force Base | Cascade Cascade Cascade | 47 31 12N 111 10 12W 47 31 12N 111 10 12W 47 31 12N 111 10 12W |
| 15 | Great Falls NWS Airport Great Falls NWS Airport Great Falls NWS Airport | Cascade Cascade Cascade | 47 28 48N 111 22 12W 47 28 48N 111 22 12W 47 28 48N 111 22 12W |
| 16 | Portage | Cascade | 47 35 00N 111 05 00W |
| 17 | Salem | Cascade | 47 34 22N 111 02 34W |
| 18 | Highwood Bench | Chouteau | 47 41 01N 110 54 02W |
| 19 | Miles City FAA Airport Miles City FAA Airport | Custer Custer | 46 25 48N 105 52 12W 46 25 48N 105 52 12W |
| 20 | Scobey Border | Daniels | 49 00 00N 105 24 00W |
| 21 | Scobey Hanrahan | Daniels | 48 53 47N 105 17 05W |
| 22 | Scobey Richardson | Daniels | 48 48 35N 105 25 13W |
| 23 | Circle | Dawson | 47 15 42N 105 16 05W |
| 24 | Glendive | Dawson | 47 05 39N 104 43 01W |
| 25 | Glendive Microwave | Dawson | 47 08 14N 104 32 45W |
| 26 | Anaconda #2 Pond Discharge | Deer Lodge | 46 09 42N 112 46 57W |
| 27 | Anaconda C-Hill | Deer Lodge | 46 06 03N 112 56 56W |
| 28 | Anaconda County Airport | Deer Lodge | 46 08 45N 112 51 13W |
| 29 | Anaconda Highway Junction | Deer Lodge | 46 08 09N 112 53 17W |
| 30 | Anaconda Lincoln School | Deer Lodge | 46 07 31N 112 56 34W |
| 31 | Anaconda Mill Creek | Deer Lodge | 46 06 19N 112 52 45W |

Table II-1. Wind Monitoring Site Locations (cont'd.)

| Site No. | Site Name | County | Location |
|-------------|---|--|--|
| 32 | Anaconda Water Office | Deer Lodge | 46 08 51N 112 56 51W |
| 33 | Anaconda Weather Hill | Deer Lodge | 46 05 51N 112 54 51W |
| 34 | Anaconda West Gate | Deer Lodge | 46 06 03N 112 54 41W |
| 35 | Antelope | Deer Lodge | 46 00 00N 113 00 00W |
| 36 | Kucera | Deer Lodge | 46 00 00N 113 00 00W |
| 37 | Opportunity Main Street | Deer Lodge | 46 08 45N 112 49 37W |
| 38 | Poor Farm | Deer Lodge | 46 10 47N 112 52 46W |
| 39 | Tailings Pond | Deer Lodge | 46 00 00N 113 00 00W |
| 40 | Lewistown FAA Airport Lewistown FAA Airport | Fergus Fergus | 47 03 00N 109 27 00W 47 03 00N 109 27 00W |
| 41 | Big Prairie | Flathead | 48 48 29N 114 18 41W |
| 42 | Bigfork Ranger Station | Flathead | 48 04 00N 114 05 57W |
| 43 | Columbia Falls Brandt | Flathead | 48 18 22N 114 15 00W |
| 44 | Columbia Falls Delbon | Flathead | 48 24 01N 114 08 21W |
| 45 | Columbia Falls Geis | Flathead | 48 20 00N 114 08 30W |
| 46 | Columbia Falls Water Supply (Trailer) Columbia Falls Water Supply | Flathead Flathead | 48 24 05N 114 08 32W 48 24 05N 114 08 32W |
| 47 | Kalispell Airport | Flathead | 48 18 38N 114 16 00W |
| 48 | Kalispell NWS Airport Kalispell NWS Airport Kalispell NWS Airport Kalispell NWS Airport | Flathead Flathead Flathead Flathead | 48 18 40N 114 16 00W 48 18 40N 114 16 00W 48 18 40N 114 16 00W 48 18 40N 114 16 00W |
| 49 | Polebridge | Flathead | 48 45 53N 114 17 01W |
| 50 | Big Sky Golf Course | Gallatin | 45 16 04N 111 17 23W |
| 51 | Bozeman FAA Airport Bozeman FAA Airport | Gallatin Gallatin | 45 46 48N 111 09 00W 45 46 48N 111 09 00W |
| 52 | Bridger Bowl | Gallatin | 45 48 00N 111 05 30W |
| 53 | Blackfoot | Glacier | 48 35 20N 112 52 35W |
| 54 | Browning RR Depot | Glacier | 48 32 15N 113 01 00W |
| 55 | Cut Bank | Glacier | 48 47 54N 112 19 37W |
| 56 | Cut Bank FAA Airport Cut Bank FAA Airport | Glacier Glacier | 48 36 00N 112 22 12W 48 36 00N 112 22 12W |
| 57 | Duck Lake | Glacier | 48 50 20N 113 20 05W |
| 58 | Rainbow Field | Glacier | 48 21 21N 113 08 10W |
| 59 | Drummond FAA Airport Drummond FAA Airport | Granite Granite | 46 37 10N 113 11 50W 46 37 10N 113 11 50W |
| 60 | Havre NWS Airport Havre NWS Airport | Hill Hill | 48 33 00N 109 46 30W 48 33 00N 109 46 30W |
| 61 | Havre NWS City Office | Hill | 48 34 00N 109 40 00W |

Table II-1. Wind Monitoring Site Locations (cont'd.)

| Site No. | Site Name | County | Location |
|-------------|--|------------------------------------|--|
| 62 | Microwave Tower | Jefferson | 46 33 27N 111 55 01W |
| 63 | Whitehall FAA Airport | Jefferson | 45 49 12N 112 12 00W |
| 64 | Polson | Lake | 47 41 20N 114 07 27W |
| 65 | Ronan | Lake | 47 30 54N 114 05 46W |
| 66 | Ronan Ninepipes | Lake | 47 27 35N 114 07 59W |
| 67 | Canyon Ferry Dam | Lewis and Clark | 46 43 54N 111 43 28W |
| 68 | East Helena A & W | Lewis and Clark | 46 35 23N 111 54 25W |
| 69 | Gibson Dam | Lewis and Clark | 47 37 47N 112 48 00W |
| 70 | Hadfield West Main | Lewis and Clark | 46 35 18N 111 55 52W |
| 71 | Helena NWS Airport Helena NWS Airport | Lewis and Clark Lewis and Clark | 46 36 21N 112 00 00W 46 36 21N 112 00 00W |
| 72 | Kleffner Residence | Lewis and Clark | 46 00 00N 112 30 00W |
| 73 | Kleffner Road | Lewis and Clark | 46 00 00N 112 30 00W |
| 74 | Sinter Plant | Lewis and Clark | 46 34 39N 111 55 21W |
| 75 | Water Tower | Lewis and Clark | 46 34 39N 111 55 21W |
| 76 | Zinc Plant | Lewis and Clark | 46 34 39N 111 55 21W |
| 77 | Tiber Dam | Liberty | 48 19 33N 111 04 47W |
| 78 | Superior NWS Airport | Mineral | 47 10 48N 114 52 12W |
| 79 | Evaro | Missoula | 47 02 00N 114 04 42W |
| 80 | Missoula Fire Lab | Missoula | 46 33 00N 114 03 00W |
| 81 | Missoula Hoerner-Waldorf #1 | Missoula | 46 57 03N 114 10 35W |
| 82 | Missoula Lions Park | Missoula | 46 51 05N 114 00 25W |
| 83 | Missoula Malfunction Junction | Missoula | 46 51 07N 114 00 53W |
| 84 | Missoula NWS Airport Missoula NWS Airport Missoula NWS Airport | Missoula Missoula Missoula | 46 55 40N 114 05 50W 46 55 40N 114 05 50W 46 55 40N 114 05 50W |
| 85 | Missoula Olofson | Missoula | 46 49 49N 114 04 24W |
| 86 87 | Missoula Rose Park Missoula Stiegler | Missoula Missoula | 46 51 26N 114 00 14W 46 54 15N 114 08 14W |
| 88 | Missoula University of Montana | Missoula | 46 51 50N 113 58 40W |
| 89 | Charles Hillman Ranch | Park | 45 43 24N 110 28 24W |
| 90 | George Meyers Ranch | Park | 45 40 03N 110 32 10W |
| 91 | Gordon Brittan Ranch | Park | 45 42 16N 110 23 37W |
| 92 | Harvatts Flat | Park | 45 38 55N 110 32 35W |
| 93 | Hunters Hot Springs | Park | 45 45 16N 110 15 38W |
| 94 | Koffee Kup Ranch | Park | 45 46 38N 110 30 54W |

Table II-1. Wind Monitoring Site Locations (cont'd.)

| Site No. | Site Name | County | Location |
|-------------|---|--------------|--|
| 95 | Livingston Candidate Wind Turbine Site | Park | 45 40 27N 110 30 01W |
| 96 | Livingston FAA Airport Livingston FAA Airport | Park Park | 45 40 12N 110 31 48W 45 40 12N 110 31 48W |
| 97 | Livingston West | Park | 45 39 23N 110 34 37W |
| 98 | McGuire Hill | Park | 45 40 23N 110 33 53W |
| 99 | Park County Landfill | Park | 45 40 07N 110 31 12W |
| 100 | Heart Butte | Pondera | 48 17 42N 112 53 03W |
| 101 | Swift Dam | Pondera | 48 13 15N 112 47 00W |
| 102 | Broadus Randall Ranch | Powder River | 45 24 27N 105 27 50W |
| 103 | McDonald Pass | Powell | 46 35 42N 112 17 05W |
| 104 | Powell County Courthouse | Powell | 46 23 49N 112 43 39W |
| 105 | Give Out Morgan | Roosevelt | 48 28 24N 105 07 54N |
| 106 | Poplar | Roosevelt | 48 06 10N 105 11 55W |
| 107 | Wolf Point | Roosevelt | 48 05 00N 105 32 00W |
| 108 | Badger Peak | Rosebud | 45 38 58N 106 33 23W |
| 109 | Colstrip BN | Rosebud | 45 51 30N 106 34 43W |
| 110 | Colstrip McRae | Rosebud | 45 45 47N 106 23 09W |
| 111 | Garfield Peak | Rosebud | 45 40 08N 106 27 54W |
| 112 | Lame Deer-Fisher Butte | Rosebud | 45 37 34N 106 39 14W |
| 113 | Morningstar Lookout | Rosebud | 45 40 06N 106 31 04W |
| 114 | Western Energy #12 | Rosebud | 45 52 06N 106 38 27W |
| 115 | Reserve | Sheridan | 48 30 58N 104 18 23W |
| 116 | Butte Alpine West | Silver Bow | 46 00 45N 112 30 32W |
| 117 | Butte FAA Airport | Silver Bow | 45 57 00N 112 30 00W |
| 118 | Butte Hebgen Park | Silver Bow | 46 00 13N 112 31 29W |
| 119 | Harrison Fire Station | Silver Bow | 46 00 00N 112 30 00W |
| 120 | Anaconda Stillwater Mine Site | Stillwater | 45 25 30N 109 53 11W |
| 121 | Hertzler Ranch | Stillwater | 45 32 26N 109 47 10W |
| 122 | Long Mountain | Sweetgrass | 45 32 20N 110 05 01W |
| 123 | Main Station | Sweetgrass | 45 30 37N 110 06 07W |
| 124 | Woolsey Ranch | Sweetgrass | 45 35 05N 110 06 37W |
| 125 | Choteau | Teton | 47 44 36N 112 26 05W |
| 126 | Fairfield | Teton | 47 36 31N 112 02 43W |
| 127 | Pendroy | Teton | 48 07 45N 112 26 20W |
| 128 | Devon | Toole | 48 26 00N 111 27 00W |

Table II-1. Wind Monitoring Site Locations (cont'd.)

| Site No. | Site Name | County | Location |
|-------------|--|---|--|
| 129 | Fort Peck | Valley | 47 59 48N 106 29 59W |
| 130 | Glasgow Air Force Base Glasgow Air Force Base Glasgow Air Force Base | Valley Valley Valley | 48 24 00N 106 31 20W 48 24 00N 106 31 20W 48 24 00N 106 31 20W |
| 131 | Glasgow NWS Airport Glasgow NWS Airport Glasgow NWS Airport | Valley Valley Valley | 48 13 12N 106 37 12W 48 13 12N 106 37 12W 48 13 12N 106 37 12W |
| 132 | Glasgow NWS City Office | Valley | 48 11 00N 106 38 00W |
| 133 | Harlowton | Wheatland | 46 28 00N 109 52 00W |
| 134 | Judith Gap | Wheatland | 46 36 57N 109 46 11W |
| 135 | Billings AQB Office | Yellowstone | 45 46 57N 108 31 56W |
| 136 | Billings 11th & 27th | Yellowstone | 45 46 18N 108 29 57W |
| 137 | Billings Central Park | Yellowstone | 45 46 51N 108 32 19W |
| 138 | Billings Metra | Yellowstone | 45 47 55N 108 28 45W |
| 139 | Billings NWS Airport Billings NWS Airport Billings NWS Airport | Yellowstone Yellowstone Yellowstone | 45 48 00N 108 31 48W 45 48 00N 108 31 48W 45 48 00N 108 31 48W |
| 140 | Billings Taft School | Yellowstone | 45 46 36N 108 29 40W |
| 141 | Coburn Road | Yellowstone | 45 47 00N 108 28 00W |
| 142 | Custer FAA Airport Custer FAA Airport | Yellowstone Yellowstone | 46 09 00N 107 31 00W 46 09 00N 107 31 00W |
| 143 | Laurel BN | Yellowstone | 45 41 00N 108 42 00W |
| 144 | Laurel Farm | Yellowstone | 45 39 39N 108 46 12W |
| 145 | Laurel New Farm | Yellowstone | 45 40 07N 108 44 25W |
| 146 | Lockwood Park | Yellowstone | 45 48 00N 108 27 00W |
| 147 | Lockwood School | Yellowstone | 45 47 57N 108 26 30W |
| 148 | North Johnson Lane | Yellowstone | 45 49 00N 108 26 00W |
| 149 | Shawnee Park | Yellowstone | 45 49 28N 108 23 56W |
| 1987 A | Additions | | |
| 150 | Hays | Blaine | 48 06 17N 108 42 43W |
| 151 | Drummond—1 | Granite | 46 37 00N 113 11 00W |
| 152 | Drummond—2 | Granite | 46 39 52N 113 15 06W |
| 153 | Whitehall | Jefferson | 45 55 57N 112 04 30W |
| 154 | Sieben 1 | Lewis and Clark | 46 55 00N 112 13 00W |
| 155 | Sieben 2 | Lewis and Clark | 46 50 30N 112 15 30W |
| 156 | Whitlash | Liberty | 48 51 36N 111 14 46W |
| 157 | Norris Hill | Madison | 45 29 42N 111 41 57W |
| 158 | Mt. Antione | Phillips | 47 57 20N 108 33 02W |

Table II-2. Monitoring Agency and Duration

| Site No. | Site Name | Monitoring Agency | Duration of Monitoring |
|-------------|--|--|---|
| 1 | Dillon FAA Airport Dillon FAA Airport | Federal Aviation Administration Federal Aviation Administration | 1951 JUN 19 - 1963 OCT 29 1963 OCT 30 - 1973 JUN 18 |
| 2 | Decker Coal #8 | Decker Coal Company | 1980 DEC 01 - 1982 MAY 31 |
| 3 | Hardin | Montana Power Company | 1980 MAY - 1981 APR |
| 4 | Hardin MDN | Air Quality Bureau | 1972 APR - 1973 JUL |
| 5 | Spring Creek #1 | Spring Creek Coal Company | 1981 JAN 01 - 1981 DEC 31 |
| 6 | Westmoreland Absaloka #2 | Westmoreland Resources, Inc. | 1980 AUG 01 - 1982 MAR 29 |
| 7 | Yellowtail Dam | Bureau of Reclamation | 1980 JAN 21 - 1981 JAN 31 |
| 8 | Youngs Creek | Shell Oil Company | 1975 OCT - 1979 DEC |
| 9 | Hays Forestry Shop | Fort Belknap Reservation | 1980 AUG - ? |
| 10 | Three Forks | Bureau of Reclamation | 1981 JUN 27 - 1982 SEP 15 |
| 11 | Ekalaka | Southeast Electric Co-op | 1982 MAR 11 - 1986 MAY 18 |
| 12 | Great Falls City Sewage Pump | Air Quality Bureau | 1972 JUN - 1972 AUG |
| 13 | Great Falls Kiwanis Park | Air Quality Bureau | 1980 JAN 01 - 1980 FEB 16 |
| 14 | Great Falls Malmstrom Air Force Base Great Falls Malmstrom Air Force Base Great Falls Malmstrom Air Force Base | United States Air Force United States Air Force United States Air Force | 1949 JAN 01 - 1953 MAY 31 1954 MAR 01 - 1958 FEB 28 1958 APR 01 - 1968 NOV 30 |
| 15 | Great Falls NWS Airport Great Falls NWS Airport Great Falls NWS Airport | National Weather Service National Weather Service National Weather Service | 1948 JAN 01 - 1959 FEB 02 1959 FEB 03 - 1964 DEC 31 1965 JAN 01 - 1978 DEC 31 |
| 16 | Portage | Montana Power Company | 1980 APR - ? |
| 17 | Salem | Montana Power Company | 1980 MAY 01 - 1984 MAR |
| 18 | Highwood Bench | Bureau of Reclamation | 1981 JUN 05 - 1983 JUN 17 |
| 19 | Miles City FAA Airport Miles City FAA Airport | Federal Aviation Administration Federal Aviation Administration | 1948 JAN 01 - 1964 DEC 31 1965 JAN 01 - 1978 DEC 31 |
| 20 | Scobey Border | Air Quality Bureau | 1977 MAR 02 - 1982 APR 26 |
| 21 | Scobey Hanrahan | Air Quality Bureau | 1981 APR 01 - 1982 MAR 31 |
| 22 | Scobey Richardson | Air Quality Bureau | 1979 JAN 16 - 1979 MAY 31 |
| 23 | Circle | McCone Electric Co-op | 1982 MAR 11 - 1985 OCT 30 |
| 24 | Glendive | Environmental Protection Agency | 1974 DEC 26 - 1976 FEB 29 |
| 25 | Glendive Microwave | Air Quality Bureau | 1975 JUL 26 - 1977 SEP 14 |
| 26 | Anaconda #2 Pond Discharge | Anaconda Copper Company | 1976 DEC 04 - 1979 MAY 31 |
| 27 | Anaconda C-Hill | Anaconda Copper Company | 1976 JAN 01 - 1979 MAY 31 |
| 28 | Anaconda County Airport | Anaconda Copper Company | 1976 DEC 04 - 1979 MAY 31 |
| 29 | Anaconda Highway Junction | Air Quality Bureau | 1975 JUN 11 - 1979 DEC 28 |
| 30 | Anaconda Lincoln School | Air Quality Bureau | 1978 JUL 03 - 1981 MAY 19 |
| 31 | Anaconda Mill Creek | Anaconda Copper Company | 1976 DEC 04 - 1979 MAY 31 |
| 32 | Anaconda Water Office | Anaconda Copper Company | 1976 DEC 04 - 1979 MAY 31 |
| 33 | Anaconda Weather Hill | Anaconda Copper Company | 1976 DEC 04 - 1979 MAY 31 |

Table II-2. Monitoring Agency and Duration (cont'd.)

| Site No. | Site Name | Monitoring Agency | Duration of Monitoring |
|-------------|--|--|--|
| 34 | Anaconda West Gate | Anaconda Copper Company | 1976 JAN 01 - 1979 MAY 31 |
| 35 | Antelope | Air Quality Bureau | 1973 FEB - 1973 AUG |
| 36 | Kucera | Air Quality Bureau | 1972 DEC - 1973 MAY |
| 37 | Opportunity Main Street | Air Quality Bureau | 1972 JUN - 1972 NOV |
| 38 | Poor Farm | Air Quality Bureau | 1971 DEC - 1973 JAN |
| 39 | Tailings Pond | Air Quality Bureau | 1974 JUL - 1974 OCT |
| 40 | Lewistown FAA Airport Lewistown FAA Airport | Federal Aviation Administration Federal Aviation Administration | 1949 DEC 21 - 1962 AUG 15 1964 OCT 13 - 1978 DEC 31 |
| 41 | Big Prairie | Air Quality Bureau | 1978 NOV 07 - 1982 JAN 04 |
| 42 | Bigfork Ranger Station Bigfork Ranger Station | Air Quality Bureau Air Quality Bureau | 1979 NOV 16 - 1980 JUN 10 1981 JUL 15 - 1981 AUG 30 |
| 43 | Columbia Falls Brandt Columbia Falls Brandt | Air Quality Bureau Air Quality Bureau | 1977 MAR 02 - 1977 JUN 06 1978 MAR 17 - 1978 MAY 29 |
| 44 | Columbia Falls Delbon | Air Quality Bureau | 1977 MAR 14 - 1978 MAY 31 |
| 45 | Columbia Falls Geis | Air Quality Bureau | 1978 JAN - 1978 MAY |
| 46 | Columbia Falls Water Supply (Trailer) Columbia Falls Water Supply | Air Quality Bureau Air Quality Bureau | 1972 FEB - 1974 JUN 1977 FEB 16 - 1979 OCT 22 |
| 47 | Kalispell Airport Kalispell Airport | Air Quality Bureau Air Quality Bureau | 1976 DEC 21 - 1977 OCT 20 1978 JUN 23 - 1982 FEB 15 |
| 48 | Kalispell NWS Airport Kalispell NWS Airport Kalispell NWS Airport Kalispell NWS Airport | National Weather Service National Weather Service National Weather Service National Weather Service | 1949 MAY 01 - 1953 JUN 30 1953 JUL 01 - 1959 JUN 30 1959 JUL 01 - 1964 JUN 30 1964 JUL 01 - 1978 DEC 31 |
| 49 | Polebridge | Air Quality Bureau | 1978 SEP 14 - 1978 NOV 07 |
| 50 | Big Sky Golf Course | Air Quality Bureau | 1981 JUL 03 - 1982 MAY 15 |
| 51 | Bozeman FAA Airport Bozeman FAA Airport | Federal Aviation Administration Federal Aviation Administration | 1948 JAN 01 - 1951 APR 27 1951 APR 28 - 1954 DEC 31 |
| 52 | Bridger Bowl | U.S. Forest Service | 1968 - 1983 APR |
| 53 | Blackfoot Blackfoot | Bonneville Power Administration Bonneville Power Administration | 1981 SEP - 1984 JUL 1984 JUL 30 - 1985 OCT 29 |
| 54 | Browning RR Depot | Burlington Northern | 1981 APR - 1983 APR |
| 55 | Cut Bank | Bureau of Reclamation | 1981 JUN 03 - 1983 AUG 3 |
| 56 | Cut Bank FAA Airport Cut Bank FAA Airport | Federal Aviation Administration Federal Aviation Administration | 1949 NOV 22 - 1959 OCT 03 1959 OCT 04 - 1978 DEC 31 |
| 57 | Duck Lake | Bonneville Power Administration | 1982 NOV - 1984 APR |
| 58 | Rainbow Field | Bonneville Power Administration | 1981 SEP - 1982 NOV |
| 59 | Drummond FAA Airport Drummond FAA Airport | Federal Aviation Administration Federal Aviation Administration | 1948 JAN 01 - 1950 OCT 15 1950 OCT 16 - 1954 DEC 31 |
| 60 | Havre NWS Airport Havre NWS Airport | National Weather Service National Weather Service | 1961 FEB 01 - 1964 DEC 31 1967 JAN 01 - 1978 DEC 31 |
| 61 | Havre NWS City Office | National Weather Service | 1950 MAY 01 - 1956 OCT 31 |
| 62 | Microwave Tower | Air Quality Bureau | 1975 JAN 16 - 1981 DEC 31 |
| 63 | Whitehall FAA Airport | Federal Aviation Administration | 1948 JAN 01 - 1954 DEC 31 |

Table II-2. Monitoring Agency and Duration (cont'd.)

| Site No. | Site Name | Monitoring Agency | Duration of Monitoring |
|-------------|--|--|---|
| 64 | Polson Polson | Air Quality Bureau Air Quality Bureau | 1978 OCT 19 - 1980 SEP 17 1981 MAR 01 - 1981 DEC 05 |
| 65 | Ronan | Air Quality Bureau | 1979 JAN 03 - 1980 JUN 15 |
| 66 | Ronan Ninepipes | Air Quality Bureau | 1980 DEC 11 - 1982 FEB 26 |
| 67 | Canyon Ferry Dam | Bureau of Reclamation | 1980 JAN 31 - 1981 JAN 31 |
| 68 | East Helena A & W | Air Quality Bureau | 1980 FEB 01 - 1980 JUN 30 |
| 69 | Gibson Dam | Bureau of Reclamation | 1980 JAN 15 - 1981 JAN 31 |
| 70 | Hadfield West Main | Air Quality Bureau | 1981 OCT 01 - 1981 DEC 31 |
| 71 | Helena NWS Airport Helena NWS Airport | National Weather Service National Weather Service | 1948 JAN 01 - 1961 SEP 19 1961 SEP 20 - 1978 DEC 31 |
| 72 | Kleffner Residence | Air Quality Bureau | 1968 JUL - 1971 SEP |
| 73 | Kleffner Road | ASARCO | 1981 OCT 01 - 1981 DEC 31 |
| 74 | Sinter Plant | ASARCO | 1981 OCT 01 - 1981 DEC 31 |
| 75 | Water Tower | ASARCO | 1981 OCT 01 - 1981 DEC 31 |
| 76 | Zinc Plant | ASARCO | 1981 OCT 01 - 1981 DEC 31 |
| 77 | Tiber Dam | Bureau of Reclamation | 1980 JAN 16 - 1981 JAN 31 |
| 78 | Superior NWS Airport | National Weather Service | 1948 JAN 01 - 1953 NOV 30 |
| 79 | Evaro | Flathead Reservation | 1980 OCT - ? |
| 80 | Missoula Fire Lab | Air Quality Bureau | 1977 DEC 01 - 1980 APR 30 |
| 81 | Missoula Hoerner-Waldorf #1 | Hoerner-Waldorf | 1977 JUL 01 - 1982 MAR 31 |
| 82 | Missoula Lions Park | Air Quality Bureau | 1977 DEC 02 - 1980 JUL 27 |
| 83 | Missoula Malfunction Junction | Air Quality Bureau | 1980 APR 03 - 1980 MAY 26 |
| 84 | Missoula NWS Airport Missoula NWS Airport Missoula NWS Airport | National Weather Service National Weather Service National Weather Service | 1948 JAN 01 - 1958 APR 03 1958 APR 04 - 1964 DEC 31 1965 JAN 01 - 1978 DEC 31 |
| 85 | Missoula Olofson | Air Quality Bureau | 1978 JUL 15 - 1980 MAR 17 |
| 86 | Missoula Rose Park | Air Quality Bureau | 1980 NOV 14 - 1982 APR 26 |
| 87 | Missoula Stiegler | Air Quality Bureau | 1978 MAY 01 - 1980 MAR 17 |
| 88 | Missoula University of Montana | Air Quality Bureau | 1978 MAY 01 - 1980 MAR 17 |
| 89 | Charles Hillman Ranch | Montana DNRC | 1979 MAR - 1979 APR |
| 90 | George Meyers Ranch | Montana DNRC | 1979 MAR - 1979 APR |
| 91 | Gordon Brittan Ranch | Montana DNRC | 1979 MAY - 1979 JUL |
| 92 | Harvatts Flat | Montana DNRC | 1978 DEC - 1979 FEB |
| 93 | Hunters Hot Springs | Montana DNRC | 1978 DEC - 1979 FEB |
| 94 | Koffee Kup Ranch | Montana DNRC | 1978 DEC - 1979 FEB |
| 95 | Livingston Candidate Wind Turbine Site | Bonneville Power Administration | 1980 SEP 01 - 1982 JUN 30 |
| 96 | Livingston FAA Airport Livingston FAA Airport | Federal Aviation Administration Federal Aviation Administration | 1948 JAN 01 - 1953 JUL 04 1953 JUL 05 - 1954 DEC 31 |

Table II-2. Monitoring Agency and Duration (cont'd.)

| Site No. | Site Name Livingston West | Monitoring Agency Montana DNRC | Duration of Monitoring |
|-------------|--|--|---|
| 98 | McGuire Hill | Montana DNRC | 1979 MAY - 1979 JUL |
| 99 | Park County Landfill | Montana DNRC | 1979 MAY - 1979 JUL |
| 100 | Heart Butte | Bonneville Power Administration | 1979 MAR - 1979 APR |
| | Heart Butte | Bonneville Power Administration | 1981 SEP - 1982 OCT 1982 NOV 13 - 1984 MAY 29 |
| 101 | Swift Dam | Bonneville Power Administration | 1981 SEP - 1984 JUN |
| 102 | Broadus Randall Ranch | Air Quality Bureau | 1976 MAR 06 - 1978 AUG 27 |
| 103 | McDonald Pass | Bonneville Power Administration | 1981 OCT - 1982 DEC |
| 104 | Powell County Courthouse | Air Quality Bureau | 1971 APR - 1972 MAY |
| 105 | Give Out Morgan | Fort Peck Reservation | 1980 AUG - ? |
| 106 | Poplar | Air Quality Bureau | 1976 MAY 18 - 1976 SEP 30 |
| 107 | Wolf Point | National Weather Service | 1958 JAN - 1962 DEC |
| 108 | Badger Peak | GeoResearch, Inc. (MPC/NCT) | 1981 APR 01 - Present |
| 109 | Colstrip BN | Air Quality Bureau | 1975 JAN 01 - 1979 AUG 22 |
| 110 | Colstrip McRae | Air Quality Bureau | 1975 JAN 01 - 1976 AUG 04 |
| 111 | Garfield Peak | GeoResearch, Inc. (MPC/NCT) | 1981 APR 01 - Present |
| 112 | Lame Deer-Fisher Butte | Air Quality Bureau | 1976 MAY 16 - 1976 OCT 26 |
| 113 | Morningstar Lookout | GeoResearch, Inc. (MPC/NCT) | 1981 APR 01 - Present |
| 114 | Western Energy #12 | Western Energy Company | 1981 JAN 01 - 1982 MAR 31 |
| 115 | Reserve | Sheridan Electric Co-op | 1982 JAN 29 - 1985 JUN 30 |
| 116 | Butte Alpine West | Air Quality Bureau | 1977 AUG 01 - 1978 JUN 15 |
| 117 | Butte FAA Airport | Federal Aviation Administration | 1948 JAN 01 - 1960 DEC 31 |
| 118 | Butte Hebgen Park | Air Quality Bureau | 1978 JUN 15 - 1980 DEC 10 |
| 119 | Harrison Fire Station | Air Quality Bureau | 1972 JAN - 1972 MAR |
| 120 | Anaconda Stillwater Mine Site | Anaconda Minerals Company | 1980 AUG - 1981 JUL |
| 121 | Hertzler Ranch | Anaconda Minerals Company | 1980 AUG - 1981 JUL |
| 122 | Long Mountain | PGM Resources | 1981 OCT - 1982 SEP |
| 123 | Main Station | PGM Resources | 1981 OCT - 1982 SEP |
| 124 | Woolsey Ranch | PGM Resources | 1981 OCT - 1982 SEP |
| 125 | Choteau | Bureau of Reclamation | 1981 JUN 04 - 1983 AUG 16 |
| 126 | Fairfield | Sun River Electric Co-op | 1981 DEC 30 - 1985 JAN 3 |
| 127 | Pendroy | Sun River Electric Co-op | 1982 MAR 17 - 1984 DEC 19 |
| 128 | Devon | Montana Power Company | 1980 APR - 1981 APR |
| 129 | Fort Peck | Air Quality Bureau | 1977 MAY 07 - 1979 JUL 19 |
| 130 | Glasgow Air Force Base Glasgow Air Force Base Glasgow Air Force Base | United States Air Force United States Air Force Old West Regional Commission | 1958 OCT 01 - 1961 JUN 07 1961 JUN 08 - 1968 JUN 30 1977 OCT 25 - 1978 AUG 31 |

Table II-2. Monitoring Agency and Duration (cont'd.)

| Site No. | Site Name | Monitoring Agency | Duration of Monitoring |
|---------------|--|--|---|
| 131 | Glasgow NWS Airport Glasgow NWS Airport Glasgow NWS Airport | National Weather Service National Weather Service National Weather Service | 1955 OCT 01 - 1962 AUG 05 1962 AUG 06 - 1968 MAY 31 1968 JUN 01 - 1978 DEC 31 |
| 132 | Glasgow NWS City Office | National Weather Service | 1948 JAN 01 - 1955 OCT 31 |
| 133 | Harlowton | Electric Power Research Institute | 1981 JUN - 1982 OCT |
| 134 | Judith Gap | Bureau of Reclamation | 1981 AUG 01 - 1985 JUL 31 |
| 135 | Billings AQB Office | Air Quality Bureau | 1970 JUN - 1971 APR |
| 136 | Billings 11th & 27th | Air Quality Bureau | 1975 SEP 21 - 1976 APR 30 |
| 137 | Billings Central Park | Air Quality Bureau | 1978 AUG 10 - 1980 MAY 08 |
| 138 | Billings Metra | Air Quality Bureau | 1980 SEP 13 - 1982 MAY 03 |
| 139 | Billings NWS Airport Billings NWS Airport Billings NWS Airport | National Weather Service National Weather Service National Weather Service | 1948 JAN 01 - 1958 JUN 25 1958 JUN 26 - 1964 DEC 31 1965 JAN 01 - 1978 DEC 31 |
| 140 | Billings Taft School | Air Quality Bureau | 1980 AUG 07 - 1982 MAY 17 |
| 141 | Coburn Road | Air Quality Bureau | 1981 SEP - 1982 SEP |
| 142 | Custer FAA Airport Custer FAA Airport | Federal Aviation Administration Federal Aviation Administration | 1948 JAN 01 - 1949 MAY 31 1949 JUN 01 - 1950 MAY 30 |
| 143 | Laurel BN | Air Quality Bureau | 1981 SEP - 1982 SEP |
| 144 | Laurel Farm | Air Quality Bureau | 1976 MAY 01 - 1980 JUL 15 |
| 145 | Laurel New Farm | Air Quality Bureau | 1980 NOV 13 - 1982 MAY 17 |
| 146 | Lockwood Park | Air Quality Bureau | 1981 SEP - 1982 SEP |
| 147 | Lockwood School | Air Quality Bureau | 1979 AUG 02 - 1980 JUN 11 |
| 148 | North Johnson Lane | Air Quality Bureau | 1981 SEP - 1982 SEP |
| 149 | Shawnee Park | Air Quality Bureau | 1981 JAN 22 - 1982 APR 30 |
| 1987 A | Additions | | |
| 150 | Hays | Montana DNRC | 1984 JAN 1 - 1985 JUL 15 |
| 151 | Drummond—1 | Montana DNRC | 1982 DEC 17 - 1983 JUL 26 |
| 152 | Drummond—2 | Montana DNRC | 1983 DEC 2 - 1985 MAY 29 |
| 153 | Whitehall | Bonneville Power Administration | 1983 SEP - 1984 JUL |
| 154 | Sieben 1 | Bonneville Power Administration | 1984 FEB 18 - 1984 JUL 28 |
| 155 | Sieben 2 | Bonneville Power Administration | 1983 OCT - 1984 JUL |
| 156 | Whitlash | Montana DNRC | 1983 NOV 18 - 1985 JUL 24 |
| 157 | Norris Hill | Montana DNRC | 1984 JAN 10 - 1986 MAR 31 |
| 158 | Mt. Antione | WAPA | 1984 FEB 8 - 1985 AUG 5 |

NOTE: The monitoring duration represents the full or known period of monitoring at a given site, or the period for which data were available to DNRC. Sites at which monitoring is continuing, but data were not available, are marked "present"; sites for which the status is unknown are marked "?".

The disadvantages of these data are:

- The values of wind speed and direction are approximately 1-minute averages, so users must be cautious when comparing them to other data sets;
- Anemometer heights are not standardized in most cases;
- Particularly in earlier years, the anemometers were located on rooftops; such an exposure creates the possibility that the wind speed values recorded were too high, due to acceleration of air over the buildings;
- The stations are located at airports and/or urban areas, which typically are areas where high winds occur less frequently.

In spite of these deficiencies, the NWS, FAA, and USAF data are a valuable resource for evaluating potential wind power.

Data from these sources are gathered and stored by the National Climatic Center (NCC) in Asheville, North Carolina. This data set has been analyzed by Battelle Pacific Northwest Laboratories, and a Wind Energy Data Base has been assembled. The data base consists of several data files:

- Station Description physical characteristics of the station;
- Means and Frequency Distribution mean wind speed and wind energy flux, as well as wind speed frequency distributions;
- Intra-/Inter-Annual monthly and annual means and standard deviations of wind speed, wind energy flux, and other parameters;
- Climatic Means and Weather Events monthly means of air density, temperature and pressure, and occurrences of significant weather events;
- Persistence of Speed and Direction number of episodes of given duration when the wind speed exceeded a threshold or the wind direction remained constant;
- Wind Data Grid wind energy flux, land surface form, resource certainty rating, and resource areal distribution by grid cell.

These files were obtained from Battelle, and portions of the data files were incorporated into the *Montana Wind Energy Atlas*.

The data that Battelle obtained from NCC consisted of either summarized, digitized, or unsummarized data from NWS, FAA, and USAF airport stations. The NWS and FAA data obtained by Battelle were collected from 1948 through 1978, except for those sites where monitoring was discontinued at an earlier date. The USAF data obtained by Battelle were collected from 1948 through 1968, when the USAF stopped coding

their meteorological data for the NCC. All NCC data originally are in unsummarized formats consisting of the original station weather records. The data for some stations have been analyzed by NCC and condensed into wind summaries. Data from some airport stations have been digitized by NCC and made available in machine-readable form.

When Battelle conducted its analyses, it used summarized or digitized data whenever possible. If both summarized and digitized data were available, the digitized data were used to prepare a more extensive characterization of the wind resource. Unsummarized data were used only when no summarized or digitized data were available.

For stations with digitized data, Battelle calculated the average wind power density from:

$$\overline{P} = \frac{1}{2n} \sum_{i=1}^{n} \rho_i V_i^3$$

where:

n = the number of observations in the averaging period;

 ρ_i = the density (in kg/m³) computed from the station pressure and temperature;

V_i = the wind speed (in m/s) at the i th observation time.

For stations with wind summaries, \overline{P} was calculated from:

$$\overline{P} = \frac{1}{2} \overline{\rho} \sum_{j=1}^{c} f_j V_j^3$$

where:

 $\overline{\rho}$ = the mean air density;

c = the number of wind speed classes;

f_j = frequency of occurrence of winds in the

 V_{i} = the median wind speed of the j th class.

In those cases for which unsummarized wind data were assessed, the seasonal and annual average speeds, \overline{V} , were estimated from a visual examination of one year's original weather records. The wind power density, \overline{P} , then was estimated by assuming the speed frequency distribution followed a Rayleigh distribution. (A Rayleigh distribution is a mathematical approximation of actual wind speed distributions; see Appendix B.) The wind power density was calculated as follows:

$$\overline{P} = 0.955 \ \overline{\rho} \ \overline{V}^3$$

Battelle also adjusted the long-term mean wind speed and wind power density to a reference level of 10 meters by means of the one-seventh power law. In the data tables presented in this *Atlas*, the mean wind speeds and wind power densities presented are for the anemometer height, and have not been adjusted to a reference height.

Montana Air Quality Bureau

The Montana Air Quality Bureau (AQB) is responsible for monitoring air quality in the state and for safeguarding the public health. To accomplish these goals, the AQB operates a number of air monitoring stations around the state. In addition, the AQB has conducted special studies, such as the Montana Air Pollution Study and the Flathead River Basin Environmental Impact Study, to evaluate meteorological conditions and air quality in specific areas.

The AQB also requires operators of certain facilities, such as power plants and smelters, to conduct monitoring programs around their projects. The data thus collected are submitted to the AQB and become part of AQB's data file.

During the past 10 years, the AQB has accumulated a large amount of meteorological data. The advantages of these data are:

- The data were collected from a large number of sites;
- The sites are distributed over a large geographic area;
- The data represent a one-hour averaging time:
- The data are readily available, in SAROAD format, in hard copy or in machine-readable form (SAROAD is the Environmental Protection Agency's standard format for coding aerometric data).

The disadvantages of these data are:

- In most cases, the monitoring period was short (less than three years);
- Anemometer heights were not standardized until recently;
- The data set, especially for earlier years, contains a significant number of errors;
- In many cases, the data are not very complete;
- The quality assurance program for meteorological data was inadequate until recently; in particular, alignment of wind direction sensors sometimes was inaccurate;
- Many of the stations were located in urban areas.

U.S. Environmental Protection Agency

The U.S. Environmental Protection Agency (EPA) has, from time to time, conducted wind monitoring studies in Montana. These studies generally were conducted as a part of studies of dispersion around sources of pollution. One such study, which was designed to study sulfur dioxide concentrations in the air near East Helena, was conducted in 1969 and 1970. Another study was conducted near Glendive in 1975 and 1976. The EPA also is a major source of funds for other agencies, such as the AQB, which conduct studies of their own. For example, two major monitoring studies conducted by the AQB, the Flathead River Basin Environmental Impact Study and the Poplar River Study, were funded largely by EPA.

Bureau of Reclamation, U.S. Department of Interior

The Bureau of Reclamation (BOR), in recent years, has initiated studies to identify areas of high potential for wind energy generation. The Northern Great Plains Wind Energy Study is one such monitoring effort. Wind monitoring sites were established at 15 sites in Montana, North Dakota, South Dakota, and Wyoming. The BOR provided the Montana data for inclusion in the Montana Wind Energy Atlas.

The data set contains the following information:

- Average hourly wind speed;
- Maximum wind speed during the hour;
- Minimum wind speed during the hour;
- Average cube of the hourly wind speed;
- Standard deviation of the hourly speed;
- · Wind direction.

The data were recorded on cassette tape by a computerized data acquisition system. The tapes were further processed by computer to yield the completed data set.

The advantages of these data are:

- The sites were located in areas of high wind potential;
- Parameters of interest to wind developers were monitored;
- Anemometer heights were standardized;
- The data are readily available, either in hard copy or machine-readable form.

Monitoring continued at these sites for at least two years.

Montana Department of Natural Resources and Conservation

The Montana Department of Natural Resources and Conservation (DNRC) assumed responsibility for operating the BOR wind monitoring sites in Montana in 1982. The monitoring equipment later was moved to other sites. Since 1982, DNRC has completed monitioring the wind at four sites and plans to continue monitoring at four other sites (Augusta, Norris Hill, Ringling, and Whitehall) at least through June 1987. BOR has provided data reduction services and issued quarterly reports for these sites.

DNRC, through its Renewable Energy Program, has funded other wind monitoring efforts around the state. Among these studies are the Wind Energy Survey (Livingston to Springdale) and the Montana Wind Energy Research and Development Program.

The advantages of these data are:

- The sites have been located in areas of high wind potential;
- The studies were specifically designed to provide data for wind energy applications;
- Anemometer heights were standardized.

The only disadvantage of these data is that the monitoring periods were short, generally a few months to a year.

In 1985, DNRC funded wind monitoring outside of Anaconda and across the Livingston bench, as well as a wind shear study in Livingston at the old Candidate Wind Turbine Site.

U.S. Department of Energy

The Department of Energy (DOE), as part of various federal energy programs, conducted research activities to provide information on wind characteristics throughout the United States. These efforts included:

- Wind Energy Resource Assessment;
- Siting Methodologies;
- Meteorological Characteristics for Design and Performance Evaluation;
- Meteorological Characteristics for Wind Energy Conversion System Operations;
- Site Selection Support;
- Site Meteorological Measurements;
- Large Machine Site Evaluation.

As part of this program, DOE collected wind data at the Livingston Candidate Wind Turbine site since September 1980. This monitoring effort was

taken over by the Bonneville Power Administration in October 1982 through June 1983.

The data collected at Livingston consist of hourly averages of wind speed and wind direction at three different anemometer heights (10, 30, and 45.7 meters above ground level). The data were recorded digitally at the site on a data cassette recording system. An instantaneous sample of data was recorded every two minutes. These data are summarized in the *Montana Wind Energy Atlas*.

The advantages of these data are:

- The site is located in an area of high wind energy potential;
- Data were collected at three different anemometer heights;
- The data set is nearly complete;
- The system was designed specifically to provide data for wind energy applications;
- The data are readily available, either in hard copy or in machine-readable form.

Bonneville Power Administration

The Bonneville Power Administration (BPA) in 1980 initiated the Wind Regional Energy Assessment Program (Wind REAP). This five-year program was designed to assess the wind resource potential throughout the Pacific Northwest. The actual research was carried out by Oregon State University. The program consisted of fly-overs of areas to identify high potential sites and later location of wind monitoring devices at some of those sites. Nine sites were instrumented in Montana.

The advantages of these data are:

- The sites were located in areas of high wind potential;
- Most of the anemometers were set at a standard height of 30 feet;
- The data are readily available in hard copy and data for three sites are available in machine-readable form:
- Information on the suitability of the sites for wind farm development was collected.

The disadvantages of the data are:

- Only wind-run data were collected at six of the sites, and at two of the other three, only wind-run data were collected for most of the time they were in operation;
- Each of the wind-run data sets had more than twenty percent missing data;
- Four of the sites had less than one year's data.

The data and reports are available at the Wind Resources Assessment Laboratory, Oregon State University.

Western Area Power Administration

The Western Area Power Administration initiated a Wind Prospecting Program in 1981. Six sites in the program were located in Montana, mostly in the eastern part of the state. Because the data were only available in hard copy, the sites were included in Appendix C and not in the main text of the *Atlas*. Four of the sites appeared to have substantial wind resources.

Private Companies

Many private companies have conducted their own wind monitoring programs in Montana. Most of these programs have been initiated to comply with air quality permit requirements. The scope of these efforts ranges from one year of monitoring at a single anemometer height to several years of monitoring at different anemometer heights. An example of the latter program is Montana Power Company's Salem site, where wind monitoring at three levels on a 100-meter tower ran from May 1980 to March 1984.

The advantages of the data gathered by these various private companies are:

- The anemometer heights are usually standardized:
- The data sets generally are complete and accurate:
- The data generally are available to the public in standard formats if submitted to fulfill permit requirements.

The disadvantages of these data are:

- Monitoring, in most cases, has taken place for only one year;
- The data may be confidential.

Other privately funded monitoring studies included the multi-site Northern Cheyenne Tribe-Montana Power Company monitoring system near Lame Deer, operated by GeoResearch, Inc., and the visibility monitoring site near Harlowton, operated for the Electric Power Research Institute (EPRI).

Conclusions

A large amount of wind data has been gathered in Montana over the last 30 years. The wind monitoring sites, however, generally have been concentrated in urban and other areas of low wind potential. In some areas of high wind potential, particularly along the eastern slopes of the Rockies, monitoring has been light. Winds in certain other promising areas, such as the upper Musselshell valley above

Harlowton and the eastern slopes of the Little Belt Mountains from Utica to Geyser, also have not been adequately investigated. Considerable wind data, nonetheless, are available for areas of potential interest to wind developers.

When comparing wind data from sites where monitoring has been conducted, caution must be exercised. The monitoring objectives of the various programs have differed from agency to agency and often from project to project. As a result, other aspects of the monitoring programs also have differed.

Collection methods and averaging times have varied and anemometer heights have not been standardized, even within studies. The most serious problem with comparability of the data, in fact, is the difference in anemometer heights. Ten meters has now become the standard exposure height for most purposes, but some agencies, particularly the NWS and FAA, are still using an anemometer height of approximately 6 meters. A discussion of collection methods and averaging times is given in the site analysis for each station included in the *Atlas*, and the anemometer height is listed in the site's wind speed frequency table.

Quality assurance activities also have been inadequate in some cases, particularly for wind direction monitoring, occasionally leading to serious questions concerning the data. Wind direction data, however, are not as critical to wind energy analyses as wind speed data, which by and large appear to be valid or within a range of reasonable values.

The period of record, the number of observations, and the percentage of data recovery also have varied. Most monitoring efforts have been short term, lasting for three years or less. Many of these projects, moreover, were not conducted during the same years. The number of observations and data completeness also are a concern with some of the data sets, particularly where missing observations or data are not distributed uniformly among the months. Sites where monitoring took place for less than one year's duration, or with long periods or large amounts of missing data, generally have not been included in the *Atlas*.

Therefore, although caution must be exercised in comparing the wind data gathered at the various stations around Montana, the data presented and analyzed in this *Atlas* have been screened to form a basis for site evaluations and comparisons that will be within acceptable and reasonable statistical limits (see Appendix B).

WIND ENERGY POTENTIAL

The average distribution of wind movements over the entire earth is called the general circulation. The primary features of this circulation are the equatorial belt of low pressure (the doldrums); the subtropical high pressure belts (the horse latitudes); the polar low pressure; and the polar caps of high pressure.

Winds blowing out of the poleward side of the subtropical high pressure belts are deflected toward the east as they move into higher latitudes. These winds, which extend from about 35 to 60 degrees (north and south) latitude, are known as the prevailing westerlies. These winds blow throughout the year, but are strongest in winter.

Montana is located in the zone of prevailing westerlies, and it is these winds, modified primarily by near-surface effects such as friction and turbulence, that provide the wind resource in the state.

Air, like all other substances, has inertia; force is required to set it in motion. The major factors that drive the circulation of air are:

- Insolation: Energy from the sun heats the air unequally, mainly because the surfaces with which the air comes into contact heat at different rates;
- Gravitation: Unequal heating of the air produces differences in its density, and gravity causes the cooler, heavier air to sink;
- Condensation: Latent heat released by condensation of water vapor supplies a large amount of energy;
- Rotation: The earth's rotation changes the direction of air movement and produces the eastward and westward motions of air in the atmosphere.

The interaction of these major air circulation factors creates more specific forces, the balance of which determines the motion of air in a given area:

- Pressure gradient force: This force drives air from areas of high pressure to areas of low pressure;
- Coriolis force: This force, due to the rota-

- tion of the earth, deflects air to the right in the northern hemisphere;
- Centripetal force: This force arises when the air is moving in a curved, rather than straight, path along the earth's surface;
- Frictional forces: These forces include friction between the atmosphere and the earth's surface, as well as internal friction within the atmosphere.

Frictional forces are most important near the earth's surface and are the determining factors of the wind climatology at a specific location. Surface features associated with high wind speeds are mountain passes, high-elevation plateaus, long valleys extending down from mountain ranges, mountain ridges and summits, and the leeward slopes of mountain ranges perpendicular to the prevailing winds. Features associated with low average wind speeds include sheltered basins, valleys perpendicular to prevailing winds, and areas of high surface roughness.

There are four distinct wind provinces in Montana: western valley floors, eastern slopes, east and northeast plains, and exposed mountain crests. A discussion of each of these wind provinces follows.

Western Valley Floors

Most of the western third of Montana is mountainous. The region is crossed by many parallel mountain ranges with deep valleys between them. These valleys include: the Flathead, Bitterroot, and Deer Lodge valleys in western Montana; the upper Missouri River, Shields River, and Smith River valleys in the west-central portion of the state; and the Big Hole and Jefferson River valleys in southwestern Montana.

These valleys generally trend north-south or northwest-southeast and, thus, are oriented perpendicular to the prevailing wind direction. Because of their orientation, depth, and narrowness, average wind speeds in these valleys are low. Periods of air stagnation, during which there is virtually no air movement, are common in these valleys, particularly in the autumn and winter. Certain limited areas in these valleys, such as the Kalispell-Columbia Falls area and the Hellgate Canyon just east of Missoula, occasionally experience high winds due to channeling through mountain gaps. Such occurrences, however, are comparatively rare.

Representative wind monitoring sites in the western valleys include the Missoula Hoerner-Waldorf site, the Ronan Nine Pipes site, and the Kalispell Airport site. Average annual wind speeds in these areas typically range from 5 to 10 miles per hour. Average annual wind power density generally ranges from 20 to 80 watts per square meter (watts/m²).

Eastern Slopes

Air flowing over the Rocky Mountains is compressed and accelerated as it descends the eastern slopes of these mountains. When a strong pressure gradient exists, as it frequently does, these winds can become very high. The winds are strongest when channeled through east-west trending valleys.

Downslope areas are found along the eastern front of mountain ranges adjacent to broad valleys, such as in the Anaconda area and in the lower Jefferson River valley near Whitehall, as well as along the entire Rocky Mountain Front where the mountains meet the plains. This wind province actually extends well out into the plains, covering much of central Montana.

Areas where channeling of the winds by east-west mountain valleys results in stronger winds include the upper Yellowstone River valley from Livingston to Big Timber, the Browning-East Glacier-Cut Bank area, the upper Musselshell River valley around Harlowton and Judith Gap, the Jefferson River valley around Whitehall, and the Missouri River valley from Cascade to Great Falls.

Representative wind monitoring sites are the Livingston Candidate Wind Turbine site, the Bureau of Reclamation's Judith Gap and Cut Bank sites, and the Whitehall Airport site. These areas show pronounced seasonal variations in wind speed and wind power density. Highest average seasonal wind speeds occur during the winter and are generally from 12 to 25 miles per hour. Lowest average seasonal wind speeds, most-

ly from 8 to 12 miles per hour, occur during the summer. Average annual wind speeds are generally from 10 to 16 miles per hour. Average seasonal wind power ranges from between 600 and 2,000 watts/m² in winter to between 100 and 500 watts/m² in summer. Average annual wind power density is generally between 150 and 500 watts/m². Other representative sites include Yellowtail and Gibson dams, with average annual wind speeds in excess of 12 miles per hour.

Prevailing winds in these areas are generally from the southwest through west. Highest average wind speeds, likewise, are from these directions. At a given location, however, the orientation of nearby mountains may have a marked effect on the prevailing wind direction and speed.

East and Northeast Plains

The eastern slopes of the mountains give way to the east and northeast plains, which roughly occupy the corner of the state east of a Malta-Baker line. Because of the low surface roughness and low to moderate relief in this area, wind movement is dominated by pressure gradient forces. Prevailing wind directions are northwest and southeast.

Representative wind monitoring sites in this area include the Scobey Hanrahan site, the Glendive Microwave site, and the Glasgow Airport site. Average seasonal wind speeds are highest in the spring, when they are generally from 12 to 16 miles per hour. Lowest average seasonal wind speeds, between 4 and 10 miles per hour, occur in the autumn. Average annual wind speed is generally from 10 to 13 miles per hour. Average seasonal wind power density varies from about 50 to 150 watts/m² in autumn to between 100 and 300 watts/m² in the spring.

Exposed Mountain Crests

High, exposed mountain ranges and summits intercept the prevailing air flow. Air moving over a mountain range is compressed and accelerated as it passes over the crest. These effects are variable and depend on the orientation of the mountains with respect to the prevailing wind direction, the slope and elevation of the range, and the location and height of other nearby mountains.


All mountain ranges in Montana have exposed ridges and crests where average wind speed and power are likely to be high. Unfortunately, data from these areas are sparse. The most extensive data set available is the National Fire Weather


Data Library, maintained by the U.S. Forest Service. These data, however, were collected only one to three times daily, and only during the fire season. Nevertheless, the data have been analyzed by Battelle Pacific Northwest Laboratories and indicate average wind power densities ranging from 200 to more than 500 watts/m² for sites in western Montana.

Aerial surveys of tree deformation caused by winds also provide information on the wind resource at exposed mountain crests. Several indices of tree deformation, such as the Griggs-Putnam Index and the Barsch Index, have been developed to show a qualitative relationship between average annual wind speed and tree deformation. Researchers from Oregon State University in May 1981 conducted aerial surveys of most of western Montana for the Bonneville Power Administration. These surveys indicated average annual wind speeds of 14 to 20 miles per hour on most exposed ridges.

Summary

In summary, Montana may be divided into four general wind provinces: the western valleys, the eastern slopes, the east and northeast plains, and the exposed mountain crests. Maps III-1 and III-2 present generalized isopleths of average annual wind speed and wind power density in Montana. Given the state's sizable territory and the consequently low density of wind data available for the state, isopleth lines cannot be drawn with a high degree of precision. In a few instances, given areas with low data density and complex terrain, isopleths cannot be inferred at all. These maps, however, do provide a good picture, from a statewide perspective, of the relative wind potential of different parts of the state.





SITE-BY-SITE WIND ANALYSES

Wind data have been gathered at numerous sites in Montana through the years. Many of these sites were analyzed for the *Montana Wind Energy Atlas*, and the results for fifty-six of the sites are presented here. Other sites identified during this study are discussed briefly in Appendix C.

The site-by-site analyses are presented alphabetically by county and site name. This order is reflected in Table IV-1, which shows annual average wind speed (in miles per hour [mph] and meters per second [m/s]) and wind power (in watts per square meter [watts/m²]) at anemometer height for each

Table IV-1
Sites Analyzed for the Montana Wind Energy Atlas
Annual Average Wind Speed and Wind Power

| County | Site | Wind | Speed | Wind Power |
|------------|---------------------------------------|-------|-------|------------|
| | | (mph) | (m/s) | (watts/m²) |
| Beaverhead | Dillon FAA Airport* | 9.2 | 4.1 | 80.0 |
| Big Horn | Decker Coal #8 | 9.4 | 4.2 | 106.0 |
| | Spring Creek #1 | 7.3 | 3.2 | 56.7 |
| | Westmoreland Absaloka #2 | 6.3 | 2.8 | 25.8 |
| Blaine | Hays | 12.0 | 5.3 | 194.6 |
| Broadwater | Three Forks | 8.6 | 3.8 | 72.5 |
| Cascade | Great Falls Malmstrom Air Force Base* | 8.7 | 3.9 | 106.0 |
| | GREAT FALLS NWS AIRPORT* | 11.9 | 5.3 | 183.0 |
| | Salem | 10.2 | 4.6 | 139.7 |
| Chouteau | Highwood Bench | 10.5 | 4.7 | 122.6 |
| Custer | Miles City FAA Airport* | 10.5 | 4.7 | 116.0 |
| Daniels | Scobey Border* | 7.2 | 3.2 | 85.3 |
| | SCOBEY HANRAHAN | 11.6 | 5.2 | 178.3 |
| Dawson | GLENDIVE MICROWAVE* | 12.2 | 5.4 | 168.5 |

Table IV-1
Sites Analyzed for the Montana Wind Energy Atlas (cont'd.)
Annual Average Wind Speed and Wind Power

| County | Site | Wind ! | Speed | Wind Power |
|---------------|---|--------|-------|------------|
| | | (mph) | (m/s) | (watts/m²) |
| Deer Lodge | ANACONDA C-HILL | 13.3 | 6.0 | 279.8 |
| | Anaconda Highway Junction | 8.0 | 3.6 | 62.8 |
| | Anaconda Mill Creek | 9.5 | 4.2 | 95.2 |
| | ANACONDA WEATHER HILL | 17.0 | 7.6 | 517.4 |
| Fergus | Lewistown FAA Airport* | 10.1 | 4.5 | 109.0 |
| Flathead | Big Prairie | 3.4 | 1.5 | 8.4 |
| | Columbia Falls Water | | | |
| | Supply Kaking all NIVO Aliments | 6.4 | 2.9 | 48.3 |
| | Kalispell NWS Airport* | 6.9 | 3.1 | 53.0 |
| Gallatin | Bozeman FAA Airport* | 7.8 | 3.5 | 71.0 |
| Glacier ` | Blackfoot* | 16.4 | 7.3 | 432.3 |
| | CUT BANK | 12.8 | 5.7 | 217.1 |
| | CUT BANK FAA AIRPORT* | 12.5 | 5.6 | 228.0 |
| Granite | Drummond FAA Airport* | 7.2 | 3.2 | 52.0 |
| Hill | Havre NWS Airport* | 10.7 | 4.8 | 135.0 |
| Jefferson | Microwave Tower* | 10.8 | 4.8 | 237.6 |
| | WHITEHALL FAA AIRPORT* | 13.2 | 5.9 | 325.0 |
| Lake | Ronan Ninepipes | 4.5 | 2.0 | 17.0 |
| Lewis & Clark | Helena NWS Airport* | 7.8 | 3.5 | 69.0 |
| | Sieben 1* | 16.7 | 7.4 | 404.3 |
| Liberty | Whitlash | 13.6 | 6.1 | 259.6 |
| Madison | Norris Hill | 17.0 | 7.6 | 414.3 |
| Mineral | Superior NWS Airport* | 5.1 | 2.3 | 16.0 |
| Missoula | Missoula Hoerner- Waldorf #1 | | | |
| | | 5.1 | 2.3 | 30.5 |
| | Missoula NWS Airport* Missoula University | 6.3 | 2.8 | 43.0 |
| | of Montana | 6.3 | 2.8 | 48.8 |
| Park | LIVINGSTON CANDIDATE WIND TURBINE SITE* | 15.6 | 7.0 | 494.4 |
| | LIVINGSTON FAA AIRPORT* | 15.7 | 7.0 | 510.0 |
| Pondera | Heart Butte* | 18.0 | 8.0 | 649.7 |
| Powder River | Broadus Randall Ranch* | 10.1 | 4.5 | 118.9 |
| Rosebud | COLSTRIP BN* | 12.9 | 5.8 | 453.6 |
| | Western Energy #12 | 7.3 | 3.3 | 48.4 |
| | | | 3,3 | 40.4 |

Table IV-1
Sites Analyzed for the Montana Wind Energy Atlas (cont'd.)
Annual Average Wind Speed and Wind Power

| County | Site | Wind | Speed | Wind Power |
|-------------|-------------------------|-------|-------|------------|
| · | | (mph) | (m/s) | (watts/m²) |
| Silver Bow | Butte FAA Airport* | 8.1 | 3.6 | 90.0 |
| | Butte Hebgen Park | 3.7 | 1.7 | 8.9 |
| Teton | Choteau | 10.1 | 4.5 | 116.0 |
| Valley | Fort Peck* | 10.6 | 4.7 | 219.9 |
| | Glasgow Air Force Base* | 9.6 | 4.3 | 109.0 |
| | GLASGOW NWS AIRPORT* | 11.0 | 4.9 | 139.0 |
| Wheatland | JUDITH GAP | 13.0 | 5.8 | 239.2 |
| Yellowstone | BILLINGS NWS AIRPORT* | 11.4 | 5.1 | 130.0 |
| | Custer FAA Airport* | 8.7 | 3.9 | 79.0 |
| | Laurel New Farm | 7.8 | 3.5 | 63.6 |
| | Shawnee Park* | 5.9 | 2.6 | 28.2 |

NOTE:

Capitalized site names indicate high-potential sites.

Table IV-2
Sites Analyzed for the Montana Wind Energy Atlas
Wind Energy Potential Ranking by Wind Speed

| Site Name | Anemometer Height (m) | Annual Average Wind Speed (mph) |
|---|--------------------------|------------------------------------|
| HEART BUTTE, Pondera County | 11.0 | 18.0 |
| ANACONDA WEATHER HILL, Deer Lodge County | 10.0 | 17.0 |
| NORRIS HILL, Madison County | 10.0 | 17.0 |
| SIEBEN 1, Lewis and Clark County | 11.0 | 16.7 |
| BLACKFOOT, Glacier County | 9.0 | 16.4 |
| LIVINGSTON FAA AIRPORT, Park County | 17.4 | 15.7 |
| LIVINGSTON CANDIDATE WIND TURBINE SITE, Park County | 9.1 | 15.6 |
| WHITLASH, Liberty County | 10.0 | 13.6 |
| ANACONDA C-HILL, Deer Lodge County | 10.0 | 13.3 |
| WHITEHALL FAA AIRPORT, Jefferson County | 9.1 | 13.2 |
| JUDITH GAP, Wheatland County | 7.0 | 13.0 |
| COLSTRIP BN, Rosebud County | 4.0 | 12.9 |
| CUT BANK, Glacier County | 10.0 | 12.8 |
| CUT BANK FAA AIRPORT, Glacier County | 6.1 | 12.5 |

^{*} Asterisk indicates those sites at which the anemometer height was other than 10 meters. Data on wind speed and power are as recorded at the anemometer height.

Table IV-2 Sites Analyzed for the Montana Wind Energy Atlas (cont'd.) Wind Energy Potential Ranking by Wind Speed

| Site Name | Anemometer Height (m) | Annual Average Wind Speed (mph) |
|--|--------------------------|---------------------------------|
| GLENDIVE MICROWAVE, Dawson County | 4.0 | 12.2 |
| HAYS, Blaine County | 10.0 | 12.0 |
| GREAT FALLS NWS AIRPORT, Cascade County | 6.7 | 11.9 |
| SCOBEY HANRAHAN, Daniels County | 10.0 | 11.6 |
| BILLINGS NWS AIRPORT, Yellowstone County | 7.6 | 11.4 |
| GLASGOW NWS AIRPORT, Valley County | 6.1 | 11.0 |
| Microwave Tower, Jefferson County | 4.0 | 10.8 |
| Havre NWS Airport, Hill County | 6.1 | 10.7 |
| Fort Peck, Valley County | 4.0 | 10.6 |
| Highwood Bench, Chouteau County | 10.0 | 10.5 |
| Miles City FAA Airport, Custer County | 12.2 | 10.5 |
| Salem, Cascade County | 10.0 | 10.2 |
| Choteau, Teton County | 10.0 | 10.1 |
| Lewistown FAA Airport, Fergus County | 6.1 | 10.1 |
| Broadus Randall Ranch, Powder River County | 4.0 | 10.1 |
| Glasgow Air Force Base, Valley County | 4.0 | 9.6 |
| Anaconda Mill Creek, Deer Lodge County | 10.0 | 9.5 |
| Decker Coal #8, Big Horn County | 10.0 | 9.4 |
| Dillon FAA Airport, Beaverhead County | 6.1 | 9.2 |
| Great Falls Malmstrom Air Force Base, Cascade County | 4.6 | 8.7 |
| Custer FAA Airport, Yellowstone County | 10.1 | 8.7 |
| Three Forks, Broadwater County | 10.0 | 8.6 |
| Butte FAA Airport, Silver Bow County | 18.0 | 8.1 |
| Anaconda Highway Junction, Deer Lodge County | 10.0 | 8.0 |
| Bozeman FAA Airport, Gallatin County | 13.1 | 7.8 |
| Helena NWS Airport, Lewis & Clark County | 6.1 | 7.8 |
| Laurel New Farm, Yellowstone County | 10.0 | 7.8 |
| Spring Creek #1, Big Horn County | 10.0 | 7.3 |
| Western Energy #12, Rosebud County | 10.0 | 7.3 |
| Drummond FAA Airport, Granite County | 8.5 | 7.2 |
| | | |

Table IV-2
Sites Analyzed for the Montana Wind Energy Atlas (cont'd.)
Wind Energy Potential Ranking by Wind Speed

| Site Name | Anemometer Height (m) | Annual Average Wind Speed (mph) |
|---|--------------------------|------------------------------------|
| Scobey Border, Daniels County | 4.0 | 7.2 |
| Kalispell NWS Airport, Flathead County | 6.1 | 6.9 |
| Columbia Falls Water Supply, Flathead County | 10.0 | 6.4 |
| Missoula NWS Airport, Missoula County | 6.1 | 6.3 |
| Missoula University of Montana, Missoula County | 10.0 | 6.3 |
| Westmoreland Absaloka #2, Big Horn County | 10.0 | 6.3 |
| Shawnee Park, Yellowstone County | 4.0 | 5.9 |
| Missoula Hoerner-Waldorf #1, Missoula County | 10.0 | 5.1 |
| Superior NWS Airport, Mineral County | 17.7 | 5.1 |
| Ronan Ninepipes, Lake County | 10.0 | 4.5 |
| Butte Hebgen Park, Silver Bow County | 10.0 | 3.7 |
| Big Prairie, Flathead County | 10.0 | 3.4 |

NOTE: Capitalized site names indicate high-potential sites.

The rankings would have been different had all anemometers been at a standard height.

site analyzed. Table IV-2 ranks the sites according to their wind energy potential. Caution should be exercised in comparing the average speeds at sites with anemometers of different heights. (Readers wishing to determine the wind speed at a standard height of 10 meters may use the power law, discussed in Chapter V.)

Each site analysis includes a discussion of the time period of data collection, the method of data collection, and the quality of the data. Suspect data have been noted or deleted where possible; however, the quality of the data by and large reflects the quality assurance programs of the agencies that did the original data collection. Data summaries of monthly and annual average wind speed and wind power are provided. Monthly and annual wind speed distributions, showing the percentage of time the wind speed was within a given range, also are presented.

Sites where the average annual wind speed is equal to or greater than 11 miles per hour (4.9 meters per second) are considered "high potential" for purposes of this *Atlas*. For those sites with high

wind energy potential, the following data summaries also are provided:

- Diurnal wind speed frequency distributions by season;
- Directional frequency and average wind speed (including wind rose graphics).

In addition, detailed descriptions of site characteristics are presented for the high-potential sites. These descriptions generally include information on current use of the site, availability of space for further development, ease of access, and distance from transmission lines, sensitive communications facilities, and aircraft corridors.

A table showing monthly and annual Weibull distribution coefficients (scale factor "c" and shape factor "k") also is presented for each of the high-potential sites. The two-parameter Weibull distribution has been found to be a reliable mathematical approximation of actual wind speed distributions for many locations and is widely used for wind modeling purposes. (The Weibull distribution is discussed in Appendix B.)

DILLON FAA AIRPORT

BEAVERHEAD COUNTY

The Dillon airport is located approximately 5 miles northeast of Dillon at 45 15 00 N and 112 33 00 W (Site No. 1 on Map II-1). Elevation at the airport is 5,223 feet. Meteorological data were collected here for many years by the Federal Aviation Administration.

These data, primarily collected for aviation and weather forecasting uses, consist of short-term (5 minutes or less) averages of wind speed and direction, as well as other meteorological parameters. Data were gathered once per hour. The data have been analyzed by Battelle Pacific Northwest Laboratories. Because of a change in anemometer height, the data set was split into two parts for analysis: June 19, 1951, through October 29, 1963; and October 30, 1963, through June 18, 1973. Data from the latter period only were selected for inclusion in the Montana Wind Energy Atlas.

The data set for Dillon consists of summaries of observations made every third hour from October 30, 1963, through June 18, 1973. The anemometer was mounted on a ground mast at a height of 6.1 meters. The site is representative of the Jefferson River Valley from Twin Bridges to south of Dillon.

Average monthly wind speed varied from 7.6 miles per hour in July and August to 10.5 miles per hour in January. Average annual wind speed was 9.2 miles per hour.

Average monthly wind power ranged from 43.0 watts/m² in August to 114.0 watts/m² in January. Average annual wind power was 80.0 watts/m².

Table IV - 3

Monthly Wind Speed Distribution

BEAVERHEAD COUNTY - DILLON FAA AIRPORT

10/30/63 - 06/18/73

| | A | , | 7.7-17.4 7.5-16.4 7.5-16.4 8.5-19.4 9.5-20.4 0.5-35.4 0.5-35.4 0.5-35.4 0.5-40.4 | |
|------|---|---|--|---|
| YEAR | ဝဲဆင်လုဝ်လုံ | | | 9.2 4.1 80.0 |
| DEC | | | 00000000000 | 9.4 4.2 85.0 |
| NOV | | | 00000000000 | 8.7 3.9 70.0 |
| OCT | | | 00000000000 | 8.9 4.0 73.0 |
| SEP | | | 00000000000 | 8.5 3.8 67.0 |
| AUG | | | -0000000000 | 7.6 3.4 43.0 |
| JUL | | | -0000000000 | 7.6 3.4 48.0 |
| JUN | | | 00000000000 | 8.5 3.8 60.0 |
| MAY | 5.7 0.8 14.2 22.5 12.0 | - 1 5 0 0 0 0 0 0 c c c c c c c c c c c c c | -0000000000 | 9.4 4.2 83.0 |
| APR | | | -0000000000 | 10.3 4.6 112.0 |
| MAR | | | 00000000000 | 10.1 4.5 101.0 |
| FEB | | | 00000000000 | 9.8 4.4 92.0 |
| JAN | 5.6 0.6 16.1 14.6 | 00004400000 0004400000 | 00000000000 | 10.5 4.7 114.0 |
| | CALM (<1. 3.4-5 3.4-5 7.8-9 10.1-10.1-10.1-10.1-10.1-10.1-10.1-10.1 | 3272318 | H 32.4-34.4 O 34.7-36.7 U 36.7-38.9 R 11.2-41.2 H 1.4-41.2 H 1.6-45.6 H 1.9-56.8 57.0-68.0 79.4-90.4 | AVERAGE SPEED (MPH) AVERAGE SPEED (M/SEC) AVERAGE WIND POWER (WATTS/M**2) |

ANEMOMETER HEIGHT = 20.0 FEET = 6.1 METERS SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

DECKER COAL #8 BIG HORN COUNTY

The Decker Coal #8 air monitoring site is located approximately 4 miles northeast of Decker at 45 03 19 N and 106 48 17 W (Site No. 2 on Map II-1). Elevation at the site is 3,480 feet. The site was established by Decker Coal Company to monitor concentrations of particulates in the air around the

Wind parameters have been monitored long enough to give a good picture of the wind resource in the area. Wind data from December 1, 1980, through May 31, 1982, were available for analysis. The data set consists of hourly averages of wind speed and wind direction, manually reduced from stripchart records, at an anemometer height of 10 meters. Data recovery was excellent, ranging from 85.5 percent in January to 100.0 percent in February, September, and October. Overall data recovery was 95.9 percent.

Average annual wind speed at this site was 9.4 miles per hour. Monthly wind speeds varied from 6.6 miles per hour in August to 11.8 miles per hour in May.

Average annual wind power was 106.0 watts/m². Monthly average wind power ranged from 37.0 watts/m² in September to 161.4 watts/m² in May.




Table IV - 4 Monthly Wind Speed Distribution BIG HORN COUNTY - DECKER COAL #8

12/01/80 - 05/31/82

ANEMOMETER HEIGHT = 10 METERS = 33 FEET NUMBER OF OBSERVATIONS = 12589
PERCENTAGE DATA RECOVERY = 95.9

SPRING CREEK #1


BIG HORN COUNTY

The Spring Creek #1 air monitoring site is located approximately 7 miles north of Decker at 45 07 02 N and 106 52 32 W (Site No. 5 on Map II-1). Elevation at the site is 3,838 feet. Wind data have been gathered at the Spring Creek Coal Company mine site since January 1, 1981. Data through December 31, 1981, were available for analysis.

The data set contains hourly averages for wind speed and wind direction at an anemometer height of 10 meters. Data recovery for the year was 90.9 percent and was greater than 80.0 percent during all months except November. Although the monitoring period was short, it was adequate to provide a good indication of the wind resource at this location.

Average annual wind speed was 7.3 miles per hour. Monthly average wind speeds were from 4.5 miles per hour in January to 9.9 miles per hour in May. April through June and September through October were the windiest months at this site.

Average monthly wind power ranged from 26.4 watts/m² in January to 107.1 watts/m² in May. Annual average wind power was 56.7 watts/m².



SATEMAS/SECOND

Table IV - 5 Monthly Wind Speed Distribution BIG HORN COUNTY - SPRING CREEK #1

01/01/81 - 12/31/81

| | 7-1-3-4-4-3-4-4-3-4-4-4-4-4-4-4-4-4-4-4-4 | |
|------|--|---|
| YEAR | 00000000000000000000000000000000000000 | 7.3 3.2 56.7 90.9 |
| DEC | 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 | 6.1 2.7 3.54.1 56 |
| NOV | 00000400440000000000000000000000000000 | 6.2 2.8 41.8 43.5 |
| OCT | 00-1-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2 | 7.2 3.2 45.7 |
| SEP | 00000 | 7.5 3.4 45.1 99.2 |
| AUG | 0000 | 6.9 3.1 32.5 99.7 |
| JUL | 000001111111111111111111111111111111111 | 7.7 3.4 38.7 99.7 |
| JUN | 00000000000000000000000000000000000000 | 9.2 4.1 84.2 90.1 |
| MAY | 0001-000-000-000-000-000-000-000-000-00 | 9.9 4.4 107.1 85.3 |
| APR | 00000000000000000000000000000000000000 | 8.2 3.7 78.3 96.7 |
| MAR | 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0 | 6.5 2.9 57.3 99.1 |
| FEB | 00000444804440000000000000000000000000 | 6.9 3.1 73.4 99.7 |
| JAN | 00000000000000000000000000000000000000 | 4.5 2.0 26.4 93.5 |
| | CALM 0 | AVERAGE SPEED (MPH) AVERAGE SPEED (M/SEC) AVERAGE WIND POWER WAITS/M**2) ERCENT DATA RECOVERY |
| | | σ <u>- </u> |

SOURCE: GEORESEARCH, INC.

ANEMOMETER HEIGHT = 10 METERS = 33 FEET NUMBER OF OBSERVATIONS = 7964 PERCENTAGE DATA RECOVERY = 90.9

WESTMORELAND ABSALOKA #2

BIG HORN COUNTY

The Absaloka #2 air monitoring site is located approximately 30 miles east of Hardin at 45 46 27 N and 107 04 57 W (Site No. 6 on Map II-1). Elevation at the site is 3,539 feet. The site was established by Westmoreland Resources to monitor particulate concentrations in the air around the Absaloka mine.

Wind data have been gathered at this site since August 1, 1980. Data through March 29, 1982, were available for analysis. The data set contains hourly averages for wind speed and wind direction, which were reduced from stripchart records. Anemometer height was 10 meters. Data recovery was excellent, ranging from 96.9 percent in October to 100.0 percent during several months. Overall, 99.3 percent of the available data were recovered.

Average annual wind speed was 6.3 miles per hour. Monthly average wind speed ranged from 5.5 miles per hour in December to 7.8 miles per hour in April. The windiest months were April through June.

Average monthly wind power varied from 18.9 watts/m² in November to 43.2 watts/m² in April. Annual average wind power was 25.8 watts/m².




Table IV - 6

Monthly Wind Speed Distribution

BIG HORN COUNTY - WESTMORELAND ABSALOKA #2

08/01/80 - 03/29/82

| | ⇒ 0 | `w œ | مبه | | ٥٥ | гνο | . ⇒. | ب م | ·- | ۸'n | ٥٥ | نه د | 0, | ٠i= | 9 | نونو | | | | | | |
|------|------------|-------------|-----------------|-----------|---------------|------|---------------|-------------|----------|----------|-------------|----------|------|------|------|------|---------|-------------|---------------|-----------------------|--------------|----------|
| | | | | | | | | | | | | | | | | | | | | | | |
| | CAL 0.1 | | ٥, ۵ | 5 € | ώĽ | ·- · | 0. | ύa | :=: | ω, | ٠. | | 9. | ó؞ | . 17 | ~ | | | | | | |
| YEAR | 0.0 | 10.5 | 14.4 | 11.4 | 9.1 6.8 | 0.0 | 80.0 | , v | <u> </u> | 9.0 | ٥,٠ | | 0.5 | 0.0 | 0.0 | 0.0 | | 6.3 | 2.8 | | 25.8 | 99.3 |
| DEC | 0.0 | | • • | | | • | | • | | • | • | | • | • | | | | 5.5 | 2.5 | , | 20.9 | 100.0 |
| NOV | 0.0 | | | | | | | | | • | ٠ | | | | | | | 5.7 | 5.6 | | 18.9 | 7.66 |
| OCT | 0.00 | 100 | ± c | VΝ | 00 | 5.2 | 8 | ر - در د | 0.0 | 1.0 |) - - | | 0.1 | 800 | 0.0 | 0.0 | | 4.9 | 2.9 | , | 26.9 | 6.96 |
| SEP | 0.0% | | | | | | | • | | • | • | | | • | | | | 9.9 | 2.9 | | 25.8 | 99.2 |
| AUG | 0.0 | | | | | | | • | | • | • | | | • | | | | 6.3 | 2.8 | | 21.9 | 97.9 |
| JUL | 0.0 | າຜー | 12.8 | o — | - | 4.3 | 5.6 | 9.0 | 0.5 | 0.3 | 0.0 | | 0.1 | - 0 | 00 | 0.0 | | 6.1 | 2.7 | | 19.9 | 100.0 |
| NUC | 0.0 | | | 'nκ | | | | | | | • | | | | | | | 7.4 | 3.3 | | 34.2 | 100.0 |
| MA∀ | 0.00 | | | | | • | | • | | • | • | | | • | | | | 7.5 | 3.4 | | 41.1 | 6.66 |
| APR | 0.00 | , 0, « | | 1, 20. | 4.6 | 6.5 | . | | | = | ر بار | 0.0 | 9.0 | 0.0 | 000 | 0.0 | | 7.8 | 3.5 | | 43.2 | 100.0 |
| MAR | 0.0 | 10.9 2.9 | 27 | 10.7 | 0, 80 7, 1 | 2 5 | 2.7 | ر در د | | 0.7 | | 0.0 | 0.1 | 0.7 | 00 | 00 | | 4.9 | 2.8 | | 28.4 | 99.1 |
| FEB | 0.0 | | | | | • | | • | | • | • | | | • | | | | 6.3 | 2.8 | | 24.3 | 100.0 |
| JAN | 0.0 | 7.00 | | | | | | • | | | | | | | | | | 5.7 | 2.6 | | 23.2 | 100.0 |
| | A-1. | S 2.1-3.0 | . . | 6.1-7 | 7.1-8 | 1-10 | 11.1-12 | 12, 1-13 | 14.1-15 | 15.1-16 | 16.1-17 | 18, 1-19 | 1-20 | 1-25 | 1-35 | 1-40 | AVERAGE | SPEED (MPH) | SPEED (M/SEC) | AVERAGE WIND POWER | (WATTS/M**2) | RECOVERY |
| | | | | | | | | | | | | | | | | | | | | | | |

SCHEO MUHUNONIO

ANEMOMETER HEIGHT = 10 METERS = 33 FEET V NUMBER OF OBSERVATIONS = 14438 PERCENTAGE DATA RECOVERY = 99.3

HAYS BLAINE COUNTY

The Hays site is located seven miles north of Hays and about twenty-eight miles south of Fort Belknap at 48 06 17 N and 108 42 43 W (Site No. 150 on Map II-1). Elevation at the site is 3,150 feet. This monitoring site is part of the wind monitoring program of the Montana Department of Natural Resources and Conservation.

The site is on top of McGuire Hill in a rolling grassland area typical of eastern Montana. It has excellent exposure to winds from all directions. The site is typical of a series of low ridges (drainage divides) that run approximately northeast-southwest between the Little Rockies and Bears Paw Mountains. The site is right next to state Highway 66. Winter access is good.

The site is located on the Fort Belknap Reservation. Electrical service in the area is provided by the Big Flat Electric Cooperative. A 69 kV line runs next to the site and a 230 kV line, 28 miles to the north, runs between Fort Peck and Havre. There is no commercial airport nearby.

The site was installed December 14, 1983. Wind data were collected from January 1, 1984 to July 15, 1985. A Met One anemometer and a Campbell Scientific datalogger were used. The anemometer height was 33 feet.

Data recovery was poor to excellent, ranging from 31.3 percent in September to 100.0 percent in October. Overall data recovery was 87.5 percent.

Average monthly wind speeds ranged from 8.9 miles per hour in August to 13.9 miles per hour in December. Average annual wind speed was 12.0 miles

Average monthly wind power ranged from 72.5 watts/m² in August to 336.4 watts/m² in December.

Average wind speed did not vary much between seasons. Average seasonal speeds were 10.7 miles per hour in the summer, 11.4 miles per hour in the au-

tumn, 13.0 miles per hour in the winter, and 12.0 miles per hour in the spring. In the winter and spring, the highest wind speed occurred in early afternoon. High winds in the summer were a little later than in the winter and spring, and high winds in the autumn were a little earlier. Diurnal range of average wind speeds was greatest in the summer and least in the winter.

Valid wind direction data were not collected between January 30, 1984 and July 20, 1984; the effect of this on the wind direction statistics is unknown. According to the available data, the wind blew most frequently from the south-southwest through the west-southwest. Winds were least common from the east-northeast through the south-southeast. By direction, average wind speeds ranged from 6.7 miles per hour from the south-southeast to 16.3 miles per hour from the northwest.




Table IV - 7

Monthly Wind Speed Distribution BLAINE COUNTY - HAYS

01/01/84 - 07/15/85

| | JAN | FEB | MAR | | MAY | N)C | 100 | AUG | SEP | 100 | AON | 떮 | YEAR | |
|------------------------|-------|-------|----------|-------|-------------|-------|--------|------|------|--------|-------|-------|-------|-----------|
| CALM | 0.4 | 0.1 | 0.0 | 0.1 | 1.8 | 9.0 | 0.0 | 2.0 | 3.1 | 0.7 | 0.4 | 0.4 | 9.0 | CALM |
| 0.1-1.0 | 1.0 | 1.2 | 0.3 | | 0.3 | 0.5 | 0.2 | 0.4 | 0.0 | 0.8 | 0.8 | 1.6 | 9.0 | 0.1-0.4 |
| 1.1-2.0 | 3.0 | 1.9 | 1.6 | | 0.8 | 0.7 | 6 0 | 0.4 | 4.0 | 2,3 | 1.2 | 1.9 | 1.5 | 0.5-0.9 |
| 2.1-3 | 2.8 | 2.7 | 4.3 | | 2.1 | | 2.6 | 4.3 | 1.8 | 2.4 | 2.9 | 3.1 | 2.7 | 1.0-1.3 |
| _ | 4.7 | 5.1 | 6.8 | | 4.7 | 5.6 | 4.3 | 7.8 | 5.3 | ა ზ | 4.5 | 4.7 | 5.2 | 1.4-1.8 |
| E 4.1-5.0 | 5,3 | 4.0 | 6.9 | | 5.4 | 4.7 | 6.8 | 10.2 | 6,3 | 5.1 | 2.9 | 5.9 | 5.6 | 1.9- 2.2 |
| 5.1 | 5,3 | 5.8 | 7.7 | | 7.6 | 7.4 | 6.6 | 8.2 | 12.4 | 8.7 | 7.0 | 7.7 | 7.5 | 2.3- 2.7 |
| 6.1-7. | 4.5 | ວີ | 7.5 | | 5,3 | 6.4 | 8.4 | 6.4 | 10.2 | 6,3 | 4.5 | 6.1 | 6.2 | 2.8- 3.1 |
| 7.1-8 | 4.9 | 6.7 | еў 88 | | 8.7 | 6.5 | 9,5 | 11.5 | 11.1 | 5.4 | 7.0 | 3.4 | 7.2 | 3.2-3.6 |
| ω, | ວີ | 6.1 | 6,3 | | 5.8 | 6.4 | 8.2 | 8.2 | 4.4 | 4.3 | 6.2 | 3,9 | 6.0 | 3.7- 4.0 |
| 9.1-10 | 4.7 | 6.2 | 7.0 | | 7.2 | 0.9 | 8,5 | 8.2 | 6.7 | 7.7 | 4.5 | ວີ | 6.5 | 4.1- 4.5 |
| L 10.1-11.0 | 3.2 | 4.4 | 4.3 | | 5.1 | 9.9 | 5.6 | 4.3 | 2.2 | 6.5 | 4.1 | 2.0 | 4.5 | 4.6- 4.9 |
| 11.1-12 | | 5,9 | 4.7 | | 4.7 | 5.4 | S S | 4.5 | 6.7 | က် | 4.5 | 3.2 | 5.0 | 5.0- 5.4 |
| 12.1-13 | | 4.3 | 3,8 | | 4.1 | 4.9 | 3.8 | 3.5 | 1.8 | 4.7 | 2.9 | 2.8 | 9.0 | 5.5-5.8 |
| 13,1-14 | | 5.2 | 4.6 | | 5,3 | 4.2 | 9°0 | 9.9 | 2.2 | 5°0 | 4.5 | 4.0 | 4.8 | 5.9-6.3 |
| H 14.1-15.0 | | 2.8 | 3.7 | | 3.0 | 3.5 | 3.0 | 2.7 | 2.2 | 3.2 | 2.5 | 2.8 | 3.1 | 6.4- 6.7 |
| 0 15.1-16.0 | | 4.2 | 3,3 | | 2.6 | 3.4 | 2.1 | 2.7 | 2.7 | 5.6 | 1.7 | 2.8 | 3.0 | 6.8- 7.2 |
| U 16.1-17.0 | | 4.0 | 3.1 | | 3,5 | 3.1 | 2.4 | 2.1 | 1.8 | 5.6 | 2.5 | 2.8 | 3.2 | 7.3- 7.6 |
| 17. | | 3.0 | 3.4 | | 2.2 | 2.4 | 5.6 | 1.4 | 1.8 | 5.6 | 1.7 | 3.2 | 2.7 | 7.7- 8.0 |
| 18.1-19.0 | | 3.6 | 3.5 | | 2.6 | 5.6 | 3.0 | 0.8 | 0.9 | 3,9 | 3,3 | 3.0 | 3.2 | 8.1-8.5 |
| 19,1-20,0 | | 2.3 | 2.5 | | 2.0 | 2.5 | 1.8 | 0.2 | 1.3 | 2.4 | 3,3 | 3.4 | 2.3 | 8.6-8.9 |
| 20.1-25.0 | | 6.6 | 4.9 | | 8.9 | 9.5 | 5.9 | 2.7 | 2 6 | 8.5 | 20.2 | 14.5 | ထ | 9.0-11.2 |
| 25.1-30.0 | | 3.5 | 1.4 | | 4.5 | 3.9 | 0.7 | 0.4 | 0.0 | 2.2 | 4.1 | 6,3 | 3.6 | 11.3-13.4 |
| 30.1-35.0 | | 1.1 | 0.1 | | 5 .8 | 1.0 | 0,3 | 0.2 | 0.0 | 0.5 | 1.7 | 2.6 | 1.4 | 13.5-15.6 |
| 35.1-40.0 | 9.0 | 0.4 | 0.1 | | 0.7 | 0.2 | 0.1 | 0.0 | 0.4 | 0.3 | 0.8 | 1.3 | 0.5 | 15.7-17.9 |
| >40.0 | 0,3 | 0.2 | 0.0 | | 0.4 | 0.1 | 0.0 | 0.2 | 0.0 | 0.0 | 0.0 | 6.0 | 0.2 | >17.9 |
| AVERAGE | | | | | | | | | | | | | | |
| SPEED (MPH) Average | 13.2 | 12.3 | 10.4 | 13.5 | 12.2 | 12.1 | 10.3 | 8.9 | 9.2 | 11.3 | 13,7 | 13.9 | 12.0 | |
| SPEED (M/SEC) | 5,9 | 5.5 | 4.6 | 6.0 | 5,5 | 5.4 | 4.6 | 4.0 | 4.1 | 5.0 | 6.1 | 6.2 | 5,3 | |
| WIND POWER | | | | | | | | | | | | | | |
| (WATTS/M**2) | 267.4 | 201.0 | 114,3 | 262.9 | 214.4 | 173.6 | 99.5 | 72.5 | 92.2 | 148.3 | 261.1 | 336.4 | 194.6 | |
| RECOVERY | 7.66 | 90.1 | 99.2 | 6.66 | 99.3 | 78.1 | 99.0 | 8.89 | 31.3 | 100.0 | 33.6 | 6.66 | 87.5 | |
| ייני עלדישישיערער | i Li | | | | | | | | | | | | | |

ANEMOMETER HEIGHT = 10 METERS = 33 FEET NUMBER OF OBSERVATIONS = 11726 PERCENTAGE DATA RECOVERY = 87.5

Table IV - 8

Percentage Frequency Summary for Wind Speed

BLAINE COUNTY - HAYS

(WINTER)

01/01/84 - 07/15/85

| į | SPEED M/SEC) | | 5.2 | 5.2 | 5 | 5.4 | 5.6 | 5.7 | 5.8 | 2,8 | 5.8 | 28 | 0.1 | 6.4 | 6.7 | 8.9 | 8.9 | 6.7 | 6.2 | 5.8 | 5.5 | 5,5 | 5.4 | 5.4 | , ro | 5.3 | | ထိ |
|----------------------------|-----------------|----------|------|-----------------|--------|------|--------|--------|------|----------|---------|------|------|------|--------|--------|------|------|-------|----------|------|------|------|------|--------|------|---------|-------------|
| | | | 11.7 | 11.6 | 11.8 | 12.2 | 12.5 | 12.7 | 13.0 | 13.0 | 13.0 | 13.1 | 13.5 | 14.3 | 15.0 | 15,3 | 15.2 | 14.9 | 13.8 | 12.9 | 12,4 | 12.4 | 12.2 | 12.1 | 12.3 | 11.8 | ! | 13.0 |
| >40.0 | >17.9 | <u>;</u> | 0.0 | 0.0 | 0.0 | 0.0 | 0.7 | 0.7 | 0.7 | 0.7 | 0.7 | 0.0 | 0.0 | 0.0 | 0.0 | 0.7 | 0.0 | 0.7 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.7 | 1.4 | 0.0 | (| e. 0 |
| 35.1- 40.0 | 15.7- 17.9 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 1.4 | 0.0 | 0.7 | 2.1 | 2.1 | 3.4 | 1.4 | 0.0 | 0.7 | 1.4 | 0.7 | 0.7 | 0.0 | 0.0 | 0.0 | (| 9.0 |
| 30.1- 35.0 | 13.5- 15.6 | | | | | | | | | | | | | | | | | | | | | | | | | 2.1 | • | 2,3 |
| 25.1- 30.0 | | | 6,3 | 2.8 | 3,5 | 4.2 | 4.2 | 2.1 | 3,5 | 3.5 | 2.8 | 4.2 | 4.2 | 5.6 | 2,8 | 6.2 | 5,5 | 5,5 | 2.1 | 2.1 | 0.0 | 1.4 | 4.1 | 2.1 | 3.55 | 4.3 | , | 3.6 |
| 20.1- 25.0 | 9.0- 11.2 | | | | | | | | | | | | | | | | | | | | | | | | | 8.6 | • | 12.6 |
| 18.1- 20.0 | 8.1- 8.9 | | 2.1 | | | | | | | | | | | | | | | | | | | | | | | | • | 6. |
| (MPH) 16.1- 18.0 | 7.2- 8.0 | | 4.9 | | | | | | | | | | | | | | | | | | | | | | | | | 0 |
| SPEED 14.1- 16.0 | 3 | | 6.3 | 4.9 | 4.2 | 4.9 | ന് | 6.9 | 7.6 | ω | 3.5 | 6.3 | 5.6 | 6,3 | ლ ზ | 6.9 | 11.0 | 0.6 | 9.7 | 7.6 | 5,5 | 4.1 | 6.9 | ນ້ຳ | 7.0 | 7.9 | , | 0. 0 |
| WIND 12.1- 14.0 | | | 11.8 | 0.6 | დ ზ | 6,3 | 5,6 | 6.9 | 0.6 | 9.0 | 10.4 | 9.7 | 9.7 | 9.1 | 7.6 | 0.6 | 13.1 | 0.6 | 9.7 | ω | 8°3 | ზ | 12.4 | 6.2 | 8 5 | 6.4 | ć | x x |
| 10.1- 12.0 | 5.4 | | H | 0.0 | 6.9 | 7.6 | 0.6 | 6.9 | 8,3 | 8°3 | 12.5 | 9.0 | 5.6 | 6.3 | 6.2 | 3.4 | 2.8 | 4.1 | 6.9 | 14.5 | 11.7 | 14.5 | 6.9 | 9.7 | 6.6 | 8.6 | 6 | ν × |
| 8.1- 10.0 | 3.6- | | 12.5 | 12.5 | 14.6 | 13.2 | 11.8 | 11.1 | 11.1 | 16.0 | 13.9 | 11.8 | 9.7 | 6,3 | 4.8 | 4.8 | 4.8 | 0.6 | 6.9 | 0.0 | 13.8 | 10.3 | 11.0 | 12.4 | 10.6 | 17.1 | 6 | 8.01 |
| 6.1- 8.0 | 2.7- | | 10.4 | :: 8: 1:8 | 12.5 | 13.9 | 11.1 | 14.6 | 12.5 | 11.8 | ж Э | 6.9 | 9.7 | 7.0 | 4.1 | 4.1 | 7.6 | 4.00 | 9.7 | 7.6 | 11.0 | 15.2 | 13.1 | 16.6 | 17.6 | 7.1 | • | 10.4 |
| 4.1- | 1.8-2.7 | | 14.6 | 13.2 | 14.6 | 9.7 | 14.6 | 11.1 | 12.5 | 6.9 | α ., | 13.9 | 11.1 | 11.2 | 7.6 | 9.7 | 4.1 | 9.7 | ω | 11.7 | 12.4 | 9.7 | 10.3 | 10.3 | 14.1 | 12.1 | 9 | 10.9 |
| 2.1- 4.0 | 0.9- | | 6,9 | 0.6 | 6.9 | 10.4 | ლ დ | დ ო | 7.6 | 6.3 | 5,6 | 6,3 | 7.6 | 4.9 | 0.6 | & 3 | 6.9 | 6.2 | 0.6 | 7.6 | 5.5 | 6.9 | 10.3 | 10.3 | 4.9 | 10.7 | , | `` |
| 0.1-2.0 | 0.1- | | 4.2 | 4.2 | 2.1 | 2.8 | 2.1 | 2.1 | 0.7 | 4.2 | 6,3 | 3.5 | 2.1 | 5.6 | ນ | 6.2 | 6.9 | 4.1 | 8 | 3.4 | 3,4 | 2.1 | 2.8 | 1.4 | 2 | 4.3 | , | 3.0 |
| CALM | CAUM | | 0.0 | 0.0 | 0.7 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.7 | 2.1 | 1.4 | 1.4 | 0.0 | 0.0 | 0.7 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | ć | ຕຸ້ |
| | | | ⊷ (| 7 | m | 4 | വ | ဖ | ~ | ∞ | 6 | ខ្ព | 11 | 15 | 13 | 14 | 12 | 91 | 17 | <u>∞</u> | 6] | ನ | 7 | 22 | 33 | 24 | | TOURS |
| | | | | | | | | | | | I | | 0 | | _ | | ∝ | | | | | | | | | | 1 1 1 1 | ALL HUUKS |

Table IV - 9

Percentage Frequency Summary for Wind Speed BLAINE COUNTY - HAYS

AINE COUNTY - HAN (SPRING)

01/01/84 - 07/15/85

| i | AV SPEED M/SFC) | , | 4.7 | 4.7 | 1.7 | 1.7 | 1.7 | 4.6 | 5 | 1.7 | 5.2 | 5.7 | 5.1 | 5.1 | 5.3 | 5.5 | 6.4 | 5.4 | 2 | 2.5 | 6.3 | 5.2 | .7 | 9. | .7 | | 5.4 |
|-------------------------|-----------------------|--------|------|------|------|------|------|------|------|------|--------|------|------|------|--------|------|------|------|------|---------|------|----------|---------|---------|------|------------|-----------|
| : | SPEED S | | | | | | | | | | | | | | | | | | | | | | | | | 10.7 | 12.0 |
| >40.0 | >17.9 | | | | | | | | | | | | | | | | 0.0 | | | | | | | | | | 0.2 1 |
| 35.1- 40.0 > | 15.7- | • | 1.1 | 0.5 | 1.1 | 1.1 | 0.5 | 0.0 | 0.0 | 1.6 | 1.1 | 0,5 | 1.6 | 1.1 | 1.1 | 1.6 | 0.0 | 0.5 | 0.5 | 0.5 | 0.5 | 1.1 | 0.0 | 0.0 | 0.0 | 0.0 | 0.7 |
| 30.1- 35.0 | 13.5- 15.6 | • | 0.5 | 1.6 | 0.0 | 0.0 | 0.5 | 1.1 | 1.1 | 1.6 | 0.5 | 2.7 | 3,3 | 4.9 | 3,3 | 2.7 | 3.8 | 2.7 | 3,3 | 1.6 | 1:1 | 0.5 | 1,1 | 0.0 | 0.0 | 1.1 | 1.6 |
| 25.1- 30.0 | 11.2- | | 1.6 | 0.0 | 2.2 | 2.7 | 1.6 | °, | 1.1 | 1:1 | 1.6 | 3,3 | 3,8 | 2.2 | დ ო | 4.9 | 5.4 | 4.9 | 5.4 | 5,4 | 4.9 | 3,3 | 2.2 | 2.7 | 1:1 | 1.7 | 3.0 |
| 20.1- 25.0 | 9.0- | ! ! | | | | | | | | | | | | | | | 10,3 | | | | | | | | | | 8.6 |
| | 8.1-8 | | | | | | | | | | | | | | | | 8.2 | | | | | | | | | | 5.5 |
| (MPH) 16.1- 18.0 | | | 5.4 | 4.9 | 2.2 | 3,3 | 6.0 | გ | 3,8 | 0.9 | φ • | 6.0 | 5,5 | 8 | 9.2 | 11.4 | 9.2 | 7.6 | 8.7 | 8.7 | 5,4 | 9.9 | 2.2 | 4.9 | 6,1 | 6.7 | 6,3 |
| SPEED 14.1- 16.0 | 6.3 7.2 | ! | 5.4 | 4.9 | 4.3 | 3°8 | 5,4 | 4.4 | 6.0 | 6.0 | 7.1 | 2.7 | 4.9 | 3,3 | 8.7 | 7.6 | 10.3 | 13.6 | 9.2 | 9.8 | 6.5 | 1.6 | ي. ش | 5.5 | 4.4 | 6.1 | 6.1 |
| WIND 12.1- 1 14.0 | 5.4- 6.3 | ; | 4.9 | 10.9 | 9.8 | 10.9 | 6,5 | 8.2 | 9,3 | 7.7 | 9.9 | 8.2 | 8.2 | 7.1 | 7.1 | 9.5 | 10.3 | 8.2 | 11.4 | 13.6 | 10.9 | 10.4 | 9,3 | α 8. | 7.7 | 6.7 | 8.8 |
| 10.1- 12.0 | 4.5- 5.4 | ; | 8.2 | 7.1 | 9.8 | 7.1 | 8.2 | 8.2 | 7.1 | 0.9 | ლ ტ | 11.5 | 7.7 | 6.6 | 6,5 | 8.7 | 10.9 | 10.9 | 8.7 | 9.5 | 12.5 | 14.2 | 12.0 | 6.6 | 11.6 | 7.8 | 9,3 |
| 8.1- 10.0 | | | 8.6 | 10.9 | 13.0 | 14.1 | 15.8 | 19.1 | 13.7 | 11.0 | 9,3 | 10.4 | 11.5 | 8.8 | 10.3 | တ္ | 6.5 | 7.1 | 10.9 | 9. 8 | 11.4 | 18.0 | 20.8 | 19.2 | 19.3 | 12.8 | 12.6 |
| 6.1- 8.0 | 2.7- | • | 18.5 | 12.0 | 17.4 | 19.6 | 18,5 | 20.2 | 21.4 | 15.4 | 10.4 | 9,3 | 11.0 | 7.1 | 10.9 | 10.3 | 10.3 | 8.2 | 8,7 | 13.0 | 12.5 | 17.5 | 18.0 | 20.3 | 15.5 | 17.2 | 14.3 |
| 4.1- 6.0 | 1.8- | • | 20.1 | 20.1 | 14.1 | 16.8 | 18.5 | 16.4 | 14.8 | 16.5 | 13.2 | 13.7 | 6.6 | 14.8 | 7.6 | 8.2 | 8.2 | 10.3 | 7.6 | 5.4 | 8.6 | <u>ه</u> | 10.9 | 11.5 | 17.7 | 19.4 | 13.1 |
| 2.1-4.0 | 0.9- 1.8 | ; | 8.7 | 14.1 | 11.4 | 9.8 | 8.2 | 9.0 | 6.6 | 12.6 | 14.3 | 9,3 | 8.2 | 7.1 | 9.2 | 4.3 | 5.4 | 4.9 | 4.9 | 0.9 | 6.5 | 3.8 | 7.1 | 7.1 | 3,9 | 5.6 | 7.9 |
| 0.1-2.0 | 0.1- | • | 2.7 | 0.5 | 1.6 | 1.1 | :: | 1:1 | 1.6 | ကို | 2.2 | 2.2 | 1.6 | 1.6 | 0.5 | 1:1 | 0.5 | 0.0 | 0.5 | 0.5 | 0.0 | 1.6 | 2.2 | 1:1 | 1:1 | 2.2 | 1.4 |
| CALM | CALM | ! | 0.5 | 0.5 | 0.5 | 0.5 | 0.5 | 0.5 | 0.5 | 0.5 | 1.1 | 0.5 | 1:1 | 0.5 | 0.5 | 0.5 | 0.5 | :: | 0.0 | 0.0 | 0.0 | 0.5 | 1:1 | 1.6 | 1:1 | 9.0 | 9.0 |
| | | | - | 2 | m | 4 | S | 9 | 7 | ∞ | 6 | 10 | I | 12 | 13 | 14 | 15 | 16 | 11 | 18 | 19 | 2 | ฆ | 25 | ຄ | 24 | ALL HOURS |
| | | | | | | | | | | | × | | 0 | | _ | | ~ | | | | | | | | | | ALL 1 |

Table IV - 10

Percentage Frequency Summary for Wind Speed

BLAINE COUNTY - HAYS

(SUMMER)

01/01/84 - 07/15/85

| AV | SPEET (M/SEC | 4.1 | , m, u | 3.8 | ب ب ب | د. 4 4. 6 | 5.1 | 5,3 | ກຸ | 4 - | ຸ້ອ | 5.9 | 5.7 | 5.7 | ່ວ່ | 8 | 5.0 | 4.4 | 4.4 | 4.2 | 4.8 |
|----------------------------------|-----------------|------|------------------|---------|-------------|--------------|------|------|--------|--------------|---------------|------|------|------------|--------------|------|----------|--------|--------|------|---------|
| AV | SPEED (MPH) | 9.7 | 0 0 0 0 | 9.00 | 7.9 | 10.4 | 11.3 | 11.9 | 11.8 | 12.1 | 13.1 | 13,3 | 12.8 | 12.8 | 12. | 13.0 | 11.2 | 6.6 | φ 0 | 9.4 | 10.7 |
| >40.0 | >17.9 | 000 | | 0.0 | 0,0 | 000 | 0.9 | 0.0 | 0.0 | 0 0 | 000 | 0.0 | 0.0 | 0.0 | 0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 35.1- 40.0 | 15.7- 17.9 | 000 | 000 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0 0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.1 |
| 30.1- 35.0 | 13.5- 15.6 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 6.0 | 6.0 | æ ο | 90 | 0.0 | 0.0 | 0.0 | 0 | .8 | 3.6 | 0.0 | 0.0 | 0.0 | 0.6 |
| 25.1- 30.0 | 11.2- 13.4 | 0.00 | 000 | 0.0 | 0.0 | 2.7 | 4.5 | 4.6 | 4.6 | 000 | 2.7 | 4.5 | 0.0 | 6.0 | ر د د | 0.0 | 0.0 | 6.0 | 0.0 | 0.0 | 1.2 |
| 20.1- 25.0 | 9.0- 11.2 | 2.7 | ່ເພ | 2.7 | 2.7 | /•/ 6.3 | 6.6 | 9.5 | ۳ و | 13.4 | 13.5 | 14.4 | 18.0 | 14.4 | ວາ ເ ວາ ເ | 9.1 | 1.8 | 3.7 | 5,5 | 2.8 | 7.5 |
| 18.1- 20.0 | 8.1- 8.9 | 2.7 | | | | | | | | | | | | | | | | | | | 4.2 |
| (MPH) 16.1- 18.0 FRS/SF | 7.2-8.0 | 1.8 | 2.7 | 0.0 | 2.7 | /. 8.1 | 4.5 | 7.3 | 7.4 | 6,3 | 0.0 | 6.6 | 7.2 | 0.0 | 2 | 10.9 | 5,5 | 3.7 | 0.9 | 3.7 | 4.9 |
| SPEED 14.1- 16.0 | • | 7.1 | 2.7 | 2.7 | 6.0 | 4.5 2.5 | 4.5 | 7.3 | 7.4 | າບຸດ 4 + | 15,3 | 8.1 | 8.1 | 0 6 | 0.01 | 11.8 | 6.4 | 2,8 | 1.8 | 4.6 | 5.9 |
| MIND 12.1- 14.0 | 5.4- | 8.0 | 5.3.4 | 4.5 | 6,3 | 5.4 5.4 | 11.7 | 7.3 | 6,5 | 13.4 | 6.3 | 6.6 | 10.8 | 12.6 | 81 | 10.9 | 9.1 | დ ო | 10.1 | 8,3 | 8.7 |
| 10.1- 1 12.0 VIN | 5.4 | 14.2 | | ် တိ | 7.1 | x 0 | 5.4 | 10.1 | 6,3 | ν. 4 - | 10.8 | 6.6 | 6.3 | 10.8 | /:: | 18.2 | 18.2 | 13.8 | 19.3 | 16.5 | 11.0 |
| 8.1- 10.0 | 3.6- 4.5 | 20.4 | 15.9 | 22.3 | 12.5 | 11.7 | 12.6 | 9.5 | 6.5 | 11.6 | 11.7 | 4.5 | 18.0 | 6 | 3.5 | 10.0 | 22.7 | 27.5 | 20.2 | 21.1 | 15.0 |
| 6.1- 8.0 | 2.7-3.6 | 23.0 | 18.6 | 17.9 | 25.0 | 13.5 | 6.6 | 12.8 | 6,3 | ου π σο υ | 13.5 | 18.0 | 12.6 | 12.6 | ٠, د | 14.5 | 16.4 | 20.2 | 23.9 | 20.2 | 16.0 |
| 4.1- 6.0 | 1.8- | 14.2 | 26.5 | 20.5 | 25.0 | 18.9 | 15,3 | 12.8 | 20.4 | 2 0 | 10.8 | 12.6 | 10.8 | 0.0 | י יי | 5.5 | 6.4 | 13.8 | 11.0 | 11.9 | 15.2 |
| 2.1- | 0.9- | 7.1 | 11.5 | 13.4 | 10.7 | 12.6 | 13.5 | 12.8 | 11.1 | , 0 0 | , 9, 9, | 2.7 | 3.6 | 2.7 | 7 7 | 1.8 | 4.5 | 2,8 | 4.6 | 8,3 | 8.1 |
| 0.1- 2.0 | 0.1- 0.9 | 0 0 | 900 | 6.0 | 4.5 | 2.7 | 2.7 | 6.0 | 0.0 | 00 | 000 | 0.0 | 0.0 | œ. | × 0 | 0.9 | 0 | 0.0 | 0.0 | 0.0 | 1.1 |
| CALM | CALM | 0.0 | | 0.0 | 6.0 | 0.0 | 0.0 | 0.0 | 6.0 | 000 | 0.0 | 0.0 | 0.0 | 0.0 | 2,0 | 0.0 | 0 | 6.0 | 6.0 | 0.9 | 0.6 |
| | | |) 4 r | 9 | ~ 0 | | | 0 11 | 15 | 13 | R 15 | 16 | 17 | <u>∞</u> : | <u> </u> | 2 | น | ខ | S | 24 | - HOURS |
| | | | | | | _ | | _ | • | _ | | | | | | | | | | | AL. |

Table IV - 11

Percentage Frequency Summary for Wind Speed BLAINE COUNTY - HAYS

(AUTUMN)

01/01/84 - 07/15/85

| CALM 2.0 - 2.1- 4.1- 6.1- 8.1-10.1-12.1-14.1- 6.1- 25.1-30.1-35.1- 35.1- 6.1- 8.1-10.1-12.1-14.1- 6.1- 8.1- 10.1- 12.1- 14.1- 6.1- 8.1- 10.1- 12.1- 14.1- 6.1- 30.1- 25.1- 30.1- 35.0 40.0 94.0 O11- 0.9- 1.8- 2.7- 3.6- 4.5- 5.4- 6.3- 7.2- 8.1- 9.0- 11.2- 13.5- 15.7- 8FEB SPEE CALM 0.9 1.8 2.7- 3.6- 4.5- 5.4- 6.3- 7.2- 8.1- 9.0- 11.2- 13.5- 15.7- 8FEB SPEE CALM 0.9 1.8 2.7- 3.6- 4.5- 5.4- 6.3- 7.2- 8.1- 9.0- 11.2- 13.5- 15.7- 8FEB SPEE CALM 0.9 1.8 2.7- 3.6- 4.5- 5.4- 6.3- 7.2- 8.1- 9.0- 11.2- 13.5- 15.7- 8FEB SPEE S.1- 9.0- 11.2- 13.5- 15.7- 9.1- 9.1- 9.1- 9.1- 9.1- 9.1- 9.1- 9.1 | | . 0 | <u>(</u> | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|------------------------|----------------|----------|------|-------------|------|----------|------|------|--------|--------|-------------|------|----------|------|------|------|---------|---------|---------|------|------|------|------|------|------|------|-------|--|
| CALM 2.0 4.0 6.0 8.0 10.0 12.1 - 14.1 - 16.1 - 18.1 - 20.1 - 25.1 - 30.1 - 35.1 - 4.0 6.0 8.0 10.0 12.1 - 14.1 - 16.1 - 18.1 - 20.1 - 25.1 - 30.1 - 35.1 - 40.0 40.0 MINO SPEED (WETERS/SECOND) 0.1 - 0.9 - 1.8 - 2.7 - 3.6 4.5 5.4 6.3 7.2 8.0 8.9 11.2 13.4 15.6 17.9 >17.9 0.0 6.0 10.0 15.0 12.0 12.0 12.0 12.0 12.0 12.0 12.0 12 | | SPEE | (M/SE | 4.7 | 4.8 | 5.0 | 4.7 | 4.7 | 4.8 | 4.8 | 5.0 | 4.8 | 5.1 | 5.8 | 6.4 | 6.0 | 0.9 | 5.9 | 5.4 | 5.4 | 5.0 | 4.5 | 4.3 | 4.3 | 4.8 | 4.6 | 4.6 | 5,1 | |
| O.1- 2.1- 4.1- 6.1- 8.1- 10.1- 12.1- 16.1- 18.1- 20.1- 25.1- 30.1- 35.1- 30.1- 35.1- 6.0 8.0 10.0 12.0 14.0 16.0 18.0 20.0 25.0 30.0 35.0 40.0 12.0 14.0 16.0 18.0 20.0 25.0 30.0 35.0 40.0 10.0 12.0 14.0 16.0 18.0 20.0 25.0 30.0 35.0 40.0 10.0 15.0 18.0 20.0 25.0 30.0 35.0 40.0 10.0 15.0 18.0 20.0 25.0 30.0 35.0 40.0 10.0 16.0 18.0 2.7 3.6 4.5 5.4 6.3 7.2- 8.0 8.9 11.2 13.4 15.6 17.9 10.0 6.0 16.0 16.0 16.0 12.0 6.0 4.0 6.0 10.0 16.0 12.0 12.0 6.0 4.0 6.0 10.0 16.0 15.0 12.0 6.0 12.0 6.0 12.0 2.0 12.0 2.0 12.0 2.0 12.0 2.0 12.0 2.0 14.0 12.0 8.0 4.0 2.0 14.0 0.0 8.0 12.0 22.0 14.0 12.0 8.0 4.0 2.0 8.0 8.0 8.0 8.0 8.0 8.0 8.0 8.0 8.0 8 | | SPEED | Œ. | 10.5 | 10.8 | 11.2 | 10.5 | 10.5 | 10.7 | 10.8 | 11.2 | 10.8 | 11.4 | 13.0 | 14.4 | 13.5 | 13.4 | 13,3 | 12.2 | 12.0 | 11.3 | 10.2 | 9.7 | 9.7 | 10.8 | 10.4 | 10.3 | 11.4 | |
| O.1- 2.1- 4.1- 6.1- 8.1- 10.1- 12.1- 16.1- 18.1- 20.1- 25.1- 30.1- 35.1- 30.1- 35.1- 6.0 8.0 10.0 12.0 14.0 16.0 18.0 20.0 25.0 30.0 35.0 40.0 12.0 14.0 16.0 18.0 20.0 25.0 30.0 35.0 40.0 10.0 12.0 14.0 16.0 18.0 20.0 25.0 30.0 35.0 40.0 10.0 15.0 18.0 20.0 25.0 30.0 35.0 40.0 10.0 15.0 18.0 20.0 25.0 30.0 35.0 40.0 10.0 16.0 18.0 2.7 3.6 4.5 5.4 6.3 7.2- 8.0 8.9 11.2 13.4 15.6 17.9 10.0 6.0 16.0 16.0 16.0 12.0 6.0 4.0 6.0 10.0 16.0 12.0 12.0 6.0 4.0 6.0 10.0 16.0 15.0 12.0 6.0 12.0 6.0 12.0 2.0 12.0 2.0 12.0 2.0 12.0 2.0 12.0 2.0 14.0 12.0 8.0 4.0 2.0 14.0 0.0 8.0 12.0 22.0 14.0 12.0 8.0 4.0 2.0 8.0 8.0 8.0 8.0 8.0 8.0 8.0 8.0 8.0 8 | >40.0 | | >17.9 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | |
| WIND SPEED (MH) 0.1- 2.1- 4.1- 6.1- 8.1- 10.1- 12.1- 14.1- 16.1- 18.1- 20.1- 25.1- 30.1- CALM 2.0 4.0 6.0 8.0 10.0 12.0 14.0 16.0 18.0 20.0 25.0 30.0 35.0 MIND SPEED (METRS/SECOND) 0.1- 0.9- 1.8- 2.7- 3.6- 4.5- 5.4- 6.3- 7.2- 8.1- CALM 0.9 1.8 2.7 3.6- 4.5- 5.4- 6.3- 7.2- 8.1- 0.0 6.0 6.0 18.0 22.0 6.0 4.0 6.0 8.0 11.2 13.4 15.6 0.0 6.0 10.0 16.0 16.0 16.0 16.0 6.0 4.0 6.0 8.0 11.2 13.4 15.6 0.0 6.0 10.0 16.0 16.0 16.0 16.0 16.0 12.0 8.0 4.0 10.0 0.0 0.0 6.0 10.0 16.0 16.0 16.0 16.0 12.0 8.0 4.0 10.0 0.0 2.0 2.0 14.0 22.0 14.0 12.0 8.0 4.0 10.0 2.0 14.0 0.0 2.0 2.0 2.0 6.0 12.0 22.0 14.0 12.0 8.0 4.0 0.0 2.0 14.0 0.0 2.0 2.0 2.0 6.0 12.0 22.0 14.0 12.0 8.0 4.0 0.0 2.0 14.0 0.0 2.0 2.0 2.0 12.0 14.0 22.0 14.0 12.0 8.0 4.0 0.0 2.0 14.0 0.0 2.0 2.0 2.0 12.0 14.0 22.0 14.0 10.0 10.0 0.0 6.0 10.0 6.0 2.0 2.0 2.0 12.0 22.0 14.0 14.0 12.0 8.0 4.0 0.0 2.0 14.0 2.0 2.0 12.0 8.0 18.0 6.0 14.0 10.0 10.0 0.0 6.0 10.0 6.0 10.0 2.0 2.0 12.0 8.0 18.0 6.0 14.0 10.0 10.0 10.0 6.0 4.0 12.0 2.0 2.0 12.0 12.0 2.0 14.0 14.0 14.0 15.0 8.0 0.0 4.0 12.0 2.0 2.0 12.0 13.0 14.0 15.0 14.0 14.0 15.0 8.0 0.0 4.0 15.0 2.0 2.0 12.0 14.0 15.0 15.0 14.0 4.0 6.0 4.0 15.0 2.0 0.0 2.0 12.0 14.0 22.0 14.0 15.0 15.0 15.0 4.0 0.0 6.0 14.0 15.0 2.0 2.0 12.0 12.0 12.0 14.0 15.0 14.0 4.0 6.0 4.0 15.0 2.0 0.0 2.0 12.0 12.0 12.0 14.0 15.0 14.0 4.0 6.0 4.0 15.0 2.0 0.0 2.0 12.0 12.0 14.0 15.0 15.0 15.0 15.0 15.0 15.0 15.0 15 | 35.1- 40.0 | 15.7- | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 2.0 | 0.0 | 0.0 | 1.9 | 0.0 | 0.0 | 2.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.2 | |
| WIND SPEED (MPH) 0.1- 2.1- 4.1- 6.1- 8.1- 10.1- 12.1- 14.1- 16.1- 18.1- 20.1- 25.1- 6.0 8.0 10.0 12.0 14.0 16.0 18.0 20.0 25.0 30.0 MIND SPEED (FETRS/SECRON) 0.1- 0.9- 1.8- 2.7- 3.6- 4.5- 5.4- 6.3- 7.2- 8.1- 9.0- 11.2- 0.0- 1.8- 2.7- 3.6- 4.5- 5.4- 6.3- 7.2- 8.1- 9.0- 11.2- 13.4- 0.0- 0.0- 0.0- 0.0- 0.0- 0.0- 0.0- 0 | 30.1- 35.0 | 13.5- | 15.6 | 0.0 | 0.0 | 2.0 | 2.0 | 2.0 | 0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 3,00 | 1.9 | 1.9 | ω | 0.0 | 2.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.8 | |
| VIND SPEED (MFH) 0.1- 2.1- 4.1- 6.1- 8.1- 10.1- 12.1- 14.1- 16.1- 18.1- 20.1- CALM 2.0 4.0 6.0 8.0 10.0 12.0 14.0 16.0 18.0 20.0 25.0 0.1- 0.9- 1.8- 2.7- 3.6- 4.5- 5.4- 6.3- 7.2- 8.1- 9.0- CALM 0.9 1.8 2.7 3.6 4.5 5.4 6.3 7.2 8.0 8.9 11.2 0.0 6.0 6.0 18.0 22.0 6.0 4.0 4.0 12.0 8.0 4.0 10.0 0.0 6.0 10.0 16.0 12.0 6.0 4.0 6.0 4.0 6.0 8.0 2.0 2.0 6.0 12.0 22.0 16.0 12.0 8.0 4.0 6.0 14.0 2.0 2.0 6.0 12.0 22.0 14.0 18.0 4.0 6.0 12.0 8.0 8.0 2.0 2.0 6.0 12.0 22.0 14.0 18.0 4.0 6.0 10.0 6.0 14.0 2.0 2.0 6.0 12.0 22.0 14.0 18.0 4.0 6.0 10.0 6.0 14.0 2.0 2.0 6.0 12.0 22.0 14.0 18.0 4.0 6.0 10.0 6.0 14.0 2.0 12.0 12.0 12.0 12.0 12.0 12.0 8.0 4.0 6.0 12.0 8.0 2.0 2.0 6.0 12.0 22.0 14.0 18.0 14.0 12.0 8.0 4.0 6.0 14.0 2.0 12.0 12.0 12.0 12.0 14.0 12.0 12.0 6.0 2.0 8.0 2.0 12.0 13.0 18.0 14.0 12.0 12.0 4.0 6.0 10.0 6.0 14.0 2.0 12.0 12.0 12.0 12.0 12.0 12.0 12.0 6.0 2.0 8.0 2.0 12.0 13.0 13.0 14.0 12.0 12.0 12.0 6.0 2.0 8.0 2.0 12.0 13.0 13.0 14.0 12.0 12.0 12.0 12.0 12.0 6.0 22.0 2.0 12.0 13.0 13.0 13.7 11.8 13.7 5.9 2.0 7.8 5.9 5.9 2.0 2.0 13.0 13.7 11.8 11.8 5.9 2.0 7.8 5.9 5.9 2.0 2.0 2.0 2.0 13.7 11.5 11.5 11.5 11.8 5.9 2.0 7.8 5.9 5.9 2.0 3.9 11.8 19.6 13.7 11.8 11.8 5.9 2.0 7.8 5.9 5.9 2.0 3.9 11.8 19.6 13.7 11.8 11.8 5.9 2.0 7.8 5.9 5.9 2.0 2.0 8.0 8.0 12.0 12.2 6.1 6.1 6.1 6.1 6.1 6.1 10.2 2.0 10.0 2.0 8.2 16.3 12.2 12.2 6.1 6.1 6.1 6.1 6.1 6.1 10.2 2.0 10.0 2.0 8.2 16.3 12.2 12.2 6.1 6.1 6.1 6.1 6.1 6.1 10.2 2.0 10.0 2.0 8.2 16.3 12.2 12.2 6.1 6.1 6.1 6.1 6.1 6.1 6.1 10.2 | | 11.2- | 13.4 | 0.0 | 0. 9 | 0.0 | 0.0 | 0.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 4.0 | 6.0 | 3.8 | 1.9 | 3.00 | ω | 0.0 | 2.0 | 2.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 1.8 | |
| MIND SPEED (MPH) CALM 2.0 4.0 6.0 8.0 10.0 12.0 14.0 16.0 18.0 18.0 1.8 2.0 4.0 6.0 8.0 10.0 12.0 14.0 16.0 18.0 18.0 1.8 2.0 4.0 6.0 8.0 10.0 12.0 14.0 16.0 18.0 18.0 1.8 2.7 3.6 4.5 5.4 6.3 7.2 8.0 0.0 6.0 10.0 16.0 18.0 2.7 3.6 4.5 5.4 6.3 7.2 8.0 0.0 6.0 10.0 16.0 16.0 16.0 12.0 8.0 0.0 6.0 10.0 16.0 16.0 16.0 12.0 8.0 0.0 4.0 2.0 14.0 20.0 16.0 6.0 12.0 8.0 6.0 12.0 2.0 2.0 2.0 2.0 2.0 12.0 2.0 12.0 8.0 4.0 0.0 2.0 2.0 2.0 12.0 14.0 14.0 12.0 8.0 0.0 2.0 2.0 2.0 12.0 2.0 12.0 14.0 12.0 8.0 0.0 2.0 2.0 12.0 12.0 12.0 12.0 8.0 0.0 2.0 2.0 12.0 12.0 12.0 12.0 12.0 | | | | 10.0 | 0 0 | 14.0 | 8.0 | 8.0 | 0.9 | 8 | 14.0 | 12.0 | 16.0 | 20.0 | 22.0 | 21.2 | 11.5 | 9.6 | 11.5 | 13.5 | 3.9 | 2.0 | 7.8 | 5,9 | 10.2 | 10.2 | 10.2 | 11.0 | |
| CALM 2.0 4.0 6.0 8.0 10.0 12.0 14.0 16.0 MIND SPEED (WETE O.1 - 0.9- 1.8- 2.7- 3.6- 4.5- 5.4- 6.3- 6.3- 6.0 10.0 12.0 12.0 14.0 16.0 16.0 10.0 12.0 14.0 16.0 16.0 10.0 12.0 14.0 16.0 16.0 10.0 10.0 12.0 14.0 16.0 16.0 10.0 10.0 10.0 10.0 10.0 10 | | 0 | | 4.0 | 9 | 2.0 | 9 | 8 | 10.0 | 6.0 | 6.0 | 4.0 | 4.0 | 6.0 | 9.0 | 7.7 | 7.7 | 3 | 0.0 | ς. α | 9.8 | 5,9 | 3,9 | 5.9 | 4.1 | 6.1 | 6.1 | 5.6 | |
| O.1- 2.1- 4.1- 6.1- 8.1- 10.1- 12.1- 12.1- 12.1- 12.1- 12.1- 0.1- 0.9- 1.8- 2.7- 3.6- 4.5- 5.4- 0.1- 0.9- 1.8- 2.7- 3.6- 4.5- 5.4- 0.0 0.0 0.0 1.8 2.7 3.6- 4.5- 5.4- 0.0 0.0 0.0 1.0 16.0 16.0 12.0 0.0 0.0 0.0 0.0 16.0 16.0 12.0 0.0 0.0 0.0 0.0 16.0 16.0 12.0 0.0 0.0 0.0 0.0 16.0 16.0 16.0 16.0 1 | (MPH) 16.1- 18.0 | ERS/SE 7.2- | 8.0 | 8.0 | 4.0 | 0.0 | 2.0 | 2.0 | 0.9 | 4.0 | 0.0 | 0.0 | 6.0 | 6.0 | 2.0 | 3.8 | 9.6 | 5.8 | 7.7 | 0.0 | 3,9 | 7.8 | 7.8 | 2.0 | 8.2 | 8.2 | 6.1 | 4.6 | |
| CALM 2.0 4.0 6.0 8.0 10.0 12.0 MINO 2.0 4.0 6.0 8.0 10.0 12.0 MINO 2.0 4.0 6.0 8.0 10.0 12.0 MINO 2.0 6.0 1.8 2.7 3.6 4.5 5.4 0.0 6.0 10.0 16.0 12.0 6.0 6.0 10.0 16.0 12.0 6.0 6.0 10.0 16.0 12.0 6.0 6.0 10.0 16.0 12.0 6.0 6.0 10.0 6.0 12.0 6.0 12.0 6.0 12.0 6.0 12.0 6.0 12.0 6.0 12.0 6.0 12.0 6.0 12.0 6.0 12.0 6.0 12.0 6.0 12.0 6.0 12.0 6.0 12.0 6.0 12.0 6.0 12.0 6.0 12.0 12.0 12.0 6.0 12.0 12.0 12.0 12.0 12.0 12.0 12.0 12 | SPEED 14.1- 16.0 | 0 (₹ 6.3 | 7.2 | 12.0 | 6.0 | 8.0 | 4.0 | 0.0 | 0.0 | 6.0 | 4.0 | 8.0 | 4.0 | 0.0 | 10.0 | 5.8 | 7.7 | 13.5 | 3.8 | 9.6 | 3,9 | 2.0 | 2.0 | 5,9 | 2.0 | 4.1 | 4.1 | 5,3 | |
| CALM 2.0 - 4.1 - 6.1 - 8.1 - 6.1 - 8.1 - 6.1 - 8.1 - 0.1 - 0.9 - 1.8 - 2.7 - 3.6 - 4.5 - 6.0 8.0 10.0 0.1 - 0.9 - 1.8 - 2.7 - 3.6 - 4.5 0.0 6.0 1.8 2.7 3.6 - 4.5 0.0 6.0 1.8 2.7 3.6 - 4.5 0.0 6.0 10.0 16.0 12.0 0.0 4.0 2.0 14.0 14.0 12.0 2.0 14.0 14.0 2.0 12.0 2.0 14.0 14.0 12.0 2.0 2.0 2.0 2.0 2.0 2.0 2.0 2.0 2.0 | WIND 12.1- 14.0 | 0 SPEE 5.4- | 6.3 | 4.0 | 4.0 | 12.0 | 8.0 | 4.0 | 10.0 | 4.0 | 12.0 | 16.0 | 10.0 | 12.0 | 6.0 | 7.7 | 5.8 | 9.6 | 15.4 | ည် | 9.8 | 5,9 | 5,9 | 7.8 | 10.2 | 6.1 | 4.1 | 8.2 | |
| CALM 2.0 - 4.1 - 6.1 - 8.1 - 6.1 - 8.1 - 6.1 - 8.1 - 0.1 - 0.9 - 1.8 - 2.7 - 3.6 - 4.5 - 6.0 8.0 10.0 0.1 - 0.9 - 1.8 - 2.7 - 3.6 - 4.5 0.0 6.0 1.8 2.7 3.6 - 4.5 0.0 6.0 1.8 2.7 3.6 - 4.5 0.0 6.0 10.0 16.0 12.0 0.0 4.0 2.0 14.0 14.0 12.0 2.0 14.0 14.0 2.0 12.0 2.0 14.0 14.0 12.0 2.0 2.0 2.0 2.0 2.0 2.0 2.0 2.0 2.0 | 10.1- 12.0 | VIN. | 5.4 | 4.0 | 6.0 | 6.0 | 12.0 | 18.0 | 10.0 | 14.0 | 10.0 | 4.0 | 6.0 | 12.0 | 8,0 | 11.5 | 19.2 | 15.4 | 13.5 | 9.6 | 11.8 | 13,7 | 11.8 | 13.7 | 14.3 | 6.1 | 10.2 | 10.9 | |
| CALM 2.0 4.0 6.0 0.1- 2.1- 4.1- 0.1- 0.9- 1.8- 0.0 6.0 6.0 18.0 0.0 6.0 6.0 18.0 2.0 2.0 6.0 14.0 2.0 2.0 6.0 14.0 2.0 2.0 6.0 12.0 2.0 2.0 6.0 14.0 2.0 2.0 12.0 12.0 2.0 2.0 6.0 14.0 2.0 2.0 6.0 14.0 2.0 2.0 6.0 14.0 2.0 2.0 6.0 14.0 2.0 0.0 7.7 13.5 1.9 0.0 7.7 11.5 1.9 1.9 5.8 15.7 9.8 0.0 3.9 11.8 19.6 0.0 3.9 11.8 19.6 0.0 4.1 4.1 24.5 | | | | 6.0 | 12.0 | 16.0 | 14.0 | 14.0 | 0.9 | 12.0 | 10.0 | 14.0 | 16.0 | 8 0.0 | 14.0 | 5.8 | 7.7 | 7.7 | တ္ | 21.2 | 15,7 | 11.8 | 11.8 | 15.7 | 12.2 | 12.2 | 8.2 | 11.6 | |
| CALM 2.0 4.0 CALM 2.0 4.0 0.1- 0.9- 0.1- 0.9- 0.0 6.0 6.0 6.0 2.0 2.0 6.0 2.0 2.0 6.0 2.0 2.0 6.0 2.0 2.0 6.0 2.0 2.0 2.0 2.0 2.0 2.0 2.0 2.0 2.0 2.0 2.0 2.0 2.0 2.0 8.0 2.0 2.0 8.0 2.0 2.0 8.0 2.0 2.0 8.0 2.0 2.0 8.0 2.0 2.0 8.0 2.0 0.0 7.7 1.9 1.9 3.8 7.7 2.0 0.0 3.9 11.8 0.0 3.9 11.8 0.0 3.9 11.8 0.0 3.9 11.8 0.0 3.9 11.8 0.0 2.0 8.2 0.0 4.1 4.1 | 6.1- 8.0 | 2.7- | 3.6 | 22.0 | 16.0 | 20.0 | 14.0 | 22.0 | 26.0 | 20.0 | 14.0 | 6. 0 | 10.0 | 8.0 | 0.9 | 11.5 | 7.7 | 5. 8 | 11.5 | 3,8 | 19.6 | 17.6 | 13.7 | 7.8 | 10.2 | 12.2 | 18.4 | 13.5 | |
| CALM 2.0 0.1- CALM 2.0 0.0- 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 | 4.1- | œ | 2.7 | 18.0 | 16.0 | 14.0 | 24.0 | 12.0 | 14.0 | 12.0 | 18.0 | 18.0 | 10.0 | 10.0 | 8.0 | 13.5 | 7.7 | 11.5 | 15.4 | 13,5 | 5,9 | 9.8 | 19.6 | 19.6 | 18.4 | 16.3 | 24.5 | 14.5 | |
| CAL CAL CAL CAL CAL CAL CAL CAL | 2.1- | 9 | 1.8 | 6.0 | 10.0 | 2.0 | 4.0 | 6.0 | 0.9 | 8 0 | ω Ο | 12.0 | 2.0 | 10.0 | 8.0 | 7.7 | 7.7 | 7.7 | 5. 8 | 7.7 | 9.8 | 15.7 | 11.8 | 11.8 | 8.2 | 8.2 | 4.1 | 7.8 | |
| 6 | 0.1- | -1 | 0.9 | 6.0 | 6.0 | 4.0 | 0.0 | 2.0 | 2.0 | 0.0 | 0.0 | 2.0 | 12.0 | 4.0 | 2.0 | 0.0 | 0.0 | 0.0 | 1.9 | 3.8 | 0.0 | 3.9 | 3.9 | 3.9 | 2.0 | 10.2 | 4.1 | 3,1 | |
| H 9 8 110 0 111 113 114 115 115 115 115 115 115 115 115 115 | CALM | j 5 | CALM | 0.0 | 0.0 | 0.0 | 2.0 | 2.0 | 2.0 | 4.0 | 2.0 | 2.0 | 2.0 | 0.0 | 0.0 | 0.0 | 1.9 | 1.9 | 1.9 | 1.9 | 2.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 1.1 | |
| N O O H THE | | | | | 7 | m | 4 | വ | 9 | 7 | ထ | 6 | 2 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | Z | 23 | 23 | 24 | IOURS | |
| | | | | | | | | | | | | × | | 0 | | _ | | ∝ | | | | | | | | | | ALL H | |

Table IV - 12

Annual Wind Rose Distribution BLAINE COUNTY - HAYS

01/01/84 - 07/15/85

| <direction< th=""><th>SPEED (M/SEC)</th><th>0.1- 0.4 0.5- 0.9 1.0- 1.3 S 1.4- 1.8 P 1.9- 2.2 E 2.3- 2.7 E 2.3- 2.7 E 2.3- 2.7 E 3.7- 4.0 M 4.1- 4.5 E 4.1- 4.5 E 6.4- 6.7 / 6.4- 6.7 / 6.8- 7.2 S 7.7- 8.0 C 8.6- 8.9 N 8.6- 8.9 N 11.3-13.4 11.3-13.4 CALM</th><th>AV SPEED (MPH)</th><th>AV SPEED (M/SEC)</th></direction<> | SPEED (M/SEC) | 0.1- 0.4 0.5- 0.9 1.0- 1.3 S 1.4- 1.8 P 1.9- 2.2 E 2.3- 2.7 E 2.3- 2.7 E 2.3- 2.7 E 3.7- 4.0 M 4.1- 4.5 E 4.1- 4.5 E 6.4- 6.7 / 6.4- 6.7 / 6.8- 7.2 S 7.7- 8.0 C 8.6- 8.9 N 8.6- 8.9 N 11.3-13.4 11.3-13.4 CALM | AV SPEED (MPH) | AV SPEED (M/SEC) |
|---|---------------|--|-------------------|---------------------|
| NNW TOTAL | | | 12.2 | |
| ¥ N | | 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 | 0.5 13.6 | 6.1 |
| ₹ | | 00000000000000000000000000000000000000 | 8.0 16.3 | 7.3 |
| NA. | | 0.0000000000000000000000000000000000000 | 15.3 | 6.8 |
| 3 | | 0.000000000000000000000000000000000000 | 14.4 | 6.5 |
| 3 | | 0.000000000000000000000000000000000000 | 14.4 | 6.4 |
| ₹ | | 0.000011010000000000000000000000000000 | 17.9 | 6.0 |
| SS | | 0.000000000000000000000000000000000000 | 11.3 | 5.1 |
| S | | 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0 | 9.8 | 4.4 |
| SSE | | 0.0000000000000000000000000000000000000 | 7.7 6.7 | 3.0 |
| S | | 0.0000000000000000000000000000000000000 | 7.7 | 3.5 |
| ESE | | 0.0000000000000000000000000000000000000 | c., 8 | 3.7 |
| ш | | 0.000000000000000000000000000000000000 | 3.5 9.6 | 4.3 |
| E E | | 10000000000000000000000000000000000000 | 3.7 8.1 | 3.6 |
| 씾 | | 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 | . 8 | |
| N N | | 000000000000000000000000000000000000000 | 9.1 | 4.1 |
| z | | 00000000000000000000000000000000000000 | 0°6 | 4.3 |
| DIRECTIONS | SPEED (MPH) | 0.1-1.0 1.1-2.0 2.1-3.0 3.1-4.0 8.1-5.0 E 7.1-8.0 D 8.1-9.0 9.1-10.0 H 10.1-11.0 I 11.1-12.0 I 11.1-12.0 I 11.1-12.0 I 12.1-13.0 I 13.1-14.0 S 14.1-15.0 I 16.1-17.0 O 17.1-18.0 U 18.1-19.0 R 19.1-20.0 25.1-30.0 35.1-40.0 CALM | AV SPEED (MPH) | AV SPÉED (M/SEC) |




Table IV - 13

Coefficients of Weibull Distribution

BLAINE COUNTY - HAYS

01/01/84 - 07/15/85

| SHAPE (C) FACTOR (K) | 75 1.5802 1.7594 1.7594 1.7592 88 1.7118 88 1.8030 74 1.8076 13 2.0507 45 2.0507 45 2.0609 62 81 1.7356 81 1.7356 | |
|---------------------------------|--|--|
| SCALE MONTH FACTOR (M/SEC | JANUARY FEBRUARY MARCH APRIL MAY JULY JULY SEPTEMBER OCTOBER NOVEMBER VEAR | |

THREE FORKS BROADWATER COUNTY

The Three Forks site was located approximately 6 miles north-northwest of the town of Three Forks at 45 59 20 N and 111 35 32 W (Site No. 10 on Map II-1). The site was located on a hill in gently rolling terrain at an elevation of 4,580 feet. The site was established by the U.S. Bureau of Reclamation as part of its Northern Great Plains Wind Energy Study.

Wind data were gathered at this site from June 27, 1981, to September 15, 1982. Data from the wind sensors were continuously recorded on cassette tape at the site. These tapes were further processed by computer to yield hourly averages of wind speed, wind direction, the average cube of the hourly speed, and standard deviation of hourly wind speed. In addition, maximum and minimum instantaneous values of wind speed during each hour were recorded. Anemometer height was 10 meters. Prevailing winds from the southwest were accurately measured, but east winds were somewhat screened by a hill.

Data recovery was fair to excellent, ranging from 56.5 percent in July and 97.1 percent in June to 100.0 percent during all other months. Overall data recovery was 93.7 percent.

The average annual wind speed at this site was 8.6 miles per hour. Average monthly wind speeds varied from 6.4 miles per hour in January. The windiest months were January through April

Average monthly wind power ranged from 27.2 watts/ m^2 in June to 139.0 watts/ m^2 in January. Average annual wind power was 72.5 watts/ m^2 .




Table IV - 14

Monthly Wind Speed Distribution

BROADWATER COUNTY - THREE FORKS

06/27/81 - 09/15/82

| | CALM 1.00-1-1 1.01-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1 1.01-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1-1 1.01-1 1. | |
|------|--|---|
| YEAR | 00000000000000000000000000000000000000 | 8.6 3.8 72.5 93.7 |
| DEC | 0.000000000000000000000000000000000000 | 8.5 3.8 72.1 |
| NOV | 0.01-7-1048-104-10-10-10-10-10-10-10-10-10-10-10-10-10- | 8.0 3.6 50.0 |
| OCT | 00-00-00-00-00-00-00-00-00-00-00-00-00- | 8.8 3.9 78.4 |
| SEP | 00-23-64-1-20-20-20-20-20-20-20-20-20-20-20-20-20- | 7.6 3.4 51.5 |
| AUG | 000000000000000000000000000000000000000 | 7.3 3.3 39.3 |
| JUL | 000000000000000000000000000000000000000 | 8.8 3.9 63.9 56.5 |
| NOC | 0.0000000000000000000000000000000000000 | 6.4 2.9 27.2 97.1 |
| MA≺ | 00000000000000000000000000000000000000 | 8.9 4.0 88.0 |
| APR | 000-12-12-12-12-12-13-13-13-13-13-13-13-13-13-13-13-13-13- | 10.1 4.5 110.9 |
| MAR | 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0 | 10.4 4.6 122.2 100.0 |
| FEB | 0.00 - 6.40 - 6. | 9.3 4.2 86.3 |
| JAN | 000100000000000000000000000000000000000 | 10.6 4.8 139.0 |
| | CALM 0.1-10 1.1-2.0 1.1-2.0 1.1-2.0 0.1-13.0 0.1-4.0 0.1-7.0 0.1-7.0 0.1-7.0 0.1-10.0 10.1-11.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 | AVERAGE SPEED (MPH) AVERAGE SPEED (M/SEC) AVERAGE WIND POWER (WATTS/M**2) PERCENT DATA RECOVERY |

DNOCES/SETHER DEELES

ANEMOMETER HEIGHT = 10 METERS = 33 FEET NUMBER OF OBSERVATIONS = 10032
PERCENTAGE DATA RECOVERY = 93.7
SOURCE: GEORESEARCH, INC.

GREAT FALLS MALMSTROM AFB

CASCADE COUNTY

Malmstrom Air Force Base is located on the eastern side of Great Falls at 47 31 12 N and 111 10 12 W (Site No. 14 on Map II-1). Elevation at the base is 3,465 feet. Meteorological data have been collected at this site for many years by the United States Air Force.

These data, primarily collected for aviation and weather forecasting uses, consist of short-term (5 minutes or less) averages of wind speed and wind direction, as well as other meteorological parameters. Data were gathered once per hour. The data have been analyzed by Battelle Pacific Northwest Laboratories. Because of changes in anemometer height, the data set was broken into three parts for analysis: January 1, 1949, through May 31, 1953; March 1, 1954, through February 28, 1958; and April 1, 1958, through November 30, 1968. Only data from the most recent of these periods were selected for inclusion in the Montana Wind Energy Atlas.

The data set for Malmstrom Air Force Base consists of data summaries of observations made every third hour from April 1, 1958, through November 30, 1968. The anemometer was mounted on a ground mast at a height of 4.6 meters. The site is representative of lower lying areas in the vicinity of Great

Average annual wind speed was 8.7 miles per hour. Monthly average wind speeds ranged from 5.6 miles per hour in July to 10.7 miles per hour in January.

Average annual wind power was 106.0 watts/m². Average monthly wind power varied from 33.0 watts/m² in July to 175.0 watts/m² in January.




Table IV - 15

Monthly Wind Speed Distribution

CASCADE COUNTY - GREAT FALLS MALMSTROM AIR FORCE BASE

04/01/58 - 11/30/68

| | ~ « | يا ہم | ليا لـ | _ | 5 | ا لنا | سا - | œ | <u>က</u> | _ | ഗ | ا ليا | . | α: | . | _ | | | | | | | | | |
|------|-----------------------------------|--------|----------------|----------|----------------|----------------|-------------------|----------|----------|----------|----------|----------|----------|----------|----------|-------|----------|----------|----------|----------|----------|---------|------------------------|--------------------------|-------------------------|
| | 6.5 | | | | | | | | | | | | | | | | ⇒ | → | . | . | + | | | | |
| | <u>^</u> ′′. | რ- | į ry | 91 | ∞ | 9,5 | <u>: :</u> | 72. | 13. | <u>.</u> | 5. | 9 | _ | <u>.</u> | <u>.</u> | 20. | Ŋ, | ö | Ę, | • | · | | | | |
| | A | יט נ | ĴΝ | ιĊι | ú'n | ιĊπ | 5. | J. | ψ | نۍ. | ان | انج | Ÿ | 7. | Ÿ | ż | Ÿ | ċ | ب | ζ, | ۸ | | | | |
| ~ | 00- | C/I C |) - | 471 | 0 I~ | & C | ,5 | - | 72 | <u></u> | I | , CT | D | , | - | 3 | 2 | S | 30 | 35 | | | | | |
| YEAR | 13.7 6.8 14.9 | 15. | 10.3 | 7.0 | シュ シレ | ლი | | 0.8 | 0.0 | 0 | 0.1 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 8.7 | 3.9 | 106.0 |
| DEC | 12.4 6.2 11.6 | • | | • | | | | • | • | • | • | • | • | • | • | • | | | | | • | | 10.1 | 4.5 | 148.0 |
| NOV | 13.3 5.4 10.4 | • | | | | | | | | ٠ | • | • | • | | • | • | | | | | • | | 10.3 | 4.6 | 150.0 1 |
| OCT | 12.1 5.1 | 13.1 | .6. | 9.5 | 9.5 9.5 | 8.0 8.0 | ;- : : : | 6.0 | 0.7 | 0.3 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 9.8 | ⊅. | 126.0 1 |
| SEP | 15.6 7.6 16.7 | • | | • | | • | | • | | • | • | • | • | | | • | • | • | • | | ٠ | | 9.7 | 3.4 | 76.0 1 |
| AUG | 15.8 8.3 20.5 | • | ; 6 | • | | - | | • | ٠ | • | • | • | ٠ | • | ٠ | • | • | • | • | | • | | 6.7 | 3.0 | 51.0 |
| JUL | 19.7 10.4 22.8 | • | | | | | | | | | • | • | | • | | | • | ٠ | | | • | | 5.6 | 2.5 | 33.0 |
| NOC | 6.1 | 0 | , 5, | ٠٠ | သက | 9- | . | ٣. | - | 0. | 0. | 0, | 0. | 0. | 0 | 0. | 0. | 0. | 0. | 0.0 | • | | 6.9 | 3.1 | 55.0 |
| MAY | 12.8 6.9 16.3 | • | | | | | | | • | | • | • | | | • | | | • | | • | | | 8.3 | 3.7 | 87.0 |
| APR | 9.9.5 9.9.9 | • | | • | | | | | | • | • | ٠ | ٠ | • | ٠ | | | • | • | | • | | 9.6 | 4.3 | 120.0 |
| MAR | 12.0 5.9 13.2 | 14.41 | 10.9 | 9.3 | 5.4 | 4.0 | 1:2 | 9.0 | 0.5 | 0.1 | 0.1 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 77.6 | 4.2 | 114.0 1 |
| FEB | 8.01 9.00 9.00 | • | | • | | | | • | • | • | • | ٠ | ٠ | • | ٠ | ٠ | • | | • | ٠ | • | | 10.3 | 4.6 | 0. |
| NAN | 12.4 5.7 10.4 | 27.5 | 9.6 | 9.6 | 7.4 | η. | | 1.7 | 1.2 | 9.0 | 0.9 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 10.7 | φ. 4.8 | 175.0 150 |
| | CALM (<1.1) 1.1-3.1 3.4-5.4 | 5.6-7. | 10.1-12. | 12.3-14. | 5-16. 8-18. | 19.0-21. | 23.5-25. | 25.7-27. | 28.0-30. | 30.2-32. | 32.4-34. | 34.7-36. | 36.9-38. | 39.1-41. | 4-43 | 6-45. | 9-56. | 0-68. | 2-79. | 4-90. | 5 | AVERAGE | SPEED (MPH) AVERAGE | SPEED (M/SEC) AVERAGE | WIND POWER (WATTS/M**2) |
| | | | | | | | | | | | | | | | | | | | | | | | | | |

ANEMOMETER HEIGHT = 15.0 FEET = 4.6 METERS

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

GREAT FALLS NWS AIRPORT CASCADE COUNTY

Great Falls International Airport is located about 4 miles southwest of Great Falls at 47 28 48 N and 111 22 12 W (Site No. 15 on Map II-1). Elevation at the airport is 3,688 feet. Meteorological data have been collected at this site for many years by the National Weather Service.

The site is located on a high, exposed bench between the Sun River valley to the north and the Missouri River valley to the south and east. The bench is occupied by the airport, by housing developments, and by farmland. Interstate Highway 15 runs past the site. Great Falls is an important communications and electric power generation center. It also is a major center of aviation, both commercial and military (at Malmstrom Air Force Base).

The data, primarily collected for aviation and weather forecasting uses, consist of short-term (5 minutes or less) averages of wind speed and wind direction, as well as other meteorological parameters. Data were gathered once per hour. The data have been analyzed by Battelle Pacific Northwest Laboratories. Because of changes in anemometer height and reporting intervals, the data set was split into three parts for analysis: January 1, 1948, through February 2, 1959; February 3, 1959, through December 31, 1964; and January 1, 1965, through December 31, 1978. Only data from the most recent of these periods were selected for inclusion in the *Montana Wind Energy Atlas*.

The data set for the Great Falls airport consists of data summaries of observations made every third hour from January 1, 1965, through December 31, 1978. The anemometer was mounted on a ground mast at a height of 6.7 meters. The site is representative of the higher, more exposed areas around Great Falls.

Average annual wind speed was 11.9 miles per hour. Average monthly wind speeds varied from 9.4 miles per hour in July to 14.8 miles per hour in December

Average annual wind power was 183.0 watts/m². Monthly average wind power ranged from 77 watts/m² in July to 324 watts/m² in December.

Average seasonal wind speeds were 9.8 miles per hour in summer, 11.9 miles per hour in spring, 12.2 miles per hour in autumn, and 13.9 miles per hour in winter. During the summer, the highest average wind speeds occurred during the late afternoon. During all other seasons, the highest average wind speeds occurred in early to mid-afternoon. The lowest average wind speeds occurred about 0600 MST during spring and summer, around 0300 MST in autumn, and from 2100 to 2400 MST in winter. Diurnal range of average wind speed was nearly equal for all seasons, except for the winter.

Winds were most common from the south-southwest through west-southwest; they blew from this sector nearly half the time. Winds from the southeast through south-southeast were least common. By direction, the average wind speeds ranged from 6.5 miles per hour for winds from the southeast to 15.7 miles per hour for southwesterly winds. The strongest winds blew from the prevailing wind directions.




Table IV - 16

Monthly Wind Speed Distribution

CASCADE COUNTY - GREAT FALLS NWS AIRPORT

01/01/65 - 12/31/78

| | CALM (< 0.5- 1. | ישוניםו | ı un | מוט | (C) | rU ru | LL) | RU R | 150 | 16 | ħ | S | ת ע | ے ا | 11 | J | N. | LΩ. | | | | |
|------|-----------------------------------|------------------------|----------|----------------|------|-------------------|------|-------------|------|----------|-----|----------|----------------|-----------|-----------|-----------|-----------|-------|---------|------------------------|---------------|-------------------------|
| YEAR | 1.9 | 4. | <u>-</u> | ۰.0 | 0 | ∞ Ի | 0. | <u>-</u> ب | | = | ٥į | <u>.</u> | - 0 | | 0 | 0. | 0 | 00 | | 11.9 | 5.3 | 183.0 |
| DEC | 1.8 | | 11.0 | 0, 00 0, 00 | 8. | 9.9 | 4.1 | ω, -†. c | 7.0 | 1 3 | 7.0 | 7.0 | | | 0.1 | 0.0 | 0.0 | 0.0 | | 14.8 | 9.9 | 324.0 |
| NOV | 2.4 | 12.8 | 13.4 | 10.0 4.8 | 8.5 | 0 7 7 | 5.6 | 0, 0 | 2.5 | 4.0 | 0.3 | 0.1 | _ - | | 0.0 | 0.0 | 0.0 | 0.0 | | 13.2 | 5.9 | 241.0 |
| OCT | 0.8 | | | | | | | | | | • | | | | | | - | | | 12.8 | 5.7 | 192.0 |
| SEP | 1.5 | 19.3 | 15.9 | 10. 6.8 | 5.8 | w 0 0.0 | | 0 0 2 | | 0.0 | 0.1 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 10.5 | 4.7 | 111.0 |
| AUG | 1.7 | 23.5 | 6 | | 3.8 | - 2 | 0.7 | 9 10 | | 0.1 | 0.0 | 0.0 | 000 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 9.6 | 4.3 | 84.0 |
| JUL | 1.8 | | | | | | | | | | | | | | | | | | | 4.6 | 4.2 | 77.0 |
| NOC | 1.8 2.0 11.4 | | | | | | | | | | - | | | | | _ | | | | 10.5 | 4.7 | 113.0 |
| MAY | 1.9 1.6 10.3 | 17.7 | 16.4 | 0, 80 5. 4. | 6.1 | 4.4 | 1.1 | 0.0 | 0.3 | 0.1 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 00.0 | | 11.0 | 4.9 | 133.0 |
| APR | 1.7 | | • | | • | | • | • | | • | • | • | • | | | • | • | | | 11.9 | 5.3 | 163.0 |
| MAR | 2.0 | 13.6 | 13.4 | 10.7 7.7 | 7.9 | . 5 . 6 . 6 | 2.6 | 0 « | 0 | 9.0 | 0.2 | 0.0 | | 0.0 | 0.1 | 0.0 | 0.0 | 0.0 | | 12.8 | 5.7 | 217.0 |
| FEB | 2.3 1.2 8.6 | 13.8 | 11.8 | 70.5 9.6 | 8.0 | 0 0 0 | 2.9 | 2.7 | .0. | 9.0 | 0.1 | 0.0 | 0.0 | 0.0 | 0.1 | 0.0 | 0.0 | 0.0 | | 13.2 | 5.9 | 247.0 |
| JAN | 2.2 2.0 11.3 | | | | • | | | • | | - | • | ٠ | • | | | • | | | | 13.6 | 6.1 | 298.0 |
| | CALM (<1.1) 1.1-3.1 3.4-5.4 | S 5.6-7.6 P 7.8-9.8 | 10. | 12. | 16.8 | 19.0 21.3 | 23.5 | 25.0 | 30.5 | 32.1 | 34. | 36.5 | χς | 43.6-45.6 | 45.9-56.8 | 57.0-68.0 | 68.2-79.2 | 4.06< | AVERAGE | SPEED (MPH) AVERAGE | SPEED (M/SEC) | WIND POWER (WATTS/M*#2) |

ANEMOMETER HEIGHT = 22.0 FEET = 6.7 METERS

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

Table IV - 17

Percentage Frequency Summary For Wind Speed CASCADE COUNTY - GREAT FALLS NWS AIRPORT (WINTER)

| | | | | | _ | | | | | | | | | | | |
|------------|-----------------------|-----------------|---------|-------|----------------|---|------|------|------|------|----------|-----------|----------|--------|---|--------|
| | | | | | (M/SEC) | | | | | | | | | , r.v. | | 6,2 |
| | | | A\ | SPEED | (MPH) | | | | | | | | | 13.0 | | 13.9 |
| | | >14.4 | | | >32.2 | | | | | | | | | ٦. | | 2.0 |
| | 13.5- | | | | 32.2 | | | | | | | | | 0.8 | | 1.5 |
| | 12.5- | 13.4 | | 28.0- | 30.0 | | | | | | | | | 2 | | 2,5 |
| | 11.5- | | | | | | | | | | | | | 2.1 | | 3.0 |
| | 10.5- | | | | | | | | | | | | | 3.4 | | 3.4 |
| | 9.5- | 10.4 | | 1.3- | 23.3 | | | | | | | | | 4.9 | | 5.8 |
| _ E | - 5.5- 6.5- 7.5- 8.5- | 7.6 | EC) | 19.0- | 21.0 | | | | | | | | | 5.7 | | 6.9 |
| ج 10 (ع | 7.5- | 7.8 | S/W) 03 | 16.8- | 18.8 | | | | | | | | | 4.6 | | 8.7 |
| 20.07 | 6.5- | 7.4 | ID SPEE | 14.5- | 16.6 | | 7 7 | 8 | 6.6 | 8.5 | 9 | 8 | ω, | 7.8 | | ω ω |
| 3 | 5.5- | † .9 | 3 | 12.3- | 14.3 | | | | | | | | | 9.6 | | 7.6 |
| | 4.5 | ت | | 10.1 | 72 | | 11 3 | 11.9 | 10.7 | 8.5 | 9.1 | → | 12.4 | 13.0 | | 1.0 |
| | 3.5- | 7.4 | | 7.8- | 9.8 | | 12.2 | 11.3 | 11.2 | 10.0 | 11.2 | 13.0 | 12.5 | 10.6 | | 1.5 |
| | 2.5- | 3.4 | | 5.6- | 7.6 | | 12.2 | 13.0 | 13.1 | 10.6 | 10.8 | 13.1 | 15.3 | 14.5 | 1 | 12.8 |
| | 1.5- | | | | | | | | | | | | | 10.1 | | 9.3 |
| | 0.5- | 1.4 | | | | | 9. | 7. | 2,2 | 1.2 | 7. | 1. | 1.6 | 1.6 | , | |
| | | <0.5 | | | - . | | 3.0 | 2.4 | 2.5 | 1.9 | 1.5 | 1.8 | 6. | 2.1 | , | 2.1 |
| | | | | | | , | m | 9 | 0 | 12 | 15 | 18 | 21 | 24 | | HOURS |
| | | | | | | | Ξ | | 0 | | - | | <u>~</u> | | ; | ALL |
| | | | | | | | | | | | | | | | | |

Table IV - 18

Percentage Frequency Summary For Wind Speed

CASCADE COUNTY - GREAT FALLS NWS AIRPORT (SPRING)

| | | ۸< | EED | /SEC) | 4.6 | +.5 | 5.4 | 5.1 | 5.4 | 5.2 | ÷.8 | 9.4 | 5.3 | |
|---------|--|----------|---------|---------|------|------|------|------|------|------|------|------|-------|--|
| | | Y | PEED SI | MPH)(M/ | 10.2 | | | | | | | | 11.9 | |
| | >14.4 | | | >32.2 (| | 0.0 | | | | | | | 0.7 1 | |
| | 13.5- 14.4 > | | | | 0.0 | 0.2 | 0.1 | 0.7 | 0.8 | 6.0 | 0.0 | 0.0 | 0.3 | |
| | 12.5- 1 13.4 | | | | | 0.3 | | | | | | | 1.2 | |
| | 11.5- 12.4 | | 25.7- | 27.7 | | ٥.4 | | | | | | | 1.4 | |
| | 10.5 - 11.4 | | | | | 1.0 | | | | | | | 1.8 | |
| | 9.5- | | 21.3- | 23.3 | | 2.3 | | | | | | | 3.7 | |
| Ή. | 9.4 | EC) | 19.0- | 21.0 | | 2.7 | | | | | | | 5.0 | |
| EED (M | 7.5-8.4 | (M/S | 16.8- | 18.8 | | 5.3 | | | | | | | 7.4 | |
| IND SPE | 6.5- | ID SPE | 14.5- | 9.91 | | 8.5 | | | | | | | 8.9 | |
| 3 | - 5.5- 6.5- 7.5- 8.5- 4 6.4 7.4 8.4 9.4 | = | 12.3- | 14.3 | | 11.3 | | | | | | | 10.1 | |
| | 7.5 | • | 10.1 | 12 | | | | | | | | 19.4 | 15.0 | |
| | 3.5- | | 7.8- | 9.8 | 20.8 | 17.5 | 13.1 | 11.9 | 12.8 | 14.3 | 19.4 | 19.2 | 16.1 | |
| | 2.5- | | 5.6- | 7.6 | 17.3 | | | | | | | | 15.1 | |
| | 1.5- | | | 5.4 | | 12.0 | | | | | | 9.9 | 9.5 | |
| | 0.5- | • | | 3.1 | | | | | | | | 2.5 | 1.8 | |
| | <0.5 | , | | 7.1 | | | | | | | | 1.9 | 2.0 | |
| | | | | | | 9 | 6 | 12 | 15 | 8 | | 54 | HOURS | |
| | | | | | I | | 0 | | _ | | œ | | ALL | |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

Table IV - 19

Percentage Frequency Summary For Wind Speed CASCADE COUNTY - GREAT FALLS NWS AIRPORT (SUMMER)

| | | ^ | 'EED | SEC) | 7.1 | 9. | | 7.1 | ~ | 7 | · " | 3.8 | 4.4 |
|--------|---------------------------|----------|----------|----------|------|------|------|------|------|------|----------------|-----------|-----------|
| | | | | (MPH)(M/ | | | | | | | | 8.6 | 9.8 |
| | >14.4 | | | >32.2 (| | | | | | | | 0.0 | 0.1 |
| | 13.5- | | | 32.2 > | | | | | | | | 0.0 | 0.1 |
| | 12.5- 1 13.4 | | | | | | | | | | | 0.5 | 4.0 |
| | 11,5- | 1 | 25.7- | 27.7 | | | | | | | | 0.1 | 9.0 |
| | 10.5 - 11.4 | 1 | 23.5- | 25.5 | | | | | | | | 0.2 | 0.7 |
| | 9.5- | | | | | | | | | | | 0.2 | 1.7 |
| Ę | 8.5- | EC) | 19.0- | 21.0 | | | | | | | | 0.7 | 2.4 |
| ED (MP | 7.5- | S/W) G | 16.8- | 18. 8 | | | | | | | | 1. | 4.3 |
| ND SPE | 6.5- | D SPEE | 14.5- | 16.6 | 4.1 | 3.5 | 5.4 | 7.2 | 7.8 | 9.7 | 4.8 | 4.3 | 5.9 |
| 3 | 5.5- 6.5- 7.5- | X . | 12.3- | 14.3 | 6.9 | 5.2 | 10.3 | 9.5 | 9.6 | 11.1 | 10.1 | 6.1 | 8.6 |
| | 4.5- | , | -10 | 12. | 13.7 | 14.0 | 14.3 | 14.1 | 15.8 | 16.7 | 18.1 | 17.3 | 15.5 |
| | 3.5-4.4 | , | -8- | 9.8 | 25.3 | 25.9 | 19.7 | 20.4 | 20.7 | 17.9 | 24.2 | 27.3 | 22.7 |
| | 2.5- 3.4 | · | 20. | 7.6 | 27.9 | 26.3 | 20.5 | 20.3 | 16.0 | 14.4 | 22.9 | 28.3 | 22.0 |
| | 1.5- 2.4 | 2 | 3.4- | 5.4 | 14.2 | 15.8 | 13.8 | 1.7 | 9.4 | 8.1 | 9.3 | 11.3 | 11.6 |
| | 0.5- 1.4 | , | <u>-</u> | 3.1 | 1.6 | 2.1 | 2.1 | 7.5 | 0. | 0.1 | 1.5 | 1.6 | 1.5 |
| | <0.5 | | , | | 3.1 | 3.7 | 1.8 | 1.3 | 9.0 | -: | - - | 1.2 | 8 |
| | | | | | н 3 | 9 | 0 | 12 | U 15 | | R 21 | 54 | ALL HOURS |
| | | | | | | | | | | | | | ₹ |

Table IV - 20

Percentage Frequency Summary for Wind Speed CASCADE COUNTY - GREAT FALLS NWS AIRPORT (AUTUMN)

| | | ۸< | PEED | //SEC) | 8.4 | 4.9 | 5.3 | 6.4 | 9.9 | 5.7 | 5.0 | 4.9 | 5.4 |
|------------------|-------------|---------|---------|----------|------|------|------|----------|------|------|------|------|-------|
| | | ¥ | SPEED S | (MPH)(M | | | | | | | | 11.0 | 12.2 |
| | >14.4 | | | >32.2 | | | | 1.0 | | | | | 9.0 |
| 6 | 14.4 | | 30.2- | 32.2 | | | | 1.3 | | | | | 9.0 |
| | 13.4 | | 28.0- | 30.0 | | | | 3.5 | | | | | 1.4 |
| | 12.4 | | 25.7- | 27.7 | | | | 3.3 | | | | | 1.5 |
| 5 | 11.4 | | 23.5- | 25.5 | | | | 4.2 | | | | | 2.2 |
| u C | 10.4 | | 21.3- | 23.3 | | | | 6.1 | | | | | 3.8 |
| H) | 9.4 | EC) | 19.0- | 21.0 | | | | 6.7 | | | | | 4.9 |
| ED (MF | 8.4 4.8 | S/W) C: | 16.8- | 18.8 | | | | 10.8 | | | | | 7.6 |
| ND SPE | 7.4 7.4 | ID SPEE | 14.5- | 16.6 | | | | 9.5 | | | | | 8.9 |
| WIND SPEED (MPH) | 7.7° 6.4 | 3 | 12.3- | 14.3 | 12.1 | 10.9 | 9.8 | ⊅ | 6.6 | 11.4 | 10.2 | 10.0 | 10.5 |
| - | + | | 10.1 | 2 | | | | | | | | 17.7 | 14.7 |
| C. | , t | | 7.8- | 9.8 | 19.9 | 16.6 | 13.7 | 1.1 | 12.2 | 17.0 | 21.9 | 20.1 | 16.6 |
| C | 3.4 | | 5.6- | 7.6 | 17.0 | 17.8 | 16.9 | 11.2 | 11.3 | 14.8 | 16.3 | 18.0 | 15.4 |
| £ | 2 2. 4 | | 3.4- | 5.4 | 9.6 | 10.2 | 9.0 | 8.0 | 7.2 | 4.9 | 7.2 | 8.8 | 8.3 |
| 4 | 1.4 | | 1.1- | 3.1 | 2.0 | | 7. | - 5 | 0.8 | 0 | 7 | 1.2 | 1,3 |
| | <0.5 | | | <u>↑</u> | 2.7 | 2.1 | 2.7 | 1.7 | 0.8 | 0.7 | 1.0 | 1.7 | 1.7 |
| | | | | | 8 | 9 | 6 | 12 | 7 | 9 | 21 | 5₫ | HOURS |
| | | | | | Ξ | | 0 | | _ | | œ | | ALL |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

Table IV - 21

Annual Wind Rose Distribution

CASCADE COUNTY - GREAT FALLS NWS AIRPORT

01/01/65 - 12/31/78

| _ | <u>(</u>) | отппо | Σm⊢mo | CO N O O N O | (S) |
|---|--------------|--|---|--|------------------------------|
| 10 I | (M/SEC) | -0.00 4.4.4.4.4.4.4.4.4.4.4.4.4.4.4.4.4.4 | ~ 0000-c | , wa wo ko wo | (MPH (M/S |
| IREC | ED (| <u> </u> | <u> </u> | 30.55.00 | IAL SPD SPD |
| 0 - | SPEED | ロトのりょう | 0 × 8 0 0 1 | 382200000000000000000000000000000000000 | CAL TOT |
| TOTAL <d!rection< td=""><td></td><td>0.0 1.6 16.4 16.0</td><td>0.85.2. 0.0.0.5.0</td><td>000000000000000000000000000000000000</td><td>0 0 0 0 4</td></d!rection<> | | 0.0 1.6 16.4 16.0 | 0.85.2. 0.0.0.5.0 | 000000000000000000000000000000000000 | 0 0 0 0 4 |
| NN | | 000000 | 448 | | 4.4 10.5 4.7 |
| ž | | 0.00 | 440 | | 4.3 4.8 4.8 |
| MNM | | 0.0000 | - - - - - - - - - | | 3.9 10.3 |
| 3 | | 0.00 | ~ | | 7.0 5.1 5.3 |
| MSM | | 0.0 0.1 1.8 7.7 | ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ | | |
| ΑS | | O- 80 9 W | -8~-~ | 0.000.000.000.000.000.000.000.000.000. | 5 67.0 |
| •• | | 000000 | madade | -00000000000 | 25. |
| SSW | | 000 | 6400 | 000000000000000000000000000000000000000 | 13.0 |
| S | | 0.0 0.1 0.1 0.1 0.1 | 4.00000 | | 4.8 10.1 4.5 |
| SSE | | | | | |
| SE | | 0.00000 | 000000 | | 2.9 |
| ESE | | 0.0000 | -00000 | | 3.1 |
| ш | | | | | |
| ENE | | | | | |
| NË | | | | | |
| NNE | | | | | |
| z | | | | 200000000000000000000000000000000000000 | |
| ۵ | - | | | | |
| DIRECT10N> | SPEED (MPH) | | 2822 | 2000 | CALL CALL OTAL MPH) |
|) I RE(| EED | - mm 1- 0 di | 700-min | 0001400-000-000 | 2.0 |
| | SF | | | NOUTE TERMINAND | A & ⊗ ⊗ |
| | | | | | |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES




Table IV - 22

CASCADE COUNTY - GREAT FALLS NWS AIRPORT

| | SCALE | |
|-----------|-------------|------------|
| MONTH | FACTOR (C) | FACTOR (K) |
| | (11/ 350) | |
| JANUARY | 7.3360 | 1,9960 |
| FEBRUARY | 7.4020 | 2,1990 |
| MARCH | 7.0660 | 2.0710 |
| APRIL | 6.5430 | 2,2810 |
| MAY | 6.2960 | 2,3180 |
| JUNE | 5.9260 | 2.3470 |
| JULY | 5.6600 | 2,4930 |
| AUGUST | 5.7710 | 2.4570 |
| SEPTEMBER | 6.1400 | 2.5050 |
| OCTOBER | 7.1040 | 2,5040 |
| NOVEMBER | 7.2100 | |
| DECEMBER | 7.8730 | - |
| YEAR | 6.7150 | 2.2100 |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

SALEM

CASCADE COUNTY

The Salem site is located 1 mile south of the Missouri River and about 15 miles east of Great Falls at 47 34 22 N and 111 02 34 W (Site No. 17 on Map II-1). Elevation at the site is 3,250 feet. The site was established by the Montana Power Company to measure background meteorological and air quality conditions for the company's proposed Salem project.

Wind data were collected from May 1980 through March 1984. Data from May 1, 1980 through October 31, 1981, were available for analysis for the first edition of the *Atlas*. The data set contains hourly averages of:

- Wind speed and direction at 10, 30, and 100 meters above ground level;
- Standard deviation of wind direction at 100 meters;
 - Average vertical wind direction at 100 meters;
 - Temperature at 10, 30, and 100 meters;
- Stability based on actual lapse rate of temperature with height.

The data were recorded by a data acquisition system that scanned each parameter every 30 seconds. All the electronic meteorological sensors were manufactured by Met One, Inc., and were mounted on a 100-meter tower. Winds were monitored long enough to adequately represent the wind resource at this location. The data are representative of the wind resource in the Great Falls area at relatively high and exposed sites.

Data recovery at the 10-meter level was excellent, ranging from 94.5 percent in January to 99.4 percent in April. Overall data recovery was 97.9 percent. Average annual wind speed was 10.2 miles per hour. Average monthly wind speed values ranged from 8.0 miles per hour in January to 14.3 miles per hour in December. Average annual wind power was 139.7 watts/m² and ranged from 50.5 watts/m² in August to 457.8 watts/m² in December.

At the 30-meter level, average annual wind speed was 11.9 miles per hour, with monthly average speeds ranging from 9.1 miles per hour in August to 16.3 miles per hour in December. Average annual wind power at this level was 214.6 watts/m², with a low monthly average of 79.2 watts/m² in August and a high monthly average of 671.5 watts/m² in December.

At the 100-meter level, wind speeds averaged 14.5 miles per hour on an annual basis, with an August low of 10.7 miles per hour and a November high of 20.8 miles per hour. Average annual wind power at this level was 379.4 watts/m², with average monthly values ranging from 127.9 watts/m² in August to 1041.2 watts/m² in December.

Further analysis of this site is presented in Chapter V.




Table IV - 23

CASCADE COUNTY - SALEM Monthly Wind Speed Distribution

05/01/80 - 10/31/81

| | 04 H H H F / 0 H O | |
|------|--|---|
| | CALM 0.6-1.5 1.6-2.5 3.6-3.5 6.6-7.5 7.6-8.5 13.6-11.5 13.6-13.5 13.6-13.5 13.6-13.5 | |
| YEAR | 0000 0000 0000 0000 0000 0000 0000 0000 0000 | 10.2 4.6 139.7 97.9 |
| DEC | 2280 23.7.2.7.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2 | 14.3 6.4 457.8 |
| NOV | 0.4014111000000000000000000000000000000 | 13.6 6.1 278.3 98.5 |
| 00.7 | 0.004.00.00.00.00.00.00.00.00.00.00.00.0 | 10.9 4.9 140.8 |
| SEP | 0.00 | 9.8 4.4 110.6 |
| AUG | 286.00 286.00 26.00 20.00 20.00 20.00 20.00 | 7.8 3.5 50.5 98.6 |
| JUL | 00000 0000 0000 0000 0000 0000 0000 0000 | 9.0 4.0 79.9 |
| NOC | 20.0 20.0 20.0 17.0 17.0 17.0 17.0 17.0 17.0 17.0 1 | 10.1 4.5 104.5 98.9 |
| MAY | 2242 2243 2011 116.0 118.3 10.3 10.3 10.3 10.3 10.3 10.3 10.3 10 | 8.7 3.9 67.5 |
| APR | 0.01 0.01 0.02 0.03 0.03 0.03 0.03 0.03 0.03 0.03 | 13.0 5.8 234.6 99.4 |
| MAR | 2001 2003 2003 2003 2003 2004 2004 2004 2004 | 8.6 3.8 77.9 4.86 |
| FEB | 0.004400000000000000000000000000000000 | 13.8 6.2 325.7 |
| JAN | 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0 | 8.0 3.6 59.4 94.5 |
| | CALM 1.3-2.6 3.6-5.6 P. 5.8-7.8 E. 10.3-12.3 D. 12.5-14.5 D. 12.2-14.5 H. 25.9-30.2 34.9-39.1 34.9-39.1 | AVERAGE SPEED (MPH) AVERAGE SPEED (M/SEC) AVERAGE WIND POWER (WATTS/M**2) PERCENT DATA RECOVERY |

CHS/X DEFPS

ANEMOMETER HEIGHT = 10 METERS = 33 FEET NUMBER OF OBSERVATIONS = 12927
PERCENTAGE DATA RECOVERY = 97.9

Table IV - 24

CASCADE COUNTY - SALEM

Monthly Average Wind Speed and Wind Power Density (30 Meters)

05/01/80 - 10/31/81

| 16.1 9.6 15.0 10.2 12.0 10.7 9.1 11.4 12.9 16.2 16.3 11.9 7.2 7.3 5.3 7.2 4.3 6.7 4.6 5.4 4.8 4.1 5.1 5.8 7.2 7.3 5.3 489.0 108.3 347.9 106.5 166.5 125.7 79.2 171.1 226.2 432.7 671.5 214.6 |
|--|
| 00 1 05 2 00 11 06 8 07 2 00 3 08 6 07 11 06 0 08 5 00 2 07 7 |
| 0 |

Table IV - 25

Monthly Average Wind Speed and Wind Power Density (100 Meters)

CASCADE COUNTY - SALEM

05/01/80 - 10/31/81

| YEAR | 14.5 | 6.5 | 379.4 | | 97.0 |
|------|------------------------|---------------------------------|--|--------------------------|------------------------------------|
| DEC | 17.5 | 5,3 6.5 5.7 4.8 6.2 7.3 9.3 7.8 | 292.8 216.6 127.9 306.2 441.9 857.1 1041.2 | | 86.1 |
| NOV | 20.8 | 9.3 | 857.1 | | 98.5 |
| OCT | 16.4 | 7.3 | 441.9 | | 0.96 |
| SEP | 13.8 | 6.2 | 306.2 | | 96.8 97.2 99.3 98.6 97.4 96.0 98.5 |
| AUG | 10.7 | 8.4 | 127.9 | | 98.6 |
| JUL | 12.7 | 5.7 | 216.6 | | 99.3 |
| JUN | 14.6 | 6.5 | 292.8 | | 97.2 |
| MA∀ | 11.8 | 5.3 | 169.1 | | 96.8 |
| APR | • | | 583.1 | | 99.3 |
| MAR | 20.3 12.1 | 5.4 | 958.4 223.8 583.1 | | 99.1 98.4 99.3 |
| FEB | 20.3 | 9.1 | 958.4 | | 1.66 |
| JAN | 12.7 | 5.7 | 240.0 | | 97.6 |
| | AVERAGE SPEED (MPH) | AVERAGE SPEED (M/SEC) | AVERAGE WIND POWER | (WATTS/M*2) PERCENT DATA | RECOVERY |

HIGHWOOD BENCH

CHOUTEAU COUNTY

The Highwood Bench site is located approximately 10 miles northwest of Highwood at 47 41 01 N and 110 54 02 W (Site No. 18 on Map II-1). Highwood Bench is an extensive flat, sloping southeastward up to the Highwood Mountains. The monitoring site is near the top of a gentle rise where wind flow is unobstructed. Elevation at the site is 3,325 feet. This site was established by the Bureau of Reclamation as part of its Northern Great Plains Wind Energy Study. The Department of Natural Resources and Conservation assumed responsibility for the monitoring site in October 1982.

Collection of wind data began on June 5, 1981 and continued through June 17, 1983. Data from the wind sensors were recorded continuously on cassette tape at the site. These tapes were processed further by computer to yield hourly averages of wind speed, wind direction, the average cube of the hourly speed, and standard deviation of the hourly speed. In addition, the maximum and minimum instantaneous values of wind speed during each hour were recorded. Anemometer height was 10 meters above ground level.

B1.5 percent in December. Overall data recovery based on data provided to DNRC was 68.0 percent. Actual data recovery, as reported by the Bureau of Reclamation in hard copy, was higher; however, numerous data tapes from the period between July 1982 and May 1983 were not available for re-analysis. The missing data do not appear to have greatly influenced monthly and yearly averages. When the site was decommissioned, the tail of the wind vane was

found to be badly bent downwards. Thus, the wind direction data is questionable, especially after the tail on the wind vane was bent, whenever that was.

Winds were monitored long enough to adequately represent the wind resource at the site. The data are representative of a limited area on the northwest and north-facing slopes of the Highwood Mountains.

Average annual wind speed at this site was 10.5 miles per hour. Average monthly wind speed varied from 7.4 miles per hour in August to 12.8 miles per hour in December.

Average monthly wind power ranged from 26.9 watts/m² in August to 224.9 watts/m² in December. Average annual wind power was 122.6 watts/m².




Table IV - 26

Monthly Wind Speed Distribution

CHOUTEAU COUNTY - HIGHWOOD BENCH

| | | CALM | | 1.0-1.3 P | | | | | | | | | 5.0-5.4 R | | | | | | | | | 9,0-11,2 | 11,3-13,4 | 13.5-15.6 | 15.7-17.9 | >17.9 | | | | | | | |
|---------------------|------|------|------------------|-----------|-----|---------|------|------|-------------|-----|------|----------|-------------|----------|------|------|-----|------|-------------|-----------|-----------|-----------|-----------|-----------|-----------|-------|---------|------------------------|---------------|-----------------------|--------------|--------------|---|
| | YEAR | 2.4 | , , | 2.4 | 5.1 | 5.7 | 7.5 | 6.7 | 8.0 | 6.8 | 8.1 | 9.9 | 9.9 | 4.6 | 4.5 | 3,3 | 2.7 | 3.0 | 1.9 | 2.1 | 1.6 | 5.6 | 2.0 | 9.0 | 0.1 | 0.0 | | 10.5 | 4.7 | | 122.6 | 0.00 | 3 |
| | DEC | 0.6 | , c | 3.0 | 5.0 | 4.8 | 4.5 | 4.9 | 5.2 | 4.7 | 4.7 | 4.5 | 3.2 | 4.1 | 5.4 | 3,3 | 4.5 | 6.4 | 3.0 | 9°6 | 2.0 | 11.3 | 3.9 | 2.0 | 0.2 | 0.2 | | 12.8 | 5.7 | | 224.9 | 2 | 3 |
| | AOM | 0.0 | | 2.6 | 4.4 | 3,3 | 5.0 | 5,9 | 6.1 | 5,3 | 6.4 | 5,2 | 8 5 | 6.7 | 8.6 | 5.1 | 4.5 | 4.5 | 5.6 | 1.7 | 2.6 | 7.0 | 1.9 | 0.0 | 0.0 | 0.0 | | 11.7 | 5.2 | | 135.5 | 6.4 A | 5 |
| | DC | 0.0 | | | 3.5 | ۳. ۳ | 7.0 | 6,3 | 8.7 | 9.1 | 11.6 | 7.5 | 9,3 | 5.0 | ω. | 3.1 | 2.7 | 5.6 | 1.6 | 1.5 | 1:1 | 6.4 | 2.3 | 0.5 | 0.0 | 0.0 | | 11.0 | 4.9 | | 121.2 | 71 0 | • |
| | SE | 0.0 | , a | 2.1 | 6.2 | 6.9 | 10.0 | 7.9 | 9,3 | 9.4 | 10.7 | 6.8 | 6.8 | 4.1 | 4.2 | 3,3 | 1.6 | 2.2 | 0.8 | 1.4 | 0.4 | 1.5 | 0.5 | 0.1 | 0.0 | 0.0 | | 9.2 | 4.1 | | 63.0 | 0 17 | • |
| 17/83 | AUG | 0.0 | , c | 1.7 | 9.9 | 11.1 | 17.0 | 12.0 | 14.4 | 6.6 | 11.3 | ω | 3,3 | 1.7 | 0.7 | 0.3 | 0.3 | 0.0 | 0.2 | 0.2 | 0.0 | 0.3 | 0.0 | 0.0 | 0.0 | 0.0 | | 7.4 | 3,3 | | 56.9 | 28 7 | Ì |
| 06/05/81 - 06/17/83 | JI. | 18.5 | | 2.4 | 6.4 | 7.0 | 8.6 | 6.7 | 0° 8 | 5.8 | 6.9 | 6.2 | 5.2 | 2.7 | 1.9 | 1.7 | 1.4 | 1.0 | 1:1 | | 6.0 | 3,5 | 1:0 | 0.0 | 0.0 | 0.0 | | 7.5 | 3.4 | | 62.3 | 78.2 |) 1 |
| /50/90 | Ŋ | 0.6 | 1.0 | 2.0 | 4.2 | 4.6 | 8.3 | 7.2 | 8.7 | 7.5 | 10.4 | 9.0 | 7.9 | 4.8 | 4.4 | 2.5 | 2.1 | 3.0 | 2.1 | | 1.3 | 4.5 | 0.4 | 0.1 | 0.0 | 0.0 | | 10.0 | 4.5 | | 82.8 | λ. C | 3 |
| | MAY | 0.0 | 2 7 7 8 | 1.9 | 3.7 | 5.5 | 6.8 | 5.9 | 6.9 | 7.2 | 10.7 | 7.6 | 10.5 | ည် | 6.7 | 3.8 | 2.7 | 3.1 | 1.8 | 1.7 | 2.1 | 4.1 | 9.0 | 0.1 | 0.0 | 0.0 | | 10.7 | 4.8 | | 96.1 | £ | 3 |
| | APR | 0.0 | - 0 | 1.8 | 4.2 | 4.8 | 7.4 | 6.4 | 8. 9 | 7.1 | 7.1 | ري ص | 0.9 | 6.4 | 5.4 | 4.8 | 3,7 | 3.6 | 2.9 | 2.9 | 2.1 | 6.4 | 2,3 | 8 | 0.1 | 0.0 | | 11.6 | 5.2 | | 144.9 | 9 | ? |
| | #AR | 4.2 | · - | 3.2 | 5.3 | 7.0 | 6.1 | 7.6 | 10.2 | 6.8 | 9.5 | 6.7 | 6.7 | ۳. ۳. | 1.9 | 2.2 | 2.3 | 2.1 | 1.4 | 2.2 | 1.7 | 4.0 | 3.0 | 0.6 | 0.1 | 0.0 | | 6 8 | 4.4 | | 117.2 | 5 | 3 |
| | FEB | 1.6 | - ~ | 0 | 5.8 | 5,3 | 5,9 | 4.4 | 7.2 | 4.5 | 4,3 | 5.4 | 7.0 | 5.2 | 6.1 | 4.8 | 3.5 | 3.0 | 1.9 | 3.0 | 2.5 | 8.1 | 5.6 | 0,5 | 0.0 | 0.0 | | 11.2 | 5.0 | | 153.2 | 67 | : |
| | JAN | 0.4 | 7 · V | 0.0 | Ġ. | ۲. | ۲. | | ۲. | 5.1 | ນ້ຳ | ب. د. | 4.1 | 3.4 | 4.1 | 2.9 | 1.5 | 2,3 | 1.9 | 1.8 | 2,6 | 7.5 | 4.6 | 1.6 | 0.4 | 0.4 | | 11.0 | 4.9 | | 194.9 | 7 69 | <u>.</u> |
| | | CALM | 1 1-2 0 | 2.1 | m | 4 | ഹ് | | 7. | οÓ | 6 | 10. | E 11.1-12.0 | 12.1 | 13.1 | 14.1 | | 16.] | R 17.1-18.0 | 18.1-19.0 | 19.1-20.0 | 20.1-25.0 | | 30,1-35,0 | 35.1-40.0 | >40.0 | AVERAGE | SPEED (MPH) AVERAGE | SPEED (M/SEC) | AVERAGE WIND POWER | (WATTS/M**2) | PENCENI DATA | 111111111111111111111111111111111111111 |

SOURCE: GEORESEARCH, INC.

ANDMOMETER HEIGHT = 10 METERS = 33 FEET NUMBER OF OBSERVATIONS = 12120 PERCENTAGE DATA RECOVERY = 68.0

MILES CITY FAA AIRPORT

CUSTER COUNTY

The Miles City Airport is located approximately 2 miles northwest of Miles City at 46 25 48 N and 105 52 12 W (Site No. 19 on Map II-1). Elevation at the airport is 2,631 feet. Meteorological data have been collected at this site for many years by the Federal Aviation Administration.

These data, primarily collected for aviation and weather forecasting uses, consist of short-term (5 minutes or less) averages of wind speed and wind direction, as well as other meteorological parameters. Data were gathered once per hour. The data have been analyzed by Battelle Pacific Northwest Laboratories. Because of a change in recording interval, the data set was split into two parts for analysis: January 1, 1948, through December 31, 1964; and January 1, 1965, through December 31, 1978. Data from the latter period only were selected for inclusion in the Montana Wind Energy Atlas.

The data set for Miles City consists of summaries of observations made every third hour from January 1, 1965, through December 31, 1978. The anemometer was mounted on a ground mast at a height of 12.2 meters. The site is representative of much of the high ground along the Yellowstone River in southeastern Montana.

Average monthly wind speeds ranged from 9.8 miles per hour during July, August, and November to 11.9 miles per hour in April. Average annual wind speed was 10.5 miles per hour.

Average monthly wind power ranged from 91.0 watts/m² in July and August to 163.0 watts/m² in April. Average annual wind power was 116.0 watts/m².




Table IV - 27

Monthly Wind Speed Distribution

CUSTER COUNTY - MILES CITY FAA AIRPORT

01/01/65 - 12/31/78

| | _ | U | ۵ د | لبا | نيا ا | 6 | | 7 | لية | . | ليا | œ | Ś | _ | 'n | LL) | () | 0 | _ | _ | | | | | | | | | |
|------|------------|----------|------------|----------------|----------|-----|---------|-----|-------------|------------|----------|----------|--------|----------|----------------|-----|---------------|----------|----------|-----|----------|----|------------|--------------|----------|---------|--------------|--------------|-------------------------|
| | <0.5 | | | | | | | | | | | | | | | | | | | | | _+ | _+ | _+ | _+ | | | | |
| | - | ٠ ، | ~ | === | 7 | 9 | 7 | 00 | 0 | 2 | Ξ | 2 | 33 | ₹ | 5 | 16 | 7 | 8 | 9 | 2 | 5 | 0 | 35 | 9 | 9 | | | | |
| | - | | ٠,٢ | | | ٠. | ٠. | ٠. | | ٠, | ٠. | ٠. | ٠. | ٠, | ٠. | | . [| | | 1. | | | . L | .1 | ^ | | | | |
| | Ą. | ۰- | ۸ | 8 | - | 5 | 9 | 7 | 00 | 0 | 10 | 7 | 12 | 13 | 7 | 15 | 16 | 17 | 8 | 19 | 20 | 25 | 30, | 35. | | | | | |
| YEAR | ٠ | | | | | | | | | | | | | | | | | | | | | | | | | | 2 | 7 | 0 |
| ⋝ | יעיכ | 20 | 6 | 23 | 5 | 6 | ī | 6 | m | ď | 0 | Ö | 0 | Ö | Ö | Ö | Ö | Ö | <u>.</u> | Ö | Ö | o. | Ö | Ö | Ö | | 10. | ⋣ | 116.0 |
| DEC | - | - « | · | 0 | N | 9 | 9 | 6 | r | 0 | 9 | # | # | | - | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | _ | 2 | |
| D | יעיכ | تا د | 20 | 24 | 15. | 0, | Ŋ | 'n. | က | 'n | 0 | · | 0 | o. | o. | 0 | 0 | 0 | o. | o. | 0 | 0 | o. | o. | o. | | 10. | ᅻ. | 109.0 |
| > | ∞ | v | · | 9 | 0 | 6 | m | ~ | 2 | ထ | ~ | m | 9 | ĸ | , _ | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 80 | † | |
| NO. | 90 | א | 20. | 25. | 16. | φ. | ď | ⇒. | ď | ή. | Ö | 0 | Ö | 0 | o. | 0 | 0 | o. | 0 | 0 | 0 | 0 | o. | Ö | 0 | | 6 | ‡ | 113.0 106.0 |
| H | مره | J C | က | 8 | a | 0 | 2 | 6 | | ر ا | œ | 9 | 7 | N | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | က | 9 | 0 1 |
| ОСТ | ⇒ ⊂ | | ; -: | | ч. | | | | | | | | | | | | | | | | | | | | | | 10. | 4 | 13. |
| ۵ | 00 | , v | · - | 0 | 6 | 0 | 7 | ~ | Ŋ | σ, | _ | 2 | a | <u>-</u> | cu | 0 | 0 | _ | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | · • | ٠, | |
| SEP | 90 | | | • | | • | | | | | | | | | | | | | | | | | | | | | 0 | 4.6 | 108.0 |
| () | 9- | | | | | | | | | | | | | | | | | | | | | | | | | | _ | _ | |
| AUG | 200 | | ٠ | | ø | | | | | | | | | | | | | | | | | | | | | | 9.8 | 4.4 | 91.0 |
| 1 | ٠ | . ~ | | | | _ | _ | | _ | | | | | | | _ | _ | | _ | _ | _ | _ | _ | _ | _ | | | | |
| JUL | 6.6 | | 0 | Š | ö | | | | | | | | | | | | | | | | | | | | | | 9.8 | 4.4 | 91.0 |
| _ | _ | _ | | 7 | | | | | _ | | | | | | | | | | | | | | | | | | | | 6 |
| NOC | 0.0 | | | | | | | | | | | | | | | | | | | | | | | | | | 0.5 | 4.7 | 106.0 |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | - | | 10 |
| MAY | 90 | | | • | | • | | • | | | | | | | | | | | | | | | | _ | | | 1.4 | 5.1 | 139.0 |
| | ⇒ C | | | | | | | | | | | | | | | | | | | | | | | | | | - | Δ, | 13. |
| APR | | | 2.5 | 6.0 | 7.0 | .5 | 6.9 | .5 | 9.0 | ≯ . | . 2 | 9. | 6. | .3 | .2 | | 0.0 | _ | <u>.</u> | 0.0 | 0.0 | 0. | 0. | 0 | 0. | | 6. | <u>ش</u> | 0. |
| | ⇒ C | | = | ಸ | _ | ~ | • | • | • ` | , | • | _ | _ | _ | _ | _ | _ | | _ | _ | <u> </u> | _ | _ | ٠, | . | | = | _ν | 163 |
| MAR | 9.6 | | | • | | | • | | | | | • | | | | | | | • | | | | | | | | 1.0 | 6 | 0. |
| _ | 20 | | 3 | N | 7 | F | w | Ų | | ca | _ | 0 | O | 0 | 0 | 0 | 0 | ٠, | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | Ξ | 4 | 138 |
| EB | ~ - | ~ | 5 | 6 | 6. | 9 | ~ | ۳. | ₹. | φ. | ⇒. | r, | 7 | <u>ښ</u> | - . | 0. | - | ٠. | 0 | 0 | • | 0. | 0 | 0 | 0. | | - | ī. | 0. |
| _ | 90 | רצו | 20 | 8 | - | ĊΛ | ц | עיו | m | _ | 0 | 0 | 0 | 0 | 0 | 0 | Φ. | <u>۔</u> | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 10 | # | 11 |
| JAN | ر ا | <u>ښ</u> | ٣. | - . | φ. | ٣. | | φ. | ⊅ . | m. | ٥ | ⊅. | į. | - | _ | 0 | 0 | ٠, | 0 | 0 | 0 | 0. | 0 | 0, | ٥. | | <u>-</u> | ī, | 114.0 111 |
| 7 | 90. | 9 | $^{\circ}$ | 24 | L) | 0 | Ŋ | r, | 'n | S | 0 | 0 | 0 | 0 | 0 | 0 | 0 | ٠ | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 10.1 | 4 | 114 |
| | 25 | | | | | | | | | | | | | | | | | | | | | | | | | | _ | (၁ | |
| | <u> </u> | 5 | - 7 | | 7 | 7 | 7 | 7 | Ÿ | Ÿ | Ÿ | Ş | ñ | ς, | ~ | ů. | ∾. | ᅻ. | Ţ. | 7 | رن | 9 | <u>-</u> - | ن ن | 90 | يز | JE H | SE(| WIND POWER (WATTS/M**2) |
| | ~~ | 3.4 | 5.6 | ė. | ÷. | 3 | ÷. | ω. | 0 | m | ~ | <u>-</u> | ٠ د | o. | - | · / | 9 | - | ÷ ' | 9 | 0 | 0 | ۰. | - | ^\ | AVERAGE | RAG FAG | RAG. | ō. ¥ |
| | CALM | , | ٠, | | <u>~</u> | - | 7 | ~ | | , | κί | 2 | ~ | <u>ج</u> | 3 | 35 | 36 | γ'n. | . | ⇒. | <u> </u> | 5 | 9 | 5 | | AVE | YEEL AVE | ED AVE | ND TTS |
| | _ | | S | ٩ | ليا | ليا | 0 | | Σ | - | | البا | က | <u> </u> | . | 0 | > 1 | × | | | | | | | | | SP | SPE | ₹X |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

12.2 METERS 40.0 FEET = ANEMOMETER HEIGHT =

BATTELLE PACIFIC NORTHWEST LABORATORIES SOURCE:

SCOBEY BORDER

DANIELS COUNTY


The Scobey Border air monitoring site is located on the United States-Canadian border 14 miles north of Scobey at 49 00 00 N and 105 24 00 W (Site No. 20 on Map II-1). Elevation at the site is 2,467 feet. The site was established by the Montana Air Quality Bureau as part of the Poplar River Study to measure particulate and sulfur dioxide concentrations, and to collect data on several meteorological parameters.

Wind data have been collected at the station since March 2, 1977. Data through April 26, 1982, were available for analysis. The data set contains hourly averages for wind speed and wind direction, which until 1980 were manually reduced from stripchart records. In 1980, a data acquisition system that scanned each parameter several times per minute was installed. A Climatronics electronic anemometer and wind vane is used to monitor winds at the site. Anemometer height is 4 meters. Winds have been monitored long enough at this site to represent the wind resource of the northeastern corner of Montana.

Overall data recovery was 78.2 percent, varying from 49.9 percent in June to 99.2 percent in December. The data indicate significant periods of calm during the winter months. This is probably due, in part, to freezing of the anemometer cups. Consequently, wind speeds recorded during the winter may be lower than they actually were. The data otherwise appear to be accurate.

Average annual wind speed at the site was 7.2 miles per hour. Average monthly wind speeds varied from 4.5 miles per hour in September to 8.8 miles per hour in April.

Average monthly wind power ranged from 4.1 watts/m² in September to 156.2 watts/m² in February. Average annual wind power was 85.3 watts/m².



NAMMO EMPHKN/NMCONO

Table IV - 28 Monthly Wind Speed Distribution

DANIELS COUNTY - SCOBEY BORDER

03/02/77 - 04/26/82

| | 7-1-1-2-2-3-3-2-1-1-2-2-3-3-2-1-1-2-2-3-3-2-1-1-2-2-3-3-2-1-1-2-2-3-3-2-1-1-2-2-3-3-2-1-1-1-1 | 7.7.7 |
|------|--|--|
| YEAR | | יסיבר ממ הימ |
| DEC | 81-00 80-00 90 90-00 90 90-00 90-00 90 90-00 90 90-00 90 90-00 90 90-00 90 90-00 90 90 90-00 90 90 90 90 90 90 90 90 90 90 90 90 9 | |
| NOV | 00-00000000000000000000000000000000000 | |
| OCT | $\begin{array}{c} O L \\ L$ | |
| SEP | 10000000000000000000000000000000000000 | |
| AUG | 8-4-80-4-80-000000000000000000000000000 | |
| JUL | - 0- 1- 1- 1- 1- 1- 1- 1- 1- 1- 1- 1- 1- 1- | |
| NOC | 04/000 06/000 08/000 08/00 00 00 00 00 00 00 00 00 00 00 00 00 | |
| MAY | - ロスト・ト・ファッシュ サイン ロー・ファット・ファット・ファット・ファット・ファット・ファット・ファット・ファット | |
| APR | - 000000000000000000000000000000000000 | |
| MAR | ###################################### | |
| FEB | $\begin{array}{cccccccccccccccccccccccccccccccccccc$ | |
| JAN | 4w90 80-00 80 80-00 80 80 80-00 80 80 80 80 80 80 80 80 80 80 80 80 8 | |
| | | 11-30. 11-35. 11-40. 11-35. 11-40. 10. 10. 10. 10. 10. 10. 10. 1 |
| | | |

ANEMOMETER HEIGHT = 4 METERS = 13 FEET NUMBER OF OBSERVATIONS = 35329 PERCENTAGE DATA RECOVERY = 78.2

SCOBEY HANRAHAN

DANIELS COUNTY

The Scobey Hanrahan site is located approximately 14 miles northeast of Scobey at 48 53 47 N and 105 17 05 W (Site No. 21 on Map II-1). Elevation at the site is 2,781 feet. This monitoring station was established by the Montana Air Quality Bureau to measure sulfur dioxide concentrations in the air and various meteorological parameters as part of the Poplar River Study.

The land to the south of the station is a flat, elevated bench used primarily for dryland grain farming. To the north and west, the land drops away into the Poplar River valley. Relief in the area is 300 to 400 feet. Access to the site is provided by gravel roads maintained by the county. During the winter, access occasionally is difficult because of blowing snow.

Land in the area is, for the most part, privately owned. However, a considerable amount of state-owned land lies west and north of the station. Most of this land is leased to private landowners for agricultural uses.

The area is served by the Sheridan Electric Cooperative and by Montana-Dakota Utilities Company. A 57 kV transmission line runs approximately 10 miles south of the site. A microwave relay tower sits on a hill approximately 1 mile northeast of the site. There is no commercial air traffic in the area. The station, however, is located near the northern edge of the Williston MOA (Military Operations Area), so there are occasional military training exercises between 4,000 and 18,000 feet MSL.

Wind speed data have been gathered at the site since April 1, 1981. Data through March 31, 1982, were available for analysis. The data set contains hourly averages of wind speed and wind direction recorded by a data acquisition system that scans each parameter several times per minute. Wind data at the site are recorded by a Climatronics electronic anemometer and wind vane on a 10-meter tower. Winds have been monitored long enough at this site to give a good indication of the wind resource at this location, which is representative of exposed sites in the northeastern corner of Montana.

The data set is relatively complete, with data recovery ranging from 61.6 percent in March to 98.7 percent in February. Data recovery was 88.9 percent for the entire period of analysis.

Average monthly wind speeds ranged from 7.2 miles per hour in November to 15.6 miles per hour in May. Average annual wind speed was 11.6 miles per hour.

Average annual wind power was 178.3 watts/m². Average monthly wind power ranged from 59.8 watts/m² in November to 378.0 watts/m² in March

Average seasonal wind speeds were 10.4 miles per hour in summer, 10.6 miles per hour in autumn, 12.4 miles per hour in winter, and 13.1 miles per hour in spring. The highest average wind speeds occurred from noon to mid-afternoon during all seasons except winter, when they occurred during the early evening. The lowest average wind speeds occurred from after midnight to dawn in spring, before dawn in summer and autumn, and during mid-morning in winter. The diurnal range of average wind speeds was greatest in spring and least in winter.

Winds were most common from the west-southwest through northwest. Winds from the north-northeast through east-northeast were least common. By direction, average wind speeds varied from 8.5 miles per hour for winds from the south-southwest to 13.9 miles per hour for northwesterly winds.



Table IV - 29

Monthly Wind Speed Distribution

DANIELS COUNTY - SCOBEY HANRAHAN

04/01/81 - 03/31/82

| | CALM 0.1- 0.4 | 1.0-1.3 | 4 | 6. | . e | 2 | | - 6 | ٠. | 7. | | <u>;</u> d | 0.00 | -7: | <u>, </u> | -9. | 2 | | 7. | _ | | | | | |
|------|-------------------|--------------|---------------|-----------|-----------|----------|------------|------------|----------|----------|----------------|------------|------|----------|--|----------|----------|------|-------|-------------------|------------------------|---------------|-----------------------|------------------------------|----------|
| YEAR | 000 | 3 C | 2.0 | יי פיי | 4.0 7. | 2.2 | 10.6 | , & , ± | 3.1 | | , r , r | | 1.7 | 3.8 | 6. | 3.4 | | , c | 0.4 | 0.1 | 11.6 | 5.5 | | 178.3 | 88.9 |
| DEC | - 0 - 5 - 1 | 8.5 | 5.2 | 0.0 | 10.4 | 8 | 7.0 | 6.7 | 4.6 | <u>۱</u> | N 4 | 0 4 | 10 | 0.9 | 1.5 | 2.1 | | 0 - | 0.0 | 0.0 | 6.6 | 7. | | 143.3 | 90.5 |
| NOV | 19.7 | | | | | | | | | | | | | | | | | | | | 7.2 | 3.2 | | 59.8 | 97.5 |
| 100 | 000 | 0.0 | 0.5 | 2,0 | 7.7 | 0.3 | - 2 | 14.5 | 0.5 | | - : | 7 0 | 0.0 | 11.6 | 0.0 | ω, ω, | 9,0 | , 0 | 0.0 | 0.0 | 13.6 | 6.1 | | 202.1 | 83.6 |
| SEP | 0.00 | | • | ٠ | | | • | | | • | | | | | | | | | | | 11.3 | 5.1 | | 157.4 | 91.6 |
| AUG | 0.00 | | • | • | | | • | | | | • | | | | | | • | | | | 4.6 | 4.2 | | 73.1 | 95.4 |
| JUL | 0.00 | 1.0 | 2.0 | 2.5 | 2,7. 5 | 6.0 | 18.4 | 10.3 | 2.5 | 10.3 | - 0 | | , O | 5.6 | 0.3 | 5.7 | 3 C | | 0.0 | 0.5 | 10.6 | 4.8 | | 112.5 | 86.2 |
| NUE | 000 | | • | | | | • | | | | • | ٠ | | | • | | | | | | 11.3 | 5.1 | | 144.4 | 74.9 |
| MAY | 000 | | | | | | | | | | | | | | | | | | | | 15.6 | 7.0 | | 323.0 | 89.3 |
| APR | 9.0 | 5.0 | 77. | 6.1 | 10.2 | 7.0 | ۰, « دن | | 4.0 | w, | . · · | 0.0 | 2.3 | 2.1 | ٠٠/ | 9 | - c | - C | 0.3 | 0.3 | 7.6 | 4.3 | | 127.9 | 93.8 |
| MAR | 1.7 | | | | | • | | | | | ٠ | | | | | | • | • | | | 14.4 | φ.9 | | 378.0 | 61.6 |
| FEB | 5.5. | - '- - r. | 1 | 0.0 | 9.9 | 1 | 9.0 | | 3.3 | ر. د. | - - | | - 8- | 1.8 | 5.6 | | c ∞ c | 20 | 0.0 | 0.0 | 12.9 | 5.8 | | 199.0 | 7.86 |
| NAC | 0.0 | | | • | | • | • | | | | • | | | | • | | | | | | 14.3 | 4.9 | | 302.0 | 98.5 |
| | CAL .1-1. | | 3.1-4. | 4.1-5. | | 7.1-8. | 8.1-9. | 10.1-11. | 11.1-12. | 12.1-13. | 13.1-14. | 14.1-12. | | 17.1-18. | . 1-19. | . 1-20. | . 1-25. | 1.35 | 1-40. | > 4 0. | AVERAGE SPEED (MPH) | SPEED (M/SEC) | AVEKAGE WIND POWER | (WATTS/M**2) PERCENT DATA | RECOVERY |

DNOCES/SRHHRM DREPS

ANEMOMETER HEIGHT = 10 METERS = 33 FEET NUMBER OF OBSERVATIONS = 7783
PERCENTAGE DATA RECOVERY = 88.9

Table IV - 30

Percentage Frequency Summary For Wind Speed

DANIELS COUNTY - SCOBEY HANRAHAN (WINTER)

04/01/81 - 03/31/82

| | | | , | سا | /SEC) | . 5 | 9.6 | 5.3 | 5.2 | 5.2 | 5.2 | 2.2 | 5.2 | 2.2 | 5.1 | 5.3 | 5.7 | ٠.7 | 8.5 | 6.5 | 5.7 | 5.7 | 8,0 | 6.0 | 0.0 | 9.0 | 7.7 | 8. | 9.6 | 5.6 |
|--------|----------|---------------|----------|--------|--------|----------|-------|----------|-----|---|----------|--------------|----------|-----|-----|--------------|------|-------------|----------------|-----|------|----------|----------|----------|----------|--------------|-----|------|----------|-----------|
| | | | | E0 | H) (M/ | 7 | ≠. | ٥. | ۲. | ۲. | ۲. | ۲. | ۲. | 9. | ≠. | 0. | . 7 | 6. | 6 | _ | ω, | ۲. | 0. | vi | ლ. | ٥, | Φ, | 0. | r. | 12.4 |
| | | | A | SPE | MP) | 12 | 12 | Ξ | = | Ξ | Ξ | Ξ | Ξ | Ξ | - | נו | 12 | 12 | 72 | 13 | 12 | 12 | 13 | -3 | -3 | 33 | 72 | 12 | 12 | |
| | | >40.0 | | 17.9 | | | | | | 0.0 | | | | | | | | | | | | | | | | | | | | 0.0 |
| | | 40.04 | | 17.9 > | | 1.2 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 1.2 | 0.0 | 0.0 | 0.0 | 0.0 | 1.2 | 0.0 | -: | 1:1 | - | <u>-</u> | - | - | <u>-</u> | 0.0 | -5 | - | <u>-</u> | 9.0 |
| | <u>+</u> | 5.0 | 7. | 5.6 | | • | | • | • | 0.0 | | • | • | • | | | ٠ | | | • | • | | | | • | 2.3 | | | | 1.1 |
| | 1- 3(| 0. | 2- 13 | 7. | | 2.3 | 3,5 | 3,5 | 2.4 | 4.7 | 4.7 | 4.7 | 3.5 | 4,7 | 1 7 | 1.7 | 7. 4 | 7.0 | 5.7 | 3.4 | 5.7 | 2,3 | -: | 2,3 | 2,3 | 0.0 | 3.5 | 4.6 | 4.6 | 3.8 |
| | 25. | .0 30 | - | | | | • | • | | 7. | • | | | | • | | | | | | • | | | • | • | | | | | 6.9 |
| | 20. | 25 | 0 | 11.2 | | _ | | | | 8 | | | | | | | | | | 6 1 | | | | | | • | | | | 9 / |
| | 18.1- | 20.0 | σ. | 8 | | | | • | | ======================================= | | | | | | | | | | | | | | | | | | | | 7. |
| | ۲. | 18.0 | , r | · 00 | | 1.2 | 7.0 | 1.2 | 1.2 | 4.7 | 3, | 2.4 | 4.7 | 4.7 | - 2 | 2.4 | 3.5 | 1.2 | 2.3 | 3.4 | 2.3 | 9.5 | 4.6 | 4.6 | 4.6 | 3.4 | 7.0 | 5.7 | | 3.6 |
| (MPH) | | 6.0 (M/SF | 3-2 | 7.2 | | - | | | | 12.9 | | | | | | _ | _ | _ | _ | _ | | _ | _ | _ | _ | | - | | _ | 17.2 |
| SPEED | .1- 14 | 4.0 . | } | m | • | | | | | 11.8 | | | | | | | | | | | | | | | | | | | | 11.8 |
| QN I X | 5 | 2.0 1 VIND | . I | 1 | | 0.5 | 2.8 | 9.7 | 8.2 | 10.6 | 8. | 2.9 | 5.9 | 7.1 | 9.3 | 9.0 | 1.6 | 5.8 | 0.5 | 8.0 | 0.2 | 8.0 | 0.3 | 1.5 | 6.9 | 8.0 | 9. | 8.0 | 9.5 | 6.6 |
| | 7 | _ | 7 | 4.5 | | ∞ | _ | + | _ | 14.1 | = | Ŋ | Ŋ | œ. | 3 | , | Ŋ | | Ŋ | 2 | _ | 6 | N | 0 | 2 | N | m | 6 | 6 | η.0 |
| | | 10.0 | | , | | | | | | | | | | | | | | | | | | | | | | | | | | 9 |
| | • | 8.0 | ~ | 3.6 | | 9. | 10. | 9. | œ | 8.2 | ζ. | - | <u>1</u> | ۲. | 7. | 9. | 9. | <u>-</u> | 12. | 10. | Ξ. | φ. | ġ | 9 | 6. | 14. | 12. | 0. | 10. | 9. |
| | 4.1- | 0.9 | -8 | 2.7 | | 9.3 | 5.8 | 7.6 | 8.2 | 5.9 | 10.6 | 9 | 7.1 | 7.1 | 5.8 | 8.2 | 9.3 | 8.1 | 9.1 | 8.0 | 11.4 | 8.0 | 6.9 | 6.9 | 8 | 4.6 | 0 | 10.3 | 9.5 | 7.9 |
| | 2, 1- | 4.0 | 0.0 | 1.8 | | 5.8 | œ | 8.2 | 7.6 | 9.4 | 7.1 | 8.2 | 8.2 | 7. | 9.3 | 7.1 | 5.8 | 3.5 | 5.7 | 4.5 | 5.7 | 5.7 | 4.6 | 4.6 | 4.6 | 4.6 | 7.0 | 4.6 | 6.9 | 6.5 |
| | | | | 0.9 | | 0.0 | 0.0 | 1.2 | 2.4 | 2.4 | 2.4 | 4.7 | 3,2 | 5.0 | + 7 | 2.4 | 0.0 | 3,5 | -: | 3.4 | 0.0 | _ | | <u>-</u> | _ | - | | 0.0 | 0.0 | 1.8 |
| | | CALM | | CALM | | 1.2 | 0.0 | 1.2 | 0.0 | 1.2 | 1.2 | - 5 | 2.4 | 2.4 | 2. | 2.4 | 2.3 | 2.3 | - - | 0.0 | 0.0 | - | -: | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 6.0 |
| | | _ | | J | | , | 7 | က | 4 | 7 | 9 | 7 | © | 6 | 10 | Ξ | 12 | 13 | 7 | 5 | 9 | 17 | ∞ | 19 | 20 | 21 | 22 | 23 | 54 | ours |
| | | | | | | | | | | | | | | Ξ | | 0 | | > | | œ | | | | | | | | | | ALL HOURS |

Table IV - 31

Percentage Frequency Summary for Wind Speed

DANIELS COUNTY - SCOBEY HANRAHAN (SPRING)

04/01/81 - 03/31/82

| | | | * | SPEE | (M/SE | 4.9 | 7 | 4.5 | Š | 7 | S | 5 | 70 | 6.2 | 6.5 | 6.7 | 6.9 | 6.9 | 7.0 | 7.0 | 9 | 9 | 9 | 5 | 7 | 5.2 | ري 1. | | 5.6 | 5.8 |
|-------|----------|------------------|----------|-------|-------|------|------|------|----------|------|----------|------|------|------|------|------|--------------|----------------|------|------|------|------|------|------|------|------|----------|------|------|-------|
| | | | ₹ | SPEED | (MPH) | 11.0 | 10.9 | 11.0 | 1.1 | 11.4 | <u>-</u> | 11.9 | 13.2 | 13.9 | 14.5 | 15.1 | 15.5 | 15.5 | 15.6 | 15.7 | 15.3 | 14.4 | 13.7 | 12.7 | 11.6 | 11.7 | 12.0 | 11.9 | 12.6 | 13.1 |
| | | >40.0 | | 17.9 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 1.4 | 1.4 | . | 0.0 | 1.3 | 1.3 | 1.3 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 1.3 | ή.0 |
| | | 40.04 | 5.7- | < 6.7 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | ٦. | 4.2 | 1.4 | 2.8 | 2.7 | 1 . | 0.0 | 0.0 | 0.0 | .3 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 9.0 |
| | <u>+</u> | 5.0 | .5- 1 | 5.6 | | • | • | | | 4.0 | | | | • | • | • | • | | | | • | • | | | | | | • | | 2.3 |
| | | 30.03 | -2. | 13.4 | | ٠ | • | • | • | 1.3 | | | • | | • | • | • | • | • | • | | - | • | • | | | • | • | • | 4.5 |
| | | 25.0 3 | 9.0- 11 | 11.2 | | 6.8 | 5.5 | 5.5 | 5.3 | 8.0 | 7.4 | 5.6 | 5.6 | 5.6 | 12.3 | 13.9 | 18.9 | 16.2 | 16.0 | 18.2 | 20.5 | 16.7 | 12.8 | 10.4 | 11.7 | 6.5 | 3.9 | 8.0 | 5.6 | 10.1 |
| | <u>-</u> | 20.02 | | 8.9 | | - | - | ~ | ۲- | 2.7 | - | Ŋ | m | ۲. | ď | ď | ≠ | Ŋ | m | ٥ų | ∞ | ≠. | _ | ٨ | Z | Ŋ | 0 | 0. | 6 | 6.2 |
| | 1 | 18.0 | .2, | 8.0 | | | • | | | 5.3 | | | | | | | • | | | • | • | | • | ٠ | ٠ | | • | | • | 6.1 |
| (MPH) | 1-1 | 16.0 1 (M/SFC | 1 | 7.2 | | 2.7 | 1.0 | 13.7 | 9.3 | 8.0 | 6.8 | 8.3 | 8.3 | 8.3 | ₩. | 4.2 | 8.1 | 6.8 | 5.3 | 11.7 | 7.7 | 0.6 | 14.1 | 10.4 | 9.1 | 9.1 | 11.8 | 12.0 | 9.5 | 8.7 |
| SPEED | 1-1 | 4.0 SPFFD | - 17 | 6.3 | | 13.5 | 13.7 | 12.3 | 8.0 | 10.7 | 4.1 | 6.9 | 8.3 | 11.1 | 8.9 | 5.6 | 9.5 | 6.8 | 10.7 | 6.9 | 11.5 | 12.8 | 7.7 | 13.0 | 13.0 | 10.4 | 7.9 | 10.7 | 11.8 | 7.6 |
| MIND | 1-15 | 0 12.0 1 WIND | -5- | 5.4 | | | | | | 6.7 | | | | | | | | | | | | | | | | | | | | 10.5 |
| | 3.1- 10 | . 0.01 | 3.6- 4 | 4.5 | | 13.5 | 9.6 | 13.7 | 22.7 | 20.0 | 14.9 | 18.1 | 8.3 | 5.6 | 9.6 | 8.3 | 9.5 | 14.9 | 8.0 | 11.7 | ₽.9 | 4.9 | 1.5 | 14.3 | 7.8 | 18.2 | 14.5 | 8.0 | 19.7 | 12.3 |
| | | 8.0 | | 3.6 | | 18.9 | 17.8 | 20.5 | 12.0 | 13,3 | 16.2 | 13.9 | 15.3 | 15.3 | 11.0 | 1.1 | 8.1 | 5.4 | 5,3 | 6.5 | 7.7 | 3.8 | 4.9 | 6.5 | 16.9 | 15.6 | 11.8 | 18.7 | 9.5 | 11.9 |
| | | | 1.8- | 2.7 | | 8.1 | 11.0 | 11.0 | 9.3 | 8.0 | 13.5 | - | 1.1 | 7.6 | 12.3 | 15.3 | 10.8 | 5.4 | 9.3 | 3.9 | φ.9 | 10.3 | 3.8 | 10.4 | 10.4 | 9.1 | 11.8 | 9.3 | 11.8 | 7.6 |
| | 2.1- | 4.0 | -0.0 | 8. | | 8.1 | 6.8 | ₽. | 6.7 | 9.3 | 8.1 | 5.6 | 2.8 | 7. | 0.0 | 0.0 | ⊅. ∵ | 6.8 | 1.3 | 5.5 | 3,00 | 3.8 | 0.6 | 6.5 | 6.5 | 5.6 | 1.3 | 0.4 | 5.3 | 4.6 |
| | | 2.0 | | | | 7. | 7. | 2.7 | 0.0 | 0 | 0.0 | 0 0 | 0.0 | 1.4 | 7. | 7. | 7. | 0.0 | 1.3 | 1.3 | 0.0 | 5,6 | 1.3 | 0.0 | 3.9 | 5 6 | 2.6 | 1.3 | 1,3 | 1.2 |
| | | CALM | | CALM | | 7. | ٦. | 7. | 2.7 | 2,7 | 2.7 | 2.8 | 2.8 | 2.8 | 2.7 | 1.4 | 0.0 | 0.0 | 0.0 | 0.0 | 1.3 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 1.1 |
| | | | | | | - | 7 | ٣ | _ | ح | 9 | 7 | 80 | 6 | 10 | Ξ | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 5φ | HOURS |
| | | | | | | | | | | | | | | I | | 0 | | > | | ~ | | | | | | | | | | ALL |

SOURCE: GEORESEARCH, INC.

75

Table IV - 32

Percentage Frequency Summary for Wind Speed

DANIELS COUNTY - SCOBEY HANRAHAN (SUMMER)

04/01/81 - 03/31/82

| | | | | 0.5 | (M/SEC) | | _ | ~ | _ | ~ | _ | ~ | _ | ~ | | _ | - | _ | • | _ | . ~ | . ~ | ۵. | | • | _ | • | _ | _ | |
|-------|------------------|----------------|------|--------|------------|------|------------|--------------|----------|-------|------|------------|--------------|------|------|------|------|------|------|--------|----------|------------|------|---------|----------|---------------|--------|------------|--------------|-----------|
| | | | | _ | _ | | | | | | | | | | | | | | | | | | | | | | | | | 4.6 |
| | | | ΛΔ | SPEF | (MPH) | 7 6 | 9.5 | ω. 8 | 8.7 | 8.5 | 8.8 | 9.5 | 11.0 | 10.7 | 1.4 | 12.0 | 12.1 | 12.0 | 11.5 | 12.0 | 12.4 | 12.3 | 11.7 | 10.8 | 9.3 | 9.5 | 9.3 | 8 | 6 | 10.4 |
| | | >40 . 0 | | 17.9 | \ | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | -3 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.1 |
| | 5.1- | 40.0 | 5 7- | 17.9 > | | | | | | | | | | _ | - | | - | | | 0.0 | _ | _ | _ | - | _ | | | | | 0.5 |
| | <u>-</u> | 35.0 | Ę. | 15.6 |) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | .3 | 0.0 | 1.3 | 0.0 | 0.0 | 1.3 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.2 |
| | | 0 | 2-1 | 3.4 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | .3 | 1.3 | .3 | 0.0 | ۳, | 0.0 | 1.3 | .3 | 0.0 | ٠. | 1,3 | 0.0 | .3 | 0.0 | 1.3 | 1.3 | 9.0 |
| | | 25.0 | ď | 11.2 | | 1.2 | 0.0 | 1.3 | 1,3 | 1.3 | 3.9 | 5.6 | 3.9 | 3.0 | 3 | 8.0 | 5.0 | 8.0 | 3.8 | 5.0 | 7.5 | | 4.9 | 1.3 | 1.3 | 1,3 | 5. | .3 | 1.3 | 3.5 |
| | 18.1- 2 | | - 8 | 8 | | • | | • | | | | • | | | | | | | | 5.0 | | - | _ | | - | | _ | | _ | 2.7 |
| | <u>-</u> | 18.0 | • | 0.8 | | | | | | | | | | | | | | | | 13,8 | | | | | | | | | | 6.5 |
| (MPH) | _ | 16.0 (M/SF | 6.3- | ٥ | | | • | • | • | • | • | | • | | | | | | | 6.3 | | | - | | | | | - | _ | 8.6 |
| SPEED | 2.1-1 | 14.0 SPFFD | 5.4- | 6.3 | | 13.6 | 6.3 | 10.0 | 6.3 | 7.7 | 16.9 | 1.8 | 19.5 | 11.7 | 13.9 | 17.7 | 13.8 | 8,0 | 12.8 | 13.8 | 15.0 | - | 1 | 15.2 | 10.1 | 3 | 10.3 | 5 | 16.7 | 12.1 |
| QN IX | | . 0 21 VIND | 1 | | | 13.6 | 20.3 | 25.0 | 10.1 | 16.7 | 10.4 | 15.8 | ۲. | 19.5 | 16.5 | 12.7 | 17.5 | 16.5 | 10.3 | 8.8 | 7.5 | ر. ر. و | 6.6 | 13.9 | 12.7 | 16.5 | 15.4 | 9.0 | 11.5 | 13.6 |
| | | 0.0 | | 4.5 | | | | | | | | | | | | | | | | 18.8 | | | | | | | | | | 17.2 |
| | 6.1- | 0.8 | | 3.6 | | 19.8 | 1 . | 8.8 | 25.3 | _ | 22.1 | 19.7 | 13.0 | 8 | 7. | 7.6 | 11.3 | 13.9 | 15.4 | 8.8 | 5.0 | 12.7 | 34.8 | & 0, | 16.5 | 5. | 7.4 | 2.8 | 15.4 | 14.9 |
| | - - | | | 2.7 | | 16.0 | 17.7 | 21.3 | 17.7 | 23.1 | 14.3 | ر ان | 9 | 10.4 | 8 | 7.6 | 6.3 | 7.6 | 7.7 | ص ص | × × | 6.3 | 9.5 | 17.7 | 16.5 | 20.3 | 23.1 | 20.5 | 17.9 | 13.4 |
| | 2.1 | 0.4 | -0.0 | 8. | (| 6.2 | ۳, ص | 5.0 | 5.1 | 7.7 | 11.7 | ω, · | . · · | ~. | 6.3 | | 5.0 | .3 | 5.6 | က် | ر. د | ر د ا | | ω, | 91 | 9.7 | ر د | 12.8 | , , | 5.8 |
| | 0. 1. | 2.0 | 0.1- | 6.0 | (| 0.0 | ~ | 0.0 | 0.0 | | ~ | <u>.</u> . | ~ | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0,0 | | 2 | ۳, ب | <u>ب</u> | <u>.</u> س | ٠ | <u>۔</u> . | • | 0.8 |
| | : | CALM | | CALM | (| 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0'0 | 0.0 | 0.0 | 0.0 | 0.0 | ٥. ٥. | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| | | | | | • | - 1 | Ω, | ~ 0 ± | = | Ŋ, | ا 0 | ~ (| x 0 (| , ۵ | 0: | = | 12 | -13 | 7 | 5, | ₽; | _ ; | Σ; | 9 | 25 | 5 | 22 | 23. | 4 7.7 | ALL HOURS |
| | | | | | | | | | | | | | ; | Ξ | • | 0 | ; | > | • | × | | | | | | | | | | ALL |

Table IV - 33

Percentage Frequency Summary for Wind Speed
DANIELS COUNTY - SCOBEY HANRAHAN (AUTUMN)

04/01/81 - 03/31/82

| | | | | | | | | | | | | | Ŧ | | 0 | | > | | œ | | | | | | | | | | ALL HOURS |
|----------|----------|-----------------|-------|--------------|--------------|--------------|--------|----------|-------|-------|-------|--------|--------|--------|----------|--------|--------|----------|--------|----------|------|--------------|--------------|------|----------|------|------|----------|-----------|
| | | | | | _ | N | ო. | ⇒ | ı, | 9 | 7 | œ | σ | 10 | Ξ | 12 | 13 | ‡ | 15 | 16 | 17 | 9 | 19 | 20 | 2 | 22 | 83 | 5₫ | OURS |
| | | CALM | | CALM | 7.1 | 7.1 | 7.1 | 7.1 | 80 | 8 | 7.1 | 7.1 | 7.1 | 7.1 | 7.1 | 7.1 | 7.1 | 7.1 | 7 1 | 5 | 5 | 5.9 | 5.0 | 5.9 | 5.9 | 5.9 | 5.0 | 7.1 | 6.8 |
| | 0.1 | 2.0 | 0.1- | 0.0 | 1.2 | 0.0 | 1.2 | 7.2 | 7.2 | 0.0 | 0.0 | 0.0 | 0.0 | 2.4 | 1.2 | 0.0 | | | | | | | | | | | | | 9.8 |
| | 2.1- | 0.4 | -0.0 | 8. | 2.4 | | | | | | | | | | | | | | | | | | | | | | | | 5.1 |
| | 4.1- | | 1.8- | | 15. | 15. | 17. | 19. | 15. | = | 10. | 9. | 9. | 7. | . | ထ | 9. | ø. | | <u>:</u> | 'n | 12 | 15. | 9. | = | = | 10. | 6 | 11.1 |
| | 6.1- | 8.0 | 2.7- | 3.6 | | | _ | _ | | _ | | | | | | | | | _ | | | | | | | | | | 11.2 |
| | | | 3.6- | 4.5 | | | | | | | | | | | | | | | 11.8 | | | | | | | | | | 12.6 |
| <u>=</u> | 10.1 | 웃동 | 4.5- | 5.4 | | | | | | | | | | | | | | | 7.1 | | | | | | | | | | 12.1 |
| ND SPE | 12.1- | 14.0 ND SPEI | 5.4- | 6.3 | | | | | | | | | | | | | | 10. | 10.6 | 15 | ø | œ | Z, | 'n, | 18. | Ξ. | 12. | <u>‡</u> | 11.1 |
| ED (MPF | 14.1- | 16.0 ED (M/S | 6.3- | 7.2 | 5 10.7 | 5 13.1 | 1 10.7 | 1 8. | 5 7.1 | 1 7.1 | 5 8.3 | 5 13.1 | 7 13.1 | 3 10.7 | 5 15.5 | 1 16.5 | 3 14.3 | | 5 11.8 | | | | | | | | | | 1.1 |
| = | | 18.0 (SEC) | | 8.0 | | αi | .≠ | m | 7 | 0 | # | ø. | ø. | ø. | ⇒. | ۲. | ۲. | ó | 11.8 | ٣ | 0 | . | , | 10. | <u>`</u> | 7 | 'n | αį | 5.8 |
| | | | 8.1- | 8.9 | 4.8 | 8.3 | 3.6 | 4.8 | 6.0 | 3.6 | 1.2 | 7.5 | 4.8 | 4.8 | 3.6 | 4.7 | 8.3 | 7.1 | 5.9 | 4.7 | 3.5 | 3.5 | 5.9 | 2.4 | 3.5 | 2.4 | ۲. ٦ | 3.5 | 4.4 |
| | | 25.0 | 9.0- | | - | , | m | ď | 33 | # | m | ς. | ď. | 9. | 10. | 9. | φ. | ∞ | 8.2 | 0 | ⇒. | S. | 0 | ÷ | <u>-</u> | m | ᅻ. | ⇒ | 4.8 |
| | | 30.0 | 11.2- | 13.4 | 3.6 | 2.4 | 2.4 | - 2 | 0.0 | 0.0 | 0.0 | 1.2 | 2.4 | 1.2 | 2.4 | 4.7 | ₽. | 4.8 | 4.7 | 5.9 | 4.7 | 7.5 | 2.4 | 1.2 | 5.₹ | 3.5 | 3.5 | 3.5 | 2.7 |
| | <u>-</u> | 35.0 | 13.5- | 15.6 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 1.2 | 2.4 | 1.2 | 0.0 | 1.2 | 2.4 | 0.0 | 0.0 | 0.0 | 0.0 | 1.2 | 1.2 | 0.0 | 0.0 | 0.0 | 0.4 |
| | | | 15.7- | 17.9 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| | | >40°0 | | ×17.9 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| | | | ¥ | SPEED | 10.2 | 10.1 | 9.8 | 7 6 | 9.3 | 9.4 | 80 | 9 | 10.3 | 11.2 | 11.8 | 12,1 | 12.3 | 12.6 | 12,9 | 12.2 | 11.1 | 10.1 | 9.5 | 10.0 | 10.3 | 10.2 | 10.4 | 10.4 | 10.6 |
| | | | ₹ | SPEE (M/S | | | | | | | | | | | | | | | Ŋ | | | | | | | | | | # |

Table IV - 34

Annual Wind Rose Distribution

DANIELS COUNTY - SCOBEY HANRAHAN

04/01/81 - 03/31/82

| × | SEC) | MAPH) |
|--|------------|--|
| ECTIC | (M/SEC | PD |
| <direction< td=""><td>SPEED</td><td>A <</td></direction<> | SPEED | A < |
| | S | マラン コース マール マース アース アース アース アース アース アース アース アース アース ア |
| TOTAL | | 0. |
| NN | | 00000000000000000000000000000000000000 |
| ¥ | | 00000000000000000000000000000000000000 |
| ANA | | 00000000000000000000000000000000000000 |
| 3 | | |
| MSM | | 000000000000000000000000000000000000000 |
| MS | | 0.0000000000000000000000000000000000000 |
| MSS | | 00000000000000000000000000000000000000 |
| s | | 00000000000000000000000000000000000000 |
| SSE | | |
| Š | | 000000000000000000000000000000000000000 |
| SE | | 0.0000000000000000000000000000000000000 |
| ESE | | 00000000000000000000000000000000000000 |
| ш | | 00000000000000000000000000000000000000 |
| ENE | | 0.000000000000000000000000000000000000 |
| N M | | 00000000000000000000000000000000000000 |
| NNE | | 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0 |
| z | | - 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0. |
| <u> </u> | PEED (MPH) | 7 CALM (MPH) |
|)T 10I | ED | |
| DIRECTION> | SPE | AV SPD AV |
| | | |




Table IV - 35

Coefficients of Weibull Distribution

DANIELS COUNTY - SCOBEY HANRAHAN

04/01/81 - 03/31/82

| SHAPE C) FACTOR (K) | 2.3374 2.5466 1.7912 1.9748 2.3549 2.3763 1.8763 1.8763 1.8763 | 1,9077 |
|------------------------|--|--------|
| SCALE FACTOR (M/SEC | 7.1983 6.8582 7.4268 4.3728 7.4408 5.6429 4.4512 6.7440 6.7440 5.0115 | 5.8299 |
| MONTH | JANUARY FEBRUARY MARCH APR!L MAY JUNE JULY AUGUST SEPTEMBER OCTOBER NOVEMBER | YEAR |

GLENDIVE MICROWAVE

DAWSON COUNTY

The Glendive Microwave site was located about 10 miles east of Glendive at 47 08 14 N and 104 32 45 W (Site No. 25 on Map II-1). Elevation at the site was 2.611 feet.

The area is rugged, badlands country, and access to the site is difficult, especially in the winter. Interstate Highway 94 runs to the south of the site. The land is mostly privately owned, although some sections of state-owned lands are scattered throughout the area.

A Montana-Dakota Utilities Company 57 kV transmission line runs within several miles of the site. The site itself was located at a microwave communications tower. The nearest commercial airport is at Glendive about 10 miles away.

Wind data were collected at the site by the Montana Air Quality Bureau from July 26, 1975, to September 14, 1977. The data set contains hourly averages for wind speed and wind direction manually reduced from stripchart records. The data were collected by a Meteorology Research, Inc., mechanical wind speed and direction recording unit. Anemometer height was 4 meters.


Overall data recovery during the period was poor—only 35.6 percent. No data were collected during January. Winds were monitored long enough at this site to provide an indication of the wind resource at this location, but care must be used in interpreting this data. The site was located on an exposed, elevated ridge and is representative of similarly exposed areas around the site.

Average monthly wind speeds at this site ranged from 9.8 miles per hour in November to 14.2 miles per hour in March. Average annual wind speed was 12.2 miles per hour. March and April were the windiest months, while the calmest months were September and November.

Average annual wind power at the site was 168.5 watts/m². Average monthly wind power values ranged from 91.5 watts/m² in November to 272.0 watts/m² in March.

Average seasonal wind speeds were 11.0 miles per hour in autumn, 11.9 miles per hour in summer, 12.4 miles per hour in winter, and 13.7 miles per hour in spring. The highest average wind speeds occurred in late morning during spring and autumn, in mid-morning during the summer, and in early evening during the winter. The lowest average wind speeds occurred in early evening during the autumn, in late evening during spring and summer, and in the early morning during the winter. The diurnal range of average wind speeds was greatest in spring and least in summer.

Winds from the south-southwest and west-northwest were most common. Winds from the northeast and east were least common. By direction, average wind speeds ranged from 9.4 miles per hour for northeasterly winds to 15.6 miles per hour for southeasterly winds.



NEHEU EHHERN/NHOOND

Table IV - 36

Monthly Wind Speed Distribution DAWSON COUNTY - GLENDIVE MICROWAVE

07/26/75 - 09/14/77

| | CGALM 00.1-1-10-1-10-1-10-1-10-1-10-1-1-10-1-1-10-1 | |
|------|--|---|
| YEAR | 000000000000000000000000000000000000000 | 12.2 5.4 168.5 35.6 |
| DEC | 0000-00-00-00-00-00-00-00-00-00-00-00-0 | 13.0 5.8 175.5 1 |
| NOV | 0000mnvvvvoonagamnannanno000 0001-0014000000000000000000000000000 | 9.8 4.4 91.5 |
| OCT | 00010404040404040400000000000000000000 | 12.1 5.4 171.7 39.5 |
| SEP | 000-04-00000000000000000000000000000000 | 10.9 4.9 116.2 |
| AUG | 00010000000000000000000000000000000000 | 11.5 5.1 155.9 51.3 |
| JUL | 00000000000000000000000000000000000000 | 5.2 5.2 138.3 |
| NUC | 000-04-0000000000000000000000000000000 | 12.8 5.7 175.1 47.3 |
| MAY | 00-00-000000000000000000000000000000000 | 12.9 5.8 215.0 |
| APR | 000-000-0000000000000000000000000000000 | 14.0 6.3 237.5 |
| MAR | 00004-000-004-004-00-000-00-00-00-00-0 | 14.2 6.3 272.0 22.2 |
| FEB | 000000000000000000000000000000000000000 | 11.6 5.2 135.8 |
| JAN | | ND O.0 |
| ٠ | CALM 0.1-1.0 1.1-2.0 3.1-4.0 B 3.1-4.0 B 6.1-7.0 C 1-7.0 C 1-10.0 C | AVERAGE SPEED (MPH) AVERAGE SPEED (M/SEC) AVERAGE WIND POWER (WATTS/M**2) PERCENT DATA RECOVERY |

ANEMOMETER HEIGHT = 4 METERS = 13 FEET NUMBER OF OBSERVATIONS = 6673 PERCENTAGE DATA RECOVERY = 35.6

Table IV - 37

Percentage Frequency Summary for Wind Speed
DAWSON COUNTY - GLENDIVE MICROWAVE (WINTER)

07/26/75 - 09/14/77

| T O D R | | | 7 | + | 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 | 80 % 0/1/0/20 0/1/0/20 0/1/20 | N. 12. 12. 12. 12. 12. 12. 12. 12. 12. 12 | | 2 1 0 2 1 0 2 1 1 0 2 | 71.00 | 50 8 | 20 20 20 21 20 21 20 20 20 20 20 20 20 20 20 20 20 20 20 | 25. 11 3. 0. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. | 30.11.13.51.00.00.00.00.00.00.00.00.00.00.00.00.00 | 35.7-1-17.7-1-17.7-1-1-17.7-1-1-17.7-1-17.7-1-17.7- | 0.0000000000000000000000000000000000000 | SP A MPH) | \$\$APA \text{APA \tex |
|-----------|-----------|-------|-----|-----|---------------------------------------|---|---|------|---|-------|------|--|---|--|--|---|------------|--|
| ALL HOURS | 0.0 | 0 | 4.5 | 7.2 | 7.8 | 9.9 | 14.9 | 15.7 | 13.1 | 10.4 | 8.5 | 7.3 | 0.9 | 0.0 | 0.0 | 0.0 | 12.4 | 5.6 |
| , 1001 | 100010010 | 11004 | | | | | | | | | | | | | | | | |

Table IV - 38

Percentage Frequency Summary for Wind Speed
DAWSON COUNTY - GLENDIVE MICROWAVE (SPRING)

07/26/75 - 09/14/77

| WIND SPEED (MPH) 6.1- 8.1- 10.1- 12.1- 14.1- 16.1- 18.1- 20.1- 25.1- 30. 8.0 10.0 12.0 14.0 16.0 18.0 20.0 25.0 30.0 35 WIND SPEED (M/SEC) | 2.7- 3.6- 4.5- 5.4- 6.3- 7.2- 8.1- 9.0-11.2-13.5-15.7- AV AV 3.6 4.5 5.4 6.3 7.2 8.0 8.9 11.2 13.4 15.6 17.9 >17.9 SPEED SPEED | A) (HdW) | 5 16.1 6.5 11.3 8.1 16.1 9.7 1.6 12.9 3.2 0.0 0.0 0.0 12.3 5 | 1 12.9 11.3 9.7 16.1 6.5 11.3 3.2 11.3 1.6 1.6 0.0 0.0 12.4 5 | 1 8.1 12.9 12.9 9.7 8.1 14.5 4.8 6.5 3.2 1.6 0.0 0.0 12.3 5 | 5 14.5 8.1 12.9 8.1 14.5 12.9 1.6 8.1 0.0 4.8 0.0 0.0 12.4 5 | 8 8.2 8.2 9.8 9.8 11.5 13.1 6.6 9.8 1.6 3.3 0.0 0.0 12.9 5 | 9 9.8 11.5 9.8 8.2 16.4 4.9 4.9 14.8 4.9 1.6 0.0 0.0 13.5 6 | 3 6.5 3.2 22.6 8.1 9.7 6.5 3.2 19.4 4.8 1.6 0.0 0.0 14.0 6 | 5 11.3 3.2 16.1 16.1 6.5 6.5 12.9 9.7 6.5 1.6 0.0 0.0 14.0 6 | 1 9.7 6.5 6.5 19.4 16.1 8.1 6.5 9.7 9.7 0.0 0.0 0.0 14.5 6 | 2 6.5 9.7 17.7 6.5 17.7 9.7 6.5 11.3 8.1 3.2 0.0 0.0 15.2 6 | 2 3.2 9.7 17.7 11.3 12.9 9.7 8.1 8.1 12.9 3.2 0.0 0.0 15.9 7 | 2 4.8 11.3 9.7 14.5 12.9 6.5 9.7 12.9 8.1 3.2 1.6 0.0 15.9 7 | 6 3.3 11.5 9.8 14.8 13.1 9.8 4.9 8.2 9.8 6.6 0.0 0.0 15.6 7 | 9 11.5 3.3 6.6 18.0 11.5 3.3 16.4 14.8 6.6 3.3 0.0 0.0 15.8 7 | 9 6.6 9.8 8.2 6.6 19.7 6.6 13.1 13.1 6.6 3.3 0.0 0.0 15.6 7 | 6 9.8 9.8 11.5 11.5 13.1 9.8 13.1 9.8 3.3 1.6 0.0 0.0 14.1 6 | 3 15.9 11.1 12.7 12.7 9.5 3.2 9.5 14.3 4.8 0.0 0.0 0.0 13.6 6 | 3 10.9 14.1 9.4 14.1 10.9 6.3 7.8 17.2 3.1 0.0 0.0 0.0 13.7 6 | 8 6.3 14.1 12.5 15.6 9.4 4.7 10.9 14.1 1.6 0.0 0.0 0.0 13.2 5 | 8 4.7 14.1 14.1 14.1 6.3 17.2 0.0 12.5 3.1 0.0 0.0 0.0 12.7 5 | 9 6.3 15.6 15.6 10.9 9.4 7.8 4.7 10.9 1.6 0.0 0.0 0.0 12.0 5 | 1 14.3 7.9 19.0 14.3 3.2 12.7 1.6 12.7 1.6 0.0 0.0 0.0 12.1 5 | 1 7.9 14.3 12.7 15.9 9.5 6.3 6.3 9.5 3.2 0.0 0.0 0.0 12.4 5 | 1 6.3 14.3 11.1 14.3 12.7 1.6 7.9 14.3 0.0 0.0 0.0 0.0 12.2 5 | 1 9.0 10.1 12.5 12.4 11.5 8.4 6.9 11.9 4.6 1.7 0.1 0.0 1 | |
|--|--|----------|--|---|---|--|--|---|--|--|--|---|--|--|---|---|---|--|---|---|---|---|--|---|---|---|--|--|
| .1- 12.1- 14.1- 16.2.0 14.0 16.0 1 | .5- 5.4- 6.3- 7 5.4 6.3 7.2 | | 8.1 16.1 | .7 16.1 6.5 1 | .9 9.7 8.1 1 | .9 8.1 14.5 1 | 8 9.8 11.5 1 | 8 8.2 16.4 | .6 8.1 9.7 | .1 16.1 6.5 | .5 19.4 16.1 | .7 6.5 17.7 | 7 11.3 12.9 | .7 14.5 12.9 | 8 14.8 13.1 | 6 18.0 11.5 | 2 6.6 19.7 | 5 11.5 13.1 | 7 12.7 9.5 | 4 14.1 10.9 | 5 15.6 9.4 | 1 14.1 6.3 1 | 6 10.9 9.4 | 0 14.3 3.2 1 | 7 15.9 9.5 | 1 14.3 12.7 | .5 12.4 11.5 | |
| 6.1- 8.1- 10 8.0 10.0 1 | 7- 3.6- 1 | | 5 16.1 6.5 | 1 12.9 11.3 | 1 8.1 12.9 | 5 14.5 8.1 | 8 8.2 8.2 | 9 9.8 11.5 | 3 6.5 3.2 | 5 11.3 3.2 | 1 9.7 6.5 | 2 6.5 9.7 | 2 3.2 9.7 | 2 4.8 11.3 | 5 3.3 11.5 | 9 11.5 3.3 | 9.6 9.9 | 9.8 9.8 | 3 15.9 11.1 | 3 10.9 14.1 | 8 6.3 14.1 | 8 4.7 14.1 | 9 6.3 15.6 | 1 14.3 7.9 | 1 7.9 14.3 | 1 6.3 14.3 | • | |
| 0.1- 2.1- 2.0 4.0 | 0.1- 0.0- 0.0- 0.9 0.9 1.8 | | 0.0 | 1.6 4.8 | 1.6 8.1 | 1.6 6.5 | 0.0 8.2 9. | 1.6 6.6 | 0.0 3.2 | 0.0 3.2 | 0.0 0.0 | 0.0 0.0 | 0.0 0.0 | 1.6 0.0 | 1.6 0.0 | 0.0 0.0 | 0.0 | 0.0 | 0.0 0.0 | 0.0 0.0 | 0.0 | 0.0 | 0.0 | 1.6 0.0 | 0.0 3.2 | 0.0 6.3 | 0.5 3.3 | |
| CALM | CALM | | | | | | 5 0.0 | | | ∞ (| | 10 | | | | 1 7 | | | | | | | | | | | ALL HOURS 0.0 | |

85

Table IV - 39

Percentage Frequency Summary for Wind Speed

DAWSON COUNTY - GLENDIVE MICROWAVE (SUMMER)

07/26/75 - 09/14/77

| | | | | | | | 3 | S | ED (MP) | T · | | , | | 1 | , | | | |
|-----------|--------------|-------|----------------------|----------------------|-------------|--------------|----------------------|------|-------------------------------|---------------|------|---------------|------|---------------------------|---------------|-------|--------------|---------------|
| | CALM | 0.1- | 2.1 - 4.0 | 4.1 . 6.0 | 6.1- 8.0 | 8.1- 10.0 | 10.1- 12. 12.0 14 | - 75 | . 14.1-) 16.0 :cn /w/c | 16.1- 18.0 | 20.0 | 20.1- 25.0 | 30.0 | 30.1 - 35.0 | 35.1- 40.0 | >40.0 | | |
| | | 0.1- | 0.0 | 1.8- | ~ | 3.6- | 4.5- | - | • | 7, | 8.1- | -0 | | • | | | A | ۸ |
| | CALM | 0.0 | | 2.7 | 3.6 | 4.5 | 5.4 | | 7.2 | - α | 8,9 | 11.2 | 13.4 | 15.6 | 17.9 | >17.9 | SPEED (MPH) | SPEED (M/SFC) |
| _ | 0.0 | 0.0 | 1,0 | 17.0 | | | 10.0 | 13.0 | 11.0 | | 7.0 | 8 | | | | | 11.3 | · · |
| 8 | 0.0 | 0. | 0.9 | 10.0 | 13.0 | 16.0 | 10.0 | 12.0 | 8.0 | 8 | 4.0 | 11.0 | 0.0 | 1.0 | 0.0 | 0.0 | 11.5 | 5.1 |
| က | 0.0 | 2.0 | 7.0 | 11.0 | | | 18.0 | 18.0 | 0.6 | | 5.0 | 8.0 | | | • | | 1.4 | 5.1 |
| = | 0.0 | 1.0 | 10.0 | 5.0 | | | 15.0 | 14.0 | 0.6 | | 9.0 | 4.0 | • | • | | | 11.2 | 5.0 |
| 5 | 0.0 | 3.0 | 6.1 | 6.1 | | | 18.2 | 14.1 | 9.1 | | 2.0 | 5.1 | | • | | • | 11.2 | 5.0 |
| 9 | 0.0 | 1.0 | 10.1 | 9.1 | | | 13.1 | 13,1 | 13.1 | | 5.1 | 7.1 | • | • | • | • | 1 5 | 5.0 |
| 7 | 0.0 | 1.0 | 6 | 14.1 | | | 13.1 | 9.1 | 12.1 | | 6.1 | 8.1 | | | • | • | 11.6 | 5.2 |
| 80 | 0.0 | 0.0 | 4.0 | 14.1 | • | | 10.1 | 11.1 | 13.1 | | 5.1 | œ - | • | | • | • | 12.0 | 5.4 |
| 6 н | 0.0 | 0.0 | 2.0 | 7.1 | • | • | 12.1 | 14.1 | 4.0 | | 5.1 | 13.1 | • | • | | • | 13.3 | 5.0 0 |
| 10 | 0.0 | 0.0 | 3.0 | 5.9 | | | 15.8 | 13.9 | 7.9 | | 5.9 | 13.9 | • | • | • | • | 3. | 5.9 |
| 0 11 | 0.0 | 0.0 | 1.0 | 12.9 | | • | 14.9 | 14.9 | 7.9 | | 5.0 | 8.9 | • | • | • | • | 12.4 | 5.5 .5 |
| | 0.0 | 0.0 | 1.0 | 9.9 | | | 20.8 | 7.9 | 6.9 | | 8.0 | 6 | | • | • | | 25 | 5.6 |
| U 13 | 0.0 | 0.0 | -0 | 15.8 | | | 11.9 | 6.6 | 5,0 | | 3.0 | 7.9 | • | | | • | 12.5 | 5.6 |
| # | 0.0 | 0.0 | 3 | 13.7 | | | 12.7 | 6.9 | 9.8 | - | 2.9 | 13.7 | ٠ | • | | • | 12.4 | r. r. |
| R 15 | 0.0 | 0.0 | 2 | 10.8 | | • | 10.8 | 14.7 | გ. გ. | | 2.9 | 13.7 | • | • | • | • | 12.7 | 5.7 |
| 16 | 0.0 | 0.0 | 2 9 | 7.8 | | • | 11.8 | 6.9 | 15.7 | | 5.9 | 12.7 | • | • | | | 12.4 | 5.6 |
| 17 | 0.0 | 0.0 | 5.9 | 11.8 | | | 13.7 | 8.8 | 12.7 | | 4.9 | 8. | • | • | • | • | 12.4 | ان ان |
| 18 | 0.0 | 0.0 | 2.9 | 11.8 | | | 9.8 | 10.8 | 8. | | 3.9 | & & | • | • | • | • | 12.7 | 2.7 |
| 19 | 0.0 | 0.0 | 4.0 | 0.4 | | • | 20.8 | 6.6 | 12.9 | | 5.9 | 9.9 | • | • | • | • | 12.5 | 5.6 |
| 20 | 0.0 | 0.0 | 4.0 | 0.4 | | • | 13.9 | 19.8 | 5.0 | • | 5.0 | 5.0 | • | • | • | • | - | ر د |
| 21 | 0.0 | 0.0 | 6.9 | 13.7 | - | - | 13.7 | 8.1. | 5.9 | | 5.9 | 8 8 | • | • | | • | 11.1 | 5.0 |
| 22 | 0.0 | 0.1 | 7.0 | 10.0 | • | | 14.0 | 10.0 | 9.0 | | 3.0 | 0.6 | • | • | • | • | 10.9 | 4.9 |
| 23 | 0.0 | 1.0 | 8.0 | 5.0 | ٠ | • | 10.0 | 15.0 | 16.0 | | 0.4 | 0.4 | ٠ | • | • | ٠ | 11.2 | 5.0 |
| 77 | 0.0 | 1.0 | 0.9 | 8.0 | • | • | 13.0 | 17.0 | 11.0 | | 5.0 | 0.4 | • | • | • | • | 11.2 | 5.0 |
| ALL HOURS | 0.0 | 0.5 | 4.9 | 6.6 | 11.4 | 13.3 | 13.6 | 12.3 | 9.7 | 7.3 | 4.9 | 9.5 | 2.2 | 9.0 | 0.0 | 0.0 | 11.9 | 5.3 |
| SOURCE: G | GEORESEARCH, | ARCH, | INC. | | | | | | | | | | | | | | | |

86

Table IV - 40

DAWSON COUNTY - GLENDIVE MICROWAVE (AUTUMN) Percentage Frequency Summary for Wind Speed

07/26/75 - 09/14/77

| | Š | _ | 2,1- | | 6,1- | 8.1- | 10.1- 12 | g - | EED (MPH 14.1- 1 | ~; | | | ' - | | 35.1- | | | |
|------------|-------|-----|------------|------|--------|------|---|---|---------------------|-----------|--------------|--------------|----------------|----------|-------|-------|------------|-------------|
| | CAL | 2.0 | 0.4 | 0.9 | ∞ | 10.0 | 12.0 XIX | 9.0 SPF | 16.0 FD (M/S | L | 20.0 | 25.0 | 30.0 | 35.0 | 40.0 | >40.0 | | |
| | | _ | 0.0 | | | 3.6- | 4.5- | -4. | 6 3- | <u> </u> | | 0. | | τ. | | | Α | > |
| | CAL | | π. | | m | 4.5 | 5.4 | 6.3 | 7.2 | 8.0 | 8.9 | 11.2 | 13.4 | 15.6 | 17.9 | >17.9 | SPEED | SPEED |
| | 1 0.0 | 0.0 | 8.0 | | 10 | 13.3 | 0.8 | 7 | 13 | 7 9 | r, | ď | , | 0 | c | | (MPH) | M/SEC) |
| | 2 0.0 | | 2.7 | | | 13.5 | 9.5 | 14.9 | 9.5 | 10.8 | | | | | 90 | | - ; - ; | ر ا ا |
| | | | 2.7 | | æ — | 12.2 | 13.5 | ω. | 13,5 | 2.2 | 5 | | | | | | | Г |
| | | | 7 | | 7 | 14.9 | 16.2 | 7 | 16.2 | 9 | . 8 | 17. | | - - | | | | Г |
| | | | - → . | | 9 | 14.9 | 16.2 | 2 | 8 | • | 2.7 | 2.7 | 2.7 | 0.0 | | | | - 0 |
| | | | ر م | | 9 | 17.6 | 16.2 | Š | 6.8 | 8. | 8.1 | 2.7 | 2.7 | 0.0 | 0.0 | | | , r. |
| | | | ر 1 - | | o, | 6 | 20.3 | Ŋ | 9.5 | 6.8 | 8.1 | - | 2.7 | 0.0 | 0.0 | | | יי מי |
| | | | 7 . | | m | 3.5 | 16.2 | 0 | 9.5 | 8.1 | | 5.4 | 0.0 | 0.0 | 0.0 | | 11.4 | , r. |
| _ | | | - I | | | 13.7 | 16.4 | 7 | 8.2 | 11.0 | 8 | 4.1 | 1.1 | 0.0 | | | 11.7 | |
| | | | 2.7 | | = | 13.7 | 15.1 | m | 12.3 | 9.6 | 5 | 9 | 2.7 | 0.0 | | | | , r. |
| - · | | | 8 | | ထ | 13.9 | 19.4 | <u>, </u> | 8.3 | 13.9 | 6.9 | 5.6 | 8 | 0 | | | | ָ י י |
| - ; | | | 5.6 | | ထ | 16.7 | 15.3 | o | 15.3 | 11.1 | 7.6 | 5.6 | 0 | 7 | | | 10 | , r. |
| - , - | | | 2,7 | | = | 19.2 | 13.7 | Ŋ | 15.1 | 9.6 | 5.5 | 5 5 | 0.0 | 7 | | | ν | , r, |
| | | | ٠. د | | _ | 17.8 | 17.8 | Ŋ | 11.0 | 8,2 | ٦.۲ | 8.9 | 0.0 | 1.4 | 0.0 | | 0 | 00 |
| -, Ľ | | | 72.3 | | တ် | 17.8 | 12.3 | 9 | 9.6 | 4.1 | - . → | 8.2 | 0.0 | 0.0 | 7 | | 20 | , r |
| - ,- | | | 0 v | | ٠. | 12:1 | 12.3 | m ı | 8 | 5.5 | 4.1 | 8.9 | 0.0 | - | 0.0 | | 10.4 | 7.7 |
| | | | 0 0 | | 2 6 | - ! | 0 i | اب | ر. د | - | 9.6 | 4.1 | 0.0 | 7. | 0.0 | | 10.7 | 8.4 |
| | | |) = 0 | | , c | 7.0 | , <u>, , , , , , , , , , , , , , , , , , </u> | ٠., | » د ت | ۳. د د | г. Б. | ÷. | <u>.</u> | 0.0 | 0.0 | | 9.8 | 4.4 |
| ۰ ۵ | | | | | , | 10 | · · · | 9 | ۰ ۱. | N. | ۳. | 5.3 | 0.0 | 0.0 | 0.0 | | 7.6 | 4.2 |
| 10 | | | - c | | ٥ | - c | 0.07 | ٥, | 0 | O 1 | ر ا | 2 | 0.0 | 0.0 | 0.0 | | 4.6 | 4.2 |
| 40 | | |) i | | Ö | 0.0 | 0.9 | 7 | 9.3 | 5 | 2.7 | 2 9 | 0.0 | 0.0 | 0.0 | | 10.0 | 2 |
| 4 | | | <u>+</u> (| | 'n | 16.0 | 8.0 | 0 | 8.0 | 6.7 | 5.3 | 2.7 | | 1.3 | 0.0 | | 10.3 | 7 7 |
| u (| | | 0 0 | | 0 | 8,0 | 21.3 | _ | 9.3 | 2 9 | 2.7 | 7 | 1,3 | 2 7 | 0.0 | |) | · (|
| V | | | 0.0 | | œ. | 12.0 | 10.7 | m | 9.3 | 2.9 | 6.7 | 2.7 | 1.3 | 1.3 | 0.0 | 0.0 | 10.7 | . 8 |
| ALL HOURS | S 0.0 | 0.2 | 7.3 | 10.3 | 11.2 | 14.6 | 15.2 | 11.7 | 6.6 | 7.5 | 5.7 | 4.7 | - | 9 | - | c | | - |
| | | | | | | | | | | | | | • | ; | ; | 3 | - | |

Table IV - 41

Annual Wind Rose Distribution

DAWSON COUNTY - GLENDIVE MICROWAVE

07/26/75 - 09/14/77

| <direction PEED (M/SEC)</direction | 1-0.4 2-1.3 S 3-2.7 E 3-2.7 E 3-2.7 E 3-2.7 E 4-0.4 M 1-4.9 H 1-4.9 |
|---|--|
| TOTAL <dire SPEED</dire | 0000000000000000000000000000000000000 |
| NNW TO | 0 |
| × | 00000000000000000000000000000000000000 |
| ANA ANA | 00000000000000000000000000000000000000 |
| 3 | 00000000000000000000000000000000000000 |
| MSM | 0.000000000000000000000000000000000000 |
| MS | 0 |
| SSW | 00000000000000000000000000000000000000 |
| S | 00000000000000000000000000000000000000 |
| SSE | 00000000000000000000000000000000000000 |
| SE | 00000000000000000000000000000000000000 |
| ESE | 00000000000000000000000000000000000000 |
| ш | 00000000000000000000000000000000000000 |
| ENE | 00000000000000000000000000000000000000 |
| Ä | 000000000000000000000000000000000000000 |
| M. E | 000000000000000000000000000000000000000 |
| z | 000000000000000000000000000000000000000 |
| DIRECTION> SPEED (MPH) | 0.1-1.0 2.1-3.0 3.1-4.0 8 4.1-5.0 P 5.1-6.0 B 7.1-6.0 P 7.1-6.0 P 10.1-11.0 11.1-12.0 11.1-12.0 12.1-13.0 13.1-14.0 14.1-15.0 15.1-16.0 16.1-17.0 17.1-18.0 18.1-19.0 19.1 |




Table IV - 42

Coefficients of Weibull Distribution

DAWSON COUNTY - GLENDIVE MICROWAVE

07/26/75 - 09/14/77

| | SCALE | SHAPE |
|-----------|-----------------------|------------|
| MONTH | FACTOR (C) (M/SEC) | FACTOR (K) |
| JANUARY | QN | QN |
| FEBRUARY | • | • |
| MARCH | | |
| APRIL | • | • |
| MAY | • | • |
| JUNE | 6.6135 | 2.4287 |
| JULY | • | • |
| AUGUST | • | |
| SEPTEMBER | | |
| OCTOBER | | |
| NOVEMBER | | |
| DECEMBER | • | • |
| YEAR | 5.4542 | 2.0683 |

ANACONDA C-HILL

DEER LODGE COUNTY

The C-Hill air monitoring site was located approximately 1 mile south of Anaconda at 46 06 03 N and 112 56 56 W (Site No. 27 on Map II-1). Elevation at the site was 7,193 feet. The site was established by the Anaconda Copper Company to measure concentrations of sulfur dioxide.

The land around the site is very rugged. To the southwest the Anaconda Range rises to more than 11,000 feet. To the north is the Flint Creek Range, with summits over 10,000 feet. The area is dissected by many deep canyons.

The Anaconda Copper Company owns the land around the site, so access is restricted. In general, land in the valleys is privately owned, and land in the mountains is controlled by the U.S. Forest Service. Several major electrical transmission lines run through the Deer Lodge valley. The nearest commercial airport is the Anaconda airport, about 5 miles northeast of the

Wind data from January 1, 1976, through May 31, 1979, were available for analysis. The data set consists of hourly averages of wind speed and wind direction manually reduced from stripchart records. Anemometer height was 10 meters.

Data recovery ranged from 39.4 percent in March to 91.7 percent in December. Overall data recovery was 59.6 percent.

Wind monitoring was conducted long enough to adequately represent the wind resource at this location. Because of the region's complex terrain, however, the data are representative only of a small area in the immediate vicinity of the site, which is on the crest of a high ridge. The rugged nature of the site limits the possibilities for development.

Average annual wind speed at this site was 13.3 miles per hour. Average monthly wind speeds ranged from 9.8 miles per hour in July to 17.5 miles per hour in December.

Average monthly wind power varied from 106.6 watts/m² in July to 618.3 watts/m² in December. Average annual wind power was 279.8 watts/m².

Average seasonal wind speeds were 11.2 miles per hour in summer, 11.4 miles per hour in autumn, 14.2 miles per hour in spring, and 15.4 miles per hour in winter. During all seasons the average wind speed was highest during the afternoon hours. In spring and summer, the highest average wind speeds occurred later in the afternoon (1700 and 1600 MST, respectively) than in the other two seasons. Average wind speeds were lowest from about 0700 to 0800 MST during all seasons except autumn, when the lowest average speeds occurred at 0400 MST.

The diurnal range of average hourly speeds was greatest in summer and least in winter. Most of the differences in average wind speeds among the seasons were due to variations in the average nighttime wind speed.

The annual wind rose distribution shows that winds were most common from the west to south-southwest. Winds from the north-northwest through north-northeast were least common. The highest average wind speeds, 14 to 19 miles per hour, were recorded for winds from the south-southwest through west. The lowest average speeds, less than 6 miles per hour, were recorded for winds from the north through north-northeast.



Table IV - 43

Monthly Wind Speed Distribution

DEER LODGE COUNTY - ANACONDA C-HILL

01/01/76 - 05/31/79

| | W-100 20 - 00 00 00 00 00 00 00 00 00 00 00 00 | |
|------|--|---|
| | 100000 | |
| | 5.3.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2. | |
| YEAR | 1111 | ж О ж Ф |
| ΥE | | 13.3 6.0 279.8 59.6 |
| DEC | | 17.5 7.8 618.3 |
| NOV | | 11.9 5.3 226.3 44.4 |
| 0CT | 00-000000000000000000000000000000000000 | 5.11 5.11 169.1 |
| SEP | $\begin{array}{cccccccccccccccccccccccccccccccccccc$ | 11.2 5.0 145.4 |
| AUG | - uawoudina + wo wo + - r - r - r o wo wo + r - r - r - r o wo wo + r - r - r - r o wo wo + r - r - r - r - r o wo wo + r - r - r - r - r o wo wo + r - r - r - r - r - r o wo wo + r - r - r - r - r - r - r - r - r - r | 10.9 4.9 129.8 |
| JUL | $\begin{array}{cccccccccccccccccccccccccccccccccccc$ | 9.8 4.4 106.6 |
| JUN | 00-80000000000000000000000000000000000 | 13.0 5.8 223.5 ' |
| MAY | $\begin{array}{c} 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 $ | 13.6 6.1 215.6 2 74.4 |
| APR | - 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 | 14.0 6.3 290.0 2 |
| MAR | 00-00000000000000000000000000000000000 | 15.5 6.9 410.5 2 |
| FEB | 0-00mm4mm0mmmmmmm0m040 10-040-80000-40000400000 | 16.5 7.4 191.5 ¹ |
| JAN | 0-88445000000000000000000000000000000000 | 12.5 5.6 264.5 ¹ |
| | CALM 0.1-1.0 1.1-2.0 8 2.1-3.0 1.1-2.0 B 3.1-4.0 B 6.1-7.0 C 1-7.0 C 1-7.0 C 1-7.0 C 1-1.0 C 1-1.0 | AVERAGE SPEED (MPH) AVERAGE SPEED (M/SEC) AVERAGE WIND POWER (WATTS/M**2) ? PERCENT DATA RECOVERY |
| | | |

DNOCES/SREHEM DEEPS

ANEMOMETER HEIGHT = 10 METERS = 33 FEET NUMBER OF OBSERVATIONS = 23061 PERCENTAGE DATA RECOVERY = 59.6

Table IV - 44

Percentage Frequency Summary for Wind Speed

01/01/76 - 05/31/79

DEER LODGE COUNTY - ANACONDA C-HILL (WINTER)

| | | SPEE | | 6.7 | 7.0 | 6.8 | 6.7 | 6.7 | 6.8 | 6.5 | 6.8 | 6.8 | 6.7 | 6.8 | 6.9 | 7.4 | 7.5 | 7.4 | 7.2 | 7.0 | 6.9 | 6.8 | 6.7 | 6.6 | 6.7 | 6.9 | 6.7 | 6.9 | |
|---------|-----------------|-------|--------------|------|------|------|-------------|------|------|------|------|-----------------|------|----------|--------|-------|------|----------|------|----------|---------|---------|---------|-----------|-------------|------|----------------|-----------|--------------|
| | ¥ | SPEED | (MPH) | 15.0 | 15.7 | 15.1 | 14.9 | 15.0 | 15.1 | 14.6 | 15.1 | 15.1 | 14.9 | 15.1 | 15.5 | 16.5 | 16.7 | 16.5 | 16.2 | 15.6 | 15,4 | 15.2 | 15.0 | 14.8 | 15.1 | 15.4 | 15.0 | 15.4 | |
| | >40.0 | | >17.9 | 2.4 | | | | | | | | | | | | | • | | • | • | | • | • | | | | • | 3.2 | |
| 25 1 | 40.0 | 15.7- | 7.9 | 2.8 | 1.4 | 2.4 | 1 .t | 1.4 | 3.1 | 1.7 | 2.1 | 2.1 | 0. | 0.7 | 2.1 | 3.8 | 3.5 | 0.7 | 2.4 | 3. T | ٠. د | 2.4 | 1.7 | 0. | 2.0 | 2.4 | 1 . | 2.0 | |
| - | 35.0 | 7 | 5.6 | 3.8 | 3.5 | 4.5 | 4.5 | 4.1 | 5.1 | 4.5 | 4.1 | 3.1 | 3,5 | ω 8 | t. 1 | _ | 2.8 | 9.9 | 7. | 5.8 8 | ۳. | 6.1 | 5.8 | 2,7 | 4.7 | 4.9 | 3.7 | 4.3 | |
| 25 1 | 30.0 | 11.2- | 13.4 | | | | | | | | | | 4.5 | | | | | | • | • | | | | | | | | 7.0 | |
| 1 | 25.0 | 9.0- | . | | | | | | | | | | 10.5 | | | • | | | ٠ | ٠ | ٠ | | | | | | | 11.4 | |
| _ | 20.0 | 8.1- | 8.9 | 8.0 | 7.6 | 4.2 | 6.5 | 2.1 | 6.5 | 5.1 | 9.9 | 5.9 | 4.9 | 6.9 | 7.9 | 4.5 | 6.3 | 6.2 | 5. | 6.8 | 6.5 | 6.1 | 5.8 | 6.1 | 4.7 | 2.0 | 5.4 | 5.7 | |
| H) | 18.0 (EC) | 7 | 8.0 | 6 + | 6.9 | 6.2 | 6.2 | 6.2 | 4.5 | 2.7 | 5.9 | ō. + | 8.7 | 6 | ∞ ⇒ | 5.9 | 6.9 | 8.6 | 8 | 6.1 | 5.8 | 5. | 5.1 | ⊅. | ۍ 8 | 4.7 | 4.1 | 5.9 | |
| ш- | 16.7 | 6.3- | 7.2 | | ٠ | | | | | | | | 7.8 | | | | | | • | • | ٠ | • | • | | ٠ | | • | 7.7 | |
| ND SPE | 14.0 ND SPEE | 5.4- | 6.3 | | | | | | | | | | 4.8 | | | | | | | | | | | | | | | 4.8 | |
| ₹ ; | 12.0 | 4.5- | 5. 4. | 9.4 | 11.8 | 9.0 | 10.0 | 8.6 | 10.3 | 13.0 | 10.7 | 7.0 | 12,5 | 10.1 | | | | | 7.8 | • | | • | | 8 | | | | 9.5 | |
| 0 | 10.0 | 3.6- | 4.5 | | • | • | | • | • | • | | • | 7.7 | • | | • | • | | • | • | • | | • | ٠ | • | | | 4.8 | |
| 7 1 | 8.0 | 2.7- | 3.6 | 6.9 | 11.4 | 9.0 | 9.3 | 10.6 | 8.9 | 11.3 | 9.3 | 9.8 | 5.6 | 5.9 | 2.6 | 8 | 7.6 | 10.0 | 7.1 | 10.5 | 7.8 | ~ .8 | 7.5 | | - - - | 7 8 | 10.9 | 8.7 | |
| - | 6.0 | 1.8- | 2.7 | 10.4 | 4.8 | 6.9 | 6.9 | 5.5 | 11.0 | 10.3 | 7.9 | 7.3 | 10.1 | 10.1 | 7.2 | 8.3 | 5.6 | 6.9 | 8.2 | | 7.8 | 6.8 | 9.6 | 4.9 | 11.2 | 7.1 | 6.5 | 8.0 | |
| ָר - | 4.0 | 0.0 | .8 | 3.8 | 6.2 | 7.3 | 6.2 | 6,5 | 6.2 | 6.2 | 7.9 | 7.3 | 7.7 | ∞ | 5 | ≈ ≠ | 5.6 | 2.4 | . 8 | 7.8 | 7 | 6.6 | & V. | 9.5 | 6.8 | 5.7 | 5.4 | 9.9 | NC. |
| , , | .0. | 0.1- | 6.0 | 5.9 | 3.1 | 2.8 | 4.5 | 4.8 | 3.1 | 4.5 | 7. | 3,1 | 2,1 | 2.1 | 3.8 | 2.1 | 2.1 | 3.8 | 3.4 | 2.7 | 2.7 | 2.7 | ω ∞ | 3.1 | 3.1 | 3.4 | 4.8 | 3.3 | ARCH. |
| | CALM | | CALM | 0.0 | 0.3 | 0.3 | 0.0 | 0.3 | 0.0 | 0.0 | 0.3 | 0.0 | 0.3 | 0.0 | 0.3 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.3 | 0.3 | 0.0 | 0.0 | 0.0 | 0.3 | 0.0 | 0.1 | GEORESEARCH. |
| | | | | _ | € | ო | 4 | 5 | 9 | _ | ထ | 0/ | 10 | Ξ | 12 | 13 | 17 | 15 | 16 | 17 | 18 | 19 | 20 | 2 | 25 | 23 | 54 | ALL HOURS | |
| | | | | | | | | | | | | æ | | 0 | | > | | <u>~</u> | | | | | | | | | | ALL | SOURCE |

Table IV - 45

DEER LODGE COUNTY - ANACONDA C-HILL (SPRING) Percentage Frequency Summary for Wind Speed

01/01/76 - 05/31/79

| | | | | | | | 3 | SP | EED (MPH | Ŧ | | | | | | | | |
|-----------|--------------|---------|-------------------------|-------------|---------|------------------|------------|------|------------|-------------|------------|-------|-------|----------|---------|-------|-------|-------|
| | CALM | 0.1-2.0 | 2.1 - 4.0 | 4.1- 6.0 | 6.1-8.0 | 8.1 - | 10.1 - 12. | -0: | <u>-</u> 2 | 5.1- | 18.1- 20.0 | 20.1- | 25.1- | 30.1- | 35.1- | 0.04< | | |
| | | , | | | | | Z | | S/W) 0 | | | , |) | • | | } | ¥ | |
| | | | 0.0 | - 8 | 2.7 | 3.6- | 4.5- | | 6.3- | 7.2- | 8.1- | -0.6 | 11.2- | 13.5- | 15.7- | | SPEED | SPEED |
| | CALM | | 8 | 2.1 | • | 4.5 | 5.4 | | 7.2 | 8 .0 | 8.9 | 1.2 | m | 15.6 | 7.9 | >17.9 | (MPH) | Ξ |
| | | 2,3 | 10.7 | 13.0 | 9.6 | 6.9 | 8.8 | 9.6 | 7.3 | 7.7 | 0. | 6.9 | | 2.3 | 8.0 | • | 12.7 | 5.7 |
| | | | 8 | 10.1 | | 10.5 | 9.3 | | 5.4 | • | ٦. | 10.5 | | 2.7 | 1.6 | | 12.6 | 5.6 |
| | | | 5.8 | 10.0 | | 11.2 | 13.1 | | 8.1 | • | œ | 10.4 | | -,9 | 5 | | 12.7 | 5.7 |
| | | | ۍ ص | 9.8 | | 11.0 | 11.0 | | 5.3 | • | ۲. | 6.8 | | 1.9 | _ | • | 12.2 | 5.5 |
| | | | 7. | 7.5 | | 6 | 10.2 | 11.7 | 6.8 | 9.9 | 3.8 | 10.2 | 5.3 | -, | 1 | 0.8 | 12.5 | 5.6 |
| | | | 9. | 8.7 | | 10.6 | 1. | | 9.5 | | ٣. | 8.3 | | 2.3 | 7 0 | | 12.2 | 5.4 |
| | | | 6.6 | 6.6 | | 15.2 | 9.1 | | 9.7 | • | - | 6.1 | | 6. | 0.8 | • | 11.4 | 5.1 |
| | | | 14.9 | 9.5 | | 11.9 | 15.6 | | 5.0 | | ۲. | 5.0 | | 2.3 | 4.0 | | 11.4 | 5.1 |
| T. | | | 6.9 | 12.0 | | 10.8 | 6.7 | | 6.5 | • | 0 | 10.4 | | 1.9 | ŋ. 0 | | 12.5 | 5.6 |
| | | | 4.6 | 9.6 | | 8 .5 | 12.3 | | - | • | 6. | 13.1 | | 1.5 | 1.2 | | 13.7 | 6.1 |
| 0 | | | <u>س</u> | o. | | 9.2 | 8 8 | | 7.3 | • | ď | 14.5 | | 2,3 | 0.8 | | 14.4 | 4.9 |
| | | | m 0 | 5.7 | | 9.1 | 12.1 | | 9.8 | | 0. | 15.8 | | 0.0 | 1,5 | | 15.3 | 8.9 |
| _ · | | | <u>-</u> . | 5.7 | | ο 80 | 8 | | 10.6 | | œ. | 15.5 | | 1.9 | 7.0 | | 15.9 | 7.1 |
| | | | 2.7 | ر م | | 9 | 8. | | 9.8 | | 0 | 18.2 | | 2,3 | 7.0 | | 16.4 | 7.3 |
| <u>~</u> | | | 5.6 | 6 | | 9.1 | 7.9 | | 7.2 | | ؈ | 13.2 | | 3.00 | 1.9 | | 16.5 | 7.4 |
| | | | 21.0 | † † | | 80 2 | <u>«</u> | | 6.3 | | ⇒։ | 20.7 | | 5.9 | 7.0 | | 16.7 | 7.5 |
| - 1 | | | 9 | æ. ⇒ | | 8 | 9.0 | | 6.7 | | ن | 22.3 | | ± ℃.5 | 1.9 | | 17.2 | 7.7 |
| - | | | 5.6 | 4. | | 6.3 | 10.4 | | 4.5 | • | ø. | 16.0 | | 3.0 | 1.5 | | 16.8 | 7.5 |
| - (| | | 9 | 3.0 | | 10.4 | 5.6 | | 10.8 | | ب | 19.0 | | 2.2 | 1.9 | | 16.3 | 7.3 |
| 2 | | | 4.1 | 0.9 | | 6.7 | 9.6 | | 10.4 | | ب | 15.7 | | 3.7 | 0.7 | | 15.8 | 7.1 |
| N · | | | 3. | 6.9 | | 9.7 | 11.2 | | 7.1 | | ď | 14.1 | | 3.0 | 5.6 | | 14.8 | 9.9 |
| ~ | | | 8.6 | 12.6 | | 9.3 | 9.3 | | 5.9 | | 9 | 14.5 | | 2.5 | - | | 13.7 | 6.1 |
| 8 | | | 9.3 | 10.7 | | 10.4 | 11.5 | | 5.5 | | = | 11.1 | | 1.9 | 1.5 | | 13.0 | 5.8 |
| N | | | 10.0 | 10.0 | | 13.3 | 7.0 | | | • | ထ | 13.7 | | 3,3 | | _ | 13.2 | 5.9 |
| ALL HOURS | 9.0 s | 1.9 | 6.0 | 8.5 | 9.5 | 7.6 | 7.6 | 8.9 | 7.5 | 7.6 | 7.0 | 13.0 | 6.2 | 2.5 | -: | 0.9 | 14.2 | 6.3 |
| SOURCE: | GEORESEARCH, | EARCH, | NC. | | | | | | | | | | | | | | | |

Table IV - 46

Percentage Frequency Summary for Wind Speed

DEER LODGE COUNTY - ANACONDA C-HILL (SUMMER)

01/01/76 - 05/31/79

| | | SPEE (M/SE | | • | . 80 | • | • | • | | | • | • | • | • | • | • | • | | • | • | • | | • | | • | • | 5.0 |
|---|---------------------------------------|-----------------|------|-----|----------|----------|------|------|------|------|--------|--------|------|------|------------|---------|------|------|------|------|------|------|------|----------|------|------|-----------|
| | \$ | SPEED (MPH)(| | | , w | • | | | | • | | | • | • | | | | • | • | | | | | | | • | 11.2 |
| | >40.0 | >17.9 | | | 0.0 | | | | | | | | | | | | | | | - | | _ | | | _ | | 0.2 |
| | 35.1- 40.0 | 15.7- 17.9 | | | 0.0 | • | | | • | • | | • | • | • | • | • | • | • | • | • | | | | • | | • | 0.5 |
| | 30.1- 35.0 | 13.5- 15.6 | 0.0 | 9 | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | 9.0 | 9.0 | 9.0 | 1.1 | Ξ: | 1.2 | 2.9 | 2.9 | 1.7 | 2,3 | 4.0 | 1 7 | 9.0 | 1.7 | 2,3 | 9.0 | 1.2 |
| | 25.1- 30.0 | 11,2- 13.4 | _ | • | 1.7 | _ | 0 | _ | _ | _ | _ | _ | _ | က | - 7 | φ | 0 | 'n | 9 | ~ | 9 | 9 | C) | ¬ | 2 | 0 | 3.4 |
| | 20.1- 25.0 | 9.0- | 4.0 | 7 | | 4.0 | 3.4 | 1.7 | 2.9 | 4,0 | 4.0 | 5.3 | 5.5 | 8.0 | 14.1 | 13.4 | 14.9 | 14.9 | 15.0 | 17.1 | 11.9 | 12.6 | 10.9 | 8 | 6.8 | 8.0 | 8.2 |
| | 18.1- 20.0 | 8.1- 8.9 | 6 | , c | 1.7 | 2.3 | 1.1 | 2.8 | 9.0 | -: | 9.0 | 5.9 | 4.0 | 8.0 | 6.8 | 8.7 | 5.7 | 8.6 | 6.9 | ۲. | | 6.9 | 5.7 | 4.5 | 5.7 | 2.3 | 4.2 |
| : | MPH) - 16.1- 0 18.0 /SEC) | 7,2- 8.0 | | | 5.7 | | | | | | | | | | | | | | | | | | | | | • | 5.6 |
| , | ED (14.1 16. | 9 | | | 7 | | | | | | | | | | | | | | • | | | | • | | | | 6.2 |
| 1 | m | | 7.4 | 00 | -1 -1 | 9.1 | 8.0 | 10.2 | 6.3 | 4.5 | 9.7 | 4.6 | 10.9 | 12.6 | 8.5 | 5.2 | 7.6 | 12.1 | 8.7 | 11.4 | 9.0 | 10.3 | 8.0 | 8.0 | 6.3 | 10.3 | 8. 8. |
| - | WIND S 10.1-12.0 - 14.0 WIND SI | 4.5- 5.4 | 14.2 | 0 | 0.01 | 6.3 | 7.6 | - 6 | 9.2 | 10.2 | 10.8 | 10.5 | 11.5 | 12.6 | 11.9 | 10.5 | 10.9 | 10.9 | 11.6 | 12.6 | 13.6 | 9 | 9 | 9.1 | 12.5 | 9.5 | 10.7 |
| | 8.1 - 10.0 | 3.6- | 14.2 | 7 | 13.7 | 13.1 | 8.0 | 10.2 | 11.5 | 14.8 | 7.6 | 12.9 | 11.5 | 1.4 | 13.6 | 16.9 | 17.1 | 10.3 | 14.5 | 10.3 | 12,4 | 16.1 | 13.8 | 11.9 | 13.6 | 9.5 | 12.7 |
| | 6.1-8.0 | 2.7- | 14. | 7 | 17.6 | 13. | 17. | φ. | 13 | 18. | 16. | 15 | 18. | 17. | 13. | | 13. | 12. | 'n | 9. | 10. | 10. | 6 | 13 | 15. | 14. | 13.7 |
| | 4.1- | 1.8- | 13.6 | 9.0 | 17.0 | 20.6 | 15.4 | 21.6 | 18.4 | 19.3 | 21.6 | 22.2 | 16.7 | 8.6 | 9.0 | ν. 9 | 4.0 | 2.9 | 6.9 | 5.7 | 4.5 | 8.6 | 14.4 | 12.5 | 7.6 | 17.2 | 13.1 |
| | 2.1- 4.0 | 0.0- | 11.4 | | 14.2 | 14.9 | 16.6 | 17.0 | 17.8 | 15.3 | 14.2 | 8 8 | 6.3 | 3.4 | 3.4 | 1.7 | 1.7 | -: | 1.7 | 2.3 | 7.5 | 2.3 | 5.2 | 8.0 | 6.7 | 10.3 | 8.5 |
| | 0.1- | 0.1- | 5.7 | | 7 | 4.0 | 6.9 | 6.8 | 9.5 | 6.3 | 2,3 | 8. | 0.0 | - | 0.0 | 0.0 | 0.0 | 0.0 | 9.0 | -: | 0.0 | 9.0 | 1.7 | 1.7 | 2,8 | 2.9 | 5.6 |
| | CALM | CALM | 0.0 | | 0.0 | 1.7 | 1.1 | 9.0 | 1.7 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.2 |
| | | | • | ۰ ۸ | i m | ⊒ | 5 | 9 | 7 | | 6 H | | 0 | | U 13 | 1,4 | R 15 | 16 | 17 | 48 | 19 | 20 | 21 | 22 | 23 | 24 | ALL HOURS |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Table IV - 47

Percentage Frequency Summary for Wind Speed

DEER LODGE COUNTY - ANACONDA C-HILL (AUTUMN)

01/01/76 - 05/31/79

| | | <u>و</u> و | | | | | | | | | | | | | | | | | | | | | | | | | |
|-------|--------------|-------------------------|------|----------------|------|----------|--------|---------|------------|----------|------|---------|------|--------|------|-------------|-----------------|------|------|----------|------|------|------|------|---------|------|-----------|
| | | SPEED (M/SEC | η | 7 | 1 | 4.3 | 4.6 | 4.7 | 7.7 | 4.5 | 7 | | , 10 | 7. | 5.8 | 6.1 | 6.0 | 6.1 | 6.0 | 5.9 | 5.5 | 5.4 | 5.1 | ₩. | 7.6 | 4.6 | 5.1 |
| | ¥ | SPEED (MPH) | 0 | 0 | 6 | 2.6 | 10.3 | 10.5 | 8 | 10.1 | 10.3 | 11.3 | 12.2 | 2.8 | 3.1 | 13.7 | 13.5 | 13.6 | 13.3 | 13.1 | 12.2 | 12.0 | 1.3 | 8.01 | 10.3 | 10.2 | 11.4 |
| | >40.0 | >17.9 | | | | | | | • | | | | | | | | | | | | | | | | | 0.0 | 0.5 |
| 35.1- | | 15.7- | c | . ⊐ | 7.0 | 7.0 | 0.0 | 0.0 | 0.0 | 7.0 | 0.0 | 7.0 | 0.0 | 0 | 0 | 0 | 0.0 | 4.0 | 0.0 | 0.0 | 0.0 | 6.0 | 6.0 | | 1.0 | 7.0 | 9.0 |
| 30.1- | | 13.5- 15.6 | 1.7 | 1.7 | 0.0 | 0.0 | 1,3 | 1.3 | 4.0 | 0.0 | 6.0 | 7.0 | | 7.0 | 1.3 | ⊅.0 | .8 | 1.7 | 1.7 | 5.6 | 4.0 | 2.1 | 5.6 | 1.7 | 6.0 | 1.7 | 1.2 |
| 25.1- | | 11.2- 13.4 | | 2.2 | | | • | | | | | | | | | | | | | | | | | | _ | | 2.8 |
| 20.1- | 5.0 | 9.0- | 7.0 | 6.1 | 5.2 | 6.1 | 6.1 | 5.3 | 7.6 | 7.4 | 10.0 | 7.5 | 7.5 | 13.2 | 15.4 | 13.8 | 14.9 | 16.4 | 10.8 | 11.3 | 12.9 | 9.0 | 8.6 | 7.6 | 4.3 | 8.9 | 9.1 |
| 18.1- | 20.0 | 8.1- 8.9 | | 2.2 | | | | | | | | | | | | | | | | | | | | | | | 4.6 |
| **** | 18.0 EC) | 7.2- 8.0 | | 4.8 | • | | | • | • | | | • | • | | | | | | | | | | | | | | 6.3 |
| • | ္ဗ | 6.3- | 5.7 | 3.9 | 7.4 | 5.2 | 6.5 | 5.7 | 6.7 | 7.0 | 6.5 | 4.8 | 11.0 | 9.6 | 10.2 | 8.9 | 5.7 | 8.2 | 6.5 | 6.1 | 9.0 | 7.6 | 7.6 | 7.7 | 6.8 | 7.3 | 7.4 |
| SPE | 4.0 SPEE | 5.4 - 6.3 | 7.8 | 11.7 | 6,5 | 5.5 | & ? | 9.6 | 7.6 | 10.0 | 4.3 | 9.3 | 10.1 | 13.2 | 9.4 | 12.1 | 9.5 | 5.6 | 7.3 | 7.4 | 7.7 | 7.7 | 6.6 | 0 | 0.6 | 9.0 | 8.6 |
| 10.1- | 12.0 WIND | 4.5- 5.4 | 8.7 | 9.1 | 9.6 | 10.0 | 8.7 | 12.3 | 8.0 | დ | 10.9 | 11.9 | 12.3 | 8 8 | 12.4 | 9.4 | 9.6 | 7.8 | 9.6 | 13.4 | 11.2 | 11.2 | 7.3 | 10.3 | 4.6 | 9.8 | 6.6 |
| 8-1- | | 3.6- | 11.3 | 10.0 | 13.5 | 9.6 | 11.3 | 11.0 | 11.6 | 12.7 | 13.9 | 11.0 | 1.0 | 11.0 | 11.5 | 10.7 | 10.1 | 10.3 | 9.5 | ۲. | 7.7 | 0.6 | 0.9 | | 10.7 | 11.5 | 10.5 |
| 6.1- | 8 | 3.6 | • | 13.0 | • | • | • | ٠ | • | • | | • | • | • | ٠ | • | | • | ٠ | | | | | | | | 12.0 |
| 4.1- | 0.9 | 1.8- | 15.2 | 14.3 | 18.3 | 15.7 | 10.9 | ω ∞ | = | 12.2 | 10.4 | 11.0 | 10.1 | 9.5 | 7.1 | 10.3 | 10.1 | 6.1 | 9. | 10.0 | 13.3 | 14.2 | 15.5 | 7. | 16.2 | 13.2 | 11.9 |
| 2,1- | 0.7 | 0.0- 1.8 | 14.8 | 12.2 | 10.0 | 13.0 | 13.9 | 14.5 | ο. Φ. | <u></u> | 3.9 | 7.9 | 5.7 | 6.1 | 7.5 | 6.3 | 3.9 | 5.6 | 5.6 | 7.4 | 0.6 | 5 | 9.1 | 14.5 | 13.7 | 15.8 | 10.2 |
| 0.1- | 2.0 | 0.1- | 7.0 | 6.1 | 4.3 | 5.7 | 4.8 | 9 | ο. Θ | 6. | 7.4 | ή. † | 8 | 0.0 | 7.0 | ↑. 0 | ۳. | .3 | 5.6 | 1.7 | 6.0 | 2. | 4.3 | 4.3 | ა. დ | 5.6 | 3.7 |
| ; | CALM | CALM | η.0 | 1.7 | 4.0 | 0.9 | 1.7 | ₹. 0 | <u>د</u> . | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 70 | 7.0 | 0 | 0.0 | 1.0 | 0 | 0 | 0.0 | 0.5 |
| | | | - | ~ | m, | ⇒ | ζ, | 91 | _ | ∞ | δ, | 10 | _ | 12 | - | 7 | ا ت: | 9 | · · | 2 | 19 | 20 | 5 | 22 | 23 | 54 | ALL HOURS |
| | | | | | | | | | | ; | Ξ | | 0 | | > | | œ | | | | | | | | | | ALL I |

Table IV - 48

DEER LODGE COUNTY - ANACONDA C-HILL Annual Wind Rose Distribution

01/01/76 - 05/31/79

| DIRECTION> | | z | NNE | N E | ENE | ш | ESE | SE | SSE | S | MSS | MS | MSM | 3 | MNM | Z | N N N | TOTAL | <direction< th=""><th>~</th></direction<> | ~ |
|--------------|---|---|--------------------------------------|--------|--|---|---|--|---|--|-----|---|--|--|-----|--|-------------|---|--|------------------|
| SPEED (MPH) | PH) | | | | | | | | | | | | | | | | | | SPEED (M/SEC) | (2) |
| AV SPD (MPP) | \$\frac{1}{2}\frac{1}\frac{1}{2}\f | 000000000000000000000000000000000000000 | 000000000000000000000000000000000000 | | - www.ww.w.m.n 00000000000000000000000000000000000 | - 4 - 4 - 4 - 4 - 4 - 4 - 4 - 4 - 4 - 4 | - mm v z z z z z mm v v v v v v v v v v v | 00000000000000000000000000000000000000 | - 0.00000000000000000000000000000000000 | 00000000000000000000000000000000000000 | | - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 | 00000000000000000000000000000000000000 | 20000000000000000000000000000000000000 | | 00000000000000000000000000000000000000 | 0 | - 0 m m m m m m m m m m m m m m m m m m | 0.1- 0.5- 0.5- 0.9- 1.4- 1.4- 1.4- 1.4- 1.4- 1.4- 1.3- 1.4- 1.3- 1.4- 1.3- 1.4- 1.3- 1.4- 1.3- 1.4- 1.3- 1.4- 1.3- 1.4- 1.3- 1.4- 1.3- 1.4- 1.3- 1.4- 1.3- 1.4- 1.3- 1.4- 1.4- 1.6- 1.4- 1.6- | PH DNOCES/SRETEN |
| SOURCE | GFORFSFARCH | VRCH. | , NC | | | | | | | | | | | | | | | | | |




Table IV - 49

Coefficients of Weibull Distribution DEER LODGE COUNTY - ANACONDA C-HILL

01/01/76 - 05/31/79

| | SCALE | SHAPE |
|-----------|-----------------------|------------|
| MONTH | FACTOR (C) (M/SEC) | FACTOR (K) |
| JANUARY | 6.2265 | 1,5942 |
| FEBRUARY | 8.7423 | 1.4705 |
| MARCH | 7.8791 | 1,7362 |
| APRIL | • | 1.5403 |
| MAY | • | 1.8666 |
| JUNE | • | 1,7193 |
| JULY | • | 1.6962 |
| AUGUST | • | 1.8563 |
| SEPTEMBER | • | 1.6344 |
| OCTOBER | • | 1.5167 |
| NOVEMBER | 5.7649 | 1.5737 |
| DECEMBER | • | 1.6476 |
| YEAR | 6.5641 | 1.5997 |

ANACONDA HIGHWAY JUNCTION

DEER LODGE COUNTY

The Highway Junction site was located approximately 3 miles north of Anaconda at 46 08 09 N and 112 53 17 W (Site No. 29 on Map II-1). Elevation at the site was 5,100 feet. The site was established by the Montana Air Quality Bureau to measure concentrations of sulfur dioxide in the area.

Wind data were collected at the site from June 11, 1975, to December 28, 1979. Data through August 27, 1979, were analyzed for this Atlas. The data set contains hourly averages of wind speed and direction manually reduced from stripchart records. When monitoring at this site began, data were gathered by a Meteorology Research, Inc., mechanical recording unit. Beginning in 1978, data were collected by a Climatronics electronic anemometer and wind vane on a 10-meter tower.

Winds were monitored long enough at this site to adequately represent the wind resource. Wind data from this location are representative of a limited area near the site since it is located near the mouth of a large canyon Data recovery ranged from 47.7 percent in December to 98.3 percent in March. Overall data recovery was 79.5 percent.

Average annual wind speed at the site was 8.0 miles per hour. Average monthly wind speeds ranged from 6.8 miles per hour in July to 9.3 miles per hour in November.

Average monthly wind power ranged from 26.9 watts/m² in July to 120.5 watts/m² in November. Average annual wind power was 62.8 watts/m².




Table IV - 50

Monthly Wind Speed Distribution DEER LODGE COUNTY - ANACONDA HIGHWAY JUNCTION

06/11/75 - 08/27/79

| | O (| | 7. | -6. | | 4.5 | ! ! | -9. | קיי | ر د م | 4-6 | 8- 7 | .3- 7 | .7- 8 | | | -0, -1, -1, | | 7-17 | 17 | | | | | |
|----------|-------|------|----------------|------|----------|--------|---------|----------------|---------|-----------|----------|----------|----------|------------|-------------|----------|-------------------|----------|---------|-----|-----------------------------------|---------------|-----------------------|----------|------|
| YEAR | 00. | 9.7 | 9.1 | 0,0 | | 7.9 | 9.0 | بر د - ب | , t | 0.0 | 2.7 | 2.5 | 2.1 | æ. | | - ı | , c | - | 0.0 | 0.0 | 8.0 | 3.6 | | 62.8 | 79.5 |
| DEC | 0.0 | | | | | • | | | • | | | | | | | | | | | | 4.6 | 4.2 | | 117.2 | 47.7 |
| № | 1.1 | | • | • | | • | | | • | | | | | | | • | • | | | • | 9.5 | 4.2 | | 120.5 | 69.8 |
| OCT | 0.0 | 10.4 | 9.0 | ~ o | 0 00 | 7.3 | | 0 | | | 0 | 2.5 | 1.7 | <u></u> , | - 0 | ٠ د د | - - | | 0.0 | 0.0 | 7.5 | 3.3 | | 46.6 | 70.8 |
| SEP | 0.0 | | 9.1 | 80 C | 13:1 | 9.0 | 7.7 | 9 | | ر د د | 1.8 | 7.5 | .5 | 0.0 | \ 0 0 | 7. | - | | 0.0 | 0.0 | 7.2 | 3.2 | | 34.7 | 74.1 |
| AUG | 000 | | • | | | • | | • | | | | | ٠ | | | | | | | | 7.1 | 3.2 | | 32.5 | 78.2 |
| JUL | 0.0 | 7.7 | 9,5 | . a | 1.6 | 10.4 | ຸສ | υ. | | . 6 | | 0.9 | 0.5 | 0.0 | 200 | 3.0 | ?- | 0 | 0.0 | 0.0 | 6.8 | 3.0 | | 26.9 | 93.9 |
| NUC | 0.00 | | • | • | | • | | • | ٠ | | | | | • | | | | | | | 8. | 3.6 | | 52.1 | 76.0 |
| MA∀ | 0.0 | | | | | | | | | | | | | | | | | | | | 8.4 | 3.8 | | 57.0 | 86.8 |
| APR | 0.7 | | | | | | | | | | | | | | | | | | | | 7.9 | 3.5 | | 51.6 | 95.1 |
| MAR | 0.0 | | | • | | | | | | | | | | | | | | | | | 8.6 | 3.8 | | 72.4 | 98.3 |
| FEB | 0.1 | | • | • | | • | | | | | | • | | • | | • | | | | | 9.3 | 4.2 | | 103.8 | 91.7 |
| JAN | 000 | עזע | 12:1 | ى – | , r. | | 3.4 | w. 0.0 | 000 | 1.8 | 1.5 | 6 | 7.5 | ۍ <u>د</u> | | o ~ | † C | 0 | 0.0 | 0.0 | 7.7 | 3.4 | | 102.8 | 4.69 |
| | S-1-5 | 2.1 | - - | | 6.1-7. | 7.1-8. | 9.1-10. | - . | 12 1-12 | 13, 1-14. | 14.1-15. | 15.1-16. | 16.1-17. | 17.1-18 | <u>.</u> | 7.1.25 | | 0.1 - 35 | 5.1-40. | | AVERAGE SPEED (MPH) AVERAGE | SPEED (M/SEC) | AVERAGE WIND POWER | ATTS/M** | 'ERY |

ANEMOMETER HEIGHT = 10 METERS = 33 FEET NUMBER OF OBSERVATIONS = 29354
PERCENTAGE DATA RECOVERY = 79.5

ANACONDA MILL CREEK

DEER LODGE COUNTY

The Mill Creek site was located approximately 4 miles east-southeast of Anaconda at 46 06 19 N and 112 52 45 W (Site No. 31 on Map II-1). Elevation at the site was 5,199 feet. The site was established by the Anaconda Copper Company to measure concentrations of particulates and sulfur dioxide in the area.

Wind data from December 4, 1976, through May 31, 1979, were collected at the site. Data through February 28, 1979, were analyzed for this Atlas. The data set consists of hourly averages of wind speed and wind direction manually reduced from stripchart records. Data recovery was fair to excellent, ranging from 41.1 percent in November to 97.5 percent in October. Overall data recovery was 70.0 percent. Winds were monitored long enough at this site to adequately represent the wind resource. The anemometer height was 10 meters. Because the site is located in complex terrain, the data are representative only of a limited area. DNRC-sponsored monitoring underway in 1986 and 1987 suggests wind speeds are greater closer to the mouth of the Mill Creek Valley.

Average annual wind speed at this site was 9.5 miles per hour. Average monthly wind speeds ranged from 7.4 miles per hour in July to 13.0 miles per hour in December.

Average monthly wind power ranged from 33.1 watts/m² in July to 211.5 watts/m² in December. Average annual wind power was 95.2 watts/m².




Table IV - 51

Monthly Wind Speed Distribution

DEER LODGE COUNTY - ANACONDA MILL CREEK

12/04/76 - 02/28/79

| AUG SEP OCT NOV DEC | 0.7 0.1 0.1 3.7 0.4 1.8 1.8 1.9 6.9 2.6 | 3.8 3.8 3.5 8.1 3.5 6.0 4.1 3.7 7.4 3.6 | 5.3 5.3 4.4 6.9 3.2 | 5.3 7.5 7.0 4.9 3.1 | 10.0 7.0 7.7 4.4 3.6 | 12.7 10.2 8.3 2.9 4.6 | 8.9 9.1 7.2 3.7 3.6 | 5.3 5.8 5.0 1.7 5.5 | 4.2 5.6 4.3 3.5 3.7 | 2.3 3.6 5.9 3.4 4.9 | 2.5 3.9 3.8 2.7 4.4 | 1.8 2.7 4.2 3.0 5.1 | 1.5 2.8 4.7 3.5 5.1 | 3.5 2.1 2.7 3.7 4.8 | 1.9 1.8 1.9 2.9 3.9 | 1.0 1.9 2.1 4.2 3.6 | 0.7 1.6 4.3 8.6 14.7 | 0.0 0.1 0.5 1.5 4.1 | 0.0 0.0 0.0 0.2 0.8 | 0.0 | | 6.1 6.6 9.6 9.4 13.0 9. | 3.6 3.8 4.3 4.2 5.8 4. | 48.2 57.4 85.0 123.4 211.5 95.2 | 45.9 97.3 97.5 41.1 93.0 70.0 |
|---------------------|--|--|---------------------|---------------------------|----------------------|-----------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|----------------------|---------------------|---------------------|----------|----------------------------|-------------------------|------------------------------|------------------------------------|-------------------------------|
| JUN JUL | 0.4 0.5 3.0 1.8 | ± ± | † † | vi= o,t | 10. | 4 10. | 0.0 | ر م م | 8 | 8 2. | 6 3. | 0 | . . | - 0 | ٠. د | | 0 | 0 0 | 0 0. | 00 | | † | 3.4 3.3 | 40.7 33.1 | 48.8 41.5 |
| APR MAY | 0.5 0.2 3.5 2.9 | - ~ - ~ | (J.) | ~ · · | - w | 8 | | 00 | 2 | 5 4 | 9 | ص ص | ~ ~ | | ~ ~ | , _ | .0 | -0 | 0 0 | 00 | | 1.0 | 3.7 3.8 | 57.1 55.7 | 97.9 89.9 |
| FEB MAR | 2.6 3.7 | N 80 M M | | λι Agr | `~ | .9 9. | ۲. | , t | 2 4. | 3 4. | ر. م | 9 . | | , , | , t | ۸ | 9 6 | 2 1. | 0.00 | 00 | 0 1 10 1 | | 4.1 4.5 | 99.0 114.0 | 44.1 48.8 |
| JAN | ٥ <u>+</u> , | 2.1-3.0 6. | .1-4.0 | 7.1-7.0 5.1-6.0 5.0 | 6.1-7.0 | 7.1-8.0. 5. | 3.1-9.0 | 1-11.0 2. | 11.1-12.0 3. | 12.1-13.0 2. | 13.1-14.0 2. | 14.1-15.0 3. | 12.1-16.0 2. | 17 1-18 0 4. | 18 1-19 0 | 1-20.0 | .1-25.0 8. | .1-30.0 1. | 1-35.0 0. | .0 0.01< | AVERAGE SPFFD (MPH) 9 5 | ; | SPEED (M/SEC) 4.2 AVERAGE | (WATTS/M**2) 120.8 PERCENT DATA | 85.7 |

ANEMOMETER HEIGHT = 10 METERS = 33 FEET NUMBER OF OBSERVATIONS = 13730 PERCENTAGE DATA RECOVERY = 70.0

ANACONDA WEATHER HILL

DEER LODGE COUNTY

The Weather Hill air monitoring site was located approximately 2 miles southeast of Anaconda at 46 05 51 N and 112 54 51 W (Site No. 33 on Map II-1). Elevation at the site was 6,378 feet. The site is owned by Anaconda Copper Company. The air monitoring station was established by the company to monitor concentrations of particulates and sulfur dioxide.

The land around the site is very rugged. To the southwest, the Anaconda Range rises to more than 11,000 feet. To the north is the Flint Creek Range, with summits over 10,000 feet. The area is dissected by many deep canyons.

In general, land in the valleys is privately owned, while land in the mountains is controlled by the U.S. Forest Service. Several major electrical transmission lines cross the Deer Lodge Valley. The nearest commercial airport is the Anaconda airport, located northeast of the site.

Wind data for December 4, 1976, through May 31, 1979, were available for analysis. The data set consists of hourly averages of wind speed and wind direction manually reduced from stripchart records. Anemometer height was 10 meters.

Data recovery varied from 32.6 percent in March to 97.3 percent in September. Overall data recovery was 63.6 percent. Winds were monitored long enough to adequately represent the wind resource at this location. Because of the region's complex terrain, however, the data are representative only of the area near the site, which is on a narrow ridge crest. The rugged nature of the site limits the possibilities for development.

Average annual wind speed at this site was 17.0 miles per hour. Average monthly wind speed ranged from 11.7 miles per hour in July to 23.9 miles per hour in December.

Average annual wind power was 517.4 watts/m². Average monthly wind power ranged from 197.1 watts/m² in July to 1,147.7 watts/m² in December

Average seasonal wind speeds were 13.1 miles per hour in summer, 16.0 miles per hour in autumn, 16.7 miles per hour in spring, and 19.8 miles per hour in winter. Average wind speeds were highest around noon during the winter. During the other seasons the highest average wind speeds occurred from mid to late afternoon. The lowest average wind speeds occurred in the early evening in autumn and winter, around midnight in spring, and after dawn during the summer.

The diurnal range of average hourly wind speeds was greatest in the summer and least in the winter. Most of the variation in average wind speeds among the seasons was due to differences in the average nighttime wind

The most common wind direction was west-southwest. Winds blew from this direction 40 percent of the time. Winds from the west and west-northwest blew 21.6 percent of the time. The least common wind directions were north-northwest through north-northeast.

Average wind speeds by direction ranged from 5.9 miles per hour from the east to 21.9 miles per hour from the west-southwest. The strongest winds were those from the prevailing wind directions.




Table IV - 52

Monthly Wind Speed Distribution

DEER LODGE COUNTY - ANACONDA WEATHER HILL

12/04/76 - 05/31/79

| | | | | | | | | | , | • | | . – | _ | | _ | | | | | | | |
|------|-----------------|-------------|--------------|--------|--------|------------------|------------|-------------------|----------|------------|----------|----------|----------|----------|-------------|------------|--------|----------------|------------------------|-------------------------|--------|--------------------------|
| | | | | | ω. | m -1 | | | 'n | ø, | ٠, | | 8 | | <u>.</u> | _ ~ | | 17.9 | | | | |
| | CALP 0.1- | - c | | 2.3 | ~ | 3.2 | 1. | 2.6 | 5.5- | ^ • | - 2 | 7.3- | 7.7- | 8.1 | ^ . | 13,01 | | 15.7- | | | | |
| YEAR | 0.1 | , v 3 | e | , w | 3.8 | w w J. | 3.5 | | 3.1 | 90 | v = | | 3.2 | 3.0 | 2 | 2.0 0.0 | 9.9 | 3.7 | 17.0 | 7.6 | 517.4 | 63.6 |
| DEC | 0.0 | | | | • | | • | | | | | | | • | | | | 10.0 9.8 | 23.9 | 10.7 | 1147.7 | 86.0 |
| NOV | 2.9 | 4.1 7.5 | 7.0 | , v. | 9.9 | 7.7 | 3,3 | 2.7 | 7. | c | - 0 | 1.7 | 1.4 | 7.5 | - · | 2.0 | 7.6 | 6.2 9.9 | 15.8 | 7.1 | 564.2 | 35.8 |
| OCT | 0.3 | | • | | • | | | | | | | | | | | | | | 16.0 | 7.2 | 6.404 | 67.5 |
| SEP | 0.1 | | | | | | | | | | | | | | | | | | 16.0 | 7.1 | 383.1 | 97.3 |
| AUG | 200 | 3.1 | 9. | | 0,9 | 4.4 | 10. | ~ O. | 2.7 | 90 | 00 | 7 | 3.4 | 2.1 | ر د ا | 0 - | 3.8 | 0.7 | 13.4 | 0.9 | 260.7 | 45.6 |
| JUL | 0.0 | 6.3 4.6. | 7. 8. | 7:0 | 6.0 | , , , , | 1 . | | 8 | ທີ່ເ | 200 | 1.6 | 3.1 | ۲۰, | ٠, c | у п. | 2.0 | 7.0 0.0 | 11.7 | 5.5 | 197.1 | 46.1 |
| NAC | 0.0 | 3 - | 00 | | 7.0 | 3.6 | † : | ਰ <i>ਹ</i> ਹ ਹ | 1. | ν. ωπ | - | 4.7 | 0.4 | 7 |) o | 0 00 | 4.7 | 1.6 | 14.1 | 6.3 | 301.9 | 48.9 |
| MAY | 0.0 | | | | | | | | - | _ | | | _ | _ | - | | | | 16.8 | 7.5 | 403.6 | 93.4 |
| APR | 0.00 | | | | | | | | | | | | | | | | | | 15.7 | 7.0 | 396.5 | 65.3 |
| MAR | 0.3 | 2.0 | ພຸດ ພຸກ | 3.0 | 9,0 | 5°0 0.0 | 2.7 | 2.4 | 1.0 | 0,0 | , c, | 5.9 | 2.8 | 3. 1. | 4.4 | 20 | 6.3 | 3.4 | 18.5 | 8.3 | 635.4 | 32.6 |
| FEB | 2.0 | | | | | | | | | | | | | | | | | | 17.4 | 7.8 | 610.1 | 44.1 |
| JAN | 0.10 | | • | | • | | • | | • | • | | | • | | | | | 3.3 2.4.2 | 17.0 | 7.6 | 542.2 | 86.1 |
| | CALM 0.1-1.0 | 2.1-3. | - <u>-</u> - | 5.1-6. | 6.1-7. | 8.1-9. | 9.1-10. | -ં તાં | 12.1-13. | 13, 1-14. | 15.1-16. | 16.1-17. | 17.1-18. | .1-19. | 1.25. | 1-30. | .1-35. | .1-40. >40. | AVERAGE SPEED (MPH) | AVERAGE PEED (M/SEC) | | PEKCEN! DATA RECOVERY |
| | | | | | | _ | | - - | | | | _ | _ | | | | | | 0, | Š | 25 | T |

ANEMOMETER HEIGHT = 10 METERS = 33 FEET NUMBER OF OBSERVATIONS = 13882
PERCENTAGE DATA RECOVERY = 63.6

Table IV - 53

Percentage Frequency Summary for Wind Speed

DEER LODGE COUNTY - ANACONDA WEATHER HILL (WINTER)

12/04/76 - 05/31/79

| | SPEED M/SEC) | 8.7 | .0. | 0.6 | φ. 0.0 | 9.0 | 0.6 | 9.3 | 9.5 | 9.3 | 9.6 | 10.0 | 6.6 | 9.6 | 0,6 | 8. | | 6.7 | 6.7 | 7.8 | 8.2 | 8.5 | 8. | 8 | 8.8 |
|--------------------------------|-----------------|----------------|----------------|------------------|-----------|-------------------------------|------|------|------|------|----------|---------|------|------|------|------|---------|------|------|------|------|------|------|-------|-------|
| > | SPEED (MPH)(| 19.4 | 19.9 | 20.5 | 20.0 | 20.1 | 20.2 | 20.8 | 20.6 | 20.7 | 21.6 | 22.3 | 22.1 | 21.4 | 20.2 | 6 | 8 | 17.6 | 17.6 | 17.5 | 18.3 | 19.0 | 16. | 19.0 | 19.8 |
| >40.0 | >17.9 | 3.1 | | | | | | | | | | | | | | | | | | | | | | | 5.5 |
| 35.1- 40.0 | 15.7- 17.9 | 5.2 | . 2. | ø. | ١ - ١ | 7 | Ŋ | ιν. | 9 | φ. | ÷ | 12. | 7. | 9. | တ်၊ | 7 | ⇉ | ~ | Ŋ | Ŋ | Ŧ | | | | 6.4 |
| 30.1- 35.0 | 13.5- 15.6 | 800 | | 7.3 | 9, | 6,7 | 7.2 | 10.9 | 7.9 | 5.5 | 14.7 | 9.8 | 15.2 | 4.6 | 12.9 | | 7. | 9.6 | 6.1 | 9.2 | 9.1 | 9.0 | 7.0 | 10.2 | 9.0 |
| 25.1 . 30.0 | 11.2- 13.4 | 14.1 | 10.7 | 15.5 | 13.8 | 13.3 | 12.9 | 13.0 | 14.2 | 14.1 | 13.1 | 12.4 | 12.6 | 15.1 | 12.4 | 13.7 | 12.1 | 10.2 | 2.11 | 9.5 | 10.2 | 10.1 | 12.5 | 9.6 | 12.5 |
| 20.1 - 25.0 | 9.0- | 18.2 | 19.2 | 16.6 | 6 | 16.4 | 17.5 | 15.1 | | 14.7 | 12.6 | 16.0 | 12.0 | 16.1 | 74.9 | 12.7 | 16.7 | 12.7 | 10.7 | 10.2 | 12.2 | 14.6 | 12.0 | 15.2 | 14.3 |
| 18.1- 20.0 | 8.1-8.9 | 4.7 | | | | • | | | | • | • | | • | | | | | | • | | | | | • | 6.0 |
| H) 16.1- 18.0 | 7,2- 8.0 | 7.3 | | | | • | | | • | • | | | • | | | • | | | | | • | | • | • | 5.5 |
| ED (MF) | 6.3- | 5.2 | . 8. | 4.7 | 6.7 | - | 5.7 | 4.7 | 6.8 | 4.7 | 5.6 | t. 1 | 6.3 | 0. | 5.2 | 9.9 | w 5 | 3.0 | 3.0 | 5.1 | 3.0 | 4.5 | 0.9 | œ | 4.9 |
| ND SPEED 12.1- 14 14.0 1 | 5.4- 6.3 | 6.3 | | 5.2 | | | | • | | | ٠ | | 5.8 | • | | ٠ | 4.0 | | 6.1 | | | ٠ | 5.5 | - | 5.5 |
| 10.1- 12.0 | 4.5- 5.4 | 4.2 | | 6.7 | 3.1 | 3.1 | .5 | 6.3 | 6.3 | 3.7 | 3.7 | 2.1 | 3.1 | 6.3 | 4.6 | | w. 5 | 5.1 | 4.1 | | | | 5.5 | | 4.9 |
| 8.1 - 10.0 | 3.6- | 2.1 | . 9. | 3.6 | 5.6 | 3. | 6.2 | 3.1 | 3.7 | 4.7 | 7.9 | 5.6 | 3.7 | 4.2 | 3.1 | 4.1 | 8.6 | 9 + | 5.6 | 9.9 | 5.1 | | 4.0 | | 4.8 |
| 6.1- 8.0 | 2.7- | 3.6 | 0 - | | | | | • | • | ٠ | | • | | | 6.7 | - | | - | - | • | | • | • | ٠ | 5.5 |
| 4.1- 6.0 | 1.8- | 7.3 | , r. | 5.7 | 1.0 | 4.1 | 5.2 | 4.7 | 3.5 | 5.2 | 4.7 | 1.7 | 6.8 | 7.8 | 6.7 | 6.1 | 8.6 | 7.6 | 9.9 | 7,7 | 9.9 | 2.5 | 4.0 | 5.6 | 5.6 |
| 2.1- 4.0 | 0.0- | 5.2 | . L. | 5.2 | 6.2 | 5.6 | 5.2 | 5.6 | 4.7 | 4.8 | 4.2 | 5.7 | 3.7 | 3.6 | 5.7 | 9.0 | 9.9 | 10.7 | 9.1 | 6.1 | 9.7 | 0.9 | 4.5 | 5.1 | 5.9 |
| 0.1- | 0.1-0.9 | 5.2 | 90. | , , , | 4.6 | - - - - | 3.1 | 3.6 | 2.1 | 0.5 | 5.6 | 5.6 | 1.0 | 1.6 | 4.1 | 3.6 | 5.6 | 3,6 | 5.1 | 8.2 | 3.0 | 5.0 | 4.0 | 4.1 | 3.9 |
| CALM | CALM | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.5 | 0.5 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| | | - 0 | Vm | . | 7 | 9 | 7 | 80 | 6 | 10 | Ξ | 12 | 73 | 14 | 15 | 16 | 17 | 18 | 9 | 20 | 21 | 22 | 23 | 24 | HOURS |
| | | | | | | | | | I | | 0 | | > | | œ | | | | | | | | | | ALL F |

Table IV - 54

DEER LODGE COUNTY - ANACONDA WEATHER HILL (SPRING) Percentage Frequency Summary for Wind Speed

12/04/76 - 05/31/79

| | į | 0.0 |) | | | | | | | | | | | | | | | | | | | | | | | | |
|---------|---------------------------|-----------------|---------|-------------|-------------|------------|------|------|---------|-------------|----------------|-------------|------|------------------|----------------|--------------|----------|----------|------------|------|------|------|------|--------|---------|---------|-----------|
| | | SPEED (M/SFC | • | 9 | 0 0 | 9 | 7 | 9 | 9.9 | 9.9 | 7.2 | 7.7 | 8 | 80 | 8.6 | 8 | 8 | 80 | 8.9 | 8.7 | 8 | 8 | 7.0 | 6.5 | 6.2 | 6.3 | 7.5 |
| | * | SPEED | | 200 | . 4 V & | 14.9 | 15.7 | 15.3 | 14.9 | 14.7 | 16.2 | 17.3 | 18.4 | 18.9 | 19.3 | 19.2 | 19.9 | 19.8 | 19.9 | 19.4 | 18.9 | 17.9 | 15.7 | 14.5 | 13.8 | 14.0 | 16.7 |
| | >40.0 | >17.9 | | - c | ٠ د د | - | - | 0.6 | 9.0 | 1.7 | 2 | 1.7 | - | 3.4 | 1.7 | 1.7 | - | 0.6 | 2.5 | 1.7 | 1 7 | 2,2 | - | 9.0 | 0.0 | 0.0 | 1.3 |
| | 35.1- 40.0 | 15.7- | | ٥ د د | | 1.7 | 0.6 | 5.9 | 2.9 | 0.0 | 2.9 | 3.5 | 3 | 2.3 | 4.5 | 2,3 | 4.5 | 5.0 | 2.2 | 4.5 | 4.5 | 2.8 | 3.4 | 2.2 | 2.5 | 2.8 | 2.7 |
| | 30.1- 35.0 | 13.5- | | , v V R | | | | | | | | | | | | | | | | | | | | | | | 5.3 |
| | 25.1 - 30.0 | 11.2- 13.4 | | טיני קיי | 10.5 | 7.5 | 8 | 9.1 | 11.0 | 8.7 | 14.0 | 13.3 | 13.1 | 19.9 | 16.4 | 17.1 | 16.2 | Ξ. | 15.6 | 11.7 | 12.8 | 12.4 | 7.8 | 7.3 | 5.6 | 6.1 | 11.1 |
| | 20.1- 25.0 | 9.0- | | - « | 0.0 | 12.1 | 13.1 | 15.4 | 15.0 | 18.6 | 15.8 | 12.7 | 17.1 | 14.8 | 19.2 | 15.4 | 22.3 | 21.1 | 16.1 | 17.9 | 15.6 | 13.5 | 15.6 | 10.6 | 13.3 | 8.3 | 15.2 |
| | 18.1- 20.0 | 8.1- 8.9 | | | | | | | | • | | | | | | | | | - | | | _ | _ | - | - | | 7.2 |
| _ | 16.1- 18.0 EC. | | | . C | | | | | | | | | | | | | | | | | | | | | | | 7.0 |
| ED (MPH | 14. 0 16. | 6.3- | ii C | 7.0 | - 6 | 9.2 | 9.7 | 7.4 | 6.4 | 8.7 | 4.7 | 5.8 | 5.1 | 6.8 | 5. | 8 | 2.6 | 8 | 80 | 10.1 | 7.8 | 7.3 | 7.8 | 8.0 | & 0. | 10.6 | 7.7 |
| SPI | . 1- 7-1- 7-1- | 7.4.5 | ď | 0 | | | • | | 8.1 | 2.9 | 4.6 | 7.5 | ., | 5.1 | 5.6 | 5.1 | 6.7 | 2.6 | 3.9 | 11.7 | 5.6 | 10.7 | 14.0 | 7.3 | 4.6 | 9.4 | 7.2 |
| 3 | 10.1- 12.0 12.0 W | 4.5- | | - 9 | | | | | | | | | | | | | | | | | | | | | | | 6.8 |
| , | 8.1 - 10.0 | 3.6- 4.5 | | | 7.6 | 8.0 | 3.4 | 4.6 | 4.6 | 5.2 | 7.0 | 8 | 4.0 | 7.4 | ~3 | 6 | 5.0 | ر و | 0.0 | 5.6 | 6.7 | 7.9 | 5.6 | 8 0 | ~ .8 | 6.1 | 9.9 |
| , | 6.1-6 8.0 | 2.7-3.6 | 0 | 7 | 5.3 | 6.9 | 5. | 6.9 | 6.9 | 6.6 | 8.5 | 7.5 | 6.7 | & O | 7.3 | 6.3 | 5.0 | 9. | ۰,0 ورو | 8.8 | 5.0 | 7.3 | 7.8 | 2.0 | 13.9 | 11.7 | 7.3 |
| | 4.1- 6.0 | 1.8-2.7 | 71. | 1:0 | 1. | 8.0 | 8.0 | 4.0 | 8 | 9 | 14.6 | 6.9 | 2.7 | 8 | य ' | 9.4 | 801 | \ . - | χ, | 7.7 | 4.5 | m : | 7.8 | 6,0 | 9 | 4.6 | 6.5 |
| , | 4.0 | 0.0- | ις Ο | 9.6 | 7.6 | 8.0 | 8.6 | 0.0 | 2.6 | 6.3 | 2.3 | † 9 | 3 | ۰ د د د | 2.8 | - | · · | 0.0 | · · | N. N | 9.0 | | 9 | - i | ~ . | 5.6 | 5.0 |
| • | 2.0 | 0.1- | 7 | / | 5.3 | 4.6 | 0.4 | 6.9 | ω, (| 80 | _ | ر د د | | - (| 0.0 | 9.0 | 9.0 | 0.6 | 0.0 | 0.0 | 0.0 | 0 | - 1 | ω i | m (| 8. O | 2.8 |
| | CALM | CALM | 9 | 0.0 | 0.0 | 9.0 | 0.0 | 9.0 | 0,0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.1 |
| | | | - | · 6/ | က | . † | יי | • | ~ (| 20 6 | ς. | ₽; | Ξ; | 2: | ~; | † | <u>.</u> | 9 [| - : | 20 | 9 | 020 | 2 | 22 | 23 | 54 | ALL HOURS |
| | | | | | | | | | | = | T | | 0 | : | > | í | ¥ | | | | | | | | | | ALL |

Table IV - 55

Percentage Frequency Summary for Wind Speed

DEER LODGE COUNTY - ANACONDA WEATHER HILL (SUMMER)

12/04/76 - 05/31/79

| | > | SEC) | 9 | 4.8 | 7 | ∞ . | 0 | | 9 | ا ت | ر | φ, | - , | د م | ۰ | ⇒ • | 01 | VI | ٠. | ٠. | 寸 (| N) | ٠. | χį | ν̈́ | , | 80 |
|----------------|----------------------------|----------------|--|------------------|-------------|-----------------|---------|------|------|------|----------|--------|--------------|------|----------|------------|-------------|-----------------|------|----------|------------|------|------|------------|------|----------|-------|
| | | S. ₹ | | | | | | | | | | | | | | | | | | | | | | | | | ŗ. |
| | Α | SPEED (MPH) | 10.4 | 10.6 | 10.6 | 10.7 | 7.5 | 11.5 | 10.4 | 6. | 10.2 | 10.7 | 7 | 13.0 | 14.7 | 16.6 | 2 | 20.0 | 2.7 | 2,0 | 9.9 | 16.1 | 5.0 | 2.0 | 2,2 | 0.6 | 13.1 |
| | >40.0 | >17.9 | - | - | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0 | 0.0 | 0.0 | ر ا ا | 7.0 | 0.0 | 0, | | 7 | 7.7 | _ | 2 | - | 0.7 |
| | < 0.04 | 15.7- | | | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | _ | -: | ۳. در | 7. 1. | | 1.2 | 0.0 | 7.5 | 2.3 | | 7.4 | | | <u>-</u> | 6.0 |
| | 35.0 | 13.5- | . 0 | - | 3.4 | 2.3 | - | 2.4 | 1.2 | - | 2.3 | ა შ | - | 5.6 | 5.7 | 7 | 10.6 | | 9 | ر د | 3.4 | 7.1 | 5.4 | 2,3 | _ | - | 3.5 |
| - | 30.0 | 11.2- | | 7.6 | | 4.6 | 5.9 | 4.7 | 3.5 | 4.5 | 2,3 | 1.2 | 8,0 | 3.4 | 6.8 | 11.8 | 10.6 | 9.6 | φ. | \ - | 6.5 | 7.1 | 10.6 | 6.9 | 3.4 | 2.3 | 5.7 |
| 1 | 25.0 | 9.0- | | 6 | 8.0 | 9.5 | ر. ص | 3.5 | 5.8 | 4.5 | 6.8 | 8.1 | 4.6 | 10.1 | 9.1 | ۍ و | 12.9 | 16.9 | 9.3 | 25.9 | 16.1 | 12.9 | 7:1 | 5.7 | 6.8 | 8. 0. | 9.5 |
| | 20.0 | 8.1-8.9 | - | 3. | 5.7 | - | 4.7 | 12.9 | 7.0 | 8.9 | 2.3 | 4.7 | 2.3 | 2.2 | Ξ: | 3.5 | 8,5 | 0.9 | 8. | 7. | 12.6 | 7.1 | 7.1 | <u>-</u> : | 6.8 | 6.9 | 5.6 |
| - - | 18.0 SEC) | 7,2- | , r | . 6 | 4.0 | 10.3 | 8.2 | ⊅. | 9.3 | 6.8 | 9.1 | 7.0 | 3.4 | 2,5 | 3.4 | 11.8 | 5.9 | 3.6 | 7.3 | 4.7 | 9.4 | 10.6 | 8.2 | 10.3 | 10.2 | 5.7 | 7.1 |
| ΣΙ | 0 | | | 2.4 | 0.8 | 3.4 | 7.1 | 5.9 | - | 5.7 | 6 | 4.7 | 2.1 | 5.6 | 15.9 | 12.9 | 7.7 | 1 .8 | 1.0 | 5.9 | 2.3 | 7.1 | 7.1 | 6.9 | 2.3 | 6.9 | 6.8 |
| D SPEE |) 14.0 16. IND SPFED (M | 5.4- | | , , | 8.0 | 5.7 | 14.1 | 4.6 | 4.7 | 5.7 | 5.7 | 3.5 | 6.9 | 10.1 | 12.5 | 5.9 | 8.2 | 7.2 | 1.0 | 15.3 | 10.3 | 3.5 | 3.5 | 12.6 | 9.1 | 3.4 | 7.9 |
| - | 12.0 14 WIND S | 4.5- | | . 0 | 3,7 | 11.5 | 3.5 | 7.4 | 3.5 | 6.8 | 4.5 | 9.3 | 10.3 | 14.6 | 2.1 | 12.9 | 12.9 | 3.3 | 14.6 | 10.6 | 9.5 | 12.9 | 7.1 | 14.9 | 2.7 | 4.6 | 8.8 |
| | 10.0 | 3.6- | | ۰ د د د | | 6.9 | 3.5 | 4.7 | 9.3 | t.5 | 8.9 | 9.3 | 9.5 | 12,4 | 11.4 | 17.6 | 10.6 | 10.8 | 2.4 | .5 .5 | 13.8 | 8.2 | 14.1 | 4.6 | 10.2 | 8.0 | 8.2 |
| | 8.0 | 2.7- | , , | - 0 | 10. | 8 | 7 6 | 8 | 11.6 | 1.6 | 13.6 | 12.8 | 20.7 | 20.5 | 18.2 | 5.9 | 7.6 | 9.6 | 3 7 | 8 | 8.0 | 12.9 | 15.3 | 8.0 | 34.8 | 18.4 | 11.6 |
| - | 6.0 | 1.8- | | 20.1 | 10:3 | 10.3 | 7.6 | 14.1 | 11.6 | 11.4 | 14.8 | 23.3 | 21.8 | 11.2 | 5.7 | 7.5 | 2.4 | 6.0 | 4.9 | 3.5 | 4.6 | 4.7 | 7.1 | 12,6 | 9.1 | 12.6 | 10.4 |
| • | 4.0 | 0.0 | - 1 | - - | , 6 i r. | 17.5 | 12.9 | 7 | 12.8 | 21.6 | 14.8 | 11.6 | 9.+ | - | 2.3 | 7 | 2.4 | 0.0 | 1.2 | 2. 7. | 2 | 2.4 | 4.7 | 8.0 | 11.4 | 11.5 | 8.2 |
| • | 2.0 | 0.1- | | ٠ د د | 2.0 | 1.0 | 1.8 | 10.6 | 11.6 | 11.4 | 8 | 1.2 | 0.0 | 0.0 | 0,0 | 0.0 | 0.0 | 0.0 | 0.0 | 1.2 | 0.0 | 7.5 | 2 | 3.4 | 5.7 | 8.0 | 5.2 |
| | CALM | M. | ֡֞֞֞֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓ | 00 | | | 0 | | 0.0 | 0 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| | | | • | - c | ۷ ۳ |) 1 | . п. | , vc | ~ | - α | 0 | ٦, | = | - 2 | <u> </u> | <u> </u> | 5 | 9 | 17 | 18 | 19 | 20 | 5 | 22 | 23 | 54 | HOURS |
| | | | | | | | | | | | Ξ | : | C | • | ₽ | • | ~ | : | | | | | | | | | ALL |

Table IV - 56

Percentage Frequency Summary for Wind Speed

DEER LODGE COUNTY - ANACONDA WEATHER HILL (AUTUMN)

12/04/76 - 05/31/79

| ; | AV FED SEC) | aprominar-a-maaran-anan- | _ |
|-------------------------------|-------------------|--|----------|
| | S.¥ | るののアファファアのののののでしてのらいろうらっ | 7. |
| ; | SPEED (MPH) | 8880054777777888888888888888888888888888 | 16.0 |
| >40.0 | >17.9 | 0000000000-00000 | -: |
| 35.1- 40.0 | 15.7- 17.9 | | 2.5 |
| 30,1- 35.0 | 13.5- 15.6 | | 5.6 |
| 25.1 - 30.0 | 11.2- 13.4 | | 2.11 |
| 20.1 - 25.0 | 9.0- | 2014444 2017661 201 | 3. |
| 18.1- 20.0 | 8.1- 8.9 | | 7.0 |
| H) 16.1- 18.0 | 7.2- 8.0 | 800800000000000000000000000000000000000 | - 0 |
| (MP | 6.3- | 000-000-1000-00-00-00-00-00-00-00-00-00- | • |
| D SPE 2.1- 14.0 SPFF | 5.4- | + + + + + + + + + + + + + + + + + + + | - |
| WIN 10.1- 13 12.0 | 4.5- 5.4 | + | |
| 8.1- | 3.6- | 09000000000000000000000000000000000000 | : |
| 6.1-8.0 | 2.7- | 8.000 8.00 8.00 8.00 8.00 8.00 8.00 8.0 | |
| 4.1- 6.0 | 1.8-2.7 | 4100001040000444800400000100 P | : |
| 2.1 - 4.0 | 0.0- | 004800044000460000000000000000000000000 | <u>}</u> |
| 0.1- | 0.1- | 00000000000000000000000000000000000000 | ; |
| CALM | CALM | 0-000-000000000000000000000000000000000 | |
| | | 00 8222233377577777777777777777777777777777 | |
| | | ALL HOURS | ! |

GEORESEARCH, INC.

SOURCE:

Table IV - 57

Annual Wind Rose Distribution

DEER LODGE COUNTY - ANACONDA WEATHER HILL

12/04/76 - 05/31/79

| CTION (M/SEC) | 00.4 11.39 S 17.22 S 17.22 S 17.25 E 17.39 C 17.39 C 17.30 C 1 |
|---|--|
| <pre><direction (m="" pre="" se<="" speed=""></direction></pre> | 0.1-1.0-1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1. |
| TOTAL | - 0.00 |
| NNW | 000000000000000000000000000000000000000 |
| ¥ | 000000000000000000000000000000000000000 |
| X X | 00000000000000000000000000000000000000 |
| 3 | 00000000000000000000000000000000000000 |
| MSM | 00000000000000000000000000000000000000 |
| MS | 0.000000000000000000000000000000000000 |
| MSS | 00000000000000000000000000000000000000 |
| S | 00000000000000000000000000000000000000 |
| SSE | 00000000000000000000000000000000000000 |
| SE | 00000000000000000000000000000000000000 |
| ESE | 00000000000000000000000000000000000000 |
| ш | - WWW 44 W 4 W 1 C C C C C C C C C C C C C C C C C C |
| ENE | 00000000000000000000000000000000000000 |
| A | |
| NNE | 0.000000000000000000000000000000000000 |
| z | 000000000000000000000000000000000000000 |
| DIRECTION> SPEED (MPH) | S 4.1-5.0 2.1-1.0 2.1-2.0 2.1-3.0 3.1-4.0 P 5.1-6.0 E 7.1-8.0 P 9.1-10.0 M 10.1-11.0 L 12.1-12.0 L 12.1-14.0 S 14.1-15.0 M 19.1-20.0 R 19.1-20.0 20.1-25.0 20.1-25.0 20.1-25.0 20.1-25.0 20.1-25.0 20.1-25.0 AV SPD (MPH) |
| | |




Table IV - 58

Coefficients of Weibull Distribution

DEER LODGE COUNTY - ANACONDA WEATHER HILL

12/04/76 - 05/31/79

| MONTH | SCALE FACTOR (C) (M/SEC) | SHAPE FACTOR (K) |
|----------------------|--------------------------------|---------------------|
| JANUARY FEBRUARY | 9.6346 | 1.2677 |
| MARCH | 10,6592 8,1883 | 1,3294 |
| MAY | 9,0770 | 1.7469 |
| JULY | 5.5180 6.0648 | 1.4126 |
| SEPTEMBER | 8.5019 8.7016 | 1.6952 |
| NOVEMBER DECEMBER | 7.6801 | 1.0634 |
| YEAR | 9.2157 | 1,4134 |

LEWISTOWN FAA AIRPORT

FERGUS COUNTY

The Lewistown airport is located approximately 4 miles southwest of Lewistown at 47 03 00 N and 109 27 00 W (Site No. 40 on Map II-1). Elevation at the airport is 4,143 feet. Meteorological data have been collected at the airport for many years by the Federal Aviation Administration.

These data, primarily collected for aviation and weather forecasting uses, consist of short-term (5 minutes or less) averages of wind speed and direction, as well as other meteorological parameters. Data were gathered once per hour. The data have been analyzed by Battelle Pacific Northwest Laboratories. Because of a change in reporting interval, the data set was split into two parts for analysis: December 21, 1949, through August 15, 1962; and October 13, 1964, through December 31, 1978. Data from the latter period only were selected for inclusion in the Montana Wind Energy Atlas.

The data set for Lewistown consists of summaries of observations made every third hour from October 13, 1964, through December 31, 1978. The anemometer was mounted on a ground mast at a height of 6.1 meters. The site is representative of a limited area within a few miles of Lewistown, since the area is surrounded by mountains.

Average annual wind speed at the airport was 10.1 miles per hour. Average monthly wind speeds ranged from 8.3 miles per hour in July to 11.2 miles per hour in December and January.

Average annual wind power was 109.0 watts/m². Average monthly wind power ranged from 54.0 watts/m² in July to 164.0 watts/m² in January.




Table IV - 59

Monthly Wind Speed Distribution

FERGUS COUNTY - LEWISTOWN FAA AIRPORT

10/13/64 - 12/31/78

| | _ | | ٠, | ^ | 1.1 | | _ | | _ | | _ | 1.1 | | | | | 1.1 | | _ | | _ | | | | | | | | | |
|----------|------------|------------|----------|----------|--------------|----------|----------|------|------|--------------|--------------|-----|-----|------|--------|-------------|----------|----------------|----------|--------------|----------------|-----|-----|-----|----------|----------|---------|----------------------|---------|-------------------------|
| | .5 | | | ۵. | | | | | | لىدا | | | | | | | | | | | | | | | | | | | | |
| | _ | _ | S | 3 | ⇉ | 5 | S | ~ | · 00 | 6 | 0 | - | Q | 3 | # | 5 | 9 | ~ | 8 | 9 | 0 | 5 | 0 | S | 7.0 | 0 | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | -₹ | | | | | |
| | Ş | 0 | _ | N | m | _ | 3 | . 6 | _ | 8 | 6 | 10. | = | 72 | 33. | 77 | 15. | 16. | 17 | 8 | 9. | 20. | 25. | 30. | 35. | | | | | |
| AR | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| YEAR | 9. | 0 | ۲. | 20. | 16. | 14. | 6 | 9 | ω, | ω. | ď | 0 | 0 | 0 | 0 | 0 | 0 | <u>.</u> | <u>.</u> | 0 | 0 | 0. | · | 0 | 0.0 | <u>.</u> | | 0 | 4.5 | 109.0 |
| O | | | | | | | | | | | | | | | | | | | | | | | | | 0 | | | - | _ | |
| DEC | 6 | 0 | 9 | 17. | <u>+</u> | 3 | 6 | .~ | 6 | - → | = | - | 0. | 0 | 0 | 0 | 0. | ·. | 0 | 0 | 0.0 | 0: | 0 | 0 | 0.0 | 0. | | 1.2 | 5.0 | 148.0 |
| _ | ~ | _ | _ | ٠ | ` | | | ~ | | _ | ٠. | | _ | | ٠. | | _ | _ | _ | _ | _ | _ | _ | _ | _ | _ | | <u> </u> | | |
| N0< | | | | | | | | | | | | | | | | | | | | | | | | | 0.0 | | | 0.3 | 4.6 | 119.0 |
| | | | | _ | _ | _ | | | | | | | | | | | | | | | | | | | | | | _ | | |
| OCT | • | | • | ٣, | Ŗ, | ⇒: | • | | | • | • | | | | | | | • | • | | | • | | | 0.0 | - | | 0.1 | 4.5 | 0.40 |
| | | | | N | _ | _ | | | | | | | | | | | | | | | | | | | | | | • | • | 10 |
| SEP | 9.4 | 7.0 | 8. | 5.7 | 8.8 | 3.7 | 7.7 | 4.8 | 6.9 | 7. | 1.2 | 0.5 | 0.1 | 0.1 | 0.0 | 0.1 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 9.2 | 4.1 | 78.0 |
| | | | | N | Ē | _ | | _ | _ | | | _ | _ | _ | _ | _ | _ | _ | _ | _ | _ | _ | ~ | Ŭ | 0 | _ | | ٠. | ~ | 32 |
| AUG | | • | • | | | • | | | | | | | | | | | | | | | | | - | | 0.0 | _ | | 8.7 | 3.9 | 0.40 |
| | Ξ | _ | • | Ñ | Ť. | ~ | , | _ | _ | | , | _ | _ | _ | _ | _ | _ | _ | _ | _ | _ | _ | _ | | _ | _ | | ω | (1) | 49 |
| JUL | 9.0 | ~ | 9. | _ | | | .9 | 6. | - | - | .5 | 0. | 0. | - | 0. | 0. | 0. | 0. | 0. | 0. | 0. | 0: | 0. | 0. | 0 | 0 | | ۳. | 3.7 | 0 |
| , | = | _ | 01 | N | <u>~</u> | 7 | , | (1) | ~ | _ | _ | 0 | 0 | ٥ | J | U | 0 | O | C | O | 0 | 0 | 0 | 0 | 0 | 0 | | ω | 3 | 54 |
| NO C | ς. | | ٣, | <u>ښ</u> | ω. | 9 | 5 | 6 | 00 | 'n | ⊅ . | ٣, | ۲. | | 0. | 0. | 0. | 0. | 0 | 0. | 0. | 0. | 0 | 0. | 0. | 0. | | 4.6 | 5. | 0. |
| ~ | 5 | 0 | ထ | 22 | 9 | 7 | ထ | z) | 9 | N | _ | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | Ö | 0 | | 6 | 7 | 78. |
| MAY | Ŋ | | • | | • | | | | | | • | | | | • | | | • | | | | | | | | | | ۳. | 9. | 0. |
| Σ | 6 | 0 | _ | 38 | 16 | 7 | 10 | 9 | 8 | 7 | S | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 10. | 7 | 104.0 |
| APR | 7 | | | | | | | | | | | | | | | | | | | | | | | | | | | 0 | 9 | |
| ∢ | 7 | 0 | S | 17 | 16 | 16 | 10 | 7 | Ò | 4 | m | 0 | 0 | 0 | 0 | 0 | Ó | o | 0 | Ö | o | Ö | 0 | Ö | o · | o | | Ξ | | 124.0 |
| MAR | 0 | ≠. | 7 | ٥ | Ŋ | ٥ | m | _ | 80 | 6 | - | ٥ | 8 | 9 | _ | _ | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 0 | 6 | |
| Σ | 00 | o' | Ö | 8 | _ | <u>+</u> | Ξ | ~ | ο. | - | က် | o | Ö | o | o. | ċ | <u>.</u> | o. | <u>.</u> | o. | o. | o. | Ċ | o | o | o. | | 11.0 | # | 129.0 |
| B | φ. | ⅎ. | t | ထ | 8 | _ | 6 | 7 | 9 | 9 | 0 | a | ~ | ~ | ر د | ,_ _ | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 7 | 80 | 0 1 |
| H | 6 | - | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | | | • | • | | 10. | ⇒. | 143. |
| z | ان ا | ι C | N | 5 | 0 | 5 | 9 | Ŋ | Ŋ | œ | m | m | _ | 3 | က | N. | _ | . . | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | ~ | C | - |
| JAN | 9. | | | | | | | | | | | | | | | | | | | | | | | | | | | Ξ. | 5.0 | 164.0 |
| | _ | , . | <u>.</u> | S. | ന | _ | co. | vo | ഹ | 0 | m | ī | _ | _ | ۸L | + | _ | <u>α</u> | NI. | - | · · · | m | _ | ۸i | + | - | | | _ | |
| | 1.1 | m | Ś | - | 9 | 2 | <u>.</u> | . 9 | 8 | 21: | 33 | 5 | 7 | 30.1 | 32 | 34. | 36. | 8 | | ~. | ₹. | 9 | 28. | 6 | - 06- | .0 | 1.1 | Ĥ | SEC | . <u>2</u> |
| | <u>V</u> , | <u>.</u> | + | 6 | 8 | <u>_</u> | 3 | 5 | 8 | - | 3- | 7 | | ŀ | 2 | 1 | | 5 | Ĭ | 1 | 7-9 | 9, | - | Ċ. | <u>-</u> | Ň, | AVERAGE | PEED (MPH AVERAGE | W/K | ¥ 502 |
| | CALM | _ ' | 'n | יע | _ | 0 | ď | 14.5 | 9 | 6 | 2 | 23 | 25 | 58 | 30. | 22 | 7 | 36. | δ. | _ | 4 3 | | 5 | 89 | 7 | | VER | ED. | 0.00 | TS/ |
| | Ö | | | | | | | ۵ | | | | | | | | | | | | | | | | | | | ⋖ | SPE | PEE | WIND POWER (WATTS/M**2) |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | (i) | _ |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

ANEMOMETER HEIGHT = 20.0 FEET = 6.1 METERS

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

BIG PRAIRIE

The Big Prairie air monitoring site was established by the Montana Air Quality Bureau as part of the Flathead River Basin Environmental Impact Study. The site is located near Polebridge at 48 48 29 N and 114 18 41 W (Site No. 41 on Map II-1 in the valley of the North Fork of the Flathead River. Elevation at the site is 3,587 feet. The valley in this area is about 5 miles wide and is bordered by mountain ranges rising 8,000 and 10,000 feet above sea level. The valley site, therefore, is representative only of a relatively small area.

Data collection began on November 7, 1978, and data through January 4, 1982, were available for analysis. Data recovery, however, was poor, ranging from 0.0 percent in February to 93.0 percent in July. Overall data recovery during the monitoring period was 42.8 percent. The site is located 2 miles from the nearest road, and because of heavy snow and severe cold, it frequently is inaccessible during the winter. Consequently, major breaks exist in the data set. No data are available for the periods December 25, 1978, through June 7, 1979, and November 8, 1979, through March 31, 1980. Winds were monitored long enough, however, to adequately represent the wind resource at this location during the summer months.

The data set contains hourly averages of wind speed and wind direction manually reduced from stripchart records. The data were collected by a battery-operated Climatronics electronic anemometer and wind vane on a 10-meter tower.

Average monthly wind speeds were low at this site; they ranged from 2.4 miles per hour in January to 4.8 miles per hour in April. Average annual wind speed was 3.4 miles per hour. Average wind speeds were highest from April through July.

Average annual wind power at the site was 8.4 watts/m². Monthly averages varied from 4.2 watts/m² in January to 18.0 watts/m² in April.




Table IV - 60

FLATHEAD COUNTY - BIG PRAIRIE Monthly Wind Speed Distribution

11/07/78 - 01/04/82

| | A | + 9 ~ 8 9 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 | | . | 8.6- 8.9 8.6- 8.9 9.0-11.2 11.3-13.4 13.5-15.6 15.7-17.9 | | |
|------|-----------------------------|---|--|----------------|---|---|--------------------|
| YEAR | 17.0 4.2 16.2 15.4 | 9 L 9 N 9 : | 01000 | 00000 | 0000000 | 3.4 | 8.4 |
| DEC | | | | | | 2.5 | 4.7 |
| NOV | 15.2 4.4 20.4 22.8 | 000000 | 0.00 | 00000 | | 2.8 | 5.0 |
| 001 | | | | | | 2.5 | 5.2 |
| SEP | | | | | 0000000 | 3.0 | 7.1 |
| AUG | | | | | 0000000 | 3.2 | 6.4 |
| JUL | 13.5 13.8 13.8 | 90.890. | ~ wa - o o | -0000 | 0000000 | 1.8 | 9.6 |
| NOC | | | | <i>.</i> | 0000000 | 1.8 | 10.9 |
| MAY | 15.3 12.0 15.6 | 60~9~= | 4 c c c c c c c c c c c c c c c c c c c | 0.000 | | 1.8 | 12.0 38.5 |
| APR | 13.8 3.2 11.6 | 8.0.0.00 6.0.000 | - NWW.NY- 0 - NW. W. W | 0000 | | 4.8 2.2 | 18.0 |
| MAR | 7.7 5.1 23.8 12.6 | 8.67.7.7.8 8.1.7.1.9.8 | -86790 | 00000 | | 3.7 | 8.8 |
| FEB | | | | | 000000 | Q Q | ND 0.0 |
| JAN | | | | | 0000000 | 2.4 | 3.7 |
| | 0.1-1 1.1-2 2.1-3 | | 21-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1- | 16.1-15 | 20.1-20.0 20.1-25.0 25.1-30.0 30.1-35.0 | AVERAGE SPEED (MPH) AVERAGE SPEED (M/SEC) AVERAGE | TTS/M** CENT DA |

NAMED ENTRY OFFICE

ANEMOMETER HEIGHT = 10 METERS = 33 FEET NUMBER OF OBSERVATIONS = 11850
PERCENTAGE DATA RECOVERY = 42.8

COLUMBIA FALLS WATER SUPPLY

FLATHEAD COUNTY

The Columbia Falls Water Supply air monitoring site is located about 1 mile northeast of Columbia Falls at 48 24 05 N and 114 08 32 W (Site No. 46 on Map II-1). Elevation at the site is 3,129 feet. The site was established by the Montana Air Quality Bureau to measure particulate concentrations in the area and to provide data for the Flathead River Basin Environmental Impact Study.

Wind data collected from February 16, 1977, through October 22, 1979, were available for analysis. The data set contains hourly averages for wind speed and direction manually reduced from stripchart records. The data were gathered by a Climatronics electronic anemometer and wind vane on a 10-meter tower.

Winds have been monitored long enough to adequately represent the wind resource at this location. The site is representative only of the immediate area, however, because it is located at the base of Teakettle Mountain and near the mouth of a large canyon. Data recovery, which for the period was 83.7 percent, ranged from 66.9 percent in August to 96.9 percent in October.

Average monthly wind speeds varied from 5.0 miles per hour in September to 7.7 miles per hour in August. Average annual wind speed was 6.4 miles per hour.

Average monthly wind power ranged from 15.9 watts/m² in September to 100.6 watts/m² in February. Average annual wind power was 48.3 watts/m².




Table IV - 61

Monthly Wind Speed Distribution

FLATHEAD COUNTY - COLUMBIA FALLS WATER SUPPLY

02/16/77 - 10/22/79

| | O: E | 7 0 | <u>+</u> | 9-2 | | , c | 7- 4 | 4.1- 4.5 | -0 -0 | 5- 5- | 9 -6 | 9 -4 | -8 1 ~ | | | 6, 6 | 0-11 | 3 - 13 | 5-15 | 7-17 | _ | | | | | | |
|------|---------|------------|-------------------|----------------|------------|--------|--------|-------------|----------------|----------|----------|----------|------------|----------|------|---------------|----------|--------|------|------|-------|---------|------------------------|---------------|-----------------------|------------------------------|----------|
| YEAR | 00.5 | ⊃≠ | _ | 寸 : | ഹം | ۰. | 80 | ٥ ٥ | N (C) | 0 | _ | 6 | س ۱ | ~ r | ~ v | . | <u>.</u> | · | Č١ | 01 | 0.0 | | 4.9 | 2.9 | | 48.3 | 83.7 |
| DEC | 0.0 | | | | | | • | | | | • | | | | | | | | | | | | 7.4 | 3.3 | | 73.9 | 72.2 |
| NOV | 0.0 | | | + | | | • | • | | | | | | | | | | | | | | | 7.1 | 3.2 | | 71.8 | 88.6 |
| OCT | 0.5 | ν ο | 6 | 19.6 | ~ œ | 6.0 | 4.5 | 2.0 | 1.0 | 1.0 | 0.8 | 0.5 | 9.0 | ٠ - د |) C | 0.0 | 7.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 5.3 | 2.3 | | 17.8 | 6.96 |
| SEP | 0.1 | | | | | | • | • | | | • | | | | | | | | | | | | 5.0 | 2.2 | | 15.9 | 93.9 |
| AUG | 0.0 | | • | • | • | | • | | | | | | | | | | | | • | | | | 7.7 | 3.4 | | 8.99 | 6.99 |
| JUL | 0.5 | 8.7 | 18.1 | 14.2 | 2.5 | 6.6 | 9.6 | 2.7 | ; - | 1:1 | 1,2 | 9.0 | 0.0 | 0 | - 0 | 7.0 | 1.0 | 0.1 | 0.0 | 0.0 | 0.0 | | 5.9 | 2.6 | | 27.1 | 72.5 |
| NUC | 1.3 | | • | • | • • | | • | • | | • | | | | | | | • | | | • | ٠ | | 5.5 | 2.5 | | 21.3 | 73.6 |
| MAY | 0.0 | | | • | | | | | | | | | | | | | | | | | | | 4.9 | 2.9 | | 26.7 | 96.5 |
| APR | 0.0 | 5.6 | 10.0 | - - | 10.7 | 10.1 | 8.9 | 7.4 9.4 | 3.0 | 3.3 | | 2. | ~ ~ | | - 0 | 7.0 | 3.9 | 0.3 | 0.0 | 0.0 | 0.0 | | 7.5 | 3.3 | | 9.99 | 84.0 |
| MAR | 0.0 | | , | | α | | | • | | | | | | | | | | | | | | | 7.5 | 3.3 | | 72.6 | 87.5 |
| FEB | 0.5 | | | • | | | ٠ | | | | | | | | | | | | | | | | 6.8 | 3.0 | | 100.6 | 78.2 |
| JAN | 0.00 | ~ | 20.7 | · · | ۰. تا | 4.6 | | ۰. د د | | 8. | 9. | 0 | - 0 | | † (\ | 9.0 | 3.4 | 7. | | - 0 | 0 | | 6.1 | 2.7 | | 81.1 | 95.3 |
| | 0. | 2.1-3. | $\frac{3.1-4}{2}$ | 4.1-5. | ٠ <u>٠</u> | 7.1-8. | 8.1-9. | 1 10.1-11.0 | 11.1-12. | 12.1-13. | 13.1-14. | 14.1-15. | 12.1-16. | | - 82 | - | _ | _ | - 1 | _ | 0.04/ | AVERAGE | SPEED (MPH) AVERAGE | SPEED (M/SEC) | AVERAGE WIND POWER | (WATTS/M**2) PERCENT DATA | RECOVERY |

DNOCES/SELLE

ANEMOMETER HEIGHT = 10 METERS = 33 FEET NUMBER OF OBSERVATIONS = 19642 PERCENTAGE DATA RECOVERY = 83.7

KALISPELL NWS AIRPORT

FLATHEAD COUNTY

The Kalispell NWS Airport is located approximately 8 miles north-northeast of Kalispell at 48 18 40 N and 114 16 00 W (Site No. 48 on Map II-1). Elevation at the airport is 2,978 feet.

Meteorological data have been collected at this site for many years by the National Weather Service. These data, primarily collected for aviation and weather forecasting uses, consist of short-term (5 minutes or less) averages of wind speed and wind direction, as well as other meteorological parameters. Data were gathered once per hour. The data have been analyzed by Battelle Pacific Northwest Laboratories. Because of changes in anemometer heights and reporting intervals, the data set was broken into four parts for analysis: May 1, 1949, through June 30, 1953; July 1, 1953, through June 30, 1954; and July 1, 1964, through December 31, 1978. Only data from the most recent of these periods were selected for inclusion in the *Montana Wind Energy Atlas*.

The data set for the site consists of summaries of observations made every third hour from July 1, 1964, through December 31, 1978. The anemometer was mounted on a ground mast at a height of 6.1 meters. The site is representative only of the immediate area because winds at the site are influenced by Flathead Lake to the south and a canyon to the northeast.

Average monthly wind speeds at Kalispell varied from 5.6 miles per hour in October and November to 8.5 miles per hour in April. Average annual wind speed was 6.9 miles per hour.

Average monthly wind power ranged from 34.0 watts/m² in October to 78.0 watts/m² in January. Average annual wind power at the site was 53.0 watts/m²




Table IV - 62

Monthly Wind Speed Distribution

FLATHEAD COUNTY - KALISPELL NWS AIRPORT

07/01/64 - 12/31/78

| JAN FEB MAR APR MAY JUIN JUL AUG SEP OCT NOV DEC YEAR CALL ST. 1.1 24.2 16.3 10.7 10.8 9.4 12.6 13.7 17.8 25.4 29.0 29.4 18.9 0.1 17.1 17.1 0.6 0.2 0.5 0.5 0.5 1.2 1.6 1.7 0.7 1.3 1.3 1.3 1.3 1.3 1.4 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 | | Arvivarion vivarion v | |
|--|------|--|--|
| CALM (<1.1) 27.1 24.2 16.3 10.7 10.8 9.4 12.6 13.7 17.8 25.4 29.0 29.4 1 1.1 3.1 27.1 24.2 16.3 10.7 10.8 9.4 12.6 13.7 17.8 25.4 29.0 29.4 1 1 1.1 3.1 27.1 24.2 16.3 10.7 10.8 9.4 12.6 13.7 17.8 25.4 29.0 29.4 1 1 1.1 27.1 24.2 16.3 19.7 18.9 21.6 27.6 26.2 23.6 2 25.6 7.6 12.8 13.7 17.8 24.6 27.6 26.2 23.6 2 25.6 7.6 12.8 13.7 17.8 24.6 27.7 12.8 18.4 24.6 27.7 12.8 18.4 24.6 27.7 12.8 18.4 24.6 19.8 19.7 19.5 19.7 19.7 19.7 19.7 19.7 19.7 19.7 19.7 | | Qo-02400000000000000000000000000000000000 | |
| CALM (<1.1) 27.1 24.2 16.3 10.7 10.8 9.4 12.6 13.7 17.8 25.4 29.0 29 1.1 1.1 27.1 24.2 16.3 10.7 10.8 9.4 12.6 13.7 17.8 25.4 29.0 29 13.3 13.4 5.4 12.8 12.1 27.1 24.2 16.3 10.7 10.8 9.4 12.6 13.7 17.8 25.4 29.0 29 13.4 5.4 12.8 14.1 17.1 17.1 0.6 0.2 0.5 0.5 12.2 1.6 17.7 0.7 13.3 13.4 5.4 12.8 14.1 17.8 19.7 15.2 16.7 16.6 14.8 14.7 17.8 19.1 17.8 19.7 15.2 16.7 16.6 14.8 14.7 17.2 10.8 19.1 19.1 19.1 19.1 19.1 19.1 19.1 19 | YEAR | 8-m8009m0-000000000000000000000000000000 | 6.9 3.1 53.0 |
| CALM (<1.1) 27.1 24.2 16.3 10.7 10.8 9.4 12.6 13.7 17.8 25.4 2 1.1 - 3.1 1 1.1 0.6 0.2 0.5 0.5 12.6 13.7 17.8 25.4 2 1.1 - 3.1 1 1.1 0.6 0.2 0.5 0.5 12.3 12.7 17.8 27.6 2.5 3 24.8 24.6 27.6 27.6 27.6 - 2.8 14.1 13.7 15.2 16.7 18.9 21.6 27.6 27.6 27.6 12.8 14.1 13.7 15.2 16.7 16.6 17.7 15.2 14.2 17.7 12.6 17.7 12.7 12.6 17.7 12.7 12.6 17.7 12.7 12.7 12.7 12.7 12.7 12.7 12.7 | DEC | 00000000000000000000000000000000000000 | 5.8 2.6 51.0 |
| CALM (<1.1) 27.1 24.2 16.3 10.7 10.8 9.4 12.6 13.7 17.8 25 3.4 - 5.4 22.1 23.7 20.3 19.7 10.8 9.4 12.6 13.7 17.8 25 3.4 - 5.4 22.1 23.7 20.3 19.7 18.9 21.6 25.3 24.8 24.6 27 28 - 7.6 12.8 14.1 17.8 18.4 20.9 22.6 23.0 21.7 20.5 177 20.5 | NOV | ••••••••••••••• | 5.6 2.5 41.0 |
| CALM (<1.1) 27.1 24.2 16.3 10.7 10.8 9.4 12.6 13.7 1 3.4 - 5.4 22.1 23.7 20.3 19.7 18.9 21.6 25.3 24.8 2 5.6 - 7.6 12.8 14.1 17.8 18.4 20.9 22.4 23.0 21.7 2 10.1 - 12.1 8 14.1 17.8 18.4 20.9 22.4 23.0 21.7 2 10.6 10.6 13.7 15.2 16.6 14.8 10.7 10.6 10.1 12.7 15.2 16.6 14.8 10.7 1 10.8 - 18.8 2.6 5.6 7.6 12.8 14.1 17.8 12.1 12.7 12.7 12.6 14.6 14.7 1 10.9 0.21.0 2.2 1.5 1.5 1.5 2.3 1.4 0.9 0.6 1.2 1.6 14.8 10.7 1.6 14.8 10.7 1.6 14.8 10.7 1.6 14.8 10.7 1.6 14.8 10.7 1.6 14.8 10.7 1.6 14.8 10.7 1.6 14.8 10.7 1.6 14.8 10.7 1.6 14.8 10.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0. | OCT | 22 22 22 24 25 25 25 25 25 25 25 25 25 25 25 25 25 | 5.6 2.5 34.0 |
| CALM (<1.1) 27.1 24.2 16.3 10.7 10.8 9.4 12.6 13 1.1-3.1 12.1 24.2 16.3 10.7 10.8 9.4 12.6 13 3.4-5.4 122.1 23.7 20.3 19.7 18.9 21.6 23.3 24 5.6-7.6 12.8 14.1 17.8 18.4 20.9 22.4 23.3 21 10.1-12.1 2.1 23.7 20.3 19.7 18.9 21.6 23.3 21 10.1-12.1 3.1 3.9 5.2 16.7 16.6 14.8 14 10.1-12.1 3.9 5.2 6.1 5.1 12.7 16.6 14.8 14 10.1-12.1 3.9 5.2 6.1 5.1 12.7 16.6 14.8 14 10.1-12.1 3.9 5.2 6.1 5.6 4.6 3.0 2 11.5-16.6 4.1 3.9 5.2 6.1 5.6 4.6 3.0 2 11.5-16.6 4.1 3.9 5.2 6.1 5.0 10.0 0.0 14.5-16.6 4.1 3.9 5.2 6.1 5.3 2.3 2.1 1.9 0.1 14.5-16.6 4.1 3.9 5.2 6.1 5.3 2.3 2.1 1.9 0.1 15.2.3-2.5.5 0.8 0.5 0.4 0.7 0.2 0.1 0.0 0.0 14.5-16.6 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 15.5-7-2.7 0.5 0.3 0.4 0.1 0.0 0.0 0.0 0.0 0.0 15.5-7-2.3 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 15.5-7-2.3 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0 | SEP | 87-700000000000000000000000000000000000 | 6.5 2.9 44.0 |
| CALM (<1.1) 27.1 24.2 16.3 10.7 10.8 9.4 12 3.4 - 3.1 1.1 1.1 0.6 0.2 0.5 0.5 1.1 3.4 - 3.1 1.1 1.1 0.6 0.2 0.5 0.5 1.1 3.4 - 3.1 1.1 1.1 0.6 0.2 0.5 0.5 1.1 3.4 - 2.1 23.7 20.3 19.7 18.9 22.4 23.7 20.3 19.7 18.9 22.4 23.7 20.3 19.7 15.2 16.7 16.6 144 10.1 12.3 - 14.3 6.0 5.6 10.4 11.8 12.1 12.7 12.6 114 10.9 14.5 12.3 - 14.3 6.0 5.6 14.4 11.8 12.1 12.7 12.6 11.8 16.8 - 18.8 2.6 2.8 2.9 3.9 2.3 1.4 0.9 0.1 16.8 - 18.8 2.6 2.8 2.9 3.9 2.3 1.4 0.9 0.1 16.8 - 18.8 2.6 2.8 2.9 3.9 2.3 1.4 0.9 0.1 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 | AUG | 22 1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 | 6.7 3.0 40.0 |
| CALM (<1.1) 27.1 24.2 16.3 10.7 10.8 9 1.1 - 3.1 1 1.1 0.6 0.2 0.5 0.5 0.5 0.5 0.5 0.2 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 | JUL | 27 28 28 28 28 28 28 28 28 28 28 28 28 28 | 6.7 3.0 39.0 |
| CALM (<1.1) 27.1 24.2 16.3 10.7 10.1 1.1 0.6 0.2 0.2 0.2 1.1 1.1 0.6 0.2 0.2 0.2 1.2 1.1 1.1 0.6 0.2 0.2 0.2 1.2 1.2 1.2 1.2 1.2 1.2 1.2 1.2 1.2 1 | NOC | 22220900000000000000000000000000000000 | 7.6 3.4 49.0 |
| CALM (<1.1) 27.1 24.2 16.3 10 3.4-5.4 22.1 23.7 20.3 19 \$ 5.6-7.6 12.8 14.1 17.8 18 E 10.1-12.1 8.6 10.6 17.8 18 E 12.3-14.3 6.0 5.6 7.4 82 D 14.5-16.6 4.1 3.9 5.2 6 D 14.5-16.6 4.1 3.9 5.2 6 D 14.5-16.6 4.1 3.9 5.2 6 D 14.5-25.5 0.8 0.5 0.4 0 S 28.0-30.0 0.4 0.1 0.2 0.0 S 28.0-30.0 0.4 0.1 0.1 0.1 0.1 0.1 A 32.4-34.4 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1 | MAY | | 8.1 3.6 57.0 |
| CALM (<1.1) 27.1 24.2 16 1.1-3.1 1.1 1.1 1.1 2 5.6-7.6 12.8 14.1 17 2 7.8-9.8 14.1 17 2 7.8-16.6 12.8 14.1 17 2 10.8-18.8 2.6 2.8 2.8 2.8 2.9 2.1 2.1 2.1 2.1 1.1 1.1 1.1 1.1 1.1 1.1 | APR | | 8.5 3.8 77.0 |
| CALM (<1.1) 27.1 28 3.4-5.4 22.1 2 5.56-7.6 12.8 1-1 1.1-3.1 1.1 3.1 1.1 27.1 28 5.6-7.6 12.8 1-1 21.3-14.3 6.0 14.5-16.6 4.1 16.8-18.8 2.6 16.8-18.8 2.6 17.3-14.3 6.0 18.5-25.5 0.8 19.2.3-14.3 6.0 18.5-25.5 0.8 19.3-23.2 0.1 18.5-25.5 0.8 19.3-23.2 0.1 19.3-23.2 0.1 19.3-23.2 0.1 19.3-23.2 0.1 19.3-23.2 0.1 19.3-2-25.5 0.8 19.3-2-32.2 0.1 19.3-2-32.2 0.1 19.3-2-32.2 0.1 19.3-3-3-32.2 0.1 19.3-3-3-3-3-3-3 19.3-3-3-3-3-3 19.3-3-3-3-3-3 19.3-3-3-3-3-3 19.3-3-3-3-3 19.3-3-3-3-3 19.3-3-3-3-3 19.3-3-3-3-3 19.3-3-3-3-3 19.3-3-3-3-3 19.3-3-3-3-3 19.3-3-3-3-3 19.3-3-3-3-3 19.3-3-3-3-3 19.3-3-3-3-3 19.3-3-3-3-3 19.3-3-3-3-3 19.3-3-3-3-3 19.3-3-3-3 19.3-3-3-3 19.3-3-3-3 19.3-3-3-3 19.3-3-3-3 19.3-3-3-3 19.3-3-3 19.3-3-3 19.3-3-3 19.3-3-3 19.3-3-3 19.3-3-3 19.3-3-3 19.3-3-3 19.3-3-3 19.3-3-3 19.3-3-3 19.3-3-3 19.3-3-3 19.3-3 19 | MAR | 2002 | 7.6 3.4 71.0 |
| CALM (<1.1) 27. 3.4-5.4 22. 5.6-7.6 12. 7.1-3.1 1. 1.1-3.1 1. 1.1-3.1 1. 1.1-3.1 1. 2.6-7.6 12. 1.1-3.1 1. | FEB | 22 | 6.5 2.9 61.0 |
| CALM (<1.1 1.1-3. 3.4-5. 8.5-6-7. 7.8-7. 10.1-12. 10.1-12. 10.2-14. 10.2-14. 10.2-14. 10.2-13. 10.2-14. 10.3-14. 10.2-13. 10.2-13. 10.2-13. 10.2-13. 10.2-13. 10.2-13. 10.2-13. 10.2-13. 10.2-13. 10.2-13. 10.2-13. 10.2-13. 10.2-13. 10.2-13. 10.3-14. | JAN | V-000000000000000000000000000000000000 | 936 |
| | | CALM (<1.1 3.4-5. 3.4-5. 7.8-9. 10.3-14-5. 12.3-14-3-14. 12.3-14. 12.3-14. 12.3-14. 12.3-14. 12.3-14. 13.0-23. 13.0-23. 13.0-33. 13.0-33. 13.0-43. 13.0-43. 13.0-43. 13.0-43. 13.0-43. 13.0-43. 13.0-43. 13.0-43. 14.1.0-43. | AVERAC SPEED (N AVERAC PEED (M, AVERAC WIND POY |

ANEMOMETER HEIGHT = 20.0 FEET = 6.1 METERS

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

BOZEMAN FAA AIRPORT

GALLATIN COUNTY

The Bozeman airport is located about 7 miles northwest of Bozeman at 45 46 48 N and 111 09 00 W (Site No. 51 on Map II-1). Elevation at the airport is 4,468 feet. Meteorological data were collected at this site for several years by the Federal Aviation Administration.

These data, primarily collected for aviation and weather forecasting uses, consist of short-term (5 minutes or less) averages of wind speed and direction, as well as other meteorological parameters. Data were gathered once per hour. The data have been analyzed by Battelle Pacific Northwest Laboratories. Because of a change in anemometer height, the Battelle data set was split into two parts for analysis: January 1, 1948, through April 27, 1951; and April 28, 1951, through December 31, 1954. Data from the latter period only were chosen for inclusion in the Montana Wind Energy Atlas.

The data set for Bozeman consists of summaries derived from hourly observations made from April 28, 1951, through December 31, 1954. The anemometer was mounted on a rooftop at a height of 13.1 meters. The site is representative of the lower Gallatin River valley from Bozeman to Belgrade.

Average annual wind speed was 7.8 miles per hour. Monthly wind speeds ranged from an average of 6.7 miles per hour in November and December to an average of 9.4 miles per hour in April.

Average monthly wind power ranged from 47.0 watts/m² in October to 96.0 watts/m² in April and May. Average annual wind power was 71.0 watts/m²




Table IV - 63

Monthly Wind Speed Distribution

GALLATIN COUNTY - BOZEMAN FAA AIRPORT

04/28/51 - 12/31/54

| | 5) P E E | DNOCES/SREHE Z | |
|--------------|--|--|---|
| | 0444444 | | |
| | ~-00±00v | _ | |
| | Annana and | orago: | |
| EAR | | 0-7009#1-00000000 | 8 L O |
| ¥ | | *************************************** | 3.1 |
| DEC | | 6-v-v-v-v-v-v-v-v-v-v-v-v-v-v-v-v-v-v-v | 6.7 3.0 |
| | 01 00 10 10 83 | | 3, 3, 61, |
| <u>№</u> | | Na00000000000000000000000000000000000 | 3.0 |
| . | | | • |
| OCT | | n-000000000000000000000000000000000000 | 6.9 3.1 47.0 |
| ΕP | مد مار | Urwa-0000000000 | |
| S | | 000000000000000000000000000000000000000 | 8.1 3.6 72.0 |
| AUG | 8 m 0 L 4 N 0 m | 29-999-000-0000000 | e r. o |
| 4 | 3777 | | 3 59 |
| JUL | 440500000 | 00000000000000000000000000000000000000 | 7.8 3.5 60.0 |
| z | W | 000000000000000000000000000000000000000 | |
| NDC | | ##-0-000000000000000000000000000000000 | 8.3 3.7 74.0 |
| MAY | 08-44- | | 0 - 0 |
| Ě | なるなりませんでき | 440000000000000000 | 9. 4. |
| APR | | 000000000000000000000000000000000000000 | 4.2 |
| • | E G E E E E E E E E E E E E E E E E E E | /www.ee.00000000000000000000000000000000 | 96. |
| MAR | ~ 200004 cm | 000000000000000000000000000000000000000 | 3.5 |
| 8 | 0 | | 9 |
| H | | | 8.3 3.7 92.0 |
| JAN | 8000WF8W | 7 | |
| 3 | K4885-548 | 717110000000000000000000000000000000000 | 8.1 3.6 89.0 |
| | CL408+80 | ##N080#N07#N07#080 | ~ (c) ~ |
| | V | 7 1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 | MPH VGE VGE VWER |
| | E 2007 | AVERAGE | PEED (MPH) AVERAGE EED (M/SEC AVERAGE IND POWER |
| | C C | Σ-JHW/TODK A | SPEED AVE SPEED AVE WIND (WATTS |
| | | | <i>u, u</i> |

ANEMOMETER HEIGHT = 43.0 FEET = 13.1 METERS

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

BLACKFOOT GLACIER COUNTY

The Blackfoot site is located four miles northeast of Browning at 48 35 20 N and 112 52 35 W (Site No. 53 on Map II-1). Elevation at the site is 4,280 feet. This monitoring site is part of the Wind Regional Energy Assessment Program run by Oregon State University for Bonneville Power Administration.

The site is in a rolling grasslands area near the Rocky Mountain Front. It is less than 20 miles east of Glacier National Park. The site is representative of a large area. Access to the area is reasonable, with an all weather highway running through the middle of the high wind area. Dirt roads criss-cross the area. Winter access is sometimes hampered by drifting snow and severe weather conditions.

The site is located on the Blackfeet Indian Reservation. Electrical service in the area is provided by the Glacier Electric Cooperative. One 115 kV line runs into Browning from Cut Bank. The nearest commercial airport is located in Cut Bank, nearly 30 miles to the east. Air traffic generally is light.

Collection of wind data began in October 1981, when a wind-run anemometer was installed. Summaries of this data are presented in Appendix C. A data logger was installed on July 30, 1984. Data through October 29, 1985 were available for analysis. BPA currently plans to continue monitoring at the site at least through 1989. The anemometer height is 30 feet.

Data recovery was fair to excellent, ranging from 67.8 percent in December to 100.0 percent in April and June. Overall data recovery was 89.4 percent.

Average monthly wind speeds ranged from 11.2 miles per hour in July to 26.1 miles per hour in February. Average annual wind speed was 16.4 miles per hour

Average monthly wind power ranged from $87.1~\text{watts/m}^2$ in July up to 1,300.7 watts/m² in February.

Average seasonal wind speeds were 13.4 miles per hour in the summer, 17.3 miles per hour in the autumn, 23.9 miles per hour in the winter, and 15.2 miles per hour in the spring. In the winter, the highest wind speed occurred in midmorning. In the spring and autumn, highest winds happened mid-morning to mid-afternoon. High winds in the summer were somewhat later, in late afternoon. Diurnal range of average wind speeds was greatest in the winter and less so in the summer and autumn. The range was smallest in the spring.

The most common wind directions were southwest to west. With the exception of winds from the east-southeast through the south, winds from other directions were minimal. By direction, average winds speeds ranged from 20.1 miles per hour from the south-southeast and west-southwest to 8.0 miles per hour from the east-northeast.




Table IV - 64

Monthly Wind Speed Distribution GLACIER COUNTY - BLACKFOOT

| FEB MAR APR MAY JUN JUL AUG SEP OCT NOV 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0. | | | ! | | | | 02/30/ | 07/30/84 - 10/29/85 | /29/85 | | | | | | | |
|--|-----------------------------------|------------|-------------|--------------|-------------|----------|--------|---------------------|--------|-------|------|----------|---|-------|-----------|--|
| 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 | | N. | | | APR | Ā | N N | 3 | AUG | SFP | 50 | Ş | 田田田田田田田田田田田田田田田田田田田田田田田田田田田田田田田田田田田田田田田 | YEAR | | |
| 0.0 1.5 0.1 0.0 0.0 0.0 0.0 0.1 0.5 0.2 0.0 0.2 0.3 0.3 0.3 0.3 0.3 0.1 1.5 0.1 0.0 0.0 0.1 0.0 0.1 0.5 0.2 0.0 0.3 0.3 0.3 0.3 0.3 0.3 0.3 0.3 0.3 | CALM | 0.0 | | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | SAL | |
| 0.3 1.3 1.9 0.0 0.1 0.0 0.0 0.0 0.4 1.4 1.1 0.3 0.6 0.3 0.6 0.3 3.7 1.4 1.1 1.9 1.2 0.1 1.9 1.2 0.3 1.3 1.9 0.0 0.8 3.7 1.4 1.1 1.9 1.2 0.3 1.3 1.3 1.9 0.0 0.8 3.7 1.4 1.1 1.9 1.2 0.3 1.3 1.3 1.3 1.9 3.2 1.0 0.5 5.0 2.9 5.0 6.9 5.1 3.8 3.3 1.3 2.4 1.1 1.9 3.2 1.0 0.5 5.0 2.9 5.0 6.9 5.1 1.9 2.7 3.7 4.1 1.9 3.2 1.0 0.0 0.5 5.0 2.3 2.6 5.5 6.7 8.6 6.0 6.9 4.1 3.0 1.9 5.3 0.6 0.5 6.8 3.1 6.6 6.8 8.6 6.0 6.9 4.1 3.0 1.9 5.3 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0 | 0.1-1.0 | 0 (| | | 0.1 | 0.0 | 0.0 | 0.0 | 0.0 | 0.1 | 0.5 | 0.2 | 0.0 | 0.2 | 0.1 - 0.4 | |
| 0.8 2.1 1.2 0.1 0.3 0.1 0.1 0.9 1.1 2.0 2.1 0.9 0.0 0.8 0.1 5.9 2.2 3.9 4.0 5.0 1.9 1.3 1.3 2.7 4.1 1.9 3.2 1.6 5.0 5.9 5.0 6.9 5.1 3.8 3.3 3.2 2.8 2.9 4.0 0.8 5.0 2.9 5.0 6.9 5.1 3.8 3.3 3.2 2.8 2.9 4.0 0.8 5.0 2.9 5.0 6.9 5.1 1.1 7.1 6.4 4.2 3.4 1.1 1.9 3.2 0.5 5.0 2.6 9.0 9.2 11.1 7.1 6.4 4.2 3.4 1.1 5.9 2.7 4.5 0.8 8.5 6.0 6.9 4.0 3.1 2.7 4.2 3.4 1.1 5.9 0.8 8.5 4.4 10.2 8.5 10.4 6.3 6.8 3.4 2.3 1.3 5.9 0.8 8.5 4.4 10.2 8.5 10.4 4.2 3.4 1.1 5.9 3.8 1.3 4.9 3.9 3.9 4.0 0.8 8.5 4.4 10.2 8.5 10.4 6.3 6.8 3.4 4.2 3.4 1.1 5.9 0.8 8.5 4.4 3.8 3.9 4.0 2.3 1.3 5.9 0.8 4.0 3.3 4.0 3.3 4.0 2.3 1.3 5.9 2.7 4.0 3.3 4.0 3.3 4.0 3.3 4.0 3.0 3.3 4.0 3.0 3.3 4.0 3.0 3.0 3.3 4.0 3.0 3.0 3.3 4.0 3.0 3.0 3.3 4.0 3.0 3.0 3.0 3.0 3.0 3.0 3.0 3.0 3.0 3 | | N = | | | ٠. | ၁. ၁. | 0.0 | 0.0 | 0.0 | 0.4 | 1.4 | : | 0.3 | 0.0 | 0.5-0.9 | |
| 0.8 3.7 1.4 1.1 1.9 1.2 0.3 1.3 2.4 1.9 3.2 1.6 0.5 5.0 2.9 3.2 0.6 6.9 5.1 3.8 3.3 3.2 2.8 2.9 4.0 0.5 0.0 0.9 5.2 3.2 0.8 2.9 3.2 0.8 5.2 0.9 5.1 3.8 3.3 3.2 2.8 2.9 4.0 0.5 0.8 5.2 3.2 0.8 5.3 3.2 2.8 3.3 3.2 2.8 2.9 4.0 0.5 0.8 5.2 3.2 0.8 4.5 3.3 2.2 3.8 2.9 4.0 0.5 0.8 6.8 6.6 6.8 6.6 6.9 4.1 3.0 1.9 5.3 0.8 4.5 0.8 6.7 6.6 6.8 8.6 6.0 6.9 4.1 3.0 1.9 5.3 0.8 4.8 0.8 4.9 2.9 3.9 8.3 6.8 7.6 6.1 5.3 3.0 2.3 1.3 5.9 3.8 3.3 4.2 2.3 1.3 5.9 0.8 4.8 1.3 4.2 2.8 6.7 6.7 7.7 7.7 4.7 4.6 3.1 3.5 5.1 3.5 5.1 3.2 3.3 3.2 3.8 3.9 4.6 5.1 6.1 3.4 4.0 3.1 4.0 3.1 3.0 3.1 3.0 3.2 3.9 3.4 3.1 3.2 3.9 3.8 3.1 3.0 3.8 3.1 3.0 3.0 3.0 3.0 3.0 3.0 3.0 3.0 3.0 3.0 | | ۰ د | | | C: . | | ກຸ ເ | 0 | | 6.0 | Ξ. | 2.0 | 2.1 | 6.0 | 1.0-1.3 | |
| 1.1 5.9 2.2 3.9 4.0 5.0 1.9 2.7 3.7 4.1 1.9 3.2 0.8 5.2 3.2 4.0 0.8 5.2 3.3 3.3 3.3 3.3 3.2 2.8 2.9 4.0 0.8 5.2 3.2 6.5 6.5 8.8 6.0 6.9 4.1 3.0 1.9 5.3 0.8 6.8 3.1 6.6 6.8 8.6 6.0 6.9 4.1 3.0 1.9 5.3 0.8 4.0 0.8 8.9 8.3 6.8 7.6 6.1 5.3 3.0 2.3 1.3 5.9 5.0 0.8 4.9 3.9 8.3 6.8 7.6 6.1 5.3 3.0 2.3 1.3 5.9 5.1 3.4 4.2 0.2 6.7 6.5 7.7 7.7 4.7 4.6 3.1 3.0 2.3 1.3 5.9 5.1 3.4 3.3 4.0 3.4 4.0 3.1 3.0 3.4 4.0 3.1 3.0 3.4 4.0 3.1 3.0 3.1 4.0 3.1 3.0 3.1 4.0 3.1 3.0 3.1 4.0 3.1 3.0 3.0 3.0 3.0 3.0 3.0 3.0 3.0 3.0 3.0 | | 7 | | | 1.4 |]. | 1.9 | 1.2 1.2 | 0.0 | T | 2.4 | 1.9 | 3.2 | 1.6 | 1.4- 1.8 | |
| 0.5 5.0 2.9 5.0 6.9 5.1 3.8 3.3 3.2 2.8 2.9 4.0 0.8 5.2 6.5 6.8 6.6 6.9 4.0 3.1 2.7 4.5 0.5 6.8 8.6 6.0 6.9 4.0 3.1 2.7 4.5 0.0 6.9 9.2 11.1 7.1 6.4 4.2 3.4 1.1 5.9 0.8 8.5 6.7 6.9 0.9 2.1 11.1 7.1 6.4 4.2 3.4 1.1 5.9 0.8 8.5 6.7 6.4 7.2 1.0 6.4 4.2 3.1 3.1 5.9 0.8 4.0 3.3 4.0 2.3 1.3 5.9 1.3 4.0 3.3 4.0 3.3 6.8 7.6 6.1 4.0 4.0 3.1 3.1 3.5 5.9 4.0 3.3 4.0 3.6 4.4 6.0 6.3 4.4 4.0 3.4 2.3 1.3 5.9 4.0 3.3 4.0 3.5 4.4 6.0 6.3 4.4 4.0 3.4 2.7 4.4 4.0 3.3 3.5 2.8 4.0 3.5 4.4 4.0 3.4 2.7 4.4 4.0 3.3 3.5 2.2 3.8 3.9 2.7 4.4 4.0 3.3 3.2 3.9 2.7 4.4 4.0 3.3 3.2 3.9 3.5 2.2 5.0 3.8 4.0 5.3 1.0 3.9 4.2 4.2 4.2 4.1 3.0 3.1 3.3 4.7 1.9 3.6 4.2 3.3 3.2 3.9 3.4 3.1 3.1 4.2 5.0 3.8 4.0 3.1 3.3 4.7 1.9 3.6 3.2 5.0 3.8 4.0 3.1 3.2 3.9 3.4 3.1 3.1 3.2 3.0 3.2 3.9 3.4 3.1 3.1 3.2 3.0 3.2 3.9 3.7 3.0 3.2 3.9 3.7 3.0 3.2 3.9 3.7 3.0 3.2 3.9 3.7 3.0 3.2 3.9 3.1 3.2 3.9 3.7 3.0 3.2 3.9 3.1 3.2 3.9 3.7 3.0 3.2 3.8 4.0 3.0 3.2 3.8 4.0 5.3 1.0 3.0 3.5 3.8 4.0 3.0 3.5 3.8 4.0 3.0 3.5 3.8 4.0 3.0 3.5 3.8 4.0 3.0 3.5 3.8 4.0 3.0 3.5 3.8 4.0 3.0 3.5 3.8 4.0 3.0 3.5 3.8 4.0 3.0 3.5 3.8 4.0 3.0 3.5 3.8 4.0 3.0 3.5 3.8 4.0 3.0 3.5 3.8 4.0 3.0 3.5 3.8 4.0 3.0 3.5 3.8 4.0 3.0 3.0 3.5 3.8 4.0 3.0 3.0 3.5 3.8 4.0 3.0 3.0 3.5 3.8 4.0 3.0 3.0 3.5 3.8 4.0 3.0 3.0 3.5 3.8 4.0 3.0 3.0 3.5 3.8 4.0 3.0 3.0 3.0 3.5 3.8 4.0 3.0 3.0 3.0 3.5 3.8 4.0 3.0 3.0 3.0 3.0 3.0 3.0 3.0 3.0 3.0 3 | | | | | 2.2 | ۍ س | 4.0 | 2.0 | 6.1 | 2.7 | 3.7 | 4.1 | 1.9 | 3.2 | 1.9- 2.2 | |
| 0.8 5.2 3.2 6.5 6.7 8.5 5.5 2.4 4.0 3.1 2.7 4.5 0.5 6.8 8.6 6.8 6.0 6.9 4.1 3.0 1.9 5.3 0.8 8.5 6.8 8.6 6.0 6.9 4.1 3.0 1.9 5.3 0.8 8.9 9.9 8.3 6.8 3.4 10.2 8.5 10.4 6.3 6.8 3.4 2.3 1.3 5.9 0.8 4.9 3.9 8.3 6.8 7.6 6.1 5.3 3.0 2.3 1.3 5.9 1.3 4.2 2.9 4.1 2.6 6.7 6.5 7.7 7.7 4.7 4.6 3.1 3.5 5.1 2.9 4.1 2.6 6.7 6.5 7.7 7.7 4.7 4.6 3.1 3.5 5.1 3.5 3.1 3.5 5.1 3.2 3.4 3.8 3.9 4.6 5.1 6.1 3.4 4.0 3.4 4.0 3.4 4.0 3.4 4.0 3.4 4.0 3.4 4.0 3.4 4.0 3.4 4.0 3.2 3.3 3.2 3.3 3.2 3.9 3.5 4.2 4.5 5.1 3.1 3.9 5.0 1.9 4.2 3.2 3.3 3.2 3.9 3.5 4.2 4.5 4.9 5.1 3.1 3.9 5.0 1.9 4.2 3.2 3.3 3.1 3.6 4.4 6.0 3.1 3.4 3.1 3.9 5.0 1.9 4.2 3.2 3.3 3.1 3.6 4.9 5.1 3.1 3.9 5.0 1.9 4.2 3.2 3.9 3.1 2.8 1.8 1.9 2.6 3.0 3.1 3.1 3.9 2.7 4.2 3.9 3.1 2.8 1.8 1.9 2.6 3.0 3.1 3.1 3.9 2.9 3.1 2.0 7.6 1.7 1.7 0.0 2.9 4.8 6.3 6.3 11.0 4.5 2.7 8.6 0.2 2.4 0.4 0.1 0.0 1.7 1.3 2.8 4.1 4.8 2.3 11.0 4.8 6.0 2.8 0.0 0.0 0.0 0.0 1.7 1.3 2.8 4.1 4.8 2.3 11.0 4.8 2.3 11.0 2.8 11.2 12.8 11.2 14.8 16.5 17.2 18.8 23.5 16.4 11.7 5.9 8.5 5.9 5.7 5.0 6.6 7.4 7.7 8.4 10.5 7.3 2.3 11.0 5.0 5.0 5.0 5.0 5.0 5.0 5.0 5.0 5.0 5 | | 4. | | | 2.9 | 5.0 | 6.0 | 2. | α | ຕຸ | 3.2 | 2.8 | 2.9 | 4.0 | 2.3- 2.7 | |
| 0.5 6.8 3.1 6.6 6.8 8.6 6.0 6.9 4.1 3.0 1.9 5.3 0.8 4.9 4.9 5.3 0.8 4.9 4.9 5.3 0.8 4.9 4.9 3.9 8.3 6.8 7.6 6.1 6.3 3.0 2.3 1.3 5.9 5.9 0.8 4.9 3.9 8.3 6.8 7.6 6.1 6.3 3.0 2.3 1.3 5.9 5.1 0.8 4.9 3.9 8.3 6.8 7.7 7.7 4.7 4.7 4.6 3.1 3.5 5.1 2.9 4.1 2.6 6.7 6.4 7.3 6.1 4.9 4.9 3.4 2.3 1.3 3.5 5.1 3.4 3.8 3.9 4.6 5.1 6.1 3.4 3.9 5.0 1.9 4.2 3.7 4.9 4.9 3.5 4.2 4.5 5.1 6.1 3.4 3.9 5.0 1.9 4.2 3.2 3.3 3.2 3.9 3.5 3.5 2.2 5.0 3.8 4.0 5.1 3.1 3.9 2.7 4.2 3.2 3.3 3.2 3.3 3.2 3.9 3.5 2.2 5.0 3.8 4.0 5.1 3.1 3.9 2.7 4.2 3.2 2.4 2.9 1.9 1.8 1.4 2.4 3.0 3.7 4.1 4.5 2.7 3.3 3.1 2.0 7.6 1.9 1.8 1.4 2.4 3.0 3.7 4.1 4.5 2.7 3.1 3.1 3.0 3.5 3.8 1.9 2.9 3.4 3.1 3.1 3.1 3.0 3.7 4.1 4.5 2.7 3.1 3.1 3.1 3.1 3.1 3.0 3.7 4.1 4.5 2.7 3.1 3.1 3.1 3.1 3.1 3.1 3.1 3.1 3.1 3.1 | | - | | | 3.2 | 6.5 | 6.7 | ထိ | 2.5 | 2.4 | 4.0 | 3.1 | 2.7 | 4.5 | 2.8- 3.1 | |
| 0.5 5.0 2.6 9.0 9.2 11.1 7.1 6.4 4.2 3.4 1.1 5.9 0.8 8.5 10.4 6.3 6.8 3.4 2.3 1.3 5.9 0.8 8.5 4.4 10.2 8.5 10.4 6.3 6.8 3.4 2.3 1.3 5.9 0.8 8.5 4.1 10.2 8.5 10.4 6.3 6.8 3.4 2.3 1.3 5.9 0.8 8.5 4.1 10.2 8.5 10.4 6.3 6.1 4.9 4.7 3.1 1.1 4.8 4.0 3.3 4.0 3.6 6.7 6.4 7.3 6.1 4.9 4.7 3.1 1.1 4.8 4.5 3.3 4.0 3.6 4.4 6.0 6.3 4.4 4.0 3.4 2.7 4.4 4.0 3.4 4.9 3.4 3.1 3.1 3.9 2.7 4.4 4.5 3.3 3.2 3.3 3.2 3.9 3.5 4.2 5.0 3.8 4.0 5.3 1.9 3.8 3.2 3.3 3.2 3.9 3.4 3.1 3.6 4.0 3.1 3.1 3.9 2.7 4.2 3.3 3.2 3.9 3.4 3.1 3.6 4.0 3.1 3.3 4.7 1.9 3.8 3.2 2.9 3.1 2.8 1.8 1.9 2.6 3.0 3.8 4.0 5.3 1.9 3.8 3.2 2.9 1.9 1.8 1.4 2.4 3.0 3.7 4.1 4.5 2.7 3.0 3.1 2.0 7.6 1.7 1.7 0.0 2.9 4.8 6.3 6.3 11.0 4.7 3.1 2.0 7.6 1.7 1.7 0.0 2.9 4.8 6.3 6.3 11.0 4.7 3.1 3.2 3.1 3.2 3.1 3.1 3.1 3.1 3.2 3.1 3.2 3.1 3.1 3.1 3.1 3.2 3.1 3.1 3.3 3.1 3.2 3.1 3.1 3.1 3.1 3.1 3.1 3.1 3.1 3.1 3.1 | | m) e | | | | 9.9 | 9.9 | 9.8 | 9 | 6.9 | 4.1 | 3.0 | 1.9 | 5.3 | 3.2- 3.6 | |
| 0.8 8.5 4.4 10.2 8.5 10.4 6.3 6.8 3.4 2.3 1.3 5.9 0.8 4.9 3.9 8.3 6.8 7.6 6.1 5.3 3.0 2.3 0.8 4.8 1.3 4.1 2.6 6.7 6.4 7.3 6.1 4.9 4.7 3.1 1.1 4.8 4.0 3.3 4.0 3.6 4.4 6.0 6.3 4.4 4.0 3.4 2.7 4.4 4.5 3.3 3.0 2.3 0.8 4.8 4.1 2.6 6.7 6.4 7.3 6.1 4.9 4.7 3.1 1.1 4.8 4.2 3.9 4.9 3.9 4.6 5.1 6.1 3.4 3.9 5.0 1.9 4.2 3.2 3.4 3.8 3.9 4.6 5.1 6.1 3.4 3.9 5.0 1.9 4.2 3.2 3.3 3.2 3.9 3.5 2.2 5.0 3.8 4.0 5.3 1.9 3.8 3.2 2.9 3.1 2.8 1.8 1.9 2.6 3.0 3.1 3.3 4.7 1.9 3.6 3.2 2.9 3.1 2.8 1.8 1.9 2.6 3.0 3.7 4.1 4.5 2.7 5.0 10.0 1.9 1.8 1.4 2.4 3.0 3.7 4.1 4.5 2.7 3.1 2.0 7.6 1.7 1.7 0.0 2.9 4.8 6.3 6.3 11.0 4.7 3.1 2.0 7.6 1.7 1.7 0.0 0.0 0.1 1.7 1.3 2.8 4.1 4.8 2.3 3.2 2.4 0.4 0.1 0.0 0.1 2.2 1.2 1.2 3.9 11.2 2.3 3.2 2.8 0.0 0.0 0.0 0.0 0.1 2.2 1.2 3.9 11.2 2.3 3.3 2.9 8.5 5.9 5.7 5.0 6.6 7.4 7.7 8.4 10.5 7.3 3.4 2.0 2.2 4 0.4 0.1 2.8 11.2 14.8 16.5 17.2 18.8 23.5 16.4 3.4 2.1 13.2 19.0 13.1 12.8 11.2 14.8 16.5 17.2 18.8 23.5 16.4 3.4 2.1 2.1 2.1 1.1 1.2 14.8 16.5 17.2 18.8 23.5 16.4 3.4 2.1 2.1 2.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 | | mī (| | | 5. 6 | 0°5 | 9.5 | 11.1 | 7.1 | 6.4 | 4.2 | 3.4 | 1:1 | 5,9 | 3.7- 4.0 | |
| $\begin{array}{cccccccccccccccccccccccccccccccccccc$ | • | ο, | | | 4.4 | 10.2 | ထ | 10.4 | 6,3 | 6.8 | 3.4 | 2,3 | 1.3 | 5,9 | 4.1- 4.5 | |
| 11.3 4.2 2.6 6.7 6.5 7.7 7.7 4.7 4.6 3.1 3.5 5.1 2.9 4.1 2.6 6.7 6.4 7.3 6.1 4.9 4.7 3.1 1.1 4.8 4.0 3.3 3.9 4.0 6.0 6.3 4.4 4.0 3.4 2.7 4.4 4.0 3.3 3.9 4.0 4.2 3.9 4.0 6.0 6.3 4.4 4.0 3.4 2.7 4.4 4.0 3.4 2.7 4.2 3.9 3.9 3.9 4.2 4.2 4.2 4.2 4.2 4.2 4.2 4.2 4.2 4.2 | | 1.5 | | | ۳ ص | | 9 | 7.6 | 6,1 | ວິ | 3.0 | 2,3 | 0.8 | 4.8 | 4.6- 4.9 | |
| 2.9 4.1 2.6 6.7 6.4 7.3 6.1 4.9 4.7 3.1 1.1 4.8 4.4 3.3 3.3 4.0 3.4 2.7 4.4 4.0 3.3 4.0 3.4 2.7 4.4 4.5 3.4 3.8 3.9 4.6 5.1 6.1 3.4 3.9 5.0 1.9 4.2 3.8 3.5 3.5 3.5 3.5 3.5 3.5 3.5 | | 6 | | | 2.6 | 6.7 | 6.5 | 7.7 | 7.7 | 4.7 | 4.6 | 3.1 | 3.5 | 5.1 | 5.0- 5.4 | |
| 4.0 3.3 4.0 3.6 4.4 6.0 6.3 4.4 4.0 3.4 2.7 4.4 4.5 3.4 3.8 3.9 4.6 5.1 6.1 3.4 3.9 5.0 1.9 4.2 3.7 4.9 4.9 3.5 4.2 4.5 5.1 6.1 3.4 3.9 5.0 1.9 4.2 3.2 3.3 3.2 3.9 3.5 2.2 5.0 3.8 4.0 5.3 1.9 3.8 3.8 3.2 2.9 3.1 3.3 3.3 4.7 1.9 3.8 3.2 2.9 3.1 2.8 1.8 1.4 2.4 3.0 3.7 4.1 4.5 2.7 3.2 2.9 3.1 2.8 1.8 1.4 2.4 3.0 3.7 4.1 4.5 2.7 3.1 3.3 4.5 5.7 13.6 3.5 3.1 0.1 4.2 8.7 8.7 9.7 13.9 2.9 3.1 2.0 7.6 1.7 1.7 0.0 2.9 4.8 6.3 6.3 11.0 4.7 8.6 0.2 2.4 0.4 0.1 0.0 0.0 0.1 7 1.3 2.8 4.1 4.8 2.3 11.0 4.7 1.3 2.8 4.1 4.8 2.3 11.0 4.7 1.3 2.8 4.1 4.8 2.3 11.0 4.7 1.3 2.8 4.1 4.8 2.3 11.0 4.7 1.3 2.8 4.1 4.8 2.3 11.2 1.3 2.8 4.1 4.8 2.3 11.2 2.3 11.2 1.3 2.8 4.1 4.8 2.3 11.2 2.3 11.2 1.3 2.8 4.1 4.8 2.3 11.2 2.3 11.2 1.3 2.8 4.1 4.8 2.3 11.2 2.3 11.2 1.3 2.8 4.1 4.8 2.3 11.2 2.3 11 | | 1.3 | | | 5.6 | 6.7 | 6.4 | 7.3 | 6.1 | 4.9 | 4.7 | 3.1 | 1:1 | 4.8 | 5.5- 5.8 | |
| 4.5 3.4 3.8 3.9 4.6 5.1 6.1 3.4 3.9 5.0 1.9 4.2 3.7 4.9 4.9 3.5 4.2 4.5 4.9 5.1 3.1 3.9 2.7 4.2 3.3 3.2 3.9 3.5 4.2 4.5 5.0 3.8 4.0 5.3 1.9 3.8 3.7 4.2 3.9 3.4 3.1 3.6 4.0 5.3 1.9 3.8 3.2 2.9 3.1 2.8 1.9 1.8 1.9 2.6 3.0 3.5 3.8 1.9 2.9 3.2 2.4 2.9 1.9 1.8 1.4 2.4 3.0 3.7 4.1 4.5 2.7 5.0 9.6 16.3 7.1 7.6 2.3 8.9 11.1 14.9 13.4 19.0 10.8 3.4 5.7 13.6 3.5 3.1 0.1 4.2 8.7 8.7 9.7 13.9 7.4 3.1 2.0 7.6 1.7 1.7 0.0 2.9 4.8 6.3 6.3 11.0 4.7 3.2 0.0 2.8 0.0 0.0 0.0 0.1 7 1.3 2.8 4.1 4.8 2.3 3.6 0.0 2.8 0.0 0.0 0.0 0.1 2.2 1.2 3.9 11.2 2.3 3.6 13.2 19.0 13.1 12.8 11.2 14.8 16.5 17.2 18.8 23.5 16.4 3.7 18.7 575.3 182.4 169.8 87.1 253.9 409.2 449.3 612.6 1127.5 432.3 3.6 82.7 100.0 99.9 100.0 99.6 99.9 87.5 76.7 88.9 67.8 89.4 3.7 1885 = 30 FEET 3.8 9.7 10.0 99.9 100.0 99.6 99.9 87.5 76.7 88.9 67.8 89.4 | | 1.7 | | | 4.0 | 3.6 | 4.4 | 6.0 | 6.3 | 4.4 | 4.0 | 3.4 | 2.7 | 4.4 | 5.9-6.3 | |
| 3.7 | | 1.5 | | | ۳ ش | 3.9 | 4.6 | 5.1 | 6.1 | 3.4 | 3,9 | 5.0 | 1.9 | 4.2 | 6.4- 6.7 | |
| 3.2 3.3 3.2 3.9 3.5 2.2 5.0 3.8 4.0 5.3 1.9 3.8 3.8 3.8 3.8 3.8 3.8 3.8 3.8 3.8 3.8 | | 1.9 | | | 4.9 | 3.5 | 4.2 | 4.5 | 4.9 | 5.1 | 3.1 | 3,9 | 2.7 | 4.2 | 6.8- 7.2 | |
| 3.7 | | 3.2 | | | 3.2 | 3,9 | 3.5 | 2.2 | 5.0 | 3,8 | 4.0 | ຕິ | 1.9 | 80 | 7.3- 7.6 | |
| 3.2 | | 3.0 | | | 3,9 | 3.4 | 3.1 | 3.6 | 4.0 | 3.1 | 33 | 4.7 | 1.9 | 3.6 | 7.7-8.0 | |
| 3.2 | 18.1-19.0 | 0. | | | 3.1 | 2.8 | ∞. | 1.9 | 2.6 | 3.0 | 3.5 | ထ | 1.9 | 2,9 | 8.1-8.5 | |
| 5.0 9.6 16.3 7.1 7.6 2.3 8.9 11.1 14.9 13.4 19.0 10.8 3.4 5.7 13.6 3.5 3.1 0.1 4.2 8.7 8.7 9.7 13.9 7.4 3.1 2.0 7.6 1.7 1.7 0.0 2.9 4.8 6.3 6.3 11.0 4.7 8.6 0.2 2.4 0.4 0.1 0.0 1.7 1.3 2.8 4.1 4.8 2.3 3.6 3.1 1.0 4.7 8.6 0.0 2.8 0.0 0.0 0.0 1.7 1.3 2.8 4.1 4.8 2.3 3.9 11.2 2.3 4.1 4.8 2.3 3.6 11.2 19.0 13.1 12.8 11.2 14.8 16.5 17.2 18.8 23.5 16.4 1.7 5.9 8.5 5.9 5.7 5.0 6.6 7.4 7.7 8.4 10.5 7.3 16.4 10.5 7.3 18.7 575.3 182.4 169.8 87.1 253.9 409.2 449.3 612.6 1127.5 432.3 5.6 82.7 100.0 99.9 100.0 99.6 99.9 87.5 76.7 88.9 67.8 89.4 18PS = 30 FEET = 89.4 | 19.1-20.0 | 1.7 | | | 2.9 | 1.9 | 1.8 | 1.4 | 2.4 | 3.0 | 3.7 | 4.1 | 4.5 | 2.7 | 8.6-8.9 | |
| 3.4 5.7 13.6 3.5 3.1 0.1 4.2 8.7 8.7 9.7 13.9 7.4 8.1 2.0 7.6 1.7 1.7 0.0 2.9 4.8 6.3 6.3 11.0 4.7 8.3 8.6 9.2 2.4 0.4 0.1 0.0 1.7 1.3 2.8 4.1 4.8 2.3 8.6 3 11.0 4.7 8.6 0.2 2.8 0.0 0.0 0.0 0.1 2.2 1.2 3.9 11.2 2.3 8.5 9.0 13.1 12.8 11.2 14.8 16.5 17.2 18.8 23.5 16.4 11.7 5.9 8.5 5.9 5.7 5.0 6.6 7.4 7.7 8.4 10.5 7.3 9.7 13.5 | 20.1-25.0 | 12.7 | | | 16,3 | 7.1 | 7.6 | 2.3 | 8,9 | 11.1 | 14.9 | 13.4 | 19.0 | 10.8 | 9.0-11.2 | |
| 3.1 2.0 7.6 1.7 1.7 0.0 2.9 4.8 6.3 6.3 11.0 4.7 8.6 0.2 2.4 0.4 0.1 0.0 1.7 1.3 2.8 4.1 4.8 2.3 3.6 3.3 3.5 0.0 0.2 2.4 0.4 0.1 0.0 1.7 1.3 2.8 4.1 4.8 2.3 3.6 0.0 2.8 0.0 0.0 0.0 0.1 2.2 1.2 3.9 11.2 2.3 3.6 11.2 2.3 3.9 11.2 3.9 11.2 2.3 3.9 11.2 2.3 3.9 11.2 2.3 3.9 11.2 2.3 3.9 11.2 2.3 3.9 11.2 2.3 3.9 11.2 2.3 3.9 11.2 2.3 3.9 11.2 2.3 3.9 11.2 2.3 3.9 11.2 2.3 3.9 11.2 2.3 3.9 11.2 2.3 3.9 11.2 2.3 3.9 11.2 2. | 25.1-30.0 | 16.6 | | | 13.6 | 3.5 | 3.1 | 0.1 | 4.2 | 8.7 | 8.7 | 9.7 | 13.9 | 7.4 | 11.3-13.4 | |
| 8.6 0.2 2.4 0.4 0.1 0.0 1.7 1.3 2.8 4.1 4.8 2.3 3.6 0.0 2.8 0.0 0.0 0.1 2.2 1.2 3.9 11.2 2.3 3.0 11.2 2.3 3.0 11.2 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2.3 3.0 11.2 2. | 30,1-35,0 | 6.6 | | | 7.6 | 1.7 | 1.7 | 0.0 | 2.9 | 4.8 | 6.3 | 6.3 | 11.0 | 4.7 | 13,5-15,6 | |
| 3.6 0.0 2.8 0.0 0.0 0.0 0.1 2.2 1.2 3.9 11.2 2.3 6.1 13.2 19.0 13.1 12.8 11.2 14.8 16.5 17.2 18.8 23.5 16.4 1.7 5.9 8.5 5.9 5.7 5.0 6.6 7.4 7.7 8.4 10.5 7.3 6.7 218.7 575.3 182.4 169.8 87.1 253.9 409.2 449.3 612.6 1127.5 432.3 6.8 82.7 100.0 99.9 100.0 99.6 99.9 87.5 76.7 88.9 67.8 89.4 6.8 89.4 6.9 99.4 69.5 67.8 89.4 67.8 69.4 67.8 69.4 67.8 67.8 67.8 67.8 67.8 67.8 67.8 67.8 | 35,1-40,0 | 9.1 | | | 2.4 | 0.4 | 0.1 | 0.0 | 1.7 | 1.3 | 2.8 | 4.1 | 4.8 | 2.3 | 15.7-17.9 | |
| 6.1 13.2 19.0 13.1 12.8 11.2 14.8 16.5 17.2 18.8 23.5 11.7 5.9 8.5 5.9 5.7 5.0 6.6 7.4 7.7 8.4 10.5 10.5 13.8 10.5 10.0 99.6 99.9 87.5 76.7 88.9 67.8 11.2 18.8 11.2 18.8 11.2 18.8 11.2 18.8 11.8 18.8 11.8 18.8 11.8 18.8 11.8 18.8 11.8 18.8 11.8 18.8 11.8 18.8 11.8 18.8 11.8 18.8 11.8 18.8 11.8 18.8 11.8 18.8 11.8 18.8 11.8 18.8 11.8 18.8 1 | ×40.0 | 6.9 | | | 2.8 | 0.0 | 0.0 | 0.0 | 0.1 | 2.2 | 1.2 | 3.9 | 11.2 | 2,3 | >17.9 | |
| 6.1 13.2 19.0 13.1 12.8 11.2 14.8 16.5 17.2 18.8 23.5 1.7 5.9 8.5 5.9 5.7 5.0 6.6 7.4 7.7 8.4 10.5 0.7 218.7 575.3 182.4 169.8 87.1 253.9 409.2 449.3 612.6 1127.5 5.6 82.7 100.0 99.9 100.0 99.6 99.9 87.5 76.7 88.9 67.8 IERS = 30 FEET 9076 = 89.4 | AVERACE | ; | ; | , | , | , | | | | | | | | | | |
| 1.7 5.9 8.5 5.9 5.7 5.0 6.6 7.4 7.7 8.4 10.5 0.7 218.7 575.3 182.4 169.8 87.1 253.9 409.2 449.3 612.6 1127.5 5.6 82.7 100.0 99.9 100.0 99.6 99.9 87.5 76.7 88.9 67.8 TERS = 30 FEET = 89.4 | SPEED (MPH) AVERAGE | 27.2 | 76.1 | 13.2 | 19.0 | 13.1 | 12.8 | 11.2 | 14.8 | 16.5 | 17.2 | 18.8 | 23.5 | 16.4 | | |
| 0.7 218.7 575.3 182.4 169.8 87.1 253.9 409.2 449.3 612.6 1127.5 5.6 82.7 100.0 99.9 100.0 99.6 99.9 87.5 76.7 88.9 67.8 IERS = 30 FEET 9076 = 89.4 | SPEED (M/SEC) | | 11.7 | 5,9 | 8.5 | 5.9 | 5.7 | 5.0 | 9.9 | 7.4 | 7.7 | 8.4 | 10.5 | 7.3 | | |
| 0.7 218.7 575.3 182.4 169.8 87.1 253.9 409.2 449.3 612.6 1127.5 5.6 82.7 100.0 99.9 100.0 99.6 99.9 87.5 76.7 88.9 67.8 TERS = 30 FEET 9076 = 89.4 | AVERAGE | | | | | | | | | | | | | | | |
| 5.6 82.7 100.0 99.9 100.0 99.6 99.9 87.5 76.7 88.9 67.8 TERS = 30 FEET 9076 = 89.4 | (CATTC/MX*2) | σ | 1 300 7 | 7 8 12 | 575 2 | 180 | 9 091 | 1 40 | 253.0 | 400 | 000 | . 2 6 13 | 107 | 5 | | |
| 5.6 82.7 100.0 99.9 100.0 99.6 99.9 87.5 76.7 88.9 67.8 IERS = 30 FEET 9076 = 89.4 | PERCENT DATA | • | 1.000 | 7.017 | 0,00 | 106.4 | 103.0 | 7. | 6.00 | 7-604 | 2.0 | 0.210 | C*/711 | 432.3 | | |
| ₩ 23 | RECOVERY | _ | 86.6 | 82.7 | 100.0 | 6.66 | 100.0 | 9.66 | 6.66 | 87.5 | 76.7 | 88.9 | 8.79 | 89.4 | | |
| 10 | ANDWOMETER HEI(| 6 = 1 5 | METERS | = 30 FI | 덡 | | | | | | | | | | | |
| | NUMBEK UF UBSEI PERCENTAGE DAT | WA!IUN | ERY = | 90/6 89.4 | | | | | | | | | | | | |

NGUMU XUFURS/SHOONO

Table IV - 65

Percentage Frequency Summary for Wind Speed GLACIER COUNTY - BLACKFOOT

(WINTER)

07/30/84 - 10/29/85

| | | _ | | | | | | | | | | | | | | | | | | | | | | | | | |
|----------------|----------|------------------|---------|-------------|------|------|-------|------|------|------|------|------|------|------|------|------|--------|------|--------|----------|----------|--------|------|--------|------|------|-------|
| | W | SPEED (M/SEC) | 10.5 | 10.2 | 10.0 | 10.2 | 10,3 | 6.6 | 10.8 | 11.4 | 12.1 | 12.4 | 12.3 | 13.2 | 11.4 | 11.0 | 11.0 | 10.3 | 10.2 | 6.6 | 9.5 | 9.6 | 9.4 | 10.1 | 10.8 | 10.8 | 10.7 |
| | AV | SPEED (APPE) | 23.6 | 22.9 | 22.3 | 22.9 | 23.0 | 22.2 | 24.2 | 25.5 | 27.2 | 27.7 | 27.6 | 29.6 | 25.6 | 24.5 | 24.7 | 22.9 | 22.9 | 22.2 | 21.3 | 21.5 | 21.1 | 22.5 | 24.1 | 24.2 | 23.9 |
| 0 0× | | >17.9 | 10.0 | 7.5 | 0.0 | 10.0 | 5.0 | 5,0 | 3.0 | 3.2 | 9.7 | 12.9 | 16.1 | 19.4 | 18,6 | 14.0 | & & | 8°.8 | 5,9 | 5,9 | 5,9 | ω ω | 6.1 | 9.1 | 11.1 | 7.7 | 8.8 |
| 35.1- | • | 15.7- 17.9 | 5.0 | 0.0 | 5.0 | 2.5 | 2.5 | 5.0 | 9.1 | 12.9 | 12.9 | 16.1 | 12.9 | 16.1 | 4.7 | 7.0 | 11.8 | 5.9 | 14.7 | α | α | 5.9 | 9.1 | ۰ ۳ | 11.1 | 3.8 | 7.8 |
| 30.1- | 3 | 13.5- 15.6 | 10.0 | 15.0 | 25.0 | 20.0 | 20.02 | 7.5 | 18.2 | 12.9 | 12.9 | 9.7 | 9.7 | 9.7 | 9.3 | 9,3 | 17.6 | 14.7 | 11.8 | 17.6 | 11.8 | 11.8 | 9.1 | 21.2 | 3.7 | 11.5 | 13.5 |
| 25.1- | 2 | 11.2- 13.4 | 20.0 | 25.0 | 15.0 | 7.5 | 12.5 | 12.5 | 9.1 | 29.0 | 19.4 | 19.4 | 16,1 | 9.7 | 14.0 | 7.0 | 8 | 8.8 | α 8 | 5,9 | 5,9 | 2.9 | 9.1 | 6.1 | 14.8 | 15.4 | 12.5 |
| 20.1- | 2.0 | 9.0- 11.2 | 12.5 | 10.0 | 12.5 | 17.5 | 20.0 | 27.5 | 30.3 | 7.6 | 16.1 | 12.9 | 16.1 | 25.8 | 18.6 | 23,3 | 11.8 | 17.6 | 11.8 | 17.6 | 20.6 | 14.7 | 12.1 | 6.1 | 7.4 | 15.4 | 16.4 |
| 18.1- | COND) | 8.1- 8.9 | 2,5 | 7.5 | 2.5 | 10.0 | 5.0 | 10.0 | 0.0 | 6.5 | 6.5 | 12.9 | 16.1 | 0.0 | 2.3 | 9,3 | 5,9 | 2.9 | 5,9 | 2.9 | 2.9 | α α | 6.1 | 6.1 | 18.5 | 11.5 | 9.9 |
| (MPH) 16.1- | · 🔟 | | | 7.5 | 7.5 | 2.5 | 7.5 | 2.5 | 3.0 | 6.5 | 6.5 | 3.2 | 0.0 | 0.0 | 4.7 | 2.3 | 17.6 | 11.8 | 0.0 | 2.9 | ω ω | 11.8 | 3.0 | 12.1 | 11.1 | 15.4 | 9.9 |
| SPEED 14.1- | \Box | | | 2.0 | 5.0 | 2.5 | 5.0 | 2.5 | 9.1 | 9.7 | 3.2 | 0.0 | 0.0 | 0.0 | 7.0 | 7.0 | 0.0 | 5.9 | 11.8 | 11.8 | 2.9 | 11.8 | 12.1 | 12.1 | 0.0 | 3.8 | 5.6 |
| VIND 12.1- | SPEC | 5.4- | 0.0 | 0.0 | 7.5 | 7.5 | 7.5 | 10.0 | 6.1 | 0.0 | 3.2 | 3.2 | 0.0 | 9.7 | 4.7 | 4.7 | 2.9 | 0.0 | 5,9 | 2.9 | 2.9 | 0.0 | 15.2 | 6.1 | 7.4 | 0.0 | 4.8 |
| 10.1- | NIM | 4.5- 5.4 | 7 | 2,5 | 2,5 | 2.5 | 0.0 | 2.5 | 0.0 | 0.0 | 3.2 | 3.2 | 3.2 | 0.0 | 0.0 | 4.7 | 0.0 | 5.9 | 2.9 | 2.9 | 5.9 | 2.9 | 0.0 | 3.0 | 3.7 | 0.0 | 2.3 |
| 8.1- | 10.0 | 3.6- | 7.5 | 0 | 50.0 | 5.0 | 2.5 | 0.0 | 0.0 | 3,2 | 3.2 | 0.0 | 0.0 | 6.5 | 2.3 | 0.0 | 0.0 | 5.9 | 2.9 | 2.9 | 5,9 | 8 | 0.0 | 3.0 | 0.0 | 7.7 | 3.0 |
| 6.1- | • | 2.7-3.6 | r. | 2,5 | 2,5 | 2.5 | 0.0 | 2.5 | 0.0 | 0.0 | 0.0 | 3.2 | 6.5 | 0.0 | 2.3 | 0.0 | 11.8 | 2.9 | 11.8 | 5.9 | 8.8 | 2.9 | 0.0 | 0.0 | 7.4 | 0.0 | 3.2 |
| 4.1- | 0.0 | 1.8- | ر بر | ָ ה ה | 5.0 | 5.0 | 7.5 | 7.5 | 12.1 | 6.5 | 0.0 | 0.0 | 0.0 | 3.2 | 4.7 | 7.0 | 0.0 | 2.9 | 0.0 | 2.9 | 5,9 | 5.9 | 12.1 | 6.1 | 0.0 | 7.7 | 4.7 |
| 2.1- | . | 0.9- | ر. د | 200 | 2,5 | 2.5 | 5.0 | 5.0 | 0.0 | 0.0 | 0.0 | 3.2 | 3.2 | 0.0 | 4.7 | 2,3 | 0.0 | 2.9 | 2.9 | 2.9 | 0.0 | 0.0 | 3.0 | 6.1 | 3,7 | 0.0 | 2.5 |
| 0.1- | 7.0 | 0.1- | 0 | , r | 2,5 | 2.5 | 0.0 | 0.0 | 0 | 0.0 | 3.2 | 0.0 | 0.0 | 0.0 | 2.3 | 2.3 | 2.9 | 2.9 | 2.9 | 5.9 | 2.9 | 2.9 | 3 | 0.0 | 0.0 | 0.0 | 1.8 |
| ā | E E | CALM | - | | 0 | 0 | 0.0 | 0 | 0 | 0.0 | 0.0 | 0 | 0.0 | 0.0 | 0.0 | 0.0 | 0 | 0.0 | 0.0 | 0.0 | 0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| | | | - | • | 1 m | 4 | · ru | 9 | 7 | ω | 6 | 10 | Π | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | ส | 22 | 2 | 24 | HOURS |

SOURCE: GEORESEARCH, INC.

ALL HOURS 0,0 1.8 2.5

0 \neg

Table IV - 66

Percentage Frequency Summary for Wind Speed GLACIER COUNTY - BLACKFOOT

(SPRING)

07/30/84 - 10/29/85

| | M IS | 0.1- | 2.1- | 4.1- | 6.1- | 8.1- | 10.1- 1 | WIND 12.1- 1 | SPEED [4,1-] | (MPH) 16.1-1 | 18.1- 7 | 20.1- 3 | 25.1- | 30.1- | 35.1- | 0 | | |
|-------------------|------|------|------|---------|------|------|---------|-----------------|-----------------|-----------------|---------|---------|---------|---------|-------|-------|-------|--------|
| | Š | 3 | • | • | • | | MIN | SPEEL | (MET | | | | | | • | 2 | A | A |
| | | 0.1- | -6.0 | 1.8- | 2.7- | 3.6- | 4.5- | 5.4- | 6.3- | | 8.1- | -0.6 | 11.2- | 13.5- 1 | 15.7- | | SPEED | SPEED |
| | CALM | 0.9 | 1.8 | 2.7 | 3.6 | | 5.4 | 6.3 | 7.2 | | 8.9 | | | | | >17.9 | (HE) | M/SEC) |
| - | 0.0 | 2.2 | 3,3 | 13.2 | 17.6 | 13.2 | 9.9 | 13.2 | 9.9 | 9.9 | 1.1 | 7.7 | 4.4 | 4.4 | 0.0 | 0.0 | 12.8 | 5.7 |
| 2 | 0.0 | 1.1 | 5.5 | 14.3 | 11.0 | 17.6 | | | 12.1 | | | 11.0 | 3,3 | 1.1 | 0.0 | 1.1 | 13.1 | 8 |
| m | 0.0 | 2.2 | 4.4 | 9.9 | 12.1 | 13.2 | | | 9.9 | | | 6.6 | 4.4 | 3,3 | 0.0 | 1.1 | 13.6 | 6,1 |
| 4 | 0.0 | 2.2 | 9.9 | 8.8 | 12.1 | 15.4 | | | 6.6 | | | 12.1 | 2.2 | 3,3 | 0.0 | 1.1 | 13.4 | 0.9 |
| 5 | 0.0 | 3,3 | 5.5 | 11.0 | 16.5 | 14.3 | | | 8.8 | | | α α | 4.4 | 2.2 | 0.0 | 1:1 | 12.7 | 5.7 |
| 9 | 0.0 | 3,3 | 7.7 | 12.1 | 7.7 | 15.4 | | | 2.2 | | | 9.9 | 3,3 | 4 4 | 1.1 | 0.0 | 13.5 | 0.9 |
| _ | 0.0 | 1.2 | 6.0 | 10.7 | 10.7 | 16.7 | | | 9.0 | | | ω 3 | 0.9 | 3.6 | 1.2 | 1.2 | 13.8 | 6.2 |
| | 0.0 | 1.2 | 4.8 | 10.7 | 10.7 | 13.1 | | | 9.5 | | | 7.1 | 4.8 | 0.9 | 2.4 | 2.4 | 15.4 | 6.9 |
| 6 + | 0.0 | 2.4 | 1.2 | & .3 | 15.5 | 9.5 | | | 2.4 | | | 20.2 | 6.0 | 7.1 | 4.8 | 1.2 | 17.2 | 7.7 |
| 20 | 0.0 | 2.4 | 2.4 | 2.4 | 11.9 | 13.1 | | | 7.1 | | | 16.7 | ж Э | 6.0 | 3.6 | 2.4 | 17.7 | 7.9 |
| 0 11 | 0.0 | 1.2 | 1.2 | 9.5 | 3.6 | 13.1 | | | 11.9 | | | 15.5 | 9.5 | 9,5 | 0.0 | 2.4 | 17.8 | 8,0 |
| 12 | 0.0 | 1.2 | 0.0 | 4.8 | 9.5 | 11.9 | | | 3.6 | | | 17.9 | 10.7 | 7.1 | 1.2 | 1.2 | 18.1 | 8.1 |
| U 13 | 0.0 | 0.0 | 3,3 | 4,3 | 7.6 | 7.6 | | | 5.4 | | | 19.6 | 8.7 | 6.5 | 2.2 | 0.0 | 17.9 | 8.0 |
| | 0.0 | 0.0 | 3,3 | 7.6 | 5.4 | 6.5 | | | 9.7 | | | 22.8 | 6.5 | 6.5 | 1.1 | 1.1 | 18.0 | 8.1 |
| R 15 | 0.0 | 0.0 | 2.4 | 4.7 | 7.1 | 4.7 | | | 7.1 | | | 18.8 | 10.6 | 5.9 | 0.0 | 1.2 | 17.9 | 8.0 |
| 16 | 0.0 | 0.0 | 1.2 | 2.4 | 5,9 | 8.2 | | | 10.6 | | | 21.2 | 10.6 | 3.5 | 1.2 | 0.0 | 17.9 | 8.0 |
| 17 | 0.0 | 0.0 | 1.2 | 4.7 | 5.9 | 4.7 | | | 10.6 | | | 18.8 | 7.1 | 5.9 | 1.2 | 0.0 | 17.8 | 7.9 |
| 18 | 0.0 | 1.2 | 0.0 | 4.7 | 5.9 | 4.6 | | | 14.1 | | | 15,3 | 5. 9 | 2.4 | 1.2 | 0.0 | 16.4 | 7.3 |
| 19 | 0.0 | 0.0 | 1.2 | 3,5 | 8.2 | 16.5 | | | 8.2 | | | 11.8 | 2.4 | 2.4 | 0.0 | 0.0 | 14.6 | 6.5 |
| ຂ | 0.0 | 0.0 | 2.4 | 7.1 | 12.9 | 22.4 | | | 9.4 | | | 8.2 | 2.4 | 1.2 | 0.0 | 0.0 | 13.0 | 5,8 |
| 7 | 0.0 | 1.2 | 2.4 | 9.4 | 12.9 | 16.5 | | | 5,9 | | | 5,9 | 3,5 | 1.2 | 0.0 | 0.0 | 12.9 | 5.8 |
| 8 | 0.0 | 2.4 | 2.4 | 7.1 | 11.8 | 18.8 | | | 10.6 | | | 8.2 | 3,5 | 1.2 | 0.0 | 0.0 | 12.7 | 5.7 |
| ຊ | 0.0 | 0.0 | 2.4 | 12.0 | 15.7 | 21.7 | | | 10.8 | | | 9.6 | 2.4 | 2.4 | 1.2 | 0.0 | 13.1 | 5.9 |
| 24 | 0.0 | 0.0 | 4.9 | 12.3 | 11.1 | 17.3 | | | 7.4 | | | 6.6 | 2.5 | 3.7 | 0.0 | 0.0 | 13,3 | 5.9 |
| 1 HOURS | 0.0 | 1.2 | 3.2 | 8.2 | 10.4 | 13.3 | 10.3 | 8.2 | 8,1 | 7.3 | 5,3 | 13.1 | 5,5 | 4.2 | 0.9 | 0.7 | 15.2 | 6.8 |
| | | | | | | | | | | | | | | | | | | |

Table IV - 67

Percentage Frequency Summary for Wind Speed GLACIER COUNTY - BLACKFOOT

(SUMMER)

07/30/84 - 10/29/85

| | | 2 | 0.1- | 2.1- | 4.1- | 6.1- | 8.1- | 10.1- 1 | WIND | SPEED 14.1- 1 | (MPH) 6.1- 1 | 8.1- 2 | 20.1- | 25.1- 3 | 30.1- | 35,1- | 0.00 | | |
|----------|-------|--------|------|------|--------|--------|--------|---------|-------------|----------------------|-----------------|--------|---------|---------|----------|--------|-------|--------|---------|
| | | 5 5 | 7.0 | 4 | o o | o o | | NIM | S E | 10. (¥.) 10. (¥.) | | | - | 2.00 | 2 | ? | | AV | ₽ |
| | | | 0.1- | 9-0 | 1.8- | 2.7- | | 4.5- | 5.4- | 6,3- | | 8.1- | 0.6 | 11.2- | 13.5- | 15.7- | | SPEED | |
| | | Š | 0.0 | 1.8 | 2.7 | 3.6 | | 5.4 | 6.3 | 7.2 | | တ္ | 11.2 | 13,4 | 15.6 | 1/.9 | ۷./۱× | E E | ₹ ₹ |
| | - | 0.0 | 0.0 | 2.4 | 12.1 | 19.4 | 21.8 | 13.7 | 11.3 | 8.1 | 3.2 | 1.6 | 3.2 | 0.0 | 2.4 | 0.8 | 0.0 | 11.2 | 5.0 |
| | 7 | 0.0 | 0.0 | 2.4 | 14.5 | 21.0 | 21.8 | 15.3 | 10.5 | 5.6 | 3.2 | 1.6 | 2.4 | 0.0 | 8.0 | 0.0 | 0.8 | 10.6 | φ. |
| | m | 0.0 | 0.0 | 4.0 | 17.7 | 18.5 | 17.7 | 17.7 | 6.5 | 8. 1. | 4.0 | ۰ 8 | 2.4 | 8.0 | 1.6 | 0.0 | 0.0 | 10.6 | 4.7 |
| | 4 | 0.0 | 0.0 | 3.2 | 12.1 | 24.2 | 17.7 | 16.1 | 7.6 | 6.5 | 4.8 | 1.6 | 2.4 | 0.8 | 0.8 | 0.0 | 0.0 | 10.7 | 8 |
| | ເດ | 0.0 | 0.0 | 4.0 | 18.5 | 18.5 | 16.1 | 13.7 | 12.9 | 7.3 | 4.0 | о 8 | 2.4 | 0.8 | 0.0 | 0.8 | 0.0 | 10.4 | 4.7 |
| | 9 | 0.0 | 0.0 | 3.2 | 19.4 | 20.2 | 17.7 | 12.1 | 8. 1 | 10.5 | 0.8 | 1.6 | 5,6 | 0.0 | တ ထ | 0 | 0.0 | 10.5 | 7 |
| | _ | 0.0 | 0.8 | 1.6 | 18.5 | 15.3 | 16.1 | 13.7 | 13.7 | 7.3 | 4. 8. | 0.0 | 3.2 | 3.2 | 0.8 | 0.8 | 0.0 | 11.4 | 2 |
| | ∞ | 0.0 | 0.0 | 0.0 | 12.9 | 16.1 | 16.1 | 14.5 | ۍ ه | 13.7 | 3.2 | 4.0 | 4.0 | 5.6 | 0.0 | 0 | 0.0 | 12.7 | 5.7 |
| = | 9 | 0.0 | 0.0 | 0.8 | 8.1 | 13.7 | 13.7 | 17.7 | 10.5 | 9.7 | 7.3 | 3.2 | 8.1 | 4.0 | 3.2 | 0.0 | 0.0 | 13.7 | 6.1 |
| | 10 | 0.0 | 0.0 | 0.0 | 8.1 | 11.3 | 13.7 | 11.3 | 20.2 | 8.1 | 6.5 | 4.0 | φ. • | 2.4 | 5.6 | 0.0 | 0.0 | 14.5 | 6.5 |
| 0 | 11 | 0.0 | 0.0 | 0.0 | 4.0 | 11.3 | 12.9 | 16.1 | 14.5 | 8°0 | 9.7 | 4.0 | 7.3 | 4.0 | 6,5 | 0.8 | 0.0 | 15,3 | φ. 8 |
| | 12 | 0.0 | 0.0 | 0.0 | 0.8 | 11.3 | 12.9 | 12.1 | 13.7 | 14.5 | 8.9 | 6.5 | 8,9 | 3.2 | 6.5 | ت 8 | 0.0 | 15.8 | 7.1 |
| _ | 13 | 0.0 | 0.0 | 0.0 | 1.6 | 9.6 | 13.6 | & & | 12.8 | 19.2 | 7.2 | 6.4 | 12.0 | 4.0 | 4.0 | 0.8 | 0.0 | 16.0 | 7.2 |
| | 14 | 0.0 | 0.0 | 0.0 | 1.6 | 8.0 | & & | 21.6 | 7.2 | 12.0 | 12.8 | 7.2 | 12.8 | 3.2 | 4.8 | 0.0 | 0.0 | 16.0 | 7.2 |
| ~ | 15 | 0.0 | 0.0 | 0.0 | 1.6 | 7.2 | & & | 11.2 | 12.0 | 12.0 | 16.0 | 6.4 | 14.4 | 4.0 | 6.4 | 0.0 | 0.0 | 16.7 | 7 |
| | 16 | 0.0 | 0.0 | 0.0 | 0.8 | 5.6 | 12.0 | 6.4 | 12.8 | 8.0 | 17.6 | 4.0 | 22.4 | 7.2 | 2.4 | 0 | 0.0 | 17.4 | ~ ' |
| | 17 | 0.0 | 0.0 | 0.0 | 1.6 | 5.6 | 12.0 | 6.4 | 14.4 | 9.6 | 13.6 | 12.0 | 16.8 | 5.0 | 1.6 | 0 | 0 | 16.9 | 2 |
| | 18 | 0.0 | 0.0 | 1.6 | 0.8 | 6.4 | 12.8 | 9.6 | 16.8 | 12.0 | 12.0 | 12.0 | 10.4 | 3.2 | ω Ο | 1.6 | 0 | 15.6 | 7.0 |
| | 19 | 0.0 | 0.0 | 0.0 | 4.8 | 4.0 | 14.4 | 21.6 | 14.4 | 10.4 | 12.0 | 7.2 | 9.6 | 0.0 | 1.6 | 0.0 | 0 | 14.2 | 6.4 |
| | 20 | 0.0 | 0.0 | 0.0 | 3.2 | 10.4 | 17.6 | 20.0 | 14.4 | 13.6 | 10.4 | 2.4 | 4.0 | 2.4 | <u>0</u> | 0.8 | 0.0 | 13.4 | 9 |
| | 7 | 0.0 | 0.0 | 0.8 | 2.4 | 14.4 | 22.4 | 12.8 | 20.0 | 10.4 | 4.8 | 5.6 | 4.0 | 0.8 | 1.6 | 0.0 | 0.0 | 12.8 | 5.7 |
| | 22 | 0.0 | 0.0 | 0.0 | 8.1 | 14.5 | 21.0 | 20.2 | 12.1 | 8°0 | 8.1 | 1.6 | 3.2 | 1.6 | 0.0 | 0.8 | 0.0 | 12.0 | 5.4 |
| | ສ | 0.0 | 0.0 | 0.8 | 10.6 | 17.9 | 25.2 | 13.0 | 11.4 | 8. 9. | 3,3 | 4.1 | 3,3 | 0.8 | 0.8 | 0.0 | 0 | 11.3 | 2 |
| | 24 | 0.0 | 0.0 | 0.8 | 12.2 | 17.9 | 29.3 | 12.2 | 2.7 | φ. 6. | 4.1 | 2.4 | 4.1 | 0.0 | 2.4 | 0.0 | 0.0 | 11.2 | 5 |
| ၌ | HOURS | 0.0 | 0.0 | 1.1 | 8.1 | 13.4 | 16.5 | 14.1 | 12.3 | 10.1 | 7.6 | 4.2 | 7.3 | 2.4 | 2.3 | 0.4 | 0.0 | 13.4 | 6.0 |
| | i | ; | | ! | | | | | | | | | | | | | | | |

Table IV - 68

Percentage Frequency Summary for Wind Speed GLACIER COUNTY - BLACKFOOT

(AUTUMN)

07/30/84 - 10/29/85

| | CALM | 0.1- | 2.1-4.0 | 4.1- 6.0 | 6.1- 8.0 | 8.1- 10.0 | 10.1- 1 12.0 | WIND 12.1- 1 14.0 | SPEED 14.1- 1 16.0 | (MPH) 16.1-1 18.0 | .8.1- 2 20.0 | 20.1- 2 25.0 | 25.1- 3 | 30,1- 3 35,0 | 35.1- 40.0 | >40.0 | | |
|-----------|------|--------|---------|-------------|-------------|--------------|-----------------|-------------------------|--------------------------|-------------------------|-----------------|-----------------|---------|-----------------|---------------|-------|------|--------|
| | | 0.1- | -6.0 | 1.8- | 2.7- | | VIN. | SPEEC 5.4- | (Æ∏- 6.3- | ပ | | | | | 5.7- | | SPED | S H |
| | CALM | 0.0 | 1.8 | 2.7 | 3.6 | | 5.4 | 6.3 | 7.2 | | 8.9 | 11.2 | | 15.6 | 17.9 | >17.9 | (ME) | |
| - | 0.0 | 1.5 | 5.2 | 8,9 | 5.9 | 13.3 | 8,9 | 10.4 | 7.4 | 8.1 | 5.9 | 13,3 | 4.4 | 3.7 | 1.5 | 1.5 | 15.5 | 6.9 |
| 2 | 0.0 | 1.5 | 5.2 | 0.6 | 10.4 | 6.7 | 11.2 | | 3.0 | | 7.5 | 13.4 | 3.0 | 2.2 | 2.2 | 3.7 | 15.7 | 7.0 |
| m · | 0.0 | 0.0 | 6.1 | 6.8 | 13.6 | ထီ | 9.1 | | 10,6 | | 5,3 | 12.1 | 4.5 | 2.3 | 1.5 | 8 | 15.7 | 7.0 |
| 4 | 0.0 | 0.8 | 5,3 | 7.6 | 13.7 | 6.9 | 6.9 | | 8.4 | | 4.6 | 11.5 | 4.6 | 3.1 | 3.8 | 1.5 | 15.8 | 7.1 |
| .C | 0.0 | 0 8 | 4.7 | 7.9 | 9.4 | 7.9 | 11.8 | | 10.2 | | 9.4 | 7.1 | ۍ ۳ | 7.9 | 1.6 | 1.6 | 16.0 | 7.2 |
| 9 | 0.0 | 2.4 | 3.2 | 5.6 | 12.0 | 12.0 | 10.4 | | 8.0 | | 8.0 | 12.8 | 1.6 | 4.0 | 1.6 | 4.0 | 15,9 | 7.1 |
| 7 | 0.0 | 1.7 | 5.1 | 7.7 | 10.3 | 5.1 | 14.5 | | 6. 8 | | 11.1 | 12.0 | 3.4 | 4.3 | 1.7 | 3.4 | 16.4 | 7.3 |
| œ | 0.0 | 1.7 | 6.9 | 7.8 | 6.0 | 14.7 | 5.2 | | 6.9 | | 5.2 | 17.2 | 0.9 | 0.9 | 3.4 | 1.7 | 16.8 | 7 |
| σ | 0.0 | 1.7 | 5.6 | 9.5 | 8.6 | 8.6 | 3.4 | | 5.6 | | 8.6 | 16.4 | 11.2 | 8.6 | 2.6 | 1.7 | 18.4 | 8 |
| 10 | 0.0 | 2.7 | 1.8 | 8 | 6.3 | 11.7 | 4.5 | | 5.4 | | 5.4 | 20.7 | 12.6 | 8.1 | 1.8 | 4.5 | 19.3 | 8 |
| Ξ | 0.0 | 0.0 | 2.8 | 3.7 | 5.6 | 12.0 | 6.5 | | 2.6 | | 11.1 | 16.7 | 10.2 | 11.1 | 3.7 | 2.8 | 20.3 | 9. |
| 12 | 0.0 | 1:0 | 1.0 | 1:0 | 3,9 | 13.6 | 8.7 | | 8.7 | | 2.9 | 16.5 | 12.6 | 11.7 | 3,9 | 1.9 | 20.3 | 9.1 |
| 13 | 0.0 | 1.5 | 0.0 | 3.7 | 6.0 | 9.0 | 7.5 | | 12.7 | | 3.0 | 16.4 | 7.5 | 15.7 | 3,7 | 1.5 | 19.9 | 8 |
| 14 | 0.0 | 1.5 | 0.7 | 3.7 | 6.7 | 6.7 | 6.7 | | 8.2 | | 7.5 | 16.4 | 11.2 | 7.6 | 3.7 | 2.2 | 19.9 | ထိ |
| 12 | 0.0 | 1.7 | 1.7 | 2.6 | 7.8 | 8.6 | 3.4 | | 9.5 | | 5.2 | 23.3 | 14.7 | 6.0 | 1.7 | 2.6 | 19.7 | 8 |
| 16 | 0.0 | 0. | 0.0 | 6.3 | 10.7 | 6.3 | 4.5 | | 8.0 | | 8,9 | 15.2 | 9.8 | 8.0 | 2.7 | 0.9 | 19.0 | 8 |
| 17 | 0.0 | 6.0 | 1.8 | 7.1 | 6,3 | 7.1 | 3,6 | | ထ | | 8.0 | 17.0 | 7.1 | 5.4 | 1.8 | 0.9 | 17.8 | α Ο |
| 18 | 0.0 | 6.0 | 5.4 | 3.6 | 6.3 | 7.2 | 0.6 | | 12.6 | | 5.4 | 18.9 | 8.1 | 3.6 | 0.0 | 1.8 | 16.7 | 7.5 |
| 19 | 0.0 | 8. | 2.7 | 6.4 | 1.8 | 7.3 | 10.9 | | 10.9 | | 7.3 | 16.4 | 7.3 | 2.7 | 1.8 | 0.0 | 16.6 | 7.4 |
| ଥ | 0.0 | 2.7 | 1.8 | ນໍ້ນ | 5.5 | 13.6 | 5.5 | | ນີ້ | | 3.6 | 19.1 | 5.5 | 4.5 | 1.8 | 0.0 | 16.2 | 7.2 |
| ಸ | 0.0 | 0.0 | 0.0 | 8.2 | 7.3 | 12.7 | 8,2 | | r S | | 8,2 | 13.6 | 1.8 | 4.5 | 2.7 | 0.0 | 16.0 | 7.2 |
| ឧ | 0.0 | 0.0 | 0.9 | 9,3 | 10.3 | 11.2 | 10.3 | | 11.2 | | 6.5 | 16.8 | 1.9 | 4.7 | 0.0 | 0.0 | 15.4 | 6.9 |
| ສ | 0.0 | 0.0 | 3.0 | 0.6 | 12.0 | 10.0 | 10.0 | | 10.0 | | 10.01 | 10.0 | 4.0 | 5.0 | 1.0 | 1.0 | 15.3 | 6.8 |
| 5¢ | 0.0 | 1:1 | 4.3 | 6.5 | 8.6 | 11.8 | 6.7 | | 6.5 | | 5.4 | 12.9 | 5,4 | 4,3 | 2.2 | 2.2 | 16.0 | 7.2 |
| ALL HOURS | 0.0 | 1.2 | 3.1 | 6.5 | 8.2 | 9.6 | 8.1 | 8.5 | 8.1 | 7.8 | 8.9 | 15.2 | 6.7 | 6.1 | 2.2 | 2.0 | 17.3 | 7.7 |
| | | | | | | | | | | | | | | | | | | |

Table IV - 69

Annual Wind Rose Distribution GLACIER COUNTY - BLACKFOOT

07/30/84 - 10/29/85

| 8 | () | NEMMO XMFMXN/NMCONO | | |
|--|---------|---|--|------------|
| <direction< td=""><td>(M/SEC)</td><td>4.0.0 4.0.0 6.0.1 6.0.4 6.</td><td>OTAL SPEED MPH) SPEED</td><td>(<u>)</u></td></direction<> | (M/SEC) | 4.0.0 4.0.0 6.0.1 6.0.4 6. | OTAL SPEED MPH) SPEED | (<u>)</u> |
| ⊕IO | SPEED | CALM 12.2.2.2.4.4.4.3.3.2.2.2.1.0.0.1-0.0.2.2.2.3.3.3.3.3.3.3.3.3.3.3.3.3.3.3. | 10 IAL AV SPEE (MPH) AV SPEE) | (M/S |
| TOTAL | ಶ | 001118484664444888889074790 6 | 100.0 16.1 | 7.2 |
| | | | | 2 |
| N | | | 3.9 | 5.5 |
| ₹ | | | 8°8 8°6 | 4.4 |
| ANA. | | | 2.4 9.6 | 4.3 |
| > | | | 13.5 15.2 | 6.8 |
| 35 | | 010222222222222222222222222222222222222 | | |
| ASM. | | | 25.3 20.1 | 0.6 |
| 3 | | 000000000000000000000000000000000000000 | 11.1 17.9 | 8.0 |
| SS | | 0.0000000000000000000000000000000000000 | 3.3 13.3 | 5.9 |
| S | | | 5.8 | 6.3 |
| SSE | | 00000000000000000000000000000000000000 | 9.6 | 0.6 |
| 뽔 | | 0.000000000000000000000000000000000000 | 6.4 | 7.9 |
| 161 | | | | |
| ESE | | 000000000000000000000000000000000000000 | 4.7 | 5.7 |
| ш | | | 3.2 9.1 | 4.1 |
| | | 0.0000000000000000000000000000000000000 | 1.1 | 3.6 |
| 쀨 | | | 1.3 9.8 | 4.4 |
| N | | | 1.6 9.4 | 4.2 |
| | | | | |
| Z | _ | 0.0000000000000000000000000000000000000 | 4.1 | 5.2 |
| N 0I | E E | - 1.0 - 2.0 - 3.0 - 3.0 - 3.0 - 1.0 - 1.0 | | |
| DIRECTION> | PEED | - ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' | TOTAL SPEED MPH) | (M/SEC) |
| 6 | Ŋ | 2011-1111-12-2-2-2-2-2-2-2-2-2-2-2-2-2-2 | A SPE (MPH) | (M/SEC) |




Table IV - 70

Coefficients of Weibull Distribution

GLACIER COUNTY - BLACKFOOT

07/30/84 - 10/29/85

| MONTH | SCALE FACTOR (C) (M/SEC) | SHAPE FACTOR (K) |
|---------------------------|--------------------------------|---------------------|
| UARY | 2,335 | .692 |
| RUARY | .064 | .318 |
| RCH | 6.271 | .725 |
| \blacksquare | 9,6212 | 1,9089 |
| | .542 | .405 |
| ш | .528 | . 275 |
| >- | .100 | .724 |
| 5 | .394 | .423 |
| FE | .423 | .916 |
| OBER | .587 | 50 |
| EMBE | .298 | .815 |
| E E | .452 | 9 / |
| AR | 7.3608 | 1.8587 |
| SOURCE: GEORESEARCH, INC. | INC. | |

CUT BANK GLACIER COUNTY

The Cut Bank site is located in a gently rolling area about 12 miles north of Cut Bank at 48 47 54 N and 112 19 37 W (Site No. 55 on Map II-1). Elevation at the site is 4,120 feet. This site was established by the Bureau of Reclamation as part of its Northern Great Plains Wind Energy Study. The Department of Natural Resources and Conservation assumed responsibility for the monitoring site in October 1982.

The site is on the Great Plains about 40 miles east of the Rocky Mountain Front and about 50 miles west of the Sweetgrass Hills. The land in the area is used predominantly for agriculture. While most of the land is privately owned, there are a few sections of state and federal land. The Blackfeet Indian Reservation lies a few miles to the west. Interstate Highway 15 runs near the site, and many county roads cross the area.

Electrical service in the Cut Bank area is provided by Glacier County Electric Cooperative. A 115-kV transmission line runs east-west through Cut Bank. The nearest commercial airport is at Cut Bank, approximately 15 miles to the south. Air traffic in the area generally is light.

Collection of wind data began on June 3, 1981, and continued through August 3, 1983. Data from the wind sensors were continuously recorded on cassette tape at the site. These tapes were further processed by computer to yield hourly averages of wind speed, wind direction, the average cube of the hourly speed, and standard deviation of the hourly speed. In addition, the maximum and minimum instantaneous values of wind speed during each hour were recorded. Anemometer height was 10 meters. A bushy wind break, house, and ranch buildings within 100 yards to the east and south of the site, as well as a bent and unbalanced wind vane shaft, make the wind direction data highly questionable.

Data recovery was fair to excellent, ranging from 43.3 percent in September to 100.0 percent in April. Overall data recovery for the period was 82.4 per-

Average monthly wind speeds at this site ranged from 10.5 miles per hour in August to 14.8 miles per hour in May. Average annual wind speed was 12.8 miles per hour.

Average monthly wind power ranged from 96.2 watts/m² in August to 306.3 watts/m² in January. Average annual wind power was 217.1 watts/m².

Average seasonal wind speeds were 12.2 miles per hour in summer, 12.3 miles per hour in autumn, 13.2 miles per hour in winter, and 13.5 miles per hour in spring. In winter, the highest average wind speeds occurred in midafternoon. In spring and autumn, the highest average wind speeds occurred in late afternoon, and in summer they occurred in early evening. The lowest average wind speeds occurred around 0500 to 0800 MST year round. The diurnal range of average wind speeds was greatest in summer and least in winter.

The most common wind directions were west, west-northwest, and south. Winds from the east and east-southeast were least common. By direction, average wind speeds ranged from 8.6 miles per hour for southwest winds to 15.8 miles per hour for westerly winds.




Table IV - 71

Monthly Wind Speed Distribution GLACIER COUNTY - CUT BANK

| | | CALM 0.1- 0.4 | 0.5-0.9 | 1.0-1.3 | 1.4- 1.8 | 1.9- 2.2 | 2.3- 2.7 | 2.8-3.1 | 3.2-3.6 | 3.7- 4.0 | 4.1-4.5 | 4.6- 4.9 | 5.0-5.4 | 5.5- 5.8 | 5.9-6.3 | 6.4- 6.7 | 6.8-7.2 | 7.3-7.6 (| 7.7-8.0 | 8.1-8.5 | 8.6-8.9 | 9.0-11.2 | 11.3-13.4 | 13.5-15.6 | 15.7-17.9 | >17.9 | | | | | | | |
|---------------------|---------|------------------|---------|------------|----------|----------|----------|---------|---------|----------|---------|----------|---------|----------|---------|----------|---------|-----------|---------|-----------|-----------|-----------|-----------|-----------|-----------|-------|---------|------------------------|---------------|-----------------------|---------------------------|-------|--|
| | YEAR | 0.5 | 1.5 | 2.1 | 3,8 | 4.2 | 9.0 | 5.5 | 6.7 | 5.2 | 6.7 | 4.7 | 6.4 | 4.8 | 5.1 | 4.1 | 3.6 | 4.2 | 2.9 | 3,3 | 2.1 | 8.7 | 4.3 | 2.0 | 0.7 | 0.5 | | 12.8 | 5.7 | | 217.1 | 82.4 | |
| | 33 | 0.0 | 2.5 | 2.4 | 3.5 | 4.0 | 6.5 | 5.8 | 6,3 | 4.0 | 6.9 | 4.4 | 7.5 | 4,3 | 5.0 | 3.1 | 3.5 | 3.7 | 2.4 | 3.1 | 1.6 | 8.5 | 4.7 | 3.0 | 1.4 | 1.2 | | 13.3 | 6.0 | | 291.3 | 6.66 | |
| | NO N | 2.8 | | 1.7 | 3,3 | 4.4 | 4.8 | 5.7 | 7.9 | 6.7 | 7.8 | 4.7 | 6.5 | 3.8 | 4.9 | 4.5 | 3.2 | 4.6 | 2.7 | 3.6 | 2.0 | ω | 3.4 | 6.0 | 0.2 | 0.1 | | 12.0 | 5.4 | | 167.3 | 7.36 | |
| | 0CT | 0.0 | 8.0 | 2.4 | 4.9 | 5,3 | 6.5 | 5.0 | 7.0 | 4.9 | 6.0 | 4.8 | 7.0 | 4.5 | 5.1 | 3.9 | 3.9 | 3,9 | 4.1 | 3,3 | 2.2 | 7.9 | 4.1 | 2.0 | 0.2 | 0.0 | | 12.5 | 5.6 | | 183.3 | 80.1 | |
| | SEP | 0.0 | 0.6 | 2.2 | 5.4 | 5.4 | 5.0 | 6.4 | 5.4 | 5.1 | 6.3 | 5.0 | 9.9 | 9.9 | 5.9 | 4.3 | 4.0 | 4.5 | 2.9 | 3.0 | 1.4 | 9,3 | 5.6 | 1,3 | 0.5 | 0.0 | | 12.3 | 5.5 | | 165.7 | 43.3 | |
| /03/83 | AUG | 0.0 | 1.9 | 2.5 | 5.0 | 5.8 | 7.7 | 6.8 | 9.6 | 6.5 | 8.0 | 3,9 | 6.3 | 4.5 | 4.5 | 4.2 | 2.9 | 4.8 | 5.6 | 5.6 | 1.7 | 6,3 | 0.7 | 0.0 | 0.0 | 0.0 | | 10.5 | 4.7 | | 2.96 | 71.4 | |
| 06/03/81 - 08/03/83 | JIF. | 0.0 | 0.2 | 1.0 | 3.2 | 4.0 | 6.7 | 7.1 | 7.5 | 9.9 | 7.7 | | 6.4 | 5.9 | 5.7 | 4.4 | 3.4 | 2.6 | 5.6 | ۳ ۳ | 2.1 | 8°3 | 2.8 | 1.5 | 0.4 | 0.8 | | 12,6 | 5.6 | | 184.2 | 64.6 | |
| 06/03 | 35 | 0.0 | 9.0 | 1.5 | 2.7 | 3.4 | 6.5 | 5,3 | 7.7 | 5.5 | 6.5 | 4.9 | 9.9 | 4.4 | 5.7 | 4.2 | 4.4 | 5.4 | 3,5 | 3.4 | 2.9 | 8.5 | 4.2 | 1.8 | 0.2 | 0.1 | | 13.1 | 5.8 | | 188.5 | 78.4 | |
| | ₩ | 0.0 | 0.2 | 9.0 | 2.0 | 2.2 | 4.8 | 3.7 | 6.5 | 8. | 5,0 | 4.8 | 6,5 | 4.7 | 5.9 | 4.8 | 4.7 | 5.7 | ж С | დ ლ | 3.0 | 12.4 | 5.7 | 2.8 | 1.2 | 0.1 | | 14.8 | 9.9 | | 264.9 | 79.1 | |
| | APR | 0.0 | 0.7 | 1.5 | 4.3 | 3.4 | 5.7 | 5.9 | 6.5 | 6.3 | 6.4 | 5.2 | 6.9 | ນີ້ | 5.2 | 4.2 | 2.4 | 3,5 | 2,3 | ۳, ش | 2.2 | 8,3 | 6.2 | 2,3 | 1.0 | 0.8 | | 13.5 | 6.0 | | 255.0 | 100.0 | |
| | MAR | 0.1 | 2.6 | 2.7 | 3.1 | 3,8 | 4.7 | 4.3 | 6.4 | 4.1 | 6.5 | 5.1 | 6.5 | 6,5 | 6,1 | 4.6 | 4.8 | 4.9 | 3.2 | 3.6 | 5.6 | 8 2 | 2.8 | 0.7 | 0.2 | 0.3 | | 12.4 | 5.6 | | 176.5 | 91.4 | |
| | FEB | 2.9 | 3.9 | 5.6 | 3.6 | 3.6 | 5,6 | 3.9 | 4.5 | 4.3 | 6.7 | დ ლ | 5.1 | 4,3 | 3,9 | 3.9 | 2.8 | 3.6 | 3.0 | 3.0 | 1.5 | 10.3 | 5,3 | 2.9 | 1.6 | 0.5 | | 12.9 | 5.8 | | 271.8 | 98.3 | |
| | JAN | 0.0 | 2 | m | 5,5 | 6.3 | 6.4 | 3.4 | 4.7 | 3 | 5.2 | 4.0 | 5,4 | 4.0 | 3,6 | 3.2 | 3.3 | 3.6 | 2.6 | 3.6 | 8: | 2 | 7.2 | 3.4 | | 1.3 | | 13.4 | 6.0 | | 306,3 | 9.66 | |
| | | CALM 0.1-1.0 | 1.1-2 | \$ 2.1-3.0 | 3.1-4 | 4.1-5 | | 6.1 | : | | 9 | 10.1-1 | 11.1-1 | 12.1-1 | 13,1-1 | 14.1-1 | 15.1-16 | 16.1-1 | 17.1-1 | 18.1-19.0 | 19.1-20.0 | 20.1-25.0 | 25.1-30.0 | 30,1-35,0 | 35.1-40.0 | >40.0 | AVERAGE | SPEED (MPH) AVERAGE | SPEED (M/SEC) | AVERAGE WIND POWER | (WATTS/M**2) PERCENT DATA | Ε¥ | |

ドミエミスタイションのNロ

ANEMOMETER HEIGHT = 10 METERS = 33 FEET NUMBER OF OBSERVATIONS = 15672 PERCENTAGE DATA RECOVERY = 82.4

Table IV - 72

Percentage Frequency Summary for Wind Speed GLACIER COUNTY - CUT BANK (WINTER)

06/03/81 - 08/03/83

| 2 | SPEED (N/SEC) | 5.8 | 5.4 | 5,3 | 5.3 | 2.2 | 5.1 | 5.1 | 5,3 | 5.5 | 5.7 | 2.7 | 6.1 | 6.7 | 7.2 | 7.3 | 7.1 | 8.9 | 6.3 | 6.2 | 5.9 | 5.9 | 5.7 | 5.6 | 5,9 |
|----------------------------------|------------------|------|------|------|----------|-------------|---------|---------|------|------|-------------|------|------|------|----------|------|------|------|------|--------|------|----------|------|------|---------|
| | SPEED (MPH.) | 13.0 | 12.1 | 11.8 | 11.7 | 11.7 | 11.5 | 11.5 | 11.8 | 12.2 | 12.7 | 12.8 | 13.7 | 15.1 | 16.1 | 16.4 | 15.8 | 15.1 | 14.1 | 13.8 | 13,3 | 13,3 | 12.9 | 12.6 | 13.2 |
| >40.0 | >17.9 | 1.7 | 1.1 | 1.1 | 1:1 | 9.0 | 0.6 | 9.0 | 9.0 | 0.0 | 0.0 | 0.6 | 0.0 | 1.7 | 2.2 | 1.7 | 1:1 | 9.0 | 0.0 | 0.6 | 1.7 | 0.0 | 9.0 | 0.0 | 0.8 |
| 30.1- 35.1- 35.0 40.0 | 15.7- 17.9 | 0.6 | 0.0 | 0.0 | 0.6 | 1:1 | 1.7 | 9.0 | 0.0 | 0.6 | 1.7 | 1:1 | 1.1 | 9.0 | 1.1 | 2.8 | 1.7 | 1:1 | 1.7 | 2.2 | 0.0 | 1.7 | 1.7 | 1.7 | 1.1 |
| | 13.5- 15.6 | 2,48 | 1.7 | 2.8 | 2.2 | 2.2 | 1.7 | 2.8 | 3,9 | 5.6 | 5.1 | 4.5 | 3,9 | 8,4 | 7.8 | 6.1 | 3,9 | 5.0 | 3,9 | 1.7 | 2.2 | 1:1 | 1:1 | 1.7 | 3.6 |
| 25.1- 30.0 | 11.2- 13.4 | 2.2 | 33 | 5.6 | m m | 2.2 | 1.7 | 3.4 | 3.9 | 3.4 | 4.5 | 5.7 | 8.4 | 7,3 | ο. Θ. | 4.5 | 7.8 | 6.1 | 3.9 | 3.4 | 2.8 | 3.4 | 5.1 | 3.4 | 4.5 |
| 20.1- 25.0 | 9.0- 11.2 | 10.6 | 9 | 5.0 | α 3.3 | 7.2 | 6.1 | 4.5 | 7.3 | 7.9 | 10.2 | 10.2 | 12.3 | 11.2 | 14.5 | 21.2 | 18.4 | 15.1 | 10.6 | 8 | 9.5 | 11.2 | 7.9 | 9.0 | 10,3 |
| 18.1- 20.0 | , | 6.7 | 6.7 | 2.8 | 1.7 | 2.8 | 3.4 | 3°0 | 3.9 | 6.2 | 4.0 | 6,3 | 4.5 | 5.6 | 3.4 | 5.0 | 7.8 | 6.7 | 5.0 | 5.0 | 7.3 | 5.6 | 3,4 | 6.2 | 4.9 |
| (MPH) 16.1- 18.0 ERS/SE | 7.2- 8.0 | 7.2 | 2 | 4.4 | 3,3 | 6. 7 | 7.3 | 7.9 | 7.9 | 3.4 | 4.5 | 4.5 | 5.0 | 5.0 | 6.1 | 6.7 | 5.6 | 7.3 | 6.7 | 8 6 | 5.6 | α, 4. | 11.2 | 5.1 | 6.2 |
| SPEED 14.1- 16.0 | 6.3- 7.2 | 8.3 | 5.0 | 7.8 | 6.1 | 8.9 | 6.1 | გ. • | 2.8 | 5.6 | 4.5 | 3.4 | 5.6 | 7.3 | 6.7 | 5.6 | 6.1 | 6.1 | 10.6 | 9,5 | 7.8 | 7.8 | 7.9 | 7.9 | 9.9 |
| WIND 12.1- 14.0 | 5.4- 6.3 | 6.1 | 6.7 | 10.6 | 11.7 | 7.8 | 7.8 | ω. | 7.3 | 6.8 | 4.5 | 6.8 | 6.7 | 7.8 | 3.9 | 5.6 | 7.3 | 8.4 | 10.1 | 12.8 | 13.4 | 11.7 | 7.9 | 10.2 | 8.4 |
| 10.1- 1 12.0 | 4.5- 5.4 | 8.3 | 12.2 | 10.0 | 10.6 | 10.6 | 13.4 | 12.9 | 8.4 | 9.6 | 10.7 | 5.7 | 8.4 | 6.7 | 12.3 | 9.5 | 7.3 | 10.6 | 11.2 | 12.3 | 11.2 | 10.1 | 11.8 | 11.9 | 10.1 |
| 8.1- 10.0 | 3.6- | 13.9 | 14.4 | 9.4 | 11.1 | 8°.0 | 14.5 | 11.2 | 17.4 | 9.6 | 10.2 | 11.4 | 7.3 | 6.1 | 6.1 | 4.5 | 9.5 | 8.4 | 15.6 | 10.1 | 12.3 | 10.1 | 10.1 | 7.9 | 10.3 |
| 6.1- 8.0 | 2.7- 3.6 | 7.8 | 6.7 | 9.4 | 12.8 | 12.2 | 10.1 | 11.8 | 7.9 | 9.6 | 14.7 | 6.7 | 7.3 | 6.7 | 6,1 | 8.0 | 6.7 | 8.9 | 7.8 | 10.6 | 10.1 | 6.7 | 9.6 | 11.9 | 9.6 |
| 4.1- 6.0 | 1.8-2.7 | 8,3 | 12.2 | 17.8 | 13.3 | 14.4 | 11.7 | 15.2 | 11.2 | 16.9 | 9.6 | 10.8 | 15.1 | 15.6 | 10.1 | 7.8 | 7.8 | 8.4 | 4.5 | 6.1 | 6.1 | 11.2 | 7.9 | 10.7 | 10.9 |
| 2.1- 4.0 | 0.9- | 10.0 | 8 | 6.7 | 7.2 | ۍ ه | 10.1 | 7.9 | 10.7 | 7.9 | 7.3 | 12.5 | 7.8 | 5.0 | 5.6 | 2.8 | 4.5 | 5.0 | 4.5 | 3,9 | 5.6 | 5.0 | 8.4 | 6.8 | 7.2 |
| 0.1-2.0 | 0.1- | 4.4 | 4.4 | 5.6 | 5.6 | 5.0 | ۳. ا | 5.1 | 5.6 | 5.1 | 6. 2 | 5,1 | 5.0 | 2.8 | 3.4 | 6.1 | 3,9 | 1.7 | 3.4 | 3.4 | 4.5 | 5.6 | 5.1 | 4.5 | 4.5 |
| САЦМ | CALM | 1:1 | 1.7 | 1:1 | 1:1 | 9.0 | 9.0 | 9.0 | 1:1 | 1.7 | 2.3 | 1.7 | 1:1 | 2.2 | 1.7 | 1:1 | 9.0 | 9.0 | 9.0 | 9.0 | 0.0 | 0.0 | 0.0 | 1:1 | 1.0 |
| | | ~ | ı m | 4 | ស | 9 | _ | œ | 6 | 10 | I | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 77 | ដ | 23 | 24 | HOURS |
| | | | | | | | | | × | | 0 | | > | | œ | | | | | | | | | | AL T |

Table IV - 73

Percentage Frequency Summary for Wind Speed GLACIER COUNTY - CUT BANK (SPRING)

06/03/81 - 08/03/83

| | | A | SPEED | 4/SEC) | 5.6 | 5.5 | 5,5 | 5.2 | 4.9 | 4.7 | 4.6 | 4.7 | 5.1 | 5.7 | 6.4 | 6.7 | 6.8 | 7.1 | 7.2 | 7.2 | 7.2 | 7.3 | 7.1 | 6.8 | 6.3 | 6.0 | 5.8 | 5.7 |
|------|---------------|--------|---------|--------|------|------|------|------|------|------|------|------------|------|------|--------|-------------|----------|----------|------------|------|------|------|------|------|----------|------|--------|-----------|
| | | AV | SPEED : | (MPH) | 12.6 | 12.2 | 12.3 | 11.7 | 10.9 | 10.6 | 10.2 | 10.6 | 11.3 | 12.8 | 14.2 | 15.0 | 15.3 | 15.8 | 16.0 | 16.1 | 16.0 | 16.2 | 15.9 | 12.1 | 14.0 | 13.4 | 12.9 | 12.8 |
| | >40 n | | | >17.9 | 0.0 | | | | | | | | | | | | | | | | | | | | | | | • |
| | 35.1- | | 15.7- | | 0.0 | 0.0 | 1.2 | 9.0 | 0.0 | 0.0 | 0.0 | 0.0 | 9.0 | 9.0 | 0.0 | 1.2 | 1.8 | 1.8 | 2.4 | 9.0 | 1.2 | 1.8 | 0.0 | 9.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| | 30.1- | | 13.5- | 15.6 | 1.8 | 1.2 | 9.0 | 1.8 | 0.0 | 0.0 | 0.6 | 9.0 | 1.8 | 1.2 | 2.4 | 1.2 | 3.6 | 3.0 | 3.0 | 4.8 | 4.2 | 5.4 | 4.8 | 4.3 | 1.8 | 9.0 | 1.8 | 1.8 |
| | 25.1- | | 11.2- | 13.4 | 2.4 | 2.4 | 3.6 | 2.4 | | 2.4 | 3.0 | ٠ <u>.</u> | 1.8 | 2.4 | 6.1 | r, | 4.8 | 5.4 | 9.9 | 6.0 | 7.2 | 4.2 | 7.8 | 3.0 | 3.0 | 3.7 | 0.0 | 9.0 |
| | 20.1- | | 9.0- | 11.2 | 6.0 | 7.2 | 7.8 | 9.9 | 5.4 | 1.8 | 9.0 | 3.0 | 7.8 | 13,9 | 13,3 | 13.9 | 10.8 | 15.0 | 12.6 | 16.8 | 17.4 | 22.8 | 16.9 | 16.5 | 11.0 | 11.0 | 6.1 | 13,4 |
| _ | 18.1- | (ONO) | 8.1- | 8.9 | 7.8 | 4.8 | 4.8 | 4.8 | 6.0 | 6.6 | 1.2 | 5,4 | 2.4 | ນ້ຳ | 6.1 | 5,5 | 8.4 | 3.0 | 9.0 | 6.0 | 0.6 | 7.2 | 8.4 | 7.3 | 8 | 5.5 | 9.1 | 4.3 |
| (FE) | 16,1- 18,0 | ERS/SE | 7.2- | 8.0 | 10.8 | 0.6 | 6.0 | 5.4 | 7.2 | 5.4 | 9.6 | 4.8 | 9.9 | 6.1 | 8 5 | 7.9 | 7.8 | 7.2 | 9.6 | 7.8 | 6.0 | 6.0 | 7.8 | 7.3 | 10.4 | 6.1 | 11.0 | 6.7 |
| | 14.1- 16.0 | 0 | _ | | 10.2 | 10.8 | 6.0 | 8.4 | 3.6 | 12.0 | 0.6 | 4.2 | 6.0 | 4.8 | 9.1 | 12.1 | 7.8 | 12.6 | 6.0 | 9.9 | 4.2 | 9.9 | 6.0 | 10.4 | & 6 | 12.8 | 6 8 | 12.2 |
| MINC | 12.1- | ◒ | | | 7.2 | 9.6 | 13,3 | 13.9 | 10.2 | 10.8 | 6.0 | 12.7 | 10.2 | 12.1 | 8.5 | 13.3 | 17.4 | 10.2 | 10.8 | 9.6 | 11.4 | 0.6 | 9.6 | 13.4 | 12.8 | 11.6 | 17.1 | 10.4 |
| | 10.1- | Ē | 4.5- | 5.4 | 13.9 | 9.6 | 11.4 | 7.8 | 12.7 | 7.8 | 12.0 | 13,3 | 12.7 | 13.3 | 13.9 | 10.9 | 13.8 | 13.8 | 13.8 | 12.0 | 7.2 | 8.4 | 10.2 | 8 | 12.8 | 16.5 | 10.4 | 12.8 |
| | 8.1- 0.01 | | 3.6- | 4.5 | 12.0 | 15.7 | 11.4 | 13.9 | 11.4 | 8,4 | 13.9 | 15.7 | 13.9 | 12.7 | 9.7 | 9.1 | 9.9 | α. 4. | 10.2 | 7.8 | 10.8 | 9.6 | 9.6 | 10.4 | 13.4 | 12.8 | 14.6 | 12.2 |
| | 6.1- | 5 | 2.7- | 3.6 | 12.7 | 12.0 | 14.5 | 11.4 | 17.5 | 17.5 | 21.7 | 12.0 | 13.3 | 9.1 | 9 | 8.5 | 9.9 | 9.0 | 5.4 | 10.8 | 12.0 | 0.6 | 10.2 | 8 | 6.7 | 9.1 | 9.1 | 11.6 |
| | 4.1- | • | 1.8- | 2.7 | 10.2 | 12.0 | 12.0 | 9.6 | 12.7 | 15,7 | 8.4 | 13.9 | 9.6 | 8.5 | 7.3 | 4.2 | 4.8 | 5.4 | 7.2 | 7.2 | 7.8 | 9.9 | 4.2 | 2.4 | 6.1 | 6.7 | 6.7 | 9.1 |
| | 2.1- | | -6.0 | | 3.6 | 4.2 | 5.4 | 10.2 | 8.4 | 8.4 | 10.2 | 7.8 | 9.6 | 7.3 | 4.8 | 4.2 | 4.2 | 2.4 | 1.2 | 9.0 | 9.0 | 3.0 | 1.8 | 4.3 | 1.8 | 0°° | 4.3 | 4.3 |
| | 0.1- | i | 0.1- | 0.9 | 1.2 | Ö | | m | ٥i | m | m | ന് | m | ₹. | ij | . -i | ٠. | ᅼ | <u>.</u> : | ij | oʻ | o | ∾ | o | ≓ | o | oʻ | o. |
| | A IA | • | | SAG | 0.0 | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | - | 2 | m | 4 | ഹ | 9 | 7 | œ | 6. | 10 | == | 12 | 13 | 74 | 15 | 16 | 17 | 18 | 19 | ଯ | Z | 8 | ន | 54 |
| | | | | | | | | | | | | | I | | 0 | | - | | œ | | | | | | | | | |

SOURCE: GEORESEARCH, INC.

ALL HOURS 0.0 1.7 4.8

6.0

0.3 13.5

9.0

2.2

3.7

6.1 10.7

8.4 7.5

8.3 11.2 11.4 11.7 11.3

Table IV - 74

Percentage Frequency Summary for Wind Speed

GLACIER COUNTY - CUT BANK (SUMMER)

06/03/81 - 08/03/83

| NA NA | SPEED (M/SEC) | 4.9 | 4.4 v. w. | 4.1 | 4.2 | 4.c | 2.0 | 5.8 | 6.1 | 6.4 | 6.5 | 9.9 | 0.7 | 6.0 | 6.9 | 4.0 | 5.7 | 5.4 | 5.0 | 5.5 |
|-------------------------|------------------|----------------------|---------------|--------------|----------|-------------|------|------|--------------|--------------|------|------|------------|----------|----------|--------|------|------|------|-----------|
| W | SPEED (MPH)(| 10.9 | 9.6 | 9.2 | 9,5 | 10.2 | 12.4 | 12.9 | 13.6 | 14.3 | 14.5 | 14.8 | 15.0 | 15.5 | 15.5 | 14.4 | 12.7 | 12.0 | 11.2 | 12.2 |
| >40.0 | >17.9 | 0000 | 0.0 | 0.0 | 0.0 | 000 | 0 | 0.0 | 0 0 | 9.0 | 0.6 | 1:1 | 1.1 | 9.0 | 9.0 | 9.0 | 0.0 | 0.0 | 0.0 | 0.3 |
| 35.1- 40.0 | 15.7- 17.9 | 000 | 0.0 | 0.0 | 0.0 | 000 | 0.0 | 0.0 | | 0.0 | 1:1 | 0.0 | 0.0 | 0.0 | 0.0 | 9.0 | 0.0 | 0.0 | 0.0 | 0.2 |
| 30.1- 35.0 | 13.5- 15.6 | 0.6 | 0.0 | 0.0 | 0.0 | 0.0 | 2.9 | 2.9 | ۳°، د | , 4. 0.7. | 2.8 | 4.0 | ! ! | 1 7 | 1.7 | 9.0 | 9.0 | 0.6 | 0.0 | 1.3 |
| 25.1- 30.0 | 11.2- 13.4 | 0.0 | 1.1 | 0.0 | 0.0 | 1.7 | 3 | 3.5 | ω, π 4. + | 4.5 | 4.5 | 2.3 | 4 6 | 4.0 | χ, 4. | 0.6 | 1:1 | 0.0 | :: | 2.1 |
| 20.1- 25.0 | 9.0- 11.2 | 1.7 | 2.8 | 4.5 | 5.1 | 9 6 | 9.7 | 9.8 | 10.2 | 13.6 | 12.5 | 13,7 | 1/./ | 17.7 | 8 9 | 13.7 | 9.1 | 3,4 | 2,3 | 8.5 |
| 18.1- 20.0 | ļ | 3.45 | 2.3 | 2.8 | 4.0 | ب 4 د | 4 | 5.8 | တ္ က | 7.4 | 5.7 | 7.4 | 9 | ο . « | 9,1 | ထိ | 4.6 | 5.7 | 5.7 | 5.5 |
| (MPH) 16.1- 18.0 | 7.2-8.0 | 6.8 10.2 5.1 | 4.0 | 6.3 | 6,3 | . c | 7.4 | 5.2 | 7.4 | 4.0 | 6.3 | 5.1 | 7. | 12.6 | 12.0 | 12.6 | 6,3 | 12.0 | 7.5 | 7.3 |
| SPEED 14.1- 16.0 | 6.3- 7.2 | 11.4 8.0 8.5 | 8.0 | 5.7 4.5 | 4.5 | 6,3 | 5.7 | 9.8 | ο c | | 7.4 | 12.6 | 6 | 10.9 | 8,0 | ω ω | 9.7 | 7.4 | 12.6 | 7.9 |
| WIND 12.1- 1 14.0 | 5.4- 6.3 | 11.9 | , 0 8 0 | ര് വ | 8,5 | 8,5 2,5 | 6.7 | 9.2 | 6,3 | 9.7 | 13.6 | 10.9 | 12.6 | 0°, | 12.6 | 13.7 | 15.4 | 16.6 | 10.9 | 10.3 |
| 10.1- 1 12.0 WIND | 4.5- 5.4 | 11.4 16.5 11.9 | 11.9 | 8.0 13.1 | 9.7 | 9,4 | 7.4 | 9,8 | 13.1 | 9.7 | 10.8 | 12.6 | / 6 | 13.1 | 10.9 | 14.9 | 16.0 | 14.9 | 12.1 | 11.4 |
| 8.1- 10.0 | | 17.0 15.9 19.9 | 14.8 | 13.1 11.4 | 10.2 | 12.5 | 16.0 | 12.7 | 11.9 | 3.7 10.2 | 14.2 | 13.1 | 13./ | 6 | 10.3 | 14.3 | 17.1 | 13.1 | 18.4 | 13.4 |
| 6.1- 8.0 | 2.7- | 21.0 17.6 15.9 | 21.6 | 17.6 19.3 | 15,9 | 14.2 | 15.4 | 12.1 | 13.1 | 14.8 | 10.2 | 11.4 | 11.4 | ο Ο | 9 | 6,3 | 12.6 | 13.7 | 13.8 | 14.5 |
| 4.1- 6.0 | 1.8-2.7 | 9.1 12.5 15.3 | 11.4 14.8 | 18.8 15.9 | 14.8 | 18.8 2.8 | 10.3 | 15.0 | 10.8 | 12.5 | 9.7 | 4.0 | 4.0 | 5.1 | 5.1 | 4.0 | 4.6 | 10,3 | 8.6 | 11.1 |
| 2.1- 4.0 | 0.9- | 3.44 7.7 | 10.2 8.5 | 14.2 | 17.6 | 10.8 8.0 | | 4.0 | 4.0 | 1:1 | 9.0 | 1.7 | 0.0 | 9.0 | 9.0 | 1:/ | 2.3 | 1.7 | 5.7 | 5.3 |
| 0.1-2.0 | 0.1- | 0.6 | 2,3 | 3.4 | 2.8 | 2,3 | | | | 0.0 | | | | | | | | 0.0 | 1:1 | 1.0 |
| CALM | CALM | 0000 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| | | 126 | 4 տ | 9 / | ∞ | و 5 | 2 = | 12 | ឌន | 15 | 16 | 11 | 81 | 19 | 25 | 7 | 23 | 8 | 24 | ALL HOURS |
| | | | | | | I | 0 | | > | œ | | | | | | | | | | ALL ! |

Table IV - 75

Percentage Frequency Summary for Wind Speed GLACIER COUNTY - CUT BANK (AUTUMN)

06/03/81 - 08/03/83

| | | Α | SPEE | (M/SE | 4.8 | 4.8 | 4.7 | 4.8 | 4.6 | 4.5 | 4.5 | 4.6 | 4.7 | 4.6 | 4.8 | 5,6 | 6.2 | 6.7 | 7.0 | 7.2 | 7.2 | 7.0 | 6.6 | 5,9 | 5.6 | 5.2 | 5.0 | 4.9 | 5.5 |
|----------|-------|------------------------------|-------|-------------|------|------|------|---------|------|---------|-------------|----------|-------------|------|--------|--------|----------|------|------|-------------|-------------|------|------|------|------|---------|--------|--------|-----------|
| | | ΑV | SPEED | Œ H H | 10.8 | 10.7 | 10.6 | 10.7 | 10.2 | 10.1 | 10.1 | 10.3 | 10.5 | 10.2 | 10.8 | 12.4 | 13.8 | 14.9 | 15.7 | 16.1 | 16.1 | 15.6 | 14.7 | 13.3 | 12.4 | 11.7 | 11,1 | 11.1 | 12.3 |
| | | >40.0 | | >17.9 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.7 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| | 35.1- | 40.0 | 15.7- | 17.9 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.7 | 0.7 | 0.7 | 0.7 | 0.7 | 0.0 | 0.7 | 0.0 | 0.0 | 0.0 | 0.0 | 0.2 |
| | 30.1- | 35.0 | 13,5- | 15.6 | 0.0 | 0.0 | 0.0 | 0.0 | 0.8 | 0.0 | 0.0 | 0.0 | 0.8 | 0.8 | 0.8 | 0.0 | 2.2 | 0.9 | 3.7 | 7.5 | 0.9 | 2.2 | 3.0 | 0.7 | 0.0 | 0.0 | 0.0 | 0.0 | 1.4 |
| | 25.1- | 30.0 | | | 0.0 | 0.0 | 0.7 | 2,3 | 1.5 | 1.5 | 2.3 | 1.5 | 8.0 | 8.0 | 1.5 | დ ო | 6.0 | 2.2 | 0.6 | 4.5 | 9 | 8.2 | 4.5 | 4.5 | 3.0 | 0.0 | 0.8 | 0.0 | 2.7 |
| | 20.1- | 25.0 | 9.0- | 11.2 | 7.5 | 4.5 | 3.0 | 9.0 | 3.0 | 3.0 | 4.5 | 9.1 | 6.1 | 8,3 | 8° | 16.7 | 13,4 | 15.7 | 11.2 | 17.2 | 16.4 | 13.4 | 14.2 | 6.7 | တို့ | 0.6 | 4.5 | 6,1 | 9.1 |
| | 18.1- | 20.0 0.00 0.00 0.00 | 8.1- | 8 9 | 2.2 | 0.9 | 7.5 | 1.5 | 3.0 | 3.0 | 3.0 | 3.0 | 7.6 | 3.8 | 3.0 | 5,3 | 8.2 | 9.7 | 7.5 | 5.2 | 7.5 | 0.6 | 8,2 | 4.5 | 5,3 | 2.3 | 7.5 | 3° | 5.3 |
| ₹ | 16.1- | 18.0 ERS/SE | 7.2- | 8.0 | 6.7 | 0.9 | 0.6 | 7.5 | 6.1 | 6.1 | 7.6 | 4.5 | 6. 8 | 6.1 | 7.6 | 8.3 | 7.5 | 0.6 | 7.5 | 7.5 | 0.6 | 0.6 | 0.6 | 10.4 | 7.5 | œ. 3 | 6.0 | 9.1 | 7.6 |
| SPEED | 14.1- | 16.0 (MET | 6.3- | 7.2 | 8.2 | 2.5 | 4.5 | 5,3 | 6.8 | 11.4 | 5 | 9.1 | 4.5 | 3.8 | ლ ლ | 5,3 | 4.5 | 6,0 | 11.2 | 0.6 | 10.4 | 12.7 | 9.7 | 11.9 | 12.8 | 7.5 | , 3 | 7.6 | 7.9 |
| | | 14.0 5 SPEE | | | | | | | | | | | | | | | | | 11.2 | | | | | | | | | | 9.8 |
| | 10.1- | 12.0 VIN | 4.5- | 5.4 | 10.4 | 17.2 | 14.9 | ۳. ش | 15.2 | 13.6 | 7. 6 | 9.1 | 6.8 | 12,9 | 9.1 | 6.1 | 13.4 | 9.0 | 7.5 | 7.5 | 6.7 | 10.4 | 11.9 | 12,7 | 15.0 | 20.3 | 16.5 | 13.6 | 11.5 |
| | 8.1- | 10.0 | 3.6- | 4.5 | 17.9 | 12.7 | 16.4 | 15.0 | 16.7 | φ, 0 | 13.6 | 13.6 | 7.6 | 12.1 | 11.4 | 10.6 | 6.0 | 12.7 | 11.2 | 7.5 | 0. | 6.0 | 9.7 | 15.7 | 15.0 | 15.0 | 17.3 | 20.5 | 12.6 |
| | 6.1- | & O | 2.7- | 3.6 | 14.2 | 15.7 | 13.4 | 16.5 | 13.6 | 16.7 | 18.2 | 14.4 | 22.0 | 10.6 | 10,6 | 14.4 | 13.4 | 6.7 | 7.6 | 0. 9 | 6. 7 | 4.5 | 5,2 | 0.0 | 15.0 | 18.8 | 12.0 | 13.6 | 12.6 |
| | 4.1- | 0.9 | 1.8- | 2.7 | 13.4 | 11.2 | 10.4 | 14.3 | 15.2 | 14.4 | 13.6 | 18.2 | 15.9 | 13.6 | 16.7 | 12.9 | 0.6 | 8.2 | 5.2 | 5.2 | 4.5 | 5.2 | 8.2 | 6.0 | ຕູ | 6.0 | 7.5 | & 6 | 10.4 |
| | 2.1- | 4.0 | -6.0 | 1.8 | 4.5 | 6.7 | 6.7 | œ ۳ | 9.1 | 12.1 | 10.6 | ۰ 8 | დ ო | 15.2 | 11,4 | 7.6 | 6.7 | 3.7 | 2.2 | 3.7 | 3.0 | 4.5 | 2.2 | 3.0 | 1.5 | | 7.5 | 4.5 | 6.4 |
| | 0.1- | 2.0 | 0.1- | 6.0 | 2.2 | 1.5 | 4.5 | 1.5 | 0.8 | 0.8 | 2,3 | 1.5 | 3.0 | 3.0 | 2,3 | 1.5 | 0.0 | 0.0 | 0.0 | 0.0 | 0.7 | 0.7 | 0.0 | 0.0 | 0.0 | 0 | 0 | 8.0 | 1.2 |
| | : | CALM | | CALM | 0.7 | 0.7 | 0.7 | 0.8 | 0.8 | 0 | & O | 0 | 0.8 | 0.8 | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 | | :2 | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 | 1.2 |
| | | | | | | 2 | m | 4 | S | 9 | _ | ∞ | 6 | 10 | Ξ | 12 | 2 | 14 | 15 | 16 | 17 | 18 | 19 | ଥ | 7 | 23 | ន | 54 | ALL HOURS |
| | | | | | | | | | | | | | I | | 0 | | - | | ~ | | | | | | | | | | ALL ! |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Table IV - 76

Annual Wind Rose Distribution GLACIER COUNTY - CUT BANK

06/03/81 - 08/03/83

| ØIRECTION | SPEED (M/SEC) | 0.1- 0.4 0.5- 0.9 | ۳. | | 7.7 | ,, | | 4.0 | 4.5 | 4.9 | ٠. 4 | | 6.3 | 6.7 | 7.2 | 7.6 | ω Ο | က် | ۍ ش | 11.2 | | | | >17.9 | CALM | TOTAL AV COEED | (MDH.) | (M/SEC) |
|------------------|---------------|----------------------|---------|---------|---------|------------|------------------------|-----|-----|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-----------|-----------|-----------|-----------|-------|------|-------------------|----------|---------|
| TOTAL | S | 0.6 | | | | | | | | | | | | | | | | | | | | | | | 0.5 | 100.0 | 12.8 | 5.7 |
| Ī | | 0.0 | 0 | 0.5 | 2.0 | יי ס כ | 0 | 0.4 | 0.4 | 0 | 0. | 0.2 | 0 | 0.7 | 0 | 0 | 0.1 | 5 | 0 | | 0 | | 0 | 0 | | 4.6 | 11.5 | 5.1 |
| ₹ | | 0.0 | 0.5 | ٠, س | 4.0 | 4.4 | 9.0 | 0.5 | 0.4 | 0 | 0.5 | 4.0 | 0.4 | 0.3 | 0.0 | 4.0 | 0.2 | ۳. 0 | 0.2 | 0. | 9 0 | 7.0 | 0.1 | 0.1 | | 8,3 | 14.0 | 6.3 |
| Ĭ | | 0.0 | 0.3 | 0.3 | 4. | 2,0 | 9.0 | 0.5 | 9.0 | 0.4 | 9.0 | 4.0 | 0.5 | 0.5 | 0.4 | 4.0 | 0.3 | 4.0 | 0.3 | 1.3 | 0.7 | ٥,٠ | 0.1 | 0.0 | | 10.5 | 14.3 | 6.4 |
| 3 | | 0.0 | 0.1 | e 9 | 4.0 | ه د د د | 9 | 0.4 | 9.0 | 4.0 | 0.0 | 4.0 | 0.5 | ۰° | 0.3 | 0 | 0.4 | 0.5 | 0 | 1.5 | 6.0 | ٠ - | 0.2 | 0.1 | | 11.5 | 15.8 | 7.1 |
| 155 | | 0.0 | e 0 | 0.5 | 4.0 | | 200 | 0.3 | 0.3 | 0.2 | 0.3 | 0,3 | 2.0 | 0.2 | 0.1 | 0.2 | 0.2 | 0.2 | 0.5 | 0.7 | 4.0 | 7.0 | 0.1 | 0.1 | | 7.0 | 13.3 | 0.9 |
| 3 | | 0.1 | 0.2 | 0.5 | 4 0 | 0 0 | , c | 0.3 | 0.4 | 0.0 | ۳ . | 0.2 | 0.2 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | | 0.0 | 0 | 0.0 | 0.0 | | 5,3 | 8.6 | 3.8 |
| SSW | | 0.1 | 0.2 | 0.3 | ۰. م | ດ້າ | , c | 0.3 | 0.5 | 0.3 | 0.4 | 0.2 | 0.3 | 0.2 | 0.1 | 0.1 | 0.0 | 0.0 | 0.0 | 0.1 | 0.0 | ٠ ٠ | 0.0 | 0.0 | | 5,3 | 8. 8. | 3.9 |
| S | | 0.1 | 0.2 | 0.4 | ۳. 0 | ດ້າ | + v | 0.5 | 0.8 | 0.5 | 0 | 0.6 | 0.5 | 0.4 | 0.3 | 0.4 | 0.5 | 0.3 | 0.1 | 0.0 | 4.0 | 7.0 | 0.1 | 0.0 | | 9.6 | 12.4 | 5.6 |
| SSE | | 0.0 | 0.1 | 0.1 | 0.2 | 2 0 | ۰ ر د | 0.3 | 0.5 | 0.4 | 0.0 | 0.6 | 0.5 | 0.5 | 0.3 | 0.4 | 0.3 | 0.3 | 0.2 | 0.7 | 0.2 | 7.0 | 0.1 | 0.0 | | 7.2 | 14.3 | 6.4 |
| SE | | 0.0 | 0.1 | 0.2 | 0.2 | ۳. د | - r | 0.3 | 0.3 | 0.2 | 0.5 | 0.2 | 0.3 | 0.2 | 0.1 | 0.2 | 0.1 | 0.1 | 0.0 | 0.3 | 0.2 | 0.1 | 0.0 | 0.0 | | 4.1 | 12.4 | 5.6 |
| ESE | | 0.0 | 0.1 | 0.2 | 0.2 | ۳ c | 200 | 0.1 | 0.2 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.0 | 0.0 | 0. | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 2.4 | 9.2 | 4.1 |
| ш | | 0.0 | 0.1 | 0.2 | 0.2 | ۍ 0 د | 7 0 | 0.2 | 0.2 | 0.1 | 0.2 | 0.2 | 0.2 | 0.2 | 0.1 | 0.1 | 0.0 | 0.1 | 0.0 | 0.1 | 0.0 | 0.0 | 0.0 | 0.0 | | 3.1 | 8.6 | 4.4 |
| ENE | | 0.0 | 0.0 | 0.2 | 0.2 | ۳° ۵ | 7.0 | | 0.4 | 0,3 | 0.4 | 0.3 | 0.3 | 0.2 | 0.2 | 0,3 | 0.1 | 0.1 | 0.1 | 0,3 | 0.1 | 0.0 | 0.0 | 0.0 | | 4.7 | 11.7 | 5.2 |
| 뀔 | | 0.0 | 0.1 | 0.1 | 0.2 | 2.0 | າຕ | 0.2 | 0.4 | 0.4 | 0.5 | 0.4 | ۳° 0 | 0,3 | 0.4 | 0.3 | 0.2 | 0.3 | 0.1 | 0.4 | 0.2 | 0.1 | 0.0 | 0.0 | | 2,6 | 13.3 | 5.9 |
| N N N | | 0.0 | 0.1 | 0.1 | 0.1 | 2.0 | 7.0 | 0.2 | 0.3 | 0.3 | 0.3 | 0,3 | 0,3 | 0.3 | 0.2 | 0,3 | 0.2 | 0.3 | 0.2 | 0.7 | 0,3 | 0.0 | 0.0 | 0.0 | | 5.2 | 14.5 | 6.5 |
| z | | 0.0 | | | | | | | | | | | | | | | | | | | | | | | | 5.0 | 12.6 | 5.6 |
| DIRECTION> | SPEED (MPH) | 0.1-1.0 | 2.1-3.0 | | | | г 0.1- /.0 г 71- яо | | | M 10.1-11.0 | I 11.1-12.0 | L 12.1-13.0 | E 13.1-14.0 | S 14.1-15.0 | / 15.1-16.0 | H 16.1-17.0 | 0 17.1-18.0 | U 18.1-19.0 | R 19.1-20.0 | 20.1-25.0 | 25.1-30.0 | 30.1-35.0 | 35.1-40.0 | >40.0 | САГМ | TOTAL | (MPH) | (M/SEC) |




Table IV - 64

Coefficients of Weibull Distribution

GLACIER COUNTY - CUT BANK

06/03/81 - 08/03/83

| | SCALE | SHAPE |
|----------|-----------------------|------------|
| MONTH | FACTOR (C) (M/SEC) | FACTOR (K) |
| JANUARY | .592 | 00 |
| FEBRUARY | .771 | 81 |
| MARCH | .351 | 74 |
| APRIL | 6,1606 | 1.8728 |
| MAY | .109 | .080 |
| JUNE | .266 | .979 |
| JULY | 069. | .069 |
| AUGUST | .146 | 876 |
| - | .015 | 90 |
| | .028 | 9 1 |
| NOVEMBER | .888 | 52 |
| ~ | .175 | 8 |
| YEAR | 6.1787 | 1.8271 |

CUT BANK FAA AIRPORT

GLACIER COUNTY

The Cut Bank airport is located about 5 miles south-southwest of Cut Bank at 48 36 00 N and 112 22 12 W (Site No. 56 on Map II-1). Elevation at the airport is 3,852 feet. Meteorological data have been collected at this site for many years by the Federal Aviation Administration.

Cut Bank is on the Great Plains about 40 miles east of the Rocky Mountain Front and about 50 miles west of the Sweetgrass Hills. The land around Cut Bank is used predominantly for agriculture. Most of the land is privately owned, although a few sections are owned by the state and federal governments. The Blackfeet Indian Reservation lies a few miles to the west. Interstate Highway 15 runs near the site, and many county roads cross the area.

Electrical service in the area is provided by Glacier County Electric Cooperative. A 115-kV transmission line runs east-west through Cut Bank. The nearest other commercial airport is at Shelby, approximately 25 miles to the east. Air traffic in the area is generally light.

Data for the site, collected primarily for aviation and weather forecasting uses, consist of short-term (5 minutes or less) averages of wind speed and wind direction, as well as other meteorological parameters. Data are gathered once per hour. The data have been analyzed by Battelle Pacific Northwest Laboratories. Because of a change in anemometer height, the data set was split into two parts for analysis: November 22, 1949, through October 3, 1959; and October 4, 1959, through December 31, 1978. Only data from the latter period were selected for inclusion in the *Montana Wind Energy Atlas*.

The data set for Cut Bank consists of summaries of observations made every third hour. The anemometer was mounted on a ground mast at a height of 6.1 meters. Data from the site are representative of a large portion of north-central Montana.

Average monthly wind speeds ranged from 10.3 miles per hour in July to 13.9 miles per hour in December and January. Average annual wind speed

Average monthly wind power varied from 118.0 watts/m² in July to 328.0 watts/m² in January. Average annual wind power was 228.0 watts/m².

Average seasonal wind speeds were 10.9 miles per hour in summer, 12.5 miles per hour in autumn, 13.0 miles per hour in spring, and 13.8 miles per hour in winter.

The highest average wind speeds occurred in mid-afternoon during all seasons except summer, when they occurred in late afternoon. The lowest average wind speeds occurred in early morning during all seasons. The diurnal range of average wind speeds was greatest in summer and least in winter.

The most common wind directions at this site were west-southwest and west. Winds from the east-northeast and south-southwest were least common. By direction, average wind speeds ranged from 8.1 miles per hour for winds from the northeast, east, and southeast, to 18.6 miles per hour for winds from the west-southwest. The highest average wind speeds were associated with winds from the prevailing wind directions.




Table IV - 78

Monthly Wind Speed Distribution

GLACIER COUNTY - CUT BANK FAA AIRPORT

10/04/59 - 12/31/78

| | | _ | | s | _ | ш | ш | ۵ | | Σ | LLI | _ | ш | ~ | S | _ | S | ш | O | 0 | ~ | _ | | | | | | | | | |
|---|-------------|--------------|----------|----------|-------------|--------------|--------------|--------------|----------|----------|-----|---------------|----------|------------|--------------|----------------|----------|----------|-------------|----------|----------------|----------|-------------|----------|---|--------------|----------|-----|--------------|----------|-------------------------|
| | | 0.5 | | | | | | | | | | | | | | | | | | | | | | + | + | _ | + | | | | |
| | | _ | _ | N | r | 4 | 5 | 9 | ~ | ω | 9 | 9 | _ | 2 | 3 | ₫ | 5 | 9 | \succeq | 8 | 9 | Ö | 5 | 0 | Ñ | 7.01 | Ö | | | | |
| | | ALM | 7 | 5 | 5 | 5 | 7 | 7 | 7 | 7 | 7 | ŗ | 7 | 7 | 7 | 7 | 5 | <u>*</u> | 7 | 7 | 5 | 5.0 | 5-2 | 5 | 5-3 | 5-4 | | | | | |
| | | Ö | o | <u>.</u> | ď | m | 4 | 'n | Ó | ۲. | φ. | o, | 10 | Ξ. | 12 | 13. | <u>+</u> | 5 | 16. | 17. | 18. | 19. | 20. | 25. | 30. | 35. | | | | | |
| | YEAR | m | 0 | ۵ | a | 0 | _ | N | m | ~ | 0 | n | <u>~</u> | 6 | _ | 9 | 9 | _ | ٥ | N | 0 | 0 | _ | 0 | 0 | 0 | 0 | | 5 | 9 | 0 |
| | ₹ | | • | • | • | • | ٠ | | • | • | • | • | ٠ | | | | • | | | | | | | | | 0 | | | 2 | 5. | 228.0 |
| | O | ~ | <u>+</u> | | 7 | _+ | <u>.</u> | S | m | m | _ | _ | ~ | ı۸ | 7 | | C) | ۸, | | - | _ | Δ. | _ | _ | _ | 0 | _ | | _ | • | |
| | DEC | | | | | | | | | | | - | | | | | | _ | _ | _ | | | - | | | 0 | | | 3.9 | 6.2 | 4.0 |
| | | • | _ | _ | <u>.</u> | _ | | _ | | | _ | | _ | _ | _ | ٠. | | | | | | | | | | _ | _ | | _ | | 324. |
| | ⋛ | | | | • | | | • | | • | | • | | | | | | | • | • | | | | | | 0.0 | | | 3.0 | 5.8 | 258.0 |
| | | | | | _ | _ | _ | | | | | | | | | | | | | | | | | | | | | | _ | | 25 |
| | OCT | • | ٠ | • | • | • | • | • | • | • | | • | • | • | • | • | | | | | • | • | | | | 0.0 | | | 3.2 | 5.9 | 3.0 |
| | | | | | _ | - | * | | | | | | | | | _ | | _ | _ | | | | _ | | _ | _ | _ | | - | | 23 |
| | SEP | | | • | | | • | | • | | | | | | | | | | | | • | | | | | 0.0 | | | 1.2 | 5.0 | 0:0 |
| | •• | • | | • | 7 | - | - | ٠. | • | • | - 1 | ., | • | • | _ | _ | _ | _ | _ | _ | _ | _ | _ | _ | _ | ٠. | _ | | Ξ | ш | 156 |
| | AUG | • | | • | • | • | • | | | • | | • | | | • | | | | • | | | | | | | 0 | | | 5 | .7 | 0. |
| | Q. | - | 0 | 10 | 1 | 18 | 12 | ς, | Φ | o | עט | N | _ | 0 | 0 | 0 | 0 | 0 | 0 | O | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 10 | 寸 | 121 |
| | 700 | • | | • | • | • | | • | • | • | | • | • | | | | • | • | • | • | | | | | | 0 | | | ۳. | 9. | 0. |
| | 7 | 9 | 0 | 0 | <u>~</u> | 3 | 7 | & | 9 | 7 | ⇉ | C) | _ | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 10 | -1 | 118 |
| | N O O | Ŋ | φ. | 9. | ٥ | œ. | 9 | 0. | ت | Ņ | ؈ | ო. | 0 | m | → | ت | ~ | _ | 0 | - | 0 | 0 | 0 | 0 | 0 | 0, | 9 | | 0 | m | .0 |
| | 5 | ß | 0 | œ | ⇉ | S | 2 | \circ | ~ | œ | 9 | ⇉ | αį | <u>, -</u> | | 0 | o | 0 | Ö | Ö | Ö | Ö | Ó | Ö | Ö | o (| o | | Ξ. | 5. | 175. |
| | > | 'n | œ | ω | က | ~ | 7 | _ | ~ | _ | œ | ر ا | 9 | œ | 7 | 7 | | c۷ | _ | _ | 0 | 0 | 0 | 0 | 0 | 0 (| 0 | | 8 | 7 | |
| | ¥Α | | Ö | ø | 12. | 5. | 12. | 10. | ω. | ထ | ۲- | 'n | N | ÷. | Ë. | o | o. | o. | o. | 0 | 0 | 0 | o. | 0 | Ö | o · | · | | 12. | 5. | 209.0 |
| | A H | 9. | _ | ဆ | က | 9 | , | ~ | 9 | _ | 6 | _ | 0 | _ | æ | m | ~ | CI. | Q | _ | 0 | 0 | _ | 0 | 0 | 0 | 0 | | 2 | 6 | |
| | ₹ | η, | ċ | ø. | Ξ. | 13. | 7 | 10. | φ. | φ. | ۲. | r, | " | ς. | . | <u>.</u> | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | Ö | 0 | | | 13. | δ. | 244.0 |
| | × | 9 | ۸ı | 7 | ,- - | S. | αı | 0 | 0 | _ | ī | m | _+ | ~ | _ | _ | _ | Δı | ۸ı | ۸ı | _ | _ | _ | _ | _ | _ | _ | | در | ~ | |
| | MAR | | | | | | | | | | | | | | | | | | | | | | | | | 0, | | | 3. | 5.9 | 263.0 |
| | en en | - | _ | | ` | · _ | ` | ۸. | ~~ | | _ | _ | | | | | _ | | | | | ٠. | | _ | _ | | _ | | _ | | |
| į | 1 | 6.4 | | | | | | | | | | | | | | | | | | | | | | | | | | | 3.6 | 6.1 | 3.0 |
| | | | | | _ | _ | | | | | | | | | | | | | | | | | | | | | | | _ | | 303 |
| : | AAN | 6.8 | | 9.0 | ۲.٦ | 9.0 | 9.7 | 0.8 | 6.7 | 7.7 | 7.7 | 9 | 3.5 | 3.2 | 2.9 | 7 . | | 0.3 | † .0 | 5.5 | | | 2.2 | 0.0 | 0.0 | 0.0 | | | 3.9 | 6.2 | 3.0 |
| | | | | - | • | _ | • | | _ | | | _ | | | | | | _ | _ | _ | _ | _ | _ | _ | _ | • | _ | | - | | 328 |
| | | - | ~ | 7 | 9. | 8. | ·- | ÷.3 | 5.6 | 8 | 0. | رب س | 5 | 7. | 0.0 | 2 | ⇒ | | ٠. و | | ~ . | 9. | 8 | ~ | ر. م | - | 7. | | <u>_</u> | EC) | ~ 🙃 |
| | | ₩ | | | | | 7 | 7 | 7 | Ţ | Ÿ | ۲ | Ÿ | Ÿ | ς. | | • | 3 | ÷ | ₹ | ₹ | ₹ | Ċ | 9 | <u>, </u> | Ò٥ | 7 | S. | MPP. | /SE | WIND POWER (WATTS/M**2) |
| | | Σ. | _ | 3.7 | 3 | ~. | 0.7 | S. | .5 .5 | 8. | 0.6 | <u>د</u> . | ω r | 5 | 0.0 | 2. | -7 () | _ | 9. | | 7. | 3.6 | ייטו סיי | 0.7 | α. « | ₹. | | ERA | D (ERA | ₹ | S/M |
| | | CALM | | | | | _ | _ | _ | _ | _ | C) + | N | N | N | m | m | m | m | m | ⇉ | 寸 | ⇒ i | יטי | 91 | _ | | ¥ | PEE AV | EED | ATD |
| | | | | • | S | Δ. | ш | ш | Ω | | Σ | . | | لعا | S | ` | I | 0 | ⊃ | ∝ | | | | | | | | | S | SP | 3 <u>3</u> |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

ANEMOMETER HEIGHT = 20.0 FEET = 6.1 METERS

Table IV - 79

Percentage Frequency Summary for Wind Speed

GLACIER COUNTY - CUT BANK FAA AIRPORT (WINTER)

10/04/59 - 12/31/78

| | | ٩ | SPEED | M/SEC) | | | 5.8 | | | | | | 6.2 |
|--------|--|----------|-------|------------|------|------|------|------|-------------|-----------|------|------|-------|
| | | A | SPEED | (MPH) | | | 13.1 | | | | | | 13.8 |
| | >14.4 | | | >32.2 | 1.9 | 2.3 | ÷. | 3.5 | ⊅. † | 2.8 | 2.4 | 2.3 | 2.7 |
| | 13.5- | | 30.2- | 32.2 | | | 1.5 | | | | | | 1.5 |
| | 12.5- 13.4 | | 28.0- | 30.0 | | | 2.2 | | | | | | 2.6 |
| | 11.5- | | 25.7- | 27.7 | | | 5.6 | | | | | | 2.6 |
| | 10.5- | | 23.5- | 25.5 | | | 3.8 | | | | | | 3.7 |
| | 9.5- | | 21.3- | 23.3 | | | 6.1 | | | | | | 7.1 |
| Ŧ | 8.5- | EC) | 19.0- | 21.0 | | | 7.7 | | | | | | 8.1 |
| ED (MP | 7.5- | D (M/S | 16.8- | 18.8 | | | 6.8 | | | | | | 7.7 |
| ND SPE | 6.5- 7.4 | D SPEE | 14.5- | 16.6 | | | 8.6 | | | | | | 7.2 |
| 3 | - 5.5- 6.5- 7.5- 8.5- 1 6 4 7 4 8 4 9 4 | 3 | 12.3- | 14.3 | | | 7.9 | | | | | | 7.9 |
| | 4.5- | | 10.1- | 12.1 | 8.9 | 4.8 | 8.9 | 6.5 | 8 | 10.2 | 11.3 | 6.7 | 9.0 |
| | 3.5- | | | | 11.7 | 11.6 | 10.3 | 9.8 | 10.3 | 12.2 | 12,4 | 10.3 | 11.1 |
| | 2.5- | | -9.6 | 7.6 | 12.0 | 11.7 | 10.6 | 11.1 | 4.6 | = | 12.6 | 12.7 | 11.4 |
| | 1.5- |] | 3.4- | 5.4 | 10.3 | 10.9 | 1.5 | 9.1 | 9 | 7.6 | 7.8 | 10.0 | |
| | 0.5- | • | 1.1 | 3.1 | 1,3 | | 6.0 | 1.8 | 1.0 | 0.7 | 0.9 | .3 | 1.1 |
| | ۸ م | • | | .1. 1.1 | 8.1 | 8.0 | 6.0 | 7.2 | 3.9 | | 1.9 | 7.4 | 6.8 |
| | | | | | m | 9 | 0 | 12 | 15 | \$ | 2 | 54 | HOURS |
| | | | | | Ξ | | 0 | | n | | ~ | | ALL ! |
| | | | | | | | | | | | | | |

Table IV - 80

Percentage Frequency Summary for Wind Speed

GLACIER COUNTY - CUT BANK FAA AIRPORT (SPRING)

10/04/59 - 12/31/78

| | | A < | PEED | M/SEC) | 8.17 | 7 | | | | | · · | ٥.٥ | 5.2 | 5.8 |
|--------|--|------------|-------|---------|------|----------|------|------|------|------|-------------|--------|-----|-------|
| | | | | (MPH)(M | | | | | 7.7 | | | | | 13.0 |
| | >14.4 | | | >32.2 | 8.0 | 6 | 0 | 0 | 1.0 | | , , , | ? | 9.0 | 1.3 |
| | 13.5- 14.4 | | | 32.2 | | | | | - 0 | | | | | 1.0 |
| | 12.5- 13.4 | | 28.0- | | | | | |) e | | | | | 1.8 |
| | 11.5- 12.4 | | 25.7- | 27.7 | | | | | . " | | | | | 2.1 |
| | 10.5- 11.4 | | 23.5- | 25.5 | | | | | , r | | | | | 3.0 |
| | 9.5 - 10.4 | | 21.3- | 23.3 | | | | | , 0 | | | | | 5.5 |
| Œ | 8.5- | EC) | 19.0- | 21.0 | | | | | . 0 | | | | | 7.7 |
| ED (MP | 7.5- | S/W) 0 | 16.8- | 18.8 | 6.1 | | | | | | | | | 7.9 |
| NO SPE | 6.5- | D SPEE | 14.5- | 16.6 | 7.3 | | | | | | | | | 8.1 |
| 3 | - 5.5- 6.5- 7.5- 8.5- + 6.4 7.4 8.4 9.4 | 2 | 12.3- | 14.3 | 10.1 | | | | | | | | | 6.6 |
| | 5.4 | | 10.1- | 12. | 12.0 | 1.9 | 9.3 | 12,3 | 10.3 | 10.6 | 14.8 | - | 0. | 12.0 |
| | 3.5- 4.4 | | -8 | 9.8 | 15.3 | 14.4 | 12.6 | 12.8 | 10.9 | 10.1 | 17.5 | | 0.6 | 14.2 |
| | 2.5-3.4 | , | 5.6- | 7.6 | 15.4 | 16.0 | 12.1 | 9.1 | 8.7 | 7.2 | 12.2 | 7 17 1 | 2 | 11.9 |
| | 1.5- 2.4 | , | 3.4- | 5.4 | 10.0 | 10.4 | 10.6 | 6.1 | 4.6 | 4.2 | 5.8 | , , | : | 7.4 |
| | 0.5- | , | - ' | 3.1 | 1.7 | <u> </u> | 0.0 | ٥.5 | 0.5 | 0.5 | 0.8 | , | | 0.9 |
| | <0.5 | | • | V | 8.6 | 11.0 | 9.5 | 5.6 | 1.5 | 1.6 | 3.0 | - | 7. | 5.2 |
| | | | | | က | 9 | 6 | 12 | 15 | 18 | 21 | 3.1 | j | HOURS |
| | | | | | ¥ | | 0 | | _ | | œ | | | ALL |

Table IV - 81

Percentage Frequency Summary for Wind Speed

10/04/59 - 12/31/78

GLACIER COUNTY - CUT BANK FAA AIRPORT (SUMMER)

| | AV SPEE M/SE | | 3,5 | 4.5 | r. | 6.1 | 6.3 | 0.0 | - | 4.9 |
|-----------------------|--|------|------|------|------|------|----------|--------------|------|-------|
| | AV SPEED (MPH)(| | | 10.1 | | | | | | 10.9 |
| >14.4 | >32.2 | 0.1 | 0.1 | 0.5 | 0.8 | 9.0 | 0.7 | 0.5 | 0.1 | 0.3 |
| | 30.2- | 0.0 | | 0.2 | | | | | | 0.3 |
| 12.5- 13.4 | 28.0- 30.0 | | | 0.8 | | | | | | 0.9 |
| | 25.7- | 0.3 | | 0.7 | | | | | | 0.9 |
| 10.5- 11.4 | 23.5- | | | 1.7 | | | | | | 1.4 |
| 9.5- | 21.3- | | | 2,5 | | | | | | 3.3 |
| ж) 8.5- 9.4 | 3EC) 19.0- | 2.0 | | 5.7 | | | | | | 5.4 |
| ED (MF 7.5- 8.4 | ED (M/S) 16.8- 18.8 | 3.9 | | 7.4 | | | | | | 6.8 |
| ND SPE 6.5- | 14.5- 16.6 | 8.47 | | 7.0 | | | | | | 6.8 |
| 5.5- 6.4 | WIND SPEED (M/SEC) - 12.3- 14.5- 16.8- 19.0- 3 1 14.3 16.6 18.8 21.0 | 7,8 | | 7.1 | | | | | | 9.3 |
| 4.5- | 10.1- | 12. | | | | | | | 15.3 | 13.3 |
| 3.5- | 7.8-7 | 19.1 | 16.9 | 14.8 | 16.5 | 14.7 | 12,3 | 21.5 | 23.1 | 17.4 |
| 2.5- | 5.6- | 22,5 | 21.3 | 16.2 | 13.4 | 11,3 | 11.6 | 16.7 | 21.9 | 16.9 |
| 1.5- | 3.4- | 14.8 | 16.3 | 14.0 | 7.7 | 6.3 | ٠. د. | 6.3 | 9.7 | 10.0 |
| 0.5- | 1.1 | 6.0 | 8 | 1.5 | 0.5 | 0.5 | 9.0 | 9.0 | 0.8 | 0.8 |
| <0.5 | <u>.</u> | 7,6 | 13.5 | 6.6 | 3.0 | 2,4 | 2.4 | - | 5.5 | 6.2 |
| | | m | 9 | 6 | 12 | 15 | 38 | 21 | 24 | HOURS |
| | | Ι | | 0 | | > | | œ | | ALL |

®₽₽₽₽-₩0₽ Ø

Table IV - 82

Percentage Frequency Summary for Wind Speed

GLACIER COUNTY - CUT BANK FAA AIRPORT (AUTUMN)

10/04/59 - 12/31/78

| | AV SPEED M/SEC) | 4440 808 808 808 44 44 44 44 44 44 44 44 44 44 44 44 44 | 5.6 |
|--|--------------------------|---|-------|
| | AV SPEED S (MPH)(M | 10.7 10.2 14.1 15.7 12.0 | |
| >14.4 | >32.2 | 0002-1000 | |
| | 30.2- | 000-0000 | 0.0 |
| 12.5- 13.4 | 28.0- 30.0 | -0-08 -0 -0 -08 -0 -08 -08 | |
| 11.5- 12.4 | 25.7- 27.7 | | |
| 10.5- 11.4 | 23.5- 25.5 | 01 4 4 6 0 | |
| 9.5- 10.4 | 21.3- | 4 6 4 7 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 | 5.3 |
| H) 8.5- 9.4 | EC) 19.0- 21.0 | ~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~ | 7.0 |
| ED (MP 7.5- 8.4 | D (M/S 16.8- 18.8 | 6.8 10.5 12.1 | |
| ND SPE 6.5- 7.4 | D SPEE 14.5- 16.6 | 6.77 6.70 7.00 8.33 1.43 1.43 | |
| WIND SPEED (MPH) - 5.5- 6.5- 7.5- 8.5- + 6.4 7.4 8.4 9.4 | MIN 12.3- 14.3 | 9.00 9.00 10.60 7.00 7.00 7.00 7.00 | |
| 4.5- | 12.1 | 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0 | |
| 3.5- | 9.8 | 0.44 0.65 0.65 0.83 0.83 0.83 | 13.4 |
| 3.4 | 5.6- | 7.47 12.9 13.9 13.9 | |
| 1.5- | 3.4-5.4 | 122.7 122.7 122.5 12.5 14.9 14.9 | 8.7 |
| 0.5- | 3.1 | E | - |
| <0.5 | <u>.</u> | 10.6 132.7 132.7 143.5 17.5 17.5 17.5 17.5 17.5 17.5 17.5 17 | 7.0 |
| | | 12 17 17 18 18 18 | HOURS |
| | | ≖ Ο ⊃ α | ALL ! |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

Table IV - 83

Annual Wind Rose Distribution

GLACIER COUNTY - CUT BANK FAA AIRPORT

10/04/59 - 12/31/78

| ON SEC) | ONOCHECTETETETETETETETETETETETETETETETETETE |
|---|--|
| ECT ION (M/SEC) | 00 00 00 00 00 00 00 00 00 00 00 00 00 |
| <dire< td=""><td>A V V V V V V V V V V V V V V V V V V V</td></dire<> | A V V V V V V V V V V V V V V V V V V V |
| TOTAL <direction SPEED (M/SE</direction | 00000000000000000000000000000000000000 |
| N N N | 00000000000000000000000000000000000000 |
| 3 | 00000000000000000000000000000000000000 |
| MNM | 0000000000000000000000000000000000 |
| 3 | 000-0000000000000000000000000000000000 |
| MSM | 0000 |
| MS | 0.000000000000000000000000000000000000 |
| MSS | 000000000000000000000000000000000000000 |
| S | 000000000000000000000000000000000000 |
| SSE | 0000-0000000000000000000000000000000000 |
| SE | 000000000000000000000000000000000000 |
| ESE | 00000000000000000000000000000000000000 |
| ш | 00000000000000000000000000000000000000 |
| ENE | 00000000000000000000000000000000000000 |
| NE | 00000000000000000000000000000000000000 |
| N E | 00000000000000000000000000000000000000 |
| z | 000000000000000000000000000000000 |
| DIRECTION> PEED (MPH) | 7. 1. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. |
| DIRE | 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0 |
| _ & | A≷ RCOH∕SGEL-3 DEGEPS |
| | |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES




Table IV - 84

Coefficients of Weibull Distribution

GLACIER COUNTY - CUT BANK FAA AIRPORT

10/04/59 - 12/31/78

| MONTH | SCALE FACTOR (C) (M/SEC) | SHAPE FACTOR (K) |
|--|--|---|
| JANUARY FEBRUARY MARCH APRIL AUNE JUNE JUNE JULST SEPTEMBER OCTOBER NOVEMBER DECEMBER | 7.9270 7.9290 7.5310 7.7180 7.3050 6.2710 6.2710 6.5610 7.3240 7.4580 | 2.1000 2.1560 2.1560 2.1560 2.1560 2.1560 2.1560 2.3560 2.3590 2.3590 2.070 |
| YEAR | 7.3750 | 2.1980 |

DRUMMOND FAA AIRPORT

GRANITE COUNTY

The Drummond Airport is located about 3 miles south-southwest of Drummond at 46 37 10 N and 113 11 50 W (Site No. 59 on Map II-1). Elevation at the airport is 4,238 feet. Meteorological data were collected at the airport for several years by the Federal Aviation Administration.

These data, primarily collected for aviation and weather forecasting uses, consist of short-term (5 minutes or less) averages of wind speed and wind direction, as well as other meteorological parameters. Data were gathered once per hour. The data have been analyzed by Battelle Pacific Northwest Laboratories. Because of a change in anemometer height, the data set was split into two parts for analysis: January 1, 1948, through October 15, 1950; and October 16, 1950, through December 31, 1954. Hourly summaries of data from the latter period were used in the Montana Wind Energy Atlas. For this period, data were gathered by an anemometer mounted on a ground mast at a height of 8.5 meters.

Since the site is located in a mountain valley, wind data from the site are representative only of the immediate area. The wind across nearby saddles and ridges is believed to be much higher in speed. Attempts by Montana DNRC to measure wind speeds at those sites were hampered by equipment failure and possible vandalism.

Average annual wind speed was 7.2 miles per hour. Average monthly wind speeds varied from 6.0 miles per hour in November to 8.3 miles per hour in April.

Average monthly wind power ranged from 36.0 watts/m² in October to 75.0 watts/m² in January. Average annual wind power was 52.0 watts/m².




Table IV - 85

Monthly Wind Speed Distribution

GRANITE COUNTY - DRUMMOND FAA AIRPORT

10/16/50 - 12/31/54

| | 5) | ωd | ш. | ш | ۵ | Σ | · Ш | _ | ا لما | × | n ~ | , v, | ш | ပ | 0 | z | ۵ | | | | | | | | |
|------|----------------|-----------------------|----------------|------------|----------|---|-------------------|---------|--------------------|----------------|---------|---------|---------|---------|---------|-----|-----|-----|-----|-----|------|---------|-------------|---------------|-------------------------|
| | 1 (<0. 1.4. | • • | | • | • | | | | | • | | | | | - | _ | | | | | | | | | |
| | CALM 0.5- | \vec{v} , \vec{v} | 'nΫ | Ÿ | יָי | ֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡֡ | 'n | Ϋ́ | ψı | Ÿ٢ | ŸŖ | 7 | 'n | Ÿ | 7 | Ÿ | 7 | 7 | Ϋ. | ψı | Ϋ́ , | | | | |
| YEAR | ۰-: | | | | | | | | | | | | | | | | | | | | | | Ŋ | <2 | 0 |
| 7 | ထထ | 75 | 13 | 13. | က်၊ | 'nΜ | - | 0 | oʻ | ြဲ | o c | ċ | o. | 0 | o. | 0 | ö | o. | o. | oʻ | | | 7. | ω. | 52. |
| DEC | 12.3 | uΩ | , - | S. | ۰, ر | 7 7 | 0.8 | 7.0 | 0.3 | 0 0 | | 0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 6.3 | 2.8 | 40.0 |
| NOV | 12.8 | | | • | • | | • | • | • | | | | | | | | | | | - | | | 0.9 | 2.7 | 39.0 |
| OCT | 9.5 | | _ | o. | | | | • | • | | | | | | | | | • | • | | | | 6.3 | 2.8 | 36.0 |
| SEP | 6.4 | 26.2 21.0 | 14.5 | 13.8 | w (| n vi | 1.1 | 0.3 | | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 6.9 | 3.1 | 42.0 |
| AUG | 5.8 5.8 | | 9 | نی | | | | | | | | | | | | | | | | | | | 7.2 | 3.2 | 39.0 |
| JUL | 6.9 | 22.3 19.6 | 9 | 'n. | 7.5 | . t. | -: | 0.5 | 0.0 | 1 0 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 7.6 | 3.4 | 51.0 |
| NOC | 5.3 | | _; | vi. | | | | | | | | | | | | | | | | | | | 9.7 | 3.4 | 54.0 |
| MAY | 5.9 | 24.1 16.9 | ~ | ഹ. | ~ c | ; 4 | 2.3 | - ; |)) (| ÷ • | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 8.1 | 3.6 | 65.0 |
| APR | 4.8 | 22.1 17.1 | \sim | ┗. | φ. φ. | | 2.0 | - · | · . | ÷ • | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 8.3 | 3.7 | 71.0 |
| MAR | 7.6 | 24.3 18.0 | 12.0 | 4.9 | 4.5 | , w | 1.5 | 0 0 |) (| | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 7.4 | 3.3 | 59.0 |
| FEB | 7.2 | 23.5 19.4 | 'n | <u>ښ</u> . | 4. | ດ ເບ ບໍ່າບໍ່ | ۔ ھ | 0.0 | ٠ د د | 000 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 9.7 | 3.4 | 61.0 |
| JAN | 8.8 | 24.0 16.3 | N | cu : | - c | 6.5 | 2,3 | ლ (| о с Э с | > 0 | 1.0 | 0.1 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 00 | | 7.8 | 3.5 | 75.0 |
| | CALM (<1,1) | 3.4-5 5.6-7 | 7.8- 9 | 10.1-12 | 16.3-14 | | 19.0-21 | 21.3-23 | 73.7-72 70-7-80 | 28.0-30 | 30.2-32 | 32.4-34 | 34.7-36 | 36.9-38 | 39.1-41 | | | | | | | AVERAGE | SPEED (MPH) | SPEED (M/SEC) | WIND POWER (WATTS/M**2) |
| | | | | | | | | | | | | | | | | | | | | | | | | | |

ANEMOMETER HEIGHT = 28.0 FEET = 8.5 METERS

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

157

HAVRE NWS AIRPORT

HILL COUNTY

The Havre airport is located approximately 4 miles west of Havre at 48 33 00 N and 109 46 30 W (Site No. 60 on Map II-1). Elevation at the airport is 2,585 feet. Meteorological data have been collected at this site for many years by the National Weather Service.

These data, primarily collected for aviation and weather forecasting uses, consist of short-term (5 minutes or less) averages of wind speed and wind direction, as well as other meteorological parameters. Data were gathered once per hour. The data have been analyzed by Battelle Pacific Northwest Laboratories. Because of a change in reporting interval, the data set was split into two parts for analysis: February 1, 1961, through December 31, 1964; and January 1, 1967, through December 31, 1964; and January 1, 1967, through December 31, 1978. Data from the latter period only were selected for inclusion in the *Montana Wind Energy Atlas*.

The data set for Havre consists of summaries of observations made every third hour from January 1, 1967, through December 31, 1978. The anemometer was mounted on a ground mast at a height of 6.1 meters. The site is representative of a large area of north-central Montana.

Average annual wind speed was 10.7 miles per hour. Average monthly wind speeds ranged from 9.6 miles per hour in August to 11.6 miles per hour in April.

Average annual wind power was 135.0 watts/m². Average monthly wind power varied from 96.0 watts/m² in August to 170.0 watts/m² in April.




Table IV - 86

Monthly Wind Speed Distribution HILL COUNTY - HAVRE NWS AIRPORT

01/01/67 - 12/31/78

| | S P P | чФО Σп⊢л | XN/NHOONU | |
|------|--|---|--|---|
| | 23.24.4.2 | | , , , , , , , , , , , , , , , , , , , | |
| | A | <u>ว่ากุ่ากุ่ากุ่ากุ่า</u> | 2002 200 200 200 200 200 200 200 200 20 | |
| YEAR | | | | 10.7 4.8 135.0 |
| DEC | | | | 5.0 5.0 164.0 |
| NOV | 0 0 4 1 1 2 0 0 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | 00/00/00/00/00/00/00/00/00/00/00/00/00/ | 000000000000000000000000000000000000000 | 10.5 4.7 146.0 |
| 00.7 | | | 000000000000000000000000000000000000000 | 10.5 4.7 133.0 |
| SEP | 5.0 13.8 19.2 | 01-46-4920 | 000000000000000000000000000000000000000 | 10.1 4.5 103.0 |
| AUG | | | ± = - 0000000000000000000000000000000000 | 9.6 |
| JUL | 80 # O 0 | | 000000000000000000000000000000000000000 | 10.1 4.5 100.0 |
| NOO | | | ,0-0000000000000 | 10.7 4.8 121.0 |
| MA∀ | | | 000000000000000000000000000000000000000 | 5.0 |
| APR | | | 000000000000 | 5.2 |
| MAR | | | 000000000000000000000000000000000000000 | 11.0 4.9 146.0 |
| FEB | | | -4.000000000000 | 11.0 4.9 144.0 |
| JAN | 7.00 7.00 7.00 7.00 7.00 7.00 7.00 7.00 | ,∪∞∞⊙™∞− • | -00000000000000 | 11.0 11 4.9 4 154.0 144 |
| | CALM (<1. 1.1-3 3.4-5 5.6-7 | 6.81-12 6.81-12 1.01-12 1.01-13 1.01-1 | S 280.0-20.0 1 32.4-34.4 1 35.4-34.4 1 36.9-38.9 1 36.9-38.9 1 36.9-38.9 1 36.9-38.9 1 36.9-56.8 1 36.9-68.0 1 36 | AVERAGE SPEED (MPH) AVERAGE SPEED (M/SEC) AVERAGE WIND POWER (WATTS/M**2) |

ANEMOMETER HEIGHT = 20.0 FEET = 6.1 METERS

MICROWAVE TOWER

JEFFERSON COUNTY


The Jefferson County Microwave Tower site was located on a hill 2 miles south of East Helena at 46 33 27 N and 111 55 01 W (Site No. 62 on Map II-1). Elevation at the site was 4,360 feet. The site was established by the Montana Air Quality Bureau to measure concentrations of particulates and sulfur dioxide in the area.

Wind data from the site that were available for analysis were collected from January 16, 1975, through December 31, 1981. The data set contains hourly averages of wind speed and wind direction manually reduced from stripchart records. Data were gathered by a Meteorology Research, Inc., mechanical recording anemometer and wind vane. Anemometer height was 4 meters.

Winds have been monitored long enough to adequately represent the wind resource at this location. The data, however, are representative only of a limited area on the northern slopes south of East Helena. Also, data recovery was poor, ranging from 24.1 percent in September to 53.0 percent in May. Overall data recovery was 39.3 percent.

Average monthly wind speeds ranged from 7.2 miles per hour in January to 13.4 miles per hour in December. Average annual wind speed was 10.8 miles per hour.

Average monthly wind power values ranged from 132.1 watts/m² in January to 415.3 watts/m² in December. Average annual wind power was 237.6 watts/m².



омпыпо Жыныжо∕оноо×о

Table IV - 87

Monthly Wind Speed Distribution

JEFFERSON COUNTY - MICROWAVE TOWER

01/16/75 - 12/31/81

| | 0-111 22-12:000000 | |
|------|--|--|
| | 20000044440000000000000000000000000 | |
| | 000 | |
| YEAR | - 1 - 1 - 0 - 0 - 0 - 0 - 0 - 0 - 0 - 0 | 889 98 |
| Ϋ́E | 000140000000000000444000000000000000000 | 10. 4. |
| DEC | 0.00-0000000000000000000000000000000000 | 13.4 6.0 415.3 26.9 |
| NOV | 000004400000000000000000000000000000000 | 12.1 5.4 349.8 |
| OCT | 000000000000000000000000000000000000000 | 11.6 5.2 246.4 39.3 |
| SEP | 00-804-00000000000000000000000000000000 | 10.2 4.5 180.6 |
| AUG | 000040000000000000000000000000000000000 | 10.5 4.7 185.0 51.0 |
| JUL | 00000000000000000000000000000000000000 | 10.6 4.7 188.7 37.9 |
| NUC | 000-00000000000000000000000000000000000 | 11.3 5.1 235.5 |
| MAY | 000-8400000000000444400-000 | 11.7 5.2 256.0 2 |
| APR | 00011120111111111111111111111111111111 | 10.7 4.8 226.9 2 |
| MAR | 000000000000000000000000000000000000000 | 10.0 4.5 209.4 2 |
| FEB | $\begin{array}{c} 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 $ | 9.7 4.4 252.9 3 |
| JAN | - 0 - 1 + + 0 0 + 0 + 0 + 0 + 0 + 0 + 0 + 0 + | 7.2 3.2 3.2 132.1 3 |
| | CALM 0.1-1-2.0 2.1-1-2.0 2.1-1-2.0 6.1-7-0 7.1-8.0 7.1-1.0 | AVERAGE SPEED (MPH) AVERAGE SPEED (M/SEC) AVERAGE WIND POWER WATTS/M**2) PERCENT DATA |
| | NCOTA DUMPN | S G X X |

ANEMOMETER HEIGHT = 4 METERS = 13 FEET NUMBER OF OBSERVATIONS = 23961
PERCENTAGE DATA RECOVERY = 39.3

WHITEHALL FAA AIRPORT

JEFFERSON COUNTY

The Whitehall airport site was located 5 miles southwest of Whitehall at 45 49 12 N and 112 12 00 W (Site No. 63 on Map II-1). Elevation at the airport, located in the Jefferson valley, is 4,600 feet. To the south are the Tobacco Root Mountains, which rise to more than 10,000 feet. Bull Mountain, with a summit of about 7,500 feet, lies to the north. West of the site are peaks in the Deerlodge National Forest, with summits ranging from 8,000 to 10,000 feet.

Most of the land in the valley is privately owned. Some sections west of the site are owned by the state. Land in the mountains is controlled predominantly by the Bureau of Land Management and the U.S. Forest

Electrical service in the area is provided by the Montana Power Company and by the Vigilante Electric Cooperative. Many transmission lines run through the area. Commercial airports are located at Whitehall, Butte, Belgrade, and Helena.

Meteorological data were collected at this site for several years by the Federal Aviation Administration. These data, primarily collected for aviation and weather forecasting uses, consist of short-term (5 minutes or less) averages of wind speed and wind direction, as well as other meteorological parameters. Data were gathered once per hour. The data have been analyzed by Battelle Pacific Northwest Laboratories. The Battelle data set was derived from hourly observations made from January 1, 1948, through December 31, 1954. The anemometer was mounted on a ground mast at a height of 9.1 meters. The site is representative of a limited area in the Jefferson River Valley. More recent monitoring by Montana DNRC found lower speeds in the immediate area; however, BPA found even higher wind speeds at the microwave tower northeast of town.

Average monthly wind speeds varied from 9.8 miles per hour in August to 17.7 miles per hour in January. Average annual wind speed was 13.2 miles

Average monthly wind power ranged from 132.0 watts/m² in August to 794.0 watts/m² in January. Average annual wind power was 325.0

Average wind speeds were 10.8 miles per hour in summer, 12.1 miles per hour in autumn, 12.7 miles per hour in spring, and 17.0 miles per hour in winter. During all seasons, the highest average wind speeds occurred in midafternoon. The lowest average speeds occurred in mid-morning in winter, and from around 0600 to 0700 MST during the other seasons.

The diurnal range of average wind speeds was greatest in summer and least in winter. Most of the variation in average wind speeds among the seasons was due to differences in the average nighttime wind speed; however, wind speeds were significantly greater during the winter than they were at all hours during the other seasons.

The most common wind directions at the site were south-southwest through southwest. Winds from the east-northeast through south-southeast were least common. By direction, average wind speeds varied from 6.3 miles per hour for winds from the southeast to 22.6 miles per hour for winds from the southeast to 22.6 miles per hour for winds from the south-southwest. The highest average wind speeds were those from the most common wind directions.




Table IV - 88

Monthly Wind Speed Distribution

JEFFERSON COUNTY - WHITEHALL FAA AIRPORT

01/01/48 - 12/31/54

| | 5) | ഗമ | لبداء | <u>.</u> | ۵ | | Σ | ئىنا | _ | LLI | œ | s | _ | .v | ш | ပ | 0 | z | _ | | | | | | | | | |
|------|-----------------|-------------|-------|----------|----------|----------------|----------|----------|------------|--------------|------------|-------------|------------|--------------|------------|--------------|----------|--------------|------|------------|---------|----------|----------------|------------------|---------|-----------------------|---------------|------------|
| | ≎ | ≠ .⊐ | -= | -7 | # | ₹. | ા | ٦. | ા | ≠ . | # | | ≠ . | ₹. | =: | ≠ . | ⊅. | = | ≠. | ⇒. | _÷ | ⇒ | ≠ | ≠ . | | | | |
| | LM (< | 1.1 | | 1 | 1 | • | ı | • | ī | ٦ | ٦ | 7 | 7 | ٦ | ï | ï | ï | ٦ | 7 | ٢ | ទ | ొ | 7 | × 4 0 | | | | |
| | CAL 0.5 | רי ע תית | | | | - | | _ | | | | | _ | _ | | | | | | | | | | | | | | |
| YEAR | من. | | | | | | | | | | | | | | | | | | | | | | | 0 | | 2 | 6 | 0 |
| YE | ٠. ښ | • | | | - | • | • | • | • | • | | • | • | • | | | • | • | | | | | | • | | <u></u> | 7 | 325.0 |
| DEC | -0: | ص ح | . ⇒ | _ | ۳. | ď | ٥ | m | 0. | ٦. | œ | ۲. | ٠. | ۲. | ⇒. | - | 0. | ۲. | 9 | ≠. | ņ | 0 | ۰. | 0. | | 0. | 9. | |
| ۵ | ⊅ € | | - 9 | 10 | -⇒ | ⇉ | 9 | 7 | J | Ŋ | 9 | 'n | N | N | _ | _ | ,- | 0 | 0 | _ | 0 | 0 | 0 | 0 | | 17. | 7. | 623.0 |
| NOV | 3.53 | 2.5 | | | • | | | • | | | | | | | | | | | | | | | | | | 4.3 | 6.4 | 397.0 |
| L | 99 | | | | | | | | | | | | | | | | | | | | | | | | | _ | | |
| OCT | 9 % | 20.0 | 8 | 3. | 7 | ~ . | 9 | 2. | 3. | | ٣. | - | 0 | 0 | 7.0 | ö | 0 | 0 | | 0 | | 0 | 0.0 | 0 | | 11.6 | 5.2 | 244.0 |
| SEP | 0 | ~ ~ | 0 | _ | ۵ | 9 | 9 | 5 | 7 | ď | cu | 0 | → | | , - | 0 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | r. | 9 | |
| S | 7.2 | | = | 16 | .≠ | 'n | Ġ | ⇒ | 'n | 'n | 'n | - | 0 | o. | Ö | Ö | Ö | Ö | o. | င | Ċ | · | Ö | o. | | 10. | ± | 143.0 |
| AUG | ≠ 9 | | | | • | | • | • | • | • | ٠ | | | • | | | • | | • | | • | • | | | | 9.8 | ħ. † | 32.0 |
| | 9 = 7 | | | | | | | | | | | | | | | | | | | | | 0 | | | | 0 | ⇉ | - |
| JUL | 3.4 | 90 | 2 | 9.2 | 6.1 | 5.7 | 6.8 | 4.7 | 2.0 | 2.3 | 2.0 | 0. | 0.5 | 0.5 | 0.1 | | | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | | 0.7 | 4.8 | 154.0 |
| z | ~9 | ۰. م | . 9 | 3 | <u></u> | 9 | _ | - | 6 0 | ø | ~ | m | 2 | 'n | _ | _ | _ | 0 | 0 | 0 | _ | <u> </u> | <u> </u> | _ | | 6 | ~ | |
| NSC | 4.7 | | 10. | 20. | 9 | ė | φ. | 9 | 4 | 'n | તં | | 0 | 0 | 0 | 0 | ö | · | · | 0 | 0 | <u>.</u> | 0 | 0 | | = | 3 | 182.0 |
| MAY | | m - | | | | | | | | | | | | | | | | - | - | | | | | - | | 9.1 | ٥į | |
| Σ | η. w. | 7 6 | 10 | 200 | 9 | 9 | 7 | 9 | m | N | ~ i | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | Ö | Ó | | = | Ŗ | 181.0 |
| APR | 200 | 9.0 | - | 5.1 | 8 | 8. | .5 | 3.5 | ⇒ | - | 9. | 6: | | ٠. ت | 2.5 | | .2 | | _ | | 0 | 0 | 0. | 0. | | 3.0 | 5.8 | |
| | יטטי | | | | | | | | | | | | | | | | | | | | | | | | | _ | ш, | 243.0 |
| MAR | 44.5 | 7.6 | 6.7 | 3.0 | 6.2 | 6.9 | 9.6 | 7.9 | 4.3 | 0.4 | ÷.3 | S S | | | 7.0 | 0.2 | 0.5 | ٥. | 0. | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 3. T | 6.0 | 295.0 |
| E3 | 99 | | 6 | _ | 0 | 2 | | _ | _ | ~ | cv. | ~ | ο, | m | = | 0 | 0 | œ | ω. | <u>.</u> | 0 | 0 | ٥, | 0 | | | က | 0 29 |
| H | # m | 2 9 | 'n | <u>.</u> | ζ. | ŗ. | ۲. | 7. | Ų. | . | _ | ÷ | ζ. | m | - | - | <u>.</u> | 0 | 0 | 0 | 0 | 0 | - | 0 | | 9 | 7 | 521. |
| NAC | e. −. e | | | • | • | • | • | • | • | • | | | | | | | | | | | | | | | | ۲. | 7.9 | |
| 7 | υ ユ ; | | S | 0 | ť | ₽. | ~ | 9. | t | īΟ. | 9 | ŝ | N | m | _ | _ | _ | 0 | 0 | ~ ∶ | 0 | 0 | 0 | 0 | | 17 | ~ | 794.0 |
| | (<1.1) - 3.1 | ۰۲ م | 8 | ۲. | ÷.3 | 9.9 | 8.8 | 0 | 3. 3. | 5 | 1.1 | 0 | N N | † | 2 | 9 | ~ | 3.4 | 9.6 | 8 | 9 | 2 | # · | , | | <u>_</u> | (C) | _ |
| | <u>V</u> . | - 19 | 4 | - | 3-1 | 7-1 | 8-1 | 0-5 | 3-5 | 2-2 | 7-2 | 0-3 | 2-3 | 1-3 | 7-30 | 9-3 | 1-4 | 7-7 | 6-4. | 9-5 | آؤ ا | 2-7 | - 2 | 2 | AGE | SPEED (MPH AVERAGE | SPEED (M/SEC) | WATTS/M**2 |
| | CALM 1 | ν ιυ 4 Α | _ | 10. | 2 | <u> </u> | 16. | <u>6</u> | 21. | 23. | 25 | 28 | 30 | 32 | 34 | 36. | 39 | - | 43 | 52 | 5. | 89 | <u>,</u> | | AVERAGE | SED VER |) (1) | TS/ |
| | ਹੋ | S | ۵ | ш | ш | <u> </u> | | Σ | _ | _ | العا | w. | \ | I | 0 | > | œ | | | | | | | | 4 | SP | SPEE | , KA |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

9.1 METERS 30.0 FEET = ANEMOMETER HEIGHT =

Table IV - 89

JEFFERSON COUNTY - WHITEHALL FAA AIRPORT (WINTER) Percentage Frequency Summary for Wind Speed

| | AV SPEED M/SEC) | ですですであるのであるのののののですですです。としまるるですとこれをはららされることできます。としまるのです。としまるのです。としまるのです。としまるのです。としまるのです。としまるのです。としまるのです。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできまする。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできます。としまるのできまするのできます。としまるのできまするのできます。としまるのできまするのできます。としまるのできまするのできます。としまるのできまするのできまするのできまするのできまする。としまるのできまする | |
|--------------------|---------------------------|---|-------------|
| | AV SPEED S (MPH)(M | 67777777777777777777777777777777777777 | >: |
| >14.4 | >32.2 | 00000000000000000000000000000000000000 | • |
| 13.5- | | ールできることはようはられるはするようです。 なりのでちらしゅののめめなけられらららせてこのもののない。 | , |
| 12.5- 13.4 | • • • | 日本では、日本では、日本では、日本では、日本では、日本では、日本では、日本では、 | - |
| 11.5- | 25.7- | \$\rho \pi \rho \rho \rho \rho \rho \rho \rho \rho | , |
| 10.5- | 23.5 - 25.5 | はろろろろうちょうけんろうせてろうけれれれる ほろはさはつのはののいうらうらうらいい | - |
| 9.5- | 21.3- | はるはははらはなるなけられらららられらられる よれらうらんしょほううこうほうりつきはいい | 0.0 |
| PH) 8.5- 9.4 | SEC) 19.0- 21.0 | ~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~ | , |
| <u>. 73</u> | ED (M/S 16.8- 18.8 | てててよららららららしてしているののののでしているののののでしていることにはいることにはいるののののできませんだっている。 | : |
| SP -5- | ND SPEE 14.5- 16.6 | | , |
| 5.5- 6.4 | MIN 12.3- 14.3 | www.www.ww.a.ww.ww.ww.ww.ww.ww.ww.ww.ww. | - - - |
| 4.5- | 10.1- | 00000000000000000000000000000000000000 | 0 |
| 3.5- | 7.8- | ろろよけらろうけっちゅうりょううてうううしょうちょうちょうらん こうていらうしょうしゅうしょうしゅうしょうしゅうしょうしゅうしょうしょい | 7.7 |
| 2.5 | 5.6- | | ? |
| 1.5- | 3.4-55.4 | 4-4-0-4-0-4-0-6-6-6-6-6-6-6-6-6-6-6-6-6- | · · |
| 0.5- | 1.1- | とはははならなければなるとしてしてこれできませればっていることできるとしてしてものののはいいました。 | 0.0 |
| ^ د | . t | ろうてもららられるらららいしょうきょれんらってきらららられるからないのうことできるとうのうことできるというできるというできるというできるというというというというというというというというというというという | + |
| | | 22222222222222222222222222222222222222 | |
| | | ±ο⊃ κ | ALL |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

Table IV - 90

Percentage Frequency Summary for Wind Speed JEFFERSON COUNTY - WHITEHALL FAA AIRPORT (SPRING)

| | AV SPEED M/SEC) | 9 7 | מיה | m | بر م | 9 | က | o r | , ∞ | 2 | 寸 | . | ر ح | + - | - ⇒ | · 00 | 寸 | _ | 6 | & | 7 |
|---------------------------|-----------------------|--------------|----------------|------|----------|------|-----------------------|----------------|------|------|----------|---|----------------|------------|------|------|----------|--------|------|--------------|-------|
| | | | 3 3 | | | | | | | | | | | | | | | | | | 5.7 |
| | AV SPEED (MPH)(| 10.2 | 10.0 | 6 | y 0, | 10.3 | 11.9 | 13.4 | 15.2 | 16.1 | 16.6 | 16.6 | 8.9 | ٠ د م | 77 | 13.0 | 12,1 | 11.4 | 11.0 | 10.7 | 12.7 |
| >1h h | >32.2 | | 0.8 | | | | | | | | | | | | | | | | | | 1.5 |
| 13.5- 14.4 | 30.2- 32.2 | 0.0 | 0.5 | 0.0 | 20 | 0.3 | 0.2 | - 0 | 5.6 | 1.9 | 1.9 | 6. | - 0 | | 0.3 | 0.3 | 0.8 | 0.5 | 0.5 | 0.3 | 0.8 |
| 12.5- 13.4 | | | 0.4 | | | | | | | | | | | | | | | - | - | - | 2.0 |
| 11.5- 12 4 | | | 0, 0, 0, 0, | | | | | | | • | • | | | | | | - | | | - | 3.5 |
| 10.5 - 11.4 | 16 | 1.0 | | 6.6 | , w 6 | 2,3 | 9.0 | 4 K | 9.9 | 4.9 | 6.8 | 5.6 | | 7 7 | 4.7 | 2.2 | 2.5 | 2.5 | 0.8 | 2.1 | 3.6 |
| 9.5- | 3.3 | 3.5 | 9.0 | | | | | | | | | | | | | | | | | | 3.9 |
| H) 8.5- | EC) 19.0- 21.0 | 6.6 5.4 | 4.0 5.0 | • | | | | | | • | • | | | | | | | | | | 7.6 |
| ED (MPH 7.5- | D (¥ 16.8 18. | 7.0 | 7.5 6.2 | 6.7 | . r. | 6.0 | 7.5 | × 60 | 8.3 | 9.5 | 10.9 | 12.9 | 2. k | 12. | 12.0 | 10.2 | 8. 8. | 8.6 | 7.9 | 7.0 | 9.0 |
| ~ · · · · | SPEE 1.5- 6.6 | 5.8 | | | | • | | | | • | • | • | | | | | | • | | | 6.8 |
| 5.5- 6.4 | WIND 12.3- 14 | 5.6 | | • | | • | • | | | | ٠ | | • | | | | | | | | 9.9 |
| 4.5- 5.4 | 10.1- | 16.8 14.9 | | | 12.7 | 13.4 | 13.2 | 0 <u>1</u> | 15.0 | 13.4 | 14.2 | 9,4,6 | | 3 | 20.7 | 22.0 | 20.2 | 17.6 | 17.2 | 18.2 | 15.8 |
| 3.5- | 7.8- | 8.4 10.3 | 9.5 4.5 | 7.3 | 8.7 | 7.0 | 10.1 | 7.6 | 6.9 | 8.3 | 7.3 | -, | ٠.٧ | 0.7 | 9.5 | 10.6 | 1.2 | 11.5 | 9.6 | 10.4 | 8.5 |
| 2.5- | 5.6- | 11.7 | 8.1 12.3 | 11.3 | 7.1 | 8 | ع د ص ه | , o | 7.5 | 6.7 | 5.4 | ~ | ÷ ~ | 7 | 5 | 6.7 | 7.9 | 10.1 | 8.5 | 11.5 | 8.0 |
| 1.5- | 3.4-5.4 | 19.1 21.9 | 20.8 17.5 | 21.1 | 21.6 | 18.2 | 7.0 | 10.7 | 11.8 | 9.5 | 7.8 | <u>, , , , , , , , , , , , , , , , , , , </u> | ٥٠ د د | 6.9 | 7.1 | 8.9 | 1.5 | 15.9 | 16.9 | 16.1 | 13.8 |
| 0.5- | 3.1 | 4.5 5.6 | 7.7 | 9.9 | 6.5 | 6.5 | ر د . | 3.4 | 2.2 | .3 | 6.0 | - 0 |) -) - | 0 | - | 2.5 | ۳. | 2.8 | 3.9 | † † | 3.6 |
| <0.5 | 4.1 | 7.3 | 8 8 6 7 | 10.4 | 13.7 | 11.2 | 6.2 |) - | 2.8 | 1.6 | 0.0 | o . | - · · | . 0 | 9.0 | 1.7 | ω, ω, | ж Э | 5.9 | 5.6 | 5.0 |
| | | 5 | m ⊅ | r, | 0 ~ | ∞ (| ص ڈ | | 12 | 13 | | | 0 7 | - 🕰 | 19 | 20 | 21 | 22 | 23 | 24 | HOURS |
| | | | | | | • | I | 0 | | _ | 1 | ¥ | | | | | | | | | ALL |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

Table IV - 91

JEFFERSON COUNTY - WHITEHALL FAA AIRPORT (SUMMER) Percentage Frequency Summary for Wind Speed

| | | <u> </u> | 2 | 80 | 7 | m | _ | 0 | 0 | 0 | N. | _ | & | m | _ | c, | 7 | ~ | 0 | _ | ဆ | m | 2 | 0 | 9 | 3 | 0 | ∞ |
|-----------------|--------------|----------------|------|------|--------|------|------|-------|------|------|------|----------|--------------|------|------|------|------|----------|------|------|-----|--------------------|----------|------|----------|------|------|--------------|
| | ₹ | SPE | 5 | • | • | • | | • | • | | | | • | • | • | • | ٠ | • | | • | ٠ | • | | • | • | • | • | . |
| | ¥ | SPEED | | | | | | | | | | | | | ď | | | 14.9 | | ٠. | | | | | | | | 10.8 |
| - - - | † † | c | 35.2 | | | | | | | | | | | | | | | 1.6 | | | | | | | | | | 8.0 |
| 13.5- | r | 30.2- | v | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.2 | 9.0 | 0.5 | 1.0 | 0.8 | 1.2 | 1.7 | 1.2 | -: | 9.0 | 1.2 | 0 | 0.0 | 0.0 | 0.3 | 0.5 | 0.0 | 0.5 |
| 12.5- | ? | 28.0- | _ | | | • | | | | | | | | | | • | | 2.0 | | | | | | | | | | 1.1 |
| 11.5- | † - | 25.7- | ~ | - | | • | • | | | | • | | • | • | • | • | | 5.0 | • | | | • | • | | | • | • | 2.1 |
| 10.5- | <u>.</u> | 23.5- | 0.0 | | | | | | | | | | | | | | | 5.0 | | | | | | | | | | 2.3 |
| 9.5- | <u>.</u> | 21.3- | ; | 0.5 | 0.0 | 0.5 | 9.0 | -: | 6.0 | 9.0 | 1.7 | 1,3 | 1.9 | 4.0 | 4.0 | 3.4 | 3.6 | 4.0 | 0.4 | ±.3 | 4.3 | o. 1 | 2,5 | 1.6 | → | 0.8 | 1:1 | 2.2 |
| H) 8.5- | t. (| 9.0- | | • | 2.8 | • | • | | • | | | | | ٠ | | • | • | .± .₩ | • | • | • | | • | | • | 3.4 | • | 5.0 |
| ED (MPH 7.5- | D (M/S | S | 0.0 | | • | • | ٠ | | | | | ٠ | | • | | • | | 13.7 | | • | | ٠ | | | | ٠ | • | 7.0 |
| SPE 5- | PEE | 5 | • | | | | | | | | | | | | | | | 8.6 | | | | - | | | | | | 5.9 |
| WIND 5.5- 6. | Z Z | 15.3 - 15.3 | ÷. | | ٠ | ٠ | | ٠ | | | | | | • | • | | • | 6.7 | • | • | | | • | • | • | | | 5.8 |
| 4.5- | ` | 1.01 | v | 19.1 | 17.2 | 13.8 | 12.8 | 15.8 | 12.0 | 10.9 | 14.3 | 21.1 | 17.2 | 18.0 | 15.7 | 18.2 | 23.1 | 18.5 | 19,1 | 20.4 | 9.9 | 24.3 | 25.5 | 25.9 | 25.0 | 23.8 | 20.4 | 18.8 |
| 3.5- | ; ; | -8. | | 14.2 | 14.6 | 14.1 | 11.2 | 10.4 | 11.3 | 7.6 | 11.2 | 1.8 | 13.8 | 13.7 | 13.2 | 13.4 | 10.6 | 8.6 | 0.6 | 9.5 | 8.1 | 8.5 | 11.8 | - | | | _ | 11.9 |
| 2.5- | 7 | 5.6- | 0. | 13.4 | 13.2 | 13.2 | 14.4 | 12.1 | 12.7 | 10.9 | 10.3 | 13.8 | 12.7 | 9.5 | 10.4 | 10.0 | 5.1 | 7.0 | 7.1 | 5.4 | 4.8 | 9 | ⊅ | 11.4 | 11.5 | 11.6 | 11.8 | 10.3 |
| 1.5- | | 3.4- | 4.0 | 22.1 | 22.7 | 27.8 | 28,1 | 26.8 | 30.1 | 26.9 | 25.6 | 20.0 | 17.2 | 16.0 | 13.0 | 10.3 | 8.7 | 8.7 | 4.8 | 6.5 | 7.1 | 5.9 | 7.8 | 10.0 | 14.6 | 18.5 | 21.3 | 16.7 |
| 0.5- | <u>.</u> | 1.1 | | 4.7 | 9.7 | 7.8 | 8.3 | œ | 7.8 | 11.6 | 7.5 | ٠٠ | 2.5 | 2.9 | 2.0 | 1.5 | 1.0 | 9.0 | 0.3 | 0.7 | 9.0 | - | 2.0 | 2.8 | 9. | 3.9 | 5.6 | 3.9 |
| , , , | | ; | | 7.1 | 8 7 | 8,6 | 10.6 | 14.0 | 14.3 | 17.4 | 13.5 | 4.7 | 4.6 | 4.0 | 3.6 | 1.3 | 0.0 | 9.0 | 9.0 | 7.5 | 1.1 | 1.7 | 2,3 | 2.7 | | 4.2 | 6.2 | 5.7 |
| | | | | | | | | | | | | | | | | | | 15 | | | | | | | | | | ALL HOURS |
| | | | | | | | | | | | | I | | 0 | | > | | œ | | | | | | | | | | ALL } |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

Table IV - 92

Percentage Frequency Summary for Wind Speed

JEFFERSON COUNTY - WHITEHALL FAA AIRPORT (AUTUMN)

| Α. | PEED 1/SEC) | | | | - 82 9 0 0 0 0 8 9 0 0 0 0 0 0 0 0 0 0 0 0 0 | 5.4 |
|--------------------|---------------------------|---|----------------|--|--|-------|
| ₹ | SPEED SI (MPH)(M, | | | | 155.8 132.22 112.94 10.70 10.70 10.70 | 12.1 |
| >14.4 | >32.2 | | | | 8.99999 | 2.7 |
| . 5- 4 · 4 | 30.2- | 000-000 | | - 2.6.6 | 000000000 | 6.0 |
| 12.5- 13.4 | 28.0- 30.0 | | | | 2001-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1 | 2.3 |
| 11.5- 12.4 | 25.7- 27.7 | | | | 01 00 - 00 - 00 0 0 0 0 0 0 0 0 0 0 0 0 | 3.5 |
| 10.5- 11.4 | 23.5- 25.5 | | | | wwwa-a-a-a wwwa-a-a-a | 3.2 |
| •0 | 21.3 - 23.3 | | ٠. | | ~ + + + + + + + + + + + + + + + + + + + | 3.4 |
| PH) 8. SEC) | | <i></i> | | | e— | 5.8 |
| EED (7.5 8. | 16 | <i>.</i> | | | 201010101010101010101010101010101010101 | 7.0 |
| ND 6. | - | | | | 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0 | 5.3 |
| 7.5 7.4 7.4 | 12.3 - 14.3 | | | | 200888700 200888700 30008 | 5.2 |
| 4.5- 5.4 | 10.1 - 12.1 | | | | 13.4 222.4 222.4 20.7 20.7 18.5 14.6 | 13.9 |
| | 7.8- | | | | 8889 1 58698 | 8.7 |
| 2.5- 3.4 | 5.6- | 10.11.6 | 40.0 | 0.000 | 0.7779997775 1729997775 | 9.7 |
| 1.5- 2.4 | 3.4- 5.4 | 25.23.7.7.29.29.7.7.29.29.7.7.29.29.29.29.29.29.29.29.29.29.29.29.29. | 24.0 19.3 | 10.7 | 9.9 0.00 0.00 0.00 0.00 0.00 0.00 0.00 | 17.9 |
| 0.5- | 3.1 | 34WWWWW 10844W80 | v.w.v w.= v | 12.51 12.51 | | 3.7 |
| <0.5 | 1.1 | .00 10.00 13.00 14.00 16 | ສ.ດ. ຜ – ⊂ | ,000 3.00 3.00 3.00 3.00 3.00 3.00 3.00 | 2.1. 2.1. 3.1. 3.1. 5.1. 6.1. 7. 8. 7. | 6.8 |
| | | 08195185 | o 5 E | 2254 | 2002013 2002013 2012013 | HOURS |
| | | : | Ξ C |)) | c c | ALL |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

Table IV - 93

Annual Wind Rose Distribution

JEFFERSON COUNTY - WHITEHALL FAA AIRPORT

01/01/48 - 12/31/54

| TOTAL <direction SPEED (M/SEC)</direction | 0.5-1.4 2.5-2.4 S 4.5-5.4 E 5.5-3.4 P 6.5-7.4 D 7.5-1.4 E 10.5-11.4 E 11.5-12.4 R 12.5-14.4 / 14.5-15.4 S 13.5-14.4 / 14.5-15.4 S 13.5-14.4 / 14.5-15.4 S 13.5-14.4 / 14.5-15.4 D 15.5-17.4 C 16.5-17.4 C 16.5-17.4 C 16.5-17.4 C 17.5-17.4 C 18.5-18.4 D 20.5-25.4 D 20.5-25.4 D 20.5-25.4 D AV SPD (MPH) |
|--|--|
| TOTAL | 0 |
| X.N. | 00000000000000000000000000000000000000 |
| 3 | 04000000000000000000000000000000000000 |
| X X X | 00000-00000000000000000000000000000000 |
| 3 | 00-00-00000000000000000000000000000000 |
| MSM | 00000000000000000000000000000000000000 |
| MS. | 000000000000000000000000000000000000000 |
| MSS | 00000000000000000000000000000000000000 |
| σ | 00-00-00000000000000000000000000000000 |
| SSE | 00000000000000000000000000000000000000 |
| SE | 0.0000000000000000000000000000000000000 |
| ESE | 000000000000000000000000000000000000000 |
| ш | 00000000000000000000000000000000000000 |
| ENE | 00000000000000000000000000000000000000 |
| N E | 0.01-01-0000000000000000000000000000000 |
| NNE | 00000000000000000000000000000000000000 |
| z | 00-00000000000000000000000000000000000 |
| DIRECTION> SPEED (MPH) | 3.4-5.4 7.8-9.8 7.8-9.8 7.8-9.8 14.3-14.3 14.5-16.6 16.8-18.8 16.8-18.8 16.8-18.8 17.3-23.3 18.2-3.7-25.5 8.30.2-32.2 19.36.7 19.36.7 19.36.7 19.36.7 19.66.8 10.66.8 10.66.8 |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES




Table IV - 94

Coefficients of Weibull Distribution JEFFERSON COUNTY - WHITEHALL FAA AIRPORT

01/01/48 - 12/31/54

| MONTH | SCALE FACTOR (C) (M/SEC) | SHAPE FACTOR (K) |
|---|--|--|
| JANUARY FEBRUARY MARCH APR IL MAY JUNE JUNE JUNE SEPTEMBER OCTOBER NOVEMBER DECEMBER | 9.2990 8.4560 7.1330 7.1640 6.4880 6.4880 6.7630 5.9020 7.8100 8.9070 | 1.5450 1.7370 1.8280 1.9410 1.9780 1.8420 1.7360 1.6180 1.7390 |
| YEAR | 7.2800 | 1.6720 |

| · | | |
|---|--|--|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

RONAN NINEPIPES

LAKE COUNTY

The Ronan Ninepipes monitoring site is located 5 miles south of Ronan at 47 27 35 N and 114 07 59 W (Site No. 66 on Map II-1). Elevation at the site is 3,020 feet. The site was established by the Montana Air Quality Bureau as part of the Flathead River Basin Environmental Impact Study.

Wind data from December 11, 1980 through February 26, 1982, were available for analysis. The data set contains hourly averages for wind speed and wind direction. These data were recorded by a data acquisition system that scanned each parameter several times per minute. Measurements were made by a Climatronics electronic anemometer and wind vane on a 10-meter tower.

The period of monitoring was long enough to adequately represent the wind resource at this location. Data recovery was good, ranging from 50.0 percent in September to 100.0 percent in February and May. Overall data recovery for the monitoring period was 91.8 percent. The site is located in the Flathead Valley, and the data are representative of a large area from Ronan to Saint Ignatius, with the exception of areas on the eastern side of the valley near the openings of canyons.

Average annual wind speed was 4.5 miles per hour. Average monthly wind speeds ranged from 3.3 miles per hour in November to 6.2 miles per hour in April.

Average monthly wind power varied from 6.2 watts/m² in August to 31.4 watts/m² in February and April. Average annual wind power was 17.0




Table IV - 95

Monthly Wind Speed Distribution

LAKE COUNTY - RONAN NINEPIPES

12/11/80 - 02/26/82

YEAR

DEC

№

OCT

SEP

AUG

JUL

NOC

MAY

APR

MAR

FEB

| 4.00.4 | 0,00 W | กสา | 3 V V | 99 | - /- œ | တ်ထ | <u></u> ∞ | 2-7- | | | | |
|---|--------------------|---|-------------------|------------------------|------------|------|-----------|---------------------|-----------------------------------|--------------------------|-------------|-------|
| CALM 0.1- 1.0- 1.4- | - 0 0 0 0 0 | - 400 - 400 | 40r | 10.00 10.40 | 0.7.0 | 8 8 | 19,0 | 5. 7. 7. | | | | |
| 0 4 1 7 7 7 1 4 1 5 5 5 5 4 1 7 5 5 4 1 7 5 5 4 1 7 5 1 7 1 7 1 7 1 7 1 7 1 7 1 7 1 7 1 | | | 900 | 000 | 0 O C | 0.0 | 0.0 | 0000 | 4.5 | 2.0 | 17.0 | 91.8 |
| 0.5 6.1 19.7 21.8 14.1 | | | | | | | | 000 | 4.4 | 2.0 | 21.6 | 94.7 |
| 22.0 28.5 15.2 | 3.90 | | 0.0 | 0.00 | | 0.0 | 0.0 | 000 | 3.3 | 1.5 | 6.3 | 0.96 |
| 0.2 4.0 17.2 29.1 | 0.01 | 4.25 | 000 000 000 | 0.00 | 000 000 | 000 | 0.0 | 000 | 4.0 | . 8 | 10.1 | 71.2 |
| 0.0 2.2 11.1 24.4 19.4 | 0.8 0.4 0.4 | | -00 | 000 | 000 | 0.0 | 0.0 | 000 | 4.0 | 1.8 | 6.3 | 50.0 |
| 3.1 14.2 31.0 13.6 | | | | | | | | | 3.8 | 1.7 | 6.5 | 85.9 |
| 0.0 3.4 28.8 13.1 | 2 | ,0 - v | 000 | 000 | 00.0 | 0.0 | 0.0 | 000 | 4.5 | 2.0 | 16.0 | 7.66 |
| 0.0 2.0 9.7 18.8 | | | | | | | | | 4.9 | 2.2 | 12.1 | 8.76 |
| 0.0 3.2 13.2 24.1 | | | | | | | | | 4.1 | 1.8 | 8.9 | 100.0 |
| 0.0 0.6 7.1 15.6 | 12.9 9.5 | 1000 1000 1000 1000 1000 1000 1000 100 | 10,0 | | 0.7 | 00 | → | 000 | 6.2 | 2.8 | 31.4 | 97.9 |
| 3.0 3.0 13.7 26.9 22.8 | 13.2 5.2 4.2 | 80° | 0.3 | 000 | 000 | 0.0 | 0.0 | 000 | 3.8 | 1.7 | 8.0 | 100.0 |
| 0.4 3.4 21.5 14.4 | 5.0°V | (m = 0 | i ~ - ~ | i - i - i - | -0- | 00 | 00 | 000 | 5.4 | 2.4 | 31.4 | 99.0 |
| 0.3 11.1 16.5 27.4 8.3 | 9.4 | 2.4 | 9.6. | 9-0 | 0.0 | 0.0 | 0.0 | 0.0 | 4.2 | 1.9 | 23.0 | 4.96 |
| CALM 0.1-1.0 1.1-2.0 2.1-3.0 3.1-4.0 | 1-5 | 7.1-8 8.1-9 1-10 | 10.1-11.0 | | 1-17 | 1-19 | .1-25 | 55.53 | AVERAGE SPEED (MPH) AVERAGE | SPEED (M/SEC) AVERAGE | WATTS/M**2) | |
| ωa | шшд | ∑ - | — ш у | _ = (|) > K | : | | | š | SPE | 3 4 | - |

DAOCES/SRETEM DEFINA

ANEMOMETER HEIGHT = 10 METERS = 33 FEET NUMBER OF OBSERVATIONS = 9759 PERCENTAGE DATA RECOVERY = 91.8

HELENA NWS AIRPORT

LEWIS AND CLARK COUNTY

The Helena airport is located approximately 2 miles east of Helena at 46 36 21 N and 112 00 00 W (Site No. 71 on Map II-1). Elevation at the airport is 3,897 feet. Meteorological data have been collected at this site for many years by the National Weather Service.

These data, primarily collected for aviation and weather forecasting uses, consist of short-term (5 minutes or less) averages of wind speed and wind direction, as well as other meteorological parameters. Data were gathered once per hour. The data have been analyzed by Battelle Pacific Northwest Laboratories. Because of a change in anemometer height, the data set was split into two parts for analysis: January 1, 1948, through September 19, 1961; and September 20, 1961, through December 31, 1978. Only data from the more recent period were selected for inclusion in the Montana Wind Energy Atlas.

The data set for Helena consists of summaries of observations made every third hour from September 20, 1961, through December 31, 1978. The anemometer was mounted on a ground mast at a height of 6.1 meters. Due to the complex terrain, the site is representative only of a limited area in the Helena valley.

Average annual wind speed was 7.8 miles per hour. Average monthly wind speeds varied from 7.4 miles per hour in August through December to 9.4 miles per hour in April.

Average annual wind power was 69.0 watts/m². Average monthly wind power ranged from 50.0 watts/m² in August to 97.0 watts/m² in April.




Table IV - 96

Monthly Wind Speed Distribution LEWIS AND CLARK COUNTY - HELENA NWS AIRPORT

09/20/61 - 12/31/78

| | .5. S E | | |
|------------------|--|--|--------------|
| | ~-C~~ | , , , , , , , , , , , , , , , , , , , | |
| | - nunnun | 4 U | |
| YEAR | ლ . დ.ლ. ლ | 20.00000000000000000000000000000000000 | |
| DEC | | ###################################### | |
| N _O V | 10.0 5.2 28.1 20.3 12.4 | 7 3 4 6 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 | |
| OCT | | 7 3 4 0000000000000000000000000000000000 | |
| SEP | | 24 8 000000000 | |
| AUG | | 70000000000000000000000000000000000000 | |
| JUL | | 72 × 4 0000000000000000000000000000000000 | |
| NOC | | 20000000000000000000000000000000000000 | |
| MAY | 5.1 19.1 17.2 | 00000000000000000000000000000000000000 | |
| APR | | 0.00 | |
| MAR | | 85 % 9 % 9 % 9 % 9 % 9 % 9 % 9 % 9 % 9 % | |
| FEB | | 2 × × × × × × × × × × × × × × × × × × × | |
| JAN | | 8 × × × × × × × × × × × × × × × × × × × | |
| | CALM (<1.1 1.1-3. 3.4-5. 5.6-7. | 10.1-17.12.3-14.11.12.3-14.12.3-14.13.12.3-14.13.12.3.5.25.0.22.3.5.25.0.23.3.6.2.3.2.3.2.3.2.3.2.3.2.3.3.3.2.4.3.3.4.3.4 | (MATTS/M**2) |

ANEMOMETER HEIGHT = 20.0 FEET = 6.1 METERS

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

SIEBEN RANCH 1 LEWIS AND CLARK COUNTY

The Sieben Ranch I site is located about 25 miles northwest of Helena at 46 55 00 N and 112 13 00 W (Site No. 154 on Map II-1). Elevation at the site is about 5,600 feet. (The location and elevation are given incorrectly in earlier BPA publications.) This monitoring site was part of the Wind Regional Energy Assessment Program run by Oregon State University for Bonneville Power Administration.

The site is in an area of numerous well exposed rolling hilltops and ridges. The hilltops are smooth and the slopes are moderate to steep. The site is representative of a large area. Access to the area is excellent, with an all-weather state road to the south and west and Interstate Highway 15 to the east. Access to the site itself is by dirt road. Winter access is sometimes hampered by drifting snow.

Most of the land in the area is privately owned, though there are sections of BLM and state property. Electrical service in the area is provided by the Montana Power LMS KV line runs within 7 miles of the site, but nearest substation is outside of Helena. The nearest commercial airport is located at Helena.


Collection of wind data began February 18, 1984 and ran through July 28, 1984. This period was too brief to serve as the basis for long term predictions, but the data were sufficiently encouraging to warrant inclusion in the Atlas. The anemometer height was 35 feet.

Data recovery, made with a data logger, was excellent, ranging from 88.0 percent in February to 99.9 percent in June. The overall data recovery was 97.0 percent.

Average monthly wind speeds ranged from 14.4 miles per hour in July to 20.4 miles per hour in February. Average wind speed for the five-month period was 16.7 miles per hour. The winds blew from the west nearly half the time. It is not clear whether this preponderance of wind from one direction is due to the effects of local terrain or to a malfunctioning wind vane.

Average monthly wind power ranged from 225.9 watts/m² in July up to 627.4 watts/m² in February.

Because of the short monitoring period, only the monthly wind speed distribution is reported here, even though Sieben Ranch appears to be a high potential site.



Monthly Wind Speed Distribution LEWIS AND CLARK COUNTY - SIEBEN 1

| | | CALM | .i- 0.4 | 6.0 -6. | .U- L.3 | .4-1.8 | .9- 2.2 4 | .3- 2.7 | .8- 3.1 | 3.6 | 0.4 | م ت | 6.9 | 4. | ထ | ۳, | 5.7 | 7.2 | 9.7 | .7-8.0 0 | ഹ | ص ص | .0-11.2 | ,3-13.4 | .5-15.6 | 7-17.9 | >17.9 | | | | | | |
|---------------------|------|------|------------|------------|------------|----------|-----------|---------|---------|-----|-----------|-------------------|-------|--------|--------|--------|----------|----------|----------|----------|-----------|-----------|-----------|-----------|-----------|---------|-------|---------|------------------------|---------------|---------|--------------|----------|
| | YEAR | 1.1 | | | | | | | | | | | | | | | | | | | | | | _ | _ | _ | 1.7 | | 16.7 | 7.4 | | 404.3 | 97.0 |
| | 23 | 0.0 | 0.0 | 0.0 |)) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 2 | S | | 2 | 0.0 |
| | ΑO | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0 | 0.0 | 0.0 | | 2 | 웆 | | 2 | 0.0 |
| | 5 | 0.0 | 0.0 | 0.0 | ۰ ن | 0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0. | 0.0 | 0.0 | | 2 | 2 | | 문 | 0.0 |
| | 쭚 | 0.0 | 0.0 | 0.0 |)) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 9 | R | | 운 | 0.0 |
| 28/84 | AUG | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0. | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 2 | 윤 | | 문 | 0.0 |
| 02/18/84 - 07/28/84 | 뒭 | 1.8 | 1.5 | <u>:</u> : | <u>د.</u> | 3.2 | 2.4 | 3.6 | 5.0 | 4.1 | 3.8 | 5.3 | 5.0 | 5.0 | 4.8 | 4.2 | 5.0 | 2.7 | 4.4 | 4.8 | 5.4 | 4.1 | 12.4 | 5.0 | 1.5 | | 9.0 | | 14.4 | 6.5 | | 225.9 | 98.4 |
| 02/18/ | N) | 9.0 | 8.0 | I | -: | 2.1 | 3,6 | 4.7 | 4.9 | 4.0 | 4.0 | 3.9 | 3.2 | 0.9 | 4.9 | 4.3 | 4.3 | 3° 8° | 3.2 | 3.1 | 3.6 | 2.4 | 12.4 | 9,5 | 4.5 | 8 | 8 | | 16.3 | 7.3 | | 361.1 | 6.66 |
| | MAY | 0.4 | <u>د</u> . | 1.2 | ۲. | 2.7 | 2.2 | 1.9 | 3,3 | 3,3 | 3.9 | 2.1 | 3.3 | 2.4 | 1.8 | 3.4 | 3.1 | 2.4 | 4.0 | 3.3 | 1.8 | 3.0 | 16.3 | 14.4 | 9.2 | 5.2 | 2.7 | | 19.7 | 8.8 | | 561.0 | 98.4 |
| | APR | 1.7 | 2.1 | φ. | 3.1 | 4.1 | 4.9 | 3.1 | 4.4 | 4.4 | 5.2 | 3.0 | 4.7 | 3.7 | 3.7 | 3.6 | 5,6 | 3,3 | 3.1 | 2.9 | 2.0 | 2.3 | 0.6 | 7.6 | 4.9 | 3,1 | 0.7 | | 14.7 | 9.9 | | 328.7 | 97.1 |
| | MAR | 1.4 | 9. | Ξ: | 4.1 | 3.4 | 3.4 | 2.0 | 3.5 | 2.8 | 4.5 | 3.4 | 4.5 | 3.5 | 3.2 | 3.4 | 4.0 | 3.5 | 3°8 | 3.8 | 2.7 | 3.0 | 12.1 | 9.5 | 6.9 | 2.7 | 2.4 | | 16.9 | 7.6 | | 463.6 | 95.2 |
| | FEB | 0.4 | æ . | 2.1 | 7.1 | ., ,, | 2.5 | 0.8 | 0.8 | 2.1 | 2.1 | 2.5 | 1.6 | 2.9 | 4.5 | 0.8 | 4.1 | 2.1 | 3.7 | 4.1 | 3.7 | 4.1 | 13.6 | 17.7 | 9.1 | တ္ (| 2.5 | | 20.4 | 9.1 | | 627.4 | 88.0 |
| | JAN | 0.0 | 0.0 | 0.0 | . | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 2 | ş | | 9 | 0.0 |
| | | CALM | 0.1-1.0 | | 2.1 | | 4.1 | Ξ. | 6.1 | 7.1 | M 8.1-9.0 | 9.1- | 10.1- | 11.1-1 | 12.1-1 | 13,1-1 | 14.1-15. | 15.1-16 | 16.1-17. | 17.1 | 18.1-19.0 | 19.1-20.0 | 20.1-25.0 | 25.1-30.0 | 30.1-35.0 | | >40.0 | AVERAGE | SPEED (MPH) AVERAGE | SPEED (M/SEC) | AVERAGE | (WATTS/M**2) | RECOVERY |

NAUHO MUHUNAN/NUUNO

ANEMOMETER HEIGHT = 11 METERS = 35 FEET NUMBER OF OBSERVATIONS = 3703 PERCENTAGE DATA RECOVERY = 97.0

WHITLASH LIBERTY COUNTY

The Whitlash site is located four miles south of Whitlash and about twentyeight miles north-northwest of Chester at 48 51 36 N and 111 14 46 W (Site No. 156 on Map II-1). Elevation at the site is 4,300 feet. This monitoring site is part of the wind monitoring program of the Montana Department of Natural Resources and Conservation.

The site is atop a drainage divide in a rolling grassland area near the Sweet Grass Hills. It has excellent exposure to winds from all directions. The site is indicative of the potential of a drainage divide that runs approximately east and west and is several miles long. The site is right next to a county road, but 28 miles from a paved road. Winter access sometimes is hampered by drifting snow and severe weather conditions.

The site is located in a sparsely populated area near the Canadian border. Most of the land in the area is privately owned. Electrical service in the area is provided by the Marias Electric Cooperative. One 115 kV line runs along the highway 28 miles south from Havre to Cut Bank. There is no commercial airport nearby.

Wind data was collected from November 18, 1983 to July 24, 1985. A Met One anemometer and a Campbell Scientific datalogger were used. The anemometer height was 33 feet.

Data recovery was poor to excellent, ranging from 0.0 percent in October to 99.9 percent in August. Overall data recovery was 76.6 percent.

Average monthly wind speeds ranged from 11.7 miles per hour in March to 15.5 miles per hour in September. The March figure may be inaccurate because of the poor data recovery that month. Average annual wind speed was 13.6 miles per hour.

Average monthly wind power ranged from 129.4 watts/m² in July up to 465.0 watts/m² in January.

Average wind speed did not vary much between seasons. Average seasonal speeds were 12.7 miles per hour in the summer, 13.2 miles per hour in the autumn, 14.2 miles per hour in the winter, and 14.1 miles per hour in the spring. In the winter, the highest wind speed occurred in mid-afternoon. In the spring, highest winds happened in the late afternoon and early evening. High winds in the summer were somewhat later still in the early evening. In the fall, the highest winds came in the early afternoon. Diurnal range of average wind speeds was greatest in the summer and somewhat less in the autumn and spring. The range was smallest in the winter.

The most common wind direction was from the north. Winds blew about four to nine percent of the time from most other directions; winds from the northeast through east-southeast were fairly uncommon. By direction, average wind speeds ranged from 20.4 miles per hour from the west to 5.6 miles per hour from the east.




Table IV - 98

Monthly Wind Speed Distribution

LIBERTY COUNTY - WHITLASH

Nemuo Kmtmgs/Smcoxc

Table IV - 99

Percentage Frequency Summary for Wind Speed

LIBERTY COUNTY - WHITLASH

| | | _ | e S | | | | | | | | | | | | | | | | | | |
|----------|---------------------|--|------------------------------|-------------------|--------------|------------|--------------|------|-------------------|------------|----------------|----------|------------------|--------|-------------|--------------|------|------|------|------|-----------|
| | | • | SPEED SPEED (MPH) (M/SEC) | 6.3 | 9 | 6.1 | 0.0 | 6.4 | 9 | 5 | တီ လ | 6.0 | 7.1 | 6.7 | 6.3 | . 4 | 9.9 | 6.4 | 6.3 | 6.3 | 6.4 |
| | | • | SPEED (MPH) (| 14.0 13.8 | 13.4 | 13.7 | 14.0 | 14.3 | 13.8 | 13.2 | 13.5 14.6 | 15.4 | 15.9 | 14.9 | 14.0 | 13.5 14.4 | 14.8 | 14.4 | 14.1 | 14.2 | 14.2 |
| | | 40.0 | >17.9 | 0.0 | 0.8 | 2.3 | 4.7 | 3,1 | 2.3 | 0.8 | 2.3 | 1.5 | 0.8 | 1.6 | 1.6 | ο α Ο σ | 0.0 | 0.0 | 0.8 | 8.0 | 1.5 |
| | | 35.1- 40.0 >40.0 | 15.7- 17.9 | 2.3 | 00 | 1:6 | 0.8 | 0.8 | 1.6 | 8.0 | æ æ | 2.3 | 2.3 | 2.3 | 8.0 | 4. 4. | 3.1 | 1.6 | 1.6 | 8.0 | 1.6 |
| | | 30.1- 35.0 | 13.5- 15.6 | 4.7 | 5.4 | 3.1 | 3, 5 1, 6 | 5.4 | , n | 4.7 | 4.0 8.2 | 7.7 | 8 0 2 2 | 2,3 | ۍ د د | ນຸ ທ - ທ | 4.7 | ນີ້ | 3.2 | 4.8 | 4.8 |
| | | 25.1- 30.0 | 11.2- | 7.0 | ຕຸຕ ຕຸຕ | 3.1 | 2.3 | 5.4 | 6.3 | 3,1 | പ് പ് | 6.2 | 3° 6 | 3.1 | 9,0 | 4.4 | 5.5 | 3.9 | 5.6 | 4.0 | 4.6 |
| | | 20.1- 25.0 | 9.0- 11.2 | 8.5 10.9 | 10.9 | 11.6 | 11.6 | 5.4 | 0°8 | 11.7 | 9./ 13.8 | 9.2 | 15.4 | 15.5 | 12.4 | 11.0 | 10.2 | 13.4 | 11.1 | 11.9 | 11.0 |
| | | 18.1- 20.0 | 8.1- 8.9 | 3.9 | 5.4 4.5 | 6.0 | 3.1 | 7.8 | 3.1 | 6.3 | 0.0 | 1.5 | 0 8 4 | 4.7 | 9,0 | 2.4 | 5.5 | 4.7 | 6.3 | 1.6 | 4.3 |
| _ | 58/1 | 0 (MPH) 16.1- 18 18.0 2 | 7.2- 8.0 | 4.7 5.4 | 4.7 8.5 | 2.3 | 2.3 | 3.1 | , 0 , 3 , 4 | 9.0 | ა ი. ა 4. | 8 | 7.7 | 10.9 | 4.7 | - · · | 7.1 | 4.7 | 4.8 | 6,3 | 5.5 |
| (WINTER) | . 07/24 | SPEED 14.1- 16.0 | 6.3- 7.2 | 6.2 5.4 | 3.1 | 5.4 4.0 | 8 5 5 | 5.4 | 7.0 | ب و ، و | 0.01 | 8.5 | 6.9 | 6.2 | ຜູ້ເ | , c | 8 | 7.1 | 6.3 | 8.7 | 6.8 |
| (WIN | 11/18/83 - 07/24/85 | MIND SPEED 12.1- 14.1- 1 14.0 16.0 | 5.4- 6.3 | 8.5 10.1 | 9.3 | 7.0 | 11.6 | 10.1 | 9.4 | 8.0 | 6.2 | 12.3 | യ്യ സ് | 6,3 | 6,0 | 7 | 7.9 | 7.9 | 11.9 | 9.5 | 8.8 |
| | 11/ | 10.1- 12. 12.0 14 | 4.5- 5.4 | 11.6 6.2 | 7.8 14.0 | 10.1 | 10.1 | 11.6 | 20.7 8.6 | 14.8 | 10.8 8.8 | 13.8 | 15.4 | 13.2 | 13.2 | 13.0 | 10.2 | 11.0 | 8.7 | 15,9 | 11.4 |
| | | 8.1- 10.0 | 3.6- | 10.9 9.3 | 9.3 | 7.8 | 6.2 | 9.3 | 7.0 | 2.8 | 13. 8.5 | 10.0 | 13.8 8.5 | 8 5 | 10.9 | 7.01 | 11.0 | 10.2 | 10.3 | 8.7 | 9.5 |
| | | 6.1- 8.0 | 2.7- 3.6 | 10.9 13.2 | 18.6 10.9 | 10.9 | 11.6 | 11.6 | 10.9 | 7.0 | 12.1 10.8 | 7.7 | 12.3 | 5.4 | 7.0 | - « - : | 10.2 | 13.4 | 14.3 | 10.3 | 10.8 |
| | | 4.1-6.0 | 1.8- | 10.9 12.4 | 8.5 11.6 | 15.5 | 12.4 | 14.0 | 11.7 | 10.2 | 9.2 | 6.9 | 6.5 | 7.0 | 7.0 | ر د د | 11.0 | 12,6 | 8.7 | 10.3 | 6.6 |
| | | 2.1-4.0 | 0.9- | 7.8 | 8.5 10.9 | 7.0 | 7.0 | 4.7 | 4.4 | 4.6 | 8 ° ° . | ۳ 8 . | | 7.8 | 12.4 | סיר | 4.7 | 3.1 | 5.6 | 3.2 | 6.8 |
| | | 0.1-2.0 | 0.1- 0.9 | 1.6 | 0.0 | 3.1 | 3°5° | 2.3 | 3.9. | 6.3 | 4. 4. 0. 0. | 2.3 | 7.7 | 2.3 | 8.0 | ۰۰ بر م | 0 | 0.8 | 0.8 | 3.2 | 2.3 |
| | | CALM | CALM | 0.0 | 1.6 | 0.0 | 0.0 | 0.0 | 0.0 | 0.8 | 1.5 | 2.3 | 0 1 2 2 | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | 9.0 |
| | | | | 1 2 | ω 4 | יט או | ۸ ۵ | ∞ α | 10 | =: | 13 23 | 7: | <u> </u> | 11 | <u></u> | 2 8 | ដ | 22 | ສ | 54 | tours |
| | | | | | | | | 2 | E | 0 | > | • | × | | | | | | | | all hours |

Table IV - 100

Percentage Frequency Summary for Wind Speed

LIBERTY COUNTY - WHITLASH

(SPRING)

11/18/83 - 07/24/85

| | CALM | 0.1-2.0 | 2.1-4.0 | 4.1- 6.0 | 6.1- 8.0 | 8.1- 10.0 | 10.1- 12.0 | WIND 2.1- 1 | SPEED 14.1- 1 | _ ; | | 20.1- 25.0 | • | | 35.1- 40.0 | >40.0 | 3 | à |
|-----------|-------|-------------|-------------------|-------------|-------------|--------------|---------------|-------------|----------------------------------|-------------|-------------|------------------|---------|-----------------|---------------|-------------|---------------------|--------|
| | CALM | 0.1- | 0.9- | 1.8-2.7 | 2.7- 3.6 | 3.6- | 4.5- 5.4 | 5.4- 6.3 |) (7 € 18 6.3- 7.2 | 7.2- 8.0 | 8.1- 8.9 | 9.0- | 11.2- 1 | 13.5- 1 15.6 | 15.7- 17.9 | >17.9 | SPEED (SPEED SPEED) | SPEE |
| | • | - | , | 100 | c | 9 01 | C L | , | - | с ц | , | | • | V | | c | 7 2 | 4 |
| | | | ٠ د د | 17.0 | ν, ο • | ٥.٠ د د د | ກໍເ | . | - 0 0 | יי אינ | , r | 4.5 | 4 0 | † r | - c | 900 | 3,0 | • • |
| | | ٠ | ָ מיני מיני | 14.8 | 10.4 | | × 0 | 10.4 | × ; | ָת מיני | 4. | د د ا | ۰ ۲ | ٧.٢ |) c |)) (| 13.5 | 0 4 |
| | | | ٠ د د | 12.6 | 10.4 | 11.9 | , , | , c | | ٠ ر د د | • | 1:1 | 4, r | ٠. د | ` c | 9 0 | 13.4 | ה ה |
| | | 7.7 | 2.5 | 13.4 | 14.2 | 7.0 | 10.4 | ى د ر | 7.0 | ر. د | 0. 0. | ر د د د | 2.0 | |))) | 9 0 | 12.3 | 0 4 |
| - | | ο ο Ο C | ם היס | ָ סינו | 20.5 | 11.3 | ر. د و | | o | , v | n α | 2.0 | , - | . A | | 9 0 | 12.6 | י ע |
| - | | ۰ د د | , α | 17.3 | 10.5 | 13.5 | 0 0 | , c | | ر اما د | 0 | 0 | 0.0 | 4 | 0 | 0 | 12.4 | , LC |
| | 8 1.5 | 1.5 | , w | 19.5 | 0.6 | 7.5 | 0.9 | 0.0 | 7.5 | , w | 8,3 | 0.6 | 4.5 | 3.0 | 0.0 | 0 | 12.5 | 5.6 |
| = | | 3.0 | 0.6 | 9.0 | 11.3 | 3.0 | 12.0 | 12.8 | 6.8 | 3.8 | 6.8 | 13.5 | 5.3 | 0.8 | 1.5 | 0.0 | 13.1 | 5 |
| | | 1.5 | 5,3 | 13.5 | 6.0 | 12.0 | 9.0 | | 6.0 | 6.8 | 8.9 | 16.5 | 2,3 | 3.8 | 0.8 | 0.0 | 13.8 | 6,2 |
| 0 1 | | 1.5 | 1.5 | 10.7 | 13.0 | 6.9 | 13.7 | 8.4 | 3.1 | 6.9 | 8.4 | 14.5 | 5,3 | 5,3 | 0.0 | 0.0 | 14.5 | 6,5 |
| <u>~</u> | | 0.8 | 0.8 | 5.5 | 10.2 | 14.1 | 9.4 | 11.7 | 6,3 | 7.0 | 7.8 | 13,3 | 4.7 | 7.8 | 0.0 | 0.0 | 15.4 | 6.9 |
| U 1 | | 1.5 | 1.5 | 2.2 | 11.9 | 11.9 | 8.0 | 10.4 | 12.6 | 4.4 | 10.4 | 11.1 | 7.4 | 4.4 | 0.7 | 0.0 | 15.4 | 6.9 |
| <u>~</u> | | 0.7 | 3,7 | 5.9 | 6.7 | 11.1 | 11.1 | 10.4 | 9.6 | 10.4 | 8.9 | ۍ ص | 7.4 | 3.0 | 0.7 | 0.7 | 15.1 | 6.8 |
| ~ | | 1.5 | 3.7 | 2.2 | 8.1 | 13.3 | 7.4 | 13,3 | 8. 9 | 8,9 | 3.7 | 14.8 | 8.1 | 3.0 | 2.2 | 0.0 | 15.6 | 7.0 |
| <u>~</u> | | 0.7 | 0.7 | 4.4 | 9.6 | 11.9 | 9.6 | 13,3 | 6.7 | 3.0 | 8,9 | 20.0 | 3.7 | 5.2 | 1.5 | 0.0 | 16.0 | 7.1 |
| T | | 0.7 | 2.2 | 9.6 | 5.2 | 8.1 | 10.4 | 9.6 | 11.9 | | 5.2 | 16.3 | 5.2 | 7.4 | 0.0 | 0.0 | 15.9 | 7.1 |
| ï | | 0.0 | 5.5 | 4.4 | 5.9 | 10.4 | 12.6 | 10.4 | 6.7 | 5.9 | 8,9 | 17.8 | 2.5 | 5.9 | 0.7 | 0.0 | 15.9 | 7.1 |
| ř | | 0.7 | 3.7 | 10.4 | 5.9 | 9.6 | 8.9 | 12.6 | 3.7 | 8.1 | 8.1 | 16.3 | 5,9 | 5.2 | 0.7 | 0.0 | 15.5 | 6.9 |
| Ñ | | 1.5 | 4.4 | 8.9 | 8.0 | 11.1 | 10.4 | 7.4 | 6.7 | 8.1 | 5.9 | 14.8 | 5,9 | 5.9 | 0.0 | 0.0 | 14.8 | 9.9 |
| 7 | | 1.5 | 3.7 | 8.1 | 15.6 | 11.1 | 9.6 | 10.4 | 5,9 | 3.0 | 8,9 | 16.3 | 3.7 | 1.5 | 0.7 | 0.0 | 13.8 | 6.2 |
| 73 | | 1.5 | 3.0 | 12.7 | 10.4 | 10.4 | 12.7 | 9.7 | 4.5 | 4.5 | 7.5 | 14.9 | 3.7 | 4.5 | 0.0 | 0.0 | 14.0 | 6.3 |
| 2 | | 2.2 | 9.0 | 8.2 | 11.2 | 9.7 | 10.4 | 0.6 | 5.2 | 8.2 | 5.2 | 15.7 | 5.2 | 3.0 | 0.7 | 0.0 | 14.0 | 6.3 |
| Ž | | 1.5 | 9.0 | 9.0 | 11.9 | 11.9 | 8.2 | 7.5 | 9.7 | 2.2 | 8.2 | 12.7 | 4.5 | 3.7 | 0.0 | 0.0 | 13.4 | 6.0 |
| ALL HOURS | 5 0.5 | 1.3 | 4.8 | 10.1 | 10.4 | 10.6 | 9.5 | 9.4 | 7.1 | 6.2 | 7.3 | 13.5 | 4.7 | 4.0 | 0.5 | 0.0 | 14.1 | 6.3 |
| : | | | ! | | | | | | | | | | | | | | | |

Table IV - 101

Percentage Frequency Summary for Wind Speed LIBERTY COUNTY - WHITLASH

(SUMMER)

11/18/83 - 07/24/85

| 0.0 | | | | | |
|---|---|---------------------------|------------------------------|---|-----------|
| AV SPEED (M/SEC | 0,0,0,4,4,4,4,4,4,4,4,4,4,4,4,4,4,4,4,4 | 7.4.4 5.2.2 | 5.7 6.0 6.2 6.2 | ည်တွင် အသည်။ သည်သည် သည် သည် သည် | 5.7 |
| AV SPEED S (MPH) (M | 12.1 12.2 12.1 11.3 10.6 | 10.5 10.4 11.5 | 12.8 13.3 13.9 | 14.1 14.2 14.6 14.6 12.6 12.3 12.5 12.5 | 12.7 |
| >40.0 | 0.00 | 0000 | 0.0 | 0.0 0.0 0.0 0.0 0.0 | 0.2 |
| 35.1- 40.0 15.7- 17.9 | 0.00 | 0.000 | 0.0 | 0.0 0.0 0.0 0.0 0.0 0.0 | 0.3 |
| 30.1- 35.0 35.0 13.5- 3 | 7.0 0.0 0.0 0.0 | 7.00.0 | 0.0 | 2.2.2.2.2.4.1.1.2.2.1.1.1.2.2.1.1.1.2.2.1.1.1.2.2.1 | 0.9 |
| 25.1- 30.0 30.0 11.2- 1 | | 0.0 2.7 4.4 | 2.1 2.1 5.5 | 21.22.55.55.11.22.88 | 2.8 |
| 20.1- ; 25.0 9.0-] | _ | 6.2 6.2 10.3 7.6 | 9.0 12.4 9.7 7.6 | 111.7 113.1 113.4 113.9 13.9 7.6 8.3 | 9.6 |
| 18.1- 2 20.0 20ND) 8.1- 8.9 | 7.88.4.2.2.4.6 0.81.7.8.6 | 9.6 11.0 7.5 | 6.9 4.1 8.3 | 6.7.6 6.9.7.6 6.9.7.6 6.9.9 6.9.9 | 7.2 |
| (MPH) 16.1- 1 18.0 18.5 7.2- 8.0 | 8.9 11.0 6.2 6.2 8.4 | 2.7 2.1 7.6 | 5.5 7.6 9.7 10.3 | 12.4 12.4 12.4 6.3 9.0 9.0 5.6 | 7.9 |
| SPEED 14.1- 1 16.0) (METE 6.3- | 10.3 6.8 7.5 7.5 | 6.8 6.2 7.6 | 8.01 8.3 9.0 | 9.0 6.9 7.6 6.3 7.0 7.0 | 7.7 |
| WIND 2.1-1 14.0 SPEEI 5.4- | 11.6 8.9 8.9 11.0 6.8 | 9.6 6.8 7.5 | 15.9 12.4 9.7 10.3 | 115.2 111.0 111.1 111.1 7.6 5.6 111.1 | 10.2 |
| 10.1- 12 12.0 1 WIND 4.5- 5.4 | 7.5 9.6 10.3 10.3 | 10.3 10.3 10.3 | 11.7 11.7 13.8 17.9 | 9.0 111.0 11.8 8.3 13.2 13.2 8.5 | 11.4 |
| 8.1-1 10.0 3.6- | 6.8 6.8 14.4 13.0 | 11.0 10.3 11.7 | 14.5 16.6 12.4 9.0 | 113.1 111.8 111.8 11.1 12.0 12.0 | 12.2 |
| 6.1- 8.0 2.7- 3.6 | 11.6 14.4 8.9 13.0 17.8 | 18.5 15.8 14.5 | 10.3 9.7 15.2 | 6.2 9.7 11.7 15.3 13.2 13.2 12.7 | 12.9 |
| 4.1- 6.0 1.8- 2.7 | 9.6 8.2 13.0 11.6 17.1 | 14.4 17.1 11.0 | 10.3 5.5 6.9 | 111.0 7.6 7.6 7.6 6.3 9.9 | 7.6 |
| 2.1- 4.0 0.9- 1.8 | | | | 0.6.2.1.1.2.2.4.6.0 | 6.1 |
| 0.1- 2.0 0.1- 0.1- | 1.144.1. | 0.7 | 0.000 | 7.000.000.000.000.000.000.000.000.000.0 | 6.0 |
| САГМ | 000000 | 0000 | 0000 | 0000000000 | 0.0 |
| | H0W41001 | ~ & 6 Q ; | 1224 | \$1222222 \$222222 | OURS |
| | | = (| 0 5 | œ | ALL HOURS |
| | | | | | |

Table IV - 102

Percentage Frequency Summary for Wind Speed

LIBERTY COUNTY - WHITLASH

| | | | | | | | | (AUTUMN) | NWI | | | | | | | | | |
|----------------|-------|--------------------------|---------------------------|-----------------------------|-----------------------------|------------------------------|-----------------------------|-----------------------------------|--------------------------|--------------------------|---------------------------------|---------------------------|-------------------|-----------------------------|---------------|-------|------------------------------|---------|
| | | | | | | | 11/ | 11/18/83 - 07/24/85 | - 07/2 | 58/1 | | | | | | | | |
| | CALM | 0.1-2.0 | 2.1-4.0 | 4.1- 6.0 | 6.1- 8.0 | 8.1- 10.0 | 10.1- 12.0 | 1.0.1 1.0.1 | 1.1- 6.0 | (MPH.) 5.1- 18.0 | 0.0 | 20.1- 3 25.0 | 25.1- 30.0 | 30.1- 35.0 | 35.1- | >40.0 | ; | |
| | CALM | 0.1- 0.9 | 0.9- | 1.8- 2.7 | 2.7- | | WIND 3 | 5.4- 6.3 | ₩ .2. | % \ | 8.1- 8.9 | 9.0- | | 13.5- 15.6 | 15.7- 17.9 | >17.9 | SPEED SI (MPH) (M. | ᄶᅗ |
| 1 2 | | 1.5 | 4.6 4.6 | 13.8 13.8 | 10.8 13.8 | 12.3 12.3 | 7.7 | 10.8 13.8 | 4.6 | 7.7 | 6.2 | 7.7 | 3.1 | 7.7 | 0.0 | 0.0 | 13.2 13.6 | |
| ω ≰1 | | 0.0 | 7 7 4 6 | 7.7 | 12.3 10.8 | 20.02 13.8 | 9.2 18.5 | 10.8 | 3.1 | | m m, | 7.7 | 9.2 | 4.1 7.1 7.1 | | 000 | 13.4 | |
| 1 Q Q | | 0.0 | 7.7 | 10.9 | 21.5 | 15.4 | 9.7 | 4.6 | 6.2 | 1.5 | 3.1.0 | 6.2 | 7.7 | 4.6 7.6.7 | הייה הייה | 0.0 | 12.8 | ·· |
| - ∞ σ | | 9.2 | 7.7 | 10.8 | 10.8 | 18.5 | 6.2 | 7.7 | 4.6 | 1.5 | 1.5 | 10.8 | 7.7 | 0.55 | | 0.0 | 12.1 | |
| | | 0.0 | 15.9 | 9.5 | 15.9 | 12.7 17.5 | 9 9 | 3.2 | 6.3 | 3.2 | 1.6 | 15.9 11.1 | 3.2 | 0.0 | 1.6 | 0.0 | 12.3 12.9 | |
| | | 3.4 | 9.1 | 6.1 | 15.5 | 10.3 | 9.1 | 6.1 | 1.7 | 3.4 | 1.7 | 12.1 | 2.0 | 3.4 | 3.4 4.0.4 | 1.5 | 14.2 15.1 | |
| R 15 | | 1.5 | 4.7 | 7.6 12.1 6.1 | 7.6 12.1 | 10.6 | 7.0 12.1 16.7 | 9.1 | | 9.1 | 6.1 | 9.1 | 9.1 | 3.0 | 0.0 | 0.0 | 15.2 | |
| 17 18 19 | | 3.0 6.1 0.0 | 7.6 9.1 9.2 | 13.6 7.6 16.9 | 3.0 | 12.1 9.1 10.8 | 12.1 9.1 16.9 | 7.6 10.6 3.1 | 12.1 6.1 12.3 | 3.0 6.1 6.1 | 6.1 1.5 | 12.1 9.1 7.7 | 3.0 3.1 | 0.4.4 0.6.0 | 0.0 | 0.00 | 13.3 12.8 12.7 | , |
| 82222 | 00000 | 0.0 1.6 1.6 5.3 | 10.8 1.6 7.9 7.0 | 13.8 6.3 14.0 14.0 | 7.7 12.7 19.0 12.7 | 12.3 14.3 17.5 11.1 | 13.8 6.3 14.3 14.0 | 7.7 14.3 9.5 11.1 5.3 | 7.7 9.5 1.6 5.3 | 6.2 7.3 7.9 5.3 | 7.7 5.3 3.2 8.3 8.8 | 4.6 7.9 14.3 8.8 | 3.1 3.5 3.5 | 3.4.4.1 8.2.8.9 8.8.9 | 0.0000 | 00000 | 12.5 12.5 12.8 11.8 | |
| ALL HOURS | | 2.0 | 7.4 | 11.2 | 13.0 | 13.3 | 10.1 | 3 | 4.9 | 4.4 | 4.2 | 10.4 | 4.7 | 4.0 | 1.4 | 0.3 | 13.2 | |

0.1.10877488848084077898778

SOURCE: GEORESEARCH, INC.

Table IV - 103

Annual Wind Rose Distribution LIBERTY COUNTY - WHITLASH

11/18/83 - 07/24/85

| <direction< th=""><th>SPEED (M/SEC)</th><th>0.1- 1.0- 1.0- 1.0- 1.0- 1.0- 1.0- 1.0-</th><th>TOTAL AV SPEED</th><th>(M/SEC)</th></direction<> | SPEED (M/SEC) | 0.1- 1.0- 1.0- 1.0- 1.0- 1.0- 1.0- 1.0- | TOTAL AV SPEED | (M/SEC) |
|--|---------------|--|----------------------------|--------------|
| NNW TOTAL | 0, | 4,5044040000000000000000000000000000000 | | 13.6 |
| ¥. | | 0.0000000000000000000000000000000000000 | | 14.9 6.7 |
| Ž | | | 4.7 | 15.1 6.8 |
| MNM | | 0.0000000000000000000000000000000000000 | 0.8 | 19.4 8.7 |
| 3 | | 000000000000000000000000000000000000000 | 9.7 | 9.1 |
| MSM | | 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0 | 7.4 | 8.1 |
| 3 | | 0.0000000000000000000000000000000000000 | 2.4 | 4.7 |
| SS | | 0.0000000000000000000000000000000000000 | 8, 6 | 4.2 |
| S | | 0.0000000000000000000000000000000000000 | 6.4 | 4.1 |
| SSE | | 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0 | 7.8 | 4.3 |
| 뽔 | | 0.000000000000000000000000000000000000 | 6. 5 6. 4 | 14.4 6.4 |
| ESE | | | | ν. 4 8. 8 |
| ш | | | | 2.5 |
| H | | | 0.1 6.1 | 2.9 |
| 밀 | | | 8, 7 | 3.3 |
| ¥ | | 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 | | 5.1 |
| z | | 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0 | 13.7 | 5.8 |
| DIRECTIONS | SPEED (MPH) | 0.1-1.0 1.1-2.0 2.1-3.0 3.1-4.0 8.1-6.0 E 5.1-6.0 E 7.1-8.0 0 8.1-9.0 1 11.1-12.0 1 11.1-12.0 1 11.1-12.0 1 11.1-12.0 1 11.1-12.0 1 11.1-12.0 2 14.1-13.0 1 18.1-19.0 1 18.1-19.0 2 1.1-20.0 2 2 1.1-20.0 3 3 1.1-30.0 3 3 1.1-30.0 3 3 1.1-30.0 3 3 1.1-30.0 3 3 1.1-30.0 3 4 0.0 CALM | IOIAL AV SPEED (MBU) | (M/SEC) |




Table IV - 104

Coefficients of Weibull Distribution LIBERTY COUNTY - WHITLASH

11/18/83 - 07/24/85

| | SCALE | SHAPE |
|-----------|-----------------------|------------|
| MONTH | FACTOR (C) (M/SEC) | FACTOR (K) |
| JANUARY | .368 | 460 |
| FEBRUARY | \sim | .749 |
| MARCH | .734 | 665 |
| APRIL | .820 | .776 |
| MAY | .960 | ~ |
| JUNE | .664 | ø |
| JULY | ~ | LC: |
| AUGUST | 976. | ~ |
| SEPTEMBER | 7.5464 | 1.5741 |
| OCTOBER | - | \vdash |
| NOVEMBER | \sim | .820 |
| | .274 | 727 |
| YEAR | 6,4634 | 1.7458 |

| , | | | |
|---|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

NORRIS HILL MADISON COUNTY

41 57 W (Site No. 157 on Map II-1). Elevation at the site is 5,675 feet. This \$77% 22.9 miles per hour in December. Average annual wind speed was 17.0 miles **58** The Norris Hill site is located ten miles north of Ennis at 45 29 **42** N and 111 monitoring site is part of the wind monitoring program of the Montana Department of Natural Resources and Conservation.

could affect the winds at the site. However, both the ridge on which the site is The site is located at the crest of Norris Hill on a finger ridge. Norris Hill is at the head of the Madison River valley, which runs more or less due north. A hill to the east and southeast that is approximately 525 feet higher than the site ocated and the hill to the east have slopes in the 20 to 50 degree range and the site is otherwise well exposed to the wind. In addition, there is a very evident funneling of winds up the draw where US 287 crests Norris Hill from the south, which could compensate for the hill to the east. The site is representaison and Jefferson ranges. The range of hills is six to eight miles long, several miles wide and contains many knobs and ridges that would be suitable for the nstallation of wind generating equipment. The site is just west of state Highiive of a range of hills that runs approximately east and west between the Madway 287, but winter access still can be difficult.

trical service in the area is provided by the Montana Power Company. A 💌 🌔 kV line runs south of the site and a 100 kV line runs to the north. Both lines The site is located on private land. Much of the land in the area is held by the Bureau of Land Management; the state also owns some land nearby. Eleccome out of Montana Power's Madison powerhouse in Beartrap Canyon, man, 35 miles to the northeast. There is a private landing field five miles south three miles east of the site. The nearest commercial airport is outside of Bozeof the site in the Madison valley.

Wind data collection began January 10, 1984. Data through March 31, 1986 was available for analysis. Monitoring is scheduled to continue at least through June 1987. A Met One anemometer and a Campbell Scientific datalogger were used. The anemometer height was 33 feet. Data recovery was poor to excellent, ranging from 45.6 percent in November to 99.9 percent in May, July, and September. Overall data recovery was

Average monthly wind speeds ranged from 11.6 miles per hour in July to

Average monthly wind power ranged from 99.3 watts/m2 in July to 832.3 watts/m² in December. Average seasonal speeds were 12.9 miles per hour in the summer, 16.8 miles in early to late afternoon. High winds in the summer were a little later than in and late afternoon. Diurnal range of average wind speeds was greatest in the hour in the spring. In the winter and spring, the highest wind speed occurred he winter and spring. The highest winds in the autumn were between noon per hour in the autumn, 21.5 miles per hour in the winter, and 16.4 miles per summer, least in the winter, and about the same in spring and autumn.

The wind blew most frequently from the south-southeast through the southwest, that is, from directly down the valley. The winds came from the speeds ranged from 7.5 miles per hour from the east-southeast to 20.0 miles north-northeast and northeast about 20 percent of the time, and otherwise came very infrequently from the other directions. By direction, average wind ber hour from the south and south-southwest.




Table IV - 105

Monthly Wind Speed Distribution

MADISON COUNTY - NORRIS HILL

01/10/84 - 03/31/86

| | 3 | 0.1-0.4 | 5-0.9 | .0- 1.3 | .4- 1.8 | .9- 2.2 | .3- 2.7 | .8- 3.1 | .2- 3.6 | .7- 4.0 | .1- 4.5 | 6- 4-9 | 0-5.4 | 5-5.8 | .9-6.3 | .4- 6.7 | .8- 7.2 | .3- 7.6 | .7- 8.0 | .1-8.5 | 6-8-9 | .0-11.2 | .3-13.4 | .5-15.6 | .7-17.9 | >17.9 | | | | | | | |
|------|----------|---------|---------|---------|-----------|-----------|---------|---------|---------|---------|------------|--------|-------------|--------------|--------|---------|---------|---------|---------|-----------|-----------|-----------|-----------|-----------|-----------|---------|---------|------------------------|---------------|-----------------------|--------------|--------------|-------------|
| YEAR | | 2.0 | | | | | | | | | | | | | | | | | | | | | | | | 1.7 | | 17.0 | 7.6 | | 14.3 | 0 | 0.00 |
| 330 | C | 0.0 | 1.0 | 1.0 | 1.0 | 1.6 | 1.4 | 1.9 | 1.9 | 5.6 | 2.2 | 1:1 | 2,3 | 2,5 | 2,3 | 2.1 | 1.7 | 3,3 | 3.1 | 3,3 | 2.2 | 16.7 | 19.4 | 11.5 | 8.3 | 2 | | 22.9 | | | _ | 6 | |
| NOV | c | 0.0 | 0.8 | 0.0 | 1.2 | 1.1 | 2,3 | 1.4 | 3,7 | 3,5 | 4.3 | 3.0 | 5.2 | 2.7 | 5.8 | 3,3 | 3.7 | 4.9 | 4.4 | 6.1 | 2 | 18.3 | 9.6 | 4.4 | 2.9 | 8° 0 | | 17.9 | 8.0 | | 400.9 | 9 29 | 0 0 1 |
| Ω | c | 000 | 0.6 | 0.4 | 1.8 | 6.0 | 2.2 | 2.7 | 2.2 | 1.5 | 2.8 | 3.2 | ۳ ش | 2.9 | 2.5 | 2.2 | 2.9 | 5,3 | 4.7 | 5.4 | 3.4 | 20.0 | 16.3 | 9.4 | 2.4 | 1.0 | | 20.0 | 8 | | 517.4 | 0 | 23.0 |
| SEP | • | 0.0 | 6.0 | 1.4 | 2.8 | 3.2 | 3,3 | 4.6 | 6,3 | 5.6 | 6.4 | 4.2 | 8 | 4.0 | 4.4 | 3.6 | 4.0 | 5.4 | 3,8 | 3,9 | 3.6 | 12.8 | 5,3 | 2.9 | 6.0 | 0.6 | | 14.5 | 6.5 | | 245.0 | 8 | |
| AUG | 0 | 0.0 | 0.5 | 1.6 | 2.4 | ကိ | 5.1 | 3,5 | 5.5 | 5.5 | 5.9 | 6.1 | 7.4 | 2,3 | 8,3 | o, o | 4.0 | 5.2 | 5.6 | 2.8 | 2.4 | 9,5 | 3.9 | 1.8 | 9.0 | 0.3 | | 13.5 | 0.9 | | 187.0 | 9 | 0.66 |
| 当 | C | 000 | 0.6 | 1.0 | 3.0 | 3.0 | 6,3 | r, O | 7.1 | 7.1 | 7.4 | 9.9 | 8.4 | က် | 7.1 | 4.6 | 5.2 | 5.2 | 2.8 | 4.3 | 2,3 | 4.8 | 0.4 | 0.0 | 0.1 | 0.0 | | 11.6 | 5.2 | | 99.3 | 8 | 99.9 |
| Ŋ | c | 0 | 0.6 | 1.3 | 2.4 | 3.2 | 6.0 | 4.0 | 6.0 | 5,3 | 6.9 | 5.2 | 7.2 | 4.7 | 5.7 | 4.7 | 4.3 | 5.6 | 3.6 | 4.3 | 2.9 | 10.1 | 3.4 | 1.5 | 0.4 | 0.7 | | 13.6 | 6.1 | | 197.3 | 8 | |
| MAY | c | 9.0 | 0.5 | 0.7 | 2.0 | 2.6 | 4.6 | 4.0 | 5,9 | 5.0 | 5.7 | 4.6 | 6.5 | ຂ້ | 6.4 | 4.9 | 4.0 | 4.0 | 3.4 | 3.1 | 2.9 | 11.7 | 6.1 | 2.8 | 1.9 | 1.3 | | 15.1 | 6.8 | | 297.1 | 8 | 99.9 |
| | | 9.0 | | | | | | | | | | | | | | | | | | | | | | | | | | 17.0 | 7.6 | | 380.5 | 4 | 4.06 |
| MAR | - | 0.2 | 0.7 | 1.2 | 2.4 | 5.6 | 4.3 | 2.7 | 4.1 | 2.9 | 3.8 | 3.0 | ω. | 3.4 | 5.1 | 4.2 | 4.4 | 5.6 | 3.7 | 5,1 | 4.0 | 14.5 | 9.1 | 5.2 | 1.9 | 2.0 | | 17.1 | 7.6 | | 407.4 | 2,00 | 0.57 |
| FEB | 0 | 0.0 | 0.7 | 1,3 | 1.6 | 1.8 | 2,3 | 1.8 | 2.1 | 2.9 | 3.8 | 2.1 | 3.1 | 2.4 | 3,3 | 2.0 | 2.7 | 3.6 | 2.9 | 4.1 | 3.4 | 16.7 | 14.0 | 11.3 | 0.9 | 3.7 | | 8.0 | 9,3 | | 688.1 | 6 | 1.60 |
| JAN | - | 0.0 | 0.7 | 1.0 | 1.2 | 1.3 | 2.2 | 1.4 | 2.0 | 2.1 | 3.7 | 2,3 | 2.5 | 2.2 | 2.2 | 2.3 | 1.9 | 3.4 | 5.9 | 3.2 | 3.5 | 19.4 | 17.6 | 12.4 | 4.7 | 2.4 | | 21.1 | 9.4 | | 677.5 | 5 | 1.56 |
| | 250 | 0.1-1.0 | 1.1-2.0 | 2 | P 3.1-4.0 | E 4.1-5.0 | 5.1 | _ | | ω | I 9.1-10.0 | 10.1 | E 11.1-12.0 | \$ 12.1-13.0 | 13.1 | _ | | 16.1 | 17.1 | 18.1-19.0 | 19.1-20.0 | 20.1-25.0 | 25.1-30.0 | 30.1-35.0 | 35.1-40.0 | ×40.0 | AVERAGE | SPEED (MPH) Average | SPEED (M/SEC) | AVERAGE WIND POWER | (WATTS/M**2) | PERCENT DATA | RECOVER |

NAUU MUHUN/SHUDNO

ANEMOMETER HEIGHT = 10 METERS = 33 FEET NUMBER OF OBSERVATIONS = 16743
PERCENTAGE DATA RECOVERY = 85.8
SOURCE: GEORESEARCH, INC.

Table IV - 106

Percentage Frequency Summary for Wind Speed

MADISON COUNTY - NORRIS HILL

(WINTER)

01/10/84 - 03/31/86

| | SPEED (M/SEC) | 9,000,000,000,000,000,000,000,000,000,0 | 9.6 |
|-------------------------------------|------------------|--|-----------|
| Α | SPEED (MPH) (| 21.2 22.3 22.3 22.3 22.3 22.3 22.3 22.3 | 21.5 |
| >40.0 | >17.9 | ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, | 2.8 |
| 35.1- 40.0 | 15.7- 17.9 | ooga, uga, uga, uga, uga, uga, uga, uga, u | 5.0 |
| 30.1- 35.0 | 13.5- 15.6 | 11.0 11.0 11.0 11.0 11.0 11.0 11.0 11.0 | 13.7 |
| 25.1- 30.0 | 11.2- | 12.1 11.3 11.6 11.6 11.6 11.6 12.9 12.9 12.9 12.9 16.0 16.0 16.0 16.0 16.0 16.0 16.0 16.0 | 13.4 |
| 20.1- 25.0 | 9.0- 11.2 | 20.0 17.9 17.9 17.9 18.6 18.6 19.0 19.0 19.0 19.0 19.0 19.0 24.3 21.5 21.5 21.5 21.5 21.5 | 21.0 |
| 18.1- 20.0 COND) | | , a a a a a c c c c c c c c c c c c c c | 6.7 |
| (MPH) 16.1- 18.0 TRS/SE | | , , , , , , , , , , , , , , , , , , , | 6.4 |
| SPEED 14.1- 16.0 D (MET | 6.3- | , oo ro ro 4 4 4 6 6 9 7 10 10 10 10 10 10 10 10 10 10 10 10 10 | 4.3 |
| WIND 12.1- 1 14.0 ID SPEED | 5.4- 6.3 | , 4 സ | 5.0 |
| 10.1- 1: 12.0 WIND | 4.5- 5.4 | นูญญู่และนูญหูลูญญู่ลูญสู่ผูญสู่ลูญผู้สู่ผู้ผู้ หูนดอยสพสอสพิดิดดินยนตสตสินิทินา | 4.6 |
| 8.1- 10.0 | | ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, | 5.9 |
| 6.1- 8.0 | 2.7- | . 4 4 | 3.7 |
| 4.1- 6.0 | 1.8- 2.7 | រល់ឃុំ ក្នុងក្នុងក្រុងប្រជុំ ក្នុងក្នុងក្នុងក្នុង រល់ស្គាល់ស្គាល់ប្រភពក្រុងក្នុងក្នុងក្នុងក្នុង | 3.6 |
| 2.1- | 0.9- | | 2.4 |
| 0.1-2.0 | 0.1- | 10111000000000000000000000000000000000 | 0.9 |
| CALM | CALM | | 0.6 |
| | | 22222222222222222222222222222222222222 | ALL HOURS |
| | | I 0 D & | ALL I |

Table IV - 107

Percentage Frequency Summary for Wind Speed MADISON COUNTY - NORRIS HILL

(SPRING)

(DATE TO)

01/10/84-03/31/86

| | | | 7.0 | 7.0 | 6.9 | 6.9 | 6.9 | 6.9 | 6.9 | 7.0 | 7.3 | 7,5 | 7.7 | 8.1 | 8.2 | 8 | 8 | 8.2 | 7.9 | 7.6 | 7.2 | φ. 8 | 6.7 | 6.8 | 6.8 |
|------------------------|---------------------|------|------|------|--------|---------|------|--------|--------|------|------|------|------|------|------|------|------|------|--------|---------|------|---------|------|------|------|
| à | SPEED (APE) | 15.8 | 15.7 | 15.6 | 15.4 | 15.4 | 15.5 | 15.4 | 15.4 | 15.7 | 16.4 | 16.8 | 17.3 | 18.1 | 18.3 | 18.5 | 18.3 | 18.3 | 17.7 | 17.0 | 16.1 | 15,3 | 15.1 | 15.1 | 15.3 |
| >40.0 | >17.9 | | 0.5 | 0.5 | 0.5 | 0.0 | 0.0 | 0.5 | 1:1 | 1.6 | 1.1 | 2.7 | 2.7 | 2.1 | 2.1 | 4.2 | 1.6 | 2.1 | 1:1 | 1:1 | 1:1 | 0.0 | 0.5 | 0.5 | 1.1 |
| 35.1- 40.0 | 15.7- 17.9 | 1.6 | 0.5 | 0.5 | 0.5 | 3.2 | 1:1 | 1.1 | : | 1.6 | 2.7 | 1.6 | 2.7 | 3.2 | 4.8 | 2.6 | 3.7 | 3,2 | 3.2 | 2.1 | 1.6 | 1.1 | 1.1 | 1.6 | 0,5 |
| 30.1- 35.0 | 13.5- 15.6 | 3.7 | 5,3 | 4.3 | 4.3 | 3.7 | 5.9 | 2.7 | 3.2 | 4.3 | 5,3 | 5,3 | 3.8 | 3.7 | 4.2 | 8 | 6.9 | 7.4 | 6.3 | 6.4 | 5,9 | 4,3 | 3.2 | 2.7 | 3.8 |
| 25.1- 30.0 | 11.2- | 6.4 | 5,3 | 6.4 | ည့် | 5,3 | 5,3 | 5,9 | 6.4 | 4.8 | 3,7 | 7.0 | 5.9 | 9.5 | 7.4 | 9.0 | 7.4 | 6,3 | 8 5 | 5,9 | 4.3 | 4.3 | 3.2 | 3.2 | 4.3 |
| 20.1- 25.0 | 9.0- 11.2 | 15.4 | 16.0 | 16.5 | 16.0 | 11.7 | 12.3 | 18.7 | 13.4 | 13.4 | 14.4 | 13,4 | 16.1 | 21.2 | 17.5 | 13.8 | 19.0 | 20.6 | 14.3 | 18.1 | 16.0 | 17.6 | 17.6 | 15.6 | 14.1 |
| 18.1- 20.0 | 8.1- 8.9 | 8.0 | 7.4 | 5,3 | ထို | 10.6 | 9.1 | 5,9 | 5.0 | 5,3 | 10.7 | 7.5 | 8.1 | 6.9 | 10.6 | 13.2 | | 6,3 | 6,9 | 8. 0 | 6.4 | 8,6 | 5,3 | 8.6 | 7.1 |
| (MPH) 16.1- 18.0 | 7.2- 7.2- 8.0 | 5.9 | 6.4 | 10.1 | 5,9 | 9.6 | 11.2 | 7.0 | 7.0 | 11.2 | 8.6 | 8.6 | 7.6 | 9.0 | 11.1 | 6,3 | 9.5 | ນໍ້າ | 7.9 | 8.0 | 7.0 | 8.6 | 10.2 | 6.5 | 9.8 |
| SPEE(14.1- 16.0 | 6.3 7.2 | 8,55 | 6.9 | 10.1 | S S | ο. Θ | 7.0 | 8.6 | 11.8 | 9.6 | 8.0 | 11.2 | 10.2 | 10.6 | 6.3 | 6,9 | 6,3 | 10.1 | 11.6 | 6.4 | 9.6 | 7.0 | 9.1 | 10.2 | 12.0 |
| MINE 12.1- 14.0 | | 9.6 | 12.8 | 5,9 | 11.7 | 10.1 | 9.1 | 10.2 | 13,4 | 9.1 | 11.2 | 10.2 | 11.8 | 3.7 | 9.0 | 9.5 | ထိ | 14.8 | 10.6 | 13,3 | 8.6 | 10.7 | 9.1 | 8.6 | 10.3 |
| 10.1-] 12.0 | 4.5- | 13,3 | 10.6 | 13.8 | 8 | 6.4 | 8,6 | 10.7 | 12.3 | 12.8 | 8.0 | 4.8 | 4.3 | 5.8 | 6.3 | 7.4 | 7.9 | 5,3 | 6.3 | 8.0 | 12.3 | 5.9 | 10.7 | 12.9 | 9.2 |
| 8.1- 10.0 | 3.6- | 12.2 | 10.1 | 8,5 | 6.4 | 6.9 | 10.7 | 8 0 | 3.7 | 8.0 | 0.0 | 10.2 | 8.1 | 6.3 | 6.3 | 7.4 | 6,3 | 6.3 | 9.5 | 6.9 | 8.0 | 9.1 | 8.0 | 10.2 | 9.2 |
| 6.1- 8.0 | 2.7-3.6 | 6.4 | 6.9 | 4.8 | 0.6 | 12.2 | 8.0 | 8.0 | o o | 4.8 | 8.0 | 5,9 | 5,9 | 7.4 | 6.9 | 6.9 | 7.4 | 6.9 | 6.9 | 4.8 | 9.1 | 8.6 | 11.2 | 10.2 | 9.2 |
| 4.1- 6.0 | 1.8- | 5.9 | 6.9 | 6.4 | 10.1 | & 0 | 6.4 | 7.5 | 10.2 | 6.4 | 5,9 | 8.6 | 8.1 | 8.5 | 4.8 | ည် | 3.2 | 3.2 | 4.8 | 6.4 | 7.0 | 11.8 | 7.5 | 4.8 | 3.8 |
| 2.1- 4.0 | 0.9- | 1.6 | 4.3 | 5.3 | 2.7 | 2.7 | 3.7 | 4.3 | 2.1 | 4.8 | 3.2 | 3.2 | 2.2 | 1.6 | 2.1 | 0.5 | 3.7 | 2.1 | 2.1 | 4.3 | 2.7 | 2.1 | 1.6 | 3.8 | 3.8 |
| 0.1-2.0 | 0.1- | 1:1 | 0.0 | 1.6 | 2.1 | 1.6 | 1.6 | 1:1 | 2.1 | 2.1 | 1:1 | 0.0 | 0.5 | 0.5 | 0.5 | 0.5 | 0.0 | 0.0 | 0.0 | 0.5 | 0.5 | 0.5 | 1:1 | 0.5 | 1.6 |
| CALM | CALM | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.5 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| | | | ~ | m · | ♥ | ហ | 9 | _ | ω | 6 | 2 | Ξ | 12 | 13 | 14 | 15 | 16 | 11 | 18 | 13 | ଛ | ಸ | 8 | 23 | 24 |

SOURCE: GEORESEARCH, INC.

2.0 1.2 16.4

4.7

5.9

7.9 16.0

8.3

8.9

8.1 8.8 10.1

6.7 7.6

ALL HOURS 0.0 0.9 2.9

Table IV - 108

Percentage Frequency Summary for Wind Speed MADISON COUNTY - NORRIS HILL

(SUMMER)

01/10/84 - 03/31/86

| _ | 98 | · | | _ | _ | _ | | | | | | | _ | | | | _ | _ | _ | _ | | | | | | _ | ~ |
|------------------------|---------------------|--|------|------|------|----------|--------|------|------|------|----------|------|----------|------|----------|------|------|------|------|--------|--------|------|--------|------|------|------|-----------|
| 2 | SPEED | ֭֓֞֝֝֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֡֓֓֡֓֓֡֓֡֓֓֓֡֓֡֡֡֡֓֡֓ | 5. | 2.0 | 4 | o. | 5.1 | 5. | 5.2 | 5.4 | ഹ | ഹ | rų D | 6.1 | 9 | 6.6 | 6. | 2.0 | 7.0 | 9 | 9 | 6.1 | ۍ ص | 5.2 | 5. | 2 | 5.8 |
| X | SPEED | (11.11) | 11.5 | 11.1 | 10.9 | 11.1 | 11.5 | 11.5 | 11.7 | 12.1 | 12.4 | 12.9 | 13.2 | 13.7 | 14.0 | 14.8 | 15.0 | 15,8 | 15,6 | 15,3 | 14.5 | 13,6 | 12,6 | 11.6 | 11.5 | 11.3 | 12.9 |
| >40.0 | >17.9 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0,5 | 0 | 0.5 | 1:1 | 1:1 | 0.5 | 0.2 | 0.5 | 0.5 | 0.5 | 0.0 | 0.0 | 0.0 | 0.0 | 0.3 |
| 35.1- 40.0 | 15.7- | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 1.7 | 0.5 | 0.0 | 1:1 | 0.5 | င္ | 1:1 | 0.5 | 0.0 | 1:1 | 0.0 | 0.0 | 0.0 | 0.3 |
| 30.1- 35.0 | 13.5- | • | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | : | 0.5 | 1:7 | 3. 8. | 3.8 | 3,8 | 5,4 | 1.6 | 2.7 | 1.6 | 1.6 | 1:1 | 0.0 | 0.0 | 0.0 | 1.2 |
| 25.1- 30.0 | 11.2- | | 0.5 | 0.0 | 1.6 | 1:1 | 0.0 | 0.5 | 1:1 | 0.5 | 1:1 | 1.6 | ლ დ | 3,3 | 2.7 | 3,3 | 1.6 | 3,3 | 5,4 | 3,3 | | 1.6 | 1.6 | 0.5 | 0.5 | 0.0 | 1.8 |
| 20.1- 25.0 | 9.0- | 7.11 | 4.3 | 7.6 | 4.9 | 4.9 | ۍ 4 | 6.0 | 5,4 | 6.0 | 6.5 | 8.2 | ω ω | 6.6 | 12.0 | 14.7 | 10,3 | 12.5 | 15.2 | 12.6 | 12.0 | 12.1 | 7.1 | 12.1 | 8.2 | 7.2 | 8.9 |
| 18.1- 20.0 | 8. i- | 3 | 5.4 | 4.9 | 4,3 | 6.5 | 4.3 | 8.2 | 0.9 | 7.6 | 7.6 | 4.4 | 5,5 | 5.0 | 2.2 | 3,8 | 10.9 | 8.7 | 7.1 | 7.7 | ۍ 8 | 8.2 | 7.1 | 3.8 | 3,8 | 8,3 | 6,3 |
| (MPH) 16.1- 18.0 | 7.2- 7.2- 8.0 | • | 12.0 | 9.2 | 5.4 | 7.6 | 7.1 | 5.4 | 6.5 | 8.6 | 5.4 | 11.5 | 11.0 | 6.1 | 7.1 | 0.9 | 5,4 | 10.3 | 13.6 | 13.7 | 12.0 | 11.5 | 7.7 | 4.4 | 8.2 | 2.6 | 8,3 |
| SPEED 14.1- 16.0 | 6.3- | 1. | 6.0 | 8.7 | 8 | 9 | 12.0 | 8.2 | 10.9 | 10,3 | 11.4 | 9,3 | 9.9 | 11.6 | 7.6 | 11.4 | 12.5 | 9.8 | 12.5 | 13.7 | 8.7 | 7.7 | 6.3 | 11.0 | 9,3 | 6.1 | 9.6 |
| WIND 12.1- 14.0 | 5.4- 5.4- | 3 | 15.8 | တ | 10.3 | 12.5 | 12.5 | 12.0 | 13.0 | 12.5 | 16.8 | 16.9 | 12.6 | 11.6 | 17.9 | 14.1 | 10.9 | 12.0 | 8.6 | 8.7 | 11.5 | 11.5 | α α | 8 | 8.2 | 17.2 | 12.3 |
| 10.1- 12.0 | 4.5- | . | 13.0 | 15.8 | 14.7 | 13.6 | 18.5 | 17.4 | 15.8 | 15.8 | 16.3 | 12.6 | 15.4 | 15.5 | 14.1 | 7.6 | 12.5 | 12.5 | 10.9 | 10.9 | 9,3 | 11.0 | 17.0 | 14.3 | 15.4 | 8.3 | 13.7 |
| 8.1- 10.0 | 3.6- | | 14.7 | 14.1 | 13.0 | 12.5 | 11.4 | 14.7 | 13.6 | 12.5 | 13,6 | 10.9 | 12.1 | 10.5 | 6.0 | 18.5 | 13.0 | 14.7 | 7.1 | ۍ 8 | 12.6 | 12.1 | 13.7 | 13.7 | 15.4 | 13.9 | 12.7 |
| 6.1- 8.0 | 2.7- | 2.0 | 10.9 | 10.9 | 12.5 | 16.3 | 12.0 | 10,3 | 15.8 | 13.6 | 12.0 | 10.9 | 6.6 | 10.5 | 12.0 | 7.6 | 10.3 | 4.3 | 7.1 | 6 | 8.7 | 8.2 | 8 | 7.7 | 13.2 | 13.3 | 10.7 |
| 4.1- 6.0 | 1,8- | /•7 | 9.2 | 14.1 | 16.3 | 10.3 | 11.4 | 12.0 | 7.1 | 9.0 | 3,8 | 7.1 | ω | 9.4 | 12.5 | 6.5 | 6,5 | 4.9 | 8.7 | 4.9 | 7.7 | 8 | 6,6 | 15.4 | 12.1 | 12.2 | 4.0 |
| 2.1- 4.0 | -6.0 | 0.1 | 6.5 | 5.4 | 6.5 | 8.2 | 4.3 | 4.3 | 2.7 | 4.3 | 5.4 | 5.5 | ω | 3,3 | 1:1 | 1.6 | 0.0 | 0.5 | 0.0 | 1.1 | 1.6 | 4.9 | 6.0 | 9.0 | 3.8 | 6.7 | 3.9 |
| 0.1- | 0.1- | £. | 1.6 | 1.6 | 0.5 | 0.5 | 0.5 | 0.5 | 1 6 | 1 1 | 0.0 | 0.0 | 0.5 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.5 | 2.2 | 1.6 | :: | 9.0 |
| CALM | 2 | 5 | 0.0 | 0.5 | 0.0 | 0.0 | 0 | 0.5 | 0 | 0 0 | 0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.1 |
| | | | - | 7 | ~ | 4 | 'n | • • | 7 | 00 | 9 | 10 | Ħ | 12 | 13 | 14 | 15 | 16 | 17 | 82 | 61 | 20 | 7 | 8 | 2 | 24 | ALL HOURS |
| | | | | | | | | | | | = | : | C | • | 7 | 1 | œ | | | | | | | | | | AL. |

SOURCE: GEORESEARCH, INC.

Table IV - 109

Percentage Frequency Summary for Wind Speed

MADISON COUNTY - NORRIS HILL

| | | | | ~ | | | | | | | | | | | | | | | | | | | | |
|------|----------|---------------------|-------------------------|------------------------------|-------------|------|--------|--------|----------------|----------------|--------------|----------|----------|----------|-------------------|------|----------|--------|---------|---------|---------|------|------|-----------|
| | | | 3 | SPEED SPEED (MPH) (M/SEC) | 7.0 | 7.2 | 7.5 | 7.2 | 7.2 | 7.2 | ۰. د. ر | 8.2 | 8.5 | 8 | χ Q | 8 | 7.7 | 7.3 | 7.1 | 7.1 | 7.0 | 6,9 | 6.9 | 7.5 |
| | | | • | SPEED (MPH.) | 15.6 | 16.1 | 16.0 | 16.2 | 16.2 15.8 | 16.0 | 16.4 | 18.3 | 19.1 | 19.3 | . ŭ | 18.3 | 17.2 | 16.4 | 15.8 | 15.8 | 15.8 | 15.4 | 15.4 | 16.8 |
| | | | >40.0 | >17.9 | 0.0 | 0.0 | 0 8 | 0.0 | 000 | 0.0 | 00 | 1.0 | 2.5 | 2,5 | ۰ « | 0.0 | 0.0 | 0.0 | 0.0 | 8.0 | 0.8 | 0.0 | 0.0 | 9.0 |
| | | | 35.1- 40.0 | 15.7- 17.9 | 8 8 | 0.0 | 000 | 0.0 | 0.0 | 0.0 | 0 • • | 1.7 | ۳ ش | 1.7 | ລຸດ ລັດ | 8.0 | 8.0 | 0.8 | 0.8 | 0.0 | 0.8 | 2.5 | 0.0 | 1.1 |
| | | | 30.1- 35.0 | 13,5- 15,6 | 4.1 | w. c | 2.2 | 8 | ມູ ຕູ ກູ ຕູ | ຕໍ່ຕ | 7.5 | 0°0 | 6.6 | 11.6 | y 0 | 6.6 | 8,3 | 5.0 | 5.0 | 5.0 | 4.2 | 1.7 | 4.2 | 5.9 |
| | | | 25.1- 30.0 | 11.2- | 5.8 | 4. | ດີດ | 8.0 | 9.2 9.2 | 11.7 | 7°21 | 10.8 | 10.7 | 10.7 | ກິດ | 83 | 8.3 | 7.5 | ω. 3 | 6.7 | 4.2 | 5.9 | 5.1 | 7.6 |
| | | | 20.1- 25.0 | 9.0- 11.2 | 16.5 | 16.5 | 15.8 | 18.3 | 17.5 18.3 | 16.7 | 22.5 | 16.7 | 15.7 | 20.7 | 7.5 7.0 7.0 | 21.5 | 13,3 | 15.8 | 13,3 | 14.2 | 17.6 | 16.8 | 20.3 | 17.7 |
| | | | 18.1- 20.0 | 8.1- 8.9 | 9,1 | 9.6 | 12.5 | 11.7 | 5°C | 8 | 7.5 | .5. | 9.9 | | , o | 8 | 9.2 | 11.7 | °, | 10.0 | 10.9 | 11.8 | 5,9 | 8.9 |
| | _ | 98/ | (*PH) 6.1- 18.0 | 7.2- 8.0 | 10.7 | 10.7 | 13.3 | м 6 | 10.8 | 7.5 | ໝູ່ ທຸກ | 6.7 | 8 | ໝູ່ ເ | ຕິແ | 9.1 | 11.7 | 11.7 | 10.8 | 10.8 | 10.9 | 9.2 | 8.5 | 9.4 |
| . T | OMN | 03/31 | 0,4 = | 6.3- 7.2 | 7.4 | 9.1 | 2.0 | 6.7 | 6.7 | ۳ د | ໝູ່ ແ ຕຸດ | က် | 7.4 | 0,0 | 0 4 0 1 | 7.4 | 8. 3. | 6.7 | က် | დ ო | 6.7 | 5.9 | 7.6 | 6.8 |
| | (AUTUMN) | 01/10/84 - 03/31/86 | WIND 12.1- 1 14.0 | 5.4- 6.3 | 6.6 | 12.4 | | 10.0 | 6.7 | 7.5 | , ° | 10.01 | 2,0 | က်ပ | ດ້ທ | 9.9 | 8.3 | 2,5 | 10.0 | 5. 8 | 5,9 | 8.4 | 7.6 | 7.6 |
| | <u> </u> | 01/] | 10.1- | 4.5- 5.4 5.4 (| 8.3 | 6.6 | 0 0 | 11.7 | 11.7 | 8 | 0.01 10.0 | က် ထိ | ကို | 6,0 | 0 0 | 5 | 10.0 | 8,3 | 9.2 | 5.0 | 10.9 | 5.9 | 11.0 | 8.6 |
| | | | 8.1- | 3.6- 4.5 | 6 6 8 | 7.4 | 10.0 | 6.7 | 7.5 | ۳ د د د | 6.7 7.5 | 7.5 | 9.1 | 7.4 | 10.7 | 10.7 | 7.5 | 15.0 | ლ დ | 14.2 | % •4 | 7.6 | 8,5 | 8.9 |
| 7747 | | | 6.1- 8.0 | 2.7- 3.6 | 7.4 | 9,0 | ი დ | 10.0 | 5.8 | 10.8 | ຸດ | 6.7 | 4.1 | 6, P | ດິດເ | 9 | 9.2 | 6.7 | 12.5 | 8 3 | 2.0 | 8.4 | 11.9 | 7.9 |
| | | | 4.1- 6.0 | 1.8- 2.7 | 8.3 | 5.0 | 7.5 | 4.2 | 6.7 | 5.0 | ω « « | 4.2 | 5.0 | 2.5 | , w | 1.7 | 2.5 | 4.2 | ۳ ش | 5.0 | 6.7 | 10.9 | 5,9 | 4.9 |
| | | | 2.1-4.0 | 0.9- | 3,3 | 1.7 | 1.7 | 1.7 | 4.2 | 8.6 | 2,5 | | 5.8 | 1.7 | 7.7 | 8.0 | 1.7 | ۳ ش | 4.2 | 5.0 | 5.9 | 4.2 | 2,5 | 3.2 |
| | | | 0.1-2.0 | 0.1- | 1.7 | 2,5 | 000 | 1.7 | 1.7 | 1.7 | · · · | 0.0 | 0.0 | ω c | | 0.0 | 0.8 | 8 | 0.0 | 0.8 | 8.0 | 8° | 0.8 | 0.9 |
| | | | CALM | CALM | 0.0 | 0.0 | 0.0 | 0,0 | 0 8 | 1.7 | χ α Ξ = | 0.0 | 0.0 | 000 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.2 |
| | | | | | 7 | m ≈ | 21.1 | 91 | ~ & | 6 ; | = = | | U 13 | 14 15 | | 17 | 18 | 19 | 2 | ដ | 8 | ຮ | 24 | ALL HOURS |
| | | | | | | | | | | | | | | | | | | | | | | | | ⋖ |

Table IV - 110

Annual Wind Rose Distribution

MADISON COUNTY - NORRIS HILL

01/10/84 - 03/31/86

| <direction< th=""><th>SPEED (M/SEC)</th><th>0.1- 0.4 0.5- 0.9 1.0- 1.3 S 1.4- 1.8 P 1.9- 2.2 E 2.3- 2.7 E 2.3- 2.7 E 3.2- 3.6 3.7- 4.0 M 4.1- 4.5 E 5.9- 6.3 S 6.4- 6.7 / 6.8- 7.2 S 7.3- 7.6 E 7.3- 7.6 E 7.3- 7.6 E 7.3- 7.6 E 7.3- 7.9 E 13.5-15.6 11.3-13.4 13.5-15.6 15.7-17.9</th><th>AV SPEED (MPH) AV SPEED (M/SEC)</th></direction<> | SPEED (M/SEC) | 0.1- 0.4 0.5- 0.9 1.0- 1.3 S 1.4- 1.8 P 1.9- 2.2 E 2.3- 2.7 E 2.3- 2.7 E 3.2- 3.6 3.7- 4.0 M 4.1- 4.5 E 5.9- 6.3 S 6.4- 6.7 / 6.8- 7.2 S 7.3- 7.6 E 7.3- 7.6 E 7.3- 7.6 E 7.3- 7.6 E 7.3- 7.9 E 13.5-15.6 11.3-13.4 13.5-15.6 15.7-17.9 | AV SPEED (MPH) AV SPEED (M/SEC) |
|---|---------------|--|--|
| TOTAL | S | 0.01 0.02 0.03 0.03 0.03 0.03 0.03 0.03 0.03 | 17.0 |
| ₹ | | | 11.7 |
| ₹ | | | 9.9 |
| 3 | | | 10.8 |
| > | | 0.0000000000000000000000000000000000000 | 13.9 |
| FS | | 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.1 0.1 0.1 | 18.0 8.1 |
| ₹ | | 0.0 0.1 0.5 0.5 0.5 0.5 0.5 0.5 0.7 0.7 0.3 0.3 0.3 0.3 0.3 0.4 0.3 0.3 0.3 0.4 0.3 0.5 0.3 0.4 0.7 0.7 0.7 0.7 0.7 0.7 0.7 0.7 0.7 0.7 | 14.2 6.3 |
| SS | | 0.0 0.1 0.3 0.4 0.6 0.7 0.7 0.7 0.7 0.7 0.7 0.7 0.7 0.7 0.7 | 20.0 |
| S | | 0.0 0.1 0.1 0.2 0.7 0.7 0.7 0.9 0.9 0.9 1.1 1.1 1.3 1.3 1.3 1.3 1.3 1.3 1.3 1.3 | 20.0 |
| SSE | | 0.0 0.1 0.1 0.1 0.3 0.3 0.3 0.3 0.3 0.3 0.3 0.3 0.3 0.3 | 19.9 8.9 |
| R | | 0.0000000000000000000000000000000000000 | 10.2 |
| 器 | | 0.0000000000000000000000000000000000000 | 7.5 |
| ш | | | 7.8 |
| ä | | 0.0 0.1 0.2 0.1 0.1 0.1 0.0 0.0 0.0 0.0 0.0 0.0 0.0 | 9.4 |
| 뽀 | | 0.0 0.1 0.1 0.0 0.0 0.0 0.3 0.3 0.3 0.3 0.3 0.3 0.3 | 10.8 4.8 |
| N. | | 0.0 0.1 0.1 0.2 0.6 0.6 0.7 0.7 0.7 0.9 0.9 0.9 0.9 0.9 0.9 | 13.7 |
| z | | 0.0 0.0 0.0 0.1 0.1 0.1 0.1 0.0 0.0 0.0 | 12.7 5.7 |
| DIRECTION> | SPEED (MPH.) | | AV SPED (MPH) AV SPEED (M/SEC) |




Table IV - 111

Coefficients of Weibull Distribution

MADISON COUNTY - NORRIS HILL

01/10/84 - 03/31/86

| | SCALE | SHAPE |
|----------|-----------------------|------------|
| MONTH | FACTOR (C) (M/SEC) | FACTOR (K) |
| JANUARY | 1,325 | .312 |
| FEBRUARY | .155 | .014 |
| MARCH | 8.654 | .945 |
| APRIL | .447 | 060. |
| A X | 056 | .007 |
| JUNE | .567 | .070 |
| JULY | .750 | .328 |
| AUGUST | .432 | , 189 |
| - | .149 | .916 |
| ~ | 45 | 475 |
| ш | 8,9925 | 2,3193 |
| DECEMBER | 08 | .937 |
| YEAR | 8,4924 | 1,8549 |

SUPERIOR NWS AIRPORT

MINERAL COUNTY

The Superior Airport is located 2 miles southeast of Superior at 47 10 48 N and 114 52 12 W (Site No. 78 on Map II-1). Elevation at the airport is 2,700 feet. Meteorological data were collected at this site for several years by the National Weather Service.

These data, primarily collected for aviation and weather forecasting uses, consist of short-term (5 minutes or less) averages of wind speed and wind direction, as well as other meteorological parameters. Data were gathered once per hour. The data have been analyzed by Battelle Pacific Northwest Laboratories.

The data set consists of summaries derived from hourly observations made from January 1, 1948, through November 30, 1953. The anemometer was mounted on a beacon tower at a height of 17.7 meters. The site is representative only of a restricted area along the Clark Fork.

Average monthly wind speeds varied from 4.5 miles per hour in December to 5.8 miles per hour in April, May, and August. Average annual wind speed was 5.1 miles per hour.

Average monthly wind power ranged from 11.0 watts/m² in December to 22.0 watts/m² in August. Average annual wind power was 16.0 watts/m².




Table IV - 112

Monthly Wind Speed Distribution

MINERAL COUNTY - SUPERIOR NWS AIRPORT

01/01/48 - 11/30/53

| | A | | | |
|------|---|-----------------------------------|--------------------------|-------------------------|
| YEAR | 22.501 20.601 20 | 5.1 | 2.3 | 16.0 |
| DEC | 4857777000000000000000000000000000000000 | 4.5 | 2.0 | 11.0 |
| NOV | 60000000000000000000000000000000000000 | 4.7 | 2.1 | 13.0 |
| 100 | 20000000000000000000000000000000000000 | 4.7 | 2.1 | 13.0 |
| SEP | 74.8.1.0000000000000000000000000000000000 | 5.4 | 2.4 | 19.0 |
| AUG | 27.77.1. 20.000000000000000000000000000000000 | 5.8 | 2.6 | 22.0 |
| JUL | ###################################### | 5.6 | 2.5 | 20.0 |
| JUN | 8748781 00000000000000000000000000000000000 | 5.6 | 2.5 | 17.0 |
| MAY | 9134 | 5.8 | 2.6 | 20.0 |
| APR | 8078 - 90 - 00 00 00 00 00 00 00 00 00 00 00 00 | 5.8 | 2.6 | 21.0 |
| MAR | 0.000000000000000000000000000000000000 | 5.4 | 2.4 | 16.0 |
| FEB | 27.22 27.24 20.26 20.00 | 4.9 | 2.2 | 12.0 |
| JAN | 447.224.20000000000000000000000000000000 | 4.7 | 5.1 | 12.0 |
| | CALM (~1.1) 3.47 (~1.1) 3.47 (~1.1) 3.47 (~1.1) 7.56 (~1.1) 10.81 (~1.1) 10.81 (~1.1) 10.81 (~1.1) 10.81 (~1.1) 10.82 (~1.1) 10.82 (~1.1) 10.83 (~1.1) 10.83 (~1.1) 10.83 (~1.1) 10.84 (~1.1) 10.85 (| AVERAGE SPEED (MPH) AVFRAGE | SPEED (M/SEC) AVERAGE | WIND POWER (WATTS/M**2) |

ANEMOMETER HEIGHT = 58.0 FEET = 17.7 METERS SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

MISSOULA HOERNER-WALDORF #1

MISSOULA COUNTY

The Hoerner-Waldorf #1 site is located about 12 miles northwest of Missoula at 46 57 03 N and 114 10 50 W (Site No. 81 on Map II-1). Elevation at the site is 3,139 feet. The site was established by Hoerner-Waldorf to monitor particulate concentrations in the air and meteorological conditions in the area.

Data gathering at the site commenced on July 1, 1977. Due to problems with the data set, only data from November 1, 1977, through March 31, 1982, were analyzed for this *Atlas*. The data set consists of hourly averages of wind speed and wind direction, obtained by manually reducing the data from stripchart records. Anemometer height was 10 meters.

Data recovery was good to excellent, ranging from 74.3 percent in January to 99.9 percent in March. Overall data recovery was 89.0 percent. Winds were monitored long enough to adequately represent the wind resource at this location. The data, however, are representative only of a limited area of the Missoula Valley near the site.

Average annual wind speed at this site was 5.1 miles per hour. Average monthly wind speeds varied from 3.8 miles per hour in December and January to 6.5 miles per hour in April.

Average monthly wind power ranged from 14.8 watts/m² in October to 45.4 watts/m² in April. Average annual wind power was 30.5 watts/m².




Table IV - 113

Monthly Wind Speed Distribution

MISSOULA COUNTY - MISSOULA HOERNER-WALDORF #1

11/01/77 - 03/31/82

| | Σι. | 1.0-1.3 | - 6 | ÷. | ٠ د | . - | | | 5-5 | .6. 9-6. | . 4- 6 | .8- | - a | , <u>-</u> - | .6- 8 | 0-11 | .3-13 | .5-15 - 15 | <u>-</u> | | | | | |
|------|---------|------------|--------------|--------|--------------|----------------|---------|-------------|----------|-------------|------------|----------------|---------|------------------|---------|-----------|---------|---------------|----------|------------------------|--------------------------|--------|----------|--------------------------|
| YEAR | 6.5.9 | 900 | 12.9 | 9.7 | , t | . m | 2.5 | , v o o | 5.0 | ۲., | ⇒ . | - - | | 0.7 | 4.0 | 1.2 | | 0.0 | 0.0 | 5.1 | 2,3 | | 30.5 | 0.68 |
| DEC | 6.6 | 27.2 | - 0 - 0 | 5.3 | ν. ν. | 0.0 | ⇒.ı | | 1.3 | 0.0 | 7.5 | - 4 |) a | 0.0 | 0.3 | 0.8 | 0.1 | 0.0 | 000 | 3.8 | 1.7 | | 22.4 | 87.8 |
| NOV | 0.00 | | | | | | | | • | ٠ | | • | ٠ | | | • | • | • | 00 | 4.4 | 2.0 | | 29.9 | 98.9 |
| OCT | 3.0 | | | | | | | | | | | | | | | | | | | 0.4 | 1.8 | | 14.8 | 74.6 |
| SEP | 6.00 | | . | • | • | | • | | • | ٠ | ٠ | • | ٠ | | • | | • | • | | 5.0 | 2.2 | | 21.9 | 74.4 |
| AUG | 0.0 | | | • | • | | • | | | | • | • | | | | • | | • | | 5.6 | 2,5 | | 30.4 | 98.0 |
| JUL | 4.00 | | | | | | | | | | | | | | | | | | | 5.8 | 2.6 | | 35.6 | 99.1 |
| NOC | 0.0 | | | | | | | | | | | | | ٠. | | | • | | | 5.9 | 2.7 | | 31.6 | 82.0 |
| MA∀ | 6.00 | 11.9 | 13.4 | 8.6 | ο· | | 4.7 | 2.9 | 3.5 | 3.0 | œ i | - · · | | † - † | 0.5 | ħ.0 | 0.0 | 0.0 | 0.0 | 6.2 | 2.8 | | 32.5 | 92.7 |
| APR | 0.0 | | | | • | | • | | • | • | • | • | • | | | • | • | | | 6.5 | 5.9 | | 45.4 | 0.66 |
| MAR | 4.0°.0° | 16.6 | 12.4 | 7.1 | - | 3.6 | 3.0 | 2.0 . 4. | 2.0 | 8 | 9.6 | 2.1 | - a | . 0 | 0.5 | 1.6 | 0 | 0.0 | 0.0 | 5.5 | 2.5 | | 35.6 | 6.66 |
| FEB | 4.00 | | | • | | | | | | | | | | | | | | | | 7.4 | 2,1 | | 36.5 | 86.9 |
| JAN | 9.6 | | | | | | | | | | | | | | | | | | | 9 9 | 1.7 | | 25.7 | 74.3 |
| | A-1. | \$ 2.1-3.0 | 4.1-5. | 5.1-6. | 6.1-7. | 8.1-9. | 9.1-10. | -12. | 12.1-13. | 13.1-14. | 14.1-15. | 15.1-16. | 17 1-16 | 18.1-19. | 9.1-20. | 0.1 - 25. | 5.1-30. | 0.1 - 35. | . 0.4.0. | AVERAGE SPEED (MPH) | AVERAGE SPEED (M/SEC) | AVERAG | WATTS/M# | PERCENI DAIA RECOVERY |

SAULU DELLAS / SHOOKO

ANEMOMETER HEIGHT = 10 METERS = 33 FEET NUMBER OF OBSERVATIONS = 34442
PERCENTAGE DATA RECOVERY = 89.0

MISSOULA NWS AIRPORT

MISSOULA COUNTY

The Missoula NWS Airport is located approximately 5 miles northwest of Missoula at 46 55 40 N and 114 05 50 W (Site No. 84 on Map II-1). Elevation at the airport is 3,214 feet. Meteorological data have been collected here for many years by the National Weather Service.

These data, primarily collected for aviation and weather forecasting uses, consist of short-term (5 minutes or less) averages of wind speed and wind direction, as well as other meteorological parameters. Data were gathered once per hour. The data have been analyzed by Battelle Pacific Northwest Laboratories. Because of changes in anemometer height and reporting interval, the data set was broken into three periods for analysis: January 1, 1948, through April 3, 1958; April 4, 1958, through December 31, 1964; and January 1, 1965, through December 31, 1978. Only data from the most recent period were selected for inclusion in the Montana Wind Energy Atlas.

The data set for Missoula consists of summaries of observations made every third hour from January 1, 1965, through December 31, 1978. The anemometer was mounted on a ground mast at a height of 6.1 meters. Due to the complex terrain, the data are representative only of the immediate area.

Average annual wind speed at the site was 6.3 miles per hour. Average monthly wind speeds ranged from 4.9 miles per hour in October and November to 7.6 miles per hour in April.

Average annual wind power was 43.0 watts/m². Average monthly wind power ranged from 27.0 watts/m² in October to 65.0 watts/m² in April.




Table IV - 114

Monthly Wind Speed Distribution

MISSOULA COUNTY - MISSOULA NWS AIRPORT

01/01/65 - 12/31/78

(<0.5)

| | 332209322209322222222222222222222222222 | ₹ |
|------|--|---------------------------|
| YEAR | 7.0 | |
| DEC | 28 84 84 87 88 8 8 8 8 8 8 8 8 8 8 8 8 8 | |
| NOV | 0.08777887777100000000000000000000000000 | 0.0 4.9 2.2 29.0 |
| 00.1 | 8 m 9 d d d d d d d d d d d d d d d d d d | |
| SEP | 80000000000000000000000000000000000000 | |
| AUG | 6-8-1 6-00-1 6-00-1 6-00-00-00-00-00-00-00-00-00-00-00-00-00 | |
| JUL | 4-801- 4-801-44-0000000000000000000000000000000 | 0.0 6.7 3.0 46.0 |
| NUC | 1.001.00000000000000000000000000000000 | |
| MAY | 87.4.2.8.0.0000000000000000000000000000000 | 0.0 7.4 3.3 55.0 |
| APR | ###################################### | 0.0 7.6 3.4 65.0 |
| MAR | 2000 2000 2000 2000 2000 2000 2000 200 | |
| FEB | 200 mm m | |
| JAN | - CO | |
| | CALM (<1.1) 3.4-5.4 3.4-5.4 3.4-5.4 5.6-7.6 P 10.1-12.1 E 10.3-14.2 I 23.5-16.6 I 23.5-16.6 I 23.5-27.7 S 28.0-30.0 I 32.4-34.4 I 32.4-34.4 I 32.4-34.4 I 36.9-38.7 I 46.9-38.7 I 46.9-38. | 90. FH) EER #2) |

ANEMOMETER HEIGHT = 20.0 FEET = 6.1 METERS

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

MISSOULA UNIVERSITY OF MONTANA

MISSOULA COUNTY

The University of Montana site was located on the northeastern corner of the University of Montana campus near the mouth of Hellgate Canyon at 46 51 50 N and 113 58 40 W (Site No. 88 on Map II-1). Elevation at the site was 3,198 feet. The site was established by the Montana Air Quality Bureau to monitor wind speed and wind direction as part of the Montana Air Pollution Study.

Wind data collected from May 1, 1978, through March 17, 1980, were available for analysis. The data consist of hourly averages of wind speed and wind direction, obtained by manually reducing information from stripchart records. The data were gathered by a Climatronics electronic anemometer and wind vane on a 10-meter tower.

Winds were monitored long enough to adequately represent the wind resource at this location. The site, however, is representative only of a limited area near the mouth of Hellgate Canyon. Data recovery, which for the entire period was 83.4 percent, ranged from 33.9 percent in November to 100.0 percent in September.

Average annual wind speed at the site was 6.3 miles per hour. Average monthly wind speeds varied from 5.5 miles per hour in July to 7.5 miles per hour in December.

Average annual wind power was 48.8 watts/m². Average monthly wind power ranged from 19.5 watts/m² in September to 129.7 watts/m² in February.




Table IV - 115

Monthly Wind Speed Distribution

MISSOULA COUNTY - MISSOULA UNIVERSITY OF MONTANA

05/01/78 - 03/17/80

| | | | | | | | _ | | | | | | • | | _ | _ | _ | _ | _ | | | | | | | | | | | |
|------|-----|-------|--------------|-------------------|---------|-------|-------|-------|----------------|---------|----------|-------------|---------|---------|-------------------|---------|---------|--------|------------|------|--------|--------|------|-------|---------|------------------------|---------------|-----------------------|--------------|----------|
| | 0 | 5- 0. | , | c c | 23-27 | | | 7- 4. | . . | 5- 4. | ٠. در | ۲. در | 9- | ÷ • | 3- 7. | 3- 7 | 7- 8: | | <u>-</u> 8 | -11. | 3-13. | -15 | 7-17 | 7 | | | | | | |
| YEAR | 0.0 | Ξ. | ω. | ٠. c | 'nщ | ۳. | : ≠: | ∞. | ٥. | œ | m | φ. | ن | Ŋ | ď | ١ | ~ | Ŋ. | m. | | ~ | Q. | 0 | 0.0 | | 6.3 | 2.8 | | 48.8 | 83.4 |
| DEC | 0.2 | | | | | | | | | | | | | | | | | | | | | | | | | 7.5 | 3.4 | | 122,4 | 82.7 |
| N0V | 0.0 | • | • | • | | • | • • | • | * | ٠ | • | • | • | • | • | • | • | ٠ | • | • | | | ٠ | • | | 5.6 | 2.5 | | 39.6 | 33.9 |
| OCT | 0.1 | 8 | 16.4 | 20.0 | v /~ | 5.7 | .0 | 4.9 | 5.1 | 2.5 | ÷.5 | ⇒ . • | 0.0 | 0.9 | -: | 0 | 7.0 | 0 | 0.0 | 0.2 | 0.3 | 0.0 | 0.0 | 0.0 | | 5.7 | 5.6 | | 26.9 | 9.66 |
| SEP | 0.0 | 3.5 | 16.8 | 17.6 | 00 | 7.9 | 6.5 | 6.2 | 6.1 | 4.9 | 4.7 | ۰. د . | 9. | 0.5 | 0.4 | | 7.0 | 0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 5.6 | 2.5 | | 19.5 | 100.0 |
| AUG | 0.0 | | ٠ | • | • | | | • | | • | | • | ٠ | • | • | • | | • | • | | | | | | | 5.8 | 5.6 | | 28.2 | 93.4 |
| JUL | 0.0 | 4.3 | 15.9 | 20.4 | 10.0 | 6.2 | 5.5 | 5.7 | 5.7 | æ. | 2.0 | 0. | 1.0 | 0.7 | 0.7 | 0.5 | 0.0 | 0. | 0.3 | 0.0 | 0. | 0.0 | 0.0 | 0.0 | | 5.5 | 2.5 | | 24.0 | 99.1 |
| NOC | 0.0 | | • | | | | | | - | | _ | | | | | | | | | | _ | _ | _ | _ | | 5.8 | 5.6 | | 22.6 | 4.66 |
| MΑΥ | 0.0 | | | | | | | | | | | | | | | | | | | | | | | | | 6.3 | 2.8 | | 30.0 | 99.0 |
| APR | 0.0 | 1.6 | 6.5 | 7,7 | 7.6 | 10.1 | 7.6 | 4.6 | 5.2 | 9.3 | 0. 4. |) - - | 2.5 | | . ∞ | 0.7 | 0.0 | 7.0 | 0.7 | €. | 0.0 | 0.0 | 0.0 | 0.0 | | 7.0 | 3.1 | | 40.7 | 61.8 |
| MAR | 0.0 | | • | | | | | | ÷ | • | | | | | | | | | | | | | | | | 7.1 | 3.2 | | 83.8 | 56.3 |
| FEB | 0.0 | 7.6 | 16.2 | 16.8 | 6.5 | 4.7 | 5.2 | 4.5 | 3.4 | 8 | ٠,٠ | χ, (| 7 | 1.7 | 0.0 | 0.3 | 9.0 | 0. | 0.5 | 2.7 | 4.2 | 9. | 0.3 | 0.1 | | 7.4 | 3.3 | | 129.7 | 92.9 |
| JAN | 0.0 | Ś. | ᅻ. | • | į | | | | • | • | | • | • | | • | ٠ | • | • | | | | ٠ | | | | 6.7 | 3.0 | | 60.09 | 82.8 |
| | 21. | 1.1-2 | 2.1-3 | 7 4 7 7 7 7 | 7.1.2.0 | 6.1-7 | 7.1-8 | 8.1-9 | -10 | 10.1-11 | 11.1-12 | 12.1-13 | 13.1-14 | 14.1-15 | 15.1-16 | 16.1-17 | 17.1-18 | . 1-19 | . 1-20 | 1-25 | . 1-30 | . 1-35 | 0#- | 0.04< | AVERAGE | SPEED (MPH) AVERAGE | SPEED (M/SEC) | AVERAGE WIND POWER | (WATTS/M**2) | RECOVERY |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

ANEMOMETER HEIGHT = 10 METERS = 33 FEET NUMBER OF OBSERVATIONS = 14136
PERCENTAGE DATA RECOVERY = 83.4

LIVINGSTON CANDIDATE WIND TURBINE SITE PARK COUNTY

The Livingston Candidate Wind Turbine site is located approximately 2 miles northeast of Livingston, and just east of the old airport, at 45 40 27 N and 110 30 01 W (Site No. 95 on Map II-1). Elevation at the site is 4,658

The site is located in the Yellowstone River Valley just north of the Absaroka Mountains. Most of the land in the valley is privately owned, although there are a few sections of publicly owned land in the region. Much of the privately owned land has been leased for wind energy use. Land in the mountains is controlled predominantly by the U.S. Forest Service. Electrical service in the area is provided by the Montana Power Company and by the Park Electric Cooperative. The only commercial airport in the area is 4 miles northeast of the site.

This site was established by the U.S. Department of Energy as part of a federal wind energy program. The intent of the program was to provide information on wind characteristics to those involved in the design, evaluation, and operation of wind energy systems. The Bonneville Power Administration assumed responsibility for operating the site in October 1982 through June 1983. Little data were recovered during that period because of equipment failures. Montana DNRC in 1986 resumed monitoring at this site in a study of wind shear

Wind data from September 1, 1980, through June 30, 1982, were available for analysis. The data set consists of hourly averages of wind speed and wind direction at three heights: 9.1, 30.0, and 45.7 meters above ground level. Data recovery ranged from 49.2 percent in May to 99.5 percent in October. Overall data recovery at 9.1 meters was 78.8 percent. The percentage of data recovery was different at the different levels. (BPA is gathering data only at 15.2 meters and 45.7 meters.)

This monitoring period was long enough to adequately represent the wind resource at the location. Because the terrain in the area is complex, the data are representative only of a limited area in the Yellowstone River Valley

At 9.1 meters above ground level, average annual wind speed was 15.6 miles per hour. Average monthly wind speeds ranged from 9.5 miles per hour in August to 23.3 miles per hour in December. Average annual wind power at this height was 494.4 watts/m². Average monthly wind power varied from 95.1 watts/m² in August to 1,260.1 watts/m² in December. (The average speed and power for February may be low, due to malfunctioning equipment.)

At 30 meters above ground level, the average annual wind speed was 18.1 miles per hour. Average monthly wind speeds at this height ranged from 11.1 miles per hour in August to 26.2 miles per hour in December. Average annual wind power at this height was 738.4 watts/m². Average monthly wind power varied from 150.0 watts/m² in August to 1760.2 watts/m² in

At 45.7 meters above ground level, average annual wind speed was 19.5 miles per hour. Average monthly wind speeds ranged from 13.2 miles per hour in August to 27.4 miles per hour in December. Average annual wind power at this height was 876.4 watts/m². Average monthly wind power ranged from 196.3 watts/m² in August to 2,101.7 watts/m² in February.

Average seasonal wind speeds at 9.1 meters were 11.2 miles per hour in summer, 12.8 miles per hour in spring, 15.4 miles per hour in autumn, and 20.8 miles per hour in winter.




Table IV - 116

Monthly Wind Speed Distribution

PARK COUNTY - LIVINGSTON CANDIDATE WIND TURBINE SITE

09/01/80 - 06/30/82

YEAR

DEC

№

OCT

SEP

AUG

JUL

NOC

MAY

APR

MAR

FEB

JAN

| U | | ΣM⊢π | s & Z | S M O | OZO | | | | | |
|--------------|---|---|----------------------------|---|----------------------------------|--|-----------------------------|-----------------------------------|---|----------|
| .1-0-1 | 1.0-1.3 1.9-2.2 2.3-2.2 | 2-3. 7-4. | 0 0 0 0 0 0 | .4-6. .3-7. | . 4-8 -1-8-5 -6-8-9 | o wirit | ×17. | | | |
| 0.0 | - ฉุญญญ - ญญญ | 4 4 m m m | , w w w | | | - 6 - 4 - 6 - 6 - 6 - 7 |) th | 7.0 | 494.4 | 78.8 |
| 0.00 | - m O 4 0 . | | 999 | 2 K 2 C C C C C C C C C C C C C C C C C | 20'0 20'0 | 1.00 8.00 9.00 9.00 | 12.3 | 73.3 10.4 | 260.1 | ۲.19 |
| 000 | in way o | - 0000- | . ci = .c. | พ่งเพ | m -1 m | 75. | , w, | 8.6 | 1095.8 | 97.6 |
| 0.00 | ัดนักเก่อ เกละเก่ | 4 + v v v z | 4 ww. | 404 600 | | 14.7 8.8 7.7 2 | 10 4 | 6.7 | 358.3 | 99.5 |
| 0.0 | 3 x 8 0 8 0 9 0 9 0 9 0 9 0 9 0 9 0 9 0 9 0 | ~ 4 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 | | 4 m m | 0,01 √8.8 | | -0. | 5.1 | 160.5 | 84.7 |
| | - 6 - 6 - 7 - 6 - 6 - 7 - 7 - 6 - 6 - 6 - 6 - 6 - 7 - 7 - 6 - 7 - 7 - 7 - 7 - 7 - 7 - 7 - 7 - 7 - 7 | | | | | | | v. 4 | 95.1 | 98.9 |
| 0.00 | 8 7.36 | nnnn. oodir: | 03.FC | 88.7 6-13 | | 0000 15.75 | | 5.3 | 176.1 | 98.9 |
| | 7.5034 | | | | | | 0.0 | 5.3 | 171.8 | 69.5 |
| | 3.7.7.8 | | | | | | 000 | 0.1. | 132.4 | 49.2 |
| | 40850 | | | | | | -0 | 6.6 | 364.6 | 54.2 |
| | 4.20 | | | | | | 0.0 | 12.6 | 241.0 | 63.3 |
| | - 22.2.2 | | | | | | 0 0 0 V Q 1 | 9.3 | 044.5 | 4.68 |
| 0.0 | - 0.0.4.4 0.0.80.8 | 8. L 4. S. S. S. S. L. S. S. S. S. L. S. S. S. S. S. L. S. | 4326 | 3.5.6 3.5.6 | | 1. 9.1. | 7.4 | 7.9 | 733.9 | 7.07 |
| ₹ <u>-</u> . | S 2.1-7.0 P 3.1-3.0 E 4.1-5.0 E 5.1-6.0 | 6.1-7. 7.1-8. 8.1-9. 9.1-10. | | 14.1-15. 15.1-16. 16.1-17. | 17.1-18. 18.1-19. 19.1-20. | 1-25. | 35.1-40. >40. AVERAGE | SPEED (MPH) AVERAGE SPEED (M/SEC) | AVERAGE WIND POWER (WATTS/M**2) PERCENT DATA | RECOVERY |
| | | | | | | | | | | |

DNOCES/SETEM DEEPS

ANEMOMETER HEIGHT = 9.1 METERS = 30 FEET NUMBER OF OBSERVATIONS = 12638 PERCENTAGE DATA RECOVERY = 78.8

Table IV - 117

Monthly Average Wind Speed and Wind Power Density (30 Meters)

PARK COUNTY - LIVINGSTON CANDIDATE WIND TURBINE SITE

09/01/80 - 06/30/82

| | JAN | FEB | MAR | APR | MAY | NOC | JUL | AUG | SEP | 100 | NOV | DEC | YEAR |
|-----------------------------------|---------|--------|--|-------|-------|-------|-------|-------|-------|-------|--------|--------|-------|
| AVERAGE SPEED (MPH) AVERAGE | 20.0 | | 19.2 | 16.7 | 12.1 | 13.6 | 13.8 | 11.1 | 13.0 | 17.3 | 22.4 | 26.2 | 18.1 |
| 4/SEC) | 8.9 | | 8.6 | 7.5 | 5.4 | 6.1 | 6.2 | 5.0 | 5.8 | 7.7 | 10.0 | 11.7 | 8.1 |
| WER (**3) | 984.3 | 1740.4 | 1740.4 739.2 512.2 180.3 254.5 267.7 150.0 245.7 526.3 1059.5 1760.2 738.4 | 512.2 | 180.3 | 254.5 | 267.7 | 150.0 | 245.7 | 526.3 | 1059.5 | 1760.2 | 738.4 |
| DATA ERY | 70.6 | 75.4 | 75.4 54.8 54.2 49.1 69.0 98.8 98.9 84.6 98.8 94.3 80.4 75.5 | 54.2 | 49.1 | 0.69 | 98.8 | 98.9 | 84.6 | 98.8 | 94.3 | 4.08 | 75.5 |
| SOURCE: GEORESEARCH, | SEARCH, | | | | | | | | | | | | |

Table IV - 118

Monthly Average Wind Speed and Wind Power Density (45.7 Meters)

PARK COUNTY - LIVINGSTON CANDIDATE WIND TURBINE SITE

09/01/80 - 06/30/82

| | JAN | FEB | MAR | APR | MAY | JUN | JUL | AUG | SEP OCT | 0CT | NOV | DEC | YEAR |
|--------------------------|----------|--------|--|-------|-------|-------|-------|-------|---------|-------|--------|--------|-------|
| AVERAGE SPEED (MPH) | 22.7 | 26.5 | 20.5 | 18.2 | 14.4 | 15.3 | 15.7 | 13.2 | 14.7 | 19.0 | 22.8 | 27.4 | 19.5 |
| SPEED (M/SEC) | 10.2 | 11.9 | 9.2 | 8.1 | 6.4 | 6.8 | 7.0 | 5.9 | 9.9 | 8.5 | 10.2 | 12.2 | 8.7 |
| WIND POWER (WATTS/M**3) | 1592.4 | 2101.7 | 2101.7 916.4 601.7 243.1 323.3 328.4 196.3 309.9 670.4 1068.9 2077.9 876.4 | 601.7 | 243.1 | 323.3 | 328.4 | 196.3 | 309.9 | 4.079 | 1068.9 | 2077.9 | 4.928 |
| PERCENT DATA RECOVERY | 45.7 | 71.4 | 71.4 55.2 54.3 49.2 69.2 98.9 98.9 84.7 99.4 83.9 77.8 71.8 | 54.3 | 49.2 | 69.2 | 98.9 | 98.9 | 84.7 | 4.66 | 83.9 | 77.8 | 71.8 |
| SOURCE: GEORESEARCH, | ESEARCH, | | | | | | | | | | | | |

Table IV - 119

Percentage Frequency Summary for Wind Speed

PARK COUNTY - LIVINGSTON CANDIDATE WIND TURBINE SITE

(WINTER)

09/01/80 - 06/30/82

| | | - | ر 1 | 1-1- | 7 | α ! | 10 1- | WIND 12 1- | SPE | MPH) | | <u>, </u> | | | 35 1- | | | |
|-----------|--------------|------------|-----------|--------------|-------------|--------|---------|----------------|-----------------|------|------|--|------|--------|----------|-------|-------------|-------------|
| | CALM | 2.0 | 4.0 | 6.0 | 80.0 | 10.0 | 12.0 14 | 0 | 16.0 FD (MFT | 0.8 | 20.0 | 25.0 | 30.0 | 5.0 | 10.0 | >40.0 | > | > |
| | | 0.1- | -6.0 | 1.8- | ~ | 3.6- | 4.5- | <u> </u> | 5.3- | 7.2- | 8.1- | 6 | ٠ | | ۲. | | SPEED | SPEED |
| | CALM | 0.9 | 1.8 | 2.7 | 3.6 | 4 5 | 5.4 | 6.3 | 7.2 | 8.0 | 8.9 | 11.2 | 13.4 | 15.6 | 17.9 | >17.9 | (MPH) | M/SEC) |
| - | 0.0 | 4.6 | 5.9 | 9.2 | 5.2 | | • | 5.9 | • | | | 11.8 | | 8.6 | 3.9 | • | 19.8 | 8.8 |
| 2 | 0.0 | 4.0 | 5.4 | 8.7 | 4.0 | • | • | 7.4 | | • | • | 10.7 | | 10.7 | 6.7 | • | 20.4 | 9.1 |
| 60 | 0.0 | 5.6 | 5.3 | 9.9 | 4.6 | • | ٠ | 4.6 | • | • | ٠ | 11.3 | • | 7.9 | 6 6 | | 20.8 | 9.3 |
| . | 0.0 | 4.0 | m m | 7.3 | 2.7 | 4.7 | 3.3 | 6.7 | 9.3 | 6.7 | 0.9 | 12.0 | 7.3 | 9.3 | 7.3 | 10.0 | 21.0 | 4.6 |
| | 0.0 | ري دي | 1 | 0.9 | ς. | • | • | , , | • | • | ٠ | 12.0 | | 8. | 6.7 | ٠ | 21.2 | |
| 9 | 0 | 2.7 | 4.7 | 9 | ر م | • | • | 7 | • | • | • | 12.8 | • | 7. | - | • | 21.6 | 9.6 |
| 7 | 0.0 | 7. | ત્ર. જ | 7. | 6.7 | | • | ٠. خ | • | • | | 4.6 | • | ~ . | œ | • | 22.0 | 8.6 |
| | 0.0 | 3.4 | ъ. | O. | 6.7 | • | ٠ | 0. | • | • | • | 10.7 | ٠ | 7.6 | ω - | • | 22.5 | 10.1 |
| ۰ خ | 0.0 | 3.4 | 5.4 | 3.4 | 0.9 | | | 3.4 | • | • | • | 10.7 | | 4.6 | 8 | • | 23.0 | 10.3 |
| 10 | 0.0 | + 7 | 0.4 | 3.4 | 3.4 | | | 4.0 | • | | | 8.7 | | 10.7 | œ | • | 23.4 | 70.5 |
| 0 11 | 0.0 | - . | 3.4 | + . 1 | 5.⊄ | • | • | 6.1 | • | • | | 8.1 | • | 9.5 | 8 | ٠ | 23.8 | 10.6 |
| 12 | 0.0 | 6.1 | 4.8 | 5.4 | 3.4 | | | æ. | • | • | • | 9.5 | | 11.6 | 8 | • | 22.8 | 10.2 |
| U 13 | 0.0 | 5.4 | 2.0 | 6.8 | ۲. ۲. | | | 4 | • | • | | 14.9 | | 9.5 | 13.5 | ٠ | 22.6 | 10.1 |
| | 0.0 | 5.4 | 1.3 | 6.7 | 5.4 | | • | 5.4 | • | | | 14.8 | | 8.7 | 7.4 | ٠ | 21.2 | 9.5 |
| R 15 | 0.0 | 5.3 | 3.9 | 5,3 | 3.9 | | • | 9.9 | • | • | • | 19.7 | | 9.9 | 7.2 | • | 20.4 | 9.1 |
| 16 | 0.0 | 5.9 | 4.6 | 5.6 | 3.9 | • | • | 4.6 | • | | • | 15.7 | | 11.8 | 5.9 | ٠ | 20.1 | 0.6 |
| 17 | 0.0 | 5.2 | 33 | 5.2 | 3.9 | • | • | 10.5 | • | • | • | 11.1 | | 8 5 | 6 | | 19.3 | 8.6 |
| 9 | 0.0 | 3.9 | 3.9 | 5.2 | 5.5 | | • | 8 | • | | • | 13.1 | | 10.5 | 4.6 | | 19.1 | 8.5 5. |
| 19 | 0.0 | 3,3 | 6.5 | 7.2 | 5.2 | • | • | 5.9 | • | | ٠ | 7.8 | | 7.2 | 9.8 | • | 19.0 | 8.5 |
| 50 | 0.0 | | 5.9 | 9.5 | 5.3 | • | ٠ | 3 | • | • | ٠ | 7.9 | | 9.9 | 5.9 | • | 18.7 | ⊅. |
| 21 | 0.0 | 0.4 | 7.3 | 5.3 | 8.6 | • | | 0.9 | • | • | | 13.9 | | 5.3 | 5 | | 19.2 | 9.8 |
| 22 | 0.0 | 2,7 | 5.3 | 10.0 | 8 .0 | | ٠ | 0.9 | | | | 12.0 | | 5.3 | J. | | 19.5 | 8.7 |
| 23 | 0.0 | 5.3 | 9.8 | 7.9 | 0.4 | | ٠ | 9.0 | | | | 12.6 | | 5.3 | 7 3 | | 19.1 | 8.5 |
| 24 | 0.0 | 3.9 | 6.6 | 7.9 | 3.9 | | | 7.2 | | | | 9.5 | | 7.9 | 7.9 | | 19.0 | 8.5 |
| ALL HOURS | 0.0 | 4.2 | 4.9 | 6.3 | 4.9 | 5.0 | 4.4 | 5.7 | 5.8 | 5.8 | 5.7 | 11.7 | 6.6 | 8.6 | 7.4 | 9.8 | 20.8 | 9.3 |
| SOURCE: G | GEORESEARCH, | | INC. | | | | | | | | | | | | | | | |

Table IV - 120

Percentage Frequency Summary for Wind Speed

PARK COUNTY - LIVINGSTON CANDIDATE WIND TURBINE SITE

(SPRING)

09/01/80 - 06/30/82

| | | , | | | • | 1 | | Z . | | Ξ, | , | | , | | , | | | |
|-----------|--------|--------------|------|-------|----------------------|------|-----------|-------|---------------|----------|-----------|---------------------------|------|---------------------------|------|-------|---|-----|
| | CALM | ¥ 2.0 | -2.1 | 6.0 | 6.1 . 8.0 | 10.0 | 12.0 | 12.1- | 14.1- 16.0 | 18.0 | 20.0 | 20.1 - 25.0 | 30.0 | 30.1 - 35.0 | 40.0 | >40.0 | | |
| | | - | | 10 | ٢ | • | Z 3: u | D SPE | ME - | -KS/SE | COND) | • | (| Ŀ | ٢ | | \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ | ξ |
| | MIAC | - 0 |), L | - 0.0 | 7.7 | | ٠. | 1.7 | | ٠° | . 0 | | 13.5 | 13.7 | | | SPEED | - |
| | ב כ | | | 7.1 | | ; | t ` | ? | 7 - | 0 | 0 | - | ċ | | | × \ | Ε | _ |
| | 1 0.0 | 2.9 | 19.4 | 15.5 | 16.5 | 2.9 | 4.9 | 2.9 | 7.8 | 7.8 | 4.9 | 7.6 | 1.9 | • | | • | | 4.8 |
| | | _ | | 12.5 | 15.4 | | 8.4 | • | 7.7 | 5.8 | 2.9 | | | • | | • | | 4 |
| | | က | | 12.6 | 8.7 | | 5.8 | • | 6.8 | 9 | 4.9 | | | • | | • | | 5.1 |
| | | N | | 7.8 | 8.8 | | 12.7 | | 12.7 | 6.9 | 2.0 | | | • | | • | | |
| | | # | | 8.7 | 10.7 | • | 6.8 | | 9.7 | 8.7 | 7.8 | • | • | • | | • | | 5.2 |
| | | ⇉ | | 14.3 | 17.1 | • | 5.7 | | 8.6 | 3.8 | 10.5 | | • | • | | ٠ | | 5.2 |
| | | Ŋ | | 17.3 | 5.8 | | 5.8 | • | 3.8 | 8.7 | 6.7 | | | • | | ٠ | • | 5.2 |
| | | Ŋ | | 12.6 | 11.7 | | 4.9 | • | 2.9 | 5.8 | 4.9 | | • | • | | • | • | 5.6 |
| I | | _ | | 11.9 | 12.9 | • | 3.0 | • | 4.0 | 5.9 | 4.0 | | ٠ | • | | | | 6.2 |
| | | N | | 13.7 | 8.8 | | 3.9 | | & & | 3.9 | 6.9 | | | • | | • | | 6.5 |
| 0 | | _ | | 13.1 | 12.1 | | 5.1 | | 6.1 | 5.1 | 6.1 | | | • | | • | | 6.7 |
| | | N | | 10.2 | 10.2 | | 6.1 | • | 5.1 | 5.1 | 8.2 | | | • | | • | | 6.3 |
| _ > | | | | 11.2 | 11.2 | | 2.0 | • | 13.3 | 5. | 6.1 | | | | | | | 6.6 |
| | | 0 | | 17.1 | 12.1 | | 10.1 | | Ξ. | 6.1 | 12.1 | | | • | | | | 6.9 |
| œ | | _ | | 7.8 | 8.8 | | 8.8 | • | 5.9 | 10.8 | 12.7 | | | • | | • | | 6.8 |
| , | | 0 | | 6.8 | 7.6 | | 10.7 | | 6.8 | 7.8 | 7.6 | | | | | • | | 8.9 |
| ,, | | • | | 7.7 | 7.7 | ٠ | 6.7 | 11.5 | 11.5 | 9.6 | 12.5 | | 3.8 | 1.9 | 1.0 | 1.0 | | 6.7 |
| | | 0 | | 10.7 | 10.7 | ٠ | 10.7 | ٠ | 11.7 | 7.8 | 6.4 | | | ٠ | | | | 7.9 |
| | | 0 | | 10.7 | 13.6 | | 13.6 | • | 5.8 | 7.8 | 5.8 | | • | • | | • | • | 9 |
| | | 0 | | 13.7 | 17.6 | | 8 | ٠ | 5.9 | 10.8 | 2.0 | | | • | | • | | 5.6 |
| | | _ | | 14.4 | 14.4 | • | 10.6 | • | 6.7 | 7.7 | ₽. | | | • | | • | | ت |
| | | _ | | 19.4 | 13.6 | | 7.6 | • | 8.7 | 1.0 | 5.8 | | | • | | ٠ | | 5.0 |
| . u | | _ | | 15.5 | 12.6 | | 7.8 | | 6.8 | 5. 8. | 3.9 | - | | • | | • | | 4.7 |
| • • • | | m | | 15.4 | 13.5 | | 3.8 | | 1.9 | 6.7 | t. 8.† | | • | | | • | 10.5 | 4.7 |
| ALL HOURS | 4S 0.0 | 2.5 | 10.3 | 12.3 | 11.9 | 8.7 | 7.3 | 4.9 | 7.5 | 6.7 | 4.9 | 12.3 | 4.7 | 2.2 | 0.9 | 0.3 | 12.8 | 5.7 |
| SOURCE: | GEORES | GEORESEARCH, | INC. | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |

Table IV - 121

PARK COUNTY - LIVINGSTON CANDIDATE WIND TURBINE SITE Percentage Frequency Summary for Wind Speed

(SUMMER)

09/01/80 - 06/30/82

| AV AV | | 2.4 4.6 | . 7 | 7. | 2 | e: | .5 | .7 | . 1 | .3 4. | 4 0. | .5 | 0.0 | .4 5. | .0 6. | .9 9. | .7 6. | .7 6. | .2 | .9 6. | .9 | .5 | .4 | .4 | .6 4. | .2 5.0 | |
|--------------------------------------|----------|---------|------|-----|----------|-----|-----|-----|----------------|-------|------|-----|-----|-------|-------|-------|-------|-------|-----|-------|-----|-----|-----|-----|-------|-----------|--|
| 0.04< | N) 6.71< | 0.0 | o. | 0, | 0 | 0. | 0 | 0. | 0. | 0. | 0. | 0. | 0. | 0. | 0. | 0. | ٥. | 0. | 0. | 0. | 0. | 0. | ٥. | 0. | 0. | 0.0 | |
| •• | 17.9 | 0.0 | • | | | • | • | • | • | • | | • | • | | | | • | | • | | • | | | • | | 4.0 | |
| • 17 | 15.6 | 1.0 | ٠ | • | • | • | ٠ | • | • | • | • | • | | • | • | | | • | • | • | • | | • | • | • | 0.7 | |
| 25.1- 30.0 | 13.4 | 0.0 | • | • | | • | • | ٠ | • | • | | • | | • | | | | • | | | • | | | ٠ | • | 2.5 | |
| 5.0 | 11.2 | 1.0 | | | - | | | | | | | | | | | | | | | | | - | | _ | _ | 7.6 | |
| 18.1- 20.0 COND) | 8.9 | 7.8 | | | | • | | • | • | • | • | • | • | ٠ | • | | | • | • | • | • | | • | • | 9.6 | 7.1 | |
| (MPH) 16.1- 18.0 TERS/SE | 8.0 | 5.8 | | • | | • | | | | | | | | | | | | | | • | • | | • | • | | 7.5 | |
| D SPEED 14,1- 16.0 ED (METI | 7.2 | 3.9 | | | | | | • | | | | • | | | | | | | | • | • | | | | | 6.1 | |
| WIN 12.1- 14.0 D SPE | ٠. | 10.7 | 9 | • | • | | • | • | | ٠ | | • | | • | | | • | | | • | • | • | • | • | | 7.0 | |
| 10.1- 12.0 WIN | 7.7 | 7.8 | | | | • | | | | • | | | | | | | | | | | | | | | | 9.5 | |
| . 6. | 4.5 | 10.7 | | | | | | | | | | | | | | | | | | | | | | | | 11.0 | |
| . % , | 3.6 | 15.5 | ٠ | | • | | | • | | • | • | • | | | | • | | | | | | • | | • | | 11.8 | |
| • | 2.7 | 20.4 | | | • | | | | | | | | | | | | | | | | | | | | | 16.9 | |
| • | 1.8 | 15.5 | 23.3 | ┯, | # | œ | O. | _ | - | S | N | 7.8 | 4.0 | 1.0 | 2.0 | 3.0 | 0.0 | 0.0 | 1.0 | 0.0 | 2.9 | 1.0 | 5.7 | 6.7 | 9.6 | 11.6 | |
| 0.1-2.0 | 0.0 | 0.0 | | | | | | | | | | | | | | | | | | | | | | | | 0.7 | |
| CALM | CALM | 0.0 | 0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | |
| | | - | 2 | m. | a | Ę, | 9 | _ | ∞ | Ŧ | 10 | 0 | 12 | U 13 | 7. | R 15 | 16 | 17 | 18 | 19 | 50 | 21 | 22 | 23 | 54 | ALL HOURS | |

Table IV - 122

Percentage Frequency Summary for Wind Speed

PARK COUNTY - LIVINGSTON CANDIDATE WIND TURBINE SITE (AUTUMN)

09/01/80 - 06/30/82

| | SPEE | | | 6.2 | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | • | • | 6.9 |
|---------------------------------|-------------|-------|----------------|------|------|------------|-------------------|------------|----------|------|--------|----------|------|------|------|----------|-------|---------|------|--------|----------|----------|------|-----|-----|----------|-----------|
| | AV SPEED | (MPH) | 13 | 13,8 | 1 | 14. | 14. | 14. | <u>†</u> | 3. | 16. | 17. | 18 | 18. | 17. | 17. | 16. | 16. | 16. | 15. | <u>.</u> | <u>+</u> | 13. | 13 | 13 | 13 | 15.4 |
| >40.0 | | >17.9 | 1.2 | 1.2 | 9.0 | 1.2 | 1.2 | 0.0 | 9.0 | 1,2 | 2.9 | 2.9 | 2.9 | 1,2 | 1.2 | 1.8 | 1,2 | 1.8 | 7.5 | 2.9 | 2.3 | 1.7 | 1.7 | 1.7 | 1.7 | 1.2 | 1.6 |
| 35.1- 40.0 | 15.7- | 17.9 | | 2.3 | | • | | | | | | | | - | | | | | | | | - | _ | _ | _ | _ | 2.5 |
| 30.1 - 35.0 | 13.5- | 15.6 | 1.7 | 4.1 | 4.7 | 4.7 | 2.3 | 5.3 | 2.9 | 3 | 5.8 | 4.9 | 5.9 | 7.1 | 2.4 | 1.2 | 3.0 | 3,5 | 5.8 | 3.5 | 2.3 | 1.7 | 2,3 | 5.2 | 3.5 | 4.6 | 3.9 |
| 25.1- 30.0 | 11.2- | _ | 4.9 | 7.0 | | | | | | | | | | | | | | | | | | | | | | | 8.3 |
| 20.1- 25.0 | 9.0- | 11.2 | 10.5 | 9 | 13.5 | 11.8 | 12.9 | 13.5 | 14.5 | 11.7 | 16.3 | 15.7 | 18.8 | 15.9 | 16.2 | 17.6 | 17.5 | 12.9 | 14.5 | 8.7 | 8.7 | 9.8 | 9.5 | 9.2 | 8.1 | 9.8 | 12.7 |
| _ L | 1 | 8.9 | 5.2 | 7.0 | 3.5 | 7.6 | 5.8 | 5.3 | ۍ. ه | 5.3 | 4.7 | 4.9 | 6.5 | 10.6 | 10.8 | 9.1 | 10.2 | 11.2 | 4.9 | œ - | 6.9 | 5.8 | 4.6 | 5.7 | 5.8 | 5.8 | 6.8 |
| 16.1- 18.0 | ۲۳. ۲۰ | ω | 5.8 | 4 | 7. | + | 5. | ٠, | 'n, | φ. | 9 | 7 | m, | 7. | | 5 | 12. | φ. | φ. | = | ထ | 'n | ņ | က | ~ | <u>ب</u> | 6.8 |
| IND SPEED 1- 14.1- 0 16.0 | 5.3± | 7.2 | 5.2 | ري. | Φ | - ∓ | ھ | - ∓ | vo | N | 'n | αı | _ | _ | Φ | 9 | ∞ | | σ | • | • | 0 | | 0 | 00 | Ŋ | 6.9 |
| 12.1 14. | 5. t | ė | 6.4 | 9.3 | 7.6 | 10.6 | 5.3 | 5.8 | 4.9 | 5.3 | 5.8 | 10.5 | 8.2 | 2.9 | 3.6 | 6.7 | 9.0 | 10.6 | 14.5 | 13.3 | 9.8 | 11.0 | 8.7 | 9.8 | 7.5 | 6.9 | 8.0 |
| 10.1- | -t- | | 10.5 | ထ | | 5.3 | | | | | | | | | | | | | _ | _ | _ | _ | _ | | | | 8.3 |
| 8.1- 10.0 | 3.6- | | 8.1 | 5.8 | 4.9 | + | ۔ ھ | 4.7 | 4.7 | 9.9 | 5.2 | <u>.</u> | 4.7 | 4.7 | æ. | 7.3 | ÷. | 6.5 | 7.6 | 9.5 | 9.5 | 11.0 | 10.4 | 6.9 | 9.8 | 4.6 | 6.5 |
| 6.1- 8.0 | 2.7- | | 11.0 | 0 | ထ | ω. | 0. | φ. | = | 10. | 00 | Ś | 9 | 9 | ~ | ø. | ۲. | ထ | 'n, | ĸ, | φ. | | 0 | 0 | 10. | 7 | 8.3 |
| 4.1- 6.0 | 1.8- | | 11.0 | 8 | 2 | _ | σ, | 12 | - 2 | Q. | σ, | r. | œ | æ | 9 | ⇒ | _ | φ. | 9 | ∞ | 0 | 12 | o, | 16 | 13 | 15 | 10.3 |
| 2.1- 4.0 | 0.9- | | 12.2 | 0 | 2 | <u>~</u> | _ | ≓ | į. | 0 | 0 | 0 | S | Ŋ | 'n | | m | oi. | 'n | ٠i | ņ | Ņ | = | 0 | 12 | 12. | 8.9 |
| 0.1- | | | 0.6 | o. | | o. | o. | Ö | o. | o. | o · | o | o. | o. | Ö | Ö | 0 | o. | o. | 0 | Ö | o. | Ö | Ö | o | o. | 0.2 |
| CALM | ; | CALM | 0.0 | | | | | | | | | | | | | | | | | | | | | | | | 0.0 |
| | | | - (| N · | m. | 寸 ' | σ, | 91 | - | | ь Н | | 0 | | 13 | | R | 16 1 | 17 | 8L | 19 | 20 | 21 | 22 | 23 | 24 | ALL HOURS |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | - |

Table IV - 123

PARK COUNTY - LIVINGSTON CANDIDATE WIND TURBINE SITE Annual Wind Rose Distribution

09/01/80 - 06/30/82

| | <direction< th=""><th>SPEED (M/SEC)</th><th>CALM 13.00 CALM 13.00</th><th>TOTAL AV SPEED</th><th>(MPH) AV SPEED</th><th>(M/SEC)</th></direction<> | SPEED (M/SEC) | CALM 13.00 | TOTAL AV SPEED | (MPH) AV SPEED | (M/SEC) |
|---|---|---------------|--|-------------------|-------------------|-----------|
| | TOTAL | 0, | | 0.0 | 15.6 | 7.0 |
| | Z | | 000000000000000000000000000000000000000 | 1.9 | 7.7 | 3.4 |
| | ž | | 000000000000000000000000000000000000000 | 1.9 | 6.7 | 3.0 |
| | Z NZ | | 000000000000000000000000000000000000000 | 4.1 | 12.0 | 5.4 |
| | 3 | | 00000000000000000000000000000000000000 | 10.3 | 14.2 | 4.9 |
| | MSM | | 000000000000000000000000000000000000000 | 15.5 | 14.9 | 6.7 |
| | MS | | 000000000000000000000000000000000000000 | 17.1 | 20.8 | 9.3 |
| | MSS | | 000000000000000000000000000000000000000 | 14.3 | 25.3 | 11.3 |
| | s | | 0.0000000000000000000000000000000000000 | 4.7 | 23.5 | 10.5 |
| | SSE | | 0 | 2.1 | 6.8 | 3.1 |
| • | SE | | 000000000000000000000000000000000000000 | 2.5 | 5.9 | 5.6 |
| | ESE | | 000000000000000000000000000000000000000 | 4.8 | 9.1 | ₽. |
| | ш | | 000000000000000000000000000000000000000 | 9.5 | 12.0 | 5.4 |
| | ENE | | | 5.1 | 10.1 | 4.5 |
| | NE | | 000000000000000000000000000000000000000 | 2.4 | 4.9 | 2.9 |
| | NNE | | 000000000000000000000000000000000000000 | 1.9 | 5.6 | 2.5 |
| | z | | 000000000000000000000000000000000000000 | 1.9 | 6.9 | 3.1 |
| | DIRECTION> | SPEED (MPH) | S 4.11-2.0 P 5.41-1.0 B 6.0 B 7.11-1.0 C 17.11-1.0 C 17.11-1 | TOTAL AV SPEED | (MPH) AV SPEED | (M/SEC) |

SOURCE: GEORESEARCH, INC.

213




Table IV - 124

Coefficients of Weibull Distribution

PARK COUNTY - LIVINGSTON CANDIDATE WIND TURBINE SITE

09/01/80 - 06/30/82

| MONTH | SCALE FACTOR (C) (M/SEC) | SHAPE FACTOR (K) |
|--|--|--|
| JANUARY FEBRUARY MARCH APRIL MAY JUNE JULY AUGUST SEPTEMBER OCTOBER NOVEMBER | 8.7041 13.0890 6.2942 7.7433 5.1236 5.8431 5.3428 4.3808 7.5914 10.2543 | 1.4656 1.0187 1.4434 1.7195 1.7094 1.6060 1.6394 1.75903 1.75903 |
| YEAR | • | 1.4615 |

LIVINGSTON FAA AIRPORT

PARK COUNTY

The old Livingston airport, now abandoned, was located approximately 1 mile east of Livingston at 45 40 12 N and 110 31 48 W (Site No. 96 on Map II-1). The airport sat in the Yellowstone River Valley at an elevation of 4,590 feet, just north of the Absaroka Mountains, which rise to more than 11,000 feet. To the southwest is the Gallatin Range, and to the northwest is the Bridger Range. Both ranges have summits over 9,000 feet. Northeast of the area are the Crazy Mountains, which rise to over 11,000 feet. Two major river valleys intersect in this area: the Paradise Valley to the southwest, through which the upper Yellowstone River flows, and the Shields River Valley to the north.

Most of the land in the valley is privately owned, although there are a few scattered sections of publicly owned land. Land in the mountains is controlled predominantly by the U.S. Forest Service. Much of the privately owned land has been leased for wind energy use.

Electrical service in the area is provided by the Montana Power Company and the Park Electric Cooperative. A number of transmission lines run through the valley.

Meteorological data had been collected at this site for several years by the Federal Aviation Administration. These data, collected primarily for aviation and weather forecasting uses, consist of short-term (5 minutes or less) averages of wind speed and wind direction, as well as other meteorological parameters. Data were gathered once per hour. The data have been analyzed by Battelle Pacific Northwest Laboratories.

The Battelle data set for Livingston consists of summaries, for two time periods, of data gathered at different anemometer heights: January 1, 1948, through July 4, 1953; and July 5, 1953, through December 31, 1954. Only hourly data from the earlier period were selected for inclusion in this *Atlas*. These data were gathered by an anemometer mounted on a beacon tower at a height of 17.4 meters. Because of complex terrain in the area, the site is representative only of a limited area of the upper Yellowstone River Valley mean I iningston.

Average annual wind speed at the site was 15.7 miles per hour. Average monthly wind speeds varied from 10.7 miles per hour in July to 21.9 miles per hour in January.

Average annual wind power was 510.0 watts/m². Average monthly wind power ranged from 137.0 watts/m² in July to 1,175.0 watts/m² in January.

Average seasonal wind speeds were 11.4 miles per hour in summer, 14.5 miles per hour in spring, 15.4 miles per hour in autumn, and 21.1 miles per hour in winter. The highest average wind speeds occurred around noon in winter, early to mid-afternoon in spring and autumn, and late afternoon in summer. The lowest average wind speeds occurred shortly after midnight in autumn, in the early morning in spring and summer, and in early evening in winter. The diurnal range of average wind speeds was greatest in summer and least in winter.

The most common wind directions were south-southwest through west-southwest. Winds from the southeast and west-northwest were least common. By direction, average wind speeds ranged from 6.0 miles per hour for southeast winds to 24.6 miles per hour for winds from the south-southwest. The strongest winds were from the prevailing wind directions.




Table IV - 125

Monthly Wind Speed Distribution

PARK COUNTY - LIVINGSTON FAA AIRPORT

01/01/48 - 07/04/53

| | | _ | | တ | ۵. | ئيا | ш | ۵ | | Σ | ш | — | u | ~ | s | _ | s | ш | ပ | 0 | z | ۵ | | | | | | | | | |
|----------|---|------------|--------------|----------|----------|--------------|----------|---------|----------|----------|------------|-----------|----------|--------------|----------|--------------|----------|----------|------|----------------|----------|----------|--------------|----------|-----|----------|--------------|---------|--------------|----------------|---------------------------------------|
| | | 0.5 | _ | _ | → | _ | ⇒ | | ⇒ | = | = | - | - | = | _ | _ | . | 4 | | . | | | = | - | ᠴ - | ⇉. | 4 | | | | |
| | | Š | ÷ | ς. | ຕໍ | . | Ÿ | ø. | ~ | ထ | o. | ₽. | Ξ | 2 | . 3 | <u>.</u> | 5. | <u>.</u> | ∴' | <u>.</u> | <u>6</u> | 20. | ċ. | .30 | 32 | 우: | 9 | | | | |
| | | 뒭 | Ö | ż | ₹. | ú | 3 | ż | ċ | i. | S | ĸ, | 'n | 'n | S | J | ď. | 'n | ú | ċ | ċ | 'n | ú | ij | ď. | 'n | ^ | | | | |
| œ | | Ī | _ | | ` | | _ | _, | _ | • | ~ | - | = | - | ÷ | - | ~ | 7 | Ξ̈ | - | = | <u>~</u> | ผ | ēί | ៳ | m | | | | | |
| YEAR | | 1.7 | • | | • | | • | ٠ | • | • | ٠ | ٠ | ٠ | ٠ | • | • | ٠ | ٠ | • | • | • | ٠ | ٠ | ٠ | ٠ | 0.0 | • | | 5.7 | 7.0 | 0.0 |
| | | _ | _ | | | _ | _ | _ | _ | _ | _ | | | | | | | ٠. | | | | | _ | | | _ | _ | | _ | | 510 |
| OEC | | | | | | | | | | | | | | | | | | | | • | | ٠ | | | | 0 | | | 20.6 | 9.5 | 949.0 |
| > | | 9 | ~ | ĽΩ | ر. | a | 0 | ΓV | 0 | o | _ | ~ | m | 'n | cu | σ. | _ | cu | Ωı | ထ | ~ | ע | y Q | ۸ı | 0 | 0 | 0 | | 2 | 9 | |
| NOV | | • | • | | • | • | • | • | • | • | ٠ | ٠ | | ٠ | • | • | | • | • | ٠ | • | ٠ | ٠ | | • | <u>.</u> | • | | 19. | φ. | 769.0 |
| <u> </u> | | 8 | رح ا | 80 | 9 | ۵ | 6 | 9 | 0 | _ | 0 | \$ | 0 | _ | ι L | 7 | 8 | 6 | 6 | 0 | ~ | 0 | _ | 0 | 0 | 0 | 0 | | 0 | _ | 0 7 |
| ပ် | | ς. | ٥i | 14. | 7 | 7 | 13. | 6 | ø. | 10. | ۲. | તં | ď | ≠ | તં | | Ξ. | ö | 0 | - | o. | Ö | - | o. | ö | 0 | o. | | 15. | 9 | 446. |
| SEP | | 6 | īŲ | 9 | m | φ | _ | _ | = | ~ | ထ | ď | _ | ٥į | _ | 4 | کا | Ŋ | _ | Q | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 9 | m | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | 0 | | | Ξ. | Ŋ | 178.0 |
| AUG | | 0. | - | ۲. | 6. | 9 | ≠ | 0 | ٦. | ۲. | ď | 0. | 0. | ۲. | 7. | 2 | ≠. | ٦. | ۲. | ٦. | - | 0. | - | 0 | 0. | 0 | 0. | | ٥. | 0. | 0 |
| ∢ | | 2 | m | 17 | 1 | = | 17 | 7 | 7 | ထ | Ŋ | m | N | _ | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | _ | Ŋ | 153 |
| JIL | | | | • | | • | | • | • | | | | • | | | | | | • | | | | | | | 0. | • | | ~ | ® . | 0 |
| 7 | , | N | -7 | 5 | - | 7 | 19 | _ | Ŋ | 00 | īυ | N | N | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 10. | 7 | 137 |
| NO. | | | | | | | | | | | ٠ | | | | • | | | | | • | | | • | | • | 0.0 | | | 2.3 | 5.5 | 91.0 |
| • | , | • | • | 7 | ٥. | ÷ | - | • | 1- | ĭ | ~ | ••• | •• | • | | Ŭ | _ | Ö | _ | _ | _ | _ | _ | _ | _ | _ | _ | | - | ш, | 6 |
| ¥∀ | | - | - | _ | | _ | | _ | _ | _ | _ | _ | _ | - 4 | 4 | _ | | - 4 | _ | _ | - | _ | _ | | _ | 0.0 | _ | | 3.2 | 5.9 | 30.0 |
| | | | | _ | | _ | - | | | _ | | | | | | | | | | | | | | | | | | | - | | N |
| APR | | | | | | | | | | | | | | | | | | | | | | | | | | 0.0 | | | 14.1 | 6.3 | 3.0 |
| | | | | | | | • | | | • | | | | | | | | | | | | | | | | | | | _ | | 29 |
| MAR | | | - | - 4 | | | | | | | | | _ | | | | | | - | | | | | | | 0.0 | | | 16.1 | 7.8 | 13.0 |
| m | 1 | _ | _ | ` ~I | vo | ~ | . NI | ഹ | | , N | sc | Λı | ΔI | _+ | <u>=</u> | | _ | _ | മ | αi | _ | ~ | 0 | 0 | _ | 0 | 0 | | & | 62 | 0 5. |
| FFB | | <u>, -</u> | _ | • | | | | | | • | • | • | | | | | | | | • | • | • | | • | • | <u>.</u> | | | 20.4 | 6 | • |
| ż | : | 3 | 80 | ~ | - | 9 | . 00 | m | → | 7 | - | _ | → | → | | 8 | , | _ | m | 8 | ⊅ | ~ | N | ~ | | 0 | 0 | | | æ. | 1175.01055 |
| NAL. | • | | | | | | | | | • | • | | | | | | | | | | | | | | | Ö | | | 21.9 | 9. | 75. |
| | | | | | | | | | | | | | | | | | | | | | | | | | | = | | | _ | ပ ် | |
| | | ۲. | . 3 | 5 | _ | 6 | 12. | 7 | 9 | 80 | 21 | -23. | -25. | -27 | -30 | -32. | -34 | -36 | -38. | 7 | -43 | -45. | -56 | -68 | -79 | -90- | ×90. | Ä | MPH. | /SEC | AVERAGE WIND POWER (WATTS/M**2) |
| | | Š | <u>.</u> ; | 3.4- | 5.6 | .8 | | 3 | 7 | 8. | 9.0 | 1.3- | 5 | 7 | Ċ | 2 | 7 | <u></u> | 9. | . . | ÷ | 3.6 | 5.9 | 0 | 8.2 | 79.4-90. | ^ | AVERAGE | D () FRAC | ΞÌ | S/M |
| | | CALM | • | ••• | - | | = | - | = | = | <u>~</u> ` | N | Ň | Ñ | Ñ | ~ | 'n | 37 | ĕ | Š | → | Ť | ∃, | ī | ŏ | ζ. | | A | PEEL | EED | ATT |
| | | _ | | | S | ۵. | لبا. | لبا | ۵ | | Σ | - | _ | ш | S | _ | ·I | 0 | _ | ~ | | | | | | | | | S | SPI | 33 |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

ANEMOMETER HEIGHT = 57.0 FEET = 17.4 METERS

BATTELLE PACIFIC NORTHWEST LABORATORIES

SOURCE:

Table IV - 126

Percentage Frequency Summary for Wind Speed

PARK COUNTY - LIVINGSTON FAA AIRPORT (WINTER)

| 3 | SPEED SPEED 2 (MPH)(M/SEC) | 20022222222222222222222222222222222222 | 3 21.1 9.4 |
|----------------------------|-------------------------------|---|------------|
| >14.4 | >32. | 20.05.00.00.00.00.00.00.00.00.00.00.00.00 | 9. |
| 13.5- 14.4 | 30.2- 32.2 | | 2.1 |
| 12.5- 13.4 | 28.0- 30.0 | | 3.7 |
| 11.5- 12.4 | 25.7- 27.7 | | 5.3 |
| 10.5- 11.4 | 23.5- 25.5 | $\begin{array}{cccccccccccccccccccccccccccccccccccc$ | 5.1 |
| 9.5 - 10.4 | 21.3-23.3 | | 4.0 |
| PH) 8.5- 9.4 SEC) | 19.0- 21.0 | | ∞ • |
| Z - 7 Z | 16.8- 18.8 | | V. |
| | 14.5- | | 0.0 |
| 5.5- 6.4 | 12.3- 14.3 | ろはろうちゅうきょとはははきらららららららしましていらいらうこうきゅうてきらうファファウのラー・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・ | 7.6 |
| 4.5- 5.4 | 10.1 - 12.1 | 8800886-10000000000000000000000000000000 | , v |
| 3.5- 4.4 | 7.8- | ちらはきはられられまれまれまられるらっちられ ちうきちゅうしてらえるののうしきらいけらればしょう | |
| 2.5- 3.4 | 5.6- 7.6 | とれてもちょうないのうちょうないましょうしょうしょうしょうしょうしょうしょうしょうしょうしょうしょうしょうしょうし | ; ; |
| 1.5- 2.4 | 3.4-5.4 | 000001110000001110010010010010010010010 | • |
| 0.5- | 3.1 | 0010-00-0000 010001100000-00000 010001100000-00000 010001100000-00000 | · · |
| <0.5 | <u>^</u> | 00-000 | - |
| | | H H 100 B B B B B B B B B B B B B B B B B B | • |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

Table IV - 127

Percentage Frequency Summary for Wind Speed PARK COUNTY - LIVINGSTON FAA AIRPORT (SPRING)

| | | | SPEED | SEC) | 6 | 80 | ~ | ∞ | & | & | 6 | 4 | 6 | 0 | - | ۲3 | m | ⊅ | 2 | - # | a | 0, | 寸 | 0 | ο, | 0 | 0 | ره | 5 |
|-------|---------------|----------|-------|----------------|------|------|----------|----------|--------------|--------------|------|----------|------|------|----------|------------|-----|----------|-----|------------|-----|-----|----------|--------------|------|-----|----------|------|-------|
| | | | | | | | | | | | | | | | | | | | | | | | - | - | | _ | _ | 5. | 9 |
| | | ¥ | SPEED | HAW) | ₩. | m | ď | ď | 13.0 | 3 | ~ | # | ď. | ż | Ŗ, | ø. | Ġ | Ġ | ø. | ø. | Ġ | ζ. | # | | | | | | 14.5 |
| | >14. tt | • | | >32.2 | | | | | 2.3 | | | | | | | | | | | | | | | | | | | | 3.5 |
| | 13.5- 14 4 | | | 2 | 0.7 | 0.5 | 0.0 | 0.2 | 0.7 | 0.7 | 0.7 | .8 | | 1.5 | 1.6 | 9.0 | 1.8 | - | 1.6 | 2.0 | . 3 | 7. | | - 5 | 5.0 | 0.0 | 0.7 | 0.0 | 1.1 |
| | 12.5- 13.4 | , | 28.0- | 0 | • | • | • | • | 0.7 | | • | • | • | • | • | • | • | • | • | • | | • | • | . | • | 2.7 | | 1.7 | 1.9 |
| | 11.5- 12.4 | ł | 25.7- | ~ | | | | | 3.8 | | | | | | | | | | | | | | | | | | | | 3.6 |
| | 10.5- | | 23.5- | J. | | • | • | | 2.7 | | | • | • | • | • | • | | | | • | • | | | | | | | | 3.9 |
| | 9.5- | ; | 21.3- | | • | • | • | | 5.1 | ٠ | | • | • | | | | • | ٠ | • | • | | | | • | | ٠ | ٠ | • | 4.1 |
| _ | 8.5- 9.4 | 임(| • | - | • | • | • | • | 7 1 | • | • | • | • | • | • | • | • | • | • | • | • | | | | • | • | • | • | 8.1 |
| | 7.5- | , _ _ | • | œ. | | • | | | 9.5 | | | | | • | | | | | | | | | | | | | | | 12.2 |
| ND SP | 6.5- | S . | ₹. | 16 | • | • | • | • | 7.5 | | • | | • | • | • | ٠ | • | • | | • | | • | | • | • | • | | • | 7.9 |
| 3 | 5.5- |) | 12.3- | -T | | | | | 7.6 | | | | | | | | | | | | | | | | | | | | 9.9 |
| | 4 5- 5 4 | ` | 10.1- | ď | • | • | | • | 13.0 | | • | | • | | • | • | | • | • | | | Š. | | ٥. | | | | | 15.1 |
| | 3,5- | | 7.8- | • | • | • | • | | 7.8 | • | • | • | • | • | • | • | • | | • | ٠ | • | • | • | • | | • | • | | 8.7 |
| | 2.5- | | 5.6- | 7.6 | 7.8 | 7.1 | 10.1 | 6.7 | 8.5 | 10.3 | 5.8 | 7.1 | 5.1 | 4.9 | 6.7 | 3.4 | 5.4 | 5.3 | 5.6 | 6.2 | 2.6 | 5.3 | 6.3 | 7.0 | 10.1 | 8.3 | 10.1 | 8.9 | 7.0 |
| | 1.5- | ! | 3.4- | 5.4 | 14.9 | 17.4 | 16.5 | 16.7 | 17.8 | 18.1 | 15.9 | 12.3 | 12.5 | 10.9 | 9.1 | 8.9 | 6.0 | 6.9 | 6.9 | 9.9 | 9 | 8.0 | 10.0 | 14.5 | 14.7 | 5.1 | 13.9 | 17.6 | 12.5 |
| | 0.5- | • | | 3.1 | 1.8 | 2.9 | 2.0 | 4.0 | 3.8 | 3.1 | 3.6 | 3.1 | 2.7 | 2.4 | 2.0 | 2.5 | 0.0 | 1.6 | 0.7 | 0.5 | 0.5 | 1.6 | 0.9 | .3 | 1.3 | 3.1 | 7. | 1.6 | 2.0 |
| | <0.5 | | | . . | 2.4 | 2.7 | 2.2 | 3.7 | 2.2 | 2.5 | 2.7 | 2,2 | 1.6 | 2.2 | 0.7 | <u>-</u> : | 9.0 | 0.3 | 0.2 | 0.7 | 0.2 | 0.7 | 7 | 1.5 | 2.0 | 2.3 | 7. 8. | 1.6 | 1.6 |
| | | | | | , | N | က | _ | 5 | 9 | 7 | ထ | 6 | 10 | Ξ | 12 | 13 | ∓ | 15 | 16 | 17 | 9 | 19 | 50 | 2 | 55 | 23 | 54 | HOURS |
| | | | | | | | | | | | | | I | | 0 | | > | | ~ | | | | | | | | | | ALL |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

Table IV - 128

Percentage Frequency Summary for Wind Speed PARK COUNTY - LIVINGSTON FAA AIRPORT (SUMMER)

| | | | <u> </u> | | | | | | | | | | | | | | | | | | | | | | | | | |
|----------|---------------|----------|---------------------------|---------|----------|------|----------|------|-----------------|---------|------|------|------|------|------|----------|------|------|---------|----------------|------|------|----------|------|------|---------|------|-----------|
| | | | SPEED (M/SEC | | 7 | | | | | | | | | | | | | | | | | | | | | | | 5.1 |
| | | A | SPEED (MPH)(| О | ,0 | 9 | 8 | 8.6 | 8.6 | 9.3 | 10.3 | 11.2 | 11.3 | 11.8 | 12.2 | 13.4 | 13.9 | 14.7 | 14.8 | 14.4 | 14.2 | 13.1 | 12.1 | 11.3 | 70.7 | 10.3 | 9.8 | 11.4 |
| | >14.4 | • | >32.2 | _ | 0.8 | | | | | | | | | | | | | | | | | | | | | | | 1.0 |
| | 13.5- | • | 30.2- | c | 0.0 | 0.5 | 0.0 | 0.8 | 7.0 | 4.0 | 9.0 | 7.0 | 0.0 | 4.0 | 0.5 | 9.0 | 9.0 | 9.0 | 7.0 | . □ | .3 | 9.0 | 0.2 | 0.8 | 0.0 | 4.0 | 0.2 | 0.4 |
| | 12.5- 13.4 | • | 28.0 - 30.0 | 0 | 0 | 0.5 | 0.2 | 0.2 | 9.0 | 0.2 | 1.2 | 9.0 | 4.0 | ٦.4 | 1.6 | 1.6 | • | 1.6 | | | | | | | | | • | 0.8 |
| | 11.5- | | 25.7 - 27.7 | | . 0 | | | • | • | • | • | • | • | • | | | • | ٠ | | | • | | • | • | | 1.4 | | ٦.4 |
| | 10.5- | | 23.5- 25.5 | - | | 1.0 | 0. | 0.5 | → . | 0.9 | 2.4 | 1.6 | 2.0 | 2.4 | 2.4 | 3.6 | 3.6 | 5.4 | 2.8 | †. † | 3.0 | 2.8 | 2.8 | -8. | 1.6 | 0.8 | 2.1 | 2.2 |
| | 9.5- |) | 21.3 - 23.3 | * | | 1.4 | -: | 1.0 | - 7. | 7,7 | 2.1 | 2.6 | 3.9 | 8.8 | 3,3 | 3.4 | 5.0 | 4.5 | 5.4 | 3.8 | 2.4 | 3.9 | 3,2 | 5.6 | 7. | 7.8 | 1.9 | 2.7 |
| PH.) | 8.5- | EC. | 19.0 - 21.0 | | | - | - | - | | | | | | | | _ | _ | _ | _ | _ | | | | | | _ | _ | 5.8 |
| 'EED (MP | -5. 4. | ۵ | %. | ٠٠ ب | , w | 7.5 | 5.8 | 5.3 | 6.2 | 7.7 | 9.5 | 10.0 | 7.9 | 9 | 8.7 | 10.1 | 10.7 | 10.6 | 10.0 | 15.4 | 15.2 | 1.8 | 0.6 | 9.1 | 7.2 | 6.5 | 6.3 | 8.9 |
| | -1-3 | ND SPEE | ± 16 | | 5.5 | • | • | • | ٠ | ٠ | • | | | • | | • | | | • | • | • | • | ٠ | | | | • | 9.9 |
| 3 | 5.5- | <u>=</u> | 12.3 - 14.3 | | יי טי | • | • | • | • | • | | | | | • | • | • | • | • | • | • | • | • | | | | | 7.0 |
| | 4.5- | ١ | 10.1- 12.1 | 17.6 | 15.9 | 18.1 | 13.7 | 15.0 | 14.0 | 13.2 | 15.3 | 22.0 | 19.0 | 17.8 | 17.6 | 18.7 | 17.2 | 16.7 | 15.4 | 19.5 | 18.9 | 20.0 | 20.3 | 21.0 | 25.6 | 16.9 | 18.5 | 17.8 |
| | 3.5- | • | 7.8- 9.8 | | 12.2 | | | | | | | | | | | | | | | | | | | | | | | 12.2 |
| | 2.5- | , , | 5.6 - | 11.0 | 12.9 | 13.3 | 11.8 | 11.7 | 0.0 | 12.0 | 70.5 | 12.3 | 12.5 | 11.7 | 10.8 | 7.8 | 10.5 | 9.8 | 7.9 | ٧.0 | 6.9 | 9.1 | 10.2 | 9.5 | 12,3 | 15.6 | 17.4 | 11.0 |
| | 1.5- | | 3.4- | 22.8 | 27.7 | 25.5 | 30.1 | 26.3 | 29.9 | 21,2 | 24.2 | 16.4 | 15.6 | 17.5 | 16.2 | 12.0 | 8.4 | 6.7 | 8. U | 9.9 | 9.1 | 11.2 | 13.3 | 15.3 | 15.3 | 18.8 | 21.1 | 17.5 |
| | 0.5- | , | 3.1 | 4.5 | 2.5 | 7.3 | 5.5 | 8. | 6.9 | 6.9 | 5.5 | 2 | 8 | 2.4 | 1.7 | .3 | 1.2 | 0.8 | 7.0 | -1 | 7.0 | 7.0 | 1.6 | 1.7 | 1.7 | ر. د | 4.3 | 3.0 |
| | <0.5 | • | <u>.</u> | | 5.6 | 3.1 | <u>+</u> | 5.6 | ÷. | 4.0 | 2.8 | 9. | 1.7 | 9.0 | 9.0 | 7.0 | 0.8 | 0. | 0.0 | 0.0 | 7.0 | 0 |). 1. | 0.8 | .5 | · - | 7.4 | 1.8 |
| | | | | ,- | ~ | m | ⇒ | €. | 9 | | œ | 0 | 5 | - | 15 | | 7 | ₹. | 91 | 17 | 18 | 19 | 50 | 2 | 22 | 23 | 24 | ALL HOURS |
| | | | | | | | | | | | | ı | | 0 | | - | | ~ | | | | | | | | | | ALL |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

Table IV - 129

Percentage Frequency Summary for Wind Speed

PARK COUNTY - LIVINGSTON FAA AIRPORT (AUTUMN)

| | 0- 30.2- SPEED SPEED .0 32.2 >32.2 (MPH)(M/SEC) | 5.4 13.3 5. 4.4 13.4 6. | 1.1 5.3 1 | 1.8 5.8 14.5 6. | 1.3 6.6 14.5 6. | 0.9 7.7 15.2 6. | 0.7 8.2 16.9 7. | 1.3 10.4 17.6 7. | 0.7 8.8 17.5 7. | 2.4 8.1 17.8 8. | 0.6 7.9 17.2 7. | 0.7 7.0 16.2 7. | 1.5 7.3 14.7 6. | 2.0 6.3 14.4 6. | 1.5 6.6 14.5 6. | 1.5 6.5 13.9 6. | 1.5 5.9 13.6 6. | 3 1.3 7.1 15.4 6.9 |
|------------------------|--|----------------------------|------------------|-----------------|-----------------|-----------------|-----------------|------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|--------------------|
| 11.5- 12.5 12.4 13. | 25.7- 28.0 27.7 30.0 | .8. | 0 N | riri es en | 7 | 9.4. 9.41 | 2.2 | | .5 | υ· ο α - | .7 | : | , o | د | | .6. | .9 | 3.9 2. |
| 5- 10.5- ' | 3- 23.5- 23.5- 3 | 6 4.0 | m m | ب ب | ÷. | m | ري - | . | Ŗ, | m m | 'n | v, c | v m | - | m w | ึง | - | 2 3.6 |
| 8.5- 9. 9.4 10 | 19.0- 21.3 21.0 23. | 7.0 2. | ۳. در در | 2 | = | ~0. | 0,4 | ه م | α, | ∞⊐ | - | o o | رب تر د | σ. | ⇒ 10 | \ ~ | 0 | 7.3 3. |
| EED (MP 7.5- 8.4 | 16.8- 18.8 | 1 10.1 9 8.1 | 5 12.3 7 12.3 | | | | | | | | | | | | | | | 1 10.9 |
| 0.4 | - | 5.7 3. | č± č.v. | 8.4 | .7. | ن.ن ج.د. | .8 | , w | .6 | 6.9 | | ة. 9. | .7. | .6 7. | 8 7 9 | , r. | .2 6. | 6.7 7.1 |
| 4.5- 5.4 | 10.1-1 | 12.5 | | | | | | | | | | | | | | | | 14.6 |
| 3.5- 4.4 | • | 9.7 | ۷. | ۰ م | יטו | ~ ~ | יע ת | טיט | 9 | ±, τ. | · ~ | <u>،</u> د | 50, | ~ | 0,1 | 7 | ø | 7.7 |
| | 5.6- | | | | | | | | | | | | | | | | | 7.0 |
| 1.5- 2.4 | 3.4- 5.4 | 21.3 18.7 | 14.9 18.7 | 5. 4.4. | 7. | 10.8 | 80,5 | 7.9 | | ~ | 7.3 | 0,0 | 12.3 | 11.9 | 14.3 | 20.4 | 17.1 | 13.0 |
| 0.5- | 3.1 | 3.7 | 3.6 | د. د 0.9 | ۳, د ه د | , v, | | . 6 | 9.0 | 0.0 | 7.0 | 0.0 | | - ' | | | 4.2 | 1.9 |
| <0.5 | <u>.</u> | 2.8 4.6 | 3.0 | 4 t | 9:0 | 1.3 | c | 1.1 | 0.5 | 00.5 | 4.0 | 0.0 | 0.0 | 9.0 | , v | 2.0 | 4.2 | 2.1 |
| | | F- 0 | ಣವ | שיחי | ~ 0 | ± | 19 | | U 13 | R 14 | | <u>_</u> 0 | <u>.</u> | 50 | 2.2 | 23 | 24 | ALL HOURS |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

Table IV - 130

Annual Wind Rose Distribution

PARK COUNTY - LIVINGSTON FAA AIRPORT

01/01/48 - 07/04/53

| TOTAL <direction< th=""><th>SPEED (M/SEC)</th><th>0.5-1.4 8.5-3.4 8.5-5-3.4 8.5-6.4 10.5-11.4 11.5-12.4 11.5-12.4 11.5-13.4 11.5-1</th></direction<> | SPEED (M/SEC) | 0.5-1.4 8.5-3.4 8.5-5-3.4 8.5-6.4 10.5-11.4 11.5-12.4 11.5-12.4 11.5-13.4 11.5-1 |
|--|---------------|--|
| TOTAL < | S | 0000-84-8-6-6-8-8-8-8-8-8-8-8-8-8-8-8-8-8-8- |
| N N N | | 000000000000000000000000000000000000000 |
| ¥ | | 00000000000000000000000000000000000000 |
| HNH | | 000000000000000000000000000000000000000 |
| 3 | | 00000000000000000000 www |
| MSM | | 0000001-14-0000000000000000000000000000 |
| MS | | 000-1-12-12-12-12-12-12-12-12-12-12-12-12-1 |
| MSS | | 22 00000000000000000000000000000000000 |
| s | | 00000000000000000000000000000000000000 |
| SSE | | 00000000000000000000000000000000000000 |
| SE | | 0.0000000000000000000000000000000000000 |
| ESE | | 00000000000000000000000000000000000000 |
| ш | | 00-00-00000000000000000000000000000000 |
| ENE | | 00-00-0 |
| NE | | 00-00000000000000000000000000000000000 |
| N | | 0 |
| Z | | 00-00000000000000000000000000000000000 |
| D! RECT I ON> | SPEED (MPH) | 3.4-76 7.8-9.8 10.1-12.3-14.3 14.5-16.6 16.8-18.8 14.5-16.6 16.8-18.8 14.5-16.6 16.8-18.8 14.5-16.6 16.8-18.8 14.5-16.6 16.8-18.8 17.27.7 18.6-18.8 18.6-18. |
| _ | S | AA ACOILVOMIL-3 UMM POLOTALING |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES




Table IV - 131

Coefficients of Weibull Distribution

PARK COUNTY - LIVINGSTON FAA AIRPORT

| MONTH | SCALE FACTOR (C) (M/SEC) | SHAPE FACTOR (K) |
|--|---|--|
| JANUARY FEBRUARY MARCH APRIL AAY JUNE JULY AUGUST SEPTEMBER OCTOBER DECEMBER | 11.1560 10.8990 8.6600 7.7930 7.7930 6.9480 6.3220 6.4940 8.1120 10.2880 | 1.7780 1.7780 2.0230 2.0230 2.0310 1.8550 1.7030 1.7030 1.7030 |
| YEAR | 8.4500 | 1.7660 |

HEART BUTTE PONDERA COUNTY

The Heart Butte site is located over 3 miles west of Heart Butte and about 20 miles south of Browning at 48 17 42 N and 112 53 03 W (Site No. 100 on Map II-1). Elevation at the site is 5,161 feet. This monitoring site was part of the Wind Regional Energy Assessment Program run by Oregon State University for Bonneville Power Administration.

Well exposed and relatively smooth ridge crests abound in the area. The Rocky Mountain Front is less than 5 miles to the west. The site is representative of a large area. Access to the area is reasonable, with a state highway running to the east and a paved secondary road into Heart Butte. A number of dirt roads cut through the area. Winter access is sometimes hampered by drifting snow and severe weather conditions.

The site is located on the Blackfeet Indian Reservation. It is located south of Glacier National Park and near areas still being promoted for wilderness designation. Electrical service in the area is provided by the Glacier Electric Cooperative. One 115 kV line runs into Browning from Cut Bank. The area is at a remote end of the transmission system. The nearest commercial airport is located in Cut Bank, nearly 30 miles to the east. Air traffic generally is light.

Collection of wind data began in October 1981 when a wind-run anemometer was installed. Summaries of this data are printed in Appendix C. A data logger was installed and began collecting data on November 13, 1982. Data collection ran through May 29, 1984. The anemometer height was 35 feet.

Data recovery was fair to excellent, ranging from 68.8 percent in January to 100.0 percent in July through September. Overall data recovery was 92.3 per-

Average monthly wind speeds ranged from 10.4 miles per hour in June to 27.5 miles per hour in January. Average annual wind speed was 18.0 miles per

Average monthly wind power ranged from 113.9 watts/m² in June up to 1,753.8 watts/m² in January.

Average seasonal wind speeds were 12.6 miles per hour in the summer, 15.3 miles per hour in the autumn, 25.9 miles per hour in the winter, and 20.2 miles per hour in the spring. In the spring, highest winds happened in the afternoon. Diurnal range of average wind speeds was greatest in the spring, at 5.8 miles per hour and least in the autumn, with a range of 3.2 miles per hour. Highest speeds in winter were during the night.

The wind direction data is incomplete because the wind vane failed January 1, 1984 and was not replaced. The wind speeds during the following five months were particularly high. How this affected the distribution of the wind rose is not known; the wind speeds on the wind rose certainly are below what would have been the average for the eighteen-month monitoring period. The most common wind directions were west-southwest to north-northwest. Winds from the north-northeast through south-southeast were least com-




Table IV - 132

Monthly Wind Speed Distribution PONDERA COUNTY - HEART BUTTE

o п п п о

| | | | | | | 11/13, | 11/13/82 - 05/29/84 | /29/84 | | | | | | |
|--|-------------|-------------------|--------------|--------|-------|--------|---------------------|---------|---------|------------|----------|------------|------|-----------|
| | JAN | 8 | MAR | APR | MAY | N) | ¥ | AUG | 쭚 | ğ | <u>Q</u> | 띰 | YEAR | |
| CALM | O | 1.2 | | 1.0 | | | 0.3 | 0.7 | | | 3.5 | 6.7 | | CALM |
| 0.1-1.0 | 0.7 | 1.2 | 0.0 | 9.0 | 0.0 | 2.0 | 1.2 | 1.2 | 3,3 | 2.2 | 2.5 | 5.0 | 1.6 | 0.1 - 0.4 |
| <u> </u> | 0 | 0.7 | | 0.4 | | | 2.6 | 1.9 | | | 3.0 | 3,9 | | 0.5-0.9 |
| S 2.1-3.0 | 9 | 7.4 | | 10.1 | | | 3.0 | 2.6 | | | 3.4 | 4.4 | | 1.0-1.3 |
| ا | Ó | 0.5 | | 1:1 | | | 3.5 | 2.8 | | | 3.4 | 4.7 | | 1.4- 1.8 |
| 4.1 | ~ | 0.6 | | 1.9 | | | ж 8 | ω, Υ | | | 3,5 | 4.7 | | 1.9- 2.2 |
| 5.1 | ζ. | 0.9 | | 2.6 | | | 5.2 | 5.0 | | | 3.9 | 3.6 | | 2.3- 2.7 |
| 6.1 | - -i | 1.3 | | 2.6 | | | 3.6 | 4.4 | | | 4.0 | 4.4 | | 2.8-3.1 |
| | ٧i | 1.7 | | 3.7 | | | 3.2 | 6,3 | | | 3.6 | 3.9 | | 3.2- 3.6 |
| M 8.1-9.0 | -ĭ | 1.6 | | 3,4 | | | 4.7 | 8.1 | | | 4.9 | 4.1 | | 3.7- 4.0 |
| | | 2.3 | | 3.2 | | | 5,9 | 7.0 | | | 3.8 | 4.7 | | 4.1-4.5 |
| _ | | 2.0 | | 3,7 | | | 6.7 | 7.0 | | | 3.7 | 5.0 | | 4.6- 4.9 |
| E 11.1-12.0 | . | 2.6 | | 4.0 | | | 5,2 | 6.9 | | | 2.7 | 2.9 | | 5.0-5.4 |
| | i | 1.6 | | 4.4 | | | က် | 7.7 | | | 3.3 | 3.6 | | 5.5- 5.8 |
| | ∾. | 1.9 | | 3.6 | | | 3,9 | 5.6 | | | 3.2 | 2,3 | | 5.9-6.3 |
| | | 1.7 | | 4.5 | | | 4.4 | 5,6 | | | 2.2 | 2.8 | | 6.4- 6.7 |
| 0 15.1-16.0 | . i | 2.4 | | 4.2 | | | 3.6 | 3.5 | | | 2.8 | 2.4 | | 6.8- 7.2 |
| | ij | 1.6 | | 3.4 | | | 5.0 | 4.2 | | | 3.4 | 1.1 | | 7.3- 7.6 |
| | ∴ | 1.7 | | 3.0 | | | 3.5 | 3.6 | | | 4.1 | 1.6 | | 7.7-8.0 |
| 18,1-19,0 | ∾; | 2.1 | | 3.0 | | | 3.5 | 3.2 | | | 3.0 | 1.8 | | 8.1-8.5 |
| 19.1-20.0 | ,i | 5.6 | | 2.5 | | | 2.4 | 2,3 | | | 1.8 | 2.0 | | 8.6-8.9 |
| 20.1-25.0 | ~ | 11.5 | | 13.1 | • | | 9.4 | 5.1 | | | 10.3 | 7.0 | • | 9.0-11.2 |
| 25.1-30.0 | oʻ | 13.1 | | 8.7 | _ | | 5.1 | 0.8 | | | 9.8 | 5.4 | | 11.3-13.4 |
| 30,1-35,0 | o, | 13.5 | | 6.2 | _ | | 3.1 | 0.5 | | | 5,3 | 4.9 | | 13.5-15.6 |
| 35.1-40.0 | സ് | 4.8 | | 2.5 | | | 0.7 | 0.1 | | | 1.5 | 2.0 | | 15.7-17.9 |
| >40.0 | ×. | 17.4 | | 2.7 | _ | | 0.7 | 0.1 | | | 3.4 | 5.0 | | >17.9 |
| AVERAGE | | | | | | | | | | | | | | |
| SPEED (MPH) AVERAGE | 27.5 | 24.2 | 20.3 | 16.7 | 24.4 | 10.4 | 13.9 | 11.8 | 15.1 | 15.0 | 15.7 | 13,9 | 18.0 | |
| SPEED (M/SEC) | 12.3 | 10.8 | 9 1 | 7.5 | 10.9 | 4.7 | 6.2 | 5,3 | 6.7 | 6.7 | 7.0 | 6,2 | 8.0 | |
| AVERAGE | | | | | | | | | | | | | | |
| WIND POWER | 1752 0 | 0 7011 | 5 W3 | AEG A | 0 440 | | 0.25 | - | , כי | • | | 9 | | |
| PERCENT DATA | | 6 1130.3 | 0.160 | 4.00.4 | 0.1 | 113.9 | 6.000 | 171.4 | 233.0 | 200 | £03.2 | 7.69 | 7.6 | |
| RECOVERY | 68.8 | 81.4 | 97.1 | 97.3 | 8.8 | 91.7 | 100.0 | 100.0 | 100.0 | 85. 88. | 88.3 | 8.8 8.8 | 92.3 | |
| ANEMONETER HEIGHT NUMBER OF OBSERVA | HEIGHT = 13 | 11 METERS NS = | = 35 8830 | FEET | | | | | | | | | | |
| PERCENTAGE DATA | IA RECOVERY | ERY = | 92.3 | | | | | | | | | | | |

NOCEN/SEE

Table IV - 133

Percentage Frequency Summary for Wind Speed

| | | | | | PO | DER | Z C | PONDERA COUNTY | [Y • E | - HEART BUTTE | TBC | TTE | | | | | | | |
|------------|--------------|------------|----------------|------------|------|-------------|------------------|-----------------|--------------------------|---------------|--------------------|-----------------------|---------------|---------------|---------------|--------------|-----------------|-----------------------------|--|
| | | | | | | | | (WIN | (WINTER | _ | | | | | | | | | |
| | | | | | | | 11/ | 13/82 | 11/13/82 - 05/29/84 | /84 | | | | | | | | | |
| | | _ | 2.1- | 4.1- | 6.1- | 8.1- | 10,1- | WIND 12.1- | WIND SPEED 1.1-14.1-1 | ₹- | 4 | 0.1- | 25.1- | 30.1- | 35.1- | | | | |
| | CALM | | 4.0 | 6.0 | 8.0 | 10.0 | 12.0 WIN | 14.0 ID SPEE | 16.0 0 (MET | 8.0 S/S | 0.Q | 25.0 | 30.0 | 35.0 | 40.0 | >40.0 | A | ΑV | |
| | CALM | 0.1-0.9 | 0.9- | 1.8- | 2.7- | 3.6- 4.5 | 4.5- 5. 5.4 6 | 5.4- 6.3 | 5.4- 6.3- 7 6.3 7.2 | .2- 8.0 | 8.1 . 8 | 9.0- 11.2 | 11.2- 13.4 | 13.5- 15.6 | 15.7- 17.9 | >17.9 | SPEED (MPH.) | SPEED SPEED (MPH)(M/SEC) | |
| | | | 6.7 | 4.4 | 3,3 | 3,3 | 5.6 | 5.6 | 2.2 | 1.1 | 5.6 | 10.0 | 7.8 | 14.4 | 8.9 | 18.9 | 25.4 | 11.3 | |
| _ | | | 7.3 | 2.4 | 2.4 | 0.0 | 7.3 | 6.1 | 2.4 | 0.0 | 7,3 | 7,3 | 8 | 12.2 | 6.1 | 25.6 | 25.9 | 11.6 | |
| | | | 10.3 | 2.6 | ຕຸແ | ω, ς 8 - | 1.3 | m° | 0,0 | 5.1 | | 12.8 | 11.5 | 17.3 | φ. 4 ~ | 25.6 | 26.0 26.0 | 11.6 | |
| | | | 11.4 | 2.9 | 2.9 | 4.3 | 1.4 | 0 | 4.3 | | 0 | 14.3 | 0.01 | 11.4 | 10.0 | 24.3 | 26.8 26.8 | 12.0 | |
| _ | | | 7.2 | 5.9 | 1.4 | 1.4 | 1.4 | 1.4 | 2.9 | က် | 4.3 | 13.0 | 8.7 | 8.7 | 4.3 | 30.4 | 26.9 | 12.0 | |
| | | | 7.6 | o. | ក | ۰ د د | | 1.5 | 0.0 | | 6.1 | 16.7 | | 10.6 | 4.0 | 8,3 | 27.1 | 12.1 | |
| ∞ <i>⊙</i> | 8 0.0 0.0 | 1.6 1.6 | 9, 9, 4, 7, | 1.6 4.8 | 4.4 | 3.1 | 9.1 | 1.6 | 3.2 | ر د و | 1.6 | ວີດ | و 4 ت | 12.5 | 2, 4, 4, α | 25.0 25.4 | .0.98 8.0.98 | 11.6 | |
| | | | 8 | 3.2 | 1.6 | 3.2 | 1.6 | 4.8 | 4.8 | 3.2 | 3.2 | 11.3 | 14.5 | 9.7 | 4.8 | 24.2 | 26.4 | 11.8 | |
| 0 | | | 6.7 | 3.2 | 3.2 | 3.2 | 3.2 | 1.6 | 4.8 | 1.6 | 4.8 | 11,3 | 9.7 | 9.7 | 9.7 | 22.6 | 26.1 | 11.7 | |
| - | | | 6.5 | 3,2 | 3,2 | 3.2 | 4.8 | 8.4 | 1.6 | 3.2 | 3.2 | 11.3 | 11.3 | 11.3 | 3.2 | 27.4 | 26.5 | 8.5 | |
| - | | | 6.7 0.0 | 4.5 | 10.1 | w, 4 | 6.7 | ω, Δ 4. 0 | 2.2 | 1.1 | ω, ς 4. Δ | 10.1 | 11.2 | 10.1 | ν, κ ο – | 18.0 | 22.9 | 10.2 | |
| ~ | | | 0.6 | 1.3 | | 0.6 | , w | က်က | 2.6 | ထ | 5.1 | 14.1 | 6.4 | 10.3 | 0.0 | 3.6 | 24.3 | 10.9 | |
| | | | 6.5 | 1:3 | 5.2 | 5.2 | 2.6 | 2.6 | 10.4 | 5.2 | 5.6 | 10.4 | 7.8 | 11.7 | 6.5 | 20.8 | 25.1 | 11.2 | |
| - | | | 7.2 | 4.0 | 2,0 | 4.4 | 4 - W R | സ് ശ | 7.0 | 2, - 0, 4 | ⊢. α 4. α | \ \ \ \ \ | ~ ດ ໝໍດ | 13.0 | 10. a | 2.5 | ئ تة ه | 11.5 11.5 | |
| ∓ ≓ | | | יין ס | 2.0 | 1.5 | 4 | 1.5 | 4.4 | တို့ထ | 2.9 | 2.0 | 17.6 | 7. | 10.3 | 6.0 | 25.0 | 22.8 | 11.5 | |
| าณี | | | 4.4 | 4.4 | 1.5 | 1.5 | 4.4 | ີດ | 4.4 | 2.9 | 8.8 | 11.8 | 8.8 | 10.3 | 5,9 | 23.5 | 26.2 | 11.7 | |
| 2 | | | 6.0 | 3.0 | 3.0 | 3.0 | 4.5 | 3.0 | 4.5 | 4.5 | 3.0 | 11.9 | 10.4 | 16.4 | 3.0 | 22.4 | 26.0 | 11.6 | |
| 7 | | | 10.4 | r. | 0.0 | 4.5 | 4.5 | 0.9 | 3.0 | 3.0 | 1.5 | 13.4 | 11.9 | 10.4 | 0 | 20.9 | 26.4 | 8 | |
| 2 | | | 7.8 | 0.0 | 3.1 | 3.1 | 4.7 | 4.7 | 3.1 | 4.7 | 7 | 7 6 | 4 | 4.6 | 7.8 | 25.0 | 27.1 | 12.1 | |
| Ñ | | | 6.5 | 0.0 | 8.1 | 6.5 | 4.8 | 0.0 | 4. 8. | 3.2 | Δ. œ | 3.2 | 9.7 | 21.0 | 0.0 | 27.4 | 26.8 | 12.0 | |
| ALL HOURS | s 1.0 | 1.3 | 7.6 | 2.5 | 3.4 | 3.7 | 3.8 | 3.6 | 3.8 | 3,3 | 4.2 | 11.7 | 9.0 | 11.4 | 6.0 | 23.7 | 25.9 | 11.6 | |
| 100 | 70000 | 10081 | TNC | | | | | | | | | | | | | | | | |

SOURCE: GEORESEARCH, INC.

Table IV - 134

Percentage Frequency Summary for Wind Speed PONDERA COUNTY - HEART BUTTE

(SPRING)

11/13/82 - 05/29/84

| | CALM | 0.1-2.0 | 2.1- 4.0 | 4.1- 6.0 | 6.1- 8.0 | 8.1- 10.0 | 10.1- 1 12.0 | WIND 12.1- 1 14.0 | SPEED 14.1- | (MPH) 16.1- 18.0 | 18.1- 20.0 | 20.1- 25.0 | 25.1- 30.0 | 30.1- 35.0 | 35.1- | ×40, 0 | | |
|------------|----------------|---------|-------------|--------------|-------------|--------------|-----------------|-------------------------|----------------|------------------------|---------------|---------------|---------------|---------------|-------|--------|------|----------|
| | | • | • | | 1 | | MIM | SPEEC | (RET) | ERS/SE | (QNO) | | | | | ? | AV | A |
| | 2 | 0.1 | 9. <u>.</u> | 1.8- -, ' | 2.7- | 3.6 | 4.5- | 5.4 - | 6.3- | 7.2- | %:1- | 9.5 | | 13.5- | 15.7- | ŗ | SEE | SEE |
| | 5 | 5 | 1.0 | 7.7 | o o | o. | n 1 | 2.0 | 7./ | ٥. د | ν. Σ | 7.11 | | | 1/.9 | 6./1 | Ξ | <u>%</u> |
| | 0.0 | 1.0 | 8.2 | 4.1 | 6.2 | 8,2 | 7.2 | 5.2 | 6.2 | 10.3 | 6.2 | 12.4 | 6. 2 | 5.2 | 7.2 | 6.2 | 19.1 | 8.5 |
| (V) | 0.0 | 1.0 | 7.2 | 4.1 | 2.1 | 9,3 | 13.4 | | 4.1 | 4.1 | 6.2 | 17.5 | 7.2 | 7.2 | 2.1 | 7.2 | 19.1 | ထ |
| (T) | . . | 0.0 | 7.4 | 4.2 | 6.3 | 9.5 | 8.4 | | 5.3 | 4.2 | 6.3 | 15.8 | 8.4 | 8.4 | 3.2 | 4.2 | 18.4 | 8.2 |
| 4 | : : | 0.0 | 9 | 5.3 | 6.3 | 7.4 | 4.2 | | 3.2 | 10.5 | 4.2 | 15.8 | 8.4 | 8.4 | 1.1 | 5.3 | 18.1 | ω. |
| (D | | :: | 9.6 | 4.3 | 10.6 | 5,3 | 4.3 | | 4.3 | 7.4 | 3.2 | 16.0 | 8,5 | 6.4 | 4.3 | 5,3 | 18.3 | 8.2 |
| 9 | | 0.0 | 10.6 | 9.6 | 6.4 | 8 2 | 2.1 | | 4,3 | 3.2 | 4.3 | 18.1 | 6.4 | 5,3 | 4.3 | 5,3 | 17.5 | 7.8 |
| 7 | | 0. | 11.7 | შ | 7.4 | ထို | 4.3 | | 0.0 | 10.6 | 4.3 | 12.8 | 7.4 | 11.7 | 1:1 | 4.3 | 17.3 | 7.7 |
| ∞ . | ። | 1.1 | 10.6 | 3.2 | 11.7 | 5.3 | 8,5 | | 3.2 | 7.4 | 4.3 | 14.9 | 9.6 | 5.3 | 4.3 | 5,3 | 17.9 | 8.0 |
| ნ; ≖ | | 1:1 | 9.6 | 4.3 | 7.4 | 7.4 | 6.4 | | 6.4 | 4.3 | 7.4 | 16.0 | 10.6 | 4.3 | 0.0 | 8.5 | 18.3 | 8.2 |
| | | 0.0 | ထို | 0.0 | 2.1 | 9.6 | 9.6 | | 7.4 | 9.6 | 6.4 | 20.2 | 9.6 | 4.3 | 2.1 | 6.4 | 19.6 | ထ |
| 0 | | 0.0 | 9.5 | 1:1 | 4.3 | 7.5 | 3.2 | | 3.2 | 10.8 | 7.5 | 24.7 | 10.8 | 2.2 | 4.3 | 6.5 | 20.5 | 9.2 |
| 12 | | 0.0 | 5. 4 | 1:1 | 2.2 | 3,3 | 5.4 | | 6.5 | 8 | 6.5 | 26.1 | 12.0 | 7.6 | 1:1 | 5.4 | 21.1 | 9.4 |
| U 13 | | 0.0 | 2 | 1:1 | 1:1 | 3.2 | 6,3 | | 6.3 | 3.2 | 12.6 | 16.8 | 14.7 | 10.5 | 4.2 | 5.3 | 22.1 | 9,9 |
| | | 0.0 | ຕຸ້ | 1:1 | 2.1 | 2.1 | ນີ້ | | 7.4 | 5,3 | 10.5 | 15.8 | 16.8 | 10.5 | 5,3 | 6.3 | 22.8 | 10.2 |
| R 15 | | 0.0 | 6,3 | 0.0 | | 2.1 | 6,3 | | 6.3 | 4.2 | 7.4 | 17.9 | 14.7 | 14.7 | 2,1 | 8.4 | 23.1 | 10.3 |
| 16 | | 0 | 6.3 | Ξ. | 3.2 | 0.0 | 4.2 | | 10.5 | 3.2 | 7.4 | 21.1 | 9.5 | 15.8 | 3.2 | 7.4 | 22.9 | 10.3 |
| 17 | | 0.0 | 5.3 | 2.1 | 2.1 | 1:1 | 4.2 | | 9.5 | 8,4 | 8.4 | 14.7 | 9.5 | 11.6 | 7.4 | 8.4 | 23.0 | 10.3 |
| 18 | | 0.0 | 4.3 | Ξ | 3.2 | 2.1 | 4.3 | | 9.6 | 9.6 | 6.4 | 16.0 | 10.6 | 7.4 | 10.6 | 5.3 | 22.4 | 10.0 |
| 19 | | 0.0 | 5.3 | .; : | 2.1 | 6.4 | 11.7 | | 6.4 | 10.6 | 4.3 | 10.6 | 9.6 | 8.5 | 9.6 | 6.4 | 21.6 | 9.7 |
| 20 | | 0.0 | 4.3 | 0.0 | 7.4 | 4.3 | 7.4 | | 12.8 | 3.2 | 7.4 | 10.6 | 10.6 | 7.4 | 9.6 | 5,3 | 21.2 | 9 |
| 21 | | 0.0 | ນ | 2.1 | 6.4 | 5,3 | 5,3 | | 13.8 | 8. 5 | 5.3 | 9.6 | 8.5 | 7.4 | 8.5 | 6.4 | 20.7 | 9.2 |
| 8 | | 1:1 | 5,3 | 3.2 | 3.2 | 6.4 | 11.7 | | 9.6 | 9.6 | 5.3 | 5.3 | 9.6 | 9.6 | 3.2 | 10.6 | 20.6 | 9.2 |
| 23 | | 1:1 | 6.4 | 2.1 | 7.4 | ຜູ | 5,3 | | 5,3 | α, 3 | တ လ | 12.8 | 5,3 | 7.4 | 5,3 | 8 5 | 20.1 | 9.0 |
| 24 | | = | 9.9 | 4.4 | ນຸ | 11.0 | 6.6 | | 7.7 | 5,5 | 4.4 | 15.4 | 4.4 | 4.4 | 7.7 | ω 8 | 19.5 | 8.7 |
| ALL HOURS | 0.4 | 0.4 | 7.1 | 2.9 | 4.9 | 5,9 | 6.5 | 7.3 | 9.9 | 7.2 | 6.5 | 15.7 | 9.5 | 8.0 | 4.6 | 6.5 | 20.2 | 9.0 |
| SUIBLE | GFORESFAR | H.W. | J. | | | | | | | | | | | | | | | |

Table IV - 135

PONDERA COUNTY - HEART BUTTE Percentage Frequency Summary for Wind Speed

(SUMMER)

| 0/ | to |
|-----|----|
| // | Š |
| č | Ŝ |
| 70/ | 70 |
| 4.5 | ì |

| | CALM | 0.1-2.0 | 2.1- 4.0 | 4.1- 6.0 | 6.1- 8.0 | 8.1- 10.0 | 10.1- 12.0 | WIND 12.1- 1 14.0 | SPEED 14.1- : 16.0 | (MPH) 16.1- 1 18.0 | 20.0 20.0 | 20.1- 25.0 | 25.1- 30.0 | 30.1- 3 | 35.1- 40.0 | ×40.0 | ð | W |
|----------|-------|---------|-------------|-------------|-------------|--------------|---------------|-------------------------|--------------------------|--------------------------|--------------|---------------|---------------|---------|---------------|-------|--------|---|
| | | | 9.0 | 1.8 | 2.7- | 3.6- | 4.5- | | 6.3 | 7.2- | 8.1- 1- | 9.0 | 11.2- | 13.5- | 15.7- | | SPEE | |
| | CAL | | 1.8 | 2.7 | 3.6 | 4.5 | 5.4 | | 7.2 | 8.0 | 8,9 | 11.2 | 13.4 | 15.6 | 17.9 | >17.9 | E E | |
| - | | | 2.8 | 7.0 | 8.5 | 19.7 | 18.3 | 7.0 | 6,6 | 8.5 | 4.2 | 7.0 | 0.0 | 1.4 | 1.4 | 0.0 | 12.5 | |
| .~ | | | 5.6 | 4.2 | 12.7 | 19.7 | 15,5 | 8.5 | 7.0 | 2.8 | 2.6 | 8.5 | 2.8 | 2.8 | 0.0 | 0.0 | 12.5 | |
| ***) | | | 7.0 | 14.1 | 8,5 | 6.6 | 12.7 | 14.1 | 4.2 | 8.5 | 2.8 | 7.0 | 0.0 | 4.2 | 0.0 | 0.0 | 11.8 | |
| ~ | | | 8.5 | 6.6 | 6.6 | 8.5 | 16.9 | 16.9 | 1.4 | 4.2 | 4.2 | 7.0 | 2.8 | 1.4 | 1.4 | 0.0 | 11.9 | |
| 4, | | | 5.7 | 10.0 | 14.3 | 11.4 | 11.4 | 11.4 | 4.3 | 4.3 | 8.6 | 8.6 | 0.0 | 0.0 | 1.4 | 1.4 | 11.9 | |
| J | | | 10.1 | 17.4 | 4.3 | 10.1 | 8.7 | 11.6 | 10.1 | 7.2 | 1.4 | 7.2 | 1.4 | 1.4 | 0.0 | 1.4 | 11.6 | |
| _ | | | 7.2 | 11.6 | 14.5 | 8.7 | 8.7 | 8.7 | သ | ည် | 2.9 | 7.2 | 1.4 | 1.4 | 1.4 | 0.0 | 10.9 | |
| w | | | 11.6 | 15.9 | 11.6 | 7.2 | 13.0 | 4.3 | 4.3 | 4.3 | 4.3 | 7.2 | 1.4 | 1.4 | 1.4 | 0.0 | 10.4 | |
| ± | | | 17.4 | 15.9 | 15.9 | 10.1 | 7.2 | 2.9 | 7.2 | 4.3 | 2.9 | 7.2 | 1.4 | 1.4 | 1.4 | 0.0 | 10.3 | |
| 10 | | | 13.0 | 15,9 | 11.6 | 7.2 | 11.6 | 7.2 | 7.2 | љ. 8 | 8,7 | 7.2 | 0.0 | 1.4 | 0.0 | 0.0 | 11.2 | |
| 0 11 | | | 10.1 | 14.5 | 8.7 | 13.0 | 4.3 | 4.3 | 8.7 | 13.0 | 4.3 | 13.0 | 1.4 | 1.4 | 0.0 | 0.0 | 12.4 | |
| 12 | | | 8.7 | 10.1 | 10.1 | 14.5 | 4.3 | 13.0 | 5,8 | 10.1 | 5.8 | 11.6 | 0.0 | 2.9 | 0.0 | 0.0 | 12.6 | |
| U 13 | | | 5.6 | 8,5 | 8.5 | 8.5 | 14.1 | 9.9 | 8.5 | 7.0 | 14.1 | 9.9 | 1.4 | 0.0 | 0.0 | 0.0 | 13.1 | |
| 14 | | | 4.2 | 8.5 | 6 6 | 8 | 14.1 | 4.2 | 6 6 | 6 6 | 6 6 | 14.1 | 5.6 | 0.0 | 0.0 | 0.0 | 14.3 | |
| R 15 | 5 2.8 | | 5.6 | 8. 5 | 7.0 | 6 6 | 8.5 | 2.8 | 5.6 | 14.1 | 12.7 | 15.5 | 5.6 | 0.0 | 0.0 | 0.0 | 14.4 | |
| 16 | | | 7.0 | 6.6 | 8.5 | 2.8 | 4.2 | 16.9 | 14.1 | 15.5 | 7.0 | 11.3 | 1.4 | 0.0 | 0.0 | 0.0 | 13.8 | |
| 17 | | | 8°2 | 1.4 | 8,5 | 9.9 | 14.1 | 7.0 | 21.1 | 11.3 | 4.2 | 6,0 | 2.8 | 0.0 | 0.0 | 0.0 | 13.6 | |
| 31 | | | 1.4 | 4.2 | 4.2 | 14.1 | 16.9 | 16.9 | 14.1 | ထို | 7.0 | 5.6 | 1.4 | ۰, 8 | 0.0 | 0.0 | 13.8 | |
| 15 | | | 2.8 | 5.6 | 4.2 | 19.7 | 12.7 | 19.7 | 12.7 | 6.6 | 1.4 | 1.4 | 4.2 | 2.8 | 0.0 | 0.0 | 13.1 | |
| 2 | | | 1.4 | 2.8 | 11.3 | 16,9 | 22.5 | 14.1 | 8,5 | 4.2 | 2.8 | 7.0 | 2.8 | 4.2 | 0.0 | 0.0 | 13.6 | |
| 7 | | | 5,6 | 5,6 | 4.2 | 15.5 | 23.9 | 11.3 | 7.0 | 7.0 | 4.2 | 5.6 | 1.4 | 7.0 | 0.0 | 0.0 | 13.8 | |
| 23 | | | 1.4 | 8.6 | 7.1 | 14.3 | 15.7 | 20.0 | 5.7 | 8.6 | 4.3 | 4.3 | 1.4 | 1.4 | 1.4 | 0.0 | 12.7 | |
| 23 | | | 4.3 | 8,6 | 11.4 | 21.4 | 14.3 | 12.9 | 7.1 | 5.7 | 5.7 | 5.7 | 0.0 | 1.4 | 1.4 | 0.0 | 12.5 | |
| 5 | | 4.3 | 2.9 | 2.9 | 8.6 | 20.0 | 17.1 | 18.6 | 7.1 | 2.9 | 5.9 | 10.0 | 0.0 | 2.9 | 0.0 | 0.0 | 13.0 | |
| SAI HURS | 7 | 7.7 | 9 | 6.0 | 6 | 12.6 | 13.0 | 11.0 | 8 | 7.7 | اد) ادا | α, | 1.7 | - | 0.5 | 0.1 | 12.6 | |
| | • | • | • | , | • | 1 | 2 | • | ָ י | : | • | 3 | • | • | 3 | • | i | |

Table IV - 136

Percentage Frequency Summary for Wind Speed

| | | | | AV | SPEED | (MPH) | 14.5 | 14.6 | 14.6 | 14.6 | 14.3 | 14.2 | 13.7 | 13.7 | 14.2 | 14.8 | 15.8 | 15.8 | 16.1 | 16.2 | 16.4 | 16.9 | 16.3 | 16.2 | 16.0 | 15.9 | 16.4 | 15.7 | 15.9 | 15.2 | 15.3 |
|------------------------------|----------|---------------------|----------|---|-------|-------|------|------|------|------|------|------|------|------|--------|---------|--------|------|------|------|------|------|----------|---------|------|------|------|------|------|------|-----------|
| | | | | >40.0 | | >17.9 | 1.8 | 8. | 0.9 | 1.8 | 0.9 | 1.9 | 1.9 | 1.9 | 2.8 | 1.9 | 1.9 | 3.0 | 1.9 | 1.9 | 1:9 | 2.8 | ۳. در | 4.6 | 4.6 | 5.6 | 2.6 | 2.8 | 2.9 | 2.1 | 2,6 |
| | | | ₹ 1 | 40.0 | 15.7- | | 0.9 | 0.9 | 0.9 | 6.0 | 0.0 | 6.0 | 0.9 | 0.0 | 0.0 | 0.9 | 1.0 | 2.0 | 0.9 | 0.9 | 6.0 | 6.0 | 0.0 | 6.0 | 6.0 | 6.0 | 1.9 | 0.0 | 2.0 | 1.0 | 0.9 |
| | | | ک 1- | 35.0 | 13.5- | 15.6 | 4.6 | 3.7 | 4.6 | 2.8 | 1.8 | 2.8 | 3.7 | 1.9 | 5.6 | 1.9 | ۳ ش | 3.0 | 3,7 | 4.6 | 4.6 | 4.6 | 4.6 | 1.9 | 5.6 | 6.5 | 4.6 | 4.7 | 2.9 | 3.1 | 3.8 |
| | _ | | | 30.0 | 11.2- | 13.4 | 4.6 | 6.4 | 4.6 | 5,5 | 7.3 | 6.5 | 8,3 | 5.6 | 1.9 | 5.7 | 8.6 | 1.0 | 4.6 | 5.6 | 3.7 | 3.7 | | 9 | 4.6 | 1.9 | 5.6 | 8.4 | 8 | 7.2 | 5.5 |
| PONDERA COUNTY - HEADT BITTE | | | 20 1- | 25.0 | 9.0 | 11.2 | 12.8 | 13.8 | 15.6 | 14.7 | 15.6 | 13.0 | 8.3 | 16.7 | 13.1 | 12.3 | 12.4 | 19.0 | 21.3 | 14.8 | 13.9 | 11.1 | 13.9 | 13.0 | 12.0 | 15.7 | 18.5 | 16.8 | 14.7 | 15.5 | 14.5 |
| YT RI | | | |) 14.0 16.0 18.0 20.0 IND SPEED (METERS/SECOND) | 8.1- | 8.0 | 1.8 | 4.6 | 6.4 | 7.3 | 7.3 | 7.4 | 1.9 | 3.7 | 7.5 | 9.4 | 4.8 | 6.0 | 7.4 | 13.0 | 18.5 | 16.7 | 6.5 | 4.6 | ထိ | 7.4 | 2.8 | 5.6 | 4 | 5.2 | 7.1 |
| TFAL | 7 | 9/84 | (F) | 18.0 TERS/SI | 7.2- | 8 | 7.3 | 5.5 | 6.4 | 9.2 | 4.6 | 3,7 | 4.6 | 5.6 | 10,3 | 8 .5 | 12.4 | 12.0 | 6.5 | 7.4 | 7.4 | 13.0 | ۳ ا | ۳. م | 3,7 | 5,6 | 6,5 | 5.6 | 4.9 | 6.2 | 7.3 |
| > | (AUTUMN) | 11/13/82 - 05/29/84 | 3 SPEEI | 16.0 (3E) | 6,3- | | | | | | | | | | | | | | 6.5 | | | | • | | | | | | | | 6.4 |
| . Ż | (AUT | /13/82 | MIN 1 | 14.0 SPEI | 5.4- | 6.3 | 9.2 | | | | | | | | | | | | | | | | | | | | | | | | 7.5 |
| . V | | 11 | 10. | 12.0 W | 4.5- | 5.4 | 8,3 | | | | | | | | | | | | | | | | | | | | | | | | 7.7 |
| י ביי ביי | | | | | 3.6- | | 11.0 | 7.3 | 7.3 | 11.9 | 11.0 | 10.2 | 10.2 | 5.6 | 5.6 | 6.6 | 10.5 | 13.0 | 6.5 | 6 | 6.5 | 5.6 | 6 | 11.1 | 13,9 | ထိ | S. | 6,3 | 6 | 6.2 | 8.8 |
| Q | 5 | | | | 2.7- | 3.6 | 9.2 | | | | | | | | | | | | | | | | | | | | • • | | | | 7.4 |
| | | | | | 1.8 | | 6.4 | | | | | | | | | | | | | | | | | | | | | | | | 6.2 |
| | | | | | 9.0 | | 4.6 | | | | | | | | | | | | | | | | | | | | | | | | 6,1 |
| | | | <u>.</u> | | | 0.9 | 5.5 | | | | | | | | | | | | | | | | | | | | | | | | 5.0 |
| | | | | SALM | | SAE | 4.6 | | | | | | | | | | | | | | | | | | | | | | | | 3.2 |
| | | | | | | | 1 | 2 | က | 4 | S. | 9 | 7 | | 6 ± | | 0 11 | 12 | U 13 | | R 15 | 16 | 17 | 81 | 61 | 2 | 21 | 8 | 23 | 24 | ALL HOURS |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

SOURCE: GEORESEARCH, INC.

Table IV - 137

Annual Wind Rose Distribution

PONDERA COUNTY - HEART BUTTE

11/13/82 - 05/29/84

| DIRECTION SPEED (M/SEC) | 0.1- 0.4 0.5- 0.9 1.0- 1.3 S 1.9- 2.2 E 2.3- 2.7 E 2.8- 3.1 D 3.2- 3.6 3.7- 4.0 M 4.1- 4.5 E 4.6- 4.9 T 5.0- 5.4 E 5.0- 5.4 E 5.5- 5.8 R 5.9- 6.3 S 6.8- 7.2 S 7.7- 8.0 C 8.1- 8.5 O 8.6- 8.9 N 9.0-11.2 D 11.3-13.4 13.5-15.6 |
|---------------------------|--|
| NNW TOTAL | 22 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 |
| | 0.12 0.13 0.13 0.14 0.15 0.17 0.17 0.17 0.17 0.17 0.17 0.17 0.17 |
| ₹ | 0.2 0.3 0.3 0.3 0.6 0.6 0.7 0.7 0.0 0.8 0.0 0.8 0.0 0.0 0.0 0.0 0.0 0.0 |
| MIN. | 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0 |
| 3 | 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 |
| MSM | 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0 |
| ß | 0.2 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1 |
| MSS | 0.12 0.13 0.13 0.13 0.13 0.13 0.13 0.13 0.13 |
| S | 0.3 0.3 0.3 0.3 0.3 0.3 0.1 0.1 0.1 0.0 0.0 0.0 0.0 0.0 0.0 0.0 |
| SSE | 0.11 0.12 0.13 0.13 0.13 0.13 0.14 0.15 0.15 0.15 0.15 0.15 0.15 0.15 0.15 |
| 뽔 | 0.11 0.22 0.23 0.11 0.01 0.00 0.00 0.00 0.00 0.00 0.0 |
| ESE | 0.2 0.2 0.2 0.0 0.0 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1 |
| ш | 0.3 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1 |
| EN | 0.2 0.1 0.1 0.1 0.1 0.1 0.1 0.0 0.0 0.0 0.0 |
| 뿔 | 0.2 0.2 0.2 0.2 0.2 0.2 0.3 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1 |
| N N | 0.11 0.11 0.11 0.01 0.00 0.00 0.00 0.00 |
| Z | 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0 |
| DIRECTION> SPEED (MPH) | 0.1-1.0 1.1-2.0 2.1-3.0 3.1-4.0 8.41-5.0 P. 5.1-6.0 E. 6.1-7.0 E. 13.1-10.0 M. 10.1-11.0 I. 11.1-12.0 I. 12.1-13.0 E. 13.1-14.0 S. 14.1-15.0 I. 12.1-13.0 I. 12.1-14.0 S. 14.1-15.0 I. 13.1-16.0 I. 13.1-16.0 I. 13.1-16.0 I. 13.1-16.0 I. 14.0 S. 14.1-16.0 I. 15.1-16.0 I. 15.1-16.0 II I. 15.1-1 |




Table IV - 138

Coefficients of Weibull Distribution

PONDERA COUNTY - HEART BUTTE

11/13/82 - 05/29/84

| MONTH | SCALE FACTOR (C) (M/SEC) | SHAPE FACTOR (K) |
|-----------------------------|--------------------------------|--|
| CCEUCAPAEA CC≺↑PGLN⊀RRBN | | 4488 6664 6664 7266 7266 7266 7362 7362 7362 7362 7362 |
| IEAK | 8,9803 | 1.4363 |

BROADUS RANDALL RANCH

POWDER RIVER COUNTY


The Randall Ranch air monitoring site was established by the Montana Air Quality Bureau to measure background levels of particulates in southeastern Montana. The site was located at 45 24 27 N and 105 27 50 W (Site No. 102 on Map II-1), approximately 5 miles south of Broadus on a bluff overlooking the Powder River. Elevation at the site was 3,120 feet.

Wind data were gathered at this site from March 6, 1976, to August 27, 1978. The data set contains hourly averages of wind speed and wind direction manually reduced from stripchart records. The wind recorder, a Meteorology Research, Inc., mechanical recording anemometer and wind vane, was located 4 meters above ground level.

Winds were monitored long enough to adequately represent the wind resource at this location. The site also is representative of a large portion of southeastern Montana. Data recovery, which for the entire period was 60.3 percent, ranged from 38.4 percent in December to 97.3 percent in May.

Average monthly wind speeds varied from 8.2 miles per hour in September to 12.5 miles per hour in December. Average annual wind speed was 10.1 miles per hour. December through May were the windiest months. The lowest wind speeds occurred from July through September.

Average annual wind power was 118.9 watts/m². Average monthly wind power values ranged from 67.6 watts/m² in September to 167.7 watts/m² in December.



Monthly Wind Speed Distribution **Table IV - 139**

POWDER RIVER COUNTY - BROADUS RANDALL RANCH

03/06/76 - 08/27/78

| | CALM 00.1-1 11.00-1 | |
|------|--|---|
| YEAR | 000151100031100111000100000000000000000 | 10.1 4.5 118.9 60.3 |
| DEC | 0000-8000000000000000000000000000000000 | 12.5 5.6 167.7 38.4 |
| NOV | 0000-0000000000000000000000000000000000 | 9.9 4.4 107.6 41.5 |
| OCT | 000130013001300000000000000000000000000 | 9.0 4.0 85.8 |
| SEP | 00000000000000000000000000000000000000 | 8.2 3.7 67.6 62.3 |
| AUG | 00.00.00 | 8.5 3.8 70.3 55.2 |
| JUL | 000000000000000000000000000000000000000 | 8.5 3.8 75.0 52.1 |
| NUC | 00000-0200044200000-0000000000000000000 | 9.0 4.0 80.8 |
| MAY | 000000000000000000000000000000000000000 | 10.8 4.8 144.0 97.3 |
| APR | 000をおよるともなりなどとうのうりももとしてもののできるようできるもののでもなりなりなりをもれるのでもののでもというないというないというないといいない。 | 11.4 5.1 163.4 93.9 |
| MAR | 00037-120333333000000000000000000000000000000 | 11.0 4.9 163.6 42.6 |
| FEB | 000-000-000-000-000-000-000-000-000-000- | 11.9 5.3 153.6 50.0 |
| JAN | 00004000000000000000000000000000000000 | 10.1 4.5 136.7 49.6 |
| | CALM O.1-12.0 1.1-2.0 D. 6.1-3.0 D. 6.1-4.0 A. 1-5.0 CALM A. 1-6.0 C. 1-10.0 C. 10.0 C. 1 | AVERAGE SPEED (MPH) AVERAGE SPEED (M/SEC) AVERAGE WIND POWER (WATTS/M**2) PERCENT DATA RECOVERY |

DNOCES/SRETER DEFE

ANEMOMETER HEIGHT # 4 METERS = 13 FEET NUMBER OF OBSERVATIONS = 13092
PERCENTAGE DATA RECOVERY = 60.3

COLSTRIP BN

ROSEBUD COUNTY

The Colstrip BN air monitoring site was established by the Montana Air Quality Bureau to measure concentrations of particulates, sulfur dioxide, and nitrogen dioxide in the air at Colstrip. The site was located approximately 2 miles southeast of Colstrip on top of an isolated hill at 45 51 30 N and 106 34 43 W (Site No. 109 on Map II-1). Elevation at the site was 3,575 feet

The land in the area is hilly, with isolated steep-sided bluffs rising above the stream valleys. About 10 miles to the south, a steep escarpment rises abruptly to around 4,500 feet.

Although most of the land in the area is privately owned, a few scattered sections are controlled by the state and the Bureau of Land Management. The Northern Cheyenne Indian Reservation lies about 12 miles to the south.

Electrical power in the area is provided by the Montana Power Company and the Tongue River Electric Cooperative. Because Colstrip is a major electrical generation center, many electrical transmission lines cross the

Wind data were gathered at the site from January 1, 1975, to August 22, 1979. The wind recorder was a Meteorology Research, Inc., mechanical recording anemometer and wind vane located 4 meters above ground level. The data set consists of hourly averages of wind speed and wind direction. Data recovery was poor to fair, ranging from 11.3 percent in November to 78.2 percent in September. Overall data recovery was 39.5 percent.

Winds were monitored long enough, however, to represent the wind resource at this location. The data also are representative of other open, exposed, and elevated locations in the southern Rosebud County area.


Average annual wind speed at this site was 12.9 miles per hour. Average monthly speeds varied from 9.6 miles per hour in September to 16.8 miles per hour in February. The windiest months were January through April. The lowest wind speeds occurred during the months of July through

Average monthly wind power ranged from 205.7 watts/m² in July to 818.1 watts/m² in February. Average annual wind power was 453.6 watts/m²

Average seasonal wind speeds were 11.0 miles per hour in autumn, 11.3 miles per hour in summer, 13.6 miles per hour in spring, and 16.2 miles per hour in winter. The highest average wind speeds occurred during the midafternoon in spring and autumn, early evening in summer, and early morning and mid-afternoon in winter. The lowest average wind speeds occurred in early morning during the summer, in early evening during the autumn and winter, and in early morning and early evening during the spring.

The diurnal range of average wind speeds was greatest in spring and summer and least in winter.

The most common wind directions were west and west-northwest. Winds from the north-northeast and northeast were least common. By direction, average wind speeds varied from 8.6 miles per hour for winds blowing from the east-northeast to 17.2 miles per hour for westerly winds.



SCHEO ZHFEKS/SHOOND

Table IV - 140

Monthly Wind Speed Distribution ROSEBUD COUNTY - COLSTRIP BN

01/01/75 - 08/22/79

| | ALM | 99.7.7. | |
|------|---|---|--|
| | 000 | ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, | |
| YEAR | 0 0 0 | | 12.9 5.8 453.6 39.5 |
| DEC | 00-64600044469 | | 14.4 6.4 716.9 22.6 |
| NOV | 00000000000000000000000000000000000000 | | 14.3 6.4 490.4 |
| 0CT | 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0 | . | 12.4 5.6 355.2 55.5 |
| SEP | $\begin{array}{cccccccccccccccccccccccccccccccccccc$ | | 9.6 4.3 257.3 78.2 |
| AUG | -4v4y-00000c | | 11.5 5.1 353.8 |
| JUL | 00100000000000000000000000000000000000 | | 10.6 4.7 205.7 34.3 |
| NOC | 00000000000000000000000000000000000000 | | 11.7 5.2 287.0 3 |
| MAY | 00044040404000 | | 12.1 5.4 361.0 3 |
| APR | 000-0004-0004-000 | | 15.5 6.9 622.3 3 |
| MAR | 000-0000000444 | 44 84 84 85 7 7 7 7 8 8 8 8 8 8 8 8 8 8 8 8 8 8 | 14.8 6.6 677.1 (|
| FEB | 0000-0000000000000000000000000000000000 | | 16.8 7.5 818.1 40.8 |
| JAN | 0.4044444444444444444444444444444444444 | | 16.5 7.4 763.9 8 |
| | 0-13.84.00-0 1111-08-10-0-10-10-10-10-10-10-10-10-10-10-10-1 | 13.1-14 14.1-15.1-15.1-16.1-17.1-17.1-17.1-17.1-17.1-17.1-17 | AVERAGE SPEED (MPH) AVERAGE PEED (M/SEC) AVERAGE WIND POWER WATTS/M**2) ERCENT DATA RECOVERY |
| | | | ν |

ANEMOMETER HEIGHT = 4 METERS = 13 FEET NUMBER OF OBSERVATIONS = 16048
PERCENTAGE DATA RECOVERY = 39.5

Table IV - 141

Percentage Frequency Summary for Wind Speed ROSEBUD COUNTY - COLSTRIP BN (WINTER)

01/01/75 - 08/22/79

| AV FED 'SEC) | | 01 |
|---|--|------------------------|
| S. W. | 77777777777777777777777777777777777777 | 7.2 |
| AV SPEED MPH) | ϕ | 6.2 |
| v, - | | 0 |
| >40.0 | | - |
| 35.1- 40.0 15.7- 17.9 | 00-00-00-00-00-00-00-00-00-00-00-00-00- | 2.0 |
| 30.1- 35.0 13.5- 15.6 | | ε. ε. |
| 25.1- 3 30.0 11.2- 1 | 86.888656688666767688606886666886668866886688668 | 4.6 |
| 10 10 | ************************************** | ٥. |
| 20.1- 25.0 | 40000000000000000000000000000000000000 | 15 |
| 18.1- 20.0 8.1- 8.9 | 04-08-0049-0049-009-00-80-00-00-00-00-00-00-00-00-00-00-00- | 7.3 |
| 4PH) - 16.1- 0 18.0 /SEC) - 7.2- 2 8.0 | 950 950 950 950 950 950 950 950 950 950 | 4.8 |
| 16. (F. 3.) | 7411888867.0011.7.7.4.9.8.8.8.00.001.00.001.8.8.8.8.00.00.00.00.00.00.00.00.00.00.0 | 9.2 |
| SPE 1- 1-0 1-0 1-1-1 1-1-1 | | 8.2 |
| WIND 34.5- 5.4 6 | 00000000000000000000000000000000000000 | 8.6 |
| τ= | | |
| 8.1- 10.0 3.6- 4.5 | 80-48-0-804-058000-88-00 40-48-0-804-058-00-8-00 6-84-0-84-0 | 7.9 |
| 6.1- 8.0 2.7- 3.6 | 6000-00000-00000-0000-000 60000-0000-00 | 7.4 |
| 4.1- 6.0 1.8- 2.7 | $\frac{1}{2}$ | 9.9 |
| 2.1- 4.0 0.0- | 0.4446644666666666666666666666666666666 | 3.5 INC. |
| 0.1- 2.0 0.1- 0.9 | 0.0000000000000000000000000000000000000 | |
| CALM CALM | 000000000000000000000000000000000000000 | S 0.0 0.6 GEORESEARCH, |
| 5 0 | - 2007 - 200 | RS GEC |
| | ΞΟ⊃ α | ALL HOURS SOURCE: |
| | | |

Table IV - 142

Percentage Frequency Summary for Wind Speed ROSEBUD COUNTY - COLSTRIP BN (SPRING)

01/01/75 - 08/22/79

| | _ | ٥ (| • | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|------------------|-----|------------|------------|----------|------|------|----------|-----------|------|------------|---------|----------|------------|------|----------|----------------|----------|-------------|------------|----------|----------|----------|----------|-----|-----------|
| | | SPEED (M/SFC) | ? | 9 | 9.0 | ר ת ה | , , | . 60 | 9 | 6.0 | 6.0 | 6.2 | 6.1 | 6.5 | 7 9 | 9 | 6.5 | 9.9 | 6.5 | 4.9 | 5.9 | 5.6 | 5.7 | 5.9 | 9 | 6.0 | 6.1 |
| | 8 | SPEED | | | | 77. | | | | | | | | | | | | | | | | | | | | | 13.6 |
| | >40.0 | >17.9 | | | | 9 0 | | | | | | | | | | | | | | | | | | | | | 9.0 |
| | 35.1- 40.0 > | 15.7- | ` | ~ . | 2,0 | 9.0 | 2 | 0 | 0.0 | 1.2 | 9. | 1.8 | 0.0 | 0.0 | 1.8 | 1.2 | 8. | 1.2 | 1.8 | 9.0 | 9.0 | 9.0 | 1.2 | 1.2 | 1.2 | 1.8 | 1.1 |
| | 30.1- 35.0 | 15.6 | | • | • | 200 | • • | | • | • | • | | | | | | | • | | | • | | | | | | 1.9 |
| | 25.1- 3 | 11.2- | , | • | • | , , | | | • | | • | | | | | | | | | | | | - | | - | _ | 8.4 |
| | 20.1- 2 25.0 | 9.0-1 | | 7.5 | - c - c | 10.9 | 12.7 | 13.3 | 10.3 | 11.0 | 11.0 | 10.4 | 10.5 | 11.6 | 12.0 | 15.7 | 13.9 | 13.3 | 13.4 | 17.0 | 13.3 | 1.4 | 9.6 | 10.9 | 12.2 | 7.3 | 12.0 |
| | 18.1- 2 20.0 | 8.1- | . , | | ن۸ | 2 | ω. | 9 | ٥. | | ٣, | ≠ . | φ. | | ≠ . | ٥į | _ | m | _ | ς. | œ. | 0 | ထ | Ŋ | رك | 80 | 0.9 |
| , | 6.1- 18.0 5 | 7,2- 8.0 | | | | 6.7 | | | | | | | | | | | | | | | | | | | | | 7.6 |
| | 0 (MPH 4.1- 1 16.0 (M/SE | <u>ب</u> ۵ | (| n (| 20.5 | 10.3 | 7.8 | 10.8 | 7.3 | 9. 8. | 7.9 | 7 | 6 | 12.2 | 13.3 | 9.6 | 2.6 | 11.5 | 5.5 | ر. د. | 9.9 | 5.4 | 9.0 | 6.1 | | 7.6 | 9.5 |
| 1 | 180 SPEED 12.1- 14. 14.0 16 ND SPEED (| 5.4-6.3 | , | ٠, | ى د | . 6 | 0 | o. | ď | - | ≠. | Ŋ | m | تى | 0 | Ŋ | <u>-</u> | Ň | ان | ر ن | ۰, | ⇒ | Q | Ŋ | = | 6 | 7.6 |
| | 10.1- 12. 12.0 14 WIND S | 4.5- 5.4 | , | | | | | | | | | | | | | | | | | | | | | | | | 9.6 |
| | 8.1- 1 10.0 | 3.6- | • | ώL | - ^- | 15.2 | ~ | 80 | آبا ا | N. | Ŋ | Ŋ. | ω. | 9 | ω | o. | | , , | <u> </u> | <i>ر</i> د | ا ر | · | ~ | m. | 9 | ī. | 2.3 |
| | <u>+</u> 0. | 3.6 | c | ٦,٢ | - ~ | 10.3 | 0 | 6 | ις\ | 0 | 9 | ο, | · · | ~ | α, | Φ, | ر ا | ס ו | ر | <i>ا</i> رد | N I | ΔI | - | 0 | ထ | က | 10.8 |
| | 4.1-6.0 | | | | | | | | | | | | | | | | | | | | | | | | | | 9.6 |
| | 2.1- | | | ٠. | - LC | 8.4 | 0 | ω, | m (| ומי | ~ | ~ (| э. 1 | | . | 0 | m v | | NI C | NI C | ٠, | . | m i | ~ | ~ | ~ | 4.5 |
| | 0.1- % 2.0 | _ | ¢ | | | 9.0 | | | | | | | | | | | | | | | | | | | | | 0.3 |
| | CALM | CALM | 0 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | ٥. د د | 0.0 | 0.0 | 0.0 | ٥.٥ | 0.0 | 0.0 | 0.0 | 0.0 | > c | | 0.0 | ٥.٥ | 0.0 | o. o. | 0.0 | 0.0 | 0.0 |
| | J | J | | | | 4 | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | : | r | (| 0 | - | > | 4 | ¥ | | | | | | | | | | ALL HOURS |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Table IV - 143

ROSEBUD COUNTY - COLSTRIP BN (SUMMER) Percentage Frequency Summary for Wind Speed

01/01/75 - 08/22/79

| | | ရှင် | | | | | | _ | | | | _ | | _ | | _ | | | | ٠ | | | | | | | _ | |
|----------|-------------------------------|------------------|------|---------------|----------|-------------|------------|-----|---|-----|----------------|--------|-----|---------|----------|----------|----------|----------|----------|------|----------|-------------|----------|------|------|--------------|--------------|--------------|
| | | SPEED (M/SEC) | 5.1 | 4.9 | 4 - | † - | , = | | 1 | - | | | | , i | ν. η. | | , , | | N. | U I | U R | , H | ٠, | | V. | , | 5.1 | |
| | ≥ | MPH) | | 0 | | | | | | | | | | | | | | | | | | | | | | | . . | |
| | • | S N | Ξ | Ξ; | - 4 | 2 : | 2 5 | 2 | 2 2 | ? ; | 2 - | - ; | - ; | - ; | - ; | =; | =; | Ξ; | = ; | - 5 | 7 5 | | - ; | | Ξ; | | - | |
| | >40.0 | >17.9 | | 0.0 | | | | | | | | | | | | | | | | | | | | | | | 0.2 | |
| , | 35.1- 40.0 | 15.7- | 0.0 | 0.5 | 0.0 |)) (| 90 | 90 | | | 9 | 0.0 | 200 | 0.0 |)) | | ٠. د. | ٠. د. | - , | - 0 |) · | - (| o. o. | 0.0 | 0.0 | 1.1 | 4.0 | |
| | 30.1 - 35.0 | 13.5- 15.6 | 1.6 | 0.5 | - 0 | ٠ د د | ه د د د | | 9 4 | 0 0 | 0,7 | - , | - 0 | 0.0 | 0.0 | 0,0 | -, | - 1 | ٠. د. | 0.0 | N C |)) (| 0 | | | -:- | 0.7 | |
| | 25.1- 30.0 | 11,2- 13,4 | 2.2 | 2.2 | ر د د | N C | N - | | - 4 | , | ų , | - (| N C | N' | 0.0 | ٥. د. | 0 | 0.5 | - (| N : | ٠. د. | | <u> </u> | 1.7 | 1.7 | ю | 1.7 | |
| | 20.1- 25.0 | 9.0- | 9.9 | 4 | 9.9 | Ξ, | - ° | 0 - | , 0 | 200 | 9.0 | ~ · · | 0.3 | χ. (| 20.5 | 13.0 | ×. | 6 | 9 | | 9.5 | - (| ω | 6.1 | 8 | ٥ خ | 8 | |
| | 18.1- 20.0 | 8.1-8.9 | | 9.9 | • | | • | • | • | • | • | | | | ٠ | • | • | • | • | ٠ | • | • | • | | • | | 5.5 | |
| Ě | 16.1- 18.0 SEC) | _ | - | 5.5 | | ٠ | | ٠ | ٠ | | | | | | | ٠ | ٠ | | • | ٠ | • | | • | • | • | | 6.9 | |
| EED (MPI | - 14.1- 0 16.0 EED (M/S | 6.3- | 7.1 | 10.9 | 9,3 | 61 |) · / | ,, | 0.7 | . 0 | 0,1 | ., | 9.0 | | ر س | 7:1 | 7.7 | 10.3 | ο. 8 | o, | 9.9 | יי איני | ۰. 8 | 11.6 | 6.6 | 7.1 | 8.1 | |
| S | ÷ | 2.0 | 14.3 | 9.3 | 8.6 | 13.1 | 9.5 | 5° | 0.0 | 1 1 | -1 | , , | 0.9 | 6.0 | æ • | 9.8 | 14.2 | 16.8 | 10.4 | 10.9 | 8 | 9 | 10.6 | 11.0 | 11.6 | 11.5 | 10.4 | |
| 3 | 10.1- 12.0 | 4.5- | 17 | 10.9 | 0 | 0 | # ; | -; | 2 | ų c | , , | 2 | 2 | 0 | 6 | 5 | 9 | φ. | 14. | 5. | <u>.</u> | 0, | <u>.</u> | 5 | 7 | - | 12.3 | |
| | 8.1- 10.0 | 3.6- | 0 | 15.3 | 16 | 13 | ⊉ (| 7 | , | 7 0 | , ر | _ | 7 | 17 | 18 | 13 | 15 | 10 | 12 | _ | 2 | 35 | 5 | 18 | 'n | 15 | 13.8 | |
| | 6.1-8.0 | 2.7-3.6 | 5 | 12.6 | 10. | <u></u> | 13. | = ; | <u>, , , , , , , , , , , , , , , , , , , </u> | - : | 2 | 2 | 14. | = | = | 15 | 16. | 12. | Ξ. | œ | 0 | ~ | = | _ | œ | o, | 12.6 | |
| | 4.1-6.0 | 1.8- | | 8 | | | | | | | | | | | | | | | | | | | | | | | 10.1 | |
| | 2.1- 4.0 | 0.0- | 7 | 7.7 | ∞ | ø | m, | o r | ~ (| ⊇' | ∞ • | ထ | m | ⇉ | ~ | 0 | m | N | 2 | m | C | - | m | φ | K) | _ | 5.3 | INC. |
| | | 0.1- | - | . | - | ⇉ | -7 | m (| د | יח | ~ | m | m | N | ຕ | C. | N | ⇉ | N | N | m | N | m | m | m | m | 3.7 | EARCH, |
| | CALM | CALM | | 0.0 | | | | | | | | | | | | | | | | | | | | | | | 9.0 | GEORESEARCH, |
| | | | | - 64 | m | ⇒ | ī, | 91 | ~ • | | | 10 | | 12 | 1 13 | 14 | | 16 | 17 | 18 | 19 | 20 | 2 | 22 | 23 | 77 | ALL HOURS | SOURCE: |
| | | | | | | | | | | | I | | 0 | | د | | ~ | | | | | | | | | | ALt | SOL |

Table IV - 144

Percentage Frequency Summary for Wind Speed ROSEBUD COUNTY - COLSTRIP BN (AUTUMN)

01/01/75 - 08/22/79

| | } | SPEED (/SEC) | 6 | 6 | ۲. | ۲. | 0. | ٧. | ω, | . 00 | 0 | . 0 | 6 | . 6. | | ~ | 7 | ⊅ | _ | · & | , rJ | 'n | ۰ | ۰ | 6 | 0 | 0 |
|----------|------------------------|---------------------------|---|------------|----------|--------------|---------------|-------|----------|------|------|------|------|----------|----------|----------|------|----------|------|--------|---------------|---------------------|------------|---------|---------|------|-----------|
| | | SPEED SP (MPH)(M/ | ٦ - | 7 0 | 9 | 2 | ار | 5 | 7 | | -77 | · r. | · ~ | 7 C | . 10 | 3 | | 5 | ic. | 7 | . | - | ~ | ** | 7 | 7 | 7 0 |
| | • | SPI (MF | ======================================= | 1. | = | 1. | Ξ. | Ξ. | 10. | 10. | 10 | = | _ | Ξ | Ξ | 1. | 12. | 12. | - | 10. | 10 | 10. | 10. | 10 | 10. | 10. | Ξ |
| | >40.0 | >17.9 | | | • | • | | | | | | | | | | | 9.0 | | | | _ | | | | | | 0.5 |
| 1 | 40.0 | 15.7- | 0.0 | 0.0 | 0.0 | -: | 9.0 | 9.0 | 0.0 | 0.6 | - | _ | 0.0 | 0.0 | - | - | - | 2.3 | - | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.5 |
| | 35.0 | 13.5- 15.6 | 0.0 | 0.0 | 9.0 | 0.0 | -: | 0.0 | -: | -: | 1.7 | 2 | 2,8 | 3.4 | 2 | 2.3 | 2.3 | | 1:1 | 1.7 | 0.0 | 9.0 | 0.0 | 0.0 | 0.0 | 0.0 | .: |
| | 30.0 | 11.2 - 13.4 | 2.3 | 2.8 | 2.3 | 2.9 | 2.8 | 3.4 | 0.0 | 1.7 | 1.7 | 1.7 | 2.3 | -: | 2.3 | 2.3 | 3.4 | 3.4 | 5.1 | 2.3 | 4.0 | 2.5 | 2,3 | -: | 3.4 | 2.9 | 2.5 |
| | 25.0 | 9.0- | 9.8 | 9.0 | 11.9 | 8.6 | 6.3 | 5.7 | 9.1 | 0.0 | 5.1 | 6.2 | 7.9 | 12.4 | 11.9 | 10.7 | 9.6 | 10.2 | 5.7 | 7.3 | 5.6 | 5.6 | 5.1 | 6.3 | ر. ت | 6.3 | 7.9 |
| | 20.0 | 8.1- | • | • | • | | ٠ | • | • | | | | • | • | | • | 4.5 | | | • | | | | | | - | 4.7 |
| - 1 | 18.0 EC) | 7.2- 8.0 | | • | • | • | • | • | | | | | | | | | 9.6 | | | | | | | | - | _ | 5.8 |
| EED (MPH | 16.0 16.0 D (M/S | 6.3- | 4.6 | 2.6 | 6.2 | 9.1 | 5.7 | 0.4 | 6.9 | 9.1 | 7.3 | 9.0 | 5 | 5.1 | 9 | 8.9 | 9.6 | ٥. | 8,5 | 0.6 | 7.3 | ગ . છ | 6.8 | 7.6 | 9 | 9.5 | 7.4 |
| ᄴ | 14.0 ND SPEE | 5.4-6.3 | 14.3 | | • | • | • | • | | | | | | | | | 10.7 | | - | | - | - | - | - | | | 9.1 |
| 3 1 | 12.0 14. WIND SE | 4.5- 5.4 | 13.1 | 14.1 | 9.0 | 12.0 | 14.2 | 7.6 | 12.0 | 15.3 | 7.3 | 1.9 | 9.6 | 7.9 | 10.7 | 6.2 | 7.3 | -1.9 | 1.9 | 1.3 | 15.8 | 14.0 | <u>-</u> - | 15.4 | 17.2 | 14.4 | 11.9 |
| , - | | 3.6- 4.5 | 13.1 | 15.8 | 0.6 | 13.7 | → | 0.9 | 14.3 | 1.9 | 16.4 | 9.6 | 14.7 | 14.0 | 11.3 | 12.4 | 11.9 | 7.6 | 15.3 | 10.7 | 16.4 | 14.6 | 12.4 | 13.7 | 16.7 | 12.1 | 13.2 |
| 1 | | 3.6 | m | <u>ښ</u> | o. | ø, | ۰. | ۰ | 0 | ≠. | 'n. | 9 | 9. | o. | 9. | ۲. | m. | 'n | - | 0 | <u>_</u> | 9 | ż | ø. | œ | ŗ. | 12,2 |
| 1-1- | 0.9 | 1.8- 2.7 | 5.1 | 6.7 | 20.5 | 6.0 | 1.9 | | 9.1 | 9.0 | 6.8 | 7.3 | 10.7 | 11.2 | 11.9 | 13.6 | 11.3 | 10.2 | 10.8 | 13.0 | 1.9 | 2.9 | 9.6 | 6 | 6.9 | 5.7 | 10.0 |
| 1 | 0.4 | 0.0- | 2.3 | æ. 13.€ | <u>-</u> | .±. | Σ | ٠. | 9.4 | 5.7 | 9.6 | 0.6 | 6.2 | 3.0 | 6.2 | 0.4 | 5. | 4.5 | 4.5 | 5.0 | ر. ا | N. | 0. | ر. د | 9.4 | | 4.9 |
| 1 | 2.0 | 0.1- | 6.3 | 8 | 21 | 5.7 | ٠. د | 0.4 | O. ⊐† | 7 | 9.8 | 5.6 | 4.5 | 7 | 9 | & | 8.5 | œ. | 8. | 2.6 | ر. ا | | 9 | 9 | 2.7 | 8.0 | 6.2 |
| | CALM | CALM | 5.9 | ω, N | \. | 6 | ⇒ - ~ | # · · | 0. | 3.4 | 2.3 | 2.8 | 3.4 | <u>-</u> | <u>-</u> | | - ' | 9.0 | - | , 3 | - | - ' | 8 | 2.9 | N. | 1.7 | 2.3 |
| | | | | OJ F | η. | ⇒ † 1 | ν, | ۱۵ | _ | Φ. | 0 | 9 | = | 12 | ~ | † | 5 | 9 | 17 | 8 | 6 | 2 | 2 | 55 | 23 | 24 | ALL HOURS |
| | | | | | | | | | | | Ŧ | | 0 | : | > | | œ | | | | | | | | | | ALL ! |

Table IV - 145

ROSEBUD COUNTY - COLSTRIP BN Annual Wind Rose Distribution

01/01/75 - 08/22/79

| DIRECTION> | z | NN | N M | ENE | w | ESE | SE | SSE | တ | MSS | ΝS | MSM | 3 | MNX | ž | T MNN | TOTAL | <direction< th=""><th></th></direction<> | |
|--|--|---|---|--|---|--|----|-----|---|---|--|--|---|---|---|--|-------|--|---|
| SPEED (MPH) | | | | | | | | | | | | | | | | | S | SPEED (M/SEC) | _ |
| S 4.11.0 2.11.2.0 3.11.4.0 B 7.11.6.0 B 7.11.6.0 B 11.11.0 B 11.11.0 B 11.11.0 B 11.11.0 B 11.11.0 B 11.11.0 B 11.11.0 C 11.0 C 1 | 00000000000000000000000000000000000000 | 000000000000000000000000000000000000000 | 0.0000000000000000000000000000000000000 | 00000000000000000000000000000000000000 | | 00000000000000000000000000000000000000 | -0 | | | 00000000000000000000000 r-n 0-0000000000000000000000000000000000 | 00.00000000000000000000000000000000000 | 00000000000000000000000000000000000000 | | 114 120000000000000000000000000000000000 | | 00000000000000000000000000000000000000 | | 0.1- 1.0- | ⊗ ΦΨΨΩ ΣΠ⊢Π α⊗ ∕⊗ΨΟΟΣΩ () |
| | | . : | • | \ | | , | • | | | | | | | | | | | | |




Table IV - 146

Coefficients of Weibull Distribution

ROSEBUD COUNTY - COLSTRIP BN

01/01/75 - 08/22/79

| | SCALE | SHAPE |
|----------|-----------------------|------------|
| MONTH | FACTOR (C) (M/SEC) | FACTOR (K) |
| JANUARY | 8.1857 | 2.2640 |
| FEBRUARY | 8.7885 | 2.0113 |
| MARCH | 7.2949 | 1.8616 |
| APRIL | 7.8658 | 1.8903 |
| MAY | 5.9276 | 1.9930 |
| JUNE | 5.9357 | 1.8730 |
| JULY | 5.1494 | 2.2689 |
| AUGUST | 6.4472 | 1.6983 |
| ш | 5.4611 | 1.1807 |
| OCTOBER | 6.2151 | 2.0368 |
| NOVEMBER | 6.5962 | 2.5135 |
| DECEMBER | 6.8713 | 1.4632 |
| YEAR | 6.4642 | 1.8210 |

WESTERN ENERGY #12

ROSEBUD COUNTY

The Western Energy #12 air monitoring site was established by Western Energy Company to monitor particulate concentrations around their mine. The site is located approximately 1 mile south of Colstrip at 45 52 06 N and 106 38 27 W (Site No. 114 on Map II-1). Elevation at the site is 3,280 feet.

Wind data have been gathered at this site since January 1, 1981. Data through March 15, 1982, were available for analysis. The data set consists of hourly averages of wind speed and wind direction collected at an anemometer height of 10 meters above ground level. Data recovery was excellent, ranging from 77.6 percent in March to 98.6 percent in June and November. Overall data recovery was 91.5 percent.

Average annual wind speed was 7.3 miles per hour. Average monthly wind speeds varied from 5.9 miles per hour in November to 9.3 miles per hour in May. The windiest months were April through June.

Average monthly wind power ranged from 27.3 watts/m² in November to 79.1 watts/m² in May. Average annual wind power was 48.4 watts/m².




Table IV - 147

Monthly Wind Speed Distribution ROSEBUD COUNTY - WESTERN ENERGY #12

01/01/81 - 03/15/82

| CALM 0.1-1.0 | 3 00 | | MAR 0.5 | APR 0.0 | MAY 0.0 | | JUL 0.0 | | SEP 0.0 | 0.0 | 0.0 | DEC 0.0 | | 0. |
|---|-----------|----------|-------------------|------------------|----------------|------|----------------------|------|-------------------------|----------------|--------------|---------------------|--------------|-------|
| S 2.1-2.0 P 3.1-4.0 | . w & C | , r, o « | . ww.c | 0.70 | . 6. 6. 6. | くりけい | . 6.0.7 | | 0.00 0.00 | 4.0 | 12.4 | 11.7 | 14.5 2.00 | 0 |
| E 4.1-5.0 E 5.1-6.0 | <u>.</u> | | | 10. 10. | 88. | | 12.2 | | 13.55 13.20 13.20 | 12.9 1.1.2. | 12.6 | 9.6 | | 0 |
| V ~ 0 | α.υ.= | | ∞. o.–. | 9.0 | 7.0 | | 10.2 10.2 | | 0.8 2.7 | 80 K-1 | ٠٠٠. تنده | 8 0 c | | 2000 |
| , 6.5 | ± = 1 m | | 0 1 01 | , 60 to 10 | 4.7 | | 0 rv 3 . 0 o rv . | | 4 m m 6 Q W | 200 | 23.5 | .00. | | りすす |
| 12. | ~ ~ ~ | | 4 4 0 0 0 0 0 | 7.00 0.4.4 | 6.7.4 5.0.4 | | 25.0 9.0 9.0 | | | 0 ~ 6. | 32.7 | w 0, 0, 0, 0, 8, | | תיתית |
| H 14.1-15.0 0 15.1-16.0 U 16.1-17.0 | | | | 4.8.8. - 6.6. | 4 K K 5 4 8 | | 0.70 | | 0.60 | 7.1 | 40.0 | 8. 2. 5. | | 991 |
| 18. | -00 | | 7.00 | 96.4 | 290 | | 000 | | 7 | 0.8 | 7.00 | 000 | | ~ ∞ α |
| 20.1-25.0 | , v, o, c | | -00 | 6.00 | 900 | | 6.00 | | 000 | 000 | 000 | - 0 | | 96.5 |
| 35.1-40.0 35.1-40.0 >40.0 | 000 | | 000 | 000 | -00 | | 000 | | 000 | 000 | 000 | 000 | | īδ |
| AVERAGE SPEED (MPH) AVERAGE | 6.9 | 7.5 | 6.7 | 9.0 | 9.3 | 4.8 | 6.7 | 6.3 | 6.7 | 7.4 | 5.9 | 9.9 | 7.3 | |
| SPEED (M/SEC) AVERAGE WIND POWER | 3.1 | 3.4 | 3.0 | 4.0 | 4.1 | 3.8 | 3.0 | 2.8 | 3.0 | 3.3 | 2.7 | 3.0 | e. | |
| (WATTS/M*#2) PERCENT DATA | 54.1 | 56.9 | 34.7 | 76.2 | 79.1 | 65.4 | 31.2 | 29.5 | 30.8 | 46.8 | 27.3 | 48.8 | 48.4 | |
| RECOVERY | 93.0 | 88.1 | 77.6 | 97.5 | 92.2 | 98.6 | 93.3 | 86.3 | 96.1 | 97.9 | 98.6 | 87.2 | 91.5 | |
| TH GULLDWOMEN | 1717 | TUN OF | 100 | 33 66 | - | | | | | | | | | |

ANEMOMETER HEIGHT = 10 METERS = 33 FEET NUMBER OF OBSERVATIONS = 9638
PERCENTAGE DATA RECOVERY = 91.5

BUTTE FAA AIRPORT

SILVER BOW COUNTY

The Butte Airport is located approximately 4 miles south-southeast of Butte at 45 57 00 N and 112 30 00 W (Site No. 117 on Map II-1). Elevation at the airport is 5,540 feet. Meteorological data have been collected at this site for many years by the Federal Aviation Administration.

These data, primarily collected for aviation and weather forecasting uses, consist of short-term (5 minutes or less) averages of wind speed and wind direction, as well as other meteorological parameters. Data were gathered once per hour. The data have been analyzed by Battelle Pacific Northwest Laboratories.

The Battelle data set for Butte consists of summaries derived from hourly observations from January 1, 1948, through December 31, 1960. The anemometer was mounted on a rooftop at a height of 18.0 meters. Due to the area's complex terrain, the site is representative only of a limited area near the airport.

Average monthly wind speed at the site ranged from 6.7 miles per hour in December and January to 9.8 miles per hour in April. Average annual wind speed was 8.1 miles per hour.

Average monthly wind power ranged from 67.0 watts/m² in August to 136.0 watts/m² in April. Average annual wind power was 90.0 watts/m².




Table IV - 148

Monthly Wind Speed Distribution

SILVER BOW COUNTY - BUTTE FAA AIRPORT

01/01/48 - 12/31/60

(<0.5)

| | JAN | FEB | MAR | APR | MAY | NOC | JUL | AUG | SEP | OCT | NOV | DEC | YEAR | |
|-------------------------|----------------|------|--------------------|-------|--------------|------|-------------|-------------|-------------|-------|------|---------------------|------|--------------|
| CALM (<1.1) 1.1- 3.1 | 20.7 | 19.2 | 16.0 6.4 1.4 | 10.7 | 0.40 0.40 | 0.6 | 11.0 5.9 | 12.5 4.2 | 13.4 5.9 | 7.5.7 | 20.3 | 24.7 | 15.2 | CALM 0.5- |
| 7.6-7. | 13.1 8.0 | | 13.1 | | | 12.2 | | | 15.7 | | | . 6. 6. 7. 8. 4. | | |
| 10.1-12. | 7.6 | | 8.7 | | | | | | 10.1 | | | 6 6 | | |
| | 80 | | 3.9 | | | 5.5 | | | 3.8 | | | 3.3 | | |
| 21.3-23. | N | | | | | 2.5 | | | 7.7 | | | 9- | | |
| 23.5-25. | - - | | - L S R | | | 7.3 | | | 0.6 | | | . 6. | | |
| 28.0-30. 30.2-32. | 0.0 | | 0.0 | | | 9.0 | | | 0.3 | | | 7.0 | | |
| 32.4-34. 34.7-36. | 0.0 | | 0.5 | | | 0.0 | | | 0.0 | | | | | |
| 36.9-38. | 0.0 | | 0.0 | • | | 0.0 | | | 0.0 | | | 000 | | |
| 41.4-43. | 0.0 | | 0.0 | | | 0.0 | | | 0.0 | | | 0.00 | | |
| 9-56. | 00. | | 0.0 | | | 00 | | | 0.0 | | | 0.0 | | |
| 0-68. | 00 | | 0.0 | | | 0.0 | | | 0.0 | | | 00 | | |
| 4-90. | 0.0 | | 000 | | | 000 | | | 0.0 | | | 000 | | |
| AVERAGE SPEED (MPH) | 6.7 | 7.4 | 7.8 | 9.8 | 4.6 | 8.0 | 8.1 | 7.8 | 7.6 | 7.6 | 7.2 | 6.7 | 8.1 | |
| SPEED (M/SEC) | 3.0 | 3.3 | 3.5 | 4.4 | 4.2 | 4.0 | 3.6 | 3.5 | 3.4 | 3.4 | 3.2 | 3.0 | 3.6 | |
| WATTS/M**2) | 84.0 | 96.0 | 101.0 | 136.0 | 118.0 | 97.0 | 73.0 | 67.0 | 70.0 | 85.0 | 83.0 | 76.0 | 90.0 | |

ANEMOMETER HEIGHT = 59.0 FEET = 18.0 METERS

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

BUTTE HEBGEN PARK

SILVER BOW COUNTY

The Hebgen Park site is located in the southeastern corner of Hebgen Park in Butte at 46 00 13 N and 112 31 29 W (Site No. 118 on Map II-1). Elevation at the site is 5,520 feet. The site was established by the Montana Air Quality Bureau to measure concentrations of particulates, carbon monoxide, and nitrogen dioxide as part of the Montana Air Pollution Study.

Wind data from June 15, 1978, through December 10, 1980, were available for analysis. The data set contains hourly averages of wind speed and wind direction. The data were recorded by a data acquisition system, which scanned each measured parameter several times per minute. The wind recorder used was a Climatronics electronic anemometer and wind vane on a 10-meter tower.

Winds were monitored long enough to adequately represent the wind resource at this location. Since the site is in an urban area in complex terrain, the data are representative only of the immediate vicinity. Data recovery was fair, ranging from 35.5 percent in January to 98.7 percent in November. Overall data recovery was 75.2 percent.

Average annual wind speed at the site was 3.7 miles per hour. Average monthly wind speeds ranged from 2.8 miles per hour in November and February to 4.6 miles per hour in June. May through July were the windiest months.

Average annual wind power was 8.9 watts/m². Average monthly wind power values ranged from 2.7 watts/m² in February to 13.2 watts/m² in I.a.o.




Table IV - 149

Monthly Wind Speed Distribution

SILVER BOW COUNTY - BUTTE HEBGEN PARK

06/15/78 - 12/10/80

| | A-7-0-4-6-6-4-4-6-6-6-6-6-6-6-6-6-6-6-6-6-6 |
|------|---|
| YEAR | 22.2 27.5 27.5 27.5 20.0 |
| DEC | 41.800.800.41.800.0000000000000000000000 |
| NOV | 0.000000000000000000000000000000000000 |
| OCT | 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 |
| SEP | 0.000 |
| AUG | 0.00 |
| JUL | 0 - 2 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 |
| NUC | 23866 23866 2772 2772 2772 2772 2773 2773 2773 27 |
| ₩A∀ | 2022 1027 1027 1027 1032 |
| APR | 2.832 1.832 1.00 |
| MAR | 2 8 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 |
| FEB | 33.50 1.00 |
| NAC | 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 |
| | CALM CALM CALM 1.1-2.0 8 2.1-3.0 P 3.1-4.0 M 6.1-5.0 C 1.1-1.0 C 1.1- |
| | |

DNOCHS/SRETEN

ANEMOMETER HEIGHT = 10 METERS = 33 FEET NUMBER OF OBSERVATIONS = 16435
PERCENTAGE DATA RECOVERY = 75.2

CHOTEAU TETON COUNTY

The Choteau site is located about 12 miles southwest of Choteau at 47 44 36 N and 112 26 05 W (Site No. 125 Map II-1). Elevation at the site is 4,320 feet. This site was established by the Bureau of Reclamation as part of its Northern Great Plains Wind Energy Study. The Department of Natural Resources and Conservation assumed responsibility for monitoring winds at the site in October 1982.

Collection of wind data began on June 4, 1981 and continued until August 16, 1983. Data from the wind sensors were continuously recorded on cassette tape. These tapes were further processed by computer to yield hourly averages of wind speed, wind direction, the average cube of the hourly speed, and standard deviation of the hourly speed. In addition, the maximum and minimum instantaneous values of wind speed during each hour were recorded. Anemometer height was 10 meters.

Data recovery was good to excellent during most months; it ranged from 30.4 percent in January to 100.0 percent in May. Overall data recovery was 84.5 percent. When the site was decommissioned, the crossarm was found to be loose and probably wobbled ten to twenty degrees. This would have affected the data somewhat, particularly the data on wind direction.

Winds were monitored long enough to adequately represent the wind resource in this area during most parts of the year. The site was located towards the bottom of the Deep Creek drainage and so was somewhat protected from

the winds. The speeds recorded probably are lower than what would be found on the ridges to the north and south.

Average monthly wind speeds ranged from 7.3 miles per hour in January (probably not a representative value because of the low rate of data recovery for that month) to 12.2 miles per hour in December. Average annual wind speed was 10.1 miles per hour.

Average monthly wind power varied from 48.6 watts/m² in August to 237.7 watts/m² in December. Average annual wind power was 116.0 watts/m².




Table IV - 150

Monthly Wind Speed Distribution TETON COUNTY - CHOTEAU

06/04/81 - 08/16/83

| | | | | | | Ì | /ON TO | | | | | | | | |
|-----------------|---------|--|-------------------|-------|-------|------------|---------|--------------|----------|----------|---------|---------|-------------|-----------|---|
| | AN | FEB | Æ | APR | MAY | Ŋ | al T | AUG | 딿 | 9CT | λQN | 983 | YEAR | | |
| CALM | 0.2 | 0.1 | 0.1 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.5 | 0.2 | 1.9 | 0.3 | 0.3 | SE | |
| 0.1-1.0 | 2.0 | 1,3 | ဇ | 0.2 | 0.1 | 4.0 | 0.1 | 0.1 | 0.2 | 0.6 | 1.8 | 0.8 | 9.0 | 0.1 - 0.4 | |
| | 10.6 | 4.9 | 3.0 | 1.5 | 1.7 | 5.4 | 1.6 | 1.6 | 1.6 | 1:1 | 2.4 | 3,3 | 2.4 | 0.5-0.9 | |
| 2.1 | 10.2 | 5.1 | 5,3 | 3.2 | 2.2 | 2.7 | 3.0 | 4.0 | 2.6 | 2.0 | 3.1 | 4.7 | 3.6 | 1.0-1.3 | |
| P 3.1-4.0 | 10.2 | 6.5 | 8.0 | 7.1 | 4.5 | 8.0 | 7.2 | 9.9 | 6.4 | 6.0 | 4.7 | 7.6 | 6.7 | 1.4- 1.8 | |
| | 7.1 | 4.7 | 6.7 | 7.7 | 5.1 | 7.2 | 7.4 | 8°.9 | 7.4 | 5.2 | 5.4 | 5.0 | 6.7 | 1.9- 2.2 | |
| | 6 | 6.8 | တ | 10.1 | 9.6 | 11.0 | 12.8 | 13.2 | 10.5 | 7.4 | 7.7 | 5,7 | ۍ 8 | 2.3- 2.7 | |
| | 7.3 | 5.3 | 7.1 | | 7.9 | 0.6 | 10.5 | 10.4 | 8 | 8 | 3.8 | ω | 7.7 | 2.8-3.1 | |
| | 7.5 | 5.6 | 7.3 | 9.6 | 7.6 | 6.6 | 11.1 | 12.8 | 9.4 | 7.4 | 7.3 | ີ້ຕ | 8 | 3.2-3.6 | |
| | 9.9 | 5.6 | 4.9 | 7.2 | 6.4 | 7.6 | 7.5 | 8.8 | 7.5 | 7.4 | 6.3 | 6.0 | 8.9 | 3.7- 4.0 | |
| 9.1 | 4.4 | 4.9 | 6.9 | 7.4 | 7.1 | 6.9 | 8.5 | 9.6 | 8.1 | 6.9 | 6.7 | 5.0 | 7.2 | 4.1- 4.5 | - |
| L 10.1-11.0 | 4.4 | 4.9 | 3,8 | 4.5 | 4.8 | 4.2 | 4.4 | 5,3 | 5.6 | 5.2 | 0.9 | 4.1 | 4 | 4.6- 4.9 | |
| | у. Э | 5,9 | 5.0 | 4.2 | 2.6 | 5.8 | 5.2 | 4.6 | 6.5 | 9.9 | 6.4 | 5.2 | 5.5 | 5.0- 5.4 | |
| | 2.2 | 2.9 | 2.9 | 3.0 | 4.9 | 4.3 | 3,3 | 2.9 | 3.7 | 5.0 | 4.9 | 4.0 | 3.8 | 5.5- 5.8 | |
| | 2.2 | 4.5 | 3.1 | 3.6 | 5.1 | 3.6 | 3,4 | 2.3 | 4.1 | 4.7 | 5.7 | 4.5 | 3.9 | 5.9-6.3 | |
| | 2.0 | 3.0 | 3.4 | 2.7 | 2.6 | 2,3 | 2.2 | 1.8 | 2.4 | 4.3 | 3.1 | 3.5 | 2.7 | 6.4- 6.7 | |
| | 2.0 | 2.6 | 3.4 | 3.2 | 2,3 | 1.9 | 1.7 | 1.3 | 2.8 | 4.4 | 3.2 | 3.9 | 2.6 | 6.8- 7.2 | |
| U 16.1-17.0 | 1:1 | 3.6 | 3.2 | 2.9 | 2.6 | 3.1 | 2.4 | 1.2 | 2.4 | 2.9 | 3.9 | 4.5 | 2.8 | 7.3- 7.6 | |
| | 0.4 | 2.9 | 2.0 | 2.1 | 2.2 | 1.6 | 1.3 | 0.9 | .5 | 3.1 | 2.7 | 2.9 | 2.0 | 7.7- 8.0 | _ |
| 18.1-19.0 | 0.2 | 2.9 | 1.8 | 1.7 | 2.7 | 1:0 | 1.6 | 1.0 | 1.9 | 2,3 | 2.8 | 2.2 | 1.9 | 8.1-8.5 | _ |
| 19.1-20.0 | 0.0 | 1.6 | 1.8 | 1.2 | 2.0 | 1.0 | 1.0 | 0.5 | 1.3 | 1.2 | 2:4 | 2.0 | 1.4 | 8.6-8.9 | _ |
| 20.1-25.0 | 1:1 | 8.4 | 6.0 | 6.3 | 9.9 | 4.0 | 3.1 | 1.9 | 3.6 | 5.7 | 5.7 | 7.8 | 5.0 | 9.0-11.2 | |
| 25.1-30.0 | 1.3 | 3,3 | 2.9 | 1.3 | 2.8 | 1.8 | 0.0 | 0.3 | 1.2 | 1:1 | 1.5 | 3.6 | 1.8 | 11.3-13.4 | |
| ∹ | 0.5 | 1.3 | 0.7 | 0.3 | 1.2 | 0,3 | 0.1 | 0.1 | 0.5 | 8.0 | 0.4 | 2.1 | 0.7 | 13.5-15.6 | |
| 35.1-40.0 | 0.2 | 0.8 | 0.0 | 0.2 | 0.2 | 0.1 | 0.1 | 0.1 | 0.1 | 0.2 | 0.2 | 6.0 | 0.2 | 15.7-17.9 | |
| >40.0 | 0.2 | 8.0 | 0.0 | 0,3 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.3 | 0.0 | 1.2 | 0.2 | >17.9 | |
| AVERAGE | | | | | | | | ı | • | | } | | } | : | |
| SPEED (MPH) | 7.3 | 11.6 | 10.2 | 10.1 | 11.1 | 9,5 | 9.0 | 8,3 | 9.7 | 11.0 | 10.7 | 12.2 | 10.1 | | |
| CDCED (M/CDC) | د د | r. | 9 7 | ¥ | u | 6 | 5 | , | | • | • | L | | | |
| AVERAGE | • | 3.0 | , | | 0.0 | 4.6 | | ۲ ، ۲ | 4 | . | at X | o. O | φ. Ω | | |
| WIND POWER | | | | | | | | | | | | | | | |
| (WATTS/M**2) | 9.99 | 206.5 | 124.3 | 114.6 | 135.1 | 85.8 | 65.0 | 48.6 | 88.5 | 129.5 | 119.6 | 237.7 | 116.0 | | |
| PERCENT DATA | | | | | | | | | | | | | | | |
| RECOVERY | 8.4 | 85.7 | 71.0 | 8 | 100.0 | 87.3 | 83.2 | 99.5 | 4.6 | 77.2 | 97.1 | 9.6 | 8 .5 | | |
| HEI OBSE | HT = 10 | GHT = 10 METERS = 33 RVATIONS = 16303 | 5 = 33 F 16303 | FEET | | | | | | | | | | | |
| PERCENTAGE DATA | RECOVE | # }} | 84.5 | | | | | | | | | | | | |

Nemmo Emtess/Second

FORT PECK VALLEY COUNTY


The Fort Peck site was located in Valley County approximately 3 miles west of Fort Peck at 47 59 48 N and 106 29 59 W (Site No. 129 on Map II-1). Elevation at the site was 2,329 feet. The site was established by the Montana Air Quality Bureau to measure background levels of particulates in the

Wind data were collected at the site from May 7, 1977, through July 19, 1979. The data set consists of hourly averages of wind speed and wind direction manually reduced from stripchart records. Wind monitoring equipment included a Meteorology Research, Inc., mechanical recording anemometer and wind vane. Anemometer height was 4 meters.

Winds were monitored long enough to give an indication of the wind resource at this location. Data recovery, however, was poor during all months, ranging from 10.1 percent in April to 37.0 percent in June. Overall data recovery was 25.9 percent.

Average monthly wind speeds ranged from 8.4 miles per hour in July to 14.6 miles per hour in February. Average annual wind speed was 10.6 miles per hour

Monthly averages of wind power ranged from 105.3 watts/m² in July to 449.2 watts/m² in February. Average annual wind power was 219.9 watts/m².



ONOCHS/SHHIM

Table IV - 151 Monthly Wind Speed Distribution

05/07/77 - 07/19/79

VALLEY COUNTY - FORT PECK

| | | | | | | | | | _ | | | | | | |
|------|----------------|-------|-------|-------|------------------|---------|---------|--------------------|------------------|--------|----------|-----------------------------------|--------------------------|-------|----------|
| | 00 | ~ | 0 00 | | 4.0,1 | 000 | ~ ~ | ∞ ∞ | æ <u>-</u> | | ÿ. E. | | | | |
| | CALL 0 | 040 | က္ကေ | バレー | ώöπ | | ထက | ~ ← | 90 | آ س ۳ | | | | | |
| YEAR | 0.00 | | | | | | | | | | | 10.6 | 4.7 | 219.9 | 25.9 |
| DEC | 0.00 | | | | | | | | | | | 14.4 | 4.9 | 397.4 | 19.1 |
| NOV | 0.00 | • • • | | | | | | | | | | 12.9 | 5.8 | 381.8 | 30.2 |
| OCT | 0.00 | | 44. | | | | | | | | | 10.9 | 4.9 | 206.3 | 16.1 |
| SEP | 0.00 | | | | | | | | | | | 9.6 | 4.3 | 179.8 | 29.8 |
| AUG | 0000 | | | | | | | | | | | 4.6 | 4.2 | 140.2 | 25.5 |
| JUL | 0.00 | | | - 100 | | | | | | | | 4.8 | 3.7 | 105.3 | 12.9 |
| NUC | 0.00 | | | | | | | | | | | 9.5 | 4.2 | 141.8 | 37.0 |
| MAY | 0000 | | | | | | | | | | | 9.3 | 4.2 | 145.3 | 34.6 |
| APR | 0000 | | | | | | | | | | | 11.6 | 5.2 | 385.1 | 10.1 |
| MAR | 0.00 | | | | | | | | | | | 9.5 | 4.1 | 134.0 | 32.2 |
| FEB | 0.00 | | | | | | | | | | | 14.6 | 6.5 | 449.2 | 30.1 |
| JAN | 0.000 | | | | | | | | | | | 10.7 | 4.8 | 217.5 | 28.4 |
| | 0.1-1 1.1-2 | | 6.1-6 | 86 | 1.1-12 2.1-13 | 13.1-14 | 15.1-16 | 17.1-18 18.1-19 | 9.1-20 0.1-25 | 5.1-30 | 3.1.5 | AVERAGE SPEED (MPH) AVERAGE | SPEED (M/SEC) AVERAGE | | RECOVERY |
| | | | | | | | | | | | | | | | |

ANEMOMETER HEIGHT = 4 METERS = 13 FEET NUMBER OF OBSERVATIONS = 4988 PERCENTAGE DATA RECOVERY = 25.9

GLASGOW AIR FORCE BASE

VALLEY COUNTY

The Glasgow Air Force Base is located approximately 20 miles north-northeast of Glasgow at 48 24 00 N and 106 31 20 W (Site No. 130 on Map II-1). Elevation at the base is 2,758 feet. Meteorological data were collected at this site for many years by the United States Air Force.

These data, collected primarily for aviation and weather forecasting uses, consist of short-term (5 minutes or less) averages of wind speed and wind direction, as well as other meteorological parameters. Data were gathered once per hour. The available data have been analyzed by Battelle Pacific Northwest Laboratories. Because of a change in anemometer height, the data set was split into two parts for analysis: October 1, 1958, through June 7, 1961; and June 8, 1961, through June 30, 1968. Data from the latter period only were selected for inclusion in the Montana Wind Energy Atlas. The anemometer was mounted on a ground mast at a height of 4.0 meters. The site is representative of the northeastern corner of Montana.

Average annual wind speed at the base was 9.6 miles per hour. Average monthly wind speeds varied from 8.7 miles per hour in August and November to 11.9 miles per hour in May.

Average annual wind power was 109.0 watts/m². Average monthly wind power varied from 77.0 watts/m² in July to 172.0 watts/m² in May.




Table IV - 152

Monthly Wind Speed Distribution

VALLEY COUNTY - GLASGOW AIR FORCE BASE

06/08/61 - 06/30/68

| | _ | v | , <u>a</u> | ш | LII I | ۵ | | ¥ | ш | _ | u | <u>~</u> | S | _ | S | ш | ပ | 0 | z | ۵ | | | | | | | | | | |
|------------------|----------------|------|------------|----------|-------|----------|--------------|----------|---------------|---------|------------|----------|----------|--------|----|------|-----|--------------|------------|----------|-----|-----|--------|----------|----------|------|----------|-------------|--------------|-------------------|
| | 60.5 | t = | t == | <u> </u> | - → | → | | | | | | | | | | | | | | | | -⇒ | = | = | 4 | | | | | |
| | | - د | 1 ~ | 4 | J. | Ø | ~ | ထ | 0 | 9 | Ξ | 2 | 3 | ≢ | 5 | 9 | 17 | 8 | 5 | 2 | 3 | 2 | 5 | 9 | 9 | | | | | |
| | ALM P. | jπ | , 10 | ū | Š | 'n | 'n | Ū | 'n | 'n | Ÿ | 7 | 7 | 4 | Ÿ | 4 | 4 | 4 | 7 | 7 | 7 | 7 | 7 | Ŋ | ^ | | | | | |
| | ેં | 7 | - (\) | m | ⅎ | Z | 9 | _ | œ | 0 | 9 | Ë | 7 | -3 | 7 | 15 | 16 | 17 | 18 | 19 | 20 | 25 | 30 | 35 | | | | | | |
| YEAR | ٥,٢ | • | | • | • | • | • | • | | | • | • | | | | | | | | | | | | | | | 9. | (| ~ | 0. |
| > | & ~ | 7 2 | 16 | 15 | = | 0 | φ | Š | N | N. | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 0 | - | 寸 | 109 |
| DEC | τ, α | | | | | | | | • | | | | | | | | | | | | - | | | | | | ٥ | , | - | 0 |
| ۵ | 10 | ٦ ٢ | 16 | 5 | 7 | Q | 9 | ≠ | N | _ | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 6 | 4 | J | 110.0 |
| N _O V | 9. | - 0 | , ~ | 'n | " | ď | 9 | œ | ď | ۲. | 9 | ۳. | 'n | ď | 0 | 0 | 0 | ۲. | 0 | 0. | 0 | 0. | 0. | 0 | 0. | | 7. | (| | 0 |
| Z | ∞ .= | 7 7 | 6 | 9 | 7 | ∞ | → | m | N | _ | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 80 | • | ν) | 16 |
| DCT | 0. | • | | | • | • | | • | • | • | | • | | | | | • | | • | | | | | | | | ≠ | | N | 0. |
| 0 | ~ ۵ | 7 ~ | 12 | 16 | 15 | 0 | 9 | m | N | _ | _ | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 9. | - | # | 66 |
| SEP | | | ,0 | ۲. | ٥. | ٦. | o. | 'n | ۳, | φ, | 0 | ٠. | ij | - | ٦. | ٥. | 0. | 0 | 0. | ٥. | 0. | 0 | 0. | 0 | 0 | | Ŋ | • | - | 0. |
| S | 0/= | ٠, | <u></u> | v | S | ∞ | r | S | ~ | _ | _ | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 6 | - | . | 100.0 |
| AUG | œ. د | • | | • | • | • | • | • | • | | | • | • | • | • | | • | | | | | | | | | | ۲. | c | , | 0 |
| ⋖ | * | . 17 | 17 | 15 | 7 | 0 | 9 | # | | , | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 80 | r | 3 | 8 |
| JUL | વ . | • | | | • | • | | • | | • | | • | | | | | • | | | | | | | | | | 6. | c | ٠, | 0. |
| 7 | 7 | 2 | 10 | 9 | 16 | œ | S. | # | N | _ | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | œ | - | , | 77. |
| N N | ல் ஈ | `- | . ⇒ | o. | 6. | ۰ | # ! | ۲. | 'n. | 0, | œ. | ۲. | ⇒ | - | 0 | 0 | 0 | 0 | ۰. | 0. | 0. | 0 | 0. | 0 | 0 | | ω | | . | 0. |
| 7 | ~ " | | 16 | 13 | 15 | 10 | | 'n | N | N (| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 6 | - | 3 | 105 |
| ¥¥ | o, « | • | | • | | • | • | | | | | | | | | | | | | | | - | | | | | 6 | r | ? | 0. |
| Σ | 40 | 1 ∝ | 12 | 12 | 73 | 2 | 0 | ο. | 寸 | ، ڊي | _ | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | Ξ | Ц | 0 | 172 |
| 품 | ல் ர | • | | • | • | • | • | | ٠ | • | • | | | | • | | | • | • | | | | | | | | 0. | c | ` | 0 |
| < | 40 | 7 = | . 7 | 5 | | 2 | & | | (C) | m ı | _ | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | Ξ. | - | † | 138. |
| MAR | ٥- ا | • • | | - | • | • | | • | • | • | ٠ | ٠ | | | • | • | • | | • | | | • | | | • | | ₹. | ¢ | v | 0 |
| Σ | ∞⊲ | 17 | 17 | 7 | 13 | 0 | 1 | Ω. | m. | _ , | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 0 | - | † | 104 |
| E8 | 0.0 | 0 | ٠ | 9 | 0 | | ď. | oʻ. | ۲. | 4. | . د | ဆ | ۲. | ٩ | - | - | 0 | 0. | - | 0 | 0 | Ö | 0. | 0 | • | | 9 | c | ? | 0 |
| i. | 9.4 | 1 | 9 | 2 | 3 | | 9. | | | | | | | | | | | | | 0 | 0 | 0 | 0 | 0 | 0 | | 0 | - | 7 | 117 |
| JAN | = C | • | | • | • | • | ٠ | • | • | | • | ٠ | ٠ | ٠ | | • | • | | • | • | ٠ | | • | | | | 80 | 4 | ţ | |
| ب | ∞⊐ | 7 | 15 | * | 15 | 10 | 91 | S) | ו ניי | N C | O (| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 9. | ā | t | 118.0 |
| | _ | | φ | | | | | • | | | | | | | | | | | | - | - | - | - | _ | _ | | | 5 | , | |
| | | | | | | | 91- | | | | | | | | | ന | m, | - ∓ . | - 3 | ᢋ | ĽΩ' | v | -79 | σ. | σ. | E. | H H | 3E /o.g. | 빞 | ## # # # |
| | | . = | 5 | ₽. | ٥. | د. | ٦, ري | 9 | O, | ۰. س | יי ני | , · | 8 0 | 0 0 | 7. | ۲. ۲ | 9 | <u>_</u> | 4. | 0 | 9 | 7.0 | ر 0 | ₹ 6 | | FRAC | = | Ž. | ER. | ND POWER |
| | CALM | | | | _ | _ | _ ' | | (| N C | N (| N | N | m · | m | m | m · | m. | | ⇒ | ₹ | Ų, | ত | ~ | | ¥ | PEEI | ۾ ڏاڄ | Ş.Ş. | N I |
| | | | S | ۵. | نيا | w | _ | ; | Σ | | ا بـ |) لد | SO. | ` | I | 0 | > | ~ | | | | | | | | | S | ū | מין | ₹₹ |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

ANEMOMETER HEIGHT = 13.0 FEET = 4.0 METERS

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

GLASGOW NWS AIRPORT

VALLEY COUNTY

The Glasgow airport is located approximately 1 mile north of Glasgow at 48 13 12 N and 106 37 12 W (Site No. 131 on Map II-1). Elevation at the airport is 2,280 feet.

The Glasgow area is open plains country cut by the Milk River Valley and many tributary valleys. Land in the area is used primarily for agriculture. Much of the land is privately owned; however, a substantial amount of land is owned by the state and the federal government. The Fort Peck Indian Reservation lies about 10 miles to the east. Several state and federal highways run through the area.

Electrical power is supplied by the Montana Power Company and the Valley and Northern electric cooperatives. Many power transmission lines

The nearest other commercial airport is located at Wolf Point. The Williston Military Operations Area (MOA) is located to the northeast. The Hays and Loring MOAs are located to the southwest and northwest. These areas are subject to occasional military aviation use.

Meteorological data have been collected at this site for many years by the National Weather Service. These data, collected primarily for aviation and weather forecasting uses, consist of short-term (5 minutes or less) averages of wind speed and direction, as well as other meteorological parameters. Data were gathered once per hour. The data have been analyzed by Battelle Pacific Northwest Laboratories. Because of changes in anemometer height, the data set has been broken into three periods for analysis: October 1, 1955, through August 5, 1962; August 6, 1962, through May 31, 1968; and June 1, 1968, through December 31, 1978. Data from the most recent period only were selected for inclusion in the Montana Wind Energy Atlas.

The data set for Glasgow consists of summaries of observations made every third hour. The anemometer was mounted on a ground mast at a height of 6.1 meters. The site is representative of the northeastern corner of

Average monthly wind speeds ranged from 9.8 miles per hour in November to 13.0 miles per hour in April. Average annual wind speed was 11.0 miles per hour.

Average monthly wind power ranged from 109.0 watts/m² in July to 211.0 watts/m² in April. Average annual wind power was 139.0 watts/m².

Average seasonal wind speeds were 10.4 miles per hour in autumn and winter, 10.9 miles per hour in summer, and 12.1 miles per hour in spring. The highest average wind speeds occurred in mid-afternoon during all seasons. The lowest average wind speeds occurred in early morning, except during the winter, when they occurred in mid-morning. The diurnal range of average wind speeds was greatest in summer and least in winter.

The most common wind directions were east-southeast and northwest. Winds from the south-southwest through southwest were least common. By direction, average wind speeds ranged from 7.6 miles per hour for winds from the south-southwest and southwest to 13.0 miles per hour for northwesterly winds.




Table IV - 153

Monthly Wind Speed Distribution

VALLEY COUNTY - GLASGOW NWS AIRPORT

06/01/68 - 12/31/78

| | 5) | 0 a | ш | ш | 0 | | Σ | ш | _ | ليا | œ | s | \ | | ш | ပ | 0 | z | ۵ | | | | | | | | | |
|------|------------------------|---------|---------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|------|-----|------|-----|-----|-----|-----|---------|-------------|---------------|---------------------------------------|
| | 0,4.5 | 3.4 | η· η | ر 1 | 4.9 | 7.4 | ₩ | 9.4 | ⊅.0 | ₽. | 7.2 | 3.4 | †. † | 5.4 | 1.9 | 7.4 | 7.8 | 7.6 | 7.0 | 5.4 | .0 | 5.4 | 7.0 | 4.0 | | | | |
| | CALM (* | 747 | ω, | <u> </u> | u i | u 7 | , | G. | щJ | T, | ĽΣ | 43 | มา | L. | E. | Ω. | 'n | 'n | r. | 'n | 'n | S | r) | | | | | |
| A. | 901 | | | | | | | | | | | | | | | | | | | | | | | | | _ | _ | _ |
| YEAR | m 0 5 | | | | • | • | | • | • | | | | | | | | | | | | | | | | | 11.0 | 4.9 | 139.0 |
| DEC | 0.0 0.4. | | • | • | • | • | • | • | | • | | • | | | | • | | | | | • | | | | | 10.3 | 4.6 | . 0.921 |
| NOV | ₹.0.± | | • | ٠ | • | • | • | • | | • | | | | | | | | | | | | | | | | 9.8 | 4.4 | 114.0 |
| OCT | 3.3 | | • | • | ٠ | • | ٠ | | • | • | | • | | | | | | | • | • | | | | | | 10.5 | 4.7 | 126.0 |
| SEP | | | • | • | • | • | ٠ | | • | • | | | • | • | | | | • | • | • | ٠ | | | | | 11.0 | 4.9 | 129.0 |
| AUG | 0 - 0 | ٠. | | ġ. | <u>.</u> | | • | • | • | • | | | | | | • | | | | | | | | - | | 11.0 | 4.9 | 116.0 |
| JUL | 8.00 | | • | • | | | • | • | • | | • | | • | | | • | • | | | | | | | | | 10.5 | 4.7 | 109.0 |
| S UN | 0.20 | | | • | ٠ | • | | | • | • | | | | | | | | | | | | • | | | | 11.2 | 5.0 | 131.0 |
| MAY | 0.0 | | | | | | | | | | | | | | | | | | | | | | | | | 11.9 | 5.3 | 164.0 |
| APR | 20.5 | | • | • | ٠ | • | ٠ | • | • | • | • | • | • | • | ٠ | • | • | • | • | • | • | • | • | | | 13.0 | 5.8 | 211.0 |
| MAR | 4.00 | | • | + | | | • | • | | | • | | | | • | | | • | • | | | • | | | | 11.4 | 5.1 | 161.0 |
| FE8 | 5.0 0.3 | | • | • | • | • | • | 3.5 | • | ٠ | • | • | • | • | • | ٠ | • | • | • | ٠ | ٠ | ٠ | ٠ | • | | 10.5 | 4.7 | 152.0 |
| JAN | 6.2 | , I | 16.3 | 3 | 9 | 5.7 | 7. | 4.2 | 2.4 | 6. | 0. | 7.0 | 0.2 | 0.0 | 0.0 | 0.1 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 10.3 | 4.6 | 139.0 |
| | CALM (<1.1) 1.1-3.1 | 5.6- 7. | 6 | 10.1-12. | 12.3-14. | 14.5-16. | 10.8-18. | 19.0-21. | 21.3-23. | 23.5-25. | 25.7-27. | 28.0-30. | 30.2-32. | 32.4-34. | 34.7-36. | 36.9-38. | 39.1-41. | -43. | ₹. | .56. | .68 | .79 | 90. | | AVERAGE | SPEED (MPH) | SPEED (M/SEC) | AVERAGE WIND POWER (WATTS/M**2) |

ANEMOMETER HEIGHT = 20.0 FEET = 6.1 METERS

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

Table IV - 154

Percentage Frequency Summary for Wind Speed VALLEY COUNTY - GLASGOW NWS AIRPORT (WINTER)

| | | | | _ | | | | | | | | | |
|--------|-----------------------|----------|-------|----------------|------|------|------|------|------|------|------|------|-------|
| | | | SPEED | M/SEC | 4.5 | | | | | | | | 9.4 |
| | | A | SPEED | (MPH) | 10.0 | 6.6 | 9.8 | 10.8 | 1.3 | 10.5 | 10.3 | 10.2 | 10.4 |
| | £ 7. | r | | >32.2 | 0.1 | 0.5 | 0.3 | †։0 | 0.0 | ħ.0 | 0.2 | 0.5 | 0.2 |
| | 13.5- | | | | 9.0 | | | | | | | | 0.3 |
| | 12.5- | | | | 0.0 | | | | | | | | 0.4 |
| | 11.5- | 1.7 | 25.7- | 27.7 | 1.0 | | | | | | | | 1.2 |
| | 10.5- | | | | 1.4 | | | | | | | | 1.6 |
| | 9.5- | † 2 | 21.3- | 23.3 | 5.6 | | | | | | | | 2.6 |
| Ξ | 8.5- | EC). | 19.0- | 21.0 | 2,4 | | | | | | | | 3.8 |
| ED (MP | 7.5- | S/W) 0: | 16.8- | 8.8 | 4.5 | | | | | | | | 5.3 |
| ND SPE | 6.5- | D SPEE | 14.5- | 16.6 | 7.8 | | | | | | | | 7.7 |
| 3 | - 5.5- 6.5- 7.5- 8.5- | X X | 12.3- | 14.3 | 10.2 | | | | | | | | 9.5 |
| | 4. 7. | | | 15. | 12,7 | 15.3 | 12,4 | 12.5 | 11.6 | 15.1 | 12.2 | 12.7 | 13.0 |
| | 3.5- | † † | 7.8- | 8. | 18.1 | 18.9 | 14.9 | 13.3 | 15.3 | 14.6 | 16.2 | 18.7 | 16.2 |
| | 2.5- | • | 5.6- | 7.6 | 19.2 | 20.0 | 19.1 | 17.8 | 15.0 | 19.6 | 19.8 | 18.5 | 18.6 |
| | 1.5- -2- | 7 | 3.4- | 5.4 | 12.9 | 13.6 | 17.3 | 13.8 | 13.0 | 12.9 | 12.6 | 12.4 | 13.6 |
| | 0.5- | <u>+</u> | | 3.1 | 0.5 | 0.7 | ٥. | 0.3 | 0.1 | 0.0 | 0.5 | 0.3 | 0.2 |
| | , , | ? | | - . | 6.2 | 5.5 | 4.9 | 5.1 | æ. | 5.5 | 7 9 | 5.5 | 5.6 |
| | | | | | m | 9 | 6 | 15 | 15 | 18 | 2 | 54 | HOURS |
| | | | | | I | | 0 | | > | | œ | | ALL |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

Table IV - 155

Percentage Frequency Summary for Wind Speed VALLEY COUNTY - GLASGOW NWS AIRPORT (SPRING)

| | | | 8 | SPEED | M/SEC) | 8.4 | 4.7 | 5.4 | 6.1 | 4.9 | 6.1 | 6.4 | 4.9 | 5.4 | |
|--------|-------|-------------------|---------|-------|----------------|------|------|------|----------|-----------------|------|------|------------|-------|--|
| | | | | | (MPH) | | | | | | | | 11.0 | 12.1 | |
| | | >14.4 | | | >32.2 | | | | | | | | 1 0 | 0.5 | |
| | 13.5- | 14.4 | | 30.2- | 32.2 | 0.0 | 0.2 | 7.0 | 9.0 | 0.5 | 0.5 | 0.2 | 0.2 | 0.3 | |
| | 12.5- | 13.4 | | 28.0- | 30.0 | | | | | 1.0 | | | | 0.9 | |
| | 11.5- | 12.4 | | 25.7- | 27.7 | | | | | | | | 9.0 | 1.4 | |
| | 10.5- | 11.4 | | 23.5- | 25.5 | | | | | 3.1 | | | | 2.1 | |
| | 9.5- | 10.4 | | 7.3- | 23.3 | | | | | 5.3 | | | | 3.5 | |
| Œ | 8.5- | 4 6.4 7.4 8.4 9.4 | EC) | 19.0- | 21.0 | | | | | | | | 3.7 | 5.9 | |
| ED (MP | 7.5- | ÷. | S/W) C | 16.8- | 18.8 | | | | | | | | 5.7 | 7.6 | |
| ND SPE | 6.5- | 7.4 | ID SPEE | 14.5- | 16.6 | | | | | | | | 7.8 | 9.1 | |
| 3 | 5.5- | 4.9 | Z 3 | 12.3- | 14.3 | | | | | | | | 10.8 | 11.6 | |
| | 4.5- | 4.4 5.4 | | 10.1- | 12.1 | | | | | | | | 19.8 | 15.9 | |
| | 3.5- | 4.4 | | 7.8- | 9.8 | 18.2 | 15.8 | 14.3 | 12.5 | 12.9 | 13.8 | 23.4 | 18.8 | 16.2 | |
| | 2.5- | 3.4 | | 5.6- | 7.6 | 17.5 | 19.5 | 13.3 | 11.3 | 10.6 | 10.8 | 17.4 | 16.4 | 14.6 | |
| | 1.5- | 2.4 | | 3.4- | 5.4 | 10.7 | 10.8 | 8.7 | 6.3 | 4.9 | 5.5 | 6.8 | 3. | 7.7 | |
| | 0.5- | ≠ . | | 1.1- | ۳. د | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0. | 0.1 | 0.0 | |
| | | 60. 5 | | | . . | 2.8 | 7.0 | 3.6 | → | 1.4 | -: | 3.5 | 2.9 | 2.5 | |
| | | | | | | က | 9 | 6 | 12 | ار ة | 38 | 21 | 24 | HOURS | |
| | | | | | | I | | 0 | | > | | œ | | ALL | |

Table IV - 156

Percentage Frequency Summary for Wind Speed

VALLEY COUNTY - GLASGOW NWS AIRPORT (SUMMER)

| | | | 1 | 1 5 | с д | 2 F. | 7. 1. | יי צי נו זב | NO SPE | ED (MP | Ξ • | 0 | | 11 5. | 12 5. | 12 5- | | | |
|--------|-------|---------|------|------|--------|------------|----------|-------------------|-------------|--------|-------------|-------|------|-------|-------|--------------|-------|-------|--------------|
| | | <0.5 | 1.4 | 2.4 | 3.4 | 0.5 4.4 | 5.4 | 6.4 6.4 | 4.8 4.7 4.9 | 4.8 | #C.0 9.4 | 10.4 | 11.4 | 12.4 | 13.4 | 13.2 14.4 | >14.4 | | |
| | | | | | | | | 3 | D SPEE | 0 (M/S | (C) | | | | | | | ۸۸ | ۸ |
| | | | 1.1- | 3.4- | 5.6- | 7.8- | 10.1- | 12.3- | 14.5- | 16.8- | 19.0- | 21.3- | | 25.7- | 28.0- | 30.2- | | SPEED | SPEED |
| | | 1.1 | 3.1 | 5.4 | 7.6 | 9.8 | 12.1 | 14.3 | 16.6 | 18.8 | 21.0 | 23.3 | | 27.7 | 30.0 | 32.2 | >32.2 | (MPH) | M/SEC) |
| Ŧ | 65 | 4.4 | 0.1 | 12.2 | 22.1 | 21.5 | 17.5 | 9.3 | 4.9 | | | | | | | | 0.0 | | 4.1 |
| | 9 | 3.7 | 0.3 | 13.2 | 25.6 | 20.8 | 16.0 | 4.6 | 5.1 | 5.6 | ۳. ئ | 9.0 | 0.5 | 0.5 | 0.1 | 0.0 | 0.0 | | 4.0 |
| 0 | 6 | 2.2 | 0.2 | 10.9 | 16.1 | 18.4 | 14.4 | 13.2 | 6.6 | | | | | | | | 0.0 | | 4.9 |
| | 12 | 6.0 | 0.0 | 7.3 | 14.5 | 14.7 | 15.1 | 13.8 | 12.8 | | | | | | | | 0.2 | | 5.5 |
| ⊋ | 15 | -: | 0.1 | 5,5 | 10.0 | 13.3 | 15.0 | 15.9 | 11.2 | | | | | | | | 0.1 | | 0.9 |
| | 18 | 0.0 | 0,2 | 7.7 | 11.4 | 15.3 | 16.5 | 14.1 | 13.8 | | | | | | | | 0.2 | | 5.8 |
| œ | 21 | 2.3 | 7.0 | 10.9 | 21.9 | 25.4 | 15.0 | 7.4 | 0.9 | | | | | | | | 0.1 | | 1 . 1 |
| | 54 | 2.1 | 0.1 | 10.0 | 19.7 | 22.2 | 19.7 | 10.2 | . r. | | | | | | | | 0.0 | 10.1 | 4.5 |
| ALL HC | HOURS | 2.2 | 0.2 | 9.3 | 17.7 | 19.0 | 16.2 | 11.7 | 8.6 | 6.7 | 4.2 | 2.0 | 1.1 | 0.7 | 4.0 | 0.2 | 0.1 | 10.9 | 6.4 |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

Table IV - 157

Percentage Frequency Summary for Wind Speed
VALLEY COUNTY - GLASGOW NWS AIRPORT (AUTUMN)

| | | | ED | M/SEC) | - | _ | - | m | 6 | . 6 | m | 4.2 | 7 |
|--------|----------------------|----------|----------|---------|------|------|----------|------|----------|------|------|------|-----------|
| | | | | Ξ. | | | | | | | | | |
| | | 8 | SPEE | (MPH) | | | | | | | | 7.6 | 10.4 |
| | >14.4 | | | >32.2 | 0.1 | 0.1 | 0.0 | 9.0 | 0.8 | 0.5 | 0.5 | 0.1 | 0.2 |
| | 13.5- | | | 32.2 | 0.2 | 0.0 | 0.3 | 0.5 | 0.7 | 0.5 | 0.1 | 0.2 | 0.3 |
| | 12.5- 13.4 | | 28.0- | 30.0 | | | | | | | | 0.0 | 0.3 |
| | 11.5- 12.4 | | 25.7- | 27.7 | | | | | | | | 0.5 | 0.7 |
| | 10.5- | | | | 0.4 | 0.3 | 1.2 | 1.2 | 1.6 | 1.6 | 9.0 | 0.3 | 0.9 |
| | 9.5- | | 21,3- | 23.3 | | | | | | | | 1.6 | 2.3 |
| Ξ | 8.5- 9.4 | EC) | 19.0- | 21.0 | | | | | | | | 3.2 | 4.0 |
| ED (MP | 7.5-8.4 | S/W) C | 16.8- | 18.8 | | | | | | | | 4.2 | 5.8 |
| ND SPE | 6.5-7.4 | D SPEE | 14.5- | 16.6 | | | | | | | | 5.6 | 7.9 |
| 3 | 5.5- 6.5- 7.5- 8 | <u> </u> | 12.3- | 14.3 | 9.4 | 7.4 | 8.5 | 10.9 | 13.0 | 10.8 | 9.5 | 9.3 | 9.8 |
| | 3.5- 4.5- 4.4 5.4 | | 10.1- | 12.1 | 13.1 | 14.5 | 13,3 | = | 12.9 | 15.1 | 17.2 | 15.8 | 14.1 |
| | 3.5- | | 7.8- | 9.8 | | | | | 12.1 | | | | 18.4 |
| | 2.5- | | 5.6- | 7.6 | 20.5 | 21.7 | 21,2 | 17.9 | 1.5 | 16.0 | 21.3 | 21.3 | 12.2 18.9 |
| | 1.5- | | 3.4- | 5.4 | 14.2 | 15.4 | 15.0 | 10.2 | 8 | 6.6 | 12.6 | 12.1 | |
| | 0.5- | | <u>-</u> | 3.1 | 0,2 | 0.2 | 7.0 | 0.0 | 0.0 | 0.5 | 0.5 | 0.1 | 0.2 |
| | <0.5 | | | <u></u> | 5.9 | 4.8 | 5.1 | 2.4 | 1.8 | 2.9 | 3.5 | 6.1 | 4.1 |
| | | | | | က | 9 | 6 | 12 | 5 | 38 | 51 | 54 | HOURS |
| | | | | | I | | 0 | | > | | œ | | ALL |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

Table IV - 158

Annual Wind Rose Distribution

VALLEY COUNTY - GLASGOW NWS AIRPORT

06/01/68 - 12/31/78

| TOTAL <direction SPEED (M/SEC)</direction | 0.5-1.4 2.5-3.4 3.5-4.4 6.5-7.4 7.5-7.4 11.5-12.4 12.5-17.4 12.5-13.4 12.5-17.4 14.5-15.4 15.5-16.4 16.5-15.4 17.5-17.4 18.5-19.4 18.5-19.4 18.5-19.4 19.5-20.4 19.5-20.4 18.5-19.4 19.5-20.4 18.5-19.4 18.5-19.4 19.5-25.4 20.5-25.4 20.5-25.4 20.5-25.4 20.5-25.4 20.5-26.4 |
|--|--|
| TOTAL | 0000 000 000 000 000 000 000 00 |
| X N N | 000000000000000000000000000000000000 |
| 3 | 000000000000000000000000000000000000000 |
| MNM | 0000000000000000000000000000000000 |
| 3 | 0.00 |
| MSM | 000-0000000000000000000000000000000000 |
| MS | 000000000000000000000000000000000000000 |
| MSS | 00000000000000000000000000000000000000 |
| S | 000-0000000000000000000000000000000000 |
| SSE | 000000000000000000000000000000000000000 |
| SE | 000000000000000000000000000000000000 |
| ESE | 0000-wwww.r-0000000000000000000000000000 |
| ш | 000-00-0000000000000000000000000000000 |
| E N F | 00000000000000000000000000000000000000 |
| Ä | 00000000000000000000000000000000000000 |
| NN | 00000000000000000000000000000000000000 |
| z | 00000000000000000000000000000000000000 |
| DIRECTION> SPEED (MPH) | 3.4-5.4 5.5-6-7.6 7.8-9.8 7.8-9.8 7.8-9.8 10.1-12.1 11.5-14.3 19.0-21.0 19.0-21. |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES




Table IV - 159

Coefficients of Weibull Distribution

VALLEY COUNTY - GLASGOW NWS AIRPORT

06/01/68 - 12/31/78

| MONTH | SCALE FACTOR (C) (M/SEC) | SHAPE FACTOR (K) |
|------------------------------|--------------------------------|---------------------|
| JANUARY FEBRUARY MABCH | 5.6660 6.6380 | 1.9680 2.6350 |
| APRIL MAY | | 2.3220 |
| JUNE | · • • | ٠ |
| AUGUST SFPTFMBFR | | ν. |
| OCTOBER NOVEMBER | 6.7230 | 0.0 |
| DECEMBER | • | w. |
| YEAR | 6.7430 | 2.8560 |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

JUDITH GAP

WHEATLAND COUNTY

The Judith Gap site is located about 6 miles south of the town of Judith Gap at 46 36 57 N and 109 46 11 W (Site No. 134 on Map II-1). Elevation at the site is about 4,600 feet. The site was established by the Bureau of Reclamation as part of its Northern Great Plains Wind Energy Study.

The site sits on a gently sloping plain to the south of Judith Gap. The Musselshell River flows to the south. To the northwest are the Little Belt Mountains, with summits to about 7,000 feet. The Snowy Mountains, with summits to about 8,600 feet, rise to the northeast. Between these ranges is the Judith Gap. To the southwest, the Crazy Mountains rise to over 11,000 feat

Most of the land in the area is privately owned and used for agriculture, although a few scattered sections are owned by the state. Land in the mountains is controlled by the U.S. Forest Service.

Electrical power in the area is provided by the Montana Power Company and the Fergus Electric Cooperative. A 230-kV power transmission line runs near the site and many smaller transmission lines cross the area. The nearest commercial airport is at Lewistown. The area is in the aircraft corridors from Billings to Helena and Billings to Great Falls.

Collection of wind data at the site began on August 1, 1981. The site was closed in 1985; data are available through July 31. The data set consists of hourly averages of wind speed, wind direction, temperature, pressure, and relative humidity. Data were collected by an automatic system that transmitted information by satellite to Denver for further processing. Anemometer height was 7 meters. (It is erroneously listed in several publications as being at a height of 10 meters.)

Overall data recovery at the site was excellent; however, due to technical problems, the Bureau of Reclamation was unable to provide DNRC with copies of the data from six months. The resulting data recovery rates ranged from 47.5 percent in January to 97.9 percent in February. Overall data recovery was 81.9 percent. Data from this site should adequately represent the area in the

Average annual wind speed at the site was 13.0 miles per hour. Average monthly wind speeds varied from 10.7 miles per hour in August to 15.6 miles per hour in January.

Average annual wind power was 239.2 watts/m². Average monthly wind power ranged from 127.4 watts/m² in August to 471.7 watts/m² in January.

Average seasonal wind speeds were 11.3 miles per hour in summer, 12.4 miles per hour in autumn, 13.5 miles per hour in spring, and 14.9 miles per hour in winter. During the summer, the highest average wind speeds occurred in late afternoon. In all other seasons, the highest average wind speeds occurred in early afternoon. The lowest average wind speeds generally occurred between 2200 MST and 0500 MST in the winter, 0300 MST in the spring, 0800 MST in the summer, and 0600 MST in the autumn. The diurnal range of average wind speeds was least in winter.

The most common wind directions were north-northwest through north and west-southwest through west-northwest. Winds from the northeast through east were least common. By direction, average speeds ranged from 5.0 miles per hour for winds from the east-northeast to 17.8 miles per hour for winds from the west.




Table IV - 160

Monthly Wind Speed Distribution

WHEATLAND COUNTY - JUDITH GAP

08/06/81 - 07/31/85

| | | . | h ~ | . ~ | ٠. | | | | _ | | _ | _ | ۔۔ | | | _ | | | | _ | - | | | | | | | | | | |
|-----------|-----------------|----------|--------------|-------------|----------|----------|---------|---------|----------|----------|----------|-----------|-----------|-------------|-----------|-----------|-----------|-----------|-------------|----------|-----------|-----------|-----------|-----------|------------------|------------------------|---------------|-----------------------|--------------|----------|--|
| | CALM CALM | 7.0 | | 1.4- 1.8 | 1.9- 2.2 | 2.3- 2.7 | 2.8-3.1 | 3.2-3.6 | 3.7- 4.0 | 4.1- 4.5 | 4.6- 4.9 | 5.0- 5.4 | 5.5- 5.8 | 5.9-6.3 | 6.4- 6.7 | 6.8-7.2 | 7 3- 7 6 | 7.7-8.0 | 8.1-8.5 | 8-6-8 | 9.0-11.2 | 11.3-13.4 | 13.5-15.6 | 15,7-17 9 | >17.9 | | | | | | |
| YEAR | 0.0 | ۰ د د |) () i (i | 5.4 | 4.7 | 6,3 | 5.2 | 5.7 | 5.2 | 6.5 | 4.6 | 5.5 | 3.6 | 4.0 | 3.2 | 2.5 | 3.6 | 2.6 | 2.9 | 2.5 | 10.1 | 9 | 2.6 | 8 | 0.4 | 13.0 | 5,8 | ; | 239.2 | 81.9 | |
| 絽 | 0.0 | 0°0 | | ນີ້ | 4.8 | 5.8 | 3,9 | 3.8 | 3.1 | 4.7 | 3.0 | 4.9 | 4.2 | 4.0 | 3,9 | | 3 | 3.1 | 3.5 | 2.9 | 12.3 | 8 | 4.3 | 0.7 | 0.4 | 14.3 | 6.4 | | 307.4 | 72.3 | |
| AON | 0.0 | | 4.1 | 6.1 | 4.4 | 6.3 | 5.0 | 4.4 | 4.2 | 4.7 | 4.7 | 5.0 | 4.2 | 5.4 | 4.7 | 2.9 | 4.2 | 2.8 | 3,4 | 3.1 | 10.2 | 4.5 | 1.2 | 0.1 | 0.0 | 12.3 | 5.5 | | 184.3 | 73.5 | |
| OCT. | 0.0 | 7 0 | 3,1 | 6.0 | 4.4 | 7.1 | 5.5 | 6.2 | S S | 7.0 | 7 | 5.1 | 5.6 | 3.2 | 2.8 | 2.4 | 3.7 | 1.6 | 2 3 | 2.2 | 8 | 7.1 | e e | 0.8 | 0.0 | 12.8 | 5.7 | | 237.3 | 71.1 | |
| R | 0.0 | | | | | | | | | | | | | | | | | | | | | | | | | 12.2 | 5,5 | | 181.4 | A | |
| AUG | 0.0 | | 2.6 | 7.1 | 5.4 | 8,3 | 7.0 | 7.7 | 7.2 | 9 | 2.6 | 6.5 | 3.7 | 4.2 | 2.6 | 1.9 | 3,5 | 1.6 | 1.6 | 1.7 | 5,3 | 2.7 | 1.4 | 0,3 | 0.0 | 10.7 | 8. | | 127.4 | | |
| JI | 0.0 | 2.5 | 3.0 | 6.0 | 5.7 | 6.9 | 6.0 | 7.2 | 6.3 | 7.3 | 4.8 | ນີ້ | 4.0 | 3.9 | 3.2 | 2.5 | 3.7 | 3.0 | 2.5 | 2.9 | 7.7 | 3.0 | 1.2 | 0.2 | 0.3 | 11.5 | 5.1 | | 153.2 | 97.8 | |
| SCN | 0.0 | | | | | | | | | | | | | | | | | | | | | | | | | 11.7 | 5.2 | | 160.2 | 93.2 | |
| MAY | 0.0 | | | | | | | | | | | | | | | | | | | | | | | | | 13.7 | 6,1 | | 256.4 | 73.0 | |
| APR | 0.0 | | | | | | | | | | | | | | | | | | | | | | | | | 13.7 | 6.1 | | 302.0 | 8.5 | FEET |
| MAR | 0.0 | | | | | | | | | | | | | | | | | | | | _ | | | | | 13.3 | 5.9 | | 245.9 | 97.0 | = 22.5 |
| FEB | 0.0 | 1.9 | 2.4 | 4.0 | ۳ ش | 4.6 | က | 4.7 | 4.4 | 0°5 | 4.2 | 5.2 | 3.2 | 4.0 | 3.1 | 8 | 4.5 | 3.0 | 3.7 | 3.1 | 13.5 | 8 0 | 3.4 | 1.4 | 0.8 | 15.0 | 6.7 | | 337.4 | 6.76 | METERS |
| JAN | 0.1 | • — | m | 4.5 | 4.2 | 5,0 | 4.9 | 5.7 | 5.4 | 2.5 | ~; ~; | 9 | ۳. د د | 2.7 | 2.0 | 2.0 | 2.5 | 2.0 | 2.0 | 2 3 | 10.0 | 9.5 | 5,9 | 3.6 | 2.4 | 15,6 | 7.0 | | 471.7 | 47.5 | |
| | CALM 0.1-1.0 | 1.1-2.0 | 2.1-3.0 | 3.1-4.0 | 4.1-5.0 | 5.1-6.0 | 6.1-7.0 | 7.1-8.0 | 8.1-9.0 | 9.1-10.0 | 0.11-1.0 | 11.1-12.0 | 12.1-13.0 | 13, 1-14, 0 | 14.1-15.0 | 15.1-16.0 | 16.1-17.0 | 17.1-18.0 | 8.1-19.0 | 9.1-20.0 | 20.1-25.0 | 25.1-30.0 | | 35.1-40.0 | >40.0 Average | SPEED (MPH) AVFRAGE | SPEED (M/SEC) | AVERAGE VTND POVER | (WATTS/M**2) | RECOVERY | angmometer height = Nimber of observati |
| | | | S | Q. 1 | ш | щ | 0 | : | Σ | . | | | | | | | | | | | 2 | ~ | r | m | AV | SPEE | SPEED | Y Y | (WATT | AEC(| ANEMOR |

NGUUM KUHUKN/NUUNA

NUMBER OF OBSERVATIONS = 28626
PERCENTAGE DATA RECOVERY = 81.9
SOURCE: GEORESEARCH, INC.

Table IV - 161

Percentage Frequency Summary for Wind Speed

WHEATLAND COUNTY - JUDITH GAP (WINTER)

08/06/81-07/31/85

| ٩ | SPEED M/SEC) | 6.1 | 0.9 | ۍ و | 6.0 | 6.2 | 6,3 | 6.1 | 6,3 | 6.5 | 9.9 | 6,9 | 7.6 | 7.8 | 8.2 | α. - | 8. | 7.3 | 6. 7 | 6,3 | 6,3 | 6. 2 | 6.1 | 6.1 | 0.9 | 9.9 |
|-----------------------------------|-----------------|------|------|--------|------|-------|--------|-----------|--------|------|------|------|------|----------|------|---------|------|------|-------------|--------|------|-------------|--------|------|------|-----------|
| | SPEED (MPH) | 13.5 | 13.4 | 13.2 | 13.3 | 13.8 | 14.0 | 13.6 | 14.1 | 14.6 | 14.7 | 15.5 | 16.9 | 17.4 | 18,3 | 18.2 | 17.5 | 16.3 | 15.0 | 14.1 | 14.1 | 14.0 | 13.7 | 13.7 | 13.5 | 14.9 |
| >40.0 | >17.9 | 0.4 | 0.4 | 8.0 | 0.4 | 8 | 1:1 | 0. | 1:1 | 1:1 | 0.8 | 0.8 | 1.3 | 1:1 | 1.5 | 1.9 | 0.8 | 0.4 | 0.8 | 0.4 | 1.2 | 0.4 | 0.0 | 0.4 | 0.4 | 0.8 |
| 35.1- 40.0 > | 15.7- 17.9 | 1.1 | | | | | | | | | | | | | | | | | | | | | | | | 1.3 |
| 30.1- 35.0 | 13.5- 15.6 | 4.5 | 3.0 | 4.9 | 4.5 | 4.2 | ب 8 | 3.1 | 2,3 | 2.3 | 5.0 | 4.4 | 5.8 | 8.6 | 8.2 | 7.1 | 7.9 | 5.3 | 5.3 | 2.7 | 4.6 | 4.2 | 5.4 | വ | 3.8 | 4.9 |
| 25.1- 30.0 | 11.2- 13.4 | 4.5 | 4.5 | 4.2 | 6.8 | 4.2 | 4.2 | 6.1 | 6.5 | 5.7 | 5.0 | 6.4 | 7.6 | 9,4 | 12.0 | 14.2 | 8.7 | 8.0 | 7.3 | 7.7 | 3.9 | 6,9 | 7.4 | 4.3 | 7.6 | 6.8 |
| 20.1- 25.0 | 9.0- 11.2 | 12.8 | | | | | | | | | | | | | | | | | | | | | | | | 14.2 |
| 18.1- 20.0 | 8.1- 8.9 | 4.1 | | | | | | | | | | | | | | | | | | | | | | | | 6.1 |
| (MPH) 16.1- 18.0 ERS/SE | 7.2-8.0 | 5.6 | 6.4 | 4.2 | 8.3 | 5.7 | 6.9 | 6.9 | 6.9 | 8.4 | 5.0 | 7.6 | 8.9 | 5.2 | 4.5 | 6.7 | 0.9 | 7.3 | 6.1 | 8 | 8.1 | 5.8 | 5.4 | 5.5 | 6.8 | 6.5 |
| SPEED 14.1- 16.0 | ` | 6.0 | 6.8 | 5,3 | 6.4 | ω | 7.7 | 6.9 | 8.4 | 8.0 | 5.8 | 7.6 | 3.1 | 3.0 | 2.6 | 4.5 | 6.0 | 5.7 | 5.7 | 4.6 | 5.8 | 6.2 | 7.4 | 7.5 | 5.9 | 5,9 |
| WIND 12.1- : 14.0 0 SPEE | 5.4- 6.3 | 7.5 | 0.9 | 9.1 | 7.2 | 8.7 | 8.0 | 11.1 | & & | 6.9 | 10.0 | 6.4 | 4.0 | 4.5 | 6.0 | 4.5 | 6.8 | 5.7 | 6.9 | 5.4 | 6.2 | 9,3 | 7.8 | 8,7 | 8.4 | 7.2 |
| 10.1- 12.0 WIN | 4.5- 5.4 | 10.2 | 12.4 | ж Э | 11.7 | 9,9 | 11.5 | 8 | 9.2 | 6,5 | 5.8 | 6.4 | 5.4 | 7.5 | 8.2 | 7.1 | 6.8 | 9.2 | 10.3 | 10.4 | 8.1 | 10.8 | α Ο | 0.6 | 8.0 | 8 8 |
| 8.1- 10.0 | 3.6- 4.5 | 9.4 | 9.8 | 10.9 | 11.7 | 15.2 | 10.0 | α | 8.4 | 7.3 | 5.8 | 6.8 | 6.3 | 10.1 | 4.5 | 6.4 | 9.4 | 9,5 | 11.1 | 11.5 | 10.4 | 6,3 | 10.1 | 8.2 | 8.0 | 9.1 |
| 6.1- 8.0 | 2.7- 3.6 | 11.7 | 0.6 | 8 7 | 7.2 | 9.1 | 7.3 | 7.7 | 10.0 | 10.0 | 8.1 | 6.8 | 8.6 | 7.9 | 7.9 | 6.7 | 6.0 | 7.6 | 10.3 | 9.6 | 9,3 | တ | 10.1 | 11.4 | 11.4 | 8.7 |
| 4.1- 6.0 | 1.8- 2.7 | 9.4 | 13.2 | 12.8 | 10.6 | 7.2 | 10.0 | 12.3 | 8.0 | 11.1 | 9.2 | 12.4 | 7.6 | 8,0 | 5.2 | 7.1 | 3.0 | 7.6 | 8 | 10.8 | 10.4 | 12.7 | 8 | 10.2 | 13.5 | 9.6 |
| 2.1-4.0 | 0.9- | 8,3 | 5.6 | 7 9 | 8.7 | 9.5 | 7.3 | 8 | 9.6 | 8 | 11.2 | 0.9 | 5.8 | 4.1 | 7.1 | 3,7 | 6.8 | 5.3 | 5.7 | ъ 8 | 6 9 | 7.7 | 10.1 | 9,4 | 6,3 | 7.4 |
| 0.1- | 0.1- | 4.5 | 4.1 | 4 | 3.8 | 3.0 | ۍ 8 | 3.4 | 1.9 | 1.5 | 3,8 | 3.2 | 2.7 | 1.5 | 0.4 | 1.5 | 1:1 | 1:1 | 0.8 | 1.9 | 3.5 | 3.5 | 3 | 3.1 | 4.6 | 2.8 |
| CALM | CALM | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.4 | 0 | 0 | 0 | 0.0 | 0.0 | 0.0 |
| | | - | ~ | m | ** | 'n | 9 | 7 | ∞ | σ | 10 | Π | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 8 | 7 | 8 | 33 | \$ | ALL HOURS |
| | | | | | | | | | | × | | 0 | | ¬ | | ~ | | | | | | | | | | ALL |

Table IV - 162

Percentage Frequency Summary for Wind Speed

WHEATLAND COUNTY - JUDITH GAP (SPRING)

08/06/81 - 07/31/85

| | | | | S/VS | | 4 | 4 | 2,2 | 5.2 | 5.2 | ຜ | 6.1 | 9.9 | 7.0 | 7.2 | 7.4 | 7.5 | 7.5 | 7.5 | 7.4 | 7.2 | 6.7 | 5,9 | 5.4 | 5.2 | 4.9 | 5.0 | 5.0 | 6.0 |
|------|------------|------------------|-------|-------|------|----------|------|--------|------|------|------|------|----------|------|------------|---------|------|----------|------|--------|-------------|------|-------------|----------|------|------|---------|------|---------|
| | | ۸۸ | SPEF | Œ | 11,0 | | 11.1 | 11.7 | 11.7 | 11.6 | 12.4 | 13.6 | 14.8 | 15,6 | 16.1 | 16.5 | 16.7 | 16.8 | 16.8 | 16.5 | 16.0 | 15.0 | 13,3 | 12.1 | 11.6 | 10.9 | 11.2 | 11.2 | 13.5 |
| | | >40.0 | | >17.9 | 0.0 | 0 | 0 | 0.0 | 0.0 | 0.0 | 9.0 | 0.6 | 9.0 | 0.0 | 0.3 | 0.8 | 0.9 | 0.3 | 0.9 | 0.3 | 0.0 | 0.0 | 0.3 | 0.3 | 0.0 | 0.0 | 0.0 | 0.4 | 0.3 |
| | 35.1- | 40.0 | 15.7- | 17.9 | 0.6 | 0.9 | 0 | 0.3 | 0.3 | 0.6 | 1.5 | 1.5 | 2.1 | 1.8 | 1.0 | 1.2 | 0.6 | 0.9 | 9.0 | 0.6 | 0.9 | 9.0 | 0.9 | 0,3 | 0.3 | 0.3 | 9.0 | 0.0 | 0.8 |
| | 30.1- | 35.0 | 13.5- | 15.6 | 3.0 | | 3.6 | ω. | 3.6 | 3.0 | 4.2 | 4.5 | 4.5 | 4.0 | ຜູ | 9.9 | 6.5 | 6.5 | 5.7 | 4.5 | 3.6 | 2.4 | 6.0 | 1.2 | 1.2 | 0.6 | 2,8 | 3.5 | 3.6 |
| | 25.1- | | | 13.4 | 3,0 | 4.5 | 2.7 | 4.2 | 4.8 | 2.7 | 2.1 | 3.6 | 4.5 | 7.0 | 9.6 | 7.9 | 9.5 | 10.1 | 7.8 | 8.7 | 7.8 | 8.1 | 3,3 | 3,9 | 3.0 | 3.7 | 2.8 | 4.2 | 5.4 |
| | 20.1- | 25.0 | 0.6 | 11.2 | 8.0 | 5 | 7.1 | 6.3 | 6.8 | 9.0 | 11.1 | 16.0 | 15.8 | 19.0 | 19.3 | 18.6 | 18.7 | 19.9 | 21.5 | 22.1 | 18.3 | 16.2 | 14.1 | α. 4. | 8.5 | 7.9 | 9.9 | 4.9 | 12.9 |
| | _ | 20°0 COND) | 1 | | 2.7 | 4.5 | 3.9 | 4.2 | 2.1 | 5.1 | 5.7 | 6.3 | 9.1 | 4.9 | 4.5 | 5. 8 | 7.4 | 5.4 | 8,1 | 6.3 | 10.2 | 9.9 | 6.3 | 4.2 | 4.9 | 4.9 | 4.4 | 4.2 | 5,5 |
| (FE) | 16.1- | 18.0 ERS/SE | 7.2- | 8.0 | 3.6 | 5.6 | 4.5 | 5,4 | 5.4 | 5.4 | 0.9 | 9.9 | 7.3 | 5.8 | 6.8 | 7.4 | 6.5 | 6.5 | 5.7 | 7.8 | 8.7 | 2.7 | 6.9 | 5.7 | 4.9 | 3.0 | 4.4 | 4.6 | 5.8 |
| | | 16.0 (ME) | _ | | 5.0 | 2.4 | 4.5 | 5.1 | 6.5 | 0.9 | 6.9 | 5.7 | 2.5 | 5.8 | 4.8 | 5.0 | 4.5 | 5.4 | 7.8 | 5.7 | 5.4 | 10.2 | 6.9 | 6.0 | 4.6 | 4.9 | 5.0 | 4.2 | 5.6 |
| | | 14.0 10 SPEED | | | 8.6 | 8,0 | 8.3 | 8,3 | 8.0 | 7.8 | 3.9 | 3.9 | 4.5 | 6.1 | 6.8 8.0 | 9.9 | 8,9 | 7.7 | 7.2 | œ | 9.6 | 8.7 | 9,3 | ۍ م | 8,2 | 6.4 | 8. 4 | 9.1 | 7.6 |
| | 10.1- | 0.21 WIN | 4.5- | 5.4 | 8,3 | Ω. 80 | 8,9 | 11.6 | 11.3 | 8.1 | 8.1 | 5.4 | 20 | 10.7 | 8.4 | 9.1 | 7.1 | 10.4 | 5.4 | 6.9 | 7.8 | 11.7 | 9.6 | 13.6 | 13,4 | 13.4 | 11.6 | 11.9 | 9.5 |
| | %: -1.8 | 0.01 | 3.6- | 4.5 | 11,3 | 10.7 | 13.4 | 12.2 | 11.9 | 10.1 | 6,3 | 6.9 | 91 | 8 | 10.9 | 9.1 | 11.0 | 8 0 | 13.1 | 6 | α, 4 | 6,3 | 12.6 | 13.0 | 17.9 | 14.6 | 13.8 | 8 | 11.1 |
| | 6.1- | » C | 2.7- | 3.6 | 13.4 | 11.9 | 13.4 | 12.8 | 11.0 | 11.0 | 8.7 | 10,3 | 8.2 | 10.1 | 7.7 | 7.9 | 5,9 | 9 | 7.8 | 10.4 | ლ თ | 6.9 | 11.1 | 15.4 | 12.8 | 12.5 | 9.1 | 12.6 | 10.3 |
| | 4.1- | • | 1.8- | 2.7 | 15.4 | 14.5 | 13.4 | 15.2 | 11.9 | 14.0 | 12.0 | 11.2 | 12.7 | 6 | 6.8 | 9.5 | 7.4 | 8° 0 | 4.8 | 2 | 4 ,0 | 7.5 | 10,2 | 11.1 | 9.7 | 11.9 | 11.3 | 12,3 | 10.4 |
| | 2:1- | 4. | 9.0 | 1.8 | 11.0 | 12.8 | 11.0 | 7.7 | 12.2 | 12.5 | 15.3 | 12.4 | ထ | 3.4 | 4.5 | 4.1 | 4.2 | 3,3 | 1.8 | m m | 9,6 | 5.4 | 4 ,5 | Δ, Ω | 8,2 | 10.4 | 14.7 | 13.7 | 8.1 |
| | -1.6 | 2,2 | 0.1- | 0.9 | 6.2 | 6.2 | 5.6 | 3.6 | 4.2 | 4.8 | φ. | 4.5 | 2.1 | 2.1 | 2.9 | 0.4 | 1.2 | 0.0 | 2.1 | 9.0 | 2.1 | 6.0 | ۰ ۳ | 2.4 | 2.4 | 2 | 4.7 | 4.6 | 3,3 |
| | 3 | 5 | | CALM | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | e . | 0.0 | 0 | 0 | 0.0 | 0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0 | 0,3 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| | | | | | - | 2 | m | 4 | ഹ | 9 | _ | ∞ • | <u>ه</u> | 9 | = : | 12 | 13 | 7 | 12 | 9[| 17 | 18 | 61 | 25 | 7 | 23 | 2 | 74 | . HOURS |
| | | | | | | | | | | | | | - | • | 0 | | > | | ~ | | | | | | | | | | 1 |

GEORESEARCH, INC.

SOURCE:

Table IV - 163

Percentage Frequency Summary for Wind Speed

WHEATLAND COUNTY - JUDITH GAP (SUMMER)

08/06/81 - 07/31/85

| | ~ C | | | | | | | | | | | | | | | | | | | | | | | | | |
|------------------------------------|---------------|------|--------|-------------|-------------|------|------|--------|------|-------------|------|--------|------|--------|------|------|------|------|------------|------|------|------------|--------|------|-----------|---|
| ₽ | (M/SEC | 4.2 | 4.4 | • | . e. | 4.0 | 4.2 | 4.6 | က် | ر د د | 2 | 5.9 | 6.1 | 6.3 | 6.3 | 4.4 | 6.4 | 6.1 | 5.7 | 0 | 4.7 | 4.6 | 4.5 | 4.5 | 5.1 | |
| ¥ | (FE) | 9.4 | ک ت | , 0 | 8.0 | 9.0 | 9.5 | 10.2 | 11.3 | 12.3 | 13.0 | 13,3 | 13.7 | 14.1 | 14.2 | 14.4 | 14.3 | 13.7 | 12.8 | 11.1 | 10.5 | 10.2 | 10.1 | 10.1 | 11.3 | |
| >40.0 | >17.9 | 0.0 | 000 | 90 | 0 | 0.0 | 0.0 | 0.0 | 0 | 0.0 | 0 | 0.0 | 0.3 | 0.3 | 0.3 | 0 | 0.0 | 0.3 | 0 | 0.0 | 0.0 | 0.3 | °, | 0.0 | 0.1 | |
| 35.1- 40.0 | 17.9 | 0.0 | 0.0 | 9 0 | , e | 0.3 | 9.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.6 | 0.0 | 0.3 | 0.3 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.3 | 0.1 | |
| 30.1- | 13.5- 15.6 | 0.6 | 0.0 | , q | o m | 0.3 | 1.3 | 6.0 | 1.9 | 2.2 | 2.2 | ۰ ۳ | 2.5 | , 8 | 2.8 | 1.5 | °, | 0.6 | 0.6 | 1.3 | 1.3 | 1.3 | 1:0 | 1.0 | 1.3 | |
| 25.1-30.0 | 13.4 | 2.5 | S 1 | ه د د | 9.1 | 1.9 | 9.0 | 2.8 | ສຸນ | 4.1 | 4.2 | 3.4 | 3.4 | 4.0 | 2.5 | 3.4 | 6.3 | 5.0 | 7 8 | 1.3 | 2.2 | 0.6 | 1.3 | 1.4 | 2.6 | |
| 20.1- 2 25.0 | 9.0- 11.2 | 4.6 | 2.2 | ຄຸດ | , r | 4.7 | 6.9 | 8.5 | 8,2 | 11.4 | 12.2 | 9 2 | 11.5 | 13.0 | 13.6 | 14.9 | 13.8 | 10.3 | 9.4 | 5.7 | 4.4 | 6.7 | 5.2 | 5.1 | 8.3 | |
| 18.1- 3 20.0 30ND) | 8.9 8.9 | 2.5 | 2,7 | 2.5 | 3.1 | 2.8 | 3.8 | 5,3 | 5,4 | 4.1 | 7.4 | 11.1 | 5,3 | 5.9 | 6.8 | 7.4 | 6.3 | 6.9 | 6.9 | 2,5 | 2.8 | 1.6 | 2,3 | 4.1 | 4.6 | |
| (MPH) 16.1-] 18.0 ERS/SE | 7.2- 8.0 | 3.4 | ٠, ۲ | 200 | 3.0 | 3.4 | 4.4 | 3.1 | 5.7 | 8.2 | 7.1 | 7.4 | 0.6 | 8.0 | 9.0 | 9,3 | 9.7 | 10.7 | 10.0 | 7.9 | 5.1 | 4.5 | ტ რ | 4.1 | 6.2 | |
| SPEED 14.1- 1 16.0 | 6.3- | 4.0 | 2.5 | 7 | 1.0 | 3.4 | 4.1 | 5,3 | 6.0 | 6,3 | 5.4 | 4.4 | 8.4 | 9.6 | 0.6 | 6.5 | ထ | 9.7 | 7.2 | 6.9 | 4.1 | 4.1 | 5.2 | 6.1 | 5.7 | |
| WIND SPEET | 6.3 | 6.5 | 6.2 | ກິດ | ο Ο Ο | 6.2 | 5.0 | 6.0 | 6,3 | 6.3 | 6.4 | 6.4 | 10.8 | 9.3 | 8.4 | 12.4 | 10.0 | | 11.3 | 10.4 | 9.5 | 7.6 | 8.9 | 4.8 | 7.7 | |
| 10.1- 12 12.0 1 | 4.5- 5.4 | 10.8 | œ (| 7.0 | 2 7 0 7 | 7.2 | 7.2 | 7.2 | ထ | 9.9 | 8.0 | 12.2 | 12.7 | 12.7 | 14.9 | 14.2 | 14.7 | 16.0 | 15.4 | 16.7 | 10.8 | 12.4 | 13.2 | 11.6 | 11.0 | |
| | 3.6- | 14.2 | 14.5 | 16. | 3.0 | 13.1 | 11.3 | α α | ω | 13.0 | 15.4 | 17.9 | 13.0 | 13.3 | 11.5 | 12.4 | 12.9 | 11.6 | 13.8 | 15.4 | 21.2 | 20.1 | 14.5 | 15.3 | 14.0 | |
| 6.1- 8.0 | 2.7- 3.6 | 15,4 | 17.9 | 16.1 | ر د د | 17.8 | 12.5 | 11.9 | 15,1 | 14.2 | 13.5 | 8 | 9,3 | 9.6 | 6.6 | 9.0 | 8,2 | ထ | 7.8 | 12.9 | 13.9 | 15.3 | 18.4 | 16.7 | 13.1 | |
| 4.1-6.0 | 1.8- 2.7 | 18.8 | 16.4 | 16.4 | 7 6 | 19.0 | 20.9 | 19.5 | 15.1 | 12.3 | 11.2 | 9.5 | 6.2 | 6.5 | 7.1 | 4.3 | 6.9 | 9.9 | 9.1 | 8.2 | 14.6 | 12.4 | 14.5 | 14.3 | 12.8 | |
| 2.1-4.0 | 1.8 | 11.1 | 14.2 | 15.2 | 16.1 | 15.9 | 16.3 | 15.4 | 13.6 | 9.5 | 5.8 | 4.7 | 5.3 | 4.0 | 3.1 | 3.7 | 1.9 | 4.1 | 3,4 | 7.9 | 7.3 | 10.2 | 10.0 | 13.3 | 9.5 | ! |
| 0.1- | 0.1 - 0.9 | 5.6 | 6.5 | 20 | ν ν ν | 4.0 | 2 | 5.0 | 1.6 | 1.9 | 1.3 | 2.0 | 1.9 | 0.0 | 6.0 | 0.3 | 0.3 | 6.0 | 2.2 | 3.1 | 2.8 | 2.9 | 3,5 | 2.0 | 3.0 | į |
| CALM | CALM | 0.0 | 0.0 | e 0 | 0 0 | | 0.0 | 0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | |
| | | - | 7 | m · | 47 r. | y co | 7 | . α | 6 | 10 | Ξ | 12 | 13 | 14 | 15 | 16 | 11 | 18 | 13 | 2 | 12 | 8 | 23 | 72 | ALL HOURS | |
| | | | | | | | | | = | | 0 | • | _ | 1 | 00 | | | | | | | | | | ALL | |

Table IV - 164

Percentage Frequency Summary for Wind Speed

WHEATLAND COUNTY - JUDITH GAP (AUTUMN)

08/06/81-07/31/85

| | | | | | | | | | NIN | SPEED | Œ | | | | | | | | |
|-----------|-------------|--------|-------------|-------------|------|-------------|--------------|-----------------|---------------|-----------------|--------------|---------------|-----------------|---------------|---------------|---------------|-------|---------------|--------|
| | | SAUM | 0.1- 2.0 | 2.1- 4.0 | 4.1- | 6.1- 8.0 | 8.1- 10.0 | 10.1 - 1 12.0 | 12.1- 14.0 | 14,1- 1 16,0 | 18.0 18.0 | .8.1- 20.0 | 20.1- ; 25.0 | 25.1- 30.0 | 30,1- 35,0 | 35.1- 40.0 | >40.0 | | |
| | | | | | | | | NIX | SPEE | | RS/SEC | | | | | • | | AV | A |
| | | | 0.1- | 9. 9 | 1.8- | 2.7- | 3.6 P | 4.5- | 5.4- | 6.3- | 7.2- | 8.1- | 9.0- | 11.2- | 13.5- 1 | 15.7- | | SPEED | SPEED |
| | _ | ₹ 5 | 0.0 | 1.8 | 2.7 | 3.6 | 4.5 | 5.4 | 6.3 | 7.2 | 8°.0 | 6.8 | | 13.4 | | 17.9 | >17.9 | (<u>F</u> E) | M/SEC) |
| | - | 0.0 | 4.7 | 13.7 | 12.0 | 14.0 | 16.0 | 10.0 | 8.0 | 3,3 | 4.7 | 2.7 | 7.0 | 1.3 | 2,3 | 0.3 | 0.0 | 10.4 | 4.7 |
| | ~ | 0.0 | 5.0 | 12.3 | 17.3 | 14.3 | 11.7 | 11.0 | 5.3 | 4.3 | 3.7 | 4.7 | 6.3 | 1.7 | 2.0 | 0.3 | 0.0 | 10.2 | 4.6 |
| | crs · | 0.0 | 3.7 | 11.3 | 15.0 | 16.0 | 12.0 | 13.0 | 5.7 | 6.0 | 3,3 | 4.0 | 5.0 | 3,7 | 0.7 | 0.3 | 0.3 | 10.5 | 4.7 |
| | 4 | 0.0 | 2.3 | 12.7 | 13.0 | 17.3 | 14.7 | 9,3 | დ შ | 4.7 | 4.0 | 4.3 | 5.0 | 2.3 | 2.0 | 0.0 | 0.0 | 10.5 | 4.7 |
| | ഗ | 0 | 4.7 | 0.6 | 11.0 | 18.4 | 14.7 | 13.0 | 6.4 | 4.7 | 5.7 | 3.7 | 4.7 | 2.7 | 1.3 | 0.0 | 0.0 | 10.5 | 4.7 |
| | φ, | 0.0 | 0.9 | 6.7 | 13.1 | 15.4 | 13.8 | 12.4 | 6.7 | 5.0 | 3,4 | 3.0 | 6.7 | 2.3 | 2.0 | 0.0 | 0,3 | 10.5 | 4.7 |
| | _ | 0.0 | 3.7 | 13,1 | 11.4 | 14.1 | 14.1 | 9.4 | 6.0 | 5.4 | 5.7 | 4.0 | 8.7 | 3.4 | 0.7 | 0.0 | 0.3 | 11.0 | 4.9 |
| | œ | 0.0 | 4.7 | 11.1 | 14.1 | 10.7 | 11.7 | 7.4 | 8.1 | 5.7 | 5.7 | 5.7 | 11.7 | 1,3 | 1.7 | 0.0 | 0,3 | 11.5 | 5.2 |
| I | 6 | 0.0 | 4.4 | 12.8 | 11.1 | 10.1 | 7.6 | 7.7 | 7.4 | 6.7 | 6.7 | 6.7 | 10.7 | 3.7 | 2.0 | 0.0 | 0.3 | 12.2 | 5.4 |
| | 2 | 0.0 | 3.7 | ထို | 12,6 | 10.2 | 9.5 | က် | 7.1 | 6.5 | 7.5 | 6.1 | 13.6 | 7.5 | 1.0 | 0.3 | 0.0 | 13.3 | 5,9 |
| 0 | = : | 0.0 | 2.5 | က် | 14.2 | 6,3 | ထ ထ | 7.1 | 9.6 | 6,3 | 6.7 | က် အ | 16.7 | 7.9 | 2.1 | 0.4 | 0.0 | 14.3 | 6.4 |
| | 21 | 0.0 | 2.0 | ່ນ | က် | 9.5 | 7.0 | ထိ | 5.0 | 3.5 | 8 2 | 0.9 | 22.5 | 6,5 | 5.5 | 0.5 | 0.0 | 15.7 | 7.0 |
| - | Ξ: | 0 | 1.7 | 7.3 | 5.7 | 7.7 | 8 0 | 7.3 | 2 | 7.0 | °. | 10.0 | 18.7 | დ შ | 4.3 | 0.7 | 0.0 | 16.0 | 7.1 |
| | Z : | 0.0 | .: :: | 4. W | 7.0 | °. | 8.7 | 8 0 | ω Ο | 6,3 | 8.0 | 6.3 | 21.3 | 6.7 | 5.0 | 1.0 | 0.0 | 16.1 | 7.2 |
| œ | 515 | 0.0 | 0.3 | 3.7 | 7.4 | 7.4 | 10.0 | 9.0 | 7.4 | 7.4 | 7.7 | 7.4 | 22.7 | 6.4 | 3.0 | 0.3 | 0.0 | 15.9 | 7.1 |
| | 91 | 0.0 | 0.3 | 4.0 | φ, | 5.7 | 10.7 | 10.1 | 6.7 | 8.1 | 9.1 | 8.1 | 18.8 | 6.0 | 3.7 | 0.3 | 0.0 | 15.6 | 7.0 |
| | 7: | 0.0 | 2.0 | 4.7 | 6.4 | 10.1 | 9.4 | 7.7 | 10.7 | 7.4 | 7.0 | 10.4 | 17.4 | 4.0 | 2.0 | 0.7 | 0.0 | 14.7 | 9.9 |
| | æ : | 0.0 | 2.7 | 4.4 | 8.7 | 6.4 | 12.8 | 12.4 | 1.6 | 7.4 | 7. | 7.7 | 13.8 | 3.4 | 1.7 | 0.0 | 0.0 | 13.6 | 6.1 |
| | <u>6</u> 18 | 0.0 | 0.0 | 4.4 | 10.1 | , 8 | 13,1 | 15.4 | 11.7 | α • | 0.0 | 6.7 | 7.7 | 2.7 | 1.0 | 0.0 | 0.0 | 12.1 | 5.4 |
| | 22 | 0.0 | 3.7 | 6.1 | တို | 12.2 | 20.1 | 14.3 | 6.8 | 6.8 | 6.1 | 6.1 | 6.5 | 2.0 | 0.7 | 0.0 | 0.0 | 11.4 | 5.1 |
| | ี ส | 0.0 | 2.4 | 11.6 | 10.6 | 10.6 | 13.0 | 18.1 | 9.2 | ນີ້ | 4.4 | ည် | 6.1 | 1.7 | 0.7 | 0,3 | 0.0 | 11.0 | 4.9 |
| | ខ | 0.0 | ທີ່ ເຄື | φ 6. | 13.4 | 11.6 | 14.7 | 17.1 | 5.1 | 4.5 | 5.1 | 2.7 | 7.2 | 2.4 | 1.0 | 0.7 | 0.0 | 10.7 | 4.8 |
| | 23 | 0.0 | 7. 6 | 11.8 | 11.4 | 11.1 | 13.8 | 11.8 | 9°3 | 4.2 | 4.8 | 5.2 | 4.2 | 3,5 | 1.0 | 0.0 | 0.3 | 10.5 | 4.7 |
| | 24 | 0.4 | 7.0 | 11.0 | 10.3 | 13.2 | 17.2 | 9.5 | 7.3 | 3.7 | 4.4 | 3.7 | 8.1 | 1.8 | 2.2 | 0.4 | 0.0 | 10.7 | 4.8 |
| ALL HOURS | ম | 0.0 | 3.6 | 8.7 | 10.9 | 11.3 | 12.4 | 10.7 | 7.5 | 5.8 | 6.1 | 5.7 | 11.1 | 3.8 | 2.0 | 0.3 | 0.1 | 12.4 | 5.5 |
| | | | | | | | | | | | | | | | | | | | |

Table IV - 165

Annual Wind Rose Distribution

WHEATLAND COUNTY - JUDITH GAP

08/06/81-07/31/85

| <direction< th=""><th>(M/SEC)</th><th>AM AM A</th><th>TOTAL / Speed</th><th>(MPH.) SPEED</th><th>SEC)</th></direction<> | (M/SEC) | AM A | TOTAL / Speed | (MPH.) SPEED | SEC) |
|--|-------------|--|--------------------|-----------------|---------|
| | SPEED | 0.1 1.0 1.19 1.19 1.19 1.19 1.19 1.19 1. | A So | A S (₹ | - |
| TOTAL | 0, | | 100.0 | 13.0 | က္ခ |
| N | | 1.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 | 10.5 | 14.4 | 6.4 |
| ₹ | | 0.0000000000000000000000000000000000000 | 7.7 | 9.4 | 4.2 |
| M | | 000000000000000000000000000000000000000 | 9.4 | 11.0 | 4.9 |
| 3 | | 0.0000000000000000000000000000000000000 | 17.3 | 17.8 | 8.0 |
| 3 | | 0.000000000000000000000000000000000000 | 9.4 | 15.4 | 6.9 |
| 35 | | 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0 | 3.6 | 8.7 | 3.9 |
| SS | | 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 | 2.8 | 6.4 | 2.9 |
| S | | 10000000000000000000000000000000000000 | 3.0 | 6.8 | 3.0 |
| SSE | | 10000000000000000000000000000000000000 | ນໍາ | 8.0 | 3.6 |
| 띯 | | 00000000000000000000000000000000000000 | 5.4 | 8.6 | 3,8 |
| ESE | | | 3.0 | 9.0 | 4.0 |
| m | | | 1.2 | 5.9 | 2.6 |
| EN EN | | | 0.9 | 5.0 | 2.2 |
| 뀔 | | | 1.1 | 6,3 | 2.8 |
| ¥ | | | 3.1 | 9.6 | 4,3 |
| z | | 00000000000000000000000000000000000000 | 16.2 | 17.4 | 7.8 |
| DIRECTION> | SPEED (MPH) | H444444446000044 | TOTAL AV SPEFID | (MPH) | (M/SEC) |




Table IV - 166

Coefficients of Weibull Distribution

WHEATLAND COUNTY - JUDITH GAP

08/06/81 - 07/31/85

| SHAPE FACTOR (K) | 1.4136 1.6217 1.5179 1.5106 1.6357 1.6946 1.7580 1.4971 1.4924 | |
|--------------------------------|--|--|
| SCALE FACTOR (C) (M/SEC) | 7.4533 7.6730 6.8146 6.5247 6.6626 5.7149 5.8041 6.3852 7.4103 | |
| MONTH | JANUARY MARCH APRIL MAY JUNE JULY AUGUST SEPTEMBER OCTOBER DECEMBER | |

BILLINGS NWS AIRPORT

YELLOWSTONE COUNTY

The Billings airport is located on the rimrocks in Billings, at 45 48 00 N and 108 31 48 W (Site No. 139 on Map II-1). Elevation at the airport is 3,582 feet. The Yellowstone River Valley, which is about 400-500 feet deep, lies immediately south of the airport. Elsewhere in the area the land consists of rolling plains. The Bull Mountains, which rise to about 4,700 feet, are located about 30 miles to the north. The Pryor Mountains, with summits of nearly 9,000 feet, lie about 30 miles to the south. About 50 miles to the southwest are the Beartooth Mountains, which rise to over 12,000 feet.

Although most of the land in the area is privately owned, sections owned by the state and the federal governments are scattered throughout the area. The Crow Indian Reservation lies nearby to the south and southeast.

Electrical power in the area is provided by the Montana Power Company, Montana-Dakota Utilities, and the Yellowstone Valley Electric Cooperative. Many transmission lines cross the area.

Billings is the major communications and commercial center in the region. The Billings airport is an important air transportation center.

Meteorological data have been collected at this site for many years by the National Weather Service. These data, collected primarily for aviation and weather forecasting uses, consist of short-term (5 minutes or less) averages of wind speed and wind direction, as well as other meteorological parameters. Data were gathered once per hour. The data have been analyzed by Battelle Pacific Northwest Laboratories. Because of changes in reporting interval, the data set was broken into three sections for analysis: January 1, 1948, through June 25, 1958; June 26, 1958, through December 31, 1964; and January 1, 1965, through December 31, 1978. Data from the most recent period only were selected for inclusion in the Montana Wind Energy

The data set for Billings consists of summaries of observations made every third hour from January 1, 1965, through December 31, 1978. The anemometer was mounted on a ground mast at a height of 7.6 meters. The site is representative of a large area of south-central Montana.

Average annual wind speed at the airport was 11.4 miles per hour. Average monthly wind speeds ranged from 9.6 miles per hour in July to 13.4 miles per hour in January.

Average annual wind power was 130.0 watts/m². Average monthly wind power varied from 69.0 watts/m² in August to 211.0 watts/m² in January.

Average seasonal wind speeds were 9.9 miles per hour in summer, 11.3 miles per hour in autumn, 11.4 miles per hour in spring, and 13.2 miles per hour in winter. The highest average wind speeds occurred in mid-afternoon in autumn and winter, and in mid to late afternoon in spring and summer. The lowest average wind speeds occurred around midnight in spring and summer, and during late evening in autumn and winter. The diurnal range of average wind speeds was greatest in summer and least in winter.

The most common wind directions were southwest through west-southwest. Winds from the east-southeast through south-southeast were least common. By direction, average wind speeds varied from 7.2 miles per hour for winds from the south-southeast to 14.3 miles per hour for winds from the west-southwest through west-northwest.




Table IV - 167

Monthly Wind Speed Distribution

YELLOWSTONE COUNTY - BILLINGS NWS AIRPORT

01/01/65 - 12/31/78

| | _ | | s | ۵ | لغا | غا ا | ے ا | 3 | 5 | سا: | | لعان | 0 | S | _ | ຜ | الما | () | _ | _ | _ | | | | | | | | | |
|-------------|----------------|----------------|---|----------|-----|---------|------|----------|-----|--------------|------------|--------------|-------|--|------------|--------------|---------------|---------------|------------|-----|-------------|----------|----------|----------|---------------|--------------|------|-----------|----------|--|
| | 0.5 | | | | | | | | | | | | | | | | | | | | | | -3 | -=+ | _ | . | | | | |
| | | _ | N | ~ | - | ۳. | v | ^ | - α | 0 | 0 | | N | 3 | 7 | 5 | 16 | 7 | 20 | 5 | 20 | 5 | 30. | 35 | 9 | - | | | | |
| | Å | J | S | ٦. | S | ľ | ĸ | 7. | S | , 6 | 5 | L. | S | Š | J | 5 | 5 | 5 | 7 | r, | S | 5 | 5 | 0.5- | Š | ^ | | | | |
| œ | | | | | | | | | | | | _ | - | _ | _ | _ | _ | _ | _ | | _ | N | N | က | m | | | | | |
| YEAR | 1.5 | 0.0 | 6.6 | 6.1 | 0.7 | 6.3 | 2.4 | 5.5 | 7.9 | | 2.6 | 0.9 | 0.5 | 4.0 | 0.1 | 0. | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | - | . | 5.1 | 30.0 |
| r) | | | | | | | | | | | | | | | | | | | | | | | | | | | - | - | | _ |
| DEC | | | | | | | | | | | | | | | | | | | | | | | | | 0.0 | | 2 | • | 5.9 | 0.46 |
| ≥ | 4 | | m | 9 | _ | ۵ | 00 | 0 | m | ī | _ | & | _ | .⇒ | , | _ | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0.0 | 5 | , | _ | _+ | _ |
| NOV | - | 0 | <u>, </u> | # | 17. | 14. | 33 | 10 | 0. | 7 | ω, | 0 | o. | ö | 0 | o. | Ö | 0 | 0 | 0 | 0 | 0 | 0 | 0 | ÷. | ; | 5 | į | 7 | 147.0 |
| OCT | | | | | | | | | | | | | | | | | | | | | | | | | 00 | | - | - | - | |
| 0 | _ | 0 | 9 | 5 | 20 | 16 | 14 | 10 | œ | m | _ | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | O. | ာ်င | Š | 11 4 | - | ς. | 120.0 |
| SEP | 1.0 | 0.0 | 5.3 | 8 | ۲. | 8. ? | 3.0 | 9.0 | 2.5 | 2.2 | 2. | .3 | | .2 | .1 | | 0. | 0.0 | 0 | 0. | 0. | 0. | 0. | 0. | 00 | : | 7 | • | 4.7 | 0.06 |
| | | | | | | | | | | | | | | | | | | | | | | | | | jc | | - | - | 7 | 06 |
| AUG | • | • | ó | αį | ထံ | ά. | ÷. | | | | | • | | | | | | | | | | | | _ | 000 | | ď | | 4.4 | 69.0 |
| ليـ | 0 | 0 | | | | _ | | ï | ιΛ | Δı | S | Λı | | C. | _ | | _ | _ | | _ | | _ | _ | | > C | | ٠,- | | | |
| JUL | | | | | | | | | | | | | | | | | | | | | | | | | 50 | | 0 | • | = | 70.0 |
| N N N | 80 | 0 | 0 | ۲- | _ | _ | m | m | ٥ | 6 | Ŋ | 'n | cy. | رن ا | 0 | 0 | 0 | 0 | 0 | ٠ | 0 | 0 | 0 | 0 (|) | • | ~ | , | 9 | 0 |
| 5 | - | o i | _ | <u>დ</u> | 25 | 6 | 12. | 7 | ⇒. | ÷ | ÷ | o. | Ö | o. | 0 | o, | · | o. | ٠ د | ·. | 0 | 0 | · | 0 | ; c | 5 | 10 | | 4 | 86. |
| MΑΥ | | | | | | | | | | | | | | | | | | | | | | | | | | | 0 | | ٥. | 0. |
| _ | _ | ٠. | • | - | 2 | - 3 | 12 | 0, | 9 | (Y) | _ | 0 | 0 | 0 | Ο, | 0 (| 0 | 0 (| - | O (| 0 | 0 | 0 | 0 (| jc | • | = | | ⇉ | 109. |
| APR | | | | | | | | | | | | | | | | | | | | | | | | | | | 9.1 | • | 5.5 | 34.0 |
| ~ | | | | | | | | | | | | | | | | | | | | | | | | | | | Ξ | 1 | • | 4 |
| MAR | | | | | | | | | | | | | | | | | | | | | | | | | | | 1.6 | | 5.2 | 40.0 |
| <u> </u> | 9 | . , | _ | د د | œ | ٠ د | N | _ | 0 | ∞ . | φ. | ر د | ω, | . 0 | → (| N C | N (| . | 5 6 | 5 (| ٥, | ٥ د | ٠ - | . | 00 | 3 | 0 | | 8 | 0 14 |
| H | • | • | • | <u>.</u> | ₹. | 'n | 'n | • | ò | | | • | | | | • | | | | | | - | - | - | 0 | | 13. | | 2. | 194.(|
| N Y | | | | | | | | | | | | | | | | | | | | | | | | | 0 | | 7 | | 0. | |
| ⇒ | (| ٥١ | ٥ | = ; | ~ | = | Ξ | Ξ | ~ | 0 0 i | יטו | N. | _ (| 0 | 0 | 50 | <u> </u> | o c | Š | Š | ဆ်ဖ | o c | <u>ن</u> | <u> </u> | ċċ | | 33 | | 9 | 211.0 |
| | = | | 4, | ٥ | χ | | ~ | 9 | | 0. | ~ · | ر د ا | - (| 0 0 | N - | 4 1 | - 0 | د د | ų. | , t | 0 | 200 | ٠ • | N = | | | = | | EC) | |
| | \overline{v} | ı | ı | ŧ | ı Ì | 7 | 7 | 7 | 7 | Q I | | N (| 7 | ֓֞֜֜֜֜֜֓֓֓֓֜֜֜֜֓֓֓֓֜֜֜֟֓֓֓֓֓֜֜֜֜֓֓֓֓֜֜֜֡֓֜֡֓֡֡֡֡֓֜֡֓֡֡֡֡֡֡֡֡ |) N | יורב איני | | ν. Ι | 1 I | † - | ત્ર (૧૦ | ν c Γ | 10 | 7 6 | νŏ | ָ הַרָּ | ΣΨ | GE | 4/SE | ************************************** |
| | | • | • | | ٠, | ö | Ň. | ં પ | ۰ | o, | | 'n, | ς, | ò | | v : | ÷. | ė o | × • | ٠, | ກ່. | Ċ٢ | ٠, | 200 | | VFR | E0 . | VER | | WIND POWER WATTS/M**2) |
| | Ö | | (| n | ۱ ح | الد | اليد | ۵ | ; | Σ. | - . | ا لــ | ە ئىد | n > | <u> </u> | = 0 | > : | > c | _ | | | | | | | ٥ | SPE | ⋖ | SPEE | X A A |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | _ |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

7.6 METERS 25.0 FEET = ANEMOMETER HÈIGHT =

BATTELLE PACIFIC NORTHWEST LABORATORIES

SOURCE:

Table IV - 168

Percentage Frequency Summary for Wind Speed

YELLOWSTONE COUNTY - BILLINGS NWS AIRPORT (WINTER)

| | AV SPEED M/SEC) | | | | | | ر بر | 0.9 | 7 | | 6.3 | ۍ. ه | ч. | 0.0 | ر. م | | 5,0 | , |
|---|-----------------------|--------------------------|-------|-------------|-----|-----|----------|------|---|------|------------------|---------|--------------|------|---------|-----|------|--------|
| | ; | AV SPEED S (MPH)(M | | | | | | 13.4 | | | | | | | | | 13.2 | |
| | >14.4 | | | >32.2 | | | | 0.0 | | | | | | | | | C | • |
| | 14.4 | | 30.5- | 32.2 | | | | η.0 | | | | | | | | | | • |
| | 13.4 | | | | | | | 0.0 | | | | | | | | | 7 0 | ; |
| 11,5- | 12.4 | | 25.7- | 27.7 | | | | 0.6 | | | | | | | | | 0 | |
| 10.5- | 11.4 | | 23.5- | 25.5 | | | | 1.1 | | | | | | | | | 1 7 | : |
| WIND SPEED (MPH) - 5.5- 6.5- 7.5- 8.5- 9.5- | 10.4 | | 1.3- | 23.3 | | | | 4.9 | | | | | | | | | ď | |
| | η 6 | EC) | 19.0- | 21.0 | | | | α | | | | | | | | | 0 | |
| | 4.8 | S/W) 0 | 16.8- | 18.8 | | | | 7. | | | | | | | | | ¢ | 7.7 |
| | 7.4 | D SPEE | 14.5- | 16.6 | | | | 12.6 | | | | | | | | | - | † - |
| | 4.9 | Z 3 | 12.3- | 14.3 | | | | 101 | | | | | | | | | | 7 |
| # - | 5.4 | | 10.1- | 12.1 | | | | 7.6 | | | | | | | | | | 7.7 |
| 2.5- 3.5- 4.5- | , 1 | | 7.8- | 9.8 | L T | 7.0 | 14.8 | 0 | | 12.6 | 12.0 | 1 4 | 7.0 | 14.9 | 7 6 1 | 2 | | |
| | 3.4 | | 5.6- | 7.6 | (| 10. | 0 | . α | | 6 | 101 | | 0.0 | 14.2 | | 2.0 | , | |
| • | 2 | | • | 5.4 | | | | | | | | | | | | | ` | 0.0 |
| | \ | | - | 3.1 | , | 0.5 | <u> </u> | • | ; | 0 | | | • • | 0 | | 0.0 | , | |
| | <0.5 | | | <u>~1.1</u> | • | 9 | 1 - | - 0 | 7 | 9 | - | | - | ٥ | | ·: | , | 9. |
| | | | | | | m | V | 0 | , | 7 | - - - | 10 | • | 2 | i č | ± | | HOURS |
| | | | | | | I | ; | (| > | | = | > | | α | = | | | ALL |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

Table IV - 169

Percentage Frequency Summary for Wind Speed

YELLOWSTONE COUNTY - BILLINGS NWS AIRPORT (SPRING)

01/01/65 - 12/31/78

| | | | _ | ເວົ | | | | | | | | | | | | | |
|--------|--|----------|-------|----------------|------|------|--------|--------|--------|----------|---------|--------------|---------------------------------------|------|--------|----------|--------|
| | | | | (M/SEC) | - | • | о + | ر 5 | | ۱ (ا | ν œ | ις O | α | • | 9.7 | Ľ | |
| | | \ | SPFFD | (MPH) | 7 01 | - 6 | ○ | 11.3 | 12 | | 7.9 | 12.9 | 7 | | 10.4 | 14 | † - |
| | >14.4 | • | | >32.2 | 0 | | - 5 | | (C | , | ر. د | 0.5 | - | | 0.0 | 0 | N. |
| | 13.5- | | | | - | | ~ • | 0.5 | ٥ | 1 - | †. O | 0.1 | <u>-</u> | | - 5 | 0 | |
| | 12.5- | | | | | | | | | | | 0.5 | | | | - | ; |
| | 11.5- 12.4 | | | | - | | | 0.3 | 0 | | , | 0.8 | 9.0 | | 7.0 | C | |
| | 10.5- | | 23.5- | 25.5 | | | | | | | | .5 | | | | α | • |
| | 9.5- | | 1.3- | 23.3 | | | | | | | | 3.1 | | | | 0 | 1 |
| Ξ | 8.5- 9.4 | EC) | 19.0- | 21.0 | | | | | | | | 4.9 | | | | 3 | • |
| ED (MP | 7.5- 8.4 | S/W) 0 | 16.8- | 18.8 | 6.2 | 7 | 1 | ? | 9.5 | 0 | 0 1 | 7.11 | 5.0 | , u | ٧. | 7.7 | : |
| NO SPE | 6.5- | D SPEE | 14.5- | 16.6 | 10.1 | α | | 0.3 | 70.5 | 10 | j | 2 | 7.9 | 7 0 | 0 | 10.1 |) |
| 3 | 7.5- 6.5- 7.5- 8.5- 4 6.4 7.4 8.4 9.4 | <u>₹</u> | 12.3- | 14.3 | 11.4 | 13.8 | | - 2 | 10.6 | 15. A | | 14.7 | 10.6 | 11 9 | | 12.4 | |
| | 4.5- 5.4 | | 10.1- | 12.1 | 17.1 | | | | | | | | | | | 16.9 | |
| | 3.5- 4.4 | | 7.8- | 9.8 | 23.2 | 21.4 | | | 19.5 | 16.1 | |) - | 55.6 | 22.0 | , | 20.7 | |
| | 2.5- | , | 5.6- | 7.6 | 16.9 | 16.5 | 16.1 | 0 | 16.5 | 5 | | ر ا د | 8./[| 20 7 | | 16.1 | |
| | 1.5- 2.4 | | | | | | | | | | | | | | | 4.9 | |
| | 0.5- 1.4 | , | | 3.1 | 0.1 | 0.1 | 0 | |)) | 0.1 | | , , | 0.0 | ~ | ; | 0.1 | |
| | <0.5 | | , | - . | 2.2 | 1.8 | , L | | - | 0.5 | | 0, | ٠. | 0 | : | 1.4 | |
| | | | | | 33 | 9 | c | , | 2 | 15 | | 0 ; | \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ | 7 | , | HOURS | |
| | | | | | I | | c | > | | > | | • | ¥ | | | ALL + | |
| | | | | | | | | | | | | | | | | | |

Table IV - 170

Percentage Frequency Summary for Wind Speed

YELLOWSTONE COUNTY - BILLINGS NWS AIRPORT (SUMMER)

01/01/65 - 12/31/78

| | | AV. | L. L. | EC) | 4.1 | 2 | | ٠. | | 80 | 2 | 4 | < | 2 | †. ‡ | |
|---------|--|-------|----------|-------|------|-----|-----|--------|------------|------------|------------|--------|----------|------|-------------|--|
| | | | | | | | | | | | | | | | | |
| | | γ | SPEE | Hd M | 9.1 | 0 | , (| y. | 8. | 10.7 | 11.7 | 6.6 | c | ۷. | 9.9 | |
| | >14.4 | | 1 | >32.2 | 0.0 | 0 | | 0.0 | 0.0 | 0.1 | 0.3 | 0.1 | , | | 0.1 | |
| | 13.5- 14.4 | | 30.2- | | 0.0 | 0 | | 0.0 | 0.1 | 0.0 | 0.0 | 0.0 | 0 | 0.0 | 0.0 | |
| | 12.5- 13.4 | | 28.0- | 30.0 | 0.1 | 0 | | 0.2 | 0.1 | 0.1 | 9.0 | 4.0 | | | 0.2 | |
| | 11.5- 12.4 | | | | 0.0 | - | | 0.1 | 0.0 | 0.5 | 7.0 | 0 | | - | 0.1 | |
| | 10.5- 11.4 | | | | | | | | | | 4.0 | | | | 0.3 | |
| | 9.5- 10.4 | | 21.3- | 23.3 | | | | | | | 2.5 | | | | 0.8 | |
| Î | 8.5- 9.4 | EC) | 19.0- | 21.0 | | | | | | | 8 | | | | ٦.4 | |
| ED (MPI | 7.5- 8.4 | (M/S | 16.8- | 18.8 | 1.7 | | | ۰ د | 4.3 | 7 | 7 | 3 7 | | 2 2 | 3.7 | |
| ID SPEI | 6.5- 7.4 | SPEEI | 14.5- | 16.6 | 4.7 | | | 4.9 | 7.0 | ٦ « | 2 | ر د | | 3.4 | 6.5 | |
| = | 5.5- 6.5- 7.5- 8.5- 1 6.4 7.4 8.4 9.4 | Z 3 | 8.31 | 14.3 | 10.9 | , 0 | 0.0 | 10.2 | 0 | 10 | 7 5 | 0 | | 8.2 | 11.2 | |
| | 4.5- 5.4 | | 10.1- | 12.1 | 19 4 | | 0 | 19.3 | 180 | ٠ <u>-</u> | 0.0 | 0 |) ! ! | 17.6 | 18.8 | |
| | 3.5- | | | | | | | | | | 20.0 | | | | 27.6 | |
| | 2.5- | | -9.6 | 9 / | 0 40 | 10 | 7.0 | 10.4 | 200 | 11 c |) <u>-</u> | - 0 | 2 | 26,2 | 20.7 | |
| | 1.5- | I | 3.4- | 5.4 | α | | v. | 7.3 | 0.7 | - 4 |) =) = | י י | 5 | ₩. | 7.0 | |
| | 0.5- | | -, | 3.1 | - | | 0.0 | 0.0 | | | | | • | 0.1 | 0.0 | |
| | <0.5 | ? | | ۲.۱ | ~ | , | - > | 0 | , - , c | - c | 9.0 |) d | · • | 1.6 | 1.6 | |
| | | | | | ~ | ٠ د | ٥ | 0 | , ? | <u> </u> | <u> </u> | - c | - | 24 | HOURS | |
| | | | | | 7 | = | | C | > | = | > | ٥ | _ | | ALL H | |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

Table IV - 171

Percentage Frequency Summary for Wind Speed

YELLOWSTONE COUNTY - BILLINGS NWS AIRPORT (AUTUMN)

01/01/65 - 12/31/78

| CO.5 1.5- 2.5- 3.5- 4.5- 5.5- 6.5- 7.5- 8.5- 11.5- 11.5- 12.5- 13.5- 13.6- 13.4- 2.4 3.4 4.4 5.4 6.4 7.4 8.4 7.4 8.5 9.4 10.4 11.4 12.4 13.4 14.4 14.4 14.4 14.4 14.4 17.4 8.5 10.1 1.1 3.1 5.4 7.6 9.8 12.1 14.3 16.6 18.8 21.0 23.3 25.5 27.7 30.0 32.2 >32.2 SPEED SPEED (MPSEC) 1.2 3- 14.5- 16.8- 19.0- 21.3- 23.5- 25.7 28.0- 30.2- 8.5 SPEED SPEED 0.2 1.3 0.3 0.3 0.3 0.3 0.3 0.3 0.3 0.3 0.3 0 | | (O) | | | . ~~ | ٠ | ~~ | | |
|--|-----------------------|-------------------------|------------------|------------|----------------|------------|----------------|-------|---------|
| 5- 4.5- 5.5- 6.5- 7.5- 8.5- 9.5- 10.5- 11.5- 12.5- 13.5- 4. 5.4 6.4 7.4 8.4 9.4 10.4 11.4 12.4 13.4 14.4 > 14.4 WIND SPEED (M/SEC) 8- 10.1- 12.3- 14.5- 16.8- 19.0- 21.3- 23.5- 25.7- 28.0- 30.2- 8- 10.1- 12.3- 14.5- 16.8- 19.0- 21.3- 23.5- 25.7- 28.0- 30.2- 8- 10.1- 12.3- 14.5- 16.8- 19.0- 21.3- 23.5- 25.7- 28.0- 30.2- 8- 10.1- 12.3- 14.5- 16.8- 19.0- 21.3- 23.5- 25.7- 28.0- 30.2- 8- 10.1- 12.3- 14.5- 16.8- 19.0- 21.3- 23.5- 25.7- 28.0- 30.2- 8- 10.1- 12.3- 14.5- 16.8- 19.0- 21.3- 23.5- 25.7- 28.0- 30.2- 8- 10.1- 12.3- 14.5- 16.8- 19.0- 21.3- 23.5- 25.7- 28.0- 30.2- 9- 18.6- 17.5- 10.1 7.8 3.6 2.4 0.5 0.2 0.0 0.1 11.9 9- 18.7- 12.6- 10.7- 6.8- 4.0- 1.8- 0.5- 0.2- 0.1- 0.1- 0.1- 0.1- 0.1- 0.1- 0.1- 0.1 | | AV SPE! (M/SI | 7 | י. ייני | Ņ | ייי סיי | 7 | 7. 4 | |
| 5- 4.5- 5.5- 6.5- 7.5- 8.5- 9.5- 10.5- 11.5- 12.5 "H 5.4 6.4 7.4 8.4 9.4 10.4 11.4 12.4 13.5 "B 10.1- 12.3- 14.5- 16.8- 19.0- 21.3- 23.5- 25.7- 28.0 "B 12.1 14.3 16.6 18.8 21.0 23.3 25.5 27.7 30.3 "G 18.6 14.4 9.6 7.5 2.0 1.4 0.4 0.1 0.4 "T 18.7 16.1 11.4 7.4 3.8 1.3 0.3 0.3 0.3 "T 15.5 13.6 9.2 10.5 5.0 2.9 0.7 0.9 "T 15.4 10.3 7.8 6.7 6.1 3.0 1.3 1.3 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 0.5 "T 15.4 10.3 7.8 6.7 3.9 2.0 0.6 0.4 0.3 | | AV SPEE (MPH | 11.0 | 11.3 | 11.9 | 5. 5.5 | 70.5 | 10.6 | |
| 5- 4.5- 5.5- 6.5- 7.5- 8.5- 9.5- 10.5- 11.5- 12.5 "H 5.4 6.4 7.4 8.4 9.4 10.4 11.4 12.4 13.5 "B 10.1- 12.3- 14.5- 16.8- 19.0- 21.3- 23.5- 25.7- 28.0 "B 12.1 14.3 16.6 18.8 21.0 23.3 25.5 27.7 30.3 "G 18.6 14.4 9.6 7.5 2.0 1.4 0.4 0.1 0.4 "T 18.7 16.1 11.4 7.4 3.8 1.3 0.3 0.3 0.3 "T 15.5 13.6 9.2 10.5 5.0 2.9 0.7 0.9 "T 15.4 10.3 7.8 6.7 6.1 3.0 1.3 1.3 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 0.5 "T 15.4 10.3 7.8 6.7 3.9 2.0 0.6 0.4 0.3 | >14.4 | >32.2 | 0.0 | | | 0 C | 0.0 | 0.1 | |
| 5- 4.5- 5.5- 6.5- 7.5- 8.5- 9.5- 10.5- 11.5- 12.5 "H 5.4 6.4 7.4 8.4 9.4 10.4 11.4 12.4 13.5 "B 10.1- 12.3- 14.5- 16.8- 19.0- 21.3- 23.5- 25.7- 28.0 "B 12.1 14.3 16.6 18.8 21.0 23.3 25.5 27.7 30.3 "G 18.6 14.4 9.6 7.5 2.0 1.4 0.4 0.1 0.4 "T 18.7 16.1 11.4 7.4 3.8 1.3 0.3 0.3 0.3 "T 15.5 13.6 9.2 10.5 5.0 2.9 0.7 0.9 "T 15.4 10.3 7.8 6.7 6.1 3.0 1.3 1.3 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 "T 15.4 10.3 7.8 6.7 3.6 1.4 0.5 0.2 0.5 "T 15.4 10.3 7.8 6.7 3.9 2.0 0.6 0.4 0.3 | 13.5- 14.4 | 30.2- | 0.1 | 0.0 | 0.2 | | | 0.0 | |
| 5- 4.5- 5.5- 6.5- 7.5- 8.5- 4 5.4 6.4 7.4 8.4 9.4 WIND SPEED (M/SEC) 8- 10.1- 12.3- 14.5- 16.8- 19.0- 12.1 14.3 16.6 18.8 21.0 7 18.7 16.1 11.4 7.4 3.8 7 15.5 13.6 9.2 10.5 5.0 7 17.2 12.6 10.7 6.8 4.0 1 15.4 10.3 7.8 6.7 3.6 1 15.4 10.3 7.8 6.7 3.6 1 15.4 10.3 7.8 6.7 3.6 1 16.7 13.6 10.0 7.9 3.9 ABORATORIES | 12.5- 13.4 | 28.0- 30.0 | 0.6 | 0.0 | 0.5 | 9.0 | | 0.3 | |
| 5- 4.5- 5.5- 6.5- 7.5- 8.5- 4 5.4 6.4 7.4 8.4 9.4 WIND SPEED (M/SEC) 8- 10.1- 12.3- 14.5- 16.8- 19.0- 12.1 14.3 16.6 18.8 21.0 7 18.7 16.1 11.4 7.4 3.8 7 15.5 13.6 9.2 10.5 5.0 7 17.2 12.6 10.7 6.8 4.0 1 15.4 10.3 7.8 6.7 3.6 1 15.4 10.3 7.8 6.7 3.6 1 15.4 10.3 7.8 6.7 3.6 1 16.7 13.6 10.0 7.9 3.9 ABORATORIES | 11,5- 12.4 | 25.7- 27.7 | 0.1 | 0.0 | 0.9 | - C | 0.5 | 0.4 | |
| 5- 4.5- 5.5- 6.5- 7.5- 8.5- 4 5.4 6.4 7.4 8.4 9.4 WIND SPEED (M/SEC) 8- 10.1- 12.3- 14.5- 16.8- 19.0- 12.1 14.3 16.6 18.8 21.0 7 18.7 16.1 11.4 7.4 3.8 7 15.5 13.6 9.2 10.5 5.0 7 17.2 12.6 10.7 6.8 4.0 1 15.4 10.3 7.8 6.7 3.6 1 15.4 10.3 7.8 6.7 3.6 1 15.4 10.3 7.8 6.7 3.6 1 16.7 13.6 10.0 7.9 3.9 ABORATORIES | 10.5- 11.4 | 23.5- 25.5 | 4.0 | 000 | 7.0 | - O | 000 | 0.6 | |
| 5- 4.5- 5.5- 6.5- 7.5- 8.5- 4 5.4 6.4 7.4 8.4 9.4 WIND SPEED (M/SEC) 8- 10.1- 12.3- 14.5- 16.8- 19.0- 12.1 14.3 16.6 18.8 21.0 7 18.7 16.1 11.4 7.4 3.8 7 15.5 13.6 9.2 10.5 5.0 7 17.2 12.6 10.7 6.8 4.0 1 15.4 10.3 7.8 6.7 3.6 1 15.4 10.3 7.8 6.7 3.6 1 15.4 10.3 7.8 6.7 3.6 1 16.7 13.6 10.0 7.9 3.9 ABORATORIES | 9.5- | 21.3- | 4. | 2.4 | 6.6 | ٠ <u>-</u> | - - | 2.0 | |
| 5- 4.5- 8- 10.1- 18- 10.1- 18- 17.1- 19- 18- 18- 18- 18- 18- 18- 18- 18- 18- 18 | H) 8.5- 9.4 | 2.0 2.0 1.0 | 2.0 | 9.0 | 0.0 | - 0. | 90 | 3.9 | |
| 5- 4.5- 8- 10.1- 18- 10.1- 18- 17.1- 19- 18- 18- 18- 18- 18- 18- 18- 18- 18- 18 | ED (MP 7.5- 8.4 | D (M/S 16.8- 18.8 | | 7.8 | 10.5 | - 8.9 | 6.7 | 7.9 | |
| 5- 4.5- 8- 10.1- 18- 10.1- 18- 17.1- 19- 18- 18- 18- 18- 18- 18- 18- 18- 18- 18 | ND SPE 6.5- 7.4 | H 1 10 | 9.6 | 10.1 | 9.5 | 10.7 | 7.8 | 10.0 | |
| 5- 4.5- 8- 10.1- 8- 10.1- 6- 18.6 7- 18.7 7- 15.5 7- 17.2 7- 17.2 7 | WI 5.5- 6.4 | 12.3- 14.3 | 14.4 | 17.5 | 13.6 | 12.6 | 10.3 | | S |
| CO.5 1.5- 2.5- 3.5- 3.5- (1.1 3.1 3.4 5.6- 7.8- (1.1 3.1 5.4 7.6 9.8 1.2 0.0 5.3 14.3 19.7 0 9 1.0 0.1 6.6 11.3 19.7 0 15 0.6 0.1 6.4 14.8 16.8 1.2 0.6 0.1 6.4 14.8 16.8 1.2 0.0 6.5 15.2 22.7 R 21 1.5 0.0 6.5 15.2 22.7 R 21 1.5 0.0 7.1 19.9 20.8 ALL HOURS 1.2 0.0 6.6 16.2 20.4 SOURCE: BATTELLE PACIFIC NORTHWEST LABOR | 4.5- 5.4 | | 18.6 | 16.6 | 15.5 | 17.2 | 15.4 | 16.7 | RATORIE |
| CO.5 1.5 2.5 - 2.5 - 3.4 3.4 1.1 3.1 3.4 5.6 - 4.1 3.1 5.4 7.6 - 6.0 6.5 15.6 6 1.2 0.0 6.5 15.6 0.0 6.5 15.6 0.0 6.5 15.6 0.0 6.5 15.2 0.0 0.0 6.5 15.2 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0 | 3.5- | 7.8- 9.8 | 21.6 | 19.9 | 7.8 | 22.7 | 23.1 20.8 | | r LABOF |
| CO.5 1.5- CO.5 1.4 2.4 CO.5 1.4 2.4 CO.5 1.1 3.1 5.4 CO.6 0.0 6.5 CO.6 0.0 6.5 CO.6 0.1 6.4 CO.7 1.5 0.0 6.5 CO.8 0.1 7.4 CO.8 0.1 6.4 CO.8 0.1 6.5 CO.8 0.5 CO.8 0.5 | 2.5- | 5.6- | 15.6 | 13.7 | 17.0 | 15.2 | 22.2 19.9 | 16.2 | THWES' |
| <0.5- <0.5- 1.1- <1.1 3.1 <1.1 3.1 <0.0 0 <0.0 | 1.5- | 3.4- 5.4 | 0 0 0 0 | 9.9 | † † | 6.5 | 7:1 | 9.9 | FIC NO |
| <0.5 + 3 1.6 0 9 1.0 0 9 1.0 12 0.8 0 15 0.6 1 15 0.6 21 1.5 24 1.8 ALL HOURS 1.2 SOURCE: BATTELLE | 0.5- | 3.1 | 0.0 | -00 | | 0.0 | 00 | | PACI |
| H 3 6 0 9 12 15 U 15 R 21 ALL HOURS | <0.5 | <u>۲</u> | 1.6 | 0.0 | 0.0 | 1.2 | v & | 1.2 | ATTELL |
| H O U R ALL P | | | ღფ | φţ | <u> </u> | 18 | 24 | HOURS | SE: B/ |
| | | | I | 0 | ¬ | ć | r | ALL | SOUR |

285

Table IV - 172

Annual Wind Rose Distribution

YELLOWSTONE COUNTY - BILLINGS NWS AIRPORT

01/01/65 - 12/31/78

| _ (0) | ONOCHO CERTETE |
|---|---|
| CTION (M/SEC) | |
| TOTAL <direction SPEED (M/SE</direction | AV SPD |
| IL <c< td=""><td>00000000000000000000000000000000000000</td></c<> | 00000000000000000000000000000000000000 |
| T0T | 000000000000000000000000000000000000000 |
| N N N | 00000000000000000000000000000000000000 |
| ₹ | 00000000000000000000000000000000000000 |
| NA NA | 00000000000000000000000000000000000000 |
| 3 | 00.00000000000000000000000000000000000 |
| MSM | 000 NNNN00000000000 |
| MS | 000-mmmn-000000000000000000000000000000 |
| MSS | 000-01-00000000000000000000000000000000 |
| S | 0000000000000000000000000000000000000 |
| SSE | 00000000000000000000000000000000000000 |
| SE | 000000000000000000000000000000000000000 |
| ESE | |
| ш | 00000000000000000000000000000000000000 |
| ENE | 0000000000000000000000000000000000000 |
| N E | 000011100000000000000000000000000000000 |
| N N M | 0000000000000000000000000000000000 |
| z | +04 00000000000000000000000000000000000 |
| ON> | \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\ |
| DIRECTION> | 7.7-7-7-7-7-7-7-7-7-7-7-7-7-7-7-7-7-7-7 |
| DI | SS よりられれれるをもらなるでででしょしょしん< |
| | NEMPO E-JMN/TOJR A4 |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES




Table IV - 173

Coefficients of Weibull Distribution

YELLOWSTONE COUNTY - BILLINGS NWS AIRPORT

01/01/65 - 12/31/78

| MONTH JANUARY FEBRUARY | SCALE FACTOR (C) (M/SEC) 7.7220 7.3980 | SHAPE FACTOR (K) 2.9830 3.1830 |
|--|--|--|
| APRIL MAY JUNE JULY AUGUST SEPTEMBER OCTOBER | 7.5060 6.0330 5.6440 5.4440 5.4340 5.8100 | 2.7540 2.7540 2.3900 2.4310 2.4890 |
| NOVEMBER DECEMBER YEAR | 6.1590 | 3.0810 3.0810 2.4710 |

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

CUSTER FAA AIRPORT

YELLOWSTONE COUNTY

The Custer airport is located about 1 mile northeast of Custer at 46 09 00 N and 107 31 00 W (Site No. 142 on Map II-1). Elevation at the airport site is 2,880 feet. Meteorological data were collected at this site for a short time in the late 1940s and early 1950s by the Federal Aviation Administration.

These data, collected primarily for aviation and weather forecasting uses, consist of short-term (5 minutes or less) averages of wind speed and wind direction, as well as other meteorological parameters. Data were gathered once per hour. The data have been analyzed by Battelle Pacific Northwest Laboratories. Because of a change in anemometer height, the data set was broken into two parts for analysis: January 1, 1948, through May 31, 1949; and June 1, 1949, through May 30, 1950. Only data from the latter of the two periods were selected for inclusion in the *Montana Wind Energy Atlas*.

The data set for Custer consists of summaries derived from hourly observations made from June 1, 1949, through May 30, 1950. The anemometer was mounted on a rooftop at a height of 10.1 meters.

Average monthly wind speeds at the site varied from 7.6 miles per hour in August to 10.5 miles per hour in April. Average annual wind speed was 8.7 miles per hour.

Average monthly wind power ranged from 49.0 watts/m² in August to 137.0 watts/m² in April. Average annual wind power was 79.0 watts/m².




Table IV - 174

Monthly Wind Speed Distribution

YELLOWSTONE COUNTY - CUSTER FAA AIRPORT

06/01/49 - 05/30/50

| | 5) | S | اے | الد | ى د | 2 | 3 | E 14 | ı - | ш | <u>م</u> | · v | · ~ | . U | 1 | Ç | 0 | 2 | : 0 |) | | | | | | | | | |
|------------------|-------------------------|-------------|---------|----------|---------|----------|----------|----------------|-------------|---------|----------|----------|----------------|----------|----------|----------|----------|-----------|-----------|-----------|-----------|-----------|-----------|------------------|---------|-------------|--------------------------|---------|-------------------------|
| | 0>1 | 2 | જ | # : | ٠ - | † = | t = | † | 7 | 7. | 4 | 77. | 7 | 4 | 7 | 7.4 | 7 | | - 1 | 4 | = | | 1= | ; - + | | | | | |
| | Σ.: | ٦. | Ļ. | <u>.</u> | £ . | וַ וַ | Ļ | | Ţ | Ξ | Ξ | Ţ | 1 | ī | Ţ | Ţ | 7 | <u>.</u> | | , | ĭ | " | 7 | 7 | | | | | |
| œ | გ. | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| YEAR | 3.9 | N | | ń (| | | | | | | | | | | | | | | | | | | | | | 8.7 | | 2 | 79.0 |
| DEC | 3.9 | | | | | | | | | | | | | | | | | | | | | | | | | 8.7 | 6 | , , | 74.0 |
| NOV | 1.8 | ., | 9.6 | 7 - | J ~ | 7.7 | . 6 | 0,0 | 1.2 | | 1.2 | 9.0 | 0 | 0.1 | 0.1 | ٠. | 0.3 | 7.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 7.6 | - | 4.5 | 125.0 |
| OCT | 5.2 | o i | | i c | j. | | | | | | | | | | | | | | | | | | | | | 9.8 | 4 | | 108.0 |
| SEP | 6.3 | 5 | | ی د | ١.4 | | | | | | | | | | | | | | | | | | | | | 7.8 | ч. ц | • | 62.0 10 |
| AUG | 3.5 | | | | | | | | | | | | | | | | | | | | | | | | | 7.6 | - | · | 9 0.64 |
| JUL | 3.2 | ع. ا | , o | , « |) — | | ≠ | 0 | m, | _ | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 8.1 | ٧ « | | 63.0 |
| N C C N | 1.7 | | | | | | | | | | | | | | | | | | | | | | | | | 8.7 | 0 | ; | 70.0 |
| MAY | 7.7 | | | | | | | | | | | | | | | | | | | | | | | | | 8.9 | 0.4 | · | 68.0 |
| APR | 4.0 | ٠ | - 1- | - | . بن | - | 9 | ∞. | 0,0 | Ŋ | φ, | œ, | - - | 9 | 0 | 0 | 0 | _ | 0 | 0 | 0 | 0 | 0 | 0 | | 10.5 | 4.7 | : | 37.0 |
| MAR | 4.3 | | | | · ~ | | | | | | | | | | | | | | | | | | | | | 5.6 | 1,1 | | 87.0 13 |
| FEB | 7.3 | 23.7 | | | | • | • | • | | | ٠ | • | | • | • | | • | • | | | - | - | | - | | 7.8 | 3.5 | | 52.0 (|
| JAN | 50.0 | 21.4 | ว่า | 'n | Š | ή· † | 5.6 | 7.0 | ۍ د د | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 8.1 | 3.6 | | 53.0 |
| | CALM (<1.1) 1.1- 3.1 | х г г | 7.8-9.8 | 10.1-12 | 12.3-14 | 14.5-16. | 16.8-18 | 19.0-21 | 21.3-23 | 72-7-67 | 72-1-57 | 28.0-30. | 30.2-32. | 32.4-34. | 34.7-36. | 30.9-38. | 39.1-41. | 41.4-43.4 | 43.6-45.6 | 45.9-56.8 | 0.89-0.75 | 68.2-79.2 | 19.4-90.4 | h.06< | AVERAGE | SPEED (MPH) | AVERAGE SPEED (M/SEC) | AVERAGE | WIND POWER (WATTS/M**2) |

ANEMOMETER HEIGHT = 33.0 FEET = 10.1 METERS

SOURCE: BATTELLE PACIFIC NORTHWEST LABORATORIES

LAUREL NEW FARM

YELLOWSTONE COUNTY


The Laurel New Farm site is located about 2 miles east of Laurel at 45 40 07 N and 108 44 25 W (Site No. 145 on Map II-1). Elevation at the site is 3,270 feet. The site was established by the Montana Air Quality Bureau to measure concentrations of particulates and sulfur dioxide.

Wind data collected during the period from November 13, 1980, through May 17, 1982, were available for analysis. The data set contains hourly averages of wind speed and wind direction recorded by a data acquisition system that scanned each parameter several times per minute. The measurement device was a Climatronics electronic anemometer and wind vane on a 10-meter tower.

Winds were monitored long enough to adequately represent the wind resource at the location. Because the site sits on a level valley floor, the data are representative of the immediate area only. Data recovery ranged from 25.7 percent in August to 99.8 percent in February and April. Overall data recovery was 81.9 percent.

Average annual wind speed at the site was 7.8 miles per hour. Average monthly wind speeds ranged from 4.3 miles per hour in August to 9.5 miles per hour in February.

Average annual wind power was 63.6 watts/m². Average monthly wind power values ranged from 8.6 watts/m² in September to 96.0 watts/m² in February.



DNOCES/SEPA

Table IV - 175

Monthly Wind Speed Distribution YELLOWSTONE COUNTY - LAUREL NEW FARM

11/13/80 - 05/17/82

| AV JUN JUL AUG SEP OCT NOV DEC 1.9 0.3 0.3 2.6 1.6 1.4 1.5 1.7 3.9 15.7 7.3 23.1 13.5 11.0 16.5 15.2 20.5 10.5 7.0 7.2 4.9 10.7 15.5 17.3 23.1 13.5 11.3 8.6 10.5 7.0 7.2 10.3 7.6 10.5 10.5 17.3 23.1 13.5 11.3 8.6 10.5 10.5 7.0 7.6 10.5 10.5 10.5 7.0 7.6 10.5 10.5 10.5 7.0 7.6 10.5 10.5 10.5 7.0 7.6 10.5 10.5 10.5 7.0 7.6 10.5 10.5 10.5 7.0 7.6 10.5 10.5 10.5 7.0 7.6 10.5 10.5 10.5 10.5 7.0 7.6 10.5 10.5 10.5 7.0 6.6 6.6 6.6 6.6 6.6 6.6 6.6 6.6 6.6 6 | | | | | - 07 (07) | ±002 | _ | | |
|--|--|-------|-----------------|--|---|--|---|-----------------------------------|---|
| CALM OLD | | 4 LM | 00 m | 2-1-1-0 6-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1 | - - - - - - - - - - - - - - - - - - - | | 6- 8. 0-11. 3-13. 5-15. 7-17. | | |
| JAN FEB MAR APR MAY JUN JUL AUG SEP OCT NOV DEC CALM 0.0 0.1 0.0 0.0 0.0 0.0 0.5 0.4 2.4 0.1 2.5 1.1-2.0 6.3 2.8 4.9 2.6 6.5 0.9 0.3 0.3 2.6 1.6 1.4 1.5 4.7 1.1 0.5 0.9 0.9 0.0 0.0 0.5 0.4 2.4 0.1 2.5 1.1 0.3 2.8 4.9 2.6 6.5 0.9 0.3 0.3 2.6 1.6 1.4 1.5 4.7 1.1 0.5 0.9 0.3 0.3 2.6 1.6 1.4 1.5 1.2 0.9 1.7 1.3 1.3 1.3 1.3 1.3 1.3 1.3 1.3 1.3 1.3 | YEAR | 99-0 | ەبئىــ ماس م | 982- | بأواشغاه | v∞r-, | -89-00 | • | 63.6 81.9 |
| CALM 0.0 0.1 0.0 0.1 0.1 0.0 0.0 0.0 0.5 0.4 2.4 1.1-2.0 6.3 2.9 1.1 0.5 6.9 0.3 3.9 15.7 2.3 1.3 1.3 1.3 1.3 1.3 1.3 1.3 1.3 1.3 1 | DEC | | | | | | | 8.3 | |
| CALM 0.0 0.1 0.0 0.1 0.0 0.0 0.5 0.4 2 0.1 1.1 0.5 0.9 0.3 0.3 0.3 0.3 1.5 1.6 1.6 1.6 1.2 0.9 0.3 0.3 0.3 0.3 0.3 1.5 1.6 1.6 1.6 1.2 0.0 0.9 0.3 0.3 0.3 0.3 0.3 1.5 1.6 1.6 1.6 1.5 1.6 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 | NOV | 1.5 | 5.2.2.0 | 5.70 | w 0 0 m = 0 | | - m 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 | • • | |
| CALM 0.0 0.1 0.0 0.1 0.1 0.0 0.0 0.0 0.5 0 1.1-1.0 1.8 0.9 1.1 0.5 0.9 0.3 0.3 2.6 1 1.1-2.0 6.3 7.8 1.9 7.7 11.9 10.7 12.2 20 2.1-3.0 9.3 7.5 11.7 7.7 11.9 10.7 12.2 20 3.1-4.0 8.1 7.0 11.3 8.1 8.7 11.0 16.5 15.2 20 5.1-6.0 6.0 6.0 7.8 7.7 8.6 10.4 7.2 10.3 7.3 8.7 10.4 10.5 10.5 10.5 10.5 10.5 10.5 10.5 10.5 | OCT | | | | | | | | |
| CALM 0.0 0.1 0.0 0.1 0.0 0.0 0.1 0.1 0.0 0.0 | SEP | 0-0% | 0000 | | | | | 4.4 | 8.6 |
| JAN FEB MAR APR MAY JUN | AUG | 0050 | 7697 | | | | | | |
| CALM 0.0 0.1 0.0 0.1 0.0 0.1 0.0 0.1 0.1 0.1 | JUL | | | | | | | | 20.4 52.0 |
| JAN FEB MAR APR M O.1-1.0 1.1-2.0 S. 2.1-3.0 S. 2.1-3.0 S. 2.1-3.0 S. 2.1-3.0 S. 2.1-4.0 D. 3.1-4.0 D. 3.1-4.0 A.1-5.0 A.1-15.0 | NOC | | | | | | | 7.8 | 59.3 46.5 |
| JAN FEB MAR CALM 0.0 0.1 0.0 1.1-2.0 6.3 2.8 4.9 3.2-1-3.0 9.3 7.6 11.2 E 4.1-5.0 7.8 7.6 11.2 D 5.1-6.0 6.0 6.0 7.3 M 8.1-9.0 7.2 7.2 8.3 M 8.1-9.0 7.2 7.2 8.3 I 9.1-10.0 5.9 5.1 4.2 I 10.1-11.0 4.9 7.0 6.2 I 10.1-12.0 4.0 4.4 4.1 S 12.1-13.0 4.1 6.3 5.1 I 11.1-15.0 4.1 6.3 5.1 I 11.1-15.0 4.1 6.3 5.1 I 11.1-15.0 4.1 6.3 5.1 AVERAGE PEED (MPH) 8.1 9.5 7.6 AVERAGE WAIND POWER WAIND POWER WAIND POWER WAIND POWER RECOVERY 76.2 99.8 95.8 95.8 | MAY | | 8000 | | | | | 7.1 | 47.9 88.6 |
| CALM 0.0 0.1 0.1 1.8 0.9 1.1 1.2.0 6.3 2.8 4.2 3.1 1.4.0 8.1 7.0 111 | APR | | | | | | | | |
| CAEM 0.0 0 0 0 0 1 - 1 0 0 0 0 0 0 1 - 1 0 0 0 0 | | | | | | | | 7.6 | |
| CAEM 0 1-1.0 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | <u>. </u> | 0001 | ~~. | v. v | , 0 = W.W. | ~~~ | m-000 | | 9 6 |
| S 2 11.7 P 3 1-1.1 C 10.1-1.1 C 10.1 C 10.1-1.1 C 10.1-1.1 C 10.1-1.1 C 10.1-1.1 C 10.1-1.1 C 10.1-1.1 C 10.1-1.1 C | JAN | 0-06 | 8000 | いたらうら | 4440 | | -0000 | 3.6 | 64.6 |
| | | 0 + 0 | | 8.1-5 9.1-10 10.1-11 | 13.1-14 | 16.1-17 17.1-18 18.1-19 19.1-20 | 7.35 | SPEED (MP AVERAGE PEED (M/S | AVERAGE WIND POWER WATTS/M**2 ERCENT DAT RECOVERY |

ANEMOMETER HEIGHT = 10 METERS = 33 FEET NUMBER OF OBSERVATIONS = 10830 PERCENTAGE DATA RECOVERY = 81.9

SOURCE: GEORESEARCH, INC.

SHAWNEE PARK

YELLOWSTONE COUNTY

The Shawnee Park air monitoring site is located in a residential area approximately 6 miles northeast of downtown Billings at 45 49 28 N and 108 23 56 W (Site No. 149 on Map II-1) near the intersection of Interstate 94 and Interstate 90. Elevation at the park is 3,123 feet. The site was established by the Montana Air Quality Bureau to measure concentrations of ozone and sulfur dioxide in the area.

Wind data have been collected at the site since January 22, 1981. Data through April 30, 1982, were available for analysis. The data set contains hourly averages for wind speed and direction manually reduced from stripchart records. The wind measuring instrument was a Meteorology Research, Inc., mechanical recording anemometer and wind vane set on the monitoring trailer roof 4 meters above ground level.

Winds were monitored long enough to adequately represent the wind resource at the location. Data recovery was greater than 80 percent, except during March and from August through October. Overall data recovery was 74.2 percent. Since the site is located in a residential area on the Yellowstone Valley floor, the data are representative only of the immediate area.

Average annual wind speed was 5.9 miles per hour. Average monthly wind speeds varied from 4.5 miles per hour in August to 7.1 miles per hour in April.

Average monthly wind power ranged from 8.9 watts/m² in September to 45.4 watts/m² in April. Average annual wind power was 28.2 watts/m².




Table IV - 176

Monthly Wind Speed Distribution

YELLOWSTONE COUNTY - SHAWNEE PARK

01/22/81 - 04/30/82

| JAN FEB MAR APR MAY JUN JUL AUG SEP OCT NOV DEC Y 1.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 | |
|--|--------------------------|
| JAN FEB MAR APR MAY JUN JUL AUG SEP OCT NOV 1.5 0.6 0.5 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 | 28.2 |
| JAN FEB MAR APR MAY JUN JUL AUG SEP OCT 1.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 | 27.1 93.0 |
| JAN FEB MAR APR MAY JUN JUL AUG SEP OF 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0. | 14.1 |
| JAN FEB MAR APR MAY JUN JUL AUG 1.0 0.8 0.5 0.0 0.0 0.0 0.0 0.0 0.0 1.0 0.8 8.1 5.9 7.8 6.8 5.4 11.7 1.1 10.4 10.1 14.8 14.0 21.3 15.1 12.9 1.0 10.6 8.3 8.7 15.9 12.3 15.1 12.9 12.3 15.1 10.4 10.1 14.8 14.0 21.3 15.1 12.9 2.0 5.4 7.9 5.9 6.9 7.3 6.4 8.6 6.7 3.0 2.9 7.5 4.7 5.8 5.9 6.1 6.5 4.0 3.0 2.9 2.8 1.7 3.6 1.3 1.8 0.8 1.0 3.0 2.9 2.8 1.7 3.6 1.3 1.8 0.8 1.0 3.0 2.9 2.8 1.7 3.6 1.3 1.8 0.8 1.0 3.0 2.9 2.8 1.7 2.8 1.1 1.1 0.2 3.0 2.9 2.8 1.7 2.8 1.3 1.8 0.0 3.0 0.0 0.0 0.0 0.0 0.0 0.0 3.0 0.0 0.0 0.0 0.0 0.0 0.0 3.0 0.0 0.0 0.0 0.0 0.0 0.0 3.0 2.5 3.2 2.5 2.7 2.3 2.0 3.0 2.5 3.2 2.5 2.7 2.3 2.0 3.0 2.5 3.2 2.5 2.7 2.3 2.0 | 31.1 |
| JAN FEB MAR APR MAY JUN JUL 1.5 0.6 0.0 0.2 0.0 0.0 0.0 0.0 10.0 6.3 8.1 5.9 7.8 6.8 5.4 1 10.1 10.1 11.7 10.4 10.1 14.8 14.0 21.3 1 10.8 8.7 5.9 6.9 7.3 6.4 8.6 1 10.8 8.7 5.9 6.9 7.3 6.4 8.6 1 10.8 8.6 8.7 5.7 7.1 5.7 6.0 5.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0 | 30.6 |
| JAN FEB MAR APR MAY JUN JUN 1.5 0.6 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 | 9.0 54.2 |
| JAN FEB MAR APR MAY JIN 1.5 0.6 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 | 64.3 |
| JAN FEB MAR APR MAR AP | 99.9 |
| JAN FEB MAR AL 1.5 0.6 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 | 100.0 |
| LAN FEB M. 1.5 O. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. | 99.1 |
| AN 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | - 60 |
| Z0000000000000000000000000000000000000 | 9 |
| | 90.1 |
| CANCACE SPEED O.1-1-2 B.3-1-4-4 D.3-1-4-4 B.1-1-1-1 C.1-7-1-8 C.1-7-1-8 C.1-7-1-8 C.1-7-1-8 C.1-7-1-8 C.1-7-1-8 AVERAGE WAITS (MPH) AVERAGE WATS (MPH) WATS (MPH) WATS (MPH) SPEED WATS (MPH) | PERCENT DATA RECOVERY |

NAMED WHITE DESCRIPTION

ANEMOMETER HEIGHT # 4 METERS = 13 FEET NUMBER OF OBSERVATIONS = 8266
PERCENTAGE DATA RECOVERY = 74.2

SOURCE: GEORESEARCH, INC.

Power Law Analyses

Power Law Analyses in General

Wind speed data are available in most cases for only one anemometer height - generally 10 meters above ground level. Since wind speed normally increases with height above the ground, and since most wind energy generation systems have hub heights of more than 10 meters, some means of estimating the wind speed at heights other than the measurement height is needed.

The two most common methods of estimating wind speed at hub height from measurements at a reference level are (1) to assume a logarithmic wind profile, and (2) to assume a power law. The empirically derived power law is used more often. although the logarithmic law is theoretically more sound since it is based on the principles of fluid mechanics.

To derive an expression for the logarithmic wind profile, Businger et al. (1971) and others have assumed that the variation of wind speed with height can be treated as a function of stability and surface roughness only. Drawbacks to the use of the logarithmic wind profile are the difficulties in measuring the friction velocity and the stability parameter.

Most investigators, therefore, have used a power law wind profile instead of the logarithmic profile. The power law is expressed as:

$$U_2 = U_1 \left(\frac{Z_2}{Z_1} \right)^{\alpha}$$

where:

 U_2 = wind speed at height Z_2 ;

 $U_1 = \text{wind speed at height } Z_1$;

 Z_2 = computed height; Z_1 = reference height; α = power law exponent.

The power law exponent (α) is a function of surface roughness and stability. Empirical studies have found that an α value of 0.14 (1/7) best fits most sites. This method, therefore, is often referred to as the "one-seventh" power law.

Power Law Analyses of Montana Wind Data

GeoResearch, Inc., has performed power law analyses of wind data available from sites where monitoring was conducted at several heights. The purpose of these analyses was to compare application of the one-seventh law to use of the calculated power law exponent.

One year of data from the Livingston Candidate Wind Turbine site and 18 months of data from the Montana Power Company Salem site were analyzed. In addition, previously analyzed data from the Old West Regional Commission's monitoring site at Glasgow Air Force Base were examined and compared to the Livingston and Salem data.

The power law analyses involved calculating the power law exponent for each hour by means of the following equation:

$$\alpha = \frac{\log \left(\frac{U_{up}}{U_{low}}\right)}{\log \left(\frac{Z_{up}}{Z_{low}}\right)}$$

where:

 α = power law exponent;

log = base 10 logarithm;

U = wind speed; Z = anemometer height.

"Up" and "low" refer to the upper and lower anemometer heights, respectively.

The power law exponents were calculated for two different air layers: lowest to middle, and lowest to highest anemometer heights. Once all exponents were calculated, the monthly and yearly arithmetic mean and standard deviation of all values for each hour were computed as follows:

$$\bar{\alpha} = \frac{1}{n} \sum_{i=1}^{n} \alpha_i$$

$$\sigma = \sqrt{\frac{\sum_{i=1}^{n} \alpha_i^2 - \frac{1}{n} \left(\sum_{i=1}^{n} \alpha_i\right)^2}{n-1}}$$

where:

 $\bar{\alpha}$ = mean of α values;

 σ = standard deviation;

 $n = number of \alpha values.$

Results of the analyses are listed in Tables V-1 through V-4. As a consequence of the great variation in wind speed over any given period, the standard deviations are quite large. Though not included in these tables, additional calculations

showed that the average α values were highest during the nighttime hours and lowest during the afternoon for all months. This relationship was most pronounced during the summer.

An examination of the tables indicates that, at the Salem site, average monthly α values for the 10- to 30-meter anemometer heights ranged from 0.08 in December to 0.16 in July and November. The annual average value was 0.14. For the 10- to 100- meter heights, average monthly values of α ranged from 0.09 in December to 0.19 in November, with an annual average of 0.14.

At the Livingston site, average monthly α values for the 9.1 - to 30.0 - meter heights ranged from 0.07 in May to 0.39 in February. The annual average α value was 0.13. For the 9.1- to 45.7-meter heights, monthly average α values varied from 0.12 in December to 0.35 in February, with an annual average of 0.18.

Data from a wind monitoring site at Glasgow Air Force Base were previously analyzed to determine variation of wind speed with height by Pasquill stability category and by wind direction. Results of these analyses indicate average α values of about 0.10 for neutral and unstable conditions,

Table V-1
Power Law Exponents (Monthly Average)
Montana Power Company Salem Site
5/1/80 - 10/31/81

| Month | Alpha 10.0-30.0m | Sigma 10.0-30.0m | Alpha 10.0-100.0m | Sigma 10.0-100.0m |
|-----------|---------------------|---------------------|----------------------|----------------------|
| January | 0.12 | 0.22 | 0.18 | 0.21 |
| February | 0.14 | 0.15 | 0.16 | 0.14 |
| March | 0.12 | 0.24 | 0.13 | 0.19 |
| April | 0.14 | 0.15 | 0.14 | 0.16 |
| May | 0.13 | 0.19 | 0.12 | 0.16 |
| June | 0.15 | 0.17 | 0.16 | 0.14 |
| July | 0.16 | 0.33 | 0.15 | 0.21 |
| August | 0.13 | 0.19 | 0.12 | 0.17 |
| September | 0.13 | 0.19 | 0.13 | 0.18 |
| October | 0.15 | 0.24 | 0.17 | 0.19 |
| November | 0.16 | 0.17 | 0.19 | 0.16 |
| December | 0.08 | 0.25 | 0.09 | 0.17 |
| Year | 0.14 | 0.22 | 0.14 | 0.18 |

and from about 0.23 to 0.40 during stable conditions. Thus, applying the one-seventh law under unstable and neutral conditions would result in an overestimation of wind speeds aloft. Under stable conditions, however, the one-seventh law would underestimate actual wind speeds aloft. In

general, stable and neutral conditions primarily occur during the period shortly before sunset until shortly after sunrise. Unstable conditions are more likely during the summer than in the winter.

The effect of using actual monthly power law exponents instead of the one-seventh exponent is

Table V-2
Power Law Exponents (Annual Average)
Montana Power Company Salem Site
5/1/80 - 10/31/81

| Hour of Day | Alpha 10-30m | Sigma 10-30m | Alpha 10-100m | Sigma 10-100m |
|-------------|-----------------|-----------------|------------------|------------------|
| 1 | 0.17 | 0.30 | 0.18 | 0.23 |
| 2 | 0.17 | 0.32 | 0.18 | 0.22 |
| 3 | 0.17 | 0.31 | 0.18 | 0.23 |
| 4 | 0.17 | 0.27 | 0.18 | 0.23 |
| 5 6 | 0.17 | 0.23 | 0.19 | 0.19 |
| | 0.16 | 0.21 | 0.17 | 0.20 |
| 7 | 0.17 | 0.27 | 0.18 | 0.20 |
| 8 | 0.16 | 0.22 | 0.20 | 0.19 |
| 9 | 0.13 | 0.23 | 0.17 | 0.18 |
| 10 | 0.11 | 0.21 | 0.14 | 0.15 |
| 11 | 0.10 | 0.16 | 0.10 | 0.15 |
| 12 | 0.08 | 0.16 | 0.09 | 0.12 |
| 13 | 0.06 | 0.16 | 0.07 | 0.11 |
| 14 | 0.07 | 0.14 | 0.08 | 0.10 |
| 15 | 0.08 | 0.11 | 0.08 | 0.09 |
| 16 | 0.09 | 0.11 | 0.08 | 0.07 |
| 17 | 0.10 | 0.12 | 0.09 | 0.10 |
| 18 | 0.11 | 0.13 | 0.10 | 0.13 |
| 19 | 0.12 | 0.14 | 0.11 | 0.14 |
| 20 | 0.15 | 0.17 | 0.14 | 0.15 |
| 21 | 0.17 | 0.19 | 0.17 | 0.16 |
| 22 | 0.19 | 0.23 | 0.19 | 0.20 |
| 23 | 0.17 | 0.26 | 0.18 | 0.19 |
| 24 | 0.19 | 0.26 | 0.19 | 0.21 |
| All Hours | 0.14 | 0.22 | 0.14 | 0.18 |

shown for the Salem Site and the Livingston Candidate Wind Turbine Site in Tables V-5 through V-8. In these tables, the monthly averages of the measured wind speed readings at each anemometer height are given, together with the wind speed at that level computed from the actual

average wind speed measured at the lowest height. Two power law exponents were used: the actual average power law exponent calculated from the data, and the one-seventh power law.

Use of the actual power law exponent and the one-seventh power law produced about the same

Table V-3
Power Law Exponents (Monthly Average)
Livingston Candidate Wind Turbine Site
9/1/80 - 6/30/82

| | Alpha | Sigma | Alpha | Sigma |
|-----------|-----------|-----------|-----------|-----------|
| Month | 9.1-30.0m | 9.1-30.0m | 9.1-45.7m | 9.1-45.7m |
| January | 0.12 | 0.10 | 0.13 | 0.14 |
| February | 0.39 | 0.59 | 0.35 | 0.45 |
| March | 0.15 | 0.22 | 0.14 | 0.12 |
| April | 0.11 | 0.09 | 0.15 | 0.12 |
| May | 0.07 | 0.11 | 0.19 | 0.12 |
| June | 0.13 | 0.10 | 0.18 | 0.12 |
| July | 0.12 | 0.11 | 0.20 | 0.14 |
| August | 0.13 | 0.13 | 0.23 | 0.16 |
| September | 0.11 | 0.11 | 0.17 | 0.15 |
| October | 0.12 | 0.09 | 0.15 | 0.15 |
| November | 0.10 | 0.11 | 0.13 | 0.12 |
| December | 0.10 | 0.06 | 0.12 | 0.08 |
| Year | 0.13 | 0.21 | 0.18 | 0.19 |

level of accuracy. (See Tables V-9 and V-10.) The major exception was in February; however, the collected data at the lower height could be inac-

curate. The one-seventh power law tended to be somewhat more accurate over longer than shorter periods.

Table V-4
Power Law Exponents (Annual Average)
Livingston Candidate Wind Turbine Site
9/1/80 - 6/30/82

| Hour of Day | Alpha 9.1-30.0m | Sigma 9.1-30.0m | Alpha 9.1-45.7m | Sigma 9.1-45.7m |
|-------------|--------------------|--------------------|--------------------|--------------------|
| 1 | 0.16 | 0.20 | 0.20 | 0.19 |
| 2 | 0.15 | 0.21 | 0.20 | 0.19 |
| 3 | 0.15 | 0.20 | 0.19 | 0.19 |
| 4 | 0.15 | 0.21 | 0.19 | 0.20 |
| 5 | 0.14 | 0.22 | 0.18 | 0.21 |
| 6 | 0.15 | 0.21 | 0.19 | 0.21 |
| 7 | 0.14 | 0.22 | 0.18 | 0.21 |
| 8 | 0.15 | 0.21 | 0.18 | 0.19 |
| 9 | 0.12 | 0.21 | 0.17 | 0.19 |
| 10 | 0.12 | 0.25 | 0.15 | 0.17 |
| 11 | 0.09 | 0.16 | 0.14 | 0.14 |
| 12 | 0.11 | 0.25 | 0.15 | 0.20 |
| 13 | 0.11 | 0.23 | 0.15 | 0.19 |
| 14 | 0.10 | 0.23 | 0.14 | 0.18 |
| 15 | 0.11 | 0.20 | 0.14 | 0.16 |
| 16 | 0.11 | 0.22 | 0.15 | 0.18 |
| 17 | 0.12 | 0.19 | 0.15 | 0.16 |
| 18 | 0.12 | 0.17 | 0.16 | 0.15 |
| 19 | 0.13 | 0.15 | 0.17 | 0.14 |
| 20 | 0.15 | 0.18 | 0.19 | 0.16 |
| 21 | 0.16 | 0.20 | 0.20 | 0.18 |
| 22 | 0.15 | 0.21 | 0.20 | 0.19 |
| 23 | 0.17 | 0.22 | 0.21 | 0.20 |
| 24 | 0.17 | 0.22 | 0.21 | 0.20 |
| All Hours | 0.13 | 0.21 | 0.18 | 0.19 |

Table V-5
Actual vs Calculated Wind Speeds
Montana Power Company Salem Site - 30 Meters
(miles per hour)

| Month | Actual | Actual Exponent | 1/7 Power Law |
|-----------|--------|--------------------|------------------|
| January | 9.4 | 9.1 | 9.4 |
| February | 16.1 | 16.1 | 16.1 |
| March | 9.6 | 9.8 | 10.1 |
| April | 15.0 | 15.2 | 15.2 |
| May | 10.2 | 10.0 | 10.2 |
| June | 12.0 | 11.9 | 11.8 |
| July | 10.7 | 10.7 | 10.5 |
| August | 9.1 | 9.0 | 9.1 |
| September | 11.4 | 11.3 | 11.5 |
| October | 12.9 | 12.9 | 12.8 |
| November | 16.2 | 16.2 | 15.9 |
| December | 16.3 | 15.6 | 16.7 |
| Year | 11.9 | 11.9 | 11.9 |

Table V-6
Actual vs Calculated Wind Speed
Montana Power Company Salem Site - 100 Meters
(miles per hour)

| Month | Actual | Actual Exponent | 1/7 Power Law |
|-----------|--------|--------------------|------------------|
| January | 12.7 | 12.1 | 11.1 |
| February | 20.3 | 19.9 | 19.2 |
| March | 12.1 | 11.6 | 11.9 |
| April | 18.1 | 17.9 | 18.1 |
| May | 11.8 | 11.5 | 12.1 |
| June | 14.6 | 14.6 | 14.0 |
| July | 12.7 | 12.7 | 12.5 |
| August | 10.7 | 10.3 | 10.8 |
| September | 13.8 | 13.2 | 13.6 |
| October | 16.4 | 16.1 | 15.1 |
| November | 20.8 | 21.1 | 18.9 |
| December | 17.5 | 17.6 | 19.9 |
| Year | 14.5 | 14.1 | 14.2 |

Table V-7
Actual vs Calculated Wind Speeds
Livingston Candidate Wind Turbine Site - 30 Meters
(miles per hour)

| Month | Actual | Actual Exponent | 1/7 Power Law |
|-----------|--------|--------------------|------------------|
| January | 20.0 | 20.4 | 21.0 |
| February | 25.4 | 33.0 | 24.5 |
| March | 19.2 | 15.1 | 14.9 |
| April | 16,7 | 16.9 | 17.5 |
| May | 12.1 | 12.0 | 13.0 |
| June | 13.6 | 13.8 | 14.0 |
| July | 13.8 | 12.7 | 14.1 |
| August | 11.1 | 11.1 | 11.3 |
| September | 13.0 | 12.9 | 13.4 |
| October | 17.3 | 17.4 | 17.9 |
| November | 22.4 | 21.7 | 22.9 |
| December | 26.2 | 26.3 | 27.6 |
| Year | 18.1 | 18.2 | 18.5 |

Table V-8
Actual vs Calculated Wind Speeds
Livingston Candidate Wind Turbine Site - 45.7 Meters
(miles per hour)

| Month | Actual | Actual Exponent | 1/7 Power Law |
|-----------|--------|--------------------|------------------|
| January | 22.7 | 21.8 | 22.3 |
| February | 26.5 | 36.4 | 26.1 |
| March | 20.5 | 15.8 | 15.9 |
| April | 18.2 | 18.9 | 18.6 |
| May | 14.4 | 14.9 | 13.9 |
| June | 15.3 | 15.8 | 14.9 |
| July | 15.7 | 16.4 | 15.0 |
| August | 13.2 | 13.8 | 12.0 |
| September | 14.7 | 14.9 | 14.2 |
| October | 19.0 | 19.2 | 19.0 |
| November | 22.8 | 23.8 | 24.3 |
| December | 27.4 | 28.3 | 29.3 |
| Year | 19.5 | 20.9 | 19.6 |

Table V-9
Accuracy of Power Law Exponents
Montana Power Company Salem Site
(Percentage Difference From Actual Speed)

| | 30 N | l eters | 100] | 100 Meters | | |
|-----------|--------------------|------------------|--------------------|------------------|--|--|
| Month | Actual Exponent | 1/7 Power Law | Actual Exponent | 1/7 Power Law | | |
| January | -3 | مبن <u>ت</u> | -5 | -13 | | |
| February | _ | _ | -2 | -5 | | |
| March | 2 | 5 | -4 | -2 | | |
| April | 1 | 1 | -1 | _ | | |
| May | -2 | | -3 | 3 | | |
| June | -1 | -2 | _ | -4 | | |
| July | _ | -2 | _ | -2 | | |
| August | -1 | _ | -4 | 1 | | |
| September | -1 | 1 | -4 | -1 | | |
| October | - | -1 | -2 | -8 | | |
| November | | -2 | 1 | -9 | | |
| December | -4 | 2 | 1 | 14 | | |
| Year | _ | _ | -3 | -2 | | |

Table V-10
Accuracy of Power Law Exponents
Livingston Candidate Wind Turbine Site
(Percentage Difference From Actual Speed)

| | 30 N | 30 Meters | | Meters |
|-----------|----------|-----------|----------|-----------|
| | Actual | 1/7 Power | Actual | 1/7 Power |
| Month | Exponent | Law | Exponent | Law |
| January | 2 | 5 | -4 | -2 |
| February | 30 | -4 | 37 | -2 |
| March | -21 | -22 | -23 | -22 |
| April | 1 | 5 | 4 | 2 |
| May | -1 | 7 | 3 | -3 |
| June | 1 | 3 | 3 | -3 |
| July | -1 | 2 | 4 | -4 |
| August | | 2 | 5 | -9 |
| September | -1 | 3 | 1 | -3 |
| October | 1 | 3 | 1 | _ |
| November | -3 | 2 | 4 | 7 |
| December | _ | 5 | 3 | 7 |
| Year | 1 | 2 | 7 | 1 |

Appendix A

WIND MEASUREMENT IN GENERAL

The quality of wind data depends on the monitoring device selected, how the instrument is sited, how accurately it is calibrated, and how well it is maintained. The methods used to screen the raw data, as well as the methods used to assess the data once in edited form, also contribute to the quality of the final data.

Wind Measurement Devices

Many types of wind-measuring systems are commercially available. Most are ruggedly constructed, designed for a wide variety of applications, and require little attention for operation and maintenance. Such devices have been used for many years to measure winds in Montana.

The most common types of wind monitoring devices are anemometers, wind vanes, and combination wind sensors.

Anemometers measure wind speed. Commercially available anemometers operate on a variety of physical principles. Rotational cup and propeller anemometers are the most commonly used wind speed sensors. More esoteric designs generally are used only for very specialized studies.

Wind direction sensors, commonly called "wind vanes," operate by wind exerting pressure on a surface that rotates about a fulcrum. Although the standard vane measures only the horizontal wind direction, the bi-directional vane is free to move not only horizontally but also vertically (plus or minus 50 degrees or more from the horizontal). The shape and design of the vane surface will vary with the manufacturer.

Two types of sensors combine both wind speed and wind direction measuring capabilities into a single mechanical device. The propeller-vane sensor measures two-dimensional flow; the propellerbivane sensor measures three-dimensional flow. Simple trigonometry is used with these wind component anemometers to determine wind speed and direction.

Varieties of these wind measuring instruments and their operational principles are presented in Table A-1.

Site Location

The most important siting considerations are anemometer height and spacing in relation to obstructions. The meteorological variables measured by the anemometer obviously are affected by large-scale surface features.

The effect of cities has been studied extensively. Documented effects include a decrease in average wind speed, a decrease in atmospheric stability, an increase in turbulence, an increase in temperature, and changes in precipitation patterns. These changes, of course, will affect the evaluation and interpretation of meteorological and air quality data collected in an urban area.

The effects of mountains and valleys on wind continue to be studied. Well-known effects include the channeling of flow up or down a valley, the creation of drainage flow, the establishment of lee-waves, and an increase in turbulence generated by friction.

The important point is that almost any physical object has an effect on the wind. In fact, it is difficult to find a site that is completely free of obstructions. This being the case, the choice of a site for collecting meteorological data that will be most representative of an area must be made with a complete understanding of the meteorological parameters being investigated, the large-scale geographic area, the vertical structure of the atmosphere, and the potential uses of the data.

Once a location is chosen, the characteristics of

Table A-1

Types of Wind Sensors and Their Operational Principles

| Physical Principle | Wind Sensor Type | Measurement |
|-----------------------|---------------------------|--|
| Rotation | Cups | Horizontal speed |
| | Vane-oriented Propeller | Horizontal speed |
| | Bivane-oriented Propeller | |
| | Fixed Propeller | Three-dimensional components on perpendicular axes |
| Pressure | Plate | Horizontal speed |
| | Tube | Horizontal speed |
| | Bridled cups | Horizontal speed |
| Cooling | Hot wire | Directional flow component |
| • | Hot thermopile | Directional flow component |
| | Hot film | Directional flow component |
| Sound | Sonic | Directional flow component |
| Vortex-shedding | Vane-oriented shape | Horizontal speed |
| Ion-flow | Transport | Horizontal speed |

the site should be completely documented. This should include complete site descriptions, topographic maps, photographs of the site, and a description of the area that is adequately represented by the site. Attention to this last point is very important, for it will allow a more rational interpretation of the data by subsequent investigators. The documentation might state, for example, that a site adequately represents a certain section of a particular valley, the urban part of a given city, or several rural counties. The nature and purpose of the site, in any event, should be clearly described to assist those who may use the data.

Instrument Calibration

Wind sensors should be calibrated when they are installed and every six months thereafter. Calibration also is required after the sensors are repaired. The user's manual accompanying the measurement device generally will specify the calibration methods to be followed. Most systems will require a DC voltage input which represents some output value. In other cases, they may re-

quire a frequency to represent some output value. Many systems have a built-in calibration unit to test part of the system.

Wind vanes must be oriented to true north when installed. This orientation must be checked at least once every six months. In addition, the sensors must be set so that they are absolutely vertical.

Instrument Maintenance

A sound, preventive maintenance program for the sensors also should be established. The equipment should be checked for potential problems at least once a month. The manufacturer's recommendations for maintenance and parts replacement also should be followed.

Data Screening

Once data are collected, they should be reviewed to screen out possible incorrect data points before they are put into accessible storage or passed on to the users. While the purpose of a quality assurance program is to avoid generating

bad data, it is impossible to do so completely. Even in the best planned and best conducted programs, undetected errors can be generated by faulty equipment, noisy data transmission lines, faulty key punching, and a myriad of other causes. In both automatic and manual data screening, the most obvious checks should be performed first. These checks should include making sure that the data actually exist and are properly identified, and that forms and files are filled out properly.

Methods of editing or screening meteorological data usually involve comparing the measured values with an expected value or range of values. Techniques for checking the measured values usually fall into one or more of the following categories:

- Comparison with upper and/or lower limits on the allowed range of data;
- Comparison with known statistical distributions of the data;
- Comparison with spatial and/or temporal data fields;
- Comparison based on known physical relationships.

If data do not pass a validation procedure, the screener has two basic choices: (1) to eliminate the questionable data from the file; or (2) to flag it for further examination. Automatically discarding data is a feasible option if the screening procedure is carefully designed and each datum is not of high value. Records must be kept of all discarded data, so that the reason for the fault may later be found and corrected. With flagged data, the screener must examine the data and decide whether they are acceptable for use. If data are deemed unacceptable, it may be possible to correct them. If any values are corrected, this should be noted in the data file. Alternatively, data of questionable value may be kept in the data file under a flagged status, with a notation of why they are thought to be questionable. The user can then decide whether he or she wants to use these data. The collecting agency, however, typically is in the best position to make a decision on the validity of the data.

Data Interpretation

To assess the wind energy potential of an area, it often is necessary to evaluate data collected by different agencies, at different times, using different methods. When comparing data sets, the most important factors to consider are:

• The periods of time during which the data

were collected;

- The locations of the monitoring sites;
- The anemometer heights;
- The methods used to collect and analyze the data;
- The averaging periods of the data;
- The quality assurance procedures followed.

The period of time represented by the data is important because wind speed and direction vary from year to year. Ideally, at least five years of data should be available to characterize the long-term wind climatology of an area. When comparing data from different sites, it is best if the data are for the same period of time; otherwise, the comparison may be biased due to the interannual variability of the wind.

It is important to know the physical characteristics of a site because of the strong influence that topography has on wind direction and speed. Knowledge of an area's topography and possible obstructions to air flow is useful in determining the wind regimes that influence an area (see Chapter III).

Anemometer height is of critical importance when comparing wind data from different sites because wind speed usually increases with height. If different sites have different anemometer heights, it may be useful to adjust the wind speed values to a standard reference height by means of the one-seventh power law. Power laws, however, give only an approximation of wind speed variation with height, not actual values (see Chapter V).

The methods used to collect and analyze the data also should be known when comparing data from different sites. Computerized data acquisition systems, which measure wind speed and wind direction every few seconds, generally give more accurate results than manual reduction of data from stripchart records.

To compare wind data sets, the data averaging time also must be known. Most data sets represent one-hour averages of wind speed and direction, although some monitoring studies gather and organize data differently, with averaging times of seconds or minutes. Users must be particularly cautious when a data point representing a period of only a few minutes is said to represent a complete hour.

Finally, the quality assurance procedures followed should be examined. Of particular importance are the methods and frequency of equipment calibration and the detection and treatment of erroneous data values.

Appendix B

METHODOLOGY

Data Collection

GeoResearch, Inc., developed the *Montana Wind Energy Atlas* by assembling, at the outset, a comprehensive wind data base. This data base is the most complete of its kind existing for Montana. Major data sets obtained include those from the following sources:

- The Montana Air Quality Bureau (AQB) maintains a large data file, which includes wind speed and wind direction data, as well as data for many other meteorological and air quality parameters. Most of the data were gathered by the AQB as part of studies conducted to measure air quality in Montana. Some of the data were collected by private companies and submitted to the AQB to comply with air quality permit regulations.
- The Bureau of Reclamation (BOR), U.S. Department of the Interior, operated five wind monitoring sites in Montana as part of its Northern Great Plains Wind Energy Study. These data were obtained for use in preparing the Montana Wind Energy Atlas. BOR later reduced data from the sites run by the Montana Department of Natural Resources and Conservation (DNRC).
- The National Climatic Center (NCC) in Asheville, North Carolina, provided wind data gathered by the National Weather Service (NWS), the Federal Aviation Administration (FAA), and the United States Air Force (USAF). These agencies have collected wind speed and wind direction data at airports for many years. The data are collected primarily for aviation and weather forecasting purposes. Wind speed and wind direction data are collected each hour and disseminated over a nationwide data gathering system. These data are intended to represent a mean value of wind speed and wind

direction during the minute preceding the observation.

- The Battelle Pacific Northwest Laboratory, under a contract with the U.S. Department of Energy, obtained the NWS, FAA, and USAF data from the National Climatic Center and analyzed these data. Selected Battelle analyses were used in preparing the Montana Wind Energy Atlas. Battelle Pacific Northwest Laboratory also provided one year of wind monitoring data from the Livingston Candidate Wind Turbine site. The Livingston data include hourly wind speed and wind direction averages at 10.0, 30.0, and 45.7 meters above ground level. These data have been analyzed and included as part of the Montana Wind Energy Atlas.
- The Montana Power Company provided 18 months of data from their Salem site. The Salem data include hourly wind speed and wind direction averages at 10.0, 30.0, and 100.0 meters above ground level. These data also have been analyzed and included as part of the Montana Wind Energy Atlas.
- The Bonneville Power Administration (BPA) provided hourly data on three sites in their Wind Regional Energy Assessment Program (REAP). These data are in the data base at the Wind Resources Assessment Laboratory, Oregon State University.

In addition to these data, available in machinereadable form, a considerable amount of useful data was obtained in hard copy from other sources.

Data from these previous monitoring efforts were examined and evaluated. When the data files were examined, data from some sites were found to contain a significant number of errors. If a site was located in an area of low potential and other monitoring sites were nearby, data from that site were not analyzed. If no sites were nearby, the data set was screened and efforts were made to

delete invalid data. If after this a significant amount of the data remained suspect, the data from the site were not analyzed.

Preliminary analyses were conducted, when feasible, for all sites with a solid data set. Detailed analyses then were performed for all sites that indicated a high wind potential. These various analyses are discussed below.

Data Analyses

Several types of wind analyses were performed for all sites except those previously analyzed by Battelle. For those sites, the Battelle analysis simply was reproduced. The extent of the analysis for a particular site depended on whether the site was considered "high potential." For purposes of this Atlas, a site was defined as "high potential" if the average annual wind speed at that site was equal to or greater than 11 miles per hour.

An initial screening analysis was performed by computer on all sites for which at least one year of wind speed data was available. The result of this screening was a table showing a percentage frequency distribution of wind speed by month and a similar annual distribution. The analysis also provided information on average monthly and average annual wind speed and power.

To perform the analysis, each hourly wind speed value was evaluated and a running total of the variable representing the appropriate wind speed class was maintained. After all wind speed values had been read, the percentage frequencies of each wind speed class for all 13 periods (monthly plus annual) were computed by dividing the count for the class by the total number of readings for the period and multiplying the result by 100.

This computer program also calculated average monthly and average annual wind speeds by summing the individual wind speeds and dividing this sum by the total number of readings. To obtain the average monthly and average annual wind power values, the sum of the wind speed cubed was obtained from the data file. Once these monthly sums were obtained, the average wind speed cubed was calculated by dividing this sum by the number of observations. The average wind power was then calculated from:

$$P = 1/2 p V^3$$

where:

P = average wind power (watts/m²);

 $\rho = \text{air density (kg/m}^3) = 0.3488 \text{ (station)}$ pressure (mb))/(station temperature (K));

 $\overline{\mathbf{V}}^3$ = average wind speed cubed.

Since temperature and pressure at the monitoring sites were not available for this analysis, average values were used. For pressure, the value used was computed from:

$$P = P_0 (1-0.0226z)^{5.25}$$

where:

P = station pressure;

P_O = standard sea-level pressure; z = station elevation (km).

For temperature, average statewide values for each month were used. Table B-1 lists the pressure values for each site, while Table B-2 shows the temperature values for each month. (The Battelle analysis, since it was limited to NWS, FAA, and USAF weather stations, was able to use actual temperature and pressure data.)

Finally, anemometer height, the total number of valid observations, and the percentage of data recovery were presented for each site.

For the Livingston Candidate and Salem sites, where the wind speed actually was measured at higher levels, average wind speed and wind power were calculated using the same method used for the 10-meter tables. In addition, for these sites actual power law exponents were calculated for comparison with the one-seventh power law. Methodology and results of these power law analyses are presented in Chapter V.

Once the preliminary screening analysis was complete, the tables were examined to determine those sites to be further analyzed as high potential sites.

The first analysis performed for the high potential sites was the calculation of percentage frequency distributions of wind speed by hour and by season. In these tables, accompanying the discussion of these sites (Chapter IV), hourly periods are listed according to the time (Mountain Standard Time) at which the given period ended (e.g., hour 1 represents the time period 0001 - 0100, etc.). The four seasons are defined as:

- Winter December, January, and February
- Spring March, April, and May
- Summer June, July, and August
- Autumn September, October, and November

To analyze these distributions, a wind speed class was computed, and a running total was kept of the variable representing that class, hour, and season. In addition, the sum of wind speeds for each hour and season was computed. Once all wind speed values for a site had been read, the percentage frequencies for each wind speed class,

Table B-1 Sites Analyzed for the Montana Wind Energy Atlas Average Station Pressure (millibars)

| County | Site | Pressure |
|--------------|-----------------------------------|----------|
| Big Horn | Decker Coal #8 | 892 |
| | Spring Creek #1 | 880 |
| | Westmoreland Absaloka #2 | 890 |
| Broadwater | Three Forks | 859 |
| Cascade | Salem | 898 |
| Chouteau | Highwood Bench | 905 |
| Daniels | Scobey Border | 926 |
| | SCOBEY HANRAHAN | 915 |
| Dawson | GLENDIVE MICROWAVE | 921 |
| Deer Lodge | ANACONDA C-HILL | 776 |
| | Anaconda Highway Junction | 840 |
| | Anaconda Mill Creek | 837 |
| | ANACONDA WEATHER HILL | 800 |
| Flathead | Big Prairie | 888 |
| | Columbia Falls Water Supply | 904 |
| Glacier | CUT BANK | 888 |
| Jefferson | Microwave Tower | 863 |
| Lake | Ronan Nine Pipes | 907 |
| Missoula | Missoula Hoerner-Waldorf #1 | 903 |
| | Missoula University of Montana | 901 |
| Park | LIVINGSTON CANDIDATE WIND TURBINE | |
| | SITE | 834 |
| Powder River | Broadus Randall Ranch | 904 |
| Rosebud | COLSTRIP BN | 900 |
| | Western Energy #12 | 891 |
| Silver Bow | Butte Hebgen Park | 827 |
| Teton | Choteau | 852 |
| Valley | Fort Peck | 931 |
| Wheatland | JUDITH GAP | 852 |
| Yellowstone | Laurel New Farm | 901 |
| | Shawnee Park | 904 |
| | | |

NOTE: Capitalized site names indicate high potential sites.

Table B-2 Sites Analyzed for the Montana Wind Energy Atlas Monthly and Annual Average Temperature (degrees Kelvin)

| January | 264 | | | July | 293 |
|----------|-----|------|-----|-----------|-----|
| February | 268 | | | August | 292 |
| March | 272 | | | September | 287 |
| April | 276 | | | October | 281 |
| May | 283 | | | November | 276 |
| June | 287 | | | December | 268 |
| | | Year | 280 | | |

hour, and season were computed, and the average wind speed for each hour and season was calculated. A frequency distribution and an average speed for all hours also were calculated.

A second analysis performed for high potential sites was the calculation of an annual joint frequency distribution of wind speed and wind direction (the wind rose distribution). To perform the analysis, matching wind speed and direction values were read from the data file. A wind speed class and a wind direction class were calculated, and running totals of variables representing different wind speed and direction categories were kept. After all data had been read, percentage frequencies of each category were computed by dividing the count for each class by the total count.

A measured wind speed distribution, such as those provided in this Atlas, may be approximated by an analytical distribution such as the Rayleigh distribution:

$$p(V) = \frac{\pi V}{2\overline{V}^2} \exp \left[\frac{-\pi V^2}{4\overline{V}^2} \right]$$

where:

p(V) = probability density of wind speed (fraction per m/sec);

V = wind speed;

 \overline{V} = long term average wind speed.

The Rayleigh distribution is a special case of the Weibull distribution. This more complicated distribution, in many cases, provides a better approximation of the measured wind speed distribution. The Weibull distribution is given by:

$$p(V) = \left(\frac{k}{c}\right) \left(\frac{V}{c}\right)^{k-1} \exp \left\{-\left(\frac{V}{c}\right)^{k}\right\}$$

where:

p(V) = probability density of wind speed (fraction per m/sec)

c = scale factor related to the mean wind speed (\overline{V}) by

 $\frac{1}{V} = c \Gamma(1+1/k), \text{ where:}$ $\Gamma = \text{the gamma function, } \Gamma(n) = (n-1)!, \text{ and}$

k = shape factor related to the variance of wind speed (σ_v^2) by

 $\sigma_v^2 = c^2 \{\Gamma(1+2/k) - [\Gamma(1+1/k)]\}^2$

For the high potential sites in this Atlas, the Weibull parameters c and k have been calculated from the monthly wind speed distributions by means of a least-squares fit to the observed distribution. This method requires that wind speed categories be of equal size. The data files from which the percentage frequency for wind speed categories was obtained, however, contain wind speed categories of unequal size: one mile per hour increments between 0 and 20 miles per hour; five mile per hour increments between 20 and 40 miles per hour; and a final category of wind speeds exceeding 40 miles per hour. For wind speeds between 20 and 40 miles per hour, therefore, the wind speed frequency for each five mile per hour increment was divided by five, assuming an equal distribution over that increment. For wind speeds greater than 40 miles per hour, the category was assumed to be centered on 42.5 miles per hour.

The method of differential corrections was used to fit values of c and k to the observed wind speed frequency distribution derived from the data file. This is an iterative method in which the values of the Weibull probability density function and its derivatives with respect to c and k are computed from an initial guess of c and k. From these values, corrections are computed and added to c and k. The process is repeated several times until accurate values of c and k are obtained.

These Weibull coefficients are useful primarily for meteorological modeling purposes.

Site Selection

Analyzed sites were selected for inclusion in Chapter IV of the Atlas according to the following criteria:

- All high potential sites (e.g., those with average annual wind speeds greater than or equal to 11 miles per hour) were included;
- In general, sites with less wind potential also were included when one year's data or more were available, except that in areas with many sites, such as Missoula and Anaconda, one or two representative sites were selected to characterize the wind potential in the area;
- · Sites with low data completeness generally were not included. If a more complete data set for the area was not available, however, a site with low data completeness was included, with caveats, based on the assumption that some data for the area are better than none.

Sites not included in Chapter IV of the Atlas, either for lack of a solid data set for analysis or for the reasons outlined above, are discussed briefly in Appendix C.

Appendix C

ADDITIONAL WIND MONITORING SITES

The comprehensive wind data base from which the Atlas was prepared covers 158 wind monitoring sites in Montana. Of these sites, 56 were selected for detailed analysis in the Montana Wind Energy Atlas, according to criteria discussed in Appendix B.

Appendix C briefly discusses the other sites, by monitoring agency.

Montana Air Quality Bureau

Table C-1 lists additional wind monitoring sites operated by the Montana Air Quality Bureau or by private entities reporting data to the bureau. In most cases, less than one year's data are available for these sites. In a few cases, the data are no

longer on file with AQB, and in a few others, the data are available only in hard-copy form.

NWS/FAA/USAF

Most of the data sets for the NWS/FAA/USAF sites have been split into two or more time periods for analysis. This was done due to a change in anemometer height or a change in reporting period. If analyses for more than one monitoring period were available, the longest period, typically the most recent as well, was selected for inclusion in Chapter IV. Those analyses not presented in Chapter IV are listed in Table C-2. In addition, no data summaries are presented for the Havre and Glasgow NWS city offices since, in both cases, a more representative airport site is located nearby.

Table C-1
Additional Montana Air Quality Bureau Wind Monitoring Sites

| Site No. | Site | County | Reason For Exclusion From Atlas |
|--|---|---|--|
| 3 4 12 | Hardin Hardin MDN Great Falls City | Big Horn Big Horn | Data in hard copy only Data in hard copy only |
| 13 16 22 26 28 30 32 34 35 | Sewage Pump Great Falls Kiwanis Park Portage Scobey Richardson Anaconda #2 Pond Discharge Anaconda County Airport Anaconda Lincoln School Anaconda Water Office Anaconda West Gate Antelope | Cascade Cascade Cascade Daniels Deer Lodge Deer Lodge Deer Lodge Deer Lodge Deer Lodge Deer Lodge | Data no longer on file Less than one year's data Data no longer on file Less than one year's data Other representative site Other representative site Other representative site Other representative site Less than one year's data Data no longer on file |

Table C-1
Additional Montana Air Quality Bureau Wind Monitoring Sites (cont'd.)

| Site No. | Site | County | Reason for Exclusion from Atlas |
|-------------|--------------------------|---------------|---------------------------------|
| 36 | Kucera | Deer Lodge | Data no longer on file |
| 37 | Opportunity Main Street | Deer Lodge | Data no longer on file |
| 38 | Poor Farm | Deer Lodge | Data in hard copy only |
| 39 | Tailings Pond | Deer Lodge | Data no longer on file |
| 42 | Bigfork Ranger Station | Flathead | Less than one year's data |
| 43 | Columbia Falls Brandt | Flathead | Less than one year's data |
| 44 | Columbia Falls Delbon | Flathead | Other representative site |
| 45 | Columbia Falls Geis | Flathead | Less than one year's data |
| 46 | Columbia Falls Water | | |
| | Supply (Trailer) | Flathead | Data in hard copy only |
| 47 | Kalispell Airport | Flathead | Other representative site |
| 49 | Polebridge | Flathead | Less than one year's data |
| 50 | Big Sky Golf Course | Gallatin | Less than one year's data |
| 64 | Polson | Lake | Other representative site |
| 65 | Ronan | Lake | Other representative site |
| 68 | East Helena A & W | Lewis & Clark | Other representative site |
| 70 | Hadfield West Main | | |
| | (ASARCO) | Lewis & Clark | Less than one year's data |
| 72 | Kleffner Residence | Lewis & Clark | Data in hard copy only |
| 73 | Kleffner Road (ASARCO) | Lewis & Clark | Less than one year's data |
| 74 | Sinter Plant (ASARCO) | Lewis & Clark | Less than one year's data |
| 75 | Water Tower (ASARCO) | Lewis & Clark | Less than one year's data |
| 76 | Zinc Plant (ASARCO) | Lewis & Clark | Less than one year's data |
| 80 | Missoula Fire Lab | Missoula | Other representative site |
| 82 | Missoula Lions Park | Missoula | Other representative site |
| 83 | Missoula Malfunction | | |
| | Junction | Missoula | Other representative site |
| 85 | Missoula Olofson | Missoula | Other representative site |
| 86 | Missoula Rose Park | Missoula | Other representative site |
| 87 | Missoula Stiegler | Missoula | Other representative site |
| 104 | Powell County Courthouse | Powell | Data in hard copy only |
| 106 | Poplar | Roosevelt | Less than one year's data |
| 110 | Colstrip McRae | Rosebud | Other representative site |
| 112 | Lame Deer-Fisher Butte | Rosebud | Less than one year's data |
| 116 | Butte Alpine West | Silver Bow | Less than one year's data |
| 119 | Harrison Fire Station | Silver Bow | Data no longer on file |
| 128 | Devon | Toole | Data no longer on file |
| 129 | Fort Peck | Valley | Data no longer on file |
| 135 | Billings AQB Office | Yellowstone | Data in hard copy only |
| 136 | Billings 11th & 27th | Yellowstone | Less than one year's data |
| 137 | Billings Central Park | Yellowstone | Less than one year's data |
| 138 | Billings Metra | Yellowstone | Other representative site |
| 140 | Billings Taft School | Yellowstone | Other representative site |
| 141 | Coburn Road | Yellowstone | Data no longer on file |
| 143 | Laurel BN | Yellowstone | Data no longer on file |
| 144 | Laurel Farm | Yellowstone | Other representative site |
| 146 | Lockwood Park | Yellowstone | Data no longer on file |
| 147 | Lockwood School | Yellowstone | Less than one year's data |
| 148 | North Johnson Lane | Yellowstone | Data no longer on file |

Department of Natural Resources and Conservation

The Montana Department of Natural Resources and Conservation (DNRC) funded a two-year wind energy research and development program. The purpose of this project was to monitor winds at three locations (Livingston, Whitehall, and Big Timber) and to install a wind turbine at Livingston.

Monitoring equipment was installed at the monitoring sites in February and March 1980. Data were collected at an anemometer height of 10 meters using equipment from Campbell Scientific Corporation. A microprocessor collected the data and recorded it on magnetic tape at the site. The data were later transferred to a computer for storage and analysis. Raw data from these sites were available only in hard copy at the time computer analyses for this *Atlas* were conducted. A summary of one year's data, however, was available. Wind speed and wind

C14 -

power summaries are presented below. Wind speed figures are as collected at the 10-meter anemometer height, whereas wind power figures are calculated for 55 feet above ground level.

The Whitehall site was located approximately 4 miles west of Whitehall. Average monthly wind speeds at the site ranged from 7.0 miles per hour in January 1981 to 14.7 miles per hour in December 1980. Average wind speed for the year of monitoring was 10.6 miles per hour. Average wind power varied from 20 watts/m² in January 1981 to 187 watts/m² in December 1980. Average annual wind power was 81 watts/m².

The Big Timber site was located approximately 4 miles east of Big Timber. Average monthly wind speeds ranged from 8.0 miles per hour in May 1980 to 15.8 miles per hour in February 1981. Average wind speed for the year of monitoring was 10.5 miles per hour. Average monthly wind power density varied from 30 watts/m² in May

Table C-2
Additional NWS/FAA/USAF Wind Monitoring Periods and Sites

| Site | County | Period of | i Mo | onitoring |
|---------------------------|---------------|-----------|------|-----------|
| Dillon FAA Airport | Beaverhead | 06/19/51 | _ | 10/29/63 |
| Great Falls Malmstrom AFB | Cascade | 01/01/49 | _ | 05/31/53 |
| Great Falls Malmstrom AFB | Cascade | 03/01/54 | _ | 02/28/58 |
| Great Falls NWS Airport | Cascade | 01/01/48 | - | 02/02/59 |
| Great Falls NWS Airport | Cascade | 02/03/59 | _ | 12/31/64 |
| Miles City FAA Airport | Custer | 01/01/48 | _ | 12/31/64 |
| Lewistown FAA Airport | Fergus | 12/21/49 | _ | 08/15/62 |
| Kalispell NWS Airport | Flathead | 05/01/49 | - | 06/30/53 |
| Kalispell NWS Airport | Flathead | 07/01/53 | _ | 06/30/59 |
| Kalispell NWS Airport | Flathead | 07/01/59 | _ | 06/30/64 |
| Bozeman FAA Airport | Gallatin | 01/01/48 | _ | 04/27/51 |
| Cut Bank FAA Airport | Glacier | 11/22/49 | _ | 10/03/59 |
| Drummond FAA Airport | Granite | 01/01/48 | _ | 10/15/50 |
| Havre NWS Airport | Hill | 02/01/61 | _ | 12/31/64 |
| Havre NWS City | Hill | 05/01/50 | _ | 10/31/56 |
| Helena NWS Airport | Lewis & Clark | 01/01/48 | _ | 09/19/61 |
| Missoula NWS Airport | Missoula | 01/01/48 | _ | 04/03/58 |
| Missoula NWS Airport | Missoula | 04/04/58 | _ | 12/31/64 |
| Livingston FAA Airport | Park | 07/05/53 | _ | 12/31/54 |
| Glasgow AFB | Valley | 10/01/58 | - | 06/07/61 |
| Glasgow NWS Airport | Valley | 10/01/55 | - | 08/05/62 |
| Glasgow NWS Airport | Valley | 08/06/62 | _ | 05/31/68 |
| Glasgow NWS City | Valley | 01/01/48 | - | 10/31/55 |
| Billings NWS Airport | Yellowstone | 01/01/48 | - | 06/25/58 |
| Billings NWS Airport | Yellowstone | 06/26/58 | - | 12/31/64 |
| Custer FAA Airport | Yellowstone | 01/01/48 | - | 05/31/49 |

1980 to 234 watts/m² in February 1981. Average wind power for the year of monitoring was 80 watts/m².

The Livingston site was located approximately 2 miles east of Livingston. Average monthly wind speeds ranged from 13.2 miles per hour in August 1980 to 21.5 miles per hour in February 1981. Average wind speed during the year of monitoring was 15.8 miles per hour. Average monthly wind power density ranged from 95 watts/m² in July 1980 to 790 watts/m² in December 1980. For the year of monitoring, average wind power was 277 watts/m².

Wind speed at these sites reportedly was unusually low that year compared with historical wind speeds.

The Montana Department of Natural Resources and Conservation also funded a three-phase, one-year survey of wind speed and direction in the upper Yellowstone River Valley, between Livingston and Springdale.

During each phase of the study, wind data were collected at three sites for three months. Phase 1 ran from December 1978 through February 1979; Phase 2 was conducted in March and April 1979; Phase 3 took place from May through July 1979. Monitoring and analysis was conducted by Brelsford Engineering of Bozeman.

Each site was equipped with wind monitoring systems from Natural Power, Inc. (NPI). Sensors were mounted on 10-meter towers. The monitoring sites for this study were located as follows:

Phase 1

S1A—Harvatt's Flat—2 miles south of Livingston, south of I-90 on the eastern bench above the Yellowstone, and 6 miles west of the Livingston Municipal Airport (Mission Field).

S1B—Koffee Kup Ranch—10 miles northeast of Livingston on a hilltop 1 mile east of the Shields River and 5 miles north of the Yellowstone River. S1C—Hunter's Hot Springs—3 miles northeast of Springdale, 16 miles east of Livingston, and 2 miles north of the Yellowstone River on a hilltop west of the hot springs.

Phase 2

S2A — Park County Landfill — 4 miles east of Livingston, south of I-90 on the bench above Chicken Creek and the Yellowstone River Valley, and 2 miles west of Mission Field.

S2B — George Meyers Ranch — 1 mile southeast of Livingston, north of I-90 on the north shoulder of Harvatt's Flat and adjacent to the abandoned Livingston Airport.

S2C — Charles Hillman Ranch — 6 miles northeast of Livingston on the west side of the Shields

Table C-3

DNRC Wind Energy Survey
Livingston to Springdale

| Site | Month/Year | Mean Wind Speed (mph) | Available Power (watts/m²) |
|------|------------|--------------------------|-------------------------------|
| S1A | Dec 78 | 20.4 | 701.9 |
| SIA | Jan 79 | 13.8 | 337.6 |
| SIA | Feb 79 | 19.5 | 689.4 |
| S1B | Jan 79 | 7.7 | 83.9 |
| S1B | Feb 79 | 14.6 | 373.4 |
| S1C | Jan 79 | 16.7 | 448.3 |
| S1C | Feb 79 | 16.7 | 443.6 |
| S2A | Mar 79 | 14.9 | 334.1 |
| S2A | Apr 79 | 16.0 | 376.2 |
| S2B | Mar 79 | 10.7 | 151.3 |
| S2B | Apr 79 | 12.2 | 169.3 |
| S2C | Apr 79 | 12.9 | 153.9 |
| S2C | May 79 | 12.6 | 171.9 |
| S3A | May 79 | 13.7 | 235.8 |
| S3A | Jun 79 | 12.1 | 163.1 |
| S3A | Jul 79 | 10.4 | 96.1 |
| S3B | Jun 79 | 13.8 | 217.5 |
| S3C | May 79 | 12.9 | 247.3 |
| S3C | Jun 79 | 12.7 | 230.6 |
| S3C | Jul 79 | 10.9 | 122.3 |

River Valley as it enters the Yellowstone River Valley west of U.S. 89.

Phase 3

S3A — Livingston West — 2 miles west of Livingston, north of I-90 and south of U.S. 10, on a hill above the Leonard Adams home.

S3B — McGuire Hill — 1/2 mile northeast of Livingston and 1/4 mile north of the residential area on the abandoned police radio tower hill.

S3C — Gordon Brittan Ranch — 9 miles west of Livingston and 1.5 miles south of the Yellowstone River on the east bench above Mission Creek and the Brittan Ranch home.

A DNRC summary of mean wind speed and available power for these sites is presented in Table C-3. Monthly mean wind speeds ranged from about 8 to 20 miles per hour, and averaged about 14 miles per hour. Monthly available wind power ranged from about 100 to 700 watts per square meter and averaged about 300 watts per square meter.

Old West Regional Commission

The Old West Regional Commission funded a one-year study to establish the solar and wind energy potential and the atmospheric dispersion potential in northeastern Montana.

A 100-meter meteorological tower was installed at Glasgow Air Force Base, about 20 miles north of Glasgow, in September 1977. Wind measurements were made at three levels (10.0, 31.6, and 100.0 meters above ground level) from October 25, 1977, to August 31, 1978.

Wind speeds at the 10-meter level averaged 11.4 miles per hour during the study. Average monthly wind speeds ranged from 9.2 miles per hour in March 1978 to 15.4 miles per hour in April 1978.

At the 31.6-meter level, average wind speed during the period of study was 13.9 miles per hour. Average monthly wind speeds varied from 11.6 miles per hour in March 1978 to 18.3 miles per hour in April 1978.

The average wind speed at the 100-meter level was 17.4 miles per hour during the study period. Average monthly wind speeds ranged from 15.0 miles per hour in June 1978 to 21.7 miles per hour in April 1978.

The raw data from this site were available only in hard copy form at the time computer analyses were conducted for this Atlas. Data analyses from monitoring previously conducted at this site by the U.S. Air Force also are provided in the Atlas. The wind speeds observed in the more recent study were considerably higher than those reported by the Air

Force; however, they were similar to those reported by the National Weather Service at the airport about 20 miles south.

U.S. Department of the Interior, Bureau of Reclamation

The Bureau of Reclamation, at that time the Water and Power Resources Service of the U.S. Department of the Interior, funded a one-year study to monitor wind speed and direction at four sites in Montana. Monitoring sites were established at the Canyon Ferry, Gibson, Tiber, and Yellowtail dams. Monitoring began in January 1980 and continued through January 1981.

The monitors used were Met One wind speed and direction sensors mounted 10 meters above ground level. A Campbell Scientific CR21 data logger sampled the sensors every 60 seconds and recorded hourly averages on cassette tape. Parameters measured included: current wind speed; current wind direction; average wind speed; average wind direction and constancy; average wind speed to the first, second, third, fourth, and fifth power; maximum wind speed; and minimum wind speed. The data tapes were read by computer, checked, and stored for later processing.

The wind power speeds reported in the data summaries are not based on hourly average wind speeds, but are the cube root of the hourly average cubed wind speed.

The Canyon Ferry site was located on the summit of a hill just north of Canyon Ferry Dam at an elevation of 4,150 feet. Average monthly wind power speeds at the site ranged from 7.8 miles per hour in January 1981 to 14.1 miles per hour in November 1980. The average wind power speed for the monitoring period was 10.1 miles per hour.

The Gibson Dam site was located just south of the Sun River approximately 3.5 miles east-northeast of Gibson Dam. Elevation at the site was 4,460 feet. Average monthly wind power speeds ranged from 9.4 miles per hour in January 1981 to 17.9 miles per hour in September 1980. The average wind power speed for the monitoring period was 12.5 miles per hour.

The Tiber Dam site was located approximately 0.5 mile east-northeast of Tiber Dam at an elevation of 3,240 feet. Average monthly wind power speeds varied from 7.8 miles per hour in February 1980 to 13.0 miles per hour in December 1980. The average wind power speed for the monitoring period was 10.6 miles per hour.

The Yellowtail Dam site was located approximately 0.8 miles north-northwest of the

Yellowtail Dam at an elevation of 3,800 feet. Average monthly wind power speeds ranged from 9.6 miles per hour in January 1981 to 16.3 miles per hour in October 1980. The average wind power speed for the monitoring period was 12.1 miles per hour.

The raw data from this study were not available for analysis since the Bureau of Reclamation did not have the data in its possession.

Western Area Power Administration

The Western Area Power Administration (WAPA) ran a Wind Prospecting Program beginning in 1981. The program covered ten of the states in WAPA's fifteen-state marketing area. Over one hundred sixty sites eventually were studied; six of the sites were located in Montana. Monitoring at some of the Montana sites continued until 1986.

WAPA recruited its customers (rural electric cooperatives in Montana's case) to carry out the actual data collection. Five co-ops participated in Montana. The program collected 15-minute average wind speed data. Aeolian Kinetics or Natural Power signal conditioners were used and the raw data were recorded on cassette tape.

Data from this effort were available only in hard copy. Data tables from the WAPA report have been reproduced for the *Wind Atlas*. Brief site descriptions also have been drawn from WAPA reports. No information was available on the quality control measures in the program.

The Ekalaka site was located in extreme south-eastern Montana, about nine miles northeast of Ekalaka, at 45 57 37 N and 104 25 18 W (Site No. 11 on Map II-1). Elevation was 3,460 feet. The area is rolling grasslands. The anemometer was located at a substation. Anemometer height was 36 feet. Data was collected between March 11, 1982 and May 18, 1986, by Southeast Electric Cooperative. Average wind speed was 9.78 miles per hour. Highest average wind speed was in the spring at 10.57 miles per hour and lowest was in the fall, at 9.05 miles per hour. Data recovery for the entire period was 69 percent.

The Circle site was located 17 miles southeast of Circle, at 47 15 42 N and 105 16 05 W (Site No. 23 on Map II-1). Elevation was 3,467 feet. The site is on a high ridge, approximately 1,000 feet higher than the surrounding area. There were no obstructions in this grassland area. Anemometer height was 31 feet. Data was collected between March 11, 1982 and October 30, 1985 by the McCone Electric Cooperative. Average wind speed was 14.63 miles per hour. Highest average wind speed was in the

spring, at 15.49 miles per hour, and lowest was 14.01 in the fall. Data recovery for the entire period was 78 percent.

The Mt. Antione site was located 5 miles southeast of Hays, at 47 57 20 N and 108 33 02 W (Site No. 158 on Map II-1). The anemometer was located on the highest point in the Little Rocky Mountains, with no obstructions. The elevation was 5,785 feet. The anemometer height was 30 feet. Data were collected between February 8, 1984 and August 5, 1985; the monitoring system was in place until a later date, but no more valid data were collected. Average wind speed was 13.98 miles per hour. Highest average wind speed was during the winter, with 15.77 miles per hour, while the lowest was in the summer, with 13.28 miles per hour. Data recovery for the entire period was 69 percent.

The Reserve site was located 10 miles southeast of Reserve at 48 30 58 N and 104 18 23 W (Site No. 115 on Map II-1). Site elevation was 2,234 feet. The area is one of high grass and grains. The anemometer was installed on a radio tower leg at 30 feet. There were no obstructions in the area, but the tower itself could have affected the readings. Data was collected from January 29, 1982 to June 30, 1985 by Sheridan Electric Cooperative. Average wind speed was 11.13 miles per hour. Highest average wind speed was in the spring, at 12.17 miles per hour, and lowest was in the fall at 10.50 miles per hour. Data recovery for the entire period was 72 percent.

The Fairfield site was located 3 miles west of Fairfield, at 47 36 31 N and 112 02 43 W (Site No. 126 on Map II-1). Elevation at the site was 4,200 feet. The site was the highest ground within a ten-mile radius, in a grassland area near the Rocky Mountain Front. Anemometer height was reported at 30 feet, but DNRC has learned that the actual height probably was lower. Data were collected between December 30, 1981 and January 3, 1985 by Sun River Electric Cooperative. Average wind speed was 11.45 miles per hour. Highest average wind speed was in the winter, at 13.04 miles per hour, while the lowest was in the summer at 9.29 miles per hour. Data recovery for the entire period was 91 percent.

The Pendroy site was located 8 miles northwest of Pendroy, at 48 07 45 N and 112 26 20 W (Site No. 127 on Map II-1). Elevation at the site was 4,550 feet. The area is rolling grasslands near the Rocky Mountain Front. Data was collected from March 17, 1983 to December 19, 1984 by Sun River Electric Cooperative. Anemometer height was 31 feet. Average wind speed was 9.93 miles per hour. Highest average wind speed was 12.52 miles per hour in the winter and lowest was 9.02 miles per hour in the summer. Data recovery over the period was 86 percent.

Table C - 4A

Western Area Power Administration

EKALAKA Carter County

| ELEVATION:3460. FT ACTUAL | 50. FT | ACTUAL | | | , | : | ļ | | | | | | | | | |
|------------------------------|----------------|--|---------------|---------------------|---------------------|---|----------------------|-------------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|-----------------------------|
| ANEMOMETER HT:36.1 FT ACTUAL | 1:36.1 | FT ACT | UAL | | | MONTHLY AND DIURNAL AVERAGE WIND SPEEDS (MPH) | DIURNA | L AVERA | GE WIND | SPEEDS | E E | | | | | |
| MID-SAM HDU | WIND IRS OF | WIND SPEED (MPH) Hours of Usable Data | (MPH) DATA | JAN 9.45 279. | FEB 9.00 250. | MAR 10.93 264. | APR 10.83 267. | MAY 9.66 231. | JUN 8.91 219. | JUL 9.03 236. | AUG 9.63 230. | SEP 8.64 190. | 0CT 7.67 141. | NOV 7.76 179. | DEC 9.76 229. | CUMULATIVE 9.41 2714. |
| 3A#-6A# HOU | WIND IRS OF | WIND SPEED (MPH) HOURS OF USABLE DATA | (MPH) DATA | 9.54 | 9.30 | 9.91 263. | 9.74 | 233. | 9.17 | 8.05 237. | 8.89 229. | 8.61 188. | 7.72 | 8.86 180. | 9.69 | |
| 6AM-9AM HOU | WIND RS OF | WIND SPEED (MPH) HOURS OF USABLE DATA | (MPH) DATA | 9.26 278. | 9.10 | 9.77 | 11.39 260. | 10.99 233. | 10.85 218. | 10.00 | 9.73 | 9.11 | 9.60 141. | 9.33 180. | 9.55 | 9.87 |
| PAM-NOON HOU | WIND RS OF | WIND SPEED (MPH) HOURS OF USABLE DATA | (MPH) DATA | 9.96 275. | 10.03 251. | 11.22 266. | 12.97 271. | 12.05 | 11.28 219. | 10.37 | 10.80 232. | 11.04 | 10.81 142. | 10.08 | 9.49 | 10.87 |
| MOCK-3P# HOU | WIND RS OF | WIND SPEED (MPH) | | 10.56 279. | 10.61 | 11.75 266. | 13.38 270. | 12.54 232. | 11.21 221. | 9.84 | 10.75 | 11.57 | 11.87 | 10.27 | 9.31 | 11.15 |
| 3PM-6PM HOU | WIND RS OF | WIND SPEED (MPH) HOURS OF USABLE DATA | DATA | 9.62 278. | 9.24 | 10.64 267. | 12.36 270. | 11.78 231. | 10.68 222. | 9.77 | 10.71 234. | 10.51 | 10.14 | 8.25 | 8.86 | 10.26 |
| 6PM-9PM HOUT | RS OF | WIND SPEED (MPH) HOURS OF USABLE DATA | MPH) | 9.51 276. | 8.64 250. | 9.56 266. | 9.56 269. | 9.04 | 8.43 | 8.92 233. | 9.09 | 7.47 | 8.54 142. | 7.84 | 9.44 | 8.93 2711. |
| 9PM-MID HOUR | WIND RS OF | WIND SPEED (MPH) | | 9.51 278. | 9.00 | 10.43 | 10.17 269. | 9.64 | 9.76 219. | 9.80 233. | 9.70 | 9.35 183. | 8.75 143. | 7.87 | 9.63 | 9.47 |
| FULL MONTH HOUR | HOURS OF | SPEED (MPH) USABLE DATA | | 9.68 | 9.37 | 10.54 | 11.12 2521. | 10.09 2711. | 9.82 | 9.51 | 9.92 1852. | 9.55 1502. | 9.16 1384. | B.64 2146. | 9.31 | |
| | | SEA | SEASONAL AND | | AMBUAL VELOCITY | | ISTRIBU | DISTRIBUTION PARAMETERS | RAMETER | v | | | | | | |
| WEIBULL, K | | WINTE | WINTER (DJF) | ^+ | SPRING (MAM) | (MAM) 1.73 | NO. | SUMMER (JJA) | A) 78 | FALL | (SON) 1.68 | | A | ANNUAL 1.75 | 5 | CUMULATIVE 1.75 |
| WEIBULL, C | | | 10.64 | _ | | 11.86 | | 10.96 | 96 | | 10.14 | | 10 | 10.90 | | 10.97 |
| AYERAGE WIND SPEED (MPH) | EED (I | (H-H) | 9.48 | ue. | | 10.67 | | 9.75 | 75 | | 9.08 | | • | 9.71 | | 9.78 |
| STANDARD DEVLATION | HOI | | 5.33 | _ | | 6.29 | | 5.68 | 5 | | 5.53 | | 10 | 5.72 | | 5.78 |
| FLUX (WATT/Me+2) | S | | 84.7 | _ | | 127.2 | | 96.9 | e. | | 82.7 | | ch. | 97.1 | | 9.66 |
| HOURS OF USABLE DATA | DATA: | | 6439. | | • | 7352. | | 6506 | | | 5032. | | | | | 26320. |

Table C - 4B

Western Area Power Administration

CIRCLE

McCone County

ELEVATION:3467. FT ACTUAL

| ELEVATION:3467. FT ACTUAL | :3467. FT | ACTUAL | | | THUM | ORV A | MONTH! Y AND DIURNAL AVERAGE WIND SPEEDS | AVERAC | SE WIND | SPEEDS | (#PH) | | | | | |
|------------------------------|--|-------------|-----------------|----------------------|----------------------|----------------------|--|----------------------|----------------------|----------------------|----------------------|---------------------|---------------|----------------|----------------------|------------------------------|
| AKEMOMETER HT:30.8 FT ACTUAL | R HT:30.8 | FT ACT | LUAL | | | | | | | | | | | | | |
| MID-3AM | WIND HOURS OF | SPEED (MPH) | (MPH) | JAN 13.31 247. | FEB 12.86 144. | MAR 14.71 218. | APR 14.66 284. | MAY 15.02 153. | JUN 16.15 132. | JUL 14.44 291. | AUG 16.96 231. | SEP 14.62 90. | 14.90 114. | 13.76 266. | DEC 15.43 156. | CUMULATIVE 14.68 2326. |
| 3AM-6AM | WIND HOURS OF | SPEED (MPH) | (MPH) | 12.71 244. | 13.17 | 14.91 218. | 14.16 263. | 13.49 | 16.39 | 13.71 291. | 16.49 | 13.94 | 14.16 | 13.02 267. | 15.05 156. | 14.20 |
| 6 A M-9 A M | MINO HOURS OF | SPEED (MPH) | (MPH) | 12.90 230. | 12.78 | 15.11 216. | 14.59 282. | 13.50 | 14.90 133. | 13.76 291. | 15.35 231. | 14.31 | 12.79 | 12.25 267. | 14.05 | 13.87 |
| 9AM-NOON | WIND HOURS OF | SPEED (MPH) | (MPH) | 13.14 229. | 13.48 | 16.74 216. | 16.20 284. | 14.68 153. | 15.56 136. | 14.35 289. | 15.27 233. | 16.18 | 14.26 | 13.15 266. | 13.60 | 14.69 2318. |
| MGC - NOON | WIND HOURS OF | SPEED (MPH) | (MPH) E DATA | 15.14 | 16.20 | 17.03 221. | 16.54 282. | 15.46 151. | 16.03 139. | 13.38 289. | 14.73 228. | 16.87 93. | 16.57 | 14.30 266. | 13.86 159. | 15.33 |
| 3PM-6PM | WIND SPEED (MPH) HOURS OF USABLE DATA | SPEED | (MPH) E DATA | 14.85 | 15.52 | 16.36 | 15.52 279. | 15.26 | 15.73 138. | 12.02 291. | 14.86 225. | 16.12 93. | 15.32 118. | 13.72 | 14.39 | 14.76 |
| 6 P.M. 9 P.M | WIND SPEED (MPH) HOURS OF USABLE DATA | SPEED | (MPH) | 14.81 | 14.43 | 16.15 229. | 13.85 279. | 14.53 150. | 16.05 138. | 11.73 291. | 15.33 225. | 13.58 93. | 13.07 | 13.83 264. | 15.29 | 14.31 |
| 9 PM-MID | | SPEED (MPH) | (MPH) E DATA | 14.32 | 13.09 | 15.90 | 14.60 279. | 15.45 150. | 15.81 138. | 13.76 290. | 16.59 225. | 13.72 93. | 14.15 | 14.20 | 15.70 | 14.79 2328. |
| FULL MONTH | WIND SPEED (MPH) Hours of Usable Data | SPEED | (MPH) E DATA | 13.91 | 13.92 | 15.37 2401. | 15.91 2599. | 15.15 2439. | 14.28 | 14.09 2963. | 15.39 2214. | 14.34 1943. | 14.41 927. | 13.53 2124. | 14.67 1267. | |
| | | SE | SEASONAL | _ | AND ANNUAL VELDCITY | | DISTRIBUTION | | PARAMETERS | 35 | | | | | | |
| WEIBULL, K | | WINI | WINTER (DJF) | £6 | SPRING | (MAM) 2.04 | าร | SUMMER (J. | (JJA) 2.25 | FALL | . (SON) 2.15 | | ¥. | ARNUAL 2.08 | D U | CUMULATIVE 2.08 |
| WEIBULL,C | | | 15.90 | 90 | | 17.48 | | 16 | 16.42 | | 15.81 | | = | 16.41 | | 16.51 |
| AVERAGE WIND SPEED (MPH) | ND SPEED | (MPH) | 14.10 | 10 | | 15.49 | | 1 | 14.54 | | 14.01 | | 2 | 14.53 | | 14.63 |
| STANDARD DEVIATION | EVIATION | | 7.5 | 69 | | 7.95 | | 9 | 6.85 | | 6.86 | | ,- | 7.33 | | 7.38 |
| FLUX (WATT/M++2) | /M**2) | | 265.6 | • | | 333.9 | | 25: | 253.6 | | 235.5 | | 7 | 270.7 | | 275.9 |
| HOURS OF USABLE DATA | SABLE DAT | . | \$106 | ŏ. | | 7439. | | 7277 | .11. | | 4993. | | | | | 24814. |
| | | | | | | | | | | | | | | | | |

Table C - 4C

Western Area Power Administration

MT. ANTIONE

Phillips County

ELEVATION: 5785. FT ACTUAL

| ELEVATION | ELEVATIUS:5785. FT ACTUAL | T ACTUAL | | | 1 | : | | | | | | | | | | |
|--------------------------|--|----------------------------|----------------------|--------------|------------------------------|---|-------------------------|----------------------|----------------------|----------------------|--------------|---------------------|--------------|---------------------|---------------------|-----------------------------|
| AREMONETE | AREMOMETER HT:29.9 FT ACTUAL | P FT ACI | TUAL | | | MUNINLY ARD DIURNAL AVERAGE WIND SPEEDS | DIURAA | L AVERA | GE WIND | SPEEDS | = | | | | | |
| MID-3AM | MIND SPEED (MPH) | SPEED USABLE | (MPH) E DATA | 0.00 0.00 | 0.00 0.00 | MAR 12.99 46. | APR 17.69 93. | MAY 14.97 102. | JUN 14.96 135. | JUL 12.63 189. | AUG 11.57 | SEP 14.95 51. | 0.00 0.00 | #0V 13.21 45. | DEC 16.31 51. | CUMULATIVE 14.21 804. |
| 3AM-6AM | HOURS OF USABLE DATA | SPEED : USABLE | (MPH) E DATA | | | 12.29 48. | 17.47 97. | 13.68 102. | 13.89 | 12.09 189. | 12.31 93. | 15.32 61. | 0.00 | 13.49 45. | 15.91 51. | 13.79 |
| # W - B V 9 | MIND SPEED (MPH) | SPEED: USABLE | (MPH) E DATA | 。 。。 | 9.0 | 11.89 | 14.85 | 11.72 | 13.32 | 12.09 189. | 12.39 93. | 15.03 | 0.00 | 14.83 | 16.32 | 13.20 |
| 9 A M- H O G K | WIND SPEED (MPH) | SPEED USABLE | (MPH) | 0.0 | 0.0 | 10.36 | 14.40 | 12.12 105. | 13.91 136. | 12.38 169. | 13.21 92. | 14.86 51. | 0.00 | 13.54 | 16.78 | 13.31 |
| MOCK-3PM | HOURS OF USABLE DATA | SPEED | (MPH) | 0.0 | • • • | 10.63 | 15.31 96. | 12.72 104. | 14.14 | 12.57 188. | 14.99 | 14.89 51. | | 11.04 | 14.37 | 13.50 |
| 3PM-6PM | HOURS OF USABLE DATA | SPEED | (MPH) | %. %. | 0.0 | 10.66 | 16.14 | 13.25 102. | 14.94 135. | 12.97 189. | 15.92 90. | 15.86 51. | | 9.72 | 14.80 | 13.88 |
| 6 P.M. 9 P.M | HOURS OF | SPEED (MPH) USABLE DATA | (MPH) DATA | | 9.0 | 11.42 | 14.96 | 13.18 | | | 13.64 90. | 18.64 51. | 9. 9. | 10.94 | 16.30 | 13.83 |
| 9 P.MMID | WIND HOURS OF | SPEED (MPH) USABLE DATA | (MPH) DATA | | 。. 。. | 12.98 49. | 16.83 90. | 14.71 | 14.56 | 12.58 189. | 11.93 91. | 16.36 50. | | 12.99 | 17.67 | 14.18 |
| FULL MONTH | WIND SPEED (MPH) HOURS OF USABLE DATA | SPEED USABLE | (MPH) DATA | | 15.64 | 12.01 1071. | 15.83 | 13.71 | 14.14 | 12.50 1512. | 13.23 | 15.74 | 13.40 | 15.05 698. | 16.05 | |
| | | SE | ASONAL | AND ANI | SEASONAL AND ANNUAL VELOCITY | | DISTRIBUTION PARAMETERS | TION PAI | RAMETER | v | | | | | | |
| WEIBULL,K | | LNIM | WINTER (DJF) 1.54 | o± | SPRING | (MAM) 1.72 | # OS | SUMMER (JJA) | A) | FALL | (50%) | | A O | ANKUAL 0.00 | 70 | CUMULATIVE 1.77 |
| WEIBULL, C | | | 17.52 | Ş | | 15.29 | | 14.98 | 6 | | 16.91 | | • | 0.00 | | 15.70 |
| AVERAGE WIND SPEED (MPH) | O SPEED | (Ha | 16.77 | | | 13.63 | | 13.28 | 92 | | 16.07 | | 0 | 0.00 | | 13.98 |
| STANDARD DEVIATION | VIATION | | 10.48 | | | 9.16 | | 6.80 | 2 | | 8.91 | | ٥ | 0.00 | | 8.17 |
| FLUX (WATT/Me+2) | /He+2) | | 454.8 | 80 | | 252.1 | | 192.6 | ٦Ŏ | | 335.0 | | _ | 0.0 | | 263.4 |
| HOURS OF USABLE DATA | SABLE DATA | - | 1216. | • | | 2869. | | 3663. | <u>.</u> . | | 1262. | | | | | 8999. |
| | | | | | | | | | | | | | | | | |

Table C - 4D

Western Area Power Administration

RESERVE

Sheridan County

ELEVATION:2234. FT ACTUAL

| ELEVATION:2234. FT ACTUAL | :2234. FT | ACTUAL. | | | 1 | > | AMOUNTO | AVERA. | SCHOOL STREET AND STREET STREET | SPEEDS | E G | | | | | |
|------------------------------|--|----------------------------|----------------------|----------------------|------------------------------|----------------------|----------------|----------------------|---------------------------------|---------------------|---------------------|----------------------|--------------------|--|---------------|------------------------------|
| ANEMOMETER HT:29.9 FT ACTUAL | 3 HT:29.9 | FT ACT | UAL | | ĺ | | | | | | | | | | | |
| MID-3AM | WIND SPEED (MPH) HOURS OF USABLE DATA | SPEED | (MPH) DATA | JAN 10.78 136. | FEB 9.86 212. | MAR 11.53 171. | APR 10.58 | MAY 10.98 138. | JUN 9.11 180. | JUL 9.62 186. | AUG 9.62 234. | SEP 10.79 214. | 0CT 6.34 45. | 0.00 0.00 | DEC 11.25 | CUMULATIVE 10.23 1701. |
| 3AM-6AM | WIND SPEED (MPH) | SPEED | (MPH) DATA | 11.25 | 9.89 | 11.05 | 10.03 | 10.57 136. | 9.12 | 9.16 186. | 9.33 | 10.99 216. | 6.89 45. | 9.0 | 10.46 | 10.07 |
| 6AM-9AM | MIND HOURS OF | SPEED (MPH) | | 10.38 136. | 10.01 | 11.56 | 11.45 | 12.22 140. | 11.04 | 10.30 | 9.67 235. | 11.62 215. | 9.34 | 9.0 | 10,59 | 10.78 |
| NOOM-NOOM | WIND SPEED (MPH) HOURS OF USABLE DATA | SPEED | | 10.65 | 10.84 | 13.17 | 14.19 | 12.95 | 12.97 180. | 12.78 186. | 10.68 237. | 13.07 213. | 13.30 | | 11.04 | 12.26 1697. |
| MOOK-3PM | WIND SPEED (MPH) | SPEED | | 11.20 | 11.72 213. | 14.31 | 14.53 | 13.95 | 13.24 | 13.53 186. | 11.80 | 13.65 | 13.53 | • • • | 10.72 | 12.97 |
| 3PH-6PH | WIND SPEED (MPH) | SPEED | | 11.14 | 11.47 | 13.97 | 12.87 135. | 13.53 141. | 12.73 180. | 13.35 186. | 12.20 237. | 13.14 211. | 11.50 | •••••••••••••••••••••••••••••••••••••• | 11.37 | 12.62 |
| M 9 0 - 11 9 8 | MIND HOURS OF | SPEED (MPH) | | 11.64 | 10.98 210. | 12.91 171. | 9.90 | 11.74 | 10.42 | 10.72 | 10.96 236. | 10.91 | 9.46 | 0.00 | 10.13 | 11.04 |
| 9 P.MMID | WIND SPEED (MPH) HOURS OF USABLE DATA | SPEED | | 11.18 | 9.94 | 12.80 171. | 10.25 | 11.19 | 9.26 | 10.26 182. | 10.54 | 10.68 | 42. | • • • | 10.73 | 10.58 |
| FULL MONTH | WIND HOURS OF | SPEED (MPH) USABLE DATA | | 11.03 | 10.46 | 12.03 2124. | 12.11 2174. | 12.34 2442. | 10.95 1782. | 11.22 1482. | 10.61 | 11.82 1975. | 10.15 | 9.37 | 10.14 891. | |
| | | SE | ASONAL | AND AN | SEASONAL AND ANNUAL VELOCITY | | DISTRIB | UTION P | DISTRIBUTION PARAMETERS | ş | | | | | | |
| WEIBULL.K | | WINT | WINTER (DJF) 1.86 | . % . % | SPRING | (MAM) 1.85 | Š | SUMMER (J. | (JJA) 1.86 | FALL | . (SON) 1.75 | | AH | ARKUAL 1.83 | 3 | CUMULATIVE 1.81 |
| WEIBULL,C | | | 11.97 | 37 | | 13.70 | | 12 | 12.27 | | 11.78 | | 12 | 12.41 | | 12.51 |
| AVERAGE WIND SPEED (MPH) | ID SPEED | (MPH) | 10.55 | 2 6 | | 12.17 | | 10 | 10.90 | | 10.50 | | 11 | 11.03 | | 11.13 |
| STANDARD DEVIATION | EVIATION | | 5.89 | <u>8</u> | | 6.83 | | 6 | 6.09 | | 6.20 | | • | 6.26 | | 6.37 |
| FLUX (WATT/Me+2) | /He + 2) | | 121.3 | M | | 187.5 | | 13, | 134.1 | | 128.6 | | 1. | 141.6 | | 146.8 |
| HOURS OF USABLE DATA | SABLE DAT | • | 4011. | <i>:</i> | | 6739. | | 5151 | 51. | | 5585. | | | | | 21406. |
| | | | | | | | | | | | | | | | | |

Table C - 4E

Western Area Power Administration

FAIRFIELD

Teton County

ELEVATION: 4200. FT ACTUAL

| ELEVALIUN | ELEVALIUM: 4200. FT ACTUAL | T ACTUAL | _ | | | | | | , | | | | | | | |
|--------------------------|--|------------------------------|----------------------|----------------------|----------------------|----------------------|----------------------|--|---------------------|---------------------|---------------------|---------------------|----------------|----------------|------------------------|-----------------------------|
| ANEMOMETE | AMENDMETER HT:29.9 FT ACTUAL | P FT AC | TUAL | | | THLY AND | DIURA | MONTHLY AND DIURNAL AVERAGE WIND SPEEDS (MPH) | GE EIRD | SPEEDS | (E. | | | | | |
| MID-3AH | HOURS OF | SPEED (MPH) - USABLE DATA | CMPH) E DATA | JAN 13.31 286. | FEB 11.78 250. | MAR 10.55 194. | APR 12.52 177. | 10.12 186. | JUN 6.47 264. | JUL 7.64 126. | AUG 7.32 174. | SEP 9.50 178. | 10.24 186. | 11.44 250. | DEC 12.03 279. | CUMULATIVE 10.66 2549 |
| 3AH-6AH | MOURS OF USABLE DATA | SPEED : USABLE | (MPH) | 13.67 288. | 12.23 252. | 10.59 195. | 13.08 | 10.04 | 9.26 | 7.19 | 8.35 | 10.45 | 10.23 186. | 11.37 | 12.11 278. | 10.98 |
| 6 A III-9 A II | HOURS OF | SPEED (MPH) USABLE DATA | (MPH) | 14.60 288. | 12.02 252. | 10.72 193. | 13.51 | 11.42 | 9.55 264. | 8.56 | 8.62 | 10.67 | 9.97 | 11.71 249. | 12.32 281. | 11.37 |
| 9 A III - N O G N | WIND HOURS OF | SPEED (MPH) USABLE DATA | (MPH) | 14.56 284. | 14.40 263. | 12.86 193. | 14.61 | 12.78 186. | 9.72 | 10.28 | 10.22 | 12.27 | 12.30 | 14.48 253. | 13.13 | 12.79 |
| #45-#00# | WIND SPEED (MPH) HOURS OF USABLE DATA | SPEED | (MPH) | 15.09 285. | 15.42 261. | 12.70 191. | 13.87 177. | 13.79 186. | 9.53 | 11.45 | 10.98 176. | 12.76 181. | 13.10 184. | 15.28 254. | 13.54 | 13.27 2657. |
| 3 P III - 6 P III | WIND SPEED (MPH) HOURS OF USABLE DATA | SPEED | (MPH) | 13.50 285. | 14.04 251. | 11.26 192. | 14.48 177. | 14.73 186. | 9.86 267. | 11.34 | 11.43 | 12.40 180. | 11.31 | 12.70 258. | 12.59 284. | 12.50 2562. |
| M-8-M-9 | WIND SPEED (MPH) MOURS OF USABLE DATA | SPEED | (MPH) DATA | 12.59 285. | 11.63 252. | 10.42 191. | 12.17 | 12.91 186. | 9.09 | 9.71 | 9.72 177. | 9.94 | 10.11 | 11.25 267. | 12.04 | 11.09 |
| 9PM-MID | WIND SPEED (MPH) Hours of Usable Data | SPEED USABLE | (MPH) DATA | 12.65 283. | 11.03 252. | 10.83 191. | 11.69 | 10.49 | 8.46 267. | 9.13 | 8.32 177. | 9.63 | 10.16 186. | 11.23 | 12.17 281. | 10.64 2553. |
| FULL MOMTH | WIND SPEED (MPH) HOURS OF USABLE DATA | SPEED USABLE | (MPH) DATA | 13.75 2283. | 12.64 2012. | 10.89 2234. | 12.06 2148. | 11.60 | 9.24 | 9.38 978. | 9.30 | 11.04 | 10.93 1487. | 12.44 2023. | 12. 49 2252. | |
| | | SE | ASONAL | AND AN | IUAL YEL | OCITY 0 | ISTRIB(| SEASONAL AND ANNUAL VELOCITY DISTRIBUTION PARAMETERS | RAMETER | v | | | | | | |
| WEIBULL,K | | WINT | WINTER (DJF) 1.79 | (£) | SPRING | (MAH) 1.67 | 35 | SUMMER (JJA) | 76 | FALL | . (SOM) 1.85 | | ARK 1 | ANNUAL 1.76 | Ö | CUMULATIVE 1.72 |
| WEIBULL, C | | | 14.65 | 55 | | 12.88 | | 10.43 | 6 | | 12.96 | | 21 | 12.73 | | 12.84 |
| AVERAGE WIND SPEED (MPH) | ID SPEED | (MPH) | 13.04 | * | | 11.51 | | • | 9.29 | | 11.51 | | Ξ | 11.34 | | 11.46 |
| STANDARD DEVIATION | VIATION | | 7.52 | 32 | | 7.09 | | | 5.46 | | 6.45 | | • | 4.67 | | 6.87 |
| FLUX (WATT/Me+2) | (8002) | | 222.7 | ۲. | | 167.6 | | 82.7 | ., | | 147.7 | | 16 | 160.5 | | 158.9 |
| HOURS OF USABLE DATA | ABLE DATA | _ | 6546. | . : | | 6590. | | 5214. | ÷ | | 5636. | | | | | 23986. |

Table C - 4F

Western Area Power Administration

PENDROY

Teton County

| ¥ | MONTHLY AND DIURNAL AVERAGE WIND SPEEDS | DIURNAL | AVERAGE | ONIN: | | (Hah) | | | | | |
|--|---|-------------------------|--------------------|---------------------|---------------------|--------------------|---------------------|---------------------|---------------------|---------------|-----------------------------|
| JAN FEB WIND SPEED (MPH) 16,20 11.46 HOHRS OF HEARE DATA 93, 84. | MAR 8.64 135. | APR 8.33 151. | MAY 8.67 93. | JUN 9.36 117. | JUL 7.90 135. | AUG 8.04 64. | SEP 8.52 150. | 0CT 7.57 129. | NOV 7.89 156. | DEC 10.18 | CUMULATIVE 9.07 1305. |
| 15.89 | 7.48 135. | | 7.95 93. | 8.49 | 6.77 | 7.91 54. | 8.96 150. | 7.60 | 8.01 156. | 9.88 | 8.80 1381. |
| = | 7.93 | 8.74 1 149. | 10.84 93. | 8.98 118. | 7.95 | 7.66 | 9.07 | 6.93 | 8.51 156. | 10.24 90. | 9.16 |
| 15.04 93. | 10.53 133. | | 13.66 93. | 6.63 121. | 131. | 10.49 58. | 11.49 | 9.02 130. | 10.09 154. | 10.91 87. | 10.51 |
| WIND SPEED (MPH) 15.49 12.08 HOURS OF USABLE DATA 93. 84. | 12.20 1 | 10.29 1 150. | 14.95 93. | 9.65 | 10.52 | 11.56 57. | 13.30 | 10.32 132. | 11.01 | 11.65 90. | 11.75 |
| SPEED (MPH) 14.12 12.37 USABLE DATA 93. 84. | 12.37 1 135. | 11.05 1 150. | 16.29 1 93. | 10.61 | 11.50 | 12.13 59. | 13.32 | 10.01 | 9.46 | 11.61 89. | 11.67 |
| SPEED (MPH) 15.65 10.54 USABLE DATA 93. 84. | 9.27 | 9.34 1 | 11.87 | 9.72 | 9.35 | 10.68 | 9.41 | 8.88 132. | 7.63 153. | 10.44 88. | 9.93 1386. |
| 15.86 93. | 8.62 138. | 8.78 150. | 9.11 | 8.74 120. | 8.33 129. | 9.03 60. | 8.92 147. | 7.88 | 8.29 153. | 11.49 | 9.36 1389. |
| WIND SPEED (MPH) 15.42 11.14 Hours of Usable Data 744. 672. | 9.62 1079. 1 | 9.42 1 | 1408. 1 | 9.55 | 8.58 | 8.82 1040. | 10.36 1185. | 8.53 | 8.85 1233. | 10.80 713. | |
| SEASONAL AND ANNUAL VELOCITY | | DISTRIBUTION PARAMETERS | TION PAR | RAMETER | S | | | | | | |
| MINTER (DJF) SPRING | (MAR) 1.49 | SUMMER | MER (JJA) 1.63 | 25 | FALL | (SOM) | | # · · | 1.41 | 3 | CUMULATIVE 1.42 |
| 13.63 | 11.03 | | 10.07 | 70 | | 10.15 | | # | 11.20 | | 10.91 |
| 12.52 | 96.6 | | 9.02 | 22 | | 9.27 | | Ä | 10.19 | | 9.93 |
| 9.46 | 6.79 | | 5.69 | 5 | | 6.79 | | • • | 7.31 | | 7.11 |
| 296.5 | 124.7 | | 82.4 | • | | 113.8 | | Ä | 146.0 | | 134.5 |
| 2129. | 3914. | | 3734 | <i>:</i> | | 3461. | | | | | 13230. |

Electric Power Research Institute

The Electric Power Research Institute (EPRI) is conducting studies to acquire representative visibility and air quality data in the western United States. As part of this study, wind measurements have been collected at a site approximately 2 miles northwest of Harlowton. Monitoring was conducted from June 1981 to October 1982 with a Climatronics F460 wind measurement system. Anemometer height was 10 meters.

The data, which consist of wind speed and wind direction values recorded every five out of eight days during daylight hours, are not available to the public at this time.

Bonneville Power Administration

From May 1-3, 1981, Oregon State University, under contract to Bonneville Power Administration, conducted aerial wind prospecting surveys over western Montana as part of the Wind Regional Energy Assessment Program. Aerial surveys are a rapid means of assessing wind power potential over a large area. In such surveys, indicators of high wind speeds, such as wind-deformed trees, are observed from the air. In addition, the roughness of

the terrain, tree cover, ease of access, and location of transmission lines can be determined.

The OSU wind prospecting survey covered western Montana from south of Dillon to the Canadian border, and from the eastern front of the Rocky Mountains to the Idaho state line. Areas with an apparent high wind potential were found on exposed ridge crests and summits in all of the areas surveyed. Nearly all of these locations, however, are remote and inaccessible during the winter.

Based on the survey results, OSU recommended that wind monitors be installed at these locations:

- 1) Site 134, 24 miles south-southwest of Dillon:
- 2) Site 138, 24 miles southwest of Dillon;
- 3) Site 151, 10 miles east-northeast of Ennis;
- 4) Site 152, 4 miles southeast of Norris;
- 5) Site 159, 10 miles northeast of Whitehall;
- 6) Site 173, 6 miles north-northwest of Anaconda;
- 7) Site 178, 5 miles west-southwest of Philipsburg;
- 8) Site 186, 10 miles west of Drummond;
- 9) Site 188, 4 miles west of Drummond;
- 10) Site 200, 16 miles west of Helena;

Table C-5
Oregon State University
Wind Prospecting Fly Over

| Site Area | No. | Estimated Mean Annual Wind Speed (mph) | Existing Communications Facilities |
|-------------------|-----|---|--|
| Dillon & Butte | 134 | 15-19 | Yes |
| | 138 | 13-17 | Yes |
| | 151 | 14-17 | No |
| | 152 | 13-16 | Yes |
| | 159 | 15-18 | Yes |
| | 173 | 12-15 | No |
| | 178 | 12-15 | No |
| Missoula & Helena | 186 | 14-17 | No |
| | 188 | 14-17 | Yes |
| | 200 | 14-17 | Yes |
| | 217 | 16-19 | No |
| Browning | 252 | 17-21 | No |
| | 258 | 17-21 | No |
| | 261 | 15-18 | No |
| | 274 | 14-17 | Yes |

- 11) Site 217, 18 miles north-northwest of Helena:
- 12) Site 252, 4 miles northeast of Saint Mary;
- 13) Site 258, 16 miles south-southwest of Browning;
- 14) Site 261, 18 miles west of Dupuyer;
- 15) Site 274, 10 miles southwest of Browning.

In September 1981, wind monitors were installed at sites 188, 258 (Rainbow Field), 261 (Swift Dam), and at Heart Butte (site 260) and at Blackfoot, about 4 miles northwest of Browning. In November 1981, the anemometer at site 188 was relocated to site 200 (MacDonald Pass). Blackfoot, Swift Dam, and Heart Butte had windrun anemometers. A stripchart recorder was installed at Rainbow Field and a CR-21 data logger was installed at MacDonald Pass. The Rainbow Field equipment was removed in November 1982. That same month, a CR-21 data logger was installed at Heart Butte, and a wind-run anemometer was installed at Duck Lake, approximately 5 miles east of Babb. Wind-run anemometers were installed at Whitehall in September 1983 and at Sieben 2 in October 1983. The Whitehall site is on a microwave tower just northeast of the town, while the Sieben 2 site is on a rocky point 27 miles northwest of Helena. The Blackfoot site was converted to an hourly data logger system in July 1984. Data from wind-run anemometers at these sites are presented in Table C-6. Data recovery in many instances was poor, due to the extremely harsh weather at the sites. All the wind-run anemometers were closed down by July 1984.

U.S. Forest Service

The U.S. Forest Service maintains a collection of historical weather data from more than 800 stations in the northwestern United States. The data were recorded from observations that took place once per day (usually in the early afternoon) during the fire season (generally May through September).

The data set includes data on wind direction and speed, temperature, relative humidity, and other parameters necessary for estimating fire hazards. Each January, data from the previous year are incorporated into each station's data set and stored on computer tapes.

While most of the stations have only one observation per day, some have three observations per day. Some of the station data histories date back to the 1920s.

These data have been analyzed by Battelle Pacific Northwest Laboratories. Those stations in Montana for which at least 70 percent of the wind speed observations were equal to or greater than 3.5 meters per second (7.8 miles per hour) are listed in Tables C-7 and C-8.

Table C-6
Bonneville Power Administration Wind-Run Monitoring Sites
Average Velocity Oct 1981 - Jul 1984 (mph)

| Site | | Rainbow Field | Blackfoot | Swift Dam | Heart Butte | Duck Lake | MacDonald Pass | Sieben 2 | Whitehall |
|------------------------|--------|------------------|-----------|--------------|----------------|--------------|-------------------|----------|-----------|
| Anemome Height (ft) | | (30) | (30) | (30) | (35) | (30) | (30) | (57) | (30) |
| 1981 | Oct | 15.7 | 14.5 | 14.4 | 15.5 | | | | |
| | Nov | 19.9 | 16.8 | 17.1 | 18.2 | | 22.5 | | |
| | Dec | 17.1 | 18.0 | 17.7 | 16.5 | | 40.4 | | |
| 1982 | Jan | 18.6 | 19.3 | 16.4 | 19.1 | | М | | |
| | Feb | 21.0 | 16.8 | 16.9 | 18.9 | | М | | |
| | Mar | М | 12.6 | M | M | | M | | |
| | Apr | M | 18.4 | M | 17.3 | | M | | |
| | May | M | 11.9 | 12.9 | 16.7 | | M | | |
| | Jun | M | 11.7 | 10.8 | М | | М | | |
| | Jul | M | 12.5 | 11.4 | 14.7 | | М | | |
| | Aug | M | 13.6 | 7.4 | 12.6 | | M | | |
| | Sep | М | 13.2 | 12.9 | 11.9 | | M | | |
| | Oct | M | 14.1 | M | 18.1 | | M | | |
| | Nov | | 18.2 | M | | 20.4 | 21.1 | | |
| | Dec | | 19.3 | M | | 19.0 | 22.4 | | |
| 983 | Jan | | 19.3 | M | | 19.0 | 23.8 | | |
| | Feb | | M | 10.5 | | 16.9 | | | |
| | Mar | | 9.6 | 6.1 | | 10.4 | | | |
| | Apr | | 12.5 | 12.5 | | 13.7 | | | |
| | May | | 13.7 | 8.5 | | 14.6 | | | |
| | Jun | | 14.7 | 12.1 | | 15.6 | | | |
| | Jul | | 13.5 | 10.0 | | 13.0 | | | |
| | Aug | | IM | iM | | IM | | | |
| | Sep | | IM | IM | | 10.6 | | | 11.9 |
| | Oct | | IM | 13.1 | | 12.7 | | 12.5 | 12.4 |
| | Nov | | 16.8 | 14.7 | | 15.7 | | 14.0 | 15.3 |
| | Dec | | 14.8 | 20.2 | | 15.7 | | 14.5 | 14.2 |
| 984 | Jan | | 18.1 | 20.2 | | 20.4 | | 14.2 | 20.1 |
| | Feb | | 18.1 | 12.0 | | 20.4 | | 14.2 | 19.6 |
| | Mar | | 18.1 | 12.7 | | 20.4 | | 15.8 | 13.6 |
| | Apr | | 13.6 | 11.7 | | 14.4 | | 12.0 | 14.7 |
| | May | | 16.6 | IM | | M | | 15,5 | 14.7 |
| | Jun | | 13.5 | 8.4 | | | | 15.5 | 12.2 |
| | Jul | | 13.5 | | | | | 7.6 | 11.6 |
| Avg of m | onthly | | | | | | | | 0 |
| avera | ges | 18.5* | 15.2* | 12.9* | 16.3* | 16.1* | 22.5# | 13.6* | 14.6* |

M - Missing data

IM - Instrument malfunction

^{* -} Data recovery < 80%

^{# -} Average excludes December, 1981

N.B. Blackfoot and Heart Butte were converted to hourly logging systems at the end of data-gathering periods shown in the table.

Table C-7
U.S. Forest Service
Fire Weather Data Sites

| Station Number | Station Location | Lat. (Deg) | Long. (Deg) | Elev. (m) | Total Obser. | Period of Record |
|-------------------|----------------------------------|---------------|-------------|--------------|-----------------|---------------------|
| 240102 | Kootenai National Forest | 48.51 | 115.55 | 1,992 | 147 | 1967-72 |
| 240805 | Phillips County | 48.48 | 107.50 | 900 | 447 | 1970-72 |
| 241208 | Kaniksa National Forest | 48.06 | 115.55 | 1,879 | 616 | 1961-72 |
| 241801 | Lewis & Clark National Forest | 47.48 | 112.51 | 2,465 | 594 | 1962-73 |
| 241905 | Helena National Forest | 47.06 | 112.11 | 2,316 | 691 | 1961-73 |
| 242101 | Lewis & Clark National Forest | 46.42 | 110.16 | 2,527 | 261 | 1961-65 |
| 242201 | Lewis & Clark National Forest | 47.04 | 109.28 | 1,263 | 297 | 1961-65 |
| 243001 | Deer Lodge National Forest | 46.11 | 113.37 | 2,621 | 244 | 1960-67 |
| 243102 | Flathead National Forest | 47.24 | 113.30 | 2,516 | 457 | 1961-72 |
| 243402 | Lewis & Clark National Forest | 46.54 | 110.42 | 2,528 | 1,000 | 1962-77 |
| 244101 | Miles City | 46.23 | 105.50 | 801 | 1,407 | 1966-77 |
| 244604 | Gallatin National Forest | 44.45 | 111.13 | 2,157 | 263 | 1965-68 |
| 244605 | Helena National Forest | 45.80 | 111.16 | 2,814 | 114 | 1965-68 |
| 244701 | Gallatin National Forest | 45.60 | 110.14 | 3,008 | 242 | 1965-68 |

Table C-8
U.S. Forest Service
Fire Weather Data Summaries

| Station Number | Station Location | Anemometer Height (m) | Mean Wind Speed (m/s) | Mean Total Wind Power (watts/m²) |
|-------------------|----------------------------------|-----------------------------|-----------------------------|--|
| 240102 | Kootenai National Forest | 7 | 5.14 | 194 |
| 240805 | Phillips County | 6 | 5.00 | 196 |
| 241208 | Kaniksa National Forest | 7 | 5.55 | 262 |
| 241801 | Lewis & Clark National Forest | 8 | 5.96 | 237 |
| 241905 | Helena National Forest | 10 | 7.41 | 436 |
| 242101 | Lewis & Clark National Forest | Not reported | 6.14 | 314 |
| 242201 | Lewis & Clark National Forest | Not reported | 5.60 | 214 |
| 243001 | Deer Lodge National Forest | Not reported | 4.62 | 101 |
| 243103 | Flathead National Forest | 7 | 6.60 | 508 |
| 243402 | Lewis & Clark National Forest | 15 | 5.04 | 140 |
| 244101 | Miles City, MT | 10 | 5.69 | 227 |
| 244605 | Gallatin National Forest | 20 | 7.74 | 529 |
| 244605 | Helena National Forest | Not reported | 6.37 | 270 |
| 244703 | Gallatin National Forest | 5 | 6.74 | 218 |

Appendix D

BIBLIOGRAPHY

Alternative Energy Resources Organization

Montana Renewable Energy Directory. Billings, MT: Alternative Energy Resources Organization, 1982.

Baker, R.W., Hewson, E.W.

"Wind Power Potential in the Pacific Northwest." Journal of Applied Meteorology, 17, 1814-1826, 1979.

Network Wind Power Over the Pacific Northwest, BPA Report 80-5. Corvallis, OR: Oregon State University, 1980.

Baker, R. W., Wade, J.E., Persson, P.U.

Pacific Northwest Wind Regional Energy Assessment Program (Wind REAP). (Report No. BPA 85-19), Portland, OR: Office of Power and Resources Management, Bonneville Power Administration, 1985.

Regional Wind Energy Assessment Progress Report, October-September. Portland, OR: Office of Power and Resources Management, Bonneville Power Administration, 1980-1985.

Baker, R.W., Wade, J.E.

FY 1983 Regional Wind Energy Assessment Program, Six Month Status Report. Corvallis, OR: Department of Atmospheric Sciences, Oregon State University, 1983.

Barchet, W.R.

Approaches to Wind-Resource Verification. Richland, WA: Pacific Northwest Laboratory, 1981.

Bhumralkar, C.M., Ludwig, F.L., Mancuso, R.L.

Estimation of Wind Characteristics at Potential Wind Energy Conversion Sites. Menlo Park, CA: SRI International, 1979.

Bureau of Reclamation

Northern Great Plains Wind Energy Study. Quarterly Data Summaries June 1981 - August 1986. Volume I: Montana. Billings, MT: U.S. Department of the Interior, Bureau of Reclamation, 1982-1986.

Businger, J.A., Wyngaard, J.C., Izumi, Y., Bradley, E.F.

"Flux-Profile Relationships in the Atmosphere Surface Layer." J. Atmos. Sci. 28:181-189, 1971.

Changery, M.J., Hodge, W.T., Ramsdell, J.V.

Index - Summarized Wind Data. Asheville, NC: National Oceanic and Atmospheric Administration, 1977.

Changery, M.J.

National Wind Data Index. Asheville, NC: National Climatic Center, 1978.

- Doran, J.C., Verholek, M.G.
 - "A Note on Vertical Extrapolation Formulas for Weibull Velocity Distribution Parameters." Journal of Applied Meteorology, 17, 410-412. 1978.
- Elderkin, C.E., Ramsdell, J.V.

Semi-Annual Report of the Wind Characteristics Program Element for the Period April 1976 through December 1976. Richland, WA: Pacific Northwest Laboratory, 1976.

Annual Report of the Wind Characteristics Program Element for the Period April 1976 through December 1976.
Richland, WA: Pacific Northwest Laboratory, 1977.

Elderkin, C.E., Wendell, L.L.

Semi-Annual Report of the Wind Characteristics Program for the Period July 1977 through December 1977. Richland, WA: Pacific Northwest Laboratory, 1978.

Elliott, D.L.

Putting Wind-Resource Atlases to Use. Richland, WA: Pacific Northwest Laboratory, 1981.

Elliott, D.L., Barchet, W.R.

Wind Energy Resource Atlas: Volume 1 - The Northwest Region. Richland, WA: Pacific Northwest Laboratory, 1980.

Furman, R.W., and Brink, G.E.

The National Fire Weather Data Library. Fort Collins, CO: Rocky Mtn. Fo. and Range Exp. Stn. 1975.

Hewson, E.W., Baker, R.W.

Wind Energy Assessment at Selected Sites. BPA Report 76-1. Corvallis, OR: Oregon State University, 1976.

Network Wind Power Over the Pacific Northwest. BPA Report 77-2. Corvallis, OR: Oregon State University, 1977.

Network Wind Power Over the Pacific Northwest. BPA Report 78-3. Corvallis, OR: Oregon State University, 1978.

Network Wind Power Over the Pacific Northwest. BPA Report 79-4. Corvallis, OR: Oregon State University, 1979.

Hewson, E.W., Wade, J.E.

Wind Power Potential in the Pacific Northwest Region. Corvallis, OR: Oregon State University, 1978.

Vegetation as an Indicator of High Wind Velocity. Corvallis, OR: Oregon State University, 1979.

Hewson, E.W., Wade, J.E., Baker, R.W.

A Handbook on the Use of Trees as Indicators of Wind Power Potential. Corvallis, OR: Oregon State University, 1979.

Hewson, E.W., et al.

Network Wind Power Over the Pacific Northwest. BPA Report 78-3. Corvallis, OR: Oregon State University, 1978.

- Jong, M., Thomann, G.
 - "Sampling Wind Data for Mean Wind Speed Estimation." Journal of Applied Meteorology, 20, 323-327, 1981.
- Justus, C.G., Hargraves, W.R., Yalcin, A.

"Nationwide Assessment of Potential Output from Wind Powered Generators." Journal of Applied Meteorology, 15, 673-678, 1976.

Marlatt, W.E., et al.

Assessment of the Applicability of the National Fire Weather Data Library to Wind Energy Analysis. Fort Collins, CO: Marlatt and Associates, 1979.

Marwitz, J.D., Gilkey, K.B.

Catalog of Available Wind Data for Idaho, Montana, and Wyoming. Laramie, WY: University of Wyoming, 1979.

Montana Air Quality Bureau

A Network Review of Montana's Ambient Air Monitoring. Helena, MT: Air Quality Bureau, Department of Health and Environmental Sciences, 1979.

Air Monitoring Instrumentation. Helena, MT: Air Quality Bureau, Department of Health and Environmental Sciences, 1979.

Annual Air Quality Data Summary for Montana 1976. Helena, MT: Air Quality Bureau, Department of Health and Environmental Sciences, 1977.

Annual Air Quality Data Summary for Montana 1978. Helena, MT: Air Quality Bureau, Department of Health and Environmental Sciences, 1979.

Approach and Methodology. Montana Air Pollution Study. Helena, MT: Air Quality Bureau, Department of Health and Environmental Sciences, 1978.

Background Air Quality Studies of the Poplar River Area of Northeastern Montana. Helena, MT: Air Quality Bureau, Department of Health and Environmental Sciences, 1978.

Background Air Quality Studies of the Poplar River Area of Northeastern Montana 1978. Helena, MT: Air Quality Bureau, Department of Health and Environmental Sciences, 1979.

Deer Lodge Valley Dispersion Study. Helena, MT: Air Quality Bureau, Department of Health and Environmental Sciences, 1979.

Flathead River Basin Environmental Impact Study. Helena, MT: Air Quality Bureau, Department of Health and Environmental Sciences, 1979.

Meteorological Study, Columbia Falls, Montana. Helena, MT: Air Quality Bureau, Department of Health and Environmental Sciences, 1979.

Montana Air Quality Data and Information Summary for 1979-1980. Helena, MT: Air Quality Bureau, Department of Health and Environmental Sciences, 1981.

Montana Air Quality Data and Information Summary for 1981. Helena, MT: Air Quality Bureau, Department of Health and Environmental Sciences, 1982.

Montana Air Resources Modeling System. Helena, MT: Air Quality Bureau, Department of Health and Environmental Sciences, 1979.

1980 Network Review. Helena, M. Air Quality Bureau, Department of Health and Environmental Sciences, 1980.

Montana Department of Natural Resources and Conservation

Installation of the New Monitoring Sites For the Wind Energy Survey Study. Missoula, MT: InterMountain Ambient, 1986.

Montana Wind Energy Research and Development Program. Butte, MT: The Montana Energy and MHD Research and Development Institute, Inc., 1981.

Removal of Existing Monitoring Sites and Installation of New Monitoring Sites. Missoula, MT: InterMountain Ambient, 1984.

Wind Energy Survey, Livingston to Springdale, Final Report. Bozeman, MT: Brelsford Engineering, 1979.

National Climatic Center (NCC)

Winds Aloft Summaries, by Month. Asheville, NC: NCC, 1970.

TDF-14: Surface Observations. Asheville, NC: NCC, 1975.

WBAN Station Numbers Master List. Asheville, NC: NCC, 1978.

Old West Regional Commission

Glasgow Meteorology and Air Quality Analysis Report. Butte, MT: The Montana Energy and MHD Research and Development Institute, 1978.

Peterson, E.W.

On the Use of Power Laws for Estimates of Wind Power Potential. Journal of Applied Meteorology, 17, 390-394, 1978.

Reed, J.W.

Wind Power Climatology of the U.S. Albuquerque, NM: Sandia Laboratories, 1975.

Renne, D.C., Corotis, R.B.

Assessing the Representativeness of Wind Data for Wind Turbine Site Evaluation. PNL-SA-9747. Richland, WA: Pacific Northwest Laboratory, 1981.

Sedefian, L.

"On the Vertical Extrapolation of Mean Wind Power Density." Journal of Applied Meteorology, 19, 488-493, 1980.

Takle, E.S., Brown, J.M.

"Note on the Use of Weibull Statistics to Characterize Wind Speed Data." Journal of Applied Meteorology, 16, 556-559, 1977.

Traci, R.M., Phillips, G.T., Patnaik, P.C.

Development of a Site Selection Methodology. La Jolla, CA: Science Applications, Inc., 1978.

U.S. Department of the Interior, Water and Power Resources Service.

Wind Power Energy Generation Studies at Canyon Ferry, Gibson, Tiber, and Yellowtail Dams in Montana. Canyon Ferry Dam Site. Helena, MT: ECON, Inc., 1981.

Wind Power Generation Studies at Canyon Ferry, Gibson, Tiber, and Yellowtail Dams in Montana. Gibson Dam Site. Helena, MT: ECON, Inc., 1981.

Wind Power Energy Generation Studies at Canyon Ferry, Gibson, Tiber, and Yellowtail Dams in Montana. Tiber Dam Site. Helena, MT: ECON, Inc., 1981.

Wind Power Energy Generation Studies at Canyon Ferry, Gibson, Tiber, and Yellowtail Dams in Montana. Yellowtail Dam Site. Helena, MT: ECON, Inc., 1981.

Van der Auwera, L., et al.

"The Use of the Weibull Three-Parameter Model for Estimating Mean Wind Power Densities." Journal of Applied Meteorology, 19, 819-825, 1980.

Verholek, M.G.

A Measurement Program to Characterize the Wind at a Potential WECS Site. Richland, WA: Pacific Northwest Laboratory, 1978.

Wendell, L.L., et al.

Annual Report of the Wind Characteristics Program Element for the Period July 1977 through July 1978. Richland, WA: Pacific Northwest Laboratory, 1978.

Annual Report of the Wind Characteristics Program Element for the Period July 1978 through September 1979. Richland, WA: Pacific Northwest Laboratory, 1980.

Western Area Power Administration

C & RE Program: Wind Prospecting Program, Final Report (January 30, 1985) Golden, CO: Western Area Power Administration, 1985.